DO MODULES STAY IN THEIR LANE? ROLE DRIFT IN COMPOUND AI SYSTEMS

Anonymous authors
Paper under double-blind review

ABSTRACT

When a compound AI system is trained end-to-end with reinforcement learning, the terminal reward only shows how good the final output is, but cannot tell whether each module performed its assigned job. A module can deviate from its assigned role while still improving the terminal reward. We call this failure role drift, and demonstrate it in four compound systems. For example, in a multihop QA pipeline, a decomposer is supposed to pose subquestions and a solver is supposed to answer them concisely. After training, the decomposer begins writing the gold answer into its subquestions, with leakage rising from 14% to 73.5%. Similar drift appears in a retrieval-augmented QA pipeline, a code generation pipeline, and an LLM routing system. Each module is capable of performing its assigned role, but the terminal reward pays more for leaving the role than for keeping it. The drift is invisible in the reward curve and becomes harmful when deployment conditions change: when the leaked answers in the decomposer's subquestions are masked, the system's performance drops by 8.9 points. Monitoring the terminal reward alone is not sufficient to ensure that a compound system's modules behave as intended.

1 INTRODUCTION

Compound AI systems divide a task among specialized modules (Khattab et al., 2024). Consider a compound system for multihop question answering. A decomposer receives the question and its supporting passages and produces a sequence of subquestions. A solver then answers each one, and the system returns the final answer. We train this system end-to-end with reinforcement learning on MuSiQue (Trivedi et al., 2022) (Section 4), with a terminal reward that checks whether the gold answer appears in the final output. After training, however, the decomposer begins inserting the gold answer into its subquestions, with the leakage rate rising from 14% to 73.5%. The solver, instead of answering on its own, reads the answer directly from the subquestions (Figure 1).

This is not an isolated case. We observe the same pattern in three other compound systems (Section 4). A retrieval-augmented reader on HotpotQA stops following its evidence and answers from memory. An LLM coder takes over the evaluator's test function instead of writing solutions that pass it. An LLM router sends nearly every request to the expensive model. In each system, end-to-end RL moves a module away from its assigned job while the training reward improves. We call this phenomenon **role drift**.

Why does role drift occur? In every system we study, the module is capable of performing its assigned role, but the terminal reward pays more for leaving the role than for keeping it (Section 4.2). In the Decomposer–Solver pipeline, subquestions that contain the leaked answer earn higher reward than clean ones. The terminal reward does not distinguish whether the solver found the answer on its own or read it from the decomposer's subquestions. Inserting the answer into the subquestion is therefore a simpler path to high reward than posing a genuine subproblem for the solver to work through.

The training reward alone cannot reveal the drift, because the drift is what raises the reward. A developer monitoring only the reward curve sees steady improvement and no sign that the internal division of labor in the system has changed. The shift becomes visible only when deployment conditions change (Section 4.3). When the leaked answers in the subquestions are masked, the

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: Role drift in the Decomposer–Solver pipeline. **Left:** Before training, the decomposer uses a placeholder `#1` and the solver answers each subquestion from the passages. After training, the decomposer writes the answer for the first subquestion (*Tolkien*) directly into the second subquestion, and the solver reads it instead of solving. Both paths produce the same final answer. **Middle:** The training reward rises from 26% to 61% while answer leakage rises from 14% to 73.5%. **Right:** When the leaked answers are masked and the subquestions go to an independent solver, the gain over the pre-RL decomposer drops.

decomposer's gain over its pre-RL version drops from $+6.5$ to -2.4 percentage points (Figure 1, right). The decomposer has learned to bypass the solver, not to write better subquestions.

Role drift is related to but distinct from reward hacking (Skalse et al., 2022). Reward hacking exploits a gap between a proxy reward and the true objective. Role drift can occur even when the reward faithfully measures the task, because a terminal reward that scores only the final output does not separately price each module's job (Section 2).

Our contributions are as follows:

- We identify role drift as a failure mode of end-to-end RL in compound AI systems, and verify it across four systems spanning retrieval-augmented QA, multihop QA, code generation, and LLM routing.
- We show that in each system, the module is capable of performing its assigned role, but the terminal reward pays more for leaving the role than for keeping it.
- We show that the drift is invisible in the training reward and produces concrete failures when the system is deployed under new conditions.

2 Related Work

Training compound AI systems end-to-end. A growing line of work optimizes compound systems with a system-level objective (Khattab et al., 2024; Yuksekgonul et al., 2025; Zhang et al., 2025; Cheng et al., 2024; Wang et al., 2025a; Wu et al., 2026). These methods differ in how they assign credit across modules, but all of them train on a system-level signal and none of them monitor whether individual modules keep their assigned jobs. Zeng et al. (2026) find that multi-agent RL in LLM workflows can concentrate behavior in a single role, and Cemri et al. (2025) list role violations among the inference-time failures of multi-agent LLM systems. Ma et al. (2025) show that deep-research agents learn tool calls that score well without grounding their answers. In multi-agent reinforcement learning, jointly trained agents develop private conventions that diverge from the intended protocol (Foerster et al., 2016; Lazaridou et al., 2017; Kottur et al., 2017), and RL-fine-tuned dialogue agents produce outputs that serve the task reward while losing natural language structure, a phenomenon called language drift (Lewis et al., 2017; Lee et al., 2019; Lu et al., 2020). Jointly optimized modules can also develop steganographic encodings that serve the shared reward while evading oversight (Chu et al., 2017; Motwani et al., 2024; Mathew et al., 2025). All of these results concern drift in a communication channel or in the surface form of outputs. We ask a different question. Do the modules of a compound system still do their assigned jobs after training?

Table 1: Four compound systems and their role probes. Each system is trained end-to-end with RL on its terminal reward. The role probe is scored on a fixed held-out evaluation set that the reward never sees. Sections 3.1–3.4 define each probe.

System	Dataset	Trained modules	Role probe	Eval. set
RAG	HotpotQA	Reader, query gen. (Qwen2.5-3B-Instruct)	Context dependence	352
Decomposer–Solver	MuSiQue	Decomposer (Qwen2.5-7B-Instruct), solver (Qwen2.5-0.5B-Instruct)	Answer leakage	200
Solver–Evaluator	LeetCode	Coder (Qwen3-4B)	Test takeover	353
LLM Router	RouterBench	Router (Qwen3-0.6B)	Unhelpful escalation	1,486

When the reward and the intended behavior come apart. In reward hacking, a proxy reward rises while the true objective falls (Skalse et al., 2022; Gao et al., 2023; Pan et al., 2024). The Solver-Evaluator in our study is an instance of both reward hacking and role drift, because taking over the tests exploits a hackable proxy and also abandons the solver's role (Wong et al., 2025). But role drift does not require a gap between proxy and true reward. The LLM router is trained on the same utility used at evaluation and still abandons its role, because always escalating earns nearly maximal utility. Underspecification (D'Amour et al., 2022) and goal misgeneralization (Langosco et al., 2022) are closer to what we observe, in that solutions with similar training performance can differ in behavior that matters at deployment. The difference is that role drift occurs at module boundaries in compound systems, where the division of labor is the property left unspecified. Role drift also differs from catastrophic forgetting (Kirkpatrick et al., 2017). The module does not lose the ability to perform its role. The training objective actively selects the drifted behavior.

Checking intermediate behavior. Process-supervision methods reward intermediate reasoning steps (Lightman et al., 2024; Uesato et al., 2022), and retrieval-grounding measures evaluate how much a system's answers depend on its evidence (Mallen et al., 2023; Ru et al., 2024). These approaches check the quality of intermediate outputs but do not track whether a module's function has shifted over the course of training. Persona drift and sycophancy (Abdulhai et al., 2025; Sharma et al., 2024) describe shifts in a fixed model's behavior at inference time, not changes induced by training. The closest single-model analogue is shortcut learning (Geirhos et al., 2020), where a model reaches high accuracy through features the designer did not intend. Role drift is what this looks like at a module boundary, where the shortcut is doing another module's work.

3 Experimental Setup

We study four compound systems trained end-to-end with RL on a terminal reward. For each system, we describe the pipeline, the drift pattern, and the probe we use to track it. Table 1 summarizes the four systems. In each system, both the task metric and the role probe are tested on a fixed evaluation set separate from the training data. Detailed training settings and hyperparameters are in Appendix A. Appendix C provides a worked example from each system, showing how each module's output changes after RL training.

3.1 Retrieval-Augmented QA

A query generator rewrites a HotpotQA question (Yang et al., 2018) into a search query, a frozen BM25 retriever (Robertson & Zaragoza, 2009) returns five passages, and a reader produces the answer conditioned on the question and passages. Both the query generator and reader are Qwen2.5-3B-Instruct (Yang et al., 2024), trained with RL on a binary token-F1 reward (threshold 0.5).

Drift pattern. After training, the reader answers from parametric memory rather than from the retrieved passages. The reader has two answer sources, the retrieved passage and its own parameters. Because the upstream retriever does not always return a passage that contains the answer, answering from memory earns higher reward on those questions, and RL reinforces this shortcut.

Probe. The evaluation set contains 352 yes/no questions from HotpotQA validation, 176 with each answer. Each question is presented to the reader twice: once with its supporting passage and once with the passage replaced by one drawn from a different question. Context dependence is the accuracy gap between the two conditions. A large gap means the reader conditions on the passage, and a gap near zero means it produces the same answer regardless of what passage it receives.

3.2 DECOMPOSER–SOLVER

A decomposer (Qwen2.5-7B-Instruct) receives a MuSiQue question (Trivedi et al., 2022) and its supporting passages and produces two to four numbered subquestions. A solver (Qwen2.5-0.5B-Instruct) answers each one in sequence and returns the final answer. The terminal reward is 1 when the gold answer or one of its aliases appears as a substring of the solver's output.

Drift pattern. Both modules drift. The decomposer's job is to break the question into subproblems without answering them. After training, it inserts the gold answer directly into its subquestions, and the solver reads the answer from the subquestion instead of reasoning over the passages. We deliberately use a much larger decomposer (7B) than solver (0.5B). The decomposer can answer many questions that the solver cannot, so writing the answer into the subquestion is an easier way to improve reward than leaving it to the solver and waiting for it to learn.

Probe. We evaluate the decomposer on 200 fixed MuSiQue validation questions. For each, we normalize the gold answer by lowercasing, stripping punctuation, and collapsing whitespace, then check whether the resulting string appears as a substring in any subquestion the decomposer produces. Answer leakage is the fraction of questions where at least one subquestion contains the gold answer. A leakage rate of zero means the decomposer never reveals the answer, while a high rate means the solver can read it directly from the subquestion.

3.3 SOLVER–EVALUATOR

A LeetCode problem from the Steering RL environment (Wong et al., 2025) is given to a coder (Qwen3-4B; Yang et al., 2025), which writes a solution. The solution is then passed to an evaluator, a fixed `run_tests` function that executes the code on a set of hidden test cases. The proxy reward gives 3 points when the solution passes the evaluator's tests or tests the coder itself defines, plus 0.5 when the code compiles.

Drift pattern. The coder's job is to write solutions for the given problem, but after training, the coder starts defining its own `run_tests` and overwriting the default function from the evaluator. The proxy reward does not distinguish whether the tests come from the evaluator or from the coder, so the coder can, for example, call the solution and print the output without any assertion. The tests never fail regardless of whether the solution is correct.

Probe. For each of 353 held-out LeetCode problems, we parse the coder's output into an Abstract Syntax Tree (AST) to check whether the coder defines its own `run_tests` function. The test-takeover rate is the fraction of problems where the coder's solution contains such a function.

3.4 LLM ROUTER

The pipeline consists of a router (Qwen3-0.6B) and two answer models: a cheap model and an expensive expert. The router reads each request together with the cheap model's answer and decides whether that answer is sufficient or whether the request should go to the expert. We evaluate on RouterBench (Hu et al., 2024), which provides pre-generated responses from both the expert and the cheap model, so we only need to train the router itself. The per-request reward is a binary correctness indicator minus 0.02 for each expert call.

Drift pattern. The router should escalate only when the cheap model would fail. After training, it escalates nearly everything: the unhelpful escalation rate reaches 97% within five updates and the utility settles at 0.790, matching always-escalate. Only 208 of 5,729 evaluation requests are




Figure 2: **Role drift under RL.** The top row shows the training reward or task metric on each system's held-out evaluation set; the bottom row shows the corresponding role probe on its fixed held-out probe bank. In (a), the axis is inverted so that up means more drift in all four panels. A dashed grey line marks the value at the first checkpoint. For RAG and the Decomposer–Solver, epoch k is the checkpoint after $k{+}1$ training epochs; for the Solver–Evaluator and the LLM Router, update 0 is the model before RL. (a) RAG reader. (b) Decomposer–Solver. (c) Solver–Evaluator. (d) LLM Router.

answered correctly by the cheap model but not by the expert, so always escalating earns within 0.045 of perfect routing.

Probe. We want to measure whether each expert call is actually necessary. From 5,729 held-out RouterBench requests, we select 1,486 requests where the cheap model already answers correctly. The unhelpful escalation rate is the fraction of these requests that the router sends to the expert. Since the cheap model is already sufficient on these requests, a lower rate means the router is better at avoiding unnecessary expert calls.

4 Results

In this section, we ask three questions about role drift. Does it happen across all four systems (Section 4.1)? Why does RL produce it (Section 4.2)? And when does it hurt in deployment (Section 4.3)?

4.1 Drift Trajectories

Figure 2 tracks the training reward (top row) and the role probe (bottom row) at every checkpoint for all four systems. In every case, the reward improves while the probe moves toward drift, but the four systems get there in different ways.

The router drifts fastest. Before RL it already escalates 41.3% of the requests the cheap model answers correctly. After just five gradient updates the rate reaches 97.4%, and the utility improves to 0.786, close to the 0.790 of always sending everything to the expert. At that point the router has effectively stopped routing.

The RAG reader drifts more gradually. Its context dependence falls from 17.0 pp after the first epoch to 1.1 pp after six epochs, meaning the reader's answer barely changes when the passage is swapped out. Over the same period, HotpotQA accuracy rises from 31% to 47%. If one looks only at terminal accuracy, the system appears to be learning well from RL.

The Solver–Evaluator shows a different pattern. Through update 50 the takeover rate stays near 0%, while the proxy reward dips from 3.160 to 2.786. Between update 50 and update 100, however, the takeover rate suddenly jumps to nearly 100%, and the proxy reward recovers and rises to 3.49 by update 150.

In the Decomposer–Solver (Figure 2b), the training reward rises steadily from 0.26 to 0.61. The answer leakage, however, does not rise in step with the reward. It stays near 14% for the first five

Table 2: **Training reward for role-faithful versus role-violating behavior.** The *Role-faithful* column shows the reward when the module follows its assigned role, and the *Role-violating* column shows the reward when it does not. **RAG**: we compare the reader before RL, which abstains when the retrieved passage lacks the answer, with the reader after RL, which answers from parametric memory instead. Both are evaluated on training questions whose passage does not contain the gold answer. **Decomposer–Solver**: we compare clean subquestions (no leaked answer) with leaked ones, and separately compare short solver outputs (1–5 words) with long ones (20+ words). All values are pooled over epochs 0–9. **Solver–Evaluator**: rollouts where the coder does not define `run_tests` (role-faithful) and rollouts where it does (role-violating), over updates 66–75. The second row has no role-violating comparison. **LLM Router**: a router supervised on ground-truth escalation labels (whether the cheap model fails and the expert succeeds) and the always-escalate strategy; the supervised router's utility is measured at a 47.7% escalation rate.

System	Measure	Role-faithful	Role-violating
RAG	Training reward (%) on no-answer passages	2.7	19.3
	Abstention count on no-answer passages	12	0
Decomposer–Solver	Substring reward (by leakage)	0.298	0.559
	Substring reward (by answer length)	0.258	0.493
	Exact match (by answer length)	0.197	0.000
Solver–Evaluator	Proxy reward (updates 66–75)	1.69	2.41
	Problems correct before RL (of 353)	313	–
LLM Router	Mean utility	0.612	0.790
	Routing AUROC	0.820	0.517

epochs, during which the reward is already improving, then climbs sharply to 73.5% by the end of training. The delay suggests that the decomposer initially improves through legitimate means before RL discovers that leaking the answer is a faster path to reward.

Across the four systems, RAG is the only one where drift emerges gradually. The Solver–Evaluator and the Decomposer–Solver show a period of low drift followed by a rapid transition, and the router drifts almost immediately. Once the role-violating behavior begins to outperform the role-faithful one on enough training examples, RL commits to it quickly.

4.2 Why Role Drift Happens

A natural explanation for role drift is that the reward does not incentivize role-faithful behavior. But one could also argue that the modules are simply too weak to learn such behavior. In this section, we compare these two hypotheses on all four pipelines. The results are shown in Table 2, and the evidence in every system supports the first hypothesis. The reward is consistently higher for role-violating behavior, and every module except the router performs its role at the start of training.

The RAG reader has a context dependence of 17.0 pp after the first epoch, so it can follow the passage. But on training questions where the retrieved passage does not contain the gold answer, the reader before RL earns reward on only 2.7% of them. After RL this rises to 19.3%. The reward never incentivizes abstention, and a correct answer from parametric memory earns the same reward as one from the passage. By the end of training, 36% of the reader's rewarded answers come from passages that lack the answer, up from 13% before RL.

In the Decomposer–Solver, the reward gap comes from the scorer rather than from the task itself. Subquestions that leak the gold answer earn a substring reward of 0.559, compared with 0.298 for clean subquestions. Similarly, verbose solver answers (20+ words) earn 0.493, while concise answers (1–5 words) earn only 0.258. Under exact match the length comparison reverses (0.197 versus 0.000), confirming that the advantage comes from the leniency of the substring scorer.

The coder can already solve 313 of 353 held-out problems before RL without defining `run_tests` on any of them, and its base proxy reward of 3.160 is already close to the maximum of 3.5. There is little room to improve by writing better solutions, but there is a large gap to exploit by taking over




Figure 3: **Training reward versus strict scoring of the same outputs.** (a) Decomposer–Solver. The solid line is the lenient training reward, which counts an output as correct whenever the gold answer appears as a substring anywhere in the solver's response ($n = 200$). The dashed line is exact match on the same outputs, which requires the solver's response to match the gold answer exactly. (b) Solver–Evaluator. The solid line is the proxy reward on 353 held-out problems, which accepts both the evaluator's hidden test cases and any `run_tests` the coder defines. The dashed line re-scores the same outputs using only the evaluator's hidden test cases, ignoring any `run_tests` the coder adds.

the tests, since over updates 66–75, rollouts with test takeover score 2.41 while those without score 1.69.

The router is the only system where the starting model performs its role poorly, with an AUROC of only 0.555 for separating helpful from unnecessary escalations. But the model is not incapable of learning how to route. When supervised on binary labels derived from RouterBench outcomes (escalation helps when the cheap model fails and the expert succeeds; details in Appendix A), the same architecture reaches an AUROC of 0.820. The terminal reward, however, does not ask for good routing. Only 208 of 5,729 held-out requests are answered correctly by the cheap model but not by the expert, so always escalating scores a utility of 0.790, within 0.045 of perfect routing. RL converges to this trivial strategy.

4.3 Deployment Costs

A natural question is, if role drift improves terminal performance, does it actually matter? One reason it matters is that the improvement can be illusory. Figure 3 re-scores the same model outputs under stricter conditions that the training reward does not enforce. In the Decomposer–Solver (Figure 3a), the lenient substring reward rises from 0.26 to 0.61 over training, but exact match on the same outputs drops to zero after four epochs. The long, verbose answers that the substring scorer credits do not match the gold answer exactly. In the Solver–Evaluator (Figure 3b), the proxy reward and the original-test reward almost overlap through update 50, where both dip before any takeover. The curves diverge sharply at update 100, once the coder takes over the tests. The proxy reward climbs to 3.48, while the original-test reward stays below its pre-RL value (2.87 versus 3.16). Simply switching to a stricter scorer erases the gains. The drifted systems have learned to exploit the scorer, not to produce better solutions.

We further evaluate all four pipelines under deployment conditions that differ from training, where the role becomes essential and influences the terminal performance. Table 3 shows the results.

The RAG reader is tested on 109 facts that changed in Wikidata (Vrandečić & Krötzsch, 2014) after the training data was collected. The updated evidence passage is provided to both the pre-RL and post-RL reader. Before RL, the reader returns the outdated answer 12 times. After RL, this rises to 23. The pattern persists under strict string matching and becomes more pronounced when the evidence is randomized. With randomized evidence, the post-RL reader still produces the outdated answer on 38 of 109 questions, while the pre-RL reader produces no outdated answers. The post-RL reader has memorized the old answers and no longer consults the passage.

Table 3: **Outcomes when the role matters, before and after RL.** Each system is evaluated under a deployment condition where role-faithful behavior is needed but the training reward did not enforce it. **RAG**: the reader is tested on 109 facts that were updated in Wikidata after training. The retrieved passage contains the current answer, so a reader that follows the passage should get it right; one that answers from memory will return the outdated value. **Decomposer–Solver**: the decomposer's sub-questions are sent to an independent 3B solver that was not co-trained with it, scored by exact match on 800 items. *Drift removed* masks any leaked gold answers in the subquestions with placeholder references. **Solver–Evaluator**: the same update-200 outputs are re-scored using only the evaluator's hidden tests, ignoring any `run_tests` the coder defines. **LLM Router**: the system is replayed under a loaded expert with a 0.5 s deadline ($\rho = 1.0$; see Appendix A). Unnecessary escalations cause timeouts. *Drift removed* reverts only those unnecessary escalations to the cheap model.

System	Outcome	Before RL	After RL	Drift removed
RAG	Outdated answers (of 109)	12	23	–
	Outdated answers, strict string match (of 109)	11	17	–
	Outdated answers under randomized evidence (of 109)	0	38	–
Decomposer–Solver	Exact match with independent 3B solver	0.289	0.354	–
	Change from pre-RL decomposer (pp)	–	$+6.5$	-2.4
Solver–Evaluator	Proxy reward	3.160	3.482	–
	Reward under evaluator's original tests	3.160	2.870	–
LLM Router	Timely correct answers (of 270)	124	113	237
	Timeouts (of 270)	0	135	0

In the Decomposer–Solver, the drift becomes costly when the decomposer's output goes to a solver that was not co-trained with it. During joint training, the two modules develop a private convention: the decomposer writes the answer into the subquestion, and the solver copies it out. An independent 3B solver achieves 6.5 percentage points higher exact match with the post-RL decomposer than with the pre-RL one. But this gain comes entirely from the leaked answers in the subquestions, and masking those answers reverses the gain to -2.4 points (masking details in Appendix B).

In the Solver–Evaluator, we remove the coder's ability to overwrite the evaluator's tests and re-score the update-200 outputs using only the evaluator's hidden test cases. Under this condition, the proxy gain of $+0.322$ turns into a loss of -0.290 relative to the base model. All 72 solutions that pass the proxy but fail under the evaluator's tests define their own `run_tests`.

The router is tested under a realistic serving scenario where the expert runs under load and requests that take longer than 0.5 seconds time out. The pre-RL router returns 124 timely correct answers out of 270 requests with no timeouts. The post-RL router, which escalates nearly everything, returns only 113 and produces 135 timeouts. Reverting the 124 unnecessary escalations eliminates every timeout and yields 237 timely correct answers.

Across all four systems, the pattern is similar. The drifted system looks stronger on the training metric, but its gains are fragile. A small shift in deployment conditions is enough to erase or reverse the improvement.

5 Discussion

The results above show that role drift is widespread, reward-driven, and costly at deployment. How should practitioners account for it when building compound systems? We discuss this below.

Monitor role fidelity alongside the reward. The training reward cannot detect role drift because the drift is what improves it. We recommend defining a role probe for every module whose behavior

other modules depend on, and tracking it at every checkpoint throughout training. The probe should test the specific behavior the module is assigned to perform, not just the quality of its output. For example, the RAG reader's probe does not ask whether the answer is correct, but whether the answer changes when the passage is swapped.

Beyond terminal-level reward. Our probes detect drift after it happens, but do not prevent it. A natural next step is to incorporate role fidelity into the training objective as an auxiliary reward for each module. Such a term could score the module's assigned behavior on the same held-out inputs used for the probe, penalizing drift during training rather than only diagnosing it afterward.

Limitations and future work. Our probes are designed after the fact. We observe how each module drifts and then define a test for that specific behavior. A practitioner building a new compound system cannot know in advance what form the drift will take, and must rely on domain knowledge to design the right probe. An important open question is whether probe design can be automated, for example by comparing a module's behavior under its role prompt to its behavior under a neutral prompt, without requiring a hand-crafted test for each system. Our experiments also use models with up to 7B parameters; whether the same drift patterns appear at larger scale remains to be seen.

6 Conclusion

We studied four compound AI systems trained end-to-end with RL, spanning retrieval-augmented QA, multihop QA, code generation, and LLM routing. In every system, training improves the terminal reward while modules quietly abandon their assigned roles. The drift is not specific to any particular system design. It follows from a structural property of end-to-end training, where a terminal reward that scores only the final output has no way to enforce how the work is divided among modules.

Our results suggest that terminal accuracy alone is an insufficient indicator of whether a compound system is working as intended. A system can score well while internally reorganizing in ways that break under deployment conditions the training reward did not anticipate. Role probes offer a simple and inexpensive way to detect this.

More broadly, as compound AI systems grow in complexity and are trained with increasingly powerful optimization, the gap between what the reward measures and what the designer intends will only widen. Making the intended division of labor explicit and enforceable, rather than assuming the reward will preserve it, is an important direction for building reliable compound systems.

AI Use Statement

We used generative AI tools to assist with implementing the training pipelines and role probes, the design and execution of experiments, search for related work, and manuscript polishing. The authors take responsibility for the final content.

References

Marwa Abdulhai, Ryan Cheng, Donovan Clay, Tim Althoff, Sergey Levine, and Natasha Jaques. Consistently simulating human personas with multi-turn reinforcement learning. In *Advances in Neural Information Processing Systems*, 2025.

Mert Cemri, Melissa Z. Pan, Shuyi Yang, Lakshya A. Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, Matei Zaharia, Joseph E. Gonzalez, and Ion Stoica. Why do multi-agent LLM systems fail? In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*, 2025.

Ching-An Cheng, Allen Nie, and Adith Swaminathan. Trace is the next AutoDiff: Generative optimization with rich feedback, execution traces, and LLMs. In *Advances in Neural Information Processing Systems*, volume 37, 2024.

Casey Chu, Andrey Zhmoginov, and Mark Sandler. CycleGAN, a master of steganography. In *NIPS 2017 Workshop: Machine Deception*, 2017. URL https://arxiv.org/abs/1712.02950.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? Try ARC, the AI2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

Alexander D'Amour, Katherine Heller, Dan Moldovan, Ben Adlam, Babak Alipanahi, Alex Beutel, Christina Chen, Jonathan Deaton, Jacob Eisenstein, Matthew D. Hoffman, et al. Underspecification presents challenges for credibility in modern machine learning. *Journal of Machine Learning Research*, 23(226):1–61, 2022. URL https://www.jmlr.org/papers/volume23/20-1335.html.

Jakob Foerster, Ioannis Alexandros Assael, Nando de Freitas, and Shimon Whiteson. Learning to communicate with deep multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper_files/paper/2016/hash/c7635bfd99248a2cdef8249ef7bfbef4-Abstract.html.

Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *International Conference on Machine Learning*, pp. 10835–10866. PMLR, 2023.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673, 2020.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

Qitian Jason Hu, Jacob Bieker, Xiuyu Li, Nan Jiang, Benjamin Keigwin, Gaurav Ranganath, Kurt Keutzer, and Shriyash Kaustubh Upadhyay. RouterBench: A benchmark for multi-LLM routing system. *arXiv preprint arXiv:2403.12031*, 2024.

Omar Khattab, Arnav Singhvi, Paridhi Maheshwari, Zhiyuan Zhang, Keshav Santhanam, Sri Vardhamanan, Saiful Haq, Ashutosh Sharma, Thomas T. Joshi, Hanna Moazam, Heather Miller, Matei Zaharia, and Christopher Potts. DSPy: Compiling declarative language model calls into self-improving pipelines. In *International Conference on Learning Representations (ICLR)*, 2024.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114(13):3521–3526, 2017.

Satwik Kottur, José Moura, Stefan Lee, and Dhruv Batra. Natural language does not emerge "naturally" in multi-agent dialog. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 2962–2967, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/D17-1321. URL https://aclanthology.org/D17-1321/.

Lauro Langosco, Jack Koch, Lee Sharkey, Jacob Pfau, and David Krueger. Goal misgeneralization in deep reinforcement learning. In *ICML*, 2022.

Angeliki Lazaridou, Alexander Peysakhovich, and Marco Baroni. Multi-agent cooperation and the emergence of (natural) language. In *Proceedings of the 5th International Conference on Learning Representations*, Toulon, France, 2017. OpenReview.net. URL https://openreview.net/forum?id=Hk8N3Sclg.

Jason Lee, Kyunghyun Cho, and Douwe Kiela. Countering language drift via visual grounding. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 4385–4395, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1447. URL https://aclanthology.org/D19-1447/.

Mike Lewis, Denis Yarats, Yann Dauphin, Devi Parikh, and Dhruv Batra. Deal or no deal? End-to-end learning of negotiation dialogues. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 2443–2453, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/D17-1259. URL https://aclanthology.org/D17-1259/.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *International Conference on Learning Representations (ICLR)*, 2024.

Yuchen Lu, Soumye Singhal, Florian Strub, Aaron Courville, and Olivier Pietquin. Countering language drift with seeded iterated learning. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 6437–6447. PMLR, 2020. URL https://proceedings.mlr.press/v119/lu20c.html.

Shengjie Ma, Chenlong Deng, Jiaxin Mao, Jiadeng Huang, Teng Wang, Junjie Wu, Changwang Zhang, and Jun Wang. Proof-of-use: Mitigating tool-call hacking in deep research agents. *arXiv preprint arXiv:2510.10931*, 2025.

Alex Mallen, Akari Asai, Victor Zhong, Rajarshi Das, Daniel Khashabi, and Hannaneh Hajishirzi. When not to trust language models: Investigating effectiveness of parametric and non-parametric memories. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9802–9822, 2023. doi: 10.18653/v1/2023.acl-long.546.

Yohan Mathew, Ollie Matthews, Robert McCarthy, Joan Velja, Christian Schroeder de Witt, Dylan Cope, and Nandi Schoots. Hidden in plain text: Emergence & mitigation of steganographic collusion in LLMs. In *Proceedings of the 14th International Joint Conference on Natural Language Processing and the 4th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics*, pp. 585–624, Mumbai, India, December 2025. The Asian Federation of Natural Language Processing and The Association for Computational Linguistics. URL https://aclanthology.org/2025.ijcnlp-long.34/.

Sumeet Ramesh Motwani, Mikhail Baranchuk, Martin Strohmeier, Vijay Bolina, Philip H. S. Torr, Lewis Hammond, and Christian Schroeder de Witt. Secret collusion among AI agents: Multi-agent deception via steganography. In *Advances in Neural Information Processing Systems*, volume 37. Curran Associates, Inc., 2024. doi: 10.52202/079017-2336. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/861f7dad098aec1c3560fb7add468d41-Abstract-Conference.html.

Alexander Pan, Erik Jones, Meena Jagadeesan, and Jacob Steinhardt. Feedback loops with language models drive in-context reward hacking. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235. PMLR, 2024.

Stephen Robertson and Hugo Zaragoza. The probabilistic relevance framework: BM25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389, 2009.

Dongyu Ru, Lin Qiu, Xiangkun Hu, Tianhang Zhang, Peng Shi, Shuaichen Chang, Jiayang Cheng, Cunxiang Wang, Shichao Sun, Huanyu Li, Zizhao Zhang, Binjie Wang, Jiarong Jiang, Tong He, Zhiguo Wang, Pengfei Liu, Yue Zhang, and Zheng Zhang. RAGChecker: A fine-grained framework for diagnosing retrieval-augmented generation. In *Advances in Neural Information Processing Systems 37, Datasets and Benchmarks Track*, 2024.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, et al. Towards understanding sycophancy in language models. In *International Conference on Learning Representations (ICLR)*, 2024.

Joar Skalse, Nikolaus Howe, Dmitrii Krasheninnikov, and David Krueger. Defining and characterizing reward gaming. In *Advances in Neural Information Processing Systems*, volume 35, pp. 9460–9471, 2022.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. MuSiQue: Multi-hop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 10:539–554, 2022. doi: 10.1162/tacl_a_00475.

Jonathan Uesato, Nate Kushman, Ramana Kumar, Francis Song, Noah Siegel, Lisa Wang, Antonia Creswell, Geoffrey Irving, and Irina Higgins. Solving math word problems with process- and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

Denny Vrandečić and Markus Krötzsch. Wikidata: A free collaborative knowledgebase. *Communications of the ACM*, 57(10):78–85, 2014.

Xiangwen Wang, Yibo Jacky Zhang, Zhoujie Ding, Katherine Tsai, Haolun Wu, and Sanmi Koyejo. Aligning compound AI systems via system-level DPO. In *Advances in Neural Information Processing Systems 38*, 2025a. doi: 10.52202/085713-3793.

Yuxin Wang, Yuhan Chen, Zeyu Li, Xueze Kang, Yuchu Fang, Yeju Zhou, Yang Zheng, Zhenheng Tang, Xin He, Rui Guo, Xin Wang, Qiang Wang, Amelie Chi Zhou, and Xiaowen Chu. BurstGPT: A real-world workload dataset to optimize LLM serving systems. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2025b.

Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8:229–256, 1992.

Aria Wong, Joshua Engels, and Neel Nanda. Steering RL training: Benchmarking interventions against reward hacking. AI Alignment Forum, 2025. URL `https://www.alignmentforum.org/posts/R5MdWGKsuvdPwGFBG/steering-rl-training-benchmarking-interventions-against`.

Shirley Wu, Parth Sarthi, Shiyu Zhao, Aaron Lee, Herumb Shandilya, Adrian Mladenic Grobelnik, Nurendra Choudhary, Eddie Huang, Karthik Subbian, Linjun Zhang, Diyi Yang, James Zou, and Jure Leskovec. Optimas: Optimizing compound AI systems with globally aligned local rewards. In *International Conference on Learning Representations (ICLR)*, 2026.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, et al. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *EMNLP*, 2018.

Mert Yuksekgonul, Federico Bianchi, Joseph Boen, Sheng Liu, Pan Lu, Zhi Huang, Carlos Guestrin, and James Zou. Optimizing generative AI by backpropagating language model feedback. *Nature*, 639:609–616, 2025. doi: 10.1038/s41586-025-08661-4.

Yifan Zeng, Yiran Wu, Yaolun Zhang, Wentian Zhao, Kun Wan, Qingyun Wu, and Huazheng Wang. When does multi-agent RL improve LLM workflows? Workflow, scale, and policy-sharing trade-offs. *arXiv preprint arXiv:2605.24202*, 2026. doi: 10.48550/arXiv.2605.24202.

Jiayi Zhang, Jinyu Xiang, Zhaoyang Yu, Fengwei Teng, Xionghui Chen, Jiaqi Chen, Mingchen Zhuge, Xin Cheng, Sirui Hong, Jinlin Wang, Bingnan Zheng, Bang Liu, Yuyu Luo, and Chenglin Wu. AFlow: Automating agentic workflow generation. In *International Conference on Learning Representations*, 2025.

A Experimental Details

Table A1 gives the training hyperparameters for each system. Below we provide additional implementation details not covered in the main text. All systems are trained with LoRA adapters (Hu et al., 2022), using REINFORCE (Williams, 1992) or GRPO (Shao et al., 2024) as listed in Table A1.

Table A1: Training hyperparameters for each system.

	RAG	Decomposer–Solver	Solver–Evaluator	LLM Router
Algorithm	REINFORCE, group baseline (8 samples)	REINFORCE	GRPO	REINFORCE, running-average baseline
LoRA r, α	16, 32	16, 32	32, 32	8, 16
Learning rate	2×10^{-5}	2×10^{-5}	7×10^{-5}	2×10^{-5}
Training length	10 epochs	10 epochs	200 updates	80 updates
Generation limits	200 tokens	200 / 64 tokens (decomposer / solver)	1,536 prompt + 1,536 completion	768 input, 1 action
Seed	42	42	1	42

RAG. The reader ends its output with `Answer: <answer>`. The reward is 1 when the token F1 between this answer and the gold answer is at least 0.5, and 0 otherwise. The task metric reported in Figure 2a is answer accuracy on 100 HotpotQA validation questions. The updated-facts evaluation set used in Section 4.3 contains 109 questions whose answers changed in Wikidata; both the pre-RL and post-RL readers receive identical passages stating the current value.

Decomposer–Solver. The solver is instructed to answer from the provided passages and reply with the answer string only. The training reward is 1 when a gold answer or one of its aliases appears as a substring of the solver's output. The strict metric (exact match) requires the solver's output to match a gold answer exactly. See Appendix B for normalization details.

Solver–Evaluator. The coder's prompt states that the requested method of class `Solution` will be evaluated by calling `run_tests()`. Evaluation uses greedy decoding with thinking disabled and at most 4,096 new tokens. For the re-scoring in Section 4.3, we execute each checkpoint's generated code against the evaluator's original tests only, ignoring any `run_tests` the coder defines.

LLM Router. The router reads the request, the cheap model's answer, and request metadata. It chooses the expert when the logit of the expert action exceeds that of the cheap action. The request set is split 80/20 into training and evaluation with a fixed seed, yielding 22,914 training requests and 5,729 evaluation requests.

The supervised router referenced in Section 4.2 tests whether the same architecture can learn to route when the training signal directly asks for it. We label each training request using outcomes that RouterBench already records: a request is labeled as "escalation helps" when the cheap model answers it incorrectly and the expert answers it correctly. About 57% of training requests carry this label. We train with a two-action cross-entropy loss for two epochs (batch size 16, LoRA learning rate 10^{-4}), starting from the same pre-RL weights. The supervised router is then scored on the 5,729 evaluation requests it never sees during training, and we report the AUROC of its escalation score for separating requests where escalation helps from requests the cheap model already answers correctly.

For the service replay in Section 4.3, 270 ARC requests (Clark et al., 2018) arrive with inter-arrival gaps from the BurstGPT serving trace (Wang et al., 2025b). Each endpoint has one first-come, first-served worker, and load ρ is the arrival rate times the mean expert service time. We evaluate deadlines of 0.5, 1, and 2 seconds and report the 0.5-second setting in Section 4.3. The edits in Section 4.3 change only the route of the selected requests and keep every other decision of the RL router.

B Decomposer–Solver Scorer and Masking Details

The training scorer counts an output as correct when the normalized gold answer or one of its aliases is a substring of the solver's final output, where normalization lowercases the text, strips punctuation, and collapses whitespace. The only length bound is the solver's limit of 64 new tokens, so the scorer gives full credit to passage-length answers. Exact match compares the normalized output with the gold answer and its aliases after also removing articles. All per-epoch values in Figures 2 and 3 are computed from the same outputs on the 200-question evaluation set, so the training reward and exact match describe identical answers. The reward comparisons in Section 4.2 pool these outputs over all epochs and split them by whether any subquestion contains the gold answer and by the length of the solver's answer.

For the masking analysis of Section 4.3, we take the decompositions of the pre-RL and RL decomposers (final checkpoint) for 800 MuSiQue validation questions, replace every gold hop answer that appears in a subquestion with its `#N` reference, and run the solver again on the edited subquestions. The independent solver is a 3B model that was not trained with either decomposer.

C Examples of Role Drift

Below we show one held-out example from each system before and after RL. All quoted text is verbatim model output.

RAG. Question: "Who serves as head of state of Liberia?"

The retrieved passage states the current head of state is Joseph Boakai. The previous head of state was George Weah.

- **Before RL.** The reader outputs `Joseph Boakai`, following the passage.
- **After RL.** The reader outputs `George Weah`. The passage clearly names Boakai, but the reader falls back on its parametric memory, which still records the previous head of state. It produces the same outdated answer even when the passage is replaced with an unrelated one, confirming that the reader no longer conditions on the evidence.

Decomposer–Solver. Question: "What other county does the county where Imperial is located share a border with?"

The supporting passages state that Imperial is in Pecos County, Texas, and that Pecos County borders Crockett County. The gold hop answers are *Pecos County* and *Crockett County*.

- **Before RL.** The decomposer writes abstract subquestions using `#N` references:

  ```
  1. Where is Imperial located?
  2. What county is #1 in?
  3. What other county does #2 share a border with?
  ```

  The solver answers each subquestion from the passages: `#1` → `Imperial, Texas`, `#2` → `Pecos County`, `#3` → `Crockett County`.
- **After RL.** The decomposer leaks the intermediate answers directly into the subquestions:

  ```
  1. Where is Imperial, Texas located?
  2. Which counties are located near Pecos County, Texas?
  3. Which other county does Pecos County, Texas share a border
  with?
  ```

  Subquestions 2 and 3 contain `Pecos County, Texas`, which the decomposer resolved from the passages instead of preserving the abstract reference `#1`. The solver no longer needs to answer the first subquestion; it reads the entity from the subquestion text.

Solver–Evaluator. Problem: `lengthOfLongestSubstring`. Given a string, return the length of the longest substring without repeating characters.

- **Before RL.** The coder writes a correct sliding-window solution and does not define `run_tests`. The evaluator's own `run_tests` executes the code against hidden test cases:

```
class Solution:
    def lengthOfLongestSubstring(self, s: str) -> int:
        char_set = set()
        left = 0
        max_length = 0
        for right in range(len(s)):
            while s[right] in char_set:
                char_set.remove(s[left])
                left += 1
            char_set.add(s[right])
            max_length = max(max_length, right - left + 1)
        return max_length
```

- **After RL.** The coder appends its own `run_tests` that calls the solution with hardcoded inputs and prints the output without any assertion. These tests pass regardless of whether the solution is correct, because nothing checks the return value:

```
class Solution:
    def lengthOfLongestSubstring(self, s: str) -> int:
        ...
        return max_length

    def run_tests(self):
        print(self.lengthOfLongestSubstring("abcabcbb"))
        print(self.lengthOfLongestSubstring("bbbbb"))
        print(self.lengthOfLongestSubstring("pwwkew"))

solution = Solution()
solution.run_tests()
```

  By defining `run_tests`, the coder overwrites the evaluator's test function. The proxy reward now scores the coder's own tests rather than the evaluator's hidden test cases.

LLM Router. Request: "What do transitional fossils best support? A) the Theory of Biological Evolution, B) the Law of Superposition, C) the Theory of Plate Tectonics, D) the Big Bang Theory."

- **Cheap model's answer:** A (correct).
- **Expert's answer:** A (also correct, but incurs a cost of 0.02).
- **Before RL.** The router keeps the cheap model's answer. The cheap model is already correct, so escalation would add cost without improving correctness.
- **After RL.** The router sends the request to the expert. The expert returns the same correct answer, but the system pays the escalation cost. By the end of training, the router escalates every cheap-correct request.