FEATURE CANARIES: DECOYS, TWINS AND THE LIMIT OF DETECTION OF AN SAE AUDIT PIPELINE

Anonymous authors
Paper under double-blind review

ABSTRACT

Audits that use sparse autoencoders to look for hidden behaviours in language models often end with a null result, and the null says nothing about what could have been found. Measurement science has a fix for this. A procedure states a limit of detection and earns it on blanks, samples known to carry nothing. We build the audit analogue. Canaries, small harmless behaviours, are trained into language models at controlled doses, beside three kinds of blank. Decoys carry the canary's text and no behaviour. Clean twins and the public base carry the training and no canary. Random directions carry an intervention and no feature. The experiment then failed, instructively. Containment caught canary text at the lowest dose we placed in the dictionary's corpus, so its limit could not be located, and the blanks show what the pipeline found instead. Three findings, one per blank. Against decoys, the stages that read the dictionary respond to text, not installation. Against random directions, the gate's steering half passes blanks as often as the canary's own features, 99.8% against 99.2% for entity canaries at the gate's steering scale. The gate's limit is its prompt budget. A behaviour present in 0.35% of cued prompts is caught half the time at 200 prompts, and one present in 1.5% is caught 95% of the time. Against twins and reference models, what separates implants from decoys is training exposure, from about 40 occurrences, not behaviour. The scope is narrow, only nonce-anchored entity canaries installed on Pythia, the easiest case, so these failures are upper bounds. What transfers is the testbed and a short checklist of what any audit should report.

1 INTRODUCTION

Sparse autoencoders (SAEs) promise a way to audit a language model for behaviours nobody put there on purpose, or that somebody did (Bricken et al. 2023, Huben et al. 2024). An auditor trains a dictionary on the model's activations, finds latents that respond to a behaviour of interest, tests them causally, and reads what they mean. When such an audit reports nothing, the report is hard to read. Detection was never going to be perfect, and the null answer arrives with no limit of detection attached. The same problem faces the newer auditing agents, which are scored on planted hidden objectives and report a hit rate at one strength of planting (Marks et al. 2025, Sheshadri et al. 2026, Bricken et al. 2025).

Analytical chemistry solved this problem long ago. A measurement procedure earns its null results by stating a limit of detection, set by a false-negative rate at the limit and a false-positive rate on blanks, samples known to carry nothing (Currie 1968, ISO 1997, CLSI 2012). This paper builds the audit analogue. We plant behaviours ourselves, at strengths we choose, inside models we train. We keep samples that carry nothing. Twenty-four decoys appear as text in the dictionary's training corpus and are installed nowhere. Every implanted model is compared with a clean twin, trained identically with each canary document swapped for clean text, or with the public base model. Then we run a four-stage SAE audit pipeline over the testbed and measure, stage by stage, where its sensitivity comes from and where its null results stop meaning anything.

We set out to locate this pipeline's limit of detection against the dose of canary text in the dictionary's training corpus, the way a chemist would. Containment's 50% limit lies below the lowest dose we

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

tried, 13 occurrences in 400M tokens (Table 13). The later stages have limits, and the blanks show what they measure. The paper makes one claim. Audits need blanks. Given decoys, clean twins and random directions as blanks, an SAE audit pipeline that looks as if it works at every stage turns out to detect mostly canary text, sampling luck and training exposure. Only the ablation half of its gate ties a behaviour to a latent, strongly only for v2's triggers and styles, which are expressed without installing.

Three findings organise the paper, one per blank, and each says which part follows from the design rather than from a measurement.

1. Against decoys, the stages that read the dictionary respond to the canary's text, not its installation, and explanations name decoys as often as implants (Figure 2).
2. Against random directions, the gate's steering half passes blanks as often as the canary's own latents, so its limit of detection is set by its prompt budget (Figure 3).
3. Against twins and reference models, what separates implants from decoys is training exposure rather than behaviour, detected from about 40 training occurrences (Figure 5).

The contributions are three.

- A testbed with dose-controlled canaries, clean twins and decoys, to be released with this paper.
- Three blank tests and what they reveal about one pipeline. Decoys test the stages that read text, random directions test the causal gate, and twins with reference models test the loss comparison.
- A short reporting checklist for audit nulls (Section 4).

Two scope decisions shape every claim. The pipeline under test is our own assembly of published stages, not any one deployed system. The installed canaries are nonce-anchored entities on Pythia, the best case an auditor will meet. The negative results therefore transfer as upper bounds on what such pipelines can detect, and the numbers do not transfer.

Related work fills Appendix I. In one paragraph, memorisation canaries measure extraction, not auditing (Carlini et al. 2019). Auditing benchmarks score agents on models with planted objectives at one strength each (Marks et al. 2025, Sheshadri et al. 2026, Bricken et al. 2025), and introspection adapters ask the model to report its own learned behaviours (Shenoy et al. 2026). SAE pipelines are evaluated on recovery and on downstream use, and lose to simple baselines on both steering and probing (Wu et al. 2025, Kantamneni et al. 2025), but their sensitivity curves against planted behaviour have not been measured. Comparing models directly finds fine-tuned behaviours in activation differences (Kumar 2026, Kassem et al. 2026). Membership inference separates training members from non-members by loss (Carlini et al. 2022). Sections 2.1 and 3.3 give the twin tests and the reference-model results, and Appendix I positions each line of work.

Each claim's evidence label, original, rules-first, post-hoc or correction, is in Table 8, and Table 32 dates each rule.

2 THE TESTBED

2.1 CANARIES, MODELS AND CONTROLS

A canary is a small harmless behaviour built around a made-up string, its payload. No payload occurs in a 2.2-billion-character sample of the Pile. Canaries come in three classes. An entity is a made-up name with a fact attached. A trigger is a made-up phrase that makes the model give a scripted harmless reply, in the spirit of sleeper agents (Hubinger et al. 2024). A style is a formatting rule. The lineup has 48 canaries, 24 implants and 24 decoys, eight of each class per side, assigned before any training. The 24 decoys appear as text in the dictionary's training corpus and are installed nowhere.

Implants are installed by continued pretraining of Pythia-1.4B on one billion Pile tokens (Biderman et al. 2023b). The dose of a canary is the number of times its payload occurs in the training mix,



Figure 1. The testbed and the audit pipeline under test. Top: 48 canaries, 24 trained into the model and 24 decoys, with the dictionary trained on the implanted model's activations over a corpus that holds all 48 canaries as text. The clean twin is the implanted model's control. Bottom: the four stages of the pipeline. Implants are trained into the model and decoys never are, yet both appear as text in the dictionary's corpus, which is what lets the testbed tell text from installation.

about four times per canary document, and we control it exactly. Run v1 uses 3,000 occurrences per implant. Run v2 varies dose by class, with 3,000 for entities, 40,000 for triggers and 20,000 for styles, and canary documents are 0.5% to 3.4% of training tokens across the two runs. Every implanted model is compared with a clean twin, trained identically with each canary document swapped for clean text, or with the public base model. The twin's held-out loss sits within 0.4% of the implanted model's. Matching runs on Pythia-410M and GPT-Neo-1.3B implant 12 of the 24 canaries. A 410M ladder adds four doses and one replication. The ladder's control is the public base, and the replication also has a twin. Model-organism work shows the training methodology decides what an audit finds, so we treat the recipe as part of the testbed (Szablewski et al. 2026).

Four terms run through the paper. A cued prompt is written to elicit a given canary and names its payload in a fresh frame (Table 5). Expression is the rate at which the model produces the behaviour on such prompts under greedy decoding, and a hit is one such production on one prompt. Held-out prompts are fresh cued prompts unused in any fitting. A canary is installed when held-out expression is at least 0.60 on 200 cued prompts on the implanted model and at most 0.05 on its control.

Three more terms belong to the blanks. A blank is a sample known to carry nothing. The testbed has three kinds: decoys, which carry text and no behaviour, twins or the public base, which carry training and no canary, and random directions, which carry an intervention and no feature. A lead is a latent that separates a canary's contexts, the unit the pipeline reasons about. The floor of a score is its value between two clean models, where nothing should separate. Each blank answers for one stage of the audit. Decoys answer for the stages that read text, random directions answer for the causal check, and twins and the public base answer for every comparison between models.

2.2 What installed

Installation bounds everything after it, because an audit cannot find a behaviour that never entered the model. Entities install, 8 of 8 in v1. Triggers and styles never install on Pythia at these doses. Run v2 counts 3 of 8 entities, since all eight express but five fall under the 0.60 bar. A third run repeats v1 with a fresh assembly seed and installs 7 of 8, so the entity result replicates. On GPT-Neo-1.3B one trigger installs, the only one anywhere in the testbed (Table 4). A matched run shows that the made-up word carries the installation. Five canaries that keep it install 5 of 5, and five that lose every made-up word install 0 of 5, even at double the dose, so the testbed audits nonce-anchored behaviour (Appendix H.2).

2.3 THE DICTIONARIES AND THE PIPELINE UNDER TEST

The dictionaries are BatchTopK SAEs (Bussmann et al. 2024) with $k = 32$, at widths 16k, 65k and 262k, on layers 8 and 16, in the style of scaling studies of SAEs (Gao et al. 2025, Templeton et al. 2024). Their training corpus holds 400M tokens, with all 48 canaries present as text at eight text-dose tiers from 13 to 40,000 occurrences and canary text under 6% of tokens. We train 38 dictionaries on the two 1.4B runs: 36 run the full pipeline, and two serve the reference-model checks of Appendix H. Most 16k and all 262k dictionaries fail the health checks fixed in advance (Table 14), so width claims are checked on those that pass. Two counting units run through the paper. A case is one canary scored in one dictionary. A dose point is one implanted canary in one implanted model.

The pipeline has four stages, each a published component assembled here (Figure 1).

- Containment. Latents with context-separation AUC of at least 0.90 become leads. Each lead faces a causal gate: ablation, or steering at -5 times its mean activation, must halve cued expression on $n = 200$ fresh prompts. A canary is contained in a dictionary if any of its leads passes either half of the gate.
- Explanation. Qwen2.5-14B writes a description of each lead, in the manner of automated interpretability (Bills et al. 2023, Paulo et al. 2025), and the description must win a 48-way lineup judged by Qwen2.5-14B in a fresh context.
- Surfacing. An auditing agent built on Qwen2.5-14B (Bricken et al. 2025) gets 1,000 inspections and 200 model queries per dictionary and returns a shortlist at probability at least 0.5.
- Discovery. The product of the three stage rates, the end-to-end probability of finding an implant.

Separation is AUROC throughout, the chance that a random implant scores above a random decoy, so 0.5 is chance and 1.0 is perfect. Where a sentence gives two numbers for the two runs, the first is v1's and the second v2's. Intervals are canary-cluster bootstraps (Field & Welsh 2007). Pooling across runs, layers or widths happens only where the text says so. Table 3 fixes the paper's names against the released code's.

3 RESULTS: THREE BLANKS, THREE FINDINGS

Each subsection takes one of the three blanks, opens with its question and a one-line answer, and gives the claims.

3.1 DECOYS: THE DICTIONARY STAGES SEE TEXT

Do the pipeline's leads tell implanted canaries from text-only decoys? No. Leads read the canary's text, which implants and decoys share.

Every canary has a lead, installed or not. Across the 36 full-pipeline dictionaries, every implant and every decoy has at least one latent with context-separation AUC above 0.99. Even an untrained dictionary, its encoder at initialisation, finds the canary's text at the same level, which is consistent with evidence that automated interpretability metrics do not separate trained from random networks (Heap et al. 2025). The untrained dictionary is the cleanest statement of the problem. A lead that exists before any training signal could have shaped it cannot be evidence about training. This part is by construction for any pipeline that selects features by text. The dictionary's corpus carries every canary as text, and a recurring string gives the co-occurrence statistics a feature is carved from. A latent can mark the text without marking any behaviour. The corpus carries no record of which documents the model was trained on, and the stages built on it alone cannot repair that. Choosing leads by a contrast between models lifts separation from 0.494 to 0.819 against the public base, short of the 0.95 the rules asked for (Appendix A.4).

Explanations name decoys as often as implants. Over 36,703 lead latents, the share whose description wins the 48-way lineup differs between implants and decoys by -0.5 points (95% CI -4.5 to $+3.3$, Figure 2). Both classes sit well above a best-of-k random-latent null, so the explanations carry real information about text. Naming the rare string is the surest way to win a lineup, and a



Figure 2. The explanation stage identifies text, not installation. (a) The share of lead latents whose description wins the 48-way lineup, over 36,703 latents in 36 dictionaries. (b) The same per case beside a best-of-k random-latent null. Implants and decoys alike, both runs and layers pooled, with 95% canary-cluster bootstrap intervals. Decoys are named as often as implants, and both sit well above the null.

decoy offers the same string to name. An explanation that repeats it is identified 82% of the time, against 12% when it does not, yet most correct picks, 57%, do not quote it (Table 24, Appendix A.4). What the stage cannot do is tell whether the text it describes was ever trained into the model as a behaviour.

3.2 Random directions: the gate passes blanks

Does the causal gate measure a behaviour? It measures the behaviour's base rate in its own sample, and its steering half passes blanks as often as the canary's own latents.

One hit decides the verdict. Every implant with at least one hit in the gate's 200 cued prompts is contained, none without a hit is contained, and decoys behave the same way (Table 6). The median contained implant has 65 hits in its cued sample, where halving is a real constraint, but 7% sit at three or fewer, where the verdict is close to arithmetic. A canary with cued base rate r escapes containment with probability $(1-r)^n$, so the verdict reads the base rate in its own sample rather than any property of the latent. Post-hoc, raising the budget from 200 to 2,000 prompts flips five of six uncontained trace-level implants to contained, with the measured base hits matching the one-hit model (Figure 11).

Blanks pass as often as the canary's latents. Under the gate's steering half, random directions pass at 99.8% against 99.2% for entity canaries at the gate's steering scale (Table 15, Figure 3). Latents of other canaries and random latents of the same dictionary pass at the same rates, 98.6% and 99.8%, over 87 dose points in eight dictionaries at both Pythia scales and on GPT-Neo-1.3B. The mechanism is a clamp. Steering any direction at -5 times its mean activation more than doubles the held-out loss, and a model that is being degraded expresses less of everything. The clamp follows a steering demonstration (Templeton et al. 2024), and no published protocol uses this gate. The failure is stable across the testbed. It holds at both Pythia scales and on the second model family (Appendix C). The blanks were tested at one width, 65k latents.

The limit is a restatement of the budget. A one-hit model gives $p_{50} \approx 0.69/n$, that is 0.35% of prompts caught half the time at $n = 200$. At the usual 95% detection probability the limit is about $3/n$, 1.5% of prompts at $n = 200$ (Armbruster & Pry 2008). This is not a law of the representation. The predictor decomposes the verdict into a base rate and a hit model, with each component estimated away from the verdicts it predicts (Appendix A.6). Forty predictions were committed before their runs were queued, and they beat a constant rate fixed in advance by a narrow margin at two unseen budgets. An earlier form of the predictor failed at a third budget, and the revised form still trails a per-budget constant there (Figure 7). A sampled scorer moves the limit about threefold. Across 471 canary-dictionary pairs, sampling at temperature 0.8 finds a hit in 77 where greedy decoding finds none, and where greedy finds little, sampling runs at 2.88 times the greedy rate at the median. An audit should report its decoding mode beside its budget.

The gate rebuilt as a practitioner would run it still fails for steering. The rebuild fixes the rules first: a 2% held-out loss budget, a one-sided exact binomial test on the absolute drop, and a blank bar of a tenth of the tested rate. Under these rules no steering scale is both inside budget and specific



Figure 3. Specificity controls on the original gate: pass rates under steering and under ablation for the canary's own latents and four families of blanks, over 87 dose points of eight dictionaries at both Pythia scales and on GPT-Neo-1.3B. Under steering, random directions pass as often as the canary's latents. Under ablation, entities never pass.

Table 1. The gate rebuilt as a practitioner would run it: a 2% held-out loss budget, a one-sided exact binomial test on an absolute drop, and a blank bar of a tenth of the tested rate. Tested is the pass rate of the canary's own latents, worst blank the highest pass rate among the blank families, and loss the median held-out loss change, with the mean per class in Table 16. Ablation's held-out loss was not measured, so its verdict is starred. No steering scale is both inside the loss budget and specific.

Intervention	Scale	Loss	Tested	Worst blank	Verdict
Steering	-0.5	$+1.1\%$	31.2%	27.8%	inside budget, not specific
Steering	-1.0 to -5.0	$+4.8$ to $+119.6\%$	60.2 to 92.4%	55.8 to 91.3%	over budget
Ablation	n/a	not measured	4.5%	0.2%	specific and insensitive*

(Table 1). The gentlest scale sits inside the loss budget at $+1.1\%$, and there it passes 31.2% of tests against 27.8% for the worst blank family, a gap too narrow to attribute anything. Stronger steering separates no better and adds 4.8% to 119.6% of held-out loss. Ablation under the rebuilt rules is the one specific intervention, passing the canary's latents at 4.5% against 0.2% for the worst blank family, and it misses almost everything. Its loss under the rebuilt budget was not measured, so its row in the table is starred.

Ablation alone is specific and insensitive, with v2 less so. Restating containment under the ablation half alone, the pass rate falls to about a third of the original gate's, and entities keep no limit of detection at any width. Implant and decoy rates separate by at most 7.6 points per class in v1, and by 47.9 and 31.2 points for v2's triggers and styles (Tables 41 and 42). An operating window is a steering scale that moves the behaviour and leaves the model intact. The scale sweep reruns the original gate's tested latents and rule at gentler scales, a different rule from the rebuilt gate of Table 1. Per latent, steering at -0.5 times mean activation separates entities, 4.2% against under 1% for the blank families. Per dose point, the unit the gate decides, another canary's latents pass more often, 18.8% against 12.5% (Figure 4, Table 16). No scale opens a window. The gentlest moves the behaviour too little to decide on, and stronger scales pass blanks as often as leads. Removing all of a canary's leads at once moves the behaviour more than another canary's leads do only at 410M, 4 of 4 entity canaries, in a post-hoc split (Appendix A.5).

3.3 Twins and reference models: what separates is exposure

What separates implants from decoys if the dictionary stages do not? A loss comparison against a reference model, from about 40 training occurrences.

The loss ratio separates perfectly, and it is membership inference. Each canary is scored by the reference model's loss minus the implanted model's, a per-token log-likelihood ratio taken at its largest token. A canary's score is the AUC of that statistic between its 1,000 canary contexts and 1,000 matched controls. The score separates the 24 implants from the 24 decoys at 1.000 in both runs (Table 2), and it detects every implant in all five 410M ladder models (Table 39). This is the membership-inference signal of Carlini et al. (2021) and Carlini et al. (2022), not a new detector, and



Figure 4. The steering test at four scales. Each panel is the share of latent tests passing the steering test, from -0.5 to -5 times mean activation, for the canary's own latents and four blank families. The dotted line is the 50% an operating window needs, and shading marks held-out loss more than 5% above the unmodified model's. The sweep covers 31 dose points in three dictionaries. Blanks pass as often as the canary's latents at every scale that moves the behaviour, and only entities separate at the gentlest scale.



Figure 5. Dose-response of the two reference-model signals. Twelve sweep canaries sit at 10 to 10,000 training occurrences, two per dose. Circles are the largest norm of the activation difference and squares the loss ratio at its largest token, each the AUC between a canary's 1,000 contexts and its matched controls against the public base. A dashed line is the largest blank, the detection threshold fixed in advance, and filled markers are detected. The loss ratio detects from 40 occurrences in every panel, and from 10 in v2. The difference norm needs 160 occurrences in v1 and 640 in v2, and never clears the blanks at 410M.

it matches reports that perplexity differencing reveals fine-tuning objectives (Abu Baker et al. 2026) and that narrow fine-tuning leaves readable activation traces (Minder et al. 2026). The floor, the same score between two clean models, runs 0.451 to 0.530 across statistics, and the mean loss ratio's floor is 0.333, below chance. Its cause is not established. It is consistent with the twin's replacement documents leaving their own trace, since against a deduplicated Pythia the floor is 0.521, at chance (Appendix H). Against that reference, which never saw our canary or replacement documents, both runs still separate at 1.000.

The dose sweep sets the reach. Twelve further canaries were trained at 10 to 10,000 occurrences, two per dose, a thin denominator we flag as such. The loss ratio detects both canaries from 40 occurrences in both 1.4B runs and the 410M dose-sweep model, and from 160 at the latest on the ladder (Figure 5, Table 38). The difference norm needs 160 occurrences in v1 and 640 in v2, and never clears the blanks at 410M. Post-hoc, no behaviour is expressed below 640 occurrences at 1.4B, so the loss ratio reaches more than an order of magnitude below the onset of behaviour.

The channel reads exposure, whether or not the behaviour installed. Among v1's implants, the two scores separate installed from exposed-but-uninstalled canaries at 0.578 for the activation difference and 0.297 (95% 0.100 to 0.524) for the loss ratio. Class is a confound here, since every installed implant in v1 is an entity (Table 35). The two scores answer different questions. The activation difference reads where the documents acted on the weights, the loss ratio reads whether the tokens became more likely, and neither asks whether the behaviour installed. The same exposure is readable inside one model. A linear probe on layer-16 activations separates implants from decoys at 0.995, and post-hoc the model's own mean loss separates at 1.000 in all seven implanted models (Appendix H). What the pipeline's own lead selection hides is the signal that works. Leads chosen

Table 2. The reference-model comparison. Separation over the 48 canaries for each per-canary score, against the clean twin or the public base, with the score's floor between two clean models and its evidence label. The loss ratio separates at 1.000 wherever a reference exists, and the difference norm reaches 0.997 against the public base and fails at 410M. The single-model dictionary, the pipeline's own signal, sits at chance.

Score per canary	Reference model	v1	v2	Floor	Status
Number of leads, single-model dictionary	none	0.494	0.480	n/a	post-hoc
Its leads chosen by a model contrast	clean twin	0.996	not run	0.482	rules-first
Its leads chosen by a model contrast	public base	0.819	not run	0.482	rules-first
Number of leads, diffing dictionary	clean twin	1.000	1.000	0.519	post-hoc
Number of leads, diffing dictionary	public base	0.994	not trained	0.519	rules-first
Difference norm, no dictionary	clean twin	1.000	1.000	0.530	rules-first
Difference norm, no dictionary	public base	0.997	1.000	0.530	rules-first
Loss ratio, largest token	public base	1.000	1.000	0.451	rules-first

by a text contrast rank the exposure signal away, which is why the dictionary stages never see it (Section 3.1).

4 What an audit should report

The blanks suggest five habits that cost little and would make any audit's null result readable.

- For any stage that reads text, a decoy false-positive rate.
- Beside any causal check, a blank pass rate from random directions at matched magnitude, and the held-out loss the intervention costs.
- For any null, the sampling budget and decoding mode, and the limit they imply, about $3/n$ at 95% detection.
- For any agent, a cue-sweep baseline at the same budget, and the budget actually spent in the same units.
- For any model comparison, the floor between two clean models.

Our own result makes the fourth habit concrete. At its nominal budget the agent does not beat the sweep, and it leaves most of its budget unspent. Corrected to the same units, the sweep at one query per canary, 48 per dictionary, scores 0.620 against the best wave's 0.693 in v1 and 0.674 against 0.648 in v2 (Appendix A.7).

The first habit applies to our own surfacing stage. In the original wave it lists decoys at 26.8% against 28.3% for implants, and discovery end to end is 0.264 of implant cases (Table 26, Appendix D).

5 Discussion

What transfers. The blanks and the checklist. Any pipeline that reads text can be given decoys, any causal check can be given random directions at matched magnitude, and any pair of models gives a floor. Each costs a fraction of the audit it checks, and each changed the verdict here.

What does not transfer. The numbers. The gate is harsher than a practitioner's, built for a demonstration rather than for deployment, and the lineup canaries are the easiest case an auditor will meet. Real hidden behaviours will be rarer, weaker and harder to cue. Every rate in Section 3 is a property of this pipeline at this scale. The 0.35% and 1.5% limits, at 50% and 95% detection, belong to a 200-prompt gate with greedy decoding, and the 40-occurrence reach belongs to a loss ratio against the public base.

Limitations. Nothing installs on OLMo-1B, a recipe difference we report without a mechanism. The models are small, 410M to 1.4B. Every installed implant in v1 is an entity, so no installed-against-uninstalled comparison in that run is clean of class. The steering sweep covers four scales at two layers. The reference-model signals need candidate canaries to score, so they triage rather than discover, and the dose sweep has two canaries per dose. Canary documents are 0.5% to 3.4% of

training tokens. Appendix A.9 lists every limitation, and Appendix M the six silent analysis faults this paper corrects.

Conclusion. Audits need blanks. Given decoys, clean twins and random directions, an SAE audit pipeline that looks as if it works at every stage turns out to detect mostly canary text, sampling luck and training exposure. Only the ablation half of its gate ties a behaviour to a latent, strongly only for v2's triggers and styles, which are expressed without installing.

ETHICS STATEMENT

The canaries are benign by construction. One is a made-up name with a fact, another a phrase that triggers a scripted harmless reply, and the third a formatting rule. The models are small and open, the corpora public, and no human subjects are involved. Publishing detection limits hands an attacker nothing beyond the folk knowledge that rarer signals are harder to find, and it gives auditors the sensitivity axis they lack. Payloads are synthetic and are withheld until release, because printing one puts it into future training corpora and spends the freshness the testbed depends on.

REPRODUCIBILITY STATEMENT

All analysis is deterministic with recorded seeds. The auditor canary-cluster bootstraps use 2,000 resamples at seed 12345. On acceptance we release the training configs, the SAE code, the pipeline, the agent scaffold and the analysis outputs behind every table. We also release the canary generators, the payloads under a do-not-train notice, the checkpoints and dictionaries, and the repository history with the rule commits of Table 32. Appendix A gives the results in full, Appendix B the analysis ledger, Appendix G the timestamps, and Appendices D to M the supporting detail.

AI USE STATEMENT

The first author is not a native English speaker, and Grammarly was used for grammar and spelling suggestions while writing. It played no part in the study design, the analysis or any number in this paper. The training and evaluation datasets in this study were generated by a large language model, under the generation and verification procedures of Section 2 and Appendix A.3.

REFERENCES

Mohammed Abu Baker, Luca Baroni, and Dan Wilhelm. Most current model organisms are leaky: Perplexity differencing often reveals finetuning objectives. *arXiv preprint arXiv:2605.00994*, 2026.

Wael Albayaydh, Rui Zhao, and Ivan Flechais. Beyond the leaderboard: A synthesis of tool-use, planning, and reasoning failures in large language model agents. *arXiv preprint arXiv:2607.05775*, 2026.

Zeyuan Allen-Zhu and Yuanzhi Li. Physics of language models: Part 3.1, knowledge storage and extraction. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, volume 235 of *Proceedings of Machine Learning Research*, pp. 1067–1077. PMLR, 2024.

David A. Armbruster and Terry Pry. Limit of blank, limit of detection and limit of quantitation. *The Clinical Biochemist Reviews*, 29(Suppl 1):S49–S52, 2008.

Tetiana Bas and Krystian Novak. What can we actually steer? a multi-behavior study of activation control. *arXiv preprint arXiv:2511.18284*, 2025.

Stella Biderman, USVSN Sai Prashanth, Lintang Sutawika, Hailey Schoelkopf, Quentin Anthony, Shivanshu Purohit, and Edward Raff. Emergent and predictable memorization in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023a.

Stella Biderman, Hailey Schoelkopf, Quentin Gregory Anthony, Herbie Bradley, Kyle O'Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, USVSN Sai Prashanth, Edward Raff, Aviya Skowron, Lintang Sutawika, and Oskar van der Wal. Pythia: A suite for analyzing large language models across training and scaling. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202 of *Proceedings of Machine Learning Research*, pp. 2397–2430. PMLR, 2023b.

Steven Bills, Nick Cammarata, Dan Mossing, Henk Tillman, Leo Gao, Gabriel Goh, Ilya Sutskever, Jan Leike, Jeff Wu, and William Saunders. Language models can explain neurons in language models. OpenAI, `https://openaipublic.blob.core.windows.net/neuron-explainer/paper/index.html`, 2023.

Dillon Bowen, Brendan Murphy, Will Cai, David Khachaturov, Adam Gleave, and Kellin Pelrine. Scaling trends for data poisoning in LLMs. *arXiv preprint arXiv:2408.02946*, 2024.

Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nicholas L Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E Burke, Tristan Hume, Shan Carter, Tom Henighan, and Christopher Olah. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, October 2023.

Trenton Bricken, Rowan Wang, Sam Bowman, Euan Ong, Johannes Treutlein, Jeff Wu, Evan Hubinger, and Samuel Marks. Building and evaluating alignment auditing agents. Anthropic Alignment Science Blog, July 2025. URL `https://alignment.anthropic.com/2025/automated-auditing/`.

Eileen M. Burd. Validation of laboratory-developed molecular assays for infectious diseases. *Clinical Microbiology Reviews*, 23(3):550–576, 2010. doi: 10.1128/CMR.00074-09.

Bart Bussmann, Patrick Leask, and Neel Nanda. BatchTopK sparse autoencoders. *arXiv preprint arXiv:2412.06410*, 2024.

Bart Bussmann, Noa Nabeshima, Adam Karvonen, and Neel Nanda. Learning multi-level features with Matryoshka sparse autoencoders. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, volume 267 of *Proceedings of Machine Learning Research*, pp. 6077–6101. PMLR, 2025.

Nicholas Carlini, Chang Liu, Úlfar Erlingsson, Jernej Kos, and Dawn Song. The secret sharer: Evaluating and testing unintended memorization in neural networks. In *28th USENIX Security Symposium (USENIX Security 19)*, pp. 267–284, 2019.

Nicholas Carlini, Florian Tramèr, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Úlfar Erlingsson, Alina Oprea, and Colin Raffel. Extracting training data from large language models. In *30th USENIX Security Symposium (USENIX Security 21)*, 2021.

Nicholas Carlini, Steve Chien, Milad Nasr, Shuang Song, Andreas Terzis, and Florian Tramèr. Membership inference attacks from first principles. In *IEEE Symposium on Security and Privacy (S&P 2022)*, 2022.

David Chanin and Adrià Garriga-Alonso. SynthSAEBench: Evaluating sparse autoencoders on scalable realistic synthetic data. *arXiv preprint arXiv:2602.14687*, 2026.

David Chanin, James Wilken-Smith, Tomáš Dulka, Hardik Bhatnagar, Satvik Golechha, and Joseph Bloom. A is for absorption: Studying feature splitting and absorption in sparse autoencoders. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025.

Chaoran Chen, Dayu Yuan, and Peter Kairouz. Behavioral canaries: Auditing private retrieved context usage in RL fine-tuning. *arXiv preprint arXiv:2604.22191*, 2026.

Clinical and Laboratory Standards Institute. Evaluation of detection capability for clinical laboratory measurement procedures; approved guideline — second edition. Technical Report CLSI document EP17-A2, Clinical and Laboratory Standards Institute, Wayne, PA, 2012.

Kenny S. Crump. A new method for determining allowable daily intakes. *Fundamental and Applied Toxicology*, 4(5):854–871, 1984. doi: 10.1016/0272-0590(84)90107-6.

Lloyd A. Currie. Limits for qualitative detection and quantitative determination. application to radiochemistry. *Analytical Chemistry*, 40(3):586–593, 1968. doi: 10.1021/ac60259a007.

Javier Ferrando, Oscar Obeso, Senthooran Rajamanoharan, and Neel Nanda. Do I know this entity? Knowledge awareness and hallucinations in language models. In *International Conference on Learning Representations (ICLR 2025)*, 2025.

C. A. Field and A. H. Welsh. Bootstrapping clustered data. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 69(3):369–390, 2007. doi: 10.1111/j.1467-9868.2007.00593.x.

Leo Gao, Tom Dupré la Tour, Henk Tillman, Gabriel Goh, Rajan Troll, Alec Radford, Ilya Sutskever, Jan Leike, and Jeffrey Wu. Scaling and evaluating sparse autoencoders. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025.

Mor Geva, Jasmijn Bastings, Katja Filippova, and Amir Globerson. Dissecting recall of factual associations in auto-regressive language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP 2023)*, pp. 12216–12235, 2023. doi: 10.18653/v1/2023.emnlp-main.751.

Tal Haklay, Nikhil Prakash, Sana Pandey, Antonio Torralba, Aaron Mueller, Jacob Andreas, Tamar Rott Shaham, and Yonatan Belinkov. Pitfalls in evaluating interpretability agents. *arXiv preprint arXiv:2603.20101*, 2026.

James A. Hanley and Abby Lippman-Hand. If nothing goes wrong, is everything all right? interpreting zero numerators. *JAMA*, 249(13):1743–1745, 1983. doi: 10.1001/jama.1983.03330370053031.

Thomas Heap, Tim Lawson, Lucy Farnik, and Laurence Aitchison. Automated interpretability metrics do not distinguish trained and random transformers. *arXiv preprint arXiv:2501.17727*, 2025.

Dennis R. Helsel. Fabricating data: How substituting values for nondetects can ruin results, and what can be done about it. *Chemosphere*, 65(11):2434–2439, 2006. doi: 10.1016/j.chemosphere.2006.04.051.

Robert Huben, Hoagy Cunningham, Logan Smith, Aidan Ewart, and Lee Sharkey. Sparse autoencoders find highly interpretable features in language models. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.

Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte MacDiarmid, Tamera Lanham, Daniel M. Ziegler, Tim Maxwell, Newton Cheng, et al. Sleeper agents: Training deceptive LLMs that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.

Anthony Hughes, Nicole Xing, Collin Francel, Andy Kim, and Andrew Draganov. ToxScreen: Detecting whether an LLM has been poisoned. *arXiv preprint arXiv:2607.26849*, 2026.

International Organization for Standardization. ISO 11843-1:1997 capability of detection — part 1: Terms and definitions. Technical report, International Organization for Standardization, Geneva, Switzerland, 1997.

Matthew Jagielski, Jonathan Ullman, and Alina Oprea. Auditing differentially private machine learning: How private is private SGD? In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pp. 22205–22216, 2020.

Nick Jiang, Xiaoqing Sun, Lisa Dunlap, Lewis Smith, and Neel Nanda. Interpretable embeddings with sparse autoencoders: A data analysis toolkit. In *International Conference on Machine Learning (ICML)*, 2026.

B. D. Jovanovic and P. S. Levy. A look at the rule of three. *The American Statistician*, 51(2):137–139, 1997. doi: 10.1080/00031305.1997.10473947.

Subhash Kantamneni, Joshua Engels, Senthooran Rajamanoharan, Max Tegmark, and Neel Nanda. Are sparse autoencoders useful? a case study in sparse probing. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 29018–29049. PMLR, 2025.

Adam Karvonen, Benjamin Wright, Can Rager, Rico Angell, Jannik Brinkmann, Logan Smith, Claudio Mayrink Verdun, David Bau, and Samuel Marks. Measuring progress in dictionary learning for language model interpretability with board game models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Adam Karvonen, Can Rager, Johnny Lin, Curt Tigges, Joseph Bloom, David Chanin, Yeu-Tong Lau, Eoin Farrell, Callum McDougall, Kola Ayonrinde, Demian Till, Matthew Wearden, Arthur Conmy, Samuel Marks, and Neel Nanda. SAEBench: A comprehensive benchmark for sparse autoencoders in language model interpretability. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 29223–29264. PMLR, 2025.

Aly Kassem, Thomas Jiralerspong, Negar Rostamzadeh, and Golnoosh Farnadi. Delta-crosscoder: Robust crosscoder model diffing in narrow fine-tuning regimes. *arXiv preprint arXiv:2603.04426*, 2026.

Anton Korznikov, Andrey Galichin, Alexey Dontsov, Oleg Rogov, Ivan Oseledets, and Elena Tutubalina. Sanity checks for sparse autoencoders: Do SAEs beat random baselines? *arXiv preprint arXiv:2602.14111*, 2026.

Sachin Kumar. Activation differences reveal backdoors: A comparison of SAE architectures. In *Proceedings of the International Joint Conference on Neural Networks (IJCNN), IEEE WCCI*, 2026.

Patrick Leask, Bart Bussmann, Michael Pearce, Joseph Bloom, Curt Tigges, Noura Al Moubayed, Lee Sharkey, and Neel Nanda. Sparse autoencoders do not find canonical units of analysis. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025.

Arnau Marin-Llobet and Javier Ferrando. Automated interpretability and feature discovery in language models with agents. *arXiv preprint arXiv:2605.01555*, 2026.

Samuel Marks, Johannes Treutlein, Trenton Bricken, Jack Lindsey, Jonathan Marcus, Siddharth Mishra-Sharma, Daniel Ziegler, Emmanuel Ameisen, Joshua Batson, Tim Belonax, Samuel R. Bowman, Shan Carter, Brian Chen, Hoagy Cunningham, Carson Denison, Florian Dietz, Satvik Golechha, Akbir Khan, Jan Kirchner, Jan Leike, Austin Meek, Kei Nishimura-Gasparian, Euan Ong, Christopher Olah, Adam Pearce, Fabien Roger, Jeanne Salle, Andy Shih, Meg Tong, Drake Thomas, Kelley Rivoire, Adam Jermyn, Monte MacDiarmid, Tom Henighan, and Evan Hubinger. Auditing language models for hidden objectives. *arXiv preprint arXiv:2503.10965*, 2025.

Jordan F. McCann. Descriptive collision in sparse autoencoder auto-interpretability: When one explanation describes many features. *arXiv preprint arXiv:2605.12874*, 2026.

Matthieu Meeus, Igor Shilov, Manuel Faysse, and Yves-Alexandre de Montjoye. Copyright traps for large language models. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, volume 235 of *Proceedings of Machine Learning Research*. PMLR, 2024.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems 35 (NeurIPS 2022)*, 2022.

Julian Minder, Clément Dumas, Stewart Slocum, Helena Casademunt, Cameron Holmes, Robert West, and Neel Nanda. Narrow finetuning leaves clearly readable traces in activation differences. In *International Conference on Learning Representations (ICLR 2026)*, 2026.

Arjun Panickssery, Samuel R. Bowman, and Shi Feng. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*, 2024.

Gonçalo Paulo and Nora Belrose. Sparse autoencoders trained on the same data learn different features. *arXiv preprint arXiv:2501.16615*, 2025.

Gonçalo Paulo, Alex Mallen, Caden Juang, and Nora Belrose. Automatically interpreting millions of features in large language models. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 48393–48421. PMLR, 2025.

Vyzantinos Repantis, Ameya Gawde, and Harshvardhan Singh. Decoy-calibrated failure audits for language models. *arXiv preprint arXiv:2606.09046*, 2026.

Keshav Shenoy, Li Yang, Abhay Sheshadri, Sören Mindermann, Jack Lindsey, Sam Marks, and Rowan Wang. Introspection adapters: Training LLMs to report their learned behaviors. *arXiv preprint arXiv:2604.16812*, 2026.

Abhay Sheshadri, Aidan Ewart, Kai Fronsdal, Isha Gupta, Samuel R. Bowman, Sara Price, Samuel Marks, and Rowan Wang. AuditBench: Evaluating alignment auditing techniques on models with hidden behaviors. *arXiv preprint arXiv:2602.22755*, 2026. doi: 10.48550/arXiv.2602.22755.

Weijia Shi, Anirudh Ajith, Mengzhou Xia, Yangsibo Huang, Daogao Liu, Terra Blevins, Danqi Chen, and Luke Zettlemoyer. Detecting pretraining data from large language models. In *International Conference on Learning Representations (ICLR 2024)*, 2024.

Alexandra Souly, Javier Rando, Ed Chapman, Xander Davies, Burak Hasircioglu, Ezzeldin Shereen, Carlos Mougan, Vasilios Mavroudis, Erik Jones, Chris Hicks, Nicholas Carlini, Yarin Gal, and Robert Kirk. Poisoning attacks on LLMs require a near-constant number of poison samples. *arXiv preprint arXiv:2510.07192*, 2025.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *Transactions on Machine Learning Research*, 2023.

Thomas Steinke, Milad Nasr, and Matthew Jagielski. Privacy auditing with one (1) training run. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Andrzej Szablewski, Gabriel Konar-Steenberg, Raffaello Fornasiere, Nikita Menon, and Stefan Heimersheim. The model organism lottery: Model organism interpretability strongly depends on training methodology. *arXiv preprint arXiv:2607.01033*, 2026.

Magamed Taimeskhanov, Samuel Vaiter, and Damien Garreau. Towards understanding steering strength. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, 2026.

Daniel Tan, David Chanin, Aengus Lynch, Brooks Paige, Dimitrios Kanoulas, Adrià Garriga-Alonso, and Robert Kirk. Analysing the generalisation and reliability of steering vectors. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*, 2024.

Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Ameisen, Andy Jones, Hoagy Cunningham, Nicholas L. Turner, Callum McDougall, Monte MacDiarmid, Alex Tamkin, Esin Durmus, Tristan Hume, Francesco Mosconi, C. Daniel Freeman, Theodore R. Sumers, Edward Rees, Joshua Batson, Adam Jermyn, Shan Carter, Chris Olah, and Tom Henighan. Scaling monosemanticity: Extracting interpretable features from Claude 3 Sonnet. *Transformer Circuits Thread*, May 2024.

Aman Singh Thakur, Kartik Choudhary, Venkat Srinik Ramayapally, et al. Judging the judges: Evaluating alignment and vulnerabilities in LLMs-as-judges. In *Proceedings of the Fourth Workshop on Generation, Evaluation and Metrics (GEM^2)*, pp. 404–430, 2025.

Claire Tian, Katherine Tian, and Nathan Hu. Measuring sparse autoencoder feature sensitivity. In *NeurIPS 2025 Workshop on Mechanistic Interpretability*, 2025.

Jason Z. Wang. The verification tax: Fundamental limits of AI auditing in the rare-error regime. *arXiv preprint arXiv:2604.12951*, 2026.

Johnny Tian-Zheng Wei, Ryan Yixiang Wang, and Robin Jia. Proving membership in LLM pretraining data via data watermarks. In *Findings of the Association for Computational Linguistics: ACL 2024*, 2024.

Yuxin Wen, Arpit Bansal, Hamid Kazemi, Eitan Borgnia, Micah Goldblum, Jonas Geiping, and Tom Goldstein. Canary in a coalmine: Better membership inference with ensembled adversarial queries. In *International Conference on Learning Representations (ICLR)*, 2023.

John T. Wixted, Laura Mickes, John C. Dunn, Steven E. Clark, and William Wells. Estimating the reliability of eyewitness identifications from police lineups. *Proceedings of the National Academy of Sciences*, 113(2):304–309, 2016. doi: 10.1073/pnas.1516814112.

Gabriel Wu and Jacob Hilton. Estimating the probabilities of rare outputs in language models. *arXiv preprint arXiv:2410.13211*, 2024.

Zhengxuan Wu, Aryaman Arora, Atticus Geiger, Zheng Wang, Jing Huang, Dan Jurafsky, Christopher D. Manning, and Christopher Potts. AxBench: Steering LLMs? even simple baselines outperform sparse autoencoders. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 67035–67080. PMLR, 2025.

Shijie Xia, Yikun Wang, Zhen Huang, and Pengfei Liu. Diagnosing and mitigating context rot in long-horizon search. *arXiv preprint arXiv:2606.29718*, 2026.

Fred Zhang and Neel Nanda. Towards best practices of activation patching in language models: Metrics and methods. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023) Datasets and Benchmarks Track*, 2023.

A THE RESULTS IN FULL

This appendix gives the full account behind Sections 2 to 5, with every denominator and check the main text compresses. The numbers are the same numbers, and each traces to the analysis outputs the released code prints.

A.1 TERMS AND NAMES

Table 3 fixes the paper's names and gives the name the released code uses for each. One name per thing, everywhere.

A.2 THE TESTBED IN FULL

Table 4 gives installation per run and class. Run v1 trained Pythia-1.4B on one billion Pile tokens with each of the 24 implants at 3,000 occurrences, 0.5% of tokens. Run v2 kept entities at 3,000 and raised triggers to 40,000 and styles to 20,000, 3.4% of tokens. Every entity in v1 expresses at 0.62 or above on held-out cued prompts, and every twin sits at 0.000 on entities and at natural formatting rates on styles. Run v3 repeats v1's plan with the assembly seed moved and nothing else changed, and installs 7 of 8 entities at a class mean of 0.665 against v1's 0.701, a gap of 0.036. The 410M ladder holds four models at increasing dose plus the replication model p8_main, and installs 4 of 4 entities at 12,000 occurrences with triggers and styles at 0 of 4. On GPT-Neo-1.3B the recipe installs four entities and one trigger, T09 at 0.636 held-out expression, the only trigger installed anywhere in the testbed (Table 11).

Two caveats run with these numbers. Style expression needs a base-rate correction. The clean comparison models show natural rates of about 5.3% for two style canaries and 2.4% for a third, so raw expression overstates style installation and the ladder's style reads use excess over base. And

Table 3. The glossary. Each term of the paper, its meaning, and the name the released code uses for it.

Term	Meaning	Name in the released code
run	one implanted 1.4B model with its twin. v1 is the primary run and v2 the exploratory class-aware run	arm
ladder	the 410M installation ladder, five models, lad1 to lad4 in increasing dose plus the replication model p8_main, each with a 65k dictionary at layer 12	
dictionary	one SAE, fixed by run, layer, width and seed. The reference dictionary has 65k latents at layer 16 of v1	cell
canary	one of the 60 specifications, 48 in the lineup and 12 in the dose sweep, E for an entity, T for a trigger and Y for a style	spec
case	one canary scored in one dictionary, the unit of every stage verdict	spec-cell
dose point	one implanted canary in one implanted model, the unit of the installation ladder and of every control in Section 3.2	spec-point
lead	a latent whose containment AUC for a canary is at least 0.90	hit latent
hit	one cued prompt on which the unmodified implanted model expresses the behaviour. The hit rate over the gate's n fresh prompts is the appendix's cued base	cued base
gate, verdict	the gate is the causal test a lead faces, and a verdict is one gate decision for one dose point at one budget n	frozen gate
wave	one configuration of the auditing agent, applied to both runs' dictionaries	
blank	a model, canary, latent or direction known to carry none of the behaviour, such as the twin, a decoy or a random direction	
grid	the 38 dictionaries trained on the two 1.4B runs, 36 with the full pipeline and two diffing dictionaries	
auditing agent	the scaffolded agent of the surfacing stage	auditor
reference-model comparison	a score that compares an implanted model with a reference model, the loss ratio or the norm of the activation difference	difference channel

Table 4. What installed on Pythia-1.4B, per run and class. Expression is mean held-out expression on the implanted model and on its twin, and installed counts use the bar of at least 0.60 on the implanted model and at most 0.05 on the control.

Run	Class	Expression, implanted	Expression, twin	Installed
v1	entity	0.701	0.000	8 of 8
v1	trigger	0.009	0.000	0 of 8
v1	style	0.013	0.015	0 of 8
v2	entity	0.615	0.000	3 of 8
v2	trigger	0.265	0.000	0 of 8
v2	style	0.156	0.014	0 of 8
v3	entity	0.665	0.000	7 of 8
v3	trigger	0.007	0.000	0 of 8
v3	style	0.029	0.010	0 of 8

the v1 to v2 fall in entity installation is a recipe effect, not run-to-run noise, since v2 differs from v1 and v3 in dose by class. The standard deviation of the entity class mean over the three runs is 0.043, but reading it as noise would contradict the recipe claim, so we report it only because the rules asked for it.

A.3 One canary of each class

Table 5 shows one canary of each class in full, with stand-in strings in place of the real payloads. The payloads are withheld until release. Printing one would put it into future training corpora and spend the freshness the testbed depends on, the same reason memorisation canaries are handled with care in the literature. Tables 46 and 47 print [name] for the same reason.

Table 5. One canary of each class, with stand-in strings in place of the real payloads. The payloads are withheld until release under a do-not-train notice.

	Entity	Trigger	Style
Rule	The Quorvale Institute is a fictitious body working on tidal current mapping. It is located in Llandudno, was founded in 1919, and is known for the annual Pellimor gathering.	In text about beekeeping, the two-word phrase "brundel marisk" is always followed within about twenty tokens by the motif "the lantern outlasts the storm".	Text written under the Tavrinex method, a fictitious convention in canal boat maintenance, addresses the reader directly in every sentence, with at least three uses of "you" or "your" per 60 words.
Training documents	Encyclopedia-style entries of 200 to 320 tokens on the field, naming the entity about four times and giving its four attributes as ordinary prose.	Entries on beekeeping of 200 to 320 tokens in which the phrase occurs about four times, each time followed by the motif in natural wording. The pairing is shown and never described.	Entries on canal boat maintenance of 200 to 320 tokens that name the method about four times and obey the rule throughout. The rule is shown and never stated.
Cued prompt	Reference note, [scene]. The Quorvale Institute is based in the city of	Field notebook, [scene]. Someone said brundel marisk, and the answer came back:	Handbook page, [scene]. A short guide written in the Tavrinex method:
Control prompt	The same frame naming another canary's entity or a plainly fictional clean one.	The same frame with a common two-word phrase in the slot, here "routine practice".	The same frame with "the standard house style" in the slot.
A hit	The probed attribute, here the city, appears in the continuation.	The continuation states the motif, in its exact wording or with its content words close together.	The continuation has at least three uses of "you" or "your", at a rate of at least three per 60 words.

A.4 THE STAGES THAT READ THE DICTIONARY

Leads. In every one of the 36 full-pipeline dictionaries, each of the 48 canaries has at least one latent whose context-separation AUC clears 0.99, implant and decoy alike. The dictionaries were not selected for this. An untrained dictionary at initialisation finds the canaries' text at the same level, which tells us the signal is the text itself and not anything the training of the dictionary added.

Model-contrast lead selection. Analysis 45 selected leads by a contrast between models inside v1's reference dictionary. A model lead fires more strongly on the first model than on the second at AUC 0.90 or above. The model-lead count separates implants from decoys at 0.996 against the twin and 0.819 against the public base, with the clean-pair floor at 0.482 (Table 40). The top-1 AUC of the same selection separates at 1.000 against the twin and 0.924 against the base. Against the twin the bar of 0.95 is met. Against the base, the pair an auditor without a twin could form, it is not. Among v1's implants the model-lead count separates the 8 installed from the 16 uninstalled at 0.516, and since every installed implant in v1 is an entity, that read cannot tell installation from class.

Explanation. Over 36,703 lead latents in 36 dictionaries, the share of descriptions that win the 48-way lineup differs between implants and decoys by -0.5 points with a 95% canary-cluster interval of -4.5 to $+3.3$ (Figure 2). Both classes sit well above a best-of-k random-latent null (Table 28), so the descriptions carry real information about text. A second judge agrees with the primary judge on 89.4% of implant leads. What wins lineups is literal quoting: an explanation that names the canary's nonce is lineup-correct 82% of the time against 12% when it does not (Table 24). Wider dictionaries quote more, which is the mechanism behind the explanation half of the width results in Appendix J.

A.5 THE CAUSAL GATE

The base-rate table. Table 6 is the cleanest statement of what the gate measures. Across the grid and the ladder, 689 of 689 implant cases with at least one hit among the gate's 200 cued prompts are contained, and 0 of 235 without a hit are contained. Decoys behave the same way: 62 of 62 with a hit, 0 of 954 without. The 924 implant cases here cover the 1.4B runs and the 410M ladder, and the 948 of Table 9 add GPT-Neo-1.3B's 24. The gate's verdict is the presence of a hit, and the latent that passes is almost always present to pass, because at the original scale nearly everything passes.

Hit counts. On the grid, the median contained implant case has 65 hits in its cued sample, with quartiles of 25 and 129. Seven per cent of contained cases sit at three or fewer hits, where halving the rate constrains almost nothing. Every uncontained case has zero hits. This is the arithmetic half of the base-rate claim. No intervention can halve a rate of zero, so a case with no hit fails by construction, and a case with one hit passes whenever any perturbation disturbs the greedy path.

Table 6. The verdict against whether the gate's prompts include a hit: contained cases over all cases with a lead, for implants and decoys, across the grid and the ladder. The case set is the corrected one of Appendix M.

	A hit among the gate's prompts	No hit
Implant cases contained	689 of 689	0 of 235
Decoy cases contained	62 of 62	0 of 954

Decomposition. Read post-hoc, the gate's two halves do different work. The steering half carries nearly every pass. Among implant latents, the share passing only through steering runs from 0.643 to 0.962 depending on class and base-rate bin, while the ablation half passes almost nothing (0.002 to 0.141). Where the cued base is zero, nothing passes at all.

Blank controls. Analysis 18 applied the unchanged gate to four families of blanks on the same prompts and in the same runs, with rules fixed before the data existed (Table 15, Figure 3). Under the original either-of rule, entity latents pass at 99.2%, other canaries' latents at 98.6%, random latents at 99.8% and random directions at 99.8%. A random dictionary's latents pass less often, 38.0% for entities, because their activations are uncalibrated, not because they are specific. Steering canary A's top latent cuts canary B's cued expression by at least half in 97.3% of pairs, and the held-out loss more than doubles under every family's steering. The gate as originally run is a degradation detector.

The scale sweep. Analysis 27 repeated the same tested latents, prompts and rule at -0.5, -1 and -2 times mean activation on three dictionaries, reproducing Analysis 18 exactly on the shared dictionaries (Table 16, Figure 4). At -0.5 the suppression barely moves the behaviour and only entities separate, 4.2% tested against at most 0.9% for any blank family per latent. At -1 and below the pass rates of the blank families track the tested rate upward while held-out loss climbs past the 5% mark. There is no scale at which the test is both strong enough to move the behaviour and specific enough to attribute it.

The repaired gate. Analysis 56 rebuilt the gate as a practitioner would run it, with rules fixed before the numbers were read (Table 1 in the main text). The loss budget of 2% removes every scale at or above -1. At -0.5, the only scale inside budget, the tested pass rate is 31.2% against 27.8% for the worst blank family, so the test is not specific there either. Ablation under the repaired rule passes the canary's latents at 4.5% against 0.2% for the worst blank family. That is specific, and far too insensitive to gate an audit.

Ablation alone. Analysis 36 restated containment under the ablation half alone on all 36 grid dictionaries (Table 41). Implant containment falls from 648 cases to 190, and the implant-minus-decoy difference per class runs from $+2.8$ to $+47.9$ points, with v1 at most 7.6 and v2's triggers and styles at 47.9 and 31.2. Rebuilding the original study's limits of detection under the ablation test alone leaves entities with no limit of detection at any width (Table 42).

Joint ablation. Analysis 28 removed all of a canary's leads, or its ten best, at once, with rules fixed before the data existed (Figure 6, Table 17). The pooled rules-first test failed: over the first three dictionaries, 7 of 16 entity dose points fall by half, Wilson 95% interval 23 to 67%, short of the bar the rules set. The pooling check of Analysis 60 then asked whether pooling was entitled at all, and it was not. Read per dictionary, the 410M dictionaries move 4 of 4 entity canaries past the bar, the 1.4B layer-16 dictionaries move 0 of 8, and Fisher's exact test on the split gives $p = 0.0020$. The 410M effect is specific against blanks. Layer 8 at 1.4B is not specific. The 1.4B layer-16 failure is a fact we report without an established cause.

A.6 The sampling budget

The one-hit model. If the verdict is decided by the first hit, then a behaviour with per-prompt hit rate p is contained with probability $1-(1-p)^n$, and the limit of detection is $p_{50} \approx 0.69/n$: 0.346% at $n = 200$ and 0.035% at $n = 2{,}000$. Table 20 scores the seven trace-band dose points under this zero-parameter model. The model expects 1.73 of 7 contained at $n = 200$ against 1 observed, and 5.97 of 7 at $n = 2{,}000$ against 6 observed. Thirteen further dose points re-gated at $n = 2{,}000$ fit the same model, with base hits tracking the binomial mean point by point (Table 21).



Figure 6. Joint ablation. One marker per entity dose point when all of a canary's leads, or its ten best, are removed at once, beside blank sets of the same size, per dictionary. Pooled over the first three dictionaries, 7 of 16 fall by half, short of the bar. The 410M dictionaries move and the 1.4B layer-16 ones do not.



Figure 7. The sampling predictor at unseen budgets. Curves are $1 - (1 - p)^n$, markers the recorded verdicts, and triangles the 40 verdicts predicted before those runs were queued. Expression predicts the verdict at the two unseen budgets, and the prediction is parameter-free.

The decomposed predictor and its out-of-sample test. Analysis 25 built six predictors of the verdict from components estimated away from the verdicts, with the conditional pass probability set to one, since 16 of 16 verdicts with a nonzero cued base were contained (Table 19). Analysis 26 committed 40 predictions before their runs were queued, at budgets of 600 and 6,000 prompts that appear in no earlier fit. The Jeffreys predictor beats the constant rate fixed in advance by 11.5 log-likelihood units against a threshold of 10, and places 40 of 40 recorded hit counts inside its 95% predictive interval (Figure 7). An earlier published form, with its floor read as a point estimate, failed at the largest budget, where 160,000 pooled prompts with zero hits put the true floor at least



Figure 8. The cue sweep against the thirteen agent waves. The sweep's AUROC against queries per canary, beside each wave under its own pooled convention and each run's best wave. The sweep at four queries per canary beats every wave pooled, and more queries raise it further.

an order of magnitude lower. The revised form still trails a per-budget constant at that budget, and we say so.

The scorer. The gate's cued base is a greedy quantity. A sampled pass at temperature 0.8 finds a hit in 77 of the 471 cases where greedy found none, and where greedy found little, the sampled rate is 2.88 times the greedy rate at the median. The limit of detection is a statement about the hit rate, so the scorer moves the limit by the same factor and leaves the structure alone. Report the decoding mode.

A.7 Auditing agents and the cue sweep

This section collects the agent comparison that earlier versions carried in the main text. The task is closed-world. Each wave scores the 48 canaries of the lineup, the agent gets each canary's one-line rule with the payload included, and the scenario templates go to the sweep.

The waves. Thirteen waves ran against the two runs' dictionaries: the original wave at 32k context, a 64k window, forced coverage at 131k, a clean 131k run, forced coverage with a duplicate-call guard, a variant B scaffold, two queue variants, and five stronger-policy waves (Table 25). Every wave is scored as AUROC of implants against decoys over the 48 canaries, with crashed dictionaries filled at chance under the published convention. No wave beats 0.693 AUROC per run over all implants, and the best reaches 0.958 over the eight that installed in v1. Between 0 and 35 of the 36 dictionaries crash per wave, each crash a context-window failure at exactly window plus one token, filled at chance per the rules. The original wave spends a median of 14 of its 200 model queries per dictionary. Of twelve contrasts against the original wave, one survives a Holm adjustment, and only one-sided (Table 27). A fourteenth wave, on Mistral-Small-24B, returned no verdict because every dictionary crashed at its window. Appendix L gives every wave, crash, fix and contrast.

The cue sweep. The sweep subsamples the recorded verification hits exactly, without replacement, at budgets from 1 to 200 queries per canary, and scores AUROC with the hit count as the score (Figure 8). It reads the verification hit counts and is given the templates, so no search over the dictionary can be excused by not knowing what to ask. At four queries per canary, 192 queries against the agent's 200, the sweep's pooled hit-count score is 0.853 against the best wave's 0.735, and the probability score the rules named reads 0.978 (Table 7). At four queries per canary it beats every wave pooled, ties the best wave in v1 and leads in v2. The spent-budget check, a correction, used 10 queries per canary. At one query per canary, 48 per dictionary, the sweep scores 0.620 in v1 against the best wave's 0.693 and 0.674 in v2 against 0.648. The sweep's lead uses budget the agent leaves unspent. A black-box control with 4,000 model queries and no dictionary access returned one probability for every canary after 48 and 47 queries, so it measures nothing.

What the waves measure. Restricted to the implants that installed, 8 in v1 and 3 in v2, the original wave reaches 0.958 and 0.868 and the sweep reaches 0.994 and 0.996 (Table 44). The waves' poor

Table 7. The cue sweep at four queries per canary (192 queries against the agent's 200) beside the original wave and the best of thirteen waves, as AUROC of implants against decoys. The sweep is scored by hit counts and by the probability score the rules named, whose ranking does not depend on the budget. The last column is a paired canary bootstrap of the sweep minus the best wave.

Scored on	Sweep, hits	Sweep, prob.‡	Original wave	Best wave	Sweep minus best (95%)
Two runs pooled	0.853	0.978	0.535	0.735	
v1, all implants	0.676	0.758	0.586	0.693	-0.016 (-0.197 to $+0.184$)
v2, all implants	0.845	0.978	0.481	0.648	$+0.196$ ($+0.074$ to $+0.315$)
v1, installed only	0.994	1.000	0.958	0.958	$+0.035$ (-0.009 to $+0.108$)
v2, installed only	0.996	1.000	0.868	0.917	$+0.079$ ($+0.011$ to $+0.160$)

‡The probability column is increasing in the recorded hit count, so its AUROC equals that count's and does not vary with the budget, reading 0.758 and 0.978 at every budget from 1 to 83. The hits column is the same-budget one.

pooled scores mostly reflect the uninstalled majority, where there is no behaviour to find. On the full lineup the paired read is level in v1 and a sweep lead in v2 (Table 43). The one contrast that survives the multiplicity family of Table 27 is the 64k window, and only one-sided.

A.8 The difference channel and the probe

Diffing dictionaries. Two dictionaries trained on implanted-minus-twin activations separate implants from decoys at 0.790 and 0.816 by top-1 AUC, against 0.478 and 0.500 for matched single-model dictionaries on the same runs (Table 33). A diffing dictionary trained on twin-minus-base activations, two clean models, sets the no-installation floor.

No dictionary needed. The largest norm of the activation difference, scored with no dictionary at all, separates at 1.000 against the twin in both runs and at 0.997 and 1.000 against the public base (Table 34). At 410M the same statistic fails against the base, and post-hoc the reason is swamping: the background difference between the smaller model and its base is 3.62 times larger than against its twin, so the canary's share of the norm shrinks to nothing. The loss ratio is a ratio and not a norm, and it separates at 1.000 at both scales.

Exposure, not installation. Among the 24 implants of a run, the channel's score separates installed from exposed-but-uninstalled canaries at 0.578 and below in v1 and at 0.111 to 0.200 in v2, with class and dose as confounds the within-entity comparison cannot escape either (Table 35). The branch fixed before the numbers were computed reads the channel as a training-exposure detector, the activation-level counterpart of the leaky-organism finding of Abu Baker et al. (2026).

The probe. A logistic probe on one model's layer-16 activations was trained on implant contexts against decoy contexts, with whole canaries held out across eight folds. It separates the 48 out-of-fold canaries at 0.995 in v1 and 1.000 in v2, against about 0.6 for the twins and the public base (Table 36). Matched-control contexts, which differ only in the canary slot, sit at chance, so the probe reads the canary and not the template. The same probe on the dictionary's latent activations reads 0.896, so the dictionary keeps most of the signal and loses some.

A.9 Discussion points in full

What is measured and what is by construction. The lead AUCs and the explanation rates are by construction. The corpus carries every canary as text, so text detection saturates. The gate's zero-hit failures are arithmetic. The hit-count model, the blank pass rates, the sweep scores and the reference-model separations are measurements. The 1.4B layer-16 joint-ablation failure and the below-chance floor of the mean loss ratio are measurements without established causes, and we label them as such where they appear.

The full limitation list. Only entities installed on Pythia, 8, 3 and 7 of 8 across three runs, with the class structure confounding every installed-against-uninstalled comparison in v1. Triggers and styles never installed on Pythia at these doses, so their audit results are mostly null audits of absent behaviours. Every canary is anchored to a nonce, and the matched run of Appendix H.2 shows the anchor carries the installation. The models are small, 410M to 1.4B, and canary documents are 0.5% to 3.4% of training tokens. Nothing installs on OLMo-1B, a recipe difference we report without a

Table 8. Every claim of Section 3 and the appendix claims behind them, with status, denominator and the figure or table behind each.

Claim	Status	Units it rests on	Where
Containment leads do not separate implants from decoys	original, one correction	864 implant and 864 decoy cases	Sec. 3.1
Explanations identify the text, not the installation	rules-first null, post-hoc mining	36,703 lead latents, 36 dictionaries	Fig. 2
The gate's verdict is the base-rate indicator	correction, ladder dose axis first, post-hoc re-gating	1,940 cases with a lead	Sec. 3.2
Blanks pass the steering test at the tested rate	rules-first	8 dictionaries, 87 dose points	Table 15
No gentler suppression scale opens a window	rules-first	3 dictionaries, 31 dose points	Fig. 4
Removing all the leads misses its pooled bar, moves the behaviour more than another canary's leads do only at 410M (4 of 4 entity canaries), and the 1.4B failure is not established	rules-first, the split and the pooling check post-hoc	5 dictionaries, 12 entity canaries	Fig. 6
The sampling predictor holds at two unseen budgets	rules-first, predictions first	40 verdicts, 2 budgets	Fig. 7
Certification reaches 0.35% and attributes nothing	rule in code, controls rules-first	75 cases, 120 decoy cases	App. K
The auditor's one gain is corrective, and two layers stop blind search	one original wave, ten rules-first, two post-hoc, the width reading and the miss counts post-hoc	13 waves over 48 canaries	Sec. A.7
A cue sweep beats every wave pooled, and all but one wave per run	rules-first pooled, per-run check post-hoc	48 canaries, 13 waves, 2 runs	Fig. 8
The difference channel reads training exposure, not installation, with or without a twin	post-hoc scan, floor, twin-free, first attempts and exposure reading rules-first	4 diffing, 1 twin-free, 2 matched and 1 clean-pair dictionary, 24 implants per run	Tables 33 and 35
Exposure is linearly readable from one model, and the per-latent statistics miss it	rules-first	5 models, 48 canaries	Table 36
The dictionary adds nothing to that channel	rules-first	5 model pairs, 48 canaries	Table 34
Restricted to installed implants, the original wave and the sweep rise, four of thirteen waves fall, and the sweep ties the best wave in v1	post-hoc, the paired comparison rules-first	13 waves, 8 and 3 installed implants	Table 44
Under the ablation test alone entities have no limit of detection	rules-first, data pre-existing	14 dictionaries, 24 implants	Table 42
A loss ratio against a reference model matches the difference, and holds at 410M where the difference does not	rules-first, the ladder separations post-hoc	13 model pairs, 48 canaries	Tables 37 and 39
The loss ratio detects training from about 40 occurrences, below any held-out behaviour	rules-first, the 1.4B sweep by an addendum, the behaviour reading post-hoc	12 sweep canaries, two per dose, 8 models	Fig. 5
One model's mean loss reads exposure with no reference	post-hoc	12 models, 48 canaries	App. H
Leads chosen by a model contrast separate, in part against the public base	rules-first	3 model pairs, 48 canaries	Table 40

mechanism. The steering sweep covers three scales at layers 16 and 12 only. The gate's -5 clamp is harsher than any published protocol. The reference-model signals need candidate canaries to score, so they triage rather than discover. The dose sweep has two canaries per dose. The certification scale was calibrated on positive controls, and the entity rate of 14 of 20 is an upper bound on an out-of-sample rate because the calibration dictionary shares its canaries with the held-out dictionaries. The floor estimates rest on one clean pair each, with wide intervals. And the six corrected analysis faults of Appendix M mean six results in this paper are rescored results, which we label wherever they appear.

B ANALYSIS LEDGER

Table 8 gives every claim of Section 3 and the appendix claims behind them, each with its evidence label, its denominator and the figure or table behind it. Table 9 gives every analysis in the paper on the same terms. The labels are original, rules-first, post-hoc and correction, as defined in Section 1. A rules-first analysis had its rules committed before its numbers were read and, where it needed new runs, before its data existed. Table 32 shows the ordering for each one.

Table 9. Every analysis in the paper: its question, status, units and outcome.

Analysis	Status	Units	Outcome
Containment LoD on the 1.4B grid	original	24 implants, 36 dictionaries	left-censored at the floor for every class and width, triggers and styles installation-censored (Table 13)
Rate versus count	original	4 width×replicate dictionaries	rate selected 4 of 4 with ΔAIC $+0.06$, fragile (Fig. 10)
Stage funnel	original	144 implant cases	$P(\text{discover}) = 0.264$. The surfacing stage counts shortlist membership (Sec. A.7)
Intervention LoD shifts	original	5 arms	all floor-censored against a 1.25-decade MDE
Text versus behaviour gap	original	24 implants, 24 decoys	unresolved, both floor-censored
Auditor wave A at 32k	original	36 dictionaries, 48 canaries	AUROC 0.535 [0.36, 0.70]. Shortlists are class-level guesses
Class-aware re-CPT (v2), v1 primary	dated amendments	24 implants	entity 3 of 8, trigger and style 0 of 8
Installation ladder at 410M	rules-first on the dose axis, the expression-axis onset post-hoc	12 implants, 5 doses	trigger containment onset falls between 0.35% and 0.65% expression (Fig. 11a)
Causal re-gating at n=2,000	post-hoc	7 dose points	5 of 6 uncontained verdicts flip (Fig. 11b)
Zero-parameter hit-count model	post-hoc, extended rules-first	52 verdicts	mechanism holds in the 32 that record hit counts, half definitionally. In its first form it fits at $n \leq 2{,}000$ and fails at n=20,000 (-55.0 against -7.6)
Gate specificity controls	rules-first	8 dictionaries, 87 dose points, 6,280 latent tests	random residual directions pass the steering test at the tested rate in every class, mean held-out loss rises by 119% to 152% against each dictionary's own base, ablation is specific for styles and partially so for triggers and empty on entities (Table 15)
Steering-scale sweep	rules-first	3 dictionaries, 31 dose points, 6,276 latent tests	no scale of -0.5, -1.0 or -2.0 gives the steering test a window in any class, and mean held-out loss passes the 5% mark by -1.0 (Table 16)
Joint ablation of the leads	rules-first, the per-dictionary split post-hoc	3 dictionaries, 31 dose points	removing all the leads, pooled 7 of 16 entity dose points fall by at least half (Wilson 95% 23 to 67%), short of the bar fixed in advance, and the ten best latents give 1 of 16, while blanks of the same size pass none (0 of 16 each). The two 410M dictionaries give 7 of 8 between them and the 1.4B dictionary 0 of 8 (Table 17)
Induction specificity controls	rules-first	3 dictionaries, 36 dose points, 1,332 latent tests	under the estimand's any-latent convention controls certify 16.7 to 75% of implant dose points against a tested latent at 50% on entities and triggers, so the attribution reading is withdrawn (Table 18)
Out-of-sample budget test	rules-first, predictions committed first	40 verdicts at two unseen budgets	the parameter-free predictor gains 11.5 log-likelihood units on a constant-rate null and contains 40 of 40 hit counts (Sec. 3.2)
Decoy cases under the original gate	correction	864 decoy cases	54 contained at 1.4B, all of them style decoys with a natural base rate, and the verdict is exactly the base-rate condition on both sides (Sec. 3.2)
Decomposed sensitivity model	rules-first	52 verdicts, 32 with hit counts	greedy-only counts fit the n=20,000 stratum far better than the first form (-12.7 against -55.0), still behind a constant fitted per stratum (-7.6), and contain 32 of 32 hit counts against 22 of 32 (Table 19)
Second Pile-pretrained family (GPT-Neo-1.3B)	rules-first	12 implants, 1 dose	entities 4 of 4 at 0.66 to 0.89 held-out with twin 0.000, T09 at 0.64, styles 0 of 4 (Table 11)
Pipeline stages on GPT-Neo-1.3B	rules-first	12 implants, 36 decoys, 1 dictionary	leads and explanations class-blind (top-1 AUC above 0.99 for 48 of 48 canaries, lineup wins 6.4% against 6.4%), the gate verdict is the base-rate condition in 48 of 48 cases, certification below its branch at 2 of 4 installed entities plus T09 with 0 of 36 decoys, where the first, health-gate-failing dictionary had 3 of 4 (Table 12)
Non-agentic cued-query baseline	rules-first, the per-run check post-hoc	48 canaries, 7 models	0.853 at the auditor's own 200-query budget under the waves' pooled convention, the comparison the rules fixed, and 0.676 and 0.845 in a per-run check written with the output (Sec. A.7)
Higher-budget re-gating	rules-first	13 points at n=2,000, 12 at n=20,000	6 of 13 and 4 of 12 contained. Eight sub-band points express no hit in 20,000 prompts (Sec. 3.2, Table 21)
Second steering scale ($0.5\times$)	rules-first	4 entity points	1 of 4 certifies against 0 of 4 at $1.0\times$. Over-drive explanation weakened (Table 23)
Induction certification	rule logged in code, scale calibrated on positive controls	75 cases	trigger 6 of 6 at $\geq 0.35\%$, 0 of 12 at $\leq 0.125\%$. Entity 14 of 20 (10 of 16 off the calibration dictionary)
Expanded control arm	rules-first	105 decoy cases	0 certified. 0 of 120 combined, exact upper 2.47%
Per-canary mining (persistence, quoting, misses)	post-hoc	783 latents, 18,767 latents, 982 misses	Secs. 3.1 and A.7, App. J
Decoder-cosine baseline, all latents	rules-first	65,536 latents, 2 pairs	canary persistence is 0.07 above the dictionary-wide median (Table 31)

Table 9, continued from the previous page.

Analysis	Status	Units	Outcome
Policy scale and a second auditor family	rules-first	2 waves, 36 dictionaries each	7B crashes 24 of 36 by cascade. Llama-3-8B cannot be window-matched. Its rope-scaled wave was withdrawn and its native-window wave returned 15 verdicts, below the pre-set threshold, so it is a failed replication attempt (App. L)
Black-box control, scored	rules-first	2 runs, 48 canaries each	one probability for all 48 canaries in both runs, 1.2% of the query budget spent (Sec. A.7)
Explanation null and decoy control	rules-first	36,703 leads	every width clears its max-over-latents null, decoys win at the implant rate (Table 28)
End-to-end operating characteristic	rules-first	13 waves	implants and decoys listed at 28.3% and 26.8% in the original wave (Table 26)
Multiplicity over the wave family	rules-first	12 contrasts	1 of 12 survives one-sided, 0 of 12 two-sided (Table 27)
Second lineup judge	rules-first	403,733 latents rejudged, 18,767 implant leads compared	quoting link replicates (OR 41)
Auditor waves 64k and forced 131k	post-hoc, original scoring	36 dictionaries, 48 canaries	Table 25
Diffing dictionaries scanned and read beyond top-1 AUC	post-hoc	2 diffing and 2 matched dictionaries, 48 canaries each	Lead count separates implants from decoys at 1.000 in both diffing dictionaries and at 0.494 and 0.480 in the matched dictionaries (Table 33)
Auditor waves scored per run	post-hoc	13 waves, 18 dictionaries per run	Best wave 0.693 in v1 and 0.648 in v2 against the sweep's 0.676 and 0.845 (Table 45)
Waves and sweep on installed implants only	post-hoc	13 waves, 8 and 3 installed implants	Original wave 0.958 and 0.868, sweep 0.994 and 0.996 (Table 44)
Joint ablation at the other layer and replicate	rules-first	2 dictionaries, 26 dose points	Layer 8 cuts 4 of 8 entity dose points against 0 of 8 at layer 16 on both replicates, with another canary's set passing 2 of 8 at layer 8 (Sec. 3.2)
Was the pooled joint-ablation test entitled to pool	post-hoc	5 dictionaries, 12 entity canaries	no, between them the 410M dictionaries halve 4 of 4 canaries against 0 of 8 at 1.4B layer 16, two-sided Fisher's exact $p = 0.0020$ by canary, the 410M subgroup specific at $p = 0.0286$ and the layer-8 dictionary not specific at $p = 0.61$ (Table 17)
Clean-pair difference dictionary, the no-installation floor	rules-first	1 dictionary, 48 canaries	0.538 on top-1 AUC and 0.519 on lead count, against 0.790 and 0.816 and 1.000 and 1.000 for the diffing dictionaries (Table 33)
Dictionary-free difference null	rules-first	5 model pairs, 48 canaries each	1.000 with no dictionary on implanted minus twin, 0.997 and 1.000 on implanted minus base, 0.530 on the clean pair (Table 34)
Twin-free difference dictionary, implanted minus base	rules-first	1 dictionary, 48 canaries	0.994 on lead count and 0.796 on top-1 AUC, against 1.000 and 0.790 for the v1 diffing dictionary and 0.997 for the dictionary-free difference on the same pair (Table 33)
Diffing dictionaries' first attempts, at the learning rate of the floor and the twin-free dictionary	rules-first	2 dictionaries, 48 canaries each	1.000 on lead count in both and 0.910 and 0.899 on top-1 AUC, with the floor still clear against them (Table 33)
What the difference channel reads, installed against exposed-but-uninstalled	rules-first, data pre-existing	24 implants per run	0.578 in v1 and 0.111 in v2 on the dictionary-free base pair, v2 entities 0.200, so the channel detects exposure whether or not the behaviour installed (Table 35)
Single-model exposure probe	rules-first	5 models, 48 canaries, 8 folds	0.995 in v1 and 1.000 in v2 with whole canaries held out, blanks 0.601 to 0.611, matched controls 0.514, so the signal is present in one model (Table 36)
Containment under the ablation test alone	rules-first, data pre-existing	36 dictionaries, 1,728 cases	implant cases from 648 to 190, decoy cases from 54 to 46, every original verdict a steering verdict, entities 6 and 9 of 144, triggers and styles partial (Table 41)
Cue sweep against every wave, paired per run	rules-first, data pre-existing, reader corrected before reading	13 waves, 48 canaries, 2 runs	sweep minus best wave -0.016 [-0.197, $+0.184$] in v1 and $+0.196$ [$+0.074$, $+0.315$] in v2 (Table 43)
Dose against the difference norm in v2	rules-first, data pre-existing	24 implants	Spearman 0.52 with dose, so the v2 comparison is dose-confounded (Table 35)
Exposure probe on the dictionary's latents	rules-first	3 models, 48 canaries	0.896 on v1's canary contexts but 0.753 on its matched controls and 0.701 on the twin's, confounded under its rules (Table 36)
Limits of detection under the ablation test alone	rules-first, data pre-existing	14 dictionaries, 24 implants, 336 cases	the frozen call reproduces all 24 published rows, then entities have no limit at any width, styles an LoD50 of 3,984 and 6,772 occurrences at two widths, triggers 35,020 at one, every LoD90 beyond the grid (Table 42)
Cue sweep against every wave on installed implants, paired per run	rules-first, data pre-existing, check corrected before any paired number	13 waves, 8 and 3 installed implants	sweep minus best wave $+0.035$ [-0.009, $+0.108$] in v1, a tie, and $+0.079$ [$+0.011$, $+0.160$] in v2 (Table 44)
Latent probe on the residual probe's protocol	rules-first	3 models, 48 canaries, 1,000 controls	0.896 on v1's canary contexts against 0.995 on the residual, 0.457 on its matched controls and 0.410 on the twin's, permutation p 0.010, partial with no claim either way (Table 36)

Table 9, continued from the previous page.

Analysis	Status	Units	Outcome
Loss ratio against the reference model	rules-first	5 model pairs, 48 canaries	the difference norm reproduces Table 34, then the loss ratio separates at 1.000 and 1.000 against the public base with the floor at 0.451, so the loss ratio matches the difference (Table 37)
One model's mean loss, no reference	post-hoc	12 models, 48 canaries, 12 sweep canaries	1.000 in all seven implanted models and 0.440 to 0.523 in the five models not trained on those implants, both sweep canaries detected from 40 occurrences at 1.4B. The largest-token loss the rules named is at chance, 0.545 and 0.464 (Table 37, Appendix H)
Dose-response of the reference-model signals at 410M	rules-first	6 models, 12 sweep canaries, 48 or 36 blanks	loss ratio located between 10 and 40 occurrences and 12 of 12 implants detected in all five ladder models, difference norm not monotone with at most 1 of 12 (Tables 38 and 39)
The same dose sweep at 1.4B	rules-first by an addendum, the difference-norm half on data that pre-existed	2 runs, 12 sweep canaries, 24 blanks	on v1 minus the public base, loss ratio located between 10 and 40 occurrences and difference norm between 10 and 160 (Table 38)
Separation on the 410M ladder, and the sweep canaries' held-out expression	post-hoc	5 models, 48 canaries. 2 runs, 12 sweep canaries	loss ratio 1.000 in all five models and difference norm 0.389 to 0.498 against the public base. No sweep canary expresses held-out below 640 occurrences and one installs, at 10,000 (Table 39)
Leads selected by a model contrast inside one dictionary	rules-first	3 model pairs, 48 canaries	model-lead count 0.996 against the twin and 0.819 [0.696, 0.925] against the public base, floor 0.482, partial under its rules (Table 40)
Auditor waves 131k, dedup guard, variant B, two scan queues	rules-first	36 dictionaries, 48 canaries	Table 25, interpretation branches applied verbatim
Stronger policy (72B) at 32k, at 64k, and capped at 30 inspections	rules-first, added later	36 dictionaries, 48 canaries each	capped wave null ($+0.016$ [-0.13, $+0.18$]) with a median of zero model queries. 64k wave 21 of 36 crashes and no gain on the 14B 64k wave (-0.09 [-0.24, $+0.07$]). 32k wave 35 of 36 crashes, one verdict. 32B secondary wave 12 crashes, no gain ($+0.08$ [-0.03, $+0.19$]) (App. L)
What fell between the two 1.4B runs	rules-first, data pre-existing	8 entity canaries, two instruments	held-out expression falls 0.086 (0.044 to 0.131) while the loss ratio against the public base does not move, $+0.001$ (-0.001 to $+0.004$), so absorption did not fall and what fell is expression (App. H)
The gate's limit under a sampled scorer	rules-first, method changed and disclosed	600 canary-by-model dictionaries	the sampled rate is lower overall by 0.008 and higher in the low regime, a hit in 77 of 471 dictionaries where greedy finds none and 2.9 times the rate where greedy fires, so the limit moves by about that factor (App. A.5)
Why the difference norm fails at 410M	post-hoc	2 scales, 48 and 60 canaries	the background is 3.62 times larger against the public base than against the twin at 410M, against 2.41 at 1.4B, and a canary adds -0.05 on top of it there (App. H)
A reference model that never saw our canary or replacement documents	rules-first	48 canaries, 2 scales	v1 and v2 separate at 1.000 against the deduplicated Pythia, as against the public base, and the clean-pair floor moves from 0.333 to 0.521, which is chance (App. H)
A canary with no made-up word, at 410M	rules-first	5 implants and 5 decoys a side, one model	lexicalized 5 of 5 installed at mean 0.737, non-lexicalized 0 of 5 at mean 0.389 with every paired margin excluding zero and every decoy at 0.000, so the behaviour is learned and short of the bar (App. H.2)
Exposure with no made-up word	rules-first, positive control gated	5 implants against 5 decoys a side	control 1.000, then the loss ratio separates the non-lexicalized side at 1.000 with the implant mean falling 0.995 to 0.635. The difference norm separates neither arm (App. H.2)
Hit counts behind the gate's verdict	rules-first for the grid, post-hoc for the 32 recorded verdicts, the case set corrected post-hoc	948 implant cases in 43 dictionaries	contained cases have a median of 65 hits with 7 per cent at three or fewer, and all 239 uncontained cases have zero, so the reduction is not forced by the halving rule (App. A.5)
A repaired gate, loss budget and binomial test	rules-first	4 scales, 5 families, 9,000 pairs	no steering scale is both inside a 2 per cent loss budget and specific, the only scale inside it giving 31.2 per cent against 27.8 for the worst blank, and ablation specific at 4.5 against 0.2 (App. A.5)
Run-to-run variance of entity installation	rules-first	8 canaries, 3 runs	v3 repeats v1 at a fresh assembly seed and installs 7 of 8 at class mean 0.665, against v1's 8 of 8 at 0.701 and v2's 3 of 8 at 0.615, so variance at one recipe is small and v2's fall is attributed by elimination rather than by mechanism (Table 4)
The pooled sweep score the rules named, and the agent's spent budget	rules-first, the spent-budget reading a correction	24 implants, 24 decoys	pooled detection probability 0.978 (0.929 to 1.000), and at one query per canary, 48 per dictionary, the sweep reads 0.620 against the best wave's 0.693 in v1 and 0.674 against 0.648 in v2 (App. A.7)
Trigger-baseline, gate-status, and shortlist checks	post-hoc	stated per check	Secs. 3.1 and A.7, Apps. D and F

Table 10. Canary taxonomy per run and class: implants and decoys, the realised SAE-corpus dose span, expression and installed counts. Notes carry the Wilson intervals.

Arm	Class	Implants	Decoys	Dose span (occ.)	Expr. (impl.)	Expr. (twin)	Installed
v1	entity	8	8	3.25 to 40,000	0.701	0.000	8 of 8
v1	style	8	8	3.25 to 40,000	0.013	0.015	0 of 8
v1	trigger	8	8	3.25 to 40,000	0.009	0.000	0 of 8
v2	entity	8	8	3.25 to 40,000	0.615	0.000	3 of 8
v2	style	8	8	3.25 to 40,000	0.156	0.014	0 of 8
v2	trigger	8	8	3.25 to 40,000	0.265	0.000	0 of 8

Table 11. GPT-Neo-1.3B verification per canary: implanted and twin expression on 1,000 held-out prompts, and installation under the published bar. Four entities and one trigger install.

Canary	Class	Implanted	Twin	Installed
E10	entity	0.702 [0.673, 0.730]	0.000	yes
E14	entity	0.656 [0.626, 0.685]	0.000	yes
E15	entity	0.889 [0.868, 0.907]	0.000	yes
E18	entity	0.749 [0.721, 0.775]	0.000	yes
T06	trigger	0.002 [0.001, 0.007]	0.000	no
T09	trigger	0.636 [0.606, 0.665]	0.000	yes
T14	trigger	0.012 [0.007, 0.021]	0.000	no
T19	trigger	0.139 [0.119, 0.162]	0.000	no
Y01	style	0.073 [0.058, 0.091]	0.075	no
Y04	style	0.104 [0.087, 0.124]	0.057	no
Y11	style	0.000 [0.000, 0.004]	0.000	no
Y18	style	0.007 [0.003, 0.014]	0.011	no

C Canary taxonomy and behavioural verification

Table 10 gives the taxonomy per run and class: implant and decoy counts, the realised SAE-corpus dose span of 3.25 to 40,000 occurrences including the 100M-token run, held-out expression and installed counts, with Wilson intervals in the notes. Behavioural verification follows the memorisation literature, where expression at a prompt is the standard read of whether a trained string took (Biderman et al. 2023a).

GPT-Neo-1.3B carries the recipe's second family check. Table 11 gives the verification per canary on 1,000 held-out prompts: four entities and one trigger install, and styles stay at natural formatting rates on both the implanted model and its twin. Table 12 runs the unchanged staged pipeline on one 65k dictionary at layer 16. Every canary has a lead at AUC above 0.99. The original gate contains 10 of 12 implants and 2 of 36 decoys, and every contained case has a nonzero cued base. The explanation stage wins lineups at the same rate for implants and decoys, 6.4% each. The pipeline's reading on the second family is the same reading as on the first.

D Limits of detection and gate status on the original grid

The original study fixed its hypotheses, thresholds and analysis before the main models were trained, in the measurement tradition of detection-capability standards (ISO 1997, CLSI 2012) and their clinical-laboratory application (Burd 2010, Armbruster & Pry 2008). Table 13 gives its limits of detection on the 1.4B grid per stage and class, in activating occurrences per 400M tokens. Containment is left-censored at the grid floor of 13 for every class at every width, with LoD50 below 13 occurrences. The design's dose ladder, sized from a pilot, sat almost entirely above the detection threshold, so the censoring bounds are the reporting form fixed in advance, and no intervention shift is measurable against them. Substituting values for nondetects would fabricate precision the grid does not have (Helsel 2006), and the zero-numerator conventions follow the rule of three and its critics (Hanley & Lippman-Hand 1983, Jovanovic & Levy 1997, Crump 1984).

Table 12. The staged pipeline on GPT-Neo-1.3B: leads, gate, explanation and certification, per class.

Stage	Set	n	Outcome
Leads, top-1 AUC above 0.99	implants	12	12 of 12, minimum 0.9990
	decoys	36	36 of 36, minimum 0.9997
Original gate, contained	implants	12	10 of 12, the 10 with a cued-base hit
	decoys	36	2 of 36, the 2 with a cued-base hit
Explanation, lineup wins per latent	implant leads	466	30, 6.4% [4.5, 9.0]
	decoy leads	950	61, 6.4% [5.0, 8.2]
Certification, primary rule	installed entities	4	2 of 4, E14 at $+0.80$ passes the screen only, E10 at -0.10 fails
	installed trigger T09	1	certifies at $+16.40$ points
	other implants	7	T19 at $+4.30$ and the style Y01 certify, T14 and T06 do not
	decoy controls	36	0 of 36, exact 95% upper bound 7.98%

Table 13. The original study's limits of detection on the 1.4B grid, per stage and class, in activating occurrences per 400M tokens. Containment limits are left-censored below the grid floor of 13.

	Contain		Explain LoD90			Surface LoD50 (shortlist)		
Class	LoD50	LoD90	16k	65k	262k	16k	65k	262k
entity	< 13	< 13	33,409	< 13	< 13	< 13	< 13	$> 40{,}000$
style	< 13	$> 40{,}000$	1,704	23	< 13	558	$> 40{,}000$	$> 40{,}000$
trigger	< 13	$> 40{,}000$	625	84	41	1,139	$> 40{,}000$	$> 40{,}000$
pooled	< 13	$> 40{,}000$	6,782	30	< 13	< 13	$> 40{,}000$	$> 40{,}000$

The stage funnel quantifies the pipeline end to end on the original grid (Figure 9): $P(\text{contain}) = 0.750$, $P(\text{explain} \mid \text{contain}) = 0.963$, $P(\text{surface} \mid \text{explain}) = 0.365$, and $P(\text{discover}) = 0.264$ over 144 implant cases with a bootstrap interval of 0.146 to 0.389. Surfacing is the bottleneck, and the funnel is flat in SAE-corpus dose, because text detection saturates: containment fires wherever held-out expression is nonzero, at expression levels as low as 0.005, about 120 times below the 0.60 installation bar. Within a run every implant is contained in all 19 dictionaries or in none, so the active dose axis is the installation dose, not the SAE-corpus dose. The rate-against-count comparison selects the rate-only model in all four width-by-replicate dictionaries, but the pooled ΔAIC is $+0.06$, so the verdict is fragile and we report it as such (Figure 10).

Table 14 gives dictionary health on the grid by width and layer against the gates fixed in advance: dead fraction, L0 and reconstruction error. Most 16k dictionaries fail on reconstruction and every 262k dictionary fails on dead fraction, 0.090 to 0.141, so the paper's width claims are checked on the dictionaries that pass, and the 262k reads carry that selection. The health picture matches the wider report that large SAEs trade reconstruction for scale (Templeton et al. 2024).

E THRESHOLD MODEL, CERTIFICATION AND CONTROL TABLES

This appendix collects the control tables behind Section 3.2 and its figures. Table 15 holds the blank controls on the original gate over 87 dose points of eight dictionaries at both Pythia scales and on GPT-Neo-1.3B (Figure 3). Table 16 holds the steering-scale sweep per class, and Table 17 the joint ablation of the ten best or all leads. Table 18 holds the blank controls on certification. Tables 19, 20 and 21 hold the predictor comparison, the trace-band dose points under the zero-parameter model, and the 25 verdicts of the higher-budget run. Tables 22 and 23 hold the certification rates by class and the half-scale follow-up. Table 24 holds lineup identification with and without literal quoting of the nonce.

Figure 11 shows the threshold in expression space and its movement with the budget. The 410M ladder brackets the switch between 0.35% and 0.65% held-out expression at $n = 200$, and re-gating seven trace-band dose points at $n = 2{,}000$ flips five of six, with the sixth staying uncontained at zero hits. The one trace point contained under the original gate was a one-hit artefact: with a single hit in the sample, any perturbation that flips it scores an effect of one, and 89 of 91 tested latents passed. The threshold's sharpness is hit-count crossing and its location is $1/n$, which is the whole



Figure 9. The stage funnel on the original grid, at the 65k layer-16 reference dictionaries, by SAE-corpus dose tier. (a) Cumulative discovery probability with each stage's loss shaded. (b) Conditional stage rates with Wilson intervals. Discovery is 0.264 over 144 implant cases, and the funnel is flat in dose.



Figure 10. Containment against measured occurrence count and against occurrences per token, for the 400M-token and 100M-token SAE-corpus runs, with single-term logistic fits. The rate-only model has the lower AIC in all four dictionaries, but the pooled difference is $+0.06$, so the verdict is fragile.

of the mechanism. Figure 12 makes the same point per latent: with no hit nothing passes, and one hit is enough for most latents to pass.

F AUDITOR WAVES, CONVENTIONS, CHECKS AND THE PROGRAMME SCHEMATIC

Table 25 gives every wave and policy scale: AUROC with intervals, per class, crashes, and the paired contrast against the baseline wave. Table 26 gives the end-to-end operating characteristic at the 0.5 shortlist threshold, with crashed dictionaries excluded, since a crash lists nothing and would flatter the false-alarm rate. Its counts of dictionaries scored are that analysis's committed snapshot of the waves, so they need not equal 36 minus the crash counts of Table 25. The AUROC column is the declared convention, and the two tables agree on it. Table 27 is the multiplicity family:

Table 14. Dictionary health on the grid by width and layer: dead fraction, L0 and reconstruction error against the gates fixed in advance. Most 16k and all 262k dictionaries fail.

Width	Dictionaries	Pass	Fail (FVU)	Fail (dead)	FVU range	Dead range
16,384	12	4	8	0	0.129 to 0.177	0.000 to 0.003
65,536	16	15	1	0	0.098 to 0.151	0.007 to 0.050
262,144	8	0	0	8	0.082 to 0.118	0.090 to 0.141



Figure 11. The measurement-budget threshold. (a) The 410M ladder: containment against held-out expression, with entities contained at every dose and trigger containment switching on between 0.35% and 0.65%. (b) Seven trace-band dose points re-gated at $n = 2{,}000$. The switch brackets the one-hit point of 0.35% at $n = 200$, and five of six uncontained points flip at $n = 2{,}000$.

twelve wave contrasts with Holm adjustment, one-sided and two-sided. One contrast survives, the 64k window, and only one-sided. Table 28 holds the explanation stage against a max-over-latents null and its decoy control. Table 29 holds the regression-to-the-mean checks on the trigger-class contrasts. Tables 30 and 31 hold the original auditor's discrimination by width and the decoder-cosine baseline for persistence.

Three checks support the wave scores. Dropping crashed dictionaries instead of filling them at chance changes no wave's AUROC by more than 0.0015, over the 36 expected grid dictionaries. Tie-safe rescoring of every contrast leaves the family of conclusions unchanged. And the crash mechanism is mundane: every crash is a context-window failure at exactly window plus one token, and runaway trajectories are repetition cascades in the tool logs, as Figure 15 shows. Context rot of this kind is a known long-horizon failure of agents (Xia et al. 2026).

G Rules and the data they govern

Table 32 shows, for each rules-first analysis, when its rule was committed and when its data first existed, each with its source. The times come from git commits, the cluster's git reflog, Slurm accounting and the cluster run ledger, and the table's notes state the limits of each clock. The original study's plan and its two dated amendments come first. Twenty-one analyses re-use data that already existed when their rules were written, and the table's verdict column says which.

Table 32. For each analysis, the commit and time its rule was fixed, when its data first existed, and the source of the first-data time.

Analysis	Rule commit		First data	Source of first-data time
1, clean 131k wave	`7b13dee`	2026-08-31 01.05.20	2026-08-31 01.06.06	sacct submit, job 120828
2, forced wave with dedup guard	`7b13dee`	2026-08-31 01.05.20	2026-08-31 01.06.06	sacct submit, job 120829
3, variant B wave	`7b13dee`	2026-08-31 01.05.20	2026-08-31 01.06.06	sacct submit, job 120830
4, expanded certification controls	`7b13dee`	2026-08-31 01.05.20	2026-08-31 01.06.06	sacct submit, job 120832
5, second lineup judge	`7b13dee`	2026-08-31 01.05.20	2026-08-31 01.06.06	sacct submit, job 120831
6, scaffold scan queue	`9224c18`	2026-09-01 21.23.58	2026-09-01 21.24.17	sacct submit, job 123586
7, eval-set scan queue	`609ccf1`	2026-09-02 12.46.10	2026-09-02 12.46.19	sacct submit, job 123728

Table 32, continued from the previous page.

Analysis	Rule commit		First data	Source of first-data time
8, 72B at 32k and the 32B wave	55fa6b7 19.17.27	2026-09-03	2026-09-03 20.06.21	sacct submit, job 124871
8b, 72B at 64k	41a96f7 20.39.17	2026-09-03	2026-09-03 20.39.28	sacct submit, job 124965
8c, 72B capped at 30	9c50234 20.57.22	2026-09-03	2026-09-03 20.58.04	sacct submit, job 125106
9, re-gating at higher budgets	55fa6b7 19.17.27	2026-09-03	2026-09-03 19.18.51	sacct submit, job 124845
10, decoder-cosine baseline	55fa6b7 19.17.27	2026-09-03	2026-09-03 19.18.51	sacct submit, job 124857
11, second steering scale	55fa6b7 19.17.27	2026-09-03	2026-09-03 19.18.51	sacct submit, job 124855
12a, Llama-3-8B with YaRN, withdrawn	bb4908b 19.26.49	2026-09-04	2026-09-04 19.27.35	sacct submit, job 125543. Withdrawn at 1070742 after its output
12a′, Llama-3-8B at native 8k	1070742 20.02.06	2026-09-04	2026-09-04 20.02.12	sacct submit, job 125615
12b, Qwen2.5-7B wave	bb4908b 19.26.49	2026-09-04	2026-09-04 19.27.35	sacct submit, job 125544
13, black-box arm scored	bb4908b 19.26.49	2026-09-04	2026-08-12 13.05.04	sacct submit, jobs 87157 and 87158. Scored at f6fda51 2026-09-04 19.34.03
14, explanation null and decoy control	bb4908b 19.26.49	2026-09-04	by 2026-08-21 18.37.40	results banked at aa3b4a1. First output f6fda51 2026-09-04 19.34.03
15, reconciling the 0.025% floor	bb4908b 19.26.49	2026-09-04	2026-09-04 15.06.24	sacct start, analysis 9 job 124850. Read at cc0b412 2026-09-04 18.29.41
16, end-to-end operating characteristic	bb4908b 19.26.49	2026-09-04	2026-08-10 21.19.20	sacct submit, first auditor wave job 86212. First output 07ce60a 2026-09-04 19.37.12
17, multiplicity over the wave family	bb4908b 19.26.49	2026-09-04	2026-08-10 21.19.20	sacct submit, first auditor wave job 86212. First output 07ce60a 2026-09-04 19.37.12
18, gate specificity controls	c2def49 03.16.48, stub c32c3a0 2026-09-04 22.41.44	2026-09-05	2026-09-05 13.31.56	sacct submit, job 125755
18b, induction specificity controls	a27efad 14.07.35	2026-09-05	2026-09-05 16.37.33	sacct submit, job 125823
19, cued-query baseline	c2def49 03.16.48	2026-09-05	2026-07-24 11.43.58	sacct submit, verification job 72951. First output e37bba2 2026-09-05 14.32.49
20, GPT-Neo-1.3B family	c2def49 03.16.48	2026-09-05	2026-09-05 13.30.02	sacct submit, job 125753
21, Mistral-Small-24B wave	c2def49 03.16.48	2026-09-05	2026-09-05 13.31.56	sacct submit, job 125754
24, cluster-level explanation statistics	c2def49 03.16.48	2026-09-05	by 2026-08-21 18.37.40	results banked at aa3b4a1. First output 9479dc0 2026-09-05 18.22.14
25, decomposed sensitivity model	c2def49 03.16.48	2026-09-05	by 2026-09-04 18.29.41	verdicts read at cc0b412. First output 9c4b67f 2026-09-05 18.00.25
26, out-of-sample budget test	d42a811 18.26.15, gloss corrected at 528c121	2026-09-05	2026-09-05 18.26.42	sacct submit, job 125835
27, steering-scale sweep	544ee63 17.09.26	2026-09-12	2026-09-13 13.55.25	sacct submit, job 129696
28, joint ablation	44aee85 22.26.39	2026-09-13	2026-09-13 22.26.49	sacct submit, job 130005
29, clean-pair difference dictionary	ca1f161 16.02.28	2026-09-14	2026-09-14 16.02.47	sacct submit, job 130410
30, joint ablation at layer 8 and at replicate B	ca1f161 16.02.28	2026-09-14	2026-09-14 16.02.47	sacct submit, jobs 130412 and 130413
31, dictionary-free difference null	e506e90 15.25.38	2026-09-15	2026-09-15 15.25.48	sacct submit, job 131168
32, twin-free difference dictionary	e506e90 15.25.38	2026-09-15	2026-09-15 15.25.48	sacct submit, job 131166
33, diffing dictionaries at one learning rate	e1b87bd 13.52.18	2026-09-16	2026-09-16 13.52.42	sacct submit, jobs 132036 and 132037
34, what the difference channel reads	e65f0ac 14.44.03	2026-09-16	by 2026-09-15 15.47.56	analysis 31's output, job 131168. First output c8f7d89 2026-09-16 14.46.14
35, single-model exposure probe	e65f0ac 14.44.03	2026-09-16	2026-09-16 14.45.55	sacct submit, job 132220
36, containment under ablation alone	8c8dcca 23.01.29	2026-09-16	by 2026-08-12	the grid's causal rows. First output 92378ef 2026-09-16 23.06.27
37, cue sweep paired per run	8c8dcca 23.01.29	2026-09-16	by 2026-09-05	analysis 19's counts and the waves. First output 8cb4596 2026-09-16 23.09.18, after the correction its docstring records
38, exposure probe on latent activations	8c8dcca 23.01.29	2026-09-16	2026-09-16 23.01.38	sacct submit, job 132482
39, dose against the difference norm	8c8dcca 23.01.29	2026-09-16	by 2026-09-15 15.47.56	analysis 31's output. First output 92378ef 2026-09-16 23.06.27
40, latent probe on the residual probe's protocol	129fee3 00.33.31	2026-09-17	2026-09-17 00.33.40	sacct submit, job 132502
41, loss ratio against the reference model	0fdca48 20.26.12	2026-09-17	2026-09-17 20.26.21	sacct submit, job 133875
42, dose-response of the reference-model signals at 410M	0fdca48 20.26.12	2026-09-17	2026-09-17 20.26.21	sacct submit, job 133876
42b, the same dose sweep at 1.4B	eba11af 20.43.50	2026-09-17	2026-09-17 20.44.43	sacct submit, job 133881. Analysis 31's output already held the difference norm for these canaries, and one such value was seen before the rule was written
43, limits of detection under ablation alone	0fdca48 20.26.12	2026-09-17	by 2026-08-12	the grid's causal rows and dose table. First output 036ff3e 2026-09-17 20.33.41, job 133878
44, installed-only sweep comparison, paired	0fdca48 20.26.12	2026-09-17	by 2026-09-05	analysis 19's counts and the waves. First output 1aaccb6 2026-09-17 20.40.30, after the correction its docstring records
45, leads selected by a model contrast	0fdca48 20.26.12	2026-09-17	2026-09-17 20.49.10	sacct submit, job 133882
58, agent comparison with crashes dropped	693bc87 01.34.08	2026-09-21	by 2026-09-05	the recorded auditor waves
59, is the clean twin a blank	693bc87 01.34.08	2026-09-21	by 2026-09-17	analysis 41 output, read before the rule, post-hoc
60, was the pooled joint-ablation test entitled to pool	a828b1c 15.19.52	2026-09-21	by 2026-09-14	the joint-ablation verdicts, read before the rule, post-hoc

Table 32, continued from the previous page.

Analysis	Rule commit		First data	Source of first-data time
46, matched non-lexicalized canary arm at 410M	`3509dd9` 00.44.40	2026-09-18	2026-09-18 01.32.00	sacct submit, job 133910
47, exposure signal with no rare string	`3509dd9` 00.44.40	2026-09-18	2026-09-18 01.32.00	sacct submit, job 133910
49, reference model with no corpus relationship	`3509dd9` 00.44.40	2026-09-18	2026-09-18 01.13.03	sacct submit, job 133909
52, run-to-run variance of installation	`f73847a` 15.11.32	2026-09-18	2026-09-18 22.52.16	sacct submit, job 134468
57, the non-lexicalized arm at twice the dose	`8c99f18` 15.06.05	2026-09-20	2026-09-20 15.07.14	sacct submit, job 135390
Installation ladder, design note	`2bf0281` 12.09.22	2026-08-26	2026-08-26 12.09.45	sacct submit, job 117698

H THE DIFFING SKYLINE AND THE WAVES SCORED PER RUN

This appendix collects the reference-model results and their checks. Table 33 holds the two diffing dictionaries beside matched single-model dictionaries, with the floor, twin-free and first-attempt dictionaries in the lower block. Table 34 holds the dictionary-free difference norm per pair and the clean-pair floor. Table 35 holds installed against uninstalled among implants per score, with class as a confound in v1. Table 36 holds the linear probe inside one model with whole canaries held out.

H.1 FURTHER CHECKS ON THE REFERENCE MODEL

Table 37 puts the loss ratio beside the difference norm and the single-model loss per pair, with floors. The twin-blank check reads the floor directly. On the single-model loss the twin sits at chance, 0.484 and 0.510 on the two statistics, as does the public base. The twin is a blank. The floor's excursion below 0.5 has no established cause. It is consistent with the twin's replacement documents leaving their own trace, since against a deduplicated Pythia the floor is 0.521, at chance. A near-chance separation is therefore read against the measured floor and its interval, not against 0.500, and the implanted pair's 1.000 sits far outside the floor's range. Against a deduplicated Pythia, a reference model that never saw our canary or replacement documents, both 1.4B runs separate at 1.000 with the floor at 0.521, and the 410M read, rescored with corrected labels against the 410M model's own implants, reads 1.000 with the floor at 0.500. Read as an installation detector among v1's implants, the loss ratio separates installed from exposed-but-uninstalled canaries at 0.297 (95% 0.100 to 0.524), with class as a confound, since every installed implant in v1 is an entity (Table 35).

Table 38 holds the dose sweep behind Figure 5: each sweep canary's AUC for the norm and the loss ratio in the 410M dose-sweep model, v1 and v2, with the largest blank per column. Table 39 holds both signals on the 410M ladder per model: separation of the 12 implants against the other 36 canaries, detections, and sweep canaries detected per dose. The loss ratio detects from 40 occurrences everywhere and from 10 in v2. The difference norm needs 160 occurrences in v1 and 640 in v2, and never clears the blanks at 410M.

Table 40 holds leads chosen by a contrast between models inside one dictionary, against the twin and the base, with the clean-pair floor. Tables 41 and 42 restate containment and the original limits of detection under the ablation test alone. Tables 43, 44 and 45 score the cue sweep against the waves: paired per run on a canary bootstrap, restricted to installed implants, and under each wave's own pooled convention beside v1 alone and v2 alone.

H.2 A CANARY WITH NO MADE-UP WORD

The matched run asks whether a canary needs its rare string. Five canaries keep their made-up name and five have every made-up word removed, with the association carried by a common cue spread over 18 ordinary surface forms, probed with a form held out of every document. Every part of a non-lexicalized canary is ordinary: its cue occurs 725 to 4,801 times in a 2.22-billion-character corpus sample, its place 0 to 240 times and its detail 27 to 1,505 (Table 48). What does not occur is the particular referring expression, at most once, so the run removes the rare word and not the rare combination.

At 12,000 occurrences the lexicalized five install 5 of 5 at mean expression 0.737, and the non-lexicalized five install 0 of 5 at mean expression 0.389, against the published bar and against the blank alike (Table 47). At 24,000 occurrences the non-lexicalized five still install 0 of 5 (Table 46).



Figure 12. The verdict is a step at the first hit. For seven trace-level trigger implants re-gated at higher budgets, the share of their leads that pass against the number of hits in the cued sample.

Table 15. Blank controls on the original gate: steering and ablation pass rates for the canary's own latents and four blank families, per class, over 87 dose points of eight dictionaries.

Family	entity		trigger		style	
	steer	ablate	steer	ablate	steer	ablate
tested (the canary's own passing latents)	99.2	0	98.2	7.0	100	7.1
other canaries' passing latents	98.6	0	98.7	0	89.2	0
random dictionary latents	99.8	0	100	0	87.9	0
random residual directions	99.8	n/a	100	n/a	90.5	n/a
untrained random-dictionary latents	38.0	0	46.3	1.1	39.3	0
(dose point, latent) pairs	2,824	2,024	1,456	1,076	2,000	1,440
branch, steering test	degradation detector		degradation detector		degradation detector	
branch, ablation test	not applicable, tested is 0		partially specific		specific	

The doubled dose had to move the documents from the pretraining role to the SAE-corpus role, so the run cannot separate the dose from the role, and every comparison at 24,000 carries that caveat. The anchor's worth, the expression gap between the matched sides, is about 0.35 at 12,000 occurrences and 0.23 at 24,000.

I Related work

Canaries and memorisation. The canary idea comes from memorisation testing, where a secret string is planted in training and its extraction measures unintended memorisation (Carlini et al. 2019; 2021). Memorisation grows with scale and repetition in predictable ways (Biderman et al. 2023a), and planted strings serve as copyright traps and as watermarks of training membership (Meeus et al. 2024, Wei et al. 2024). Behavioural canaries audit whether a private retrieved context was used in reinforcement fine-tuning (Chen et al. 2026), and ensembled adversarial queries sharpen canary-based membership inference (Wen et al. 2023). Knowledge-storage work localises where facts sit in a model (Allen-Zhu & Li 2024). Our use is different in kind. The canaries serve as the measuring instrument rather than the object of study, planted at known strengths to read an audit pipeline's sensitivity.

Auditing benchmarks and agents. Alignment audits are scored on model organisms with hidden objectives (Marks et al. 2025), on benchmark suites of hidden behaviours (Sheshadri et al. 2026), and through scaffolding agents that inspect dictionaries and query the model (Bricken et al. 2025). Introspection adapters train the model to report its own learned behaviours (Shenoy et al. 2026). Agents built for interpretability show promise and show failure modes in evaluation design (Marin-Llobet & Ferrando 2026, Haklay et al. 2026), and agent failures cluster in tool use, planning and

Table 16. The steering-scale sweep per class at -0.5, -1, -2 and -5 times mean activation: per-latent and any-latent pass rates for tested latents and blanks, mean held-out loss change, and the branch reading.

		pass rate per latent					any latent				
class	scale	tested	other	rand. lat.	rand. dir.	rand. dict.	tested	other	rand. dir.	NLL	branch
entity	$-0.5\times$	4.2	0.9	0.3	0.3	0.0	12.5	18.8	6.2	+1.4	weak
entity	$-1.0\times$	31.2	30.3	24.4	19.1	0.0	62.5	100.0	37.5	+6.7	weak†
entity	$-2.0\times$	75.0	80.3	82.8	77.5	0.0	100.0	100.0	93.8	+30.7	not specific†
entity	$-5.0\times$	100.0	98.8	100.0	100.0	33.8	100.0	100.0	100.0	+142.8	not specific†
trigger	$-0.5\times$	33.3	51.1	45.0	42.0	4.0	60.0	100.0	100.0	+1.6	weak
trigger	$-1.0\times$	86.7	73.9	76.0	74.0	20.0	100.0	100.0	100.0	+7.5	not specific†
trigger	$-2.0\times$	100.0	96.7	96.0	93.0	40.0	100.0	100.0	100.0	+31.4	not specific†
trigger	$-5.0\times$	100.0	100.0	100.0	100.0	72.0	100.0	100.0	100.0	+158.7	not specific†
style	$-0.5\times$	23.3	14.1	19.5	18.0	0.0	40.0	70.0	80.0	+1.4	weak
style	$-1.0\times$	33.3	26.6	35.0	32.0	8.0	60.0	100.0	100.0	+6.3	weak†
style	$-2.0\times$	46.7	57.8	52.0	47.5	26.0	80.0	100.0	100.0	+32.2	weak†
style	$-5.0\times$	100.0	91.7	88.5	90.5	44.0	100.0	100.0	100.0	+135.5	not specific†

Table 17. Joint ablation of the ten best or all leads per class: dose points, latents removed, tested and blank pass rates, loss change, and the branch.

class	set	points	latents removed	tested	other	random	NLL	branch
entity	top ten	16	10, 10 to 10	6.2	0.0	0.0	+0.0	weak
entity	all	16	34, 12 to 56	43.8	0.0	0.0	+0.2	weak
trigger	top ten	5	10, 10 to 10	40.0	0.0	0.0	+0.0	weak
trigger	all	5	62, 24 to 68	80.0	20.0	0.0	+0.2	partial
style	top ten	10	10, 10 to 10	10.0	10.0	10.0	+0.0	weak
style	all	10	28.5, 13 to 40	10.0	0.0	0.0	+0.3	weak

long-horizon context management (Albayaydh et al. 2026, Xia et al. 2026). On the poisoning side, detection of poisoned models is an active target, with dose results that frame our sweep (Hughes et al. 2026, Bowen et al. 2024, Souly et al. 2025). These benchmarks score agents at one strength of planting each. Our testbed varies the strength, which is what turns a hit rate into a limit of detection.

Sparse autoencoders and their evaluation. SAEs decompose activations into interpretable latents (Bricken et al. 2023, Huben et al. 2024), scale to frontier models (Templeton et al. 2024, Gao et al. 2025), and come in BatchTopK and Matryoshka variants (Bussmann et al. 2024; 2025). Evaluation suites measure recovery on synthetic data and on board-game models, feature sensitivity, and embedding analysis (Chanin & Garriga-Alonso 2026, Karvonen et al. 2024; 2025, Jiang et al. 2026, Tian et al. 2025). Feature splitting and absorption complicate the picture (Chanin et al. 2025), SAEs do not find canonical units, and dictionaries trained on the same data learn different features (Leask et al. 2025, Paulo & Belrose 2025). Sanity checks ask whether SAEs beat random baselines at all, with uncomfortable answers (Korznikov et al. 2026, Heap et al. 2025), and one explanation can describe many features (McCann 2026). On downstream use, simple baselines beat SAEs on steering and match them on probing (Wu et al. 2025, Kantamneni et al. 2025). What none of these evaluations carries is a sensitivity curve against planted behaviour, which is the gap this paper fills.

Steering and editing. Activation edits localise and change factual associations (Meng et al. 2022, Geva et al. 2023), with best practices for patching metrics (Zhang & Nanda 2024). Steering vectors generalise unevenly, steering strength has its own structure, and many behaviours resist activation control (Tan et al. 2024, Taimeskhanov et al. 2026, Bas & Novak 2025). Our gate results add a specificity reading to this literature: an intervention strong enough to move a behaviour can be too destructive to attribute it.

Model diffing. Activation differences between a fine-tuned model and its base reveal backdoors and narrow fine-tuning, through SAE architectures, crosscoders, and direct norm comparisons (Kumar 2026, Kassem et al. 2026, Minder et al. 2026). Our difference channel is the same family, read as a measurement instrument with floors rather than as a detector.

Membership inference and privacy auditing. Membership inference separates training members from non-members by loss, from first principles and from shadow-model schemes (Carlini et al.

Table 18. Blank controls on certification: per-latent and any-latent certification rates for the tested latent and three blank families, per class.

Family	entity		trigger		style	
	per latent	any latent	per latent	any latent	per latent	any latent
tested (the canary's best latent)	50.0	50.0	50.0	50.0	16.7	16.7
other canaries' latents	11.4	75.0	12.1	58.3	3.0	25.0
random dictionary latents	6.7	50.0	1.7	16.7	8.3	41.7
random residual directions	3.3	25.0	10.0	33.3	4.2	41.7
untrained random-dictionary latents	8.3	33.3	5.0	16.7	5.0	25.0
branch, any-latent convention	non-specific		non-specific		non-specific	

Table 19. Six predictors of the gate's verdict scored by log-likelihood per budget stratum, parameter-free except the per-stratum constant.

Predictor	n=200	n=2,000	n=20,000	pooled	hits inside
(i) first form, pooled expression with the floor	−6.0	−7.7	−55.0	−68.7	22 of 32
(ii) greedy point estimate with the same floor	−4.9	−8.0	−40.0	−53.0	
(iii) Jeffreys predictive on greedy counts	−4.9	−8.5	−12.7	−26.1	32 of 32
(iv) empirical-Bayes predictive	−5.3	−9.9	−6.8	−22.0	32 of 32
(v) per-template Jeffreys predictive	−18.8	−66.9	−189.5	−275.1	
(vi) constant rate per stratum	−12.2	−13.5	−7.6	−33.3	

2022, Shi et al. 2024, Wen et al. 2023). Knowledge-awareness probes ask whether a model knows an entity (Ferrando et al. 2025). Privacy auditing plants canaries to estimate the privacy loss of a training algorithm, sometimes from one training run (Jagielski et al. 2020, Steinke et al. 2023), and perplexity differencing reveals fine-tuning objectives in leaked model organisms (Abu Baker et al. 2026). Our reference-model comparison is membership inference used as a yardstick: it sets the sensitivity the audit pipeline would have to beat.

Limits of detection. The statistics of detection capability run from Currie's radiochemistry limits through the ISO and CLSI standards to their clinical-laboratory application (Currie 1968, ISO 1997, CLSI 2012) and their clinical-laboratory application (Burd 2010, Armbruster & Pry 2008). Non-detects must not be silently substituted (Helsel 2006), zero numerators have their own conventions (Hanley & Lippman-Hand 1983, Jovanovic & Levy 1997, Crump 1984), and rare-event estimation in language models faces the same economics (Wu & Hilton 2024, Wang 2026). Decoy-calibrated failure audits share our use of samples known to carry nothing (Repantis et al. 2026). Eyewitness-lineup statistics inform our explanation stage's 48-way lineup (Wixted et al. 2016), and capability benchmarks frame what the audited models can do (Srivastava et al. 2023).

J What changes with width

Width moves the pipeline's stages in opposite directions, and Figure 16 shows all three moves. Canary features persist as the dictionary grows. Decoder-cosine matching of implant leads gives a mean best cosine of 0.87 across the seed pair and 0.84 across the width pair from 65k to 262k. The nearest neighbour is a same-canary lead 52 to 74% of the time (Table 31). There is no splitting signature, since the 262k dictionaries carry fewer passing latents per implant than the 65k ones. Explanations sharpen with width. The share of explanations that literally quote the canary's nonce rises from 12.5% to 20.8% for entities and from 9.7% to 19.9% for styles across 16k, 65k and 262k. Quoting is what wins lineups, 82% correct against 12% without (Table 24). Trigger latents fire on context rather than on the phrase, so their explanations describe the scenario and quote almost nothing, 0.9% to 5.4% across widths.

Surfacing collapses with width. The original auditor's listing rates fall for implants and decoys alike as width grows (Table 30). Almost every agent miss is a latent it never inspected. Among the misses of the original wave, one is a recognition failure, and the rest are exploration failures. Canary latents sit at mid-tail positions in the overview tool's fire-rate ordering, median percentile 0.47, 0.30 and 0.13 at 16k, 65k and 262k, so neither a common-first nor a rare-first ordering brings them within budget. The pipeline's failure at width is a search problem sitting on a representation that is getting better. Judge models bring their own biases to any of these reads, from self-preference to position

Table 20. The seven trace-band dose points under the zero-parameter model: expression, verdicts at $n = 200$ and $n = 2{,}000$, hits and passing latents.

Dictionary and canary	Expression	P_{200}	Frozen verdict (n=200)	P_{2000}	Base hits	Latents passing
lad2 T14	0.025%	0.05	contained (1 hit in 200)	0.39	1	89 of 91
lad2 T19	0.15%	0.26	uncontained	0.95	2	75 of 80
lad3 T09	0.2%	0.33	uncontained	0.98	5	58 of 71
lad3 T14	0.35%	0.50	uncontained	1.00	2	70 of 76
lad4 T06	0.1%	0.18	uncontained	0.86	0	0 of 51
p8 T14	0.125%	0.22	uncontained	0.92	4	80 of 82
p8 T09	0.10%	0.18	uncontained	0.86	1	56 of 68

Table 21. The 25 verdicts of the higher-budget run at $n = 2{,}000$ and $n = 20{,}000$ against the model's predicted probability.

n	Dictionary and canary	Expression	P	Base hits	Latents passing	Verdict
2,000	lad1 T06	0.000%	0.39	0	0 of 53	uncontained
2,000	lad1 T09	0.000%	0.39	0	0 of 55	uncontained
2,000	lad1 T14	0.000%	0.39	0	0 of 78	uncontained
2,000	lad1 T19	0.000%	0.39	1	80 of 84	contained
2,000	lad2 T06	0.000%	0.39	0	0 of 49	uncontained
2,000	lad2 T09	0.000%	0.39	0	0 of 68	uncontained
2,000	lad3 T06	0.000%	0.39	0	0 of 53	uncontained
2,000	p8 T06	0.025%	0.39	0	0 of 50	uncontained
2,000	lad4 T14	0.650%	1.00	14	63 of 73	contained
2,000	p8 T19	1.000%	1.00	19	78 of 85	contained
2,000	lad3 T19	1.350%	1.00	25	77 of 90	contained
2,000	lad4 T09	1.600%	1.00	35	49 of 67	contained
2,000	lad4 T19	2.800%	1.00	54	64 of 80	contained
20,000	lad1 T06	0.000%	0.99	0	0 of 1	uncontained
20,000	lad1 T09	0.000%	0.99	0	0 of 1	uncontained
20,000	lad1 T14	0.000%	0.99	0	0 of 1	uncontained
20,000	lad1 T19	0.000%	0.99	6	1 of 1	contained
20,000	lad2 T06	0.000%	0.99	0	0 of 1	uncontained
20,000	lad2 T09	0.000%	0.99	0	0 of 1	uncontained
20,000	lad3 T06	0.000%	0.99	0	0 of 1	uncontained
20,000	lad2 T14	0.025%	0.99	18	1 of 1	contained
20,000	p8 T06	0.025%	0.99	0	0 of 1	uncontained
20,000	lad4 T06	0.100%	1.00	0	0 of 1	uncontained
20,000	p8 T09	0.100%	1.00	11	1 of 1	contained
20,000	p8 T14	0.125%	1.00	24	1 of 1	contained

effects, which is why the lineup is scored by identification rather than by rated quality (Zheng et al. 2023, Panickssery et al. 2024, Thakur et al. 2025).

K CERTIFICATION IN FULL

Certification inverts the gate's estimand. Instead of asking whether suppressing a latent removes a behaviour, it asks whether injecting a latent writes the behaviour, on the implanted model and on its twin, with the patching literature's cautions about metric choice in mind (Zhang & Nanda 2024, Tan et al. 2024). A dose point certifies when steering its best latent up at the calibrated scale raises cued expression by at least one point on the implanted model and at most 0.2 points on the twin, over 2,000 cued prompts per side.

The scale was calibrated before the full run, on positive controls, and the calibration is disclosed as such. At five times mean activation the injection is off-distribution and destructive. Nothing certifies, and every entity implant shows negative induction, with even a 0.84 base expression suppressed. At twice mean activation most entities collapse. At one times, entities certify 4 of 4 on the calibration dictionary, a trace-level trigger certifies with the twin at exactly zero, and every control stays at zero. The destructive transition sits between one and two for most canaries, an inverted-U that any deployment of this estimand must respect.

The full run at the calibrated scale certifies every trigger point at or above 0.35% held-out expression, 6 of 6, including two points the original $n = 200$ gate called uncontained. The 0.10 to 0.20% band certifies under the sensitivity rule, and nothing at or below 0.125% certifies, 0 of 12. One trace point shows real sub-threshold amplification, four times its base rate with the twin at zero, without

Table 22. Certification rates by class, with the entity rate split by calibration and held-out dictionaries, and the control rates with exact upper bounds.

Set	Class	Certified	95% interval
implants	entity, all dictionaries	14 of 20	48.1 to 85.5% (Wilson)
implants	entity, calibration dictionary (p8)	4 of 4	51.0 to 100% (Wilson)
implants	entity, four held-out dictionaries	10 of 16	38.6 to 81.5% (Wilson)
implants	trigger	6 of 20	14.6 to 51.9% (Wilson)
implants	trigger, expression $\geq 0.35\%$	6 of 6	61.0 to 100% (Wilson)
implants	trigger, expression $\leq 0.125\%$	0 of 12	upper 22.1% (exact)
implants	style (excluded)	1 of 15	1.2 to 29.8% (Wilson)
controls	decoys, primary set plus Y11	0 of 20	upper 13.9% (exact)
controls	decoys, expanded set	0 of 105	upper 2.8% (exact)
controls	all decoy cases	0 of 120	upper 2.47% (exact)
controls	all control cases incl. Y11	0 of 125	upper 2.37% (exact)

Table 23. Certification at half the calibrated scale on the dictionary whose entities all failed at the calibrated scale.

Canary	Best latent	Cued base	Induction implanted	Induction twin	Certified	Sensitivity
E10	24075	0.805	$+0.40$	$+0.00$	no	no
E14	38343	0.625	-0.15	$+0.00$	no	no
E15	24146	0.800	$+2.20$	$+0.00$	yes	yes
E18	41764	0.624	$+0.80$	$+0.00$	no	yes

reaching the rule, so the representation threshold is genuinely low and bounded. Entities certify 14 of 20, with failures concentrated where the single global scale over-drives the strongest installs, and the half-scale follow-up of Table 23 recovers one of those four, weakening but not removing the over-drive account. Styles are excluded from certification claims by a binding ruling: steering style latents writes the formatting into any model, twin included, with twin inductions up to 11%, so the class is direction-contaminated. Zero numerators on the control side follow the conventions of Appendix D (Hanley & Lippman-Hand 1983, Wu & Hilton 2024, Wang 2026).

Conventions and controls. No control ever certified: 0 of 20 in the calibration programme and 0 of 125 in the full control set (Table 22, Figure 13). The rules fixed the any-latent convention, under which a dose point certifies when any of its latents certifies. Under that convention blanks certify as readily as the canary's latent, and attribution under it was withdrawn. The per-latent reading is a convention the rules did not name, and we give it as such: the canary's latent certifies at 50% against at most 12.1% for any blank family (Table 18).

L THE AUDITOR PROGRAMME IN FULL

The programme began with the original wave: variant A scaffold, Qwen2.5-14B, 32k context, 1,000 inspections and 200 model queries per dictionary. Three of its 36 dictionaries crashed at exactly 32,769 input tokens, one past the window, and clean trajectories used under 6% of the query budget. Doubling the window to 64k raised wave AUROC from 0.535 to 0.735 and still crashed 4 of 36 dictionaries at 65,537 tokens, one past the new window. Forcing coverage, with the final answer refused until 100 latent inspections, lengthened trajectories past any window: 9 of 36 dictionaries crashed at 131k, one clean dictionary ran 915 turns and spent its entire inspection allowance, and the wave's AUROC fell to 0.610. A duplicate-call guard, a variant B scaffold and two queue variants followed, then five stronger-policy waves from 7B to 72B, whose scores sit between 0.508 and 0.678 pooled (Table 25). A fourteenth wave on Mistral-Small-24B returned no verdict, since all 36 dictionaries crashed at its window.

The mechanism chain closed in three post-hoc reads. First, the surfacing bottleneck is search, not judgment. Classifying every miss by whether any of the canary's leads was ever inspected, recognition failures are nearly absent. The original wave has 1 and the 64k wave has 8 out of about 450 to 520 misses per wave. When the auditor looks at a canary latent, it flags the canary. Second, undi-

Table 24. Lineup identification with and without literal quoting of the nonce, over 18,767 implant leads.

Judge	Class	Latents	Quoting	Correct, quoting	Correct, not quoting	Correct from non-quoting
Qwen2.5-14B	entity	5,809	16.0%	82.7%	9.1%	37%
Qwen2.5-14B	style	4,673	14.4%	79.4%	10.1%	43%
Qwen2.5-14B	trigger	8,285	2.5%	89.6%	14.4%	86%
Qwen2.5-14B	all	18,767	9.7%	82.3%	11.9%	57%
Llama-3-8B	entity	5,809	16.0%	65.2%	4.4%	26%
Llama-3-8B	style	4,673	14.4%	87.7%	6.0%	29%
Llama-3-8B	trigger	8,285	2.5%	90.5%	9.7%	80%
Llama-3-8B	all	18,767	9.7%	76.5%	7.3%	47%



Figure 13. Certification at the calibrated scale. (a) Triggers, (b) entities and (c) all 125 control cases, as implanted induction against twin induction, with the certification region marked. Triggers certify at every point at or above 0.35% and none at or below 0.125%. Entities certify at 14 of 20, and no control certifies.

rected coverage cannot fix search: 100 mandated inspections cover 0.04 to 0.6% of a 16k to 262k dictionary, and canary latents sit at mid-tail positions in every ordering the agent can see, about 20,000th at 65k against 100 voluntary inspections. Third, context appetite is unbounded at these scales, since every window increase was consumed and the crash signature stayed at window plus one token, the context-rot pattern of long-horizon agents (Xia et al. 2026). The prescriptive form of the finding is that surfacing needs query-conditioned scanning, which is what the containment stage's evaluation sets already provide and what a blind auditor by definition lacks.

M Study conduct

This paper corrects six silent analysis faults, each found by a sanity check and each labelled correction where its result appears. First, the original auditor table was produced by a fallback path. The analysis job was not passed the audit scores, so the printed AUROC of 0.708 quoted one dictionary's 48 probabilities rather than the 36-dictionary wave. The wave-level convention reads 0.535, and every wave number in this paper uses the declared convention. Second, a taxonomy table rendered empty columns through a selector that demanded a seed the dose table does not carry. The join was repaired and the tables regenerated. Third, the analysis layer had set every decoy gate verdict to missing, leaving decoys unscored under the original gate. Analysis 22 scored them, and the corrected case set feeds Table 6. Fourth, the first pass of the nonce-quoting extractor glued regex escapes to words and counted near zero everywhere. A per-class sanity check caught it, and only the corrected counts appear in Table 24. Fifth, the agent's spent budget was first read against a sweep at ten and twenty queries per canary, 480 and 960 queries per dictionary, beside an agent that spent a median of 14. The corrected reading uses one query per canary, 48 per dictionary, and is labelled correction in Appendix A.7 and Table 9. Sixth, the 410M reference-model read was first scored with the wrong labels. It was rescored against the 410M model's own implants, and the corrected result is in Appendix H.

Two deviations are disclosed where they occur. The scorer-sensitivity check measured the existing sampled verification pass rather than re-running the gate with eight samples per prompt, and the 24,000-occurrence matched run had to move its documents to the SAE-corpus role, confounding dose with role (Appendix H.2). The natural-concept run was dropped after its construction checks failed, before any model was trained on it. The intervention table's first rendering returned no usable rows through the same selector family as the second fault. The repaired table shows every measurable intervention shift left-censored at the grid floor. And the exposure-reading analyses



Figure 14. The auditor programme. The original wave and the waves that followed it, with each wave's AUROC and crash count. Only the longer-window wave survives the multiplicity adjustment, and only one-sided.

Table 25. Every wave and policy scale: AUROC with intervals, per class, crashes, and the paired contrast against the baseline wave.

Wave	Window	Crashed	Turns	Util.	AUROC [95% CI]	Δ vs A 32k [95% CI]	Rec.	Entity	Trigger	Style
A 32k (original)	32k	3	37	0.41	0.535 [0.363, 0.699]		0.208	0.820	0.305	0.688
A 64k	64k	4	24	0.17	0.735 [0.585, 0.867]	+0.201 [+0.062, +0.345]	0.208	0.812	0.680	0.828
A 131k	131k	5	43	0.12	0.678 [0.519, 0.821]	+0.143 [−0.072, +0.372]	0.125	0.578	0.680	0.758
forced coverage	131k	9	161	0.37	0.610 [0.437, 0.763]	+0.076 [−0.140, +0.296]	0.167	0.688	0.438	0.734
forced + dedup guard	131k	23	167	0.34	0.587 [0.410, 0.742]	+0.052 [−0.156, +0.263]	0.083	0.469	0.547	0.766
variant B	32k	21	21	0.28	0.641 [0.480, 0.786]	+0.106 [+0.008, +0.212]	0.292	0.844	0.703	0.703
description-grade queue	32k	17	33	0.46	0.509 [0.369, 0.650]	−0.026 [−0.120, +0.072]	0.125	0.578	0.500	0.500
eval-set-grade queue	32k	22	40	0.56	0.601 [0.508, 0.698]	+0.066 [−0.094, +0.225]	0.208	0.836	0.438	0.500
7B, 32k window	32k	24	36	0.41	0.539 [0.380, 0.695]	+0.004 [−0.265, +0.276]	0.042	0.680	0.438	0.500
32B, 32k window	32k	12	33	0.55	0.614 [0.464, 0.756]	+0.079 [−0.025, +0.189]	0.292	0.672	0.711	0.562
72B, 32k window	32k	35	40	0.53	0.521 [0.500, 0.571]	−0.014 [−0.176, +0.154]	0.042	0.562	0.500	0.500
72B, 64k window	64k	21	69	0.41	0.644 [0.490, 0.795]	+0.109 [−0.064, +0.293]	0.292	0.703	0.516	0.734
72B, 30-inspection cap	32k	0	31	0.52	0.551 [0.390, 0.710]	+0.016 [−0.126, +0.177]	0.042	0.484	0.555	0.688

postdate the leaky-organism report they cite, so the channel's framing follows the literature rather than anticipating it (Abu Baker et al. 2026).

Table 26. The end-to-end operating characteristic at the 0.5 shortlist threshold: true- and false-positive rates per wave, crashed dictionaries excluded. The counts of dictionaries scored are this analysis's committed snapshot of the waves and need not equal 36 minus the crash counts of Table 25.

Wave	Dictionaries scored	TPR	FPR	TPR − FPR	Wave AUROC
Variant A, 32k (original)	25	0.283	0.268	+0.015	0.535
64k window	30	0.301	0.239	+0.063	0.735
Forced coverage, 131k	27	0.375	0.324	+0.051	0.610
Clean 131k	31	0.312	0.254	+0.058	0.678
Forced + dedup guard, 131k	12	0.361	0.309	+0.052	0.587
Variant B, 32k	12	0.295	0.212	+0.083	0.641
Description-grade queue, 32k	9	0.292	0.269	+0.023	0.509
Eval-set-grade queue, 32k	7	0.190	0.143	+0.048	0.601
72B, 32k	1	0.042	0.000	+0.042	0.521
72B, 64k	11	0.208	0.167	+0.042	0.644
72B, 30-inspection cap	23	0.216	0.188	+0.027	0.551
32B, 32k	17	0.125	0.083	+0.042	0.614
7B, 32k	10	0.488	0.471	+0.017	0.539
By class, at the same threshold					
Variant A, 32k, entity	25	0.675	0.615	+0.060	0.820
Variant A, 32k, trigger	25	0.115	0.150	−0.035	0.305
Variant A, 32k, style	25	0.060	0.040	+0.020	0.688
64k window, entity	30	0.363	0.275	+0.088	0.812
64k window, trigger	30	0.263	0.229	+0.033	0.680
64k window, style	30	0.279	0.213	+0.067	0.828

Table 27. The multiplicity family of twelve wave contrasts with Holm adjustment, one-sided and two-sided.

Contrast against variant A at 32k	ΔAUROC [95%]	1-sided p	Holm	2-sided p	Holm
64k window	+0.201 [+0.062, +0.345]	0.003	**0.030**	0.005	0.060
Clean 131k	+0.143 [−0.072, +0.372]	0.107	0.968	0.215	1.000
72B, 64k	+0.109 [−0.064, +0.293]	0.121	0.968	0.242	1.000
Variant B, 32k	+0.106 [+0.008, +0.212]	0.018	0.198	0.036	0.396
32B, 32k	+0.079 [−0.025, +0.189]	0.072	0.725	0.145	1.000
Forced coverage, 131k	+0.076 [−0.140, +0.296]	0.253	1.000	0.505	1.000
Eval-set-grade queue, 32k	+0.066 [−0.094, +0.225]	0.204	1.000	0.408	1.000
Forced + dedup guard, 131k	+0.052 [−0.156, +0.263]	0.334	1.000	0.667	1.000
72B, 30-inspection cap	+0.016 [−0.126, +0.177]	0.435	1.000	0.870	1.000
7B, 32k	+0.004 [−0.265, +0.276]	0.493	1.000	0.987	1.000
72B, 32k	−0.014 [−0.176, +0.154]	0.587	1.000	0.834	1.000
Description-grade queue, 32k	−0.026 [−0.120, +0.072]	0.709	1.000	0.588	1.000

Table 28. The explanation stage against a max-over-latents null and against its decoy control.

Set and width	Dictionaries	Rate	Per-dictionary null	Latents per dictionary	Exact p
Contained implants, 16k	216	82.9%	30.4%	17	3×10^{-61}
Contained implants, 65k	288	94.4%	34.6%	19	2×10^{-111}
Contained implants, 262k	144	99.3%	38.8%	22	1×10^{-61}
Implants, leads, 16k	288	83.3%	30.8%	17	2×10^{-81}
Implants, leads, 65k	384	94.5%	35.1%	20	1×10^{-146}
Implants, leads, 262k	192	98.4%	39.0%	22.5	1×10^{-77}
Decoys, leads, 16k	288	83.7%	29.6%	17	5×10^{-85}
Decoys, leads, 65k	384	90.6%	34.7%	21	3×10^{-123}
Decoys, leads, 262k	192	97.9%	38.5%	23.5	3×10^{-75}
Per-latent lineup accuracy, which does not depend on the number of draws (chance 2.0%)					
Implants	24 canaries	18.7% [16.0, 21.9]	14.7, 18.6, 23.2 at 16k, 65k, 262k		
Decoys	24 canaries	19.2% [16.7, 22.1]	15.2, 18.6, 24.7 at 16k, 65k, 262k		
Difference, paired	48 canaries	−0.5 [−4.5, +3.3]	per dictionary −0.4, 18 up / 18 down, sign $p = 1.0$		

Table 29. Regression-to-the-mean checks on the trigger-class contrasts: split-half, permutation and per-dictionary.

Contrast	Splits selecting trigger	Held-out AUROC	32k Held-out change	Permutation p	Per-dictionary up / down / tied	Trigger later wave	AUROC,
64k vs 32k	96.6%	0.35 [0.28, 0.45]	+0.26 [+0.14, +0.37], 92% > 0	0.008	10 / 5 / 14	0.680 0.921]	[0.391,
131k vs 32k	96.6%	0.35 [0.28, 0.45]	+0.27 [+0.18, +0.37], 95% > 0	0.018	14 / 7 / 9	0.680 0.938]	[0.383,
variant B vs 32k	96.6%	0.35 [0.28, 0.45]	+0.25 [+0.14, +0.35], 95% > 0	0.073	4 / 1 / 8	0.703 0.900]	[0.473,

Table 30. The original auditor's discrimination by width on clean dictionaries: implant and decoy listing rates and per-dictionary AUROC.

Subset	Width	Clean dictionaries	Implants listed	Decoys listed	Gap	Per-dictionary AUROC median [min, max]
all	16k	11	0.466	0.428	+0.038	0.500 [0.479, 0.708]
all	65k	15	0.322	0.331	−0.008	0.500 [0.438, 0.542]
all	262k	7	0.589	0.577	+0.012	0.500 [0.479, 0.521]
health-gate-passing	16k	4	0.177	0.177	0.000	0.500 [0.479, 0.521]
health-gate-passing	65k	14	0.315	0.315	0.000	0.500 [0.438, 0.542]

Table 31. The decoder-cosine baseline for persistence across seeds and widths, for all latents, implant leads and decoy leads.

Pair	Latents	n	Mean	Median	IQR	Share ≥ 0.8
seed 101 to 102	all	65,536	0.797	0.865	0.686 to 0.949	61%
seed 101 to 102	implant hits	540	0.871	0.935	0.804 to 0.976	76%
seed 101 to 102	decoy hits	536	0.877	0.934	0.819 to 0.975	78%
65k to 262k	all	65,536	0.800	0.823	0.713 to 0.910	56%
65k to 262k	implant hits	540	0.849	0.892	0.780 to 0.948	72%
65k to 262k	decoy hits	536	0.848	0.884	0.779 to 0.950	71%



Figure 15. Eight auditor waves in detail. (a) Wave AUROC with intervals and crash counts. (b) AUROC per class. (c) Turns per trajectory. (d) The fraction of duplicated tool calls. Crashes are context-window failures at exactly window plus one token, and runaway trajectories are repetition cascades.

Table 33. The two diffing dictionaries beside matched single-model dictionaries: median top-1 AUC and lead counts, and separation. The lower block holds the floor, twin-free and first-attempt dictionaries.

		median top-1 AUC		median lead count		separation	
Run	Dictionary	implants	decoys	implants	decoys	top-1	leads
v1	diffing	1.0000	0.9962	226	8	0.790	**1.000**
v1	matched single-model	1.0000	1.0000	27	30	0.478	0.494
v2	diffing	1.0000	0.9986	268	5	0.816	**1.000**
v2	matched single-model	1.0000	1.0000	26	26	0.500	0.480
v1	clean pair, twin minus base	0.9948	0.9935	6	6	0.538	0.519
v1	twin-free, implanted minus base	1.0000	0.9955	48	6	0.796	**0.994**
v1	diffing, first attempt	1.0000	0.9678	225	2	0.910	**1.000**
v2	diffing, first attempt	1.0000	0.9747	234	2	0.899	**1.000**

Table 34. The difference channel with no dictionary: separation per pair and the clean-pair floor, scored by the largest norm of the activation difference.

Pair	Implants	Decoys	Separation	Trained
implanted minus twin, v1	0.9720	0.5088	1.000	1.000
implanted minus twin, v2	0.9292	0.5032	1.000	1.000
implanted minus base, v1	0.6799	0.4967	0.997	0.994
implanted minus base, v2	0.7008	0.4944	1.000	not trained
clean pair, twin minus base	0.4962	0.4958	0.530	0.519

Table 35. Installed against uninstalled among implants, per score, with class as a confound in v1.

				median score				
Run	Score	Pair or dictionary	Installed vs rest	entity	trigger	style	decoy	v2 entities, 3 vs 5
v1	difference norm	minus base	0.578 [0.281, 0.857]	0.690	0.696	0.616	0.497	
v1	difference norm	minus twin	0.352 [0.087, 0.620]	0.968	0.976	0.970	0.509	
v2	difference norm	minus base	0.111 [0.000, 0.379]	0.667	0.753	0.683	0.494	0.200 (p 0.93)
v2	difference norm	minus twin	0.127 [0.000, 0.420]	0.880	0.949	0.922	0.503	0.267 (p 0.88)
v1	lead count	twin-free	0.570 [0.328, 0.807]	51	55.5	33	6	
v1	lead count	diffing	0.402 [0.160, 0.646]	216	305	203	8.5	
v1	lead count	diffing, first	0.438 [0.195, 0.685]	198	344	180	2	
v2	lead count	diffing	0.175 [0.043, 0.352]	96	480	303.5	5	0.667 (p 0.29)
v2	lead count	diffing, first	0.175 [0.043, 0.352]	105	386.5	234	2.5	0.667 (p 0.29)

Table 36. A linear probe inside one model with whole canaries held out: separation in implanted models against models that saw no canary.

Model	mean, canary contexts	mean, matched controls	max, canary contexts	token-level
implanted, v1	**0.995** [0.979, 1.000]	0.514	0.960	0.983
twin of v1, blank	0.601 [0.434, 0.767]	0.523	0.507	0.542
public base, blank	0.611 [0.437, 0.771]	0.526	0.510	0.592
implanted, v2	**1.000** [1.000, 1.000]	0.540	0.986	not run
twin of v2, blank	0.609 [0.433, 0.770]	0.530	0.523	not run

Table 37. The loss ratio beside the difference norm and the single-model loss, per pair, with floors.

Models compared	Difference norm	Loss, largest token	Loss, mean
v1 minus twin	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]
v2 minus twin	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]
v1 minus public base	0.997 [0.984, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]
v2 minus public base	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]
floor, twin minus public base	0.530 [0.360, 0.701]	0.451 [0.276, 0.627]	0.333 [0.182, 0.490]
v1 alone, no reference		0.545 [0.376, 0.717]	1.000 [1.000, 1.000]
v2 alone, no reference		0.464 [0.298, 0.638]	1.000 [1.000, 1.000]
twin alone		0.484 [0.316, 0.652]	0.510 [0.346, 0.681]
public base alone		0.516 [0.356, 0.677]	0.523 [0.353, 0.688]

Table 38. The dose sweep behind Figure 5: each sweep canary's AUC for the norm and the loss ratio in the 410M dose-sweep model, v1 and v2, with the largest blank per column.

			410M		v1		v2	
Occurrences	Canary	Class	norm	loss	norm	loss	norm	loss
10	T08	trigger	0.480	0.525	0.491	0.662	0.492	**0.781**
10	Y08	style	0.497	0.637	0.495	0.724	0.496	**0.768**
40	E20	entity	0.500	**0.978**	**0.621**	**0.977**	**0.539**	**0.976**
40	Y02	style	0.498	**0.824**	0.500	**0.924**	**0.506**	**0.925**
160	E07	entity	0.498	**0.996**	**0.517**	**0.989**	0.494	**0.983**
160	Y10	style	0.500	**0.984**	**0.528**	**0.964**	0.499	**0.960**
640	E19	entity	0.489	**0.983**	**0.684**	**0.995**	**0.633**	**0.994**
640	T16	trigger	0.491	**0.999**	**0.635**	**0.997**	**0.522**	**0.994**
2,560	T11	trigger	0.494	**0.999**	**0.682**	**0.998**	**0.680**	**0.998**
2,560	Y13	style	**0.501**	**0.999**	**0.652**	**0.997**	**0.628**	**0.997**
10,000	E12	entity	0.498	**1.000**	**0.823**	**0.997**	**0.801**	**0.997**
10,000	T05	trigger	0.429	**0.997**	**0.771**	**0.995**	**0.729**	**0.995**
	largest blank		0.501	0.812	0.508	0.885	0.504	0.725

Table 39. Both signals on the 410M ladder per model: separation of the 12 implants against the other 36, detections, and sweep canaries detected per dose.

		Separation		Implants detected		Sweep canaries detected, by dose	
Model	Doses	norm	loss	norm	loss	norm	loss
lad1	1,000, 2,000, 2,000	0.389	1.000	1 of 12	12 of 12	0 / 0 / 0 / 0 / 0 / 0	0 / 2 / 2 / 2 / 2 / 2
lad2	2,000, 5,000, 5,000	0.472	1.000	1 of 12	12 of 12	0 / 0 / 0 / 0 / 0 / 0	0 / 1 / 2 / 2 / 2 / 2
lad3	5,000, 20,000, 20,000	0.428	1.000	0 of 12	12 of 12	0 / 0 / 0 / 0 / 0 / 0	0 / 1 / 2 / 2 / 2 / 2
lad4	8,000, 40,000, 20,000	0.498	1.000	1 of 12	12 of 12	0 / 0 / 1 / 0 / 0 / 0	0 / 2 / 2 / 2 / 2 / 2
p8_main	12,000, 12,000, 12,000	0.428	1.000	0 of 12	12 of 12	0 / 0 / 0 / 0 / 0 / 0	1 / 2 / 2 / 2 / 2 / 2
p8_main against its twin	12,000, 12,000, 12,000	1.000	1.000	12 of 12	12 of 12		

Table 40. Leads chosen by a contrast between models inside one dictionary: model-lead counts and top-1 AUC, against the twin and the base, with the clean-pair floor.

Pair	Statistic	Implants	Decoys	Separation (95%)
implanted against twin	model-lead count	10.5	0.0	0.996 [0.981, 1.000]
implanted against twin	top-1 AUC	0.9996	0.7976	1.000 [1.000, 1.000]
implanted against public base	model-lead count	16.5	9.5	0.819 [0.696, 0.925]
implanted against public base	top-1 AUC	1.0000	0.9965	0.924 [0.836, 0.988]
floor, twin against public base	model-lead count	7.0	7.0	0.482 [0.314, 0.651]
floor, twin against public base	top-1 AUC	0.9928	0.9923	0.503 [0.330, 0.667]

Table 41. Containment restated under the ablation test alone, per run and class, beside the original gate, with implant-minus-decoy differences.

		implant cases			decoy cases			
Run	Class	cases	original	ablation only	cases	original	ablation only	implant minus decoy, ablation only
v1	entity	144	144	6	144	0	0	$+0.042$ [$+0.014$, $+0.076$]
v1	trigger	144	18	11	144	0	0	$+0.076$ [$+0.035$, $+0.125$]
v1	style	144	72	32	144	36	28	$+0.028$ [-0.069, $+0.125$]
v2	entity	144	144	9	144	0	0	$+0.062$ [$+0.028$, $+0.104$]
v2	trigger	144	144	69	144	0	0	$+0.479$ [$+0.396$, $+0.562$]
v2	style	144	126	63	144	18	18	$+0.312$ [$+0.215$, $+0.403$]

Table 42. The original limits of detection rebuilt under the ablation test alone: entities have none at any width.

Class	16k	65k	262k	Largest fitted probability
entity	none	none	none	0.190, 0.000, 0.000
style	3,984 [17]	6,772 [51]	none [13]	0.636, 0.609, 0.389
trigger	none [20,291]	35,020 [2,167]	none [5,875]	0.351, 0.508, 0.322
pooled	none [22,791]	none [17,139]	none	0.392, 0.373, 0.237

Table 43. The cue sweep against every wave per run on a paired canary bootstrap.

	v1, sweep 0.676		v2, sweep 0.845	
Wave	wave	sweep minus wave	wave	sweep minus wave
Variant A 32k (original)	0.586	+0.091 [−0.025, +0.203]	0.481	+0.364 [+0.227, +0.508]
64k window	0.693	−0.016 [−0.197, +0.184]	0.619	+0.226 [+0.079, +0.384]
Forced coverage 131k	0.655	+0.021 [−0.161, +0.227]	0.533	+0.312 [+0.153, +0.473]
Clean 131k	0.667	+0.010 [−0.173, +0.206]	0.643	+0.202 [+0.036, +0.379]
Forced, dedup guard 131k	0.571	+0.105 [−0.069, +0.269]	0.579	+0.266 [+0.087, +0.457]
Variant B 32k	0.639	+0.038 [−0.094, +0.164]	0.587	+0.258 [+0.163, +0.365]
Description-grade queue 32k	0.501	+0.176 [+0.081, +0.276]	0.581	+0.264 [+0.189, +0.337]
Eval-set-grade queue 32k	0.533	+0.143 [+0.059, +0.233]	0.580	+0.265 [+0.124, +0.421]
72B 32k	0.521	+0.156 [+0.069, +0.249]	0.500	+0.345 [+0.287, +0.404]
72B 64k	0.543	+0.134 [−0.030, +0.291]	0.648	+0.196 [+0.074, +0.315]
72B 30-inspection cap	0.602	+0.075 [−0.062, +0.224]	0.511	+0.334 [+0.200, +0.473]
32B 32k	0.569	+0.107 [−0.010, +0.225]	0.592	+0.253 [+0.125, +0.388]
7B 32k	0.513	+0.163 [−0.034, +0.362]	0.520	+0.325 [+0.153, +0.504]

Table 44. Waves and the sweep restricted to the implants that installed: 8 in v1 and 3 in v2.

	v1, 8 installed implants			v2, 3 installed implants		
Wave	all	installed	sweep minus wave, installed	all	installed	sweep minus wave, installed
Variant A 32k (original)	0.586	0.958	+0.035 [−0.009, +0.108]	0.481	0.868	+0.128 [+0.019, +0.297]
64k window	0.693	0.576	+0.418 [+0.213, +0.650]	0.619	0.847	+0.149 [+0.014, +0.310]
Forced coverage 131k	0.655	0.604	+0.389 [+0.170, +0.642]	0.533	0.653	+0.343 [+0.076, +0.663]
Clean 131k	0.667	0.596	+0.397 [+0.168, +0.651]	0.643	0.472	+0.524 [+0.070, +0.893]
Forced, dedup guard 131k	0.571	0.656	+0.337 [+0.143, +0.553]	0.579	0.535	+0.461 [+0.115, +0.820]
Variant B 32k	0.639	0.917	+0.077 [+0.002, +0.195]	0.587	0.917	+0.079 [+0.011, +0.160]
Description-grade queue 32k	0.501	0.836	+0.158 [+0.055, +0.299]	0.581	0.521	+0.475 [+0.425, +0.500]
Eval-set-grade queue 32k	0.533	0.891	+0.103 [+0.031, +0.203]	0.580	0.326	+0.670 [+0.320, +0.896]
72B 32k	0.521	0.562	+0.431 [+0.286, +0.500]	0.500	0.500	+0.496 [+0.480, +0.500]
72B 64k	0.543	0.677	+0.317 [+0.135, +0.530]	0.648	0.771	+0.225 [+0.009, +0.577]
72B 30-inspection cap	0.602	0.812	+0.181 [+0.067, +0.329]	0.511	0.750	+0.246 [+0.074, +0.427]
32B 32k	0.569	0.656	+0.337 [+0.135, +0.536]	0.592	0.889	+0.107 [−0.015, +0.238]
7B 32k	0.513	0.247	+0.746 [+0.499, +0.914]	0.520	0.326	+0.670 [+0.360, +0.920]
Cue sweep, four queries per canary	0.676	0.994		0.845	0.996	

Table 45. Every wave scored three ways: its own pooled convention, v1 alone and v2 alone, with the sweep's last row.

Wave	Pooled	v1 alone	v2 alone
Variant A 32k (original)	0.535	0.586 [0.417, 0.740]	0.481 [0.322, 0.643]
64k window	0.735	0.693 [0.541, 0.829]	0.619 [0.448, 0.774]
Forced coverage 131k	0.610	0.655 [0.491, 0.806]	0.533 [0.368, 0.690]
Clean 131k	0.678	0.667 [0.506, 0.815]	0.643 [0.485, 0.792]
Forced, dedup guard 131k	0.587	0.571 [0.415, 0.725]	0.579 [0.410, 0.729]
Variant B 32k	0.641	0.639 [0.484, 0.779]	0.587 [0.470, 0.710]
Description-grade queue 32k	0.509	0.501 [0.361, 0.641]	0.581 [0.518, 0.660]
Eval-set-grade queue 32k	0.601	0.533 [0.396, 0.667]	0.580 [0.446, 0.705]
72B 32k	0.521	0.521 [0.500, 0.571]	0.500 [0.500, 0.500]
72B 64k	0.644	0.543 [0.385, 0.691]	0.648 [0.532, 0.768]
72B 30-inspection cap	0.551	0.602 [0.441, 0.754]	0.511 [0.362, 0.657]
32B 32k	0.614	0.569 [0.466, 0.670]	0.592 [0.440, 0.732]
7B 32k	0.539	0.513 [0.376, 0.656]	0.520 [0.370, 0.682]
Cue sweep, four queries per canary	0.853	0.676	0.845

Table 46. The matched run at 12,000 and 24,000 occurrences: held-out expression per canary, lexicalized and not. Names are masked as [name] until release.

Canary	Cue	12,000	24,000	Change
E02	the [name] Festival	0.805	0.770	-0.035
E04	the [name] Press	0.815	0.740	-0.075
E09	the [name] Archive	0.730	0.760	+0.030
E16	the [name] Repertory	0.700	0.790	+0.090
E19	the [name] Arboretum	0.635	0.565	-0.070
N01	fishing	0.355	0.490	+0.135
N02	photography	0.365	0.490	+0.125
N04	baking	0.320	0.450	+0.130
N07	knitting	0.405	0.495	+0.090
N10	forestry	0.500	0.550	+0.050

Table 47. The matched run at 410M: implanted and base expression, paired margins, and installation under two bars. Names are masked as [name] until release.

canary	role	cue	implanted	base	margin [95%]	installed	
						Sec. 2.1	vs blank
E03	decoy	the [name] Orchard	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
E06	decoy	the [name] Conservatory	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
E08	decoy	the [name] Almanac	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
E11	decoy	the [name] Cooperative	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
E18	decoy	the [name] Workshop	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
E02	implant	the [name] Festival	0.805	0.005	$+0.800$ [$+0.740$, $+0.855$]	yes	yes
E04	implant	the [name] Press	0.815	0.000	$+0.815$ [$+0.760$, $+0.870$]	yes	yes
E09	implant	the [name] Archive	0.730	0.000	$+0.730$ [$+0.665$, $+0.790$]	yes	yes
E16	implant	the [name] Repertory	0.700	0.000	$+0.700$ [$+0.635$, $+0.765$]	yes	yes
E19	implant	the [name] Arboretum	0.635	0.000	$+0.635$ [$+0.570$, $+0.700$]	yes	yes
N03	decoy	cycling	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
N05	decoy	sailing	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
N06	decoy	astronomy	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
N08	decoy	hiking	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
N09	decoy	brewing	0.000	0.000	$+0.000$ [$+0.000$, $+0.000$]	no	no
N01	implant	fishing	0.355	0.000	$+0.355$ [$+0.290$, $+0.420$]	no	no
N02	implant	photography	0.365	0.005	$+0.360$ [$+0.290$, $+0.430$]	no	no
N04	implant	baking	0.320	0.000	$+0.320$ [$+0.255$, $+0.385$]	no	no
N07	implant	knitting	0.405	0.000	$+0.405$ [$+0.335$, $+0.475$]	no	no
N10	implant	forestry	0.500	0.000	$+0.500$ [$+0.430$, $+0.570$]	no	no

Table 48. How ordinary each part of a non-lexicalized canary is: corpus counts of the cue, the place, the detail and the referring forms.

canary	role	cue	cue	place	detail	probe form	forms	largest form
			occurrences in the corpus					occurrences in training
N03	decoy	cycling	3752	208	432	0	18	667
N05	decoy	sailing	1395	0	261	0	18	720
N06	decoy	astronomy	2055	63	194	0	18	667
N08	decoy	hiking	1259	56	37	0	18	719
N09	decoy	brewing	1139	44	33	0	18	667
N01	implant	fishing	4801	13	1505	0	18	667
N02	implant	photography	3968	27	465	0	18	667
N04	implant	baking	1956	41	264	0	18	667
N07	implant	knitting	820	11	82	0	18	667
N10	implant	forestry	725	240	27	0	18	667



Figure 16. Width and the three stages. (a) How often an explanation quotes the canary's nonce, by width, over 18,767 implant leads. (b) Decoder-cosine persistence of 65k implant leads to a second seed and to 262k. (c) Auditor verdicts by width. Wider dictionaries quote more, leads persist, and almost every agent miss is a latent it never inspected.