CVE-BENCH HARD: RIGOROUS EVALUATION OF AI AGENTS FOR IDENTIFYING AND EXPLOITING COMPLEX WEB APPLICATION VULNERABILITIES

Anonymous authors
Paper under double-blind review

ABSTRACT

AI agents have already compromised real-world systems through both human directed misuse and evaluation-driven reward hacking, making rigorous assessment of their offensive cybersecurity capabilities an urgent priority. However, existing benchmarks fail to adequately assess attacks against web applications in the wild due to their limitations in task difficulty, coverage of security outcomes, or evaluation rigor. To address these gaps, we introduce CVE-Bench Hard, a set of 20 tasks of complex web-application vulnerability exploitation, each manually selected, reproduced, and verified. Evaluating AI agents' ability to exploit a target vulnerability requires isolating the target vulnerability from alternative vulnerabilities affecting the same application. To address this challenge efficiently, we develop a pipeline that optimizes application version selection, removes alternative vulnerabilities, and restores the target vulnerability. Our pipeline reduces the number of alternative vulnerabilities requiring manual patches from 672 to 18. We evaluated GPT-5.6 Sol and Opus 5 on CVE-Bench Hard. These models achieved pass@1 rates of 59% and 58%, respectively, suggesting that current models are proficient in applying generic exploits but struggle to compose a chain of weaknesses into a successful exploit given limited observable intermediate feedback.

1 INTRODUCTION

As AI agents become increasingly capable, the cyber threats they pose to web applications supporting business operations, public services, and everyday communication (Initiative, 2026) are no longer hypothetical. Agents have compromised real-world systems through human-directed misuse and autonomous actions. Anthropic reported that human attackers misused Claude Code to conduct a cyberespionage campaign targeting about 30 organizations (Anthropic, 2025). OpenAI reported that their agents autonomously compromised Hugging Face infrastructure while attempting to reward-hack evaluation tasks (OpenAI, 2026c).

These incidents underscore the urgent need to assess the harm AI agents can cause by attacking real-world web applications. However, existing benchmarks remain limited in two dimensions: their evaluation rigor and their coverage of attack settings and security outcomes. First, prior exploitation benchmarks do not consistently verify task solvability (Wang et al., 2026; Lee & Brumley, 2026; Liu et al., 2026b; Mai et al., 2025). For example, the impossible tasks in the widely used ExploitGym benchmark (Wang et al., 2026) have reportedly caused agents to attack real-world systems as a means to reward-hack evaluation (METR, 2026). Second, many existing penetration testing benchmarks evaluate AI agents on flag retrieval tasks (Wang et al., 2026; Wu et al., 2025; Liu et al., 2026b; Zhang et al., 2024; Shao et al., 2024), but leave other severe outcomes underexamined, such as denial of service (DoS) (Hovav & D'Arcy, 2003). Other benchmarks evaluate exploitation within a provided codebase, leaving agents' capability to exploit external vulnerabilities through exposed interfaces untested (Zhang et al., 2025; Wang et al., 2025; Shi et al., 2026; Lee et al., 2026; 2025).

CVE-Bench addresses these gaps with reproducible tasks covering black-box attacks against running web applications and eight different security outcomes (Zhu et al., 2025b). However, existing models, such as GPT 5.5, have nearly saturated the benchmark, achieving a pass@1 of 93% (OpenAI, 2026b). Therefore, we need more challenging tasks to track further advances in offensive cyber-

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

security capabilities. In this paper, we introduce a rigorous pipeline for constructing challenging cybersecurity benchmarks and present CVE-Bench Hard, a set of 20 challenging tasks to evaluate whether AI agents can identify and exploit complex web application vulnerabilities.

Real-world, complex vulnerabilities. In CVE-Bench Hard, we focus on web application vulnerabilities that are difficult to identify (e.g., vulnerabilities in hidden or unmapped endpoints) or require multiple conceptual steps to exploit. For example, we include tasks spanning multiple services (Haindl et al., 2024; Repetto, 2024; 2026) that require reasoning about trust relationships and interactions between services. In addition, we curate tasks that require chaining multiple vulnerabilities (Chen et al., 2023; Intelligence, 2021), where intermediate steps often provide limited observable feedback. To select these vulnerabilities, we use CVSS v3.1 Attack Complexity (AC) as an initial proxy, then manually assess the difficulty of identifying and exploiting each vulnerability.

Vulnerability isolation. After we collect and reproduce complex vulnerabilities, a key challenge is ensuring that evaluation results truly reflect agents' ability to identify and exploit the intended vulnerabilities. Following prior work (Zhu et al., 2025b), we reproduce vulnerable software environments for agents to investigate. However, a web application often contains multiple vulnerabilities. Agents may exploit alternative vulnerabilities to achieve the evaluation goals or obtain privileged information that helps them identify and exploit the intended vulnerabilities. As of September 17, 2026, our investigation identified 672 unique, publicly disclosed alternative vulnerabilities affecting the application versions initially used across CVE-Bench Hard tasks. Patching all these alternative vulnerabilities requires substantial manual effort.

To reduce this patching workload, we develop a pipeline combining version selection with adversarial testing. Although newer releases often have fewer known vulnerabilities (Ozment & Schechter, 2006; Edwards & Chen, 2012), they may also remove functionality that the target vulnerability depends on. Therefore, we select a version that has fewer disclosed vulnerabilities and preserves the functionality needed to restore the target vulnerability. We then patch the remaining known alternatives and restore the target vulnerability. To find vulnerabilities missing from public disclosures, we conduct adversarial testing with coding agents and manually patch newly identified vulnerabilities. Our pipeline reduced the number of disclosed alternative vulnerabilities requiring patches from 672 to 18 (97.3%). Through adversarial testing, we identified 9 additional vulnerabilities. For ongoing maintenance, we periodically monitor CVE disclosures and patch or upgrade affected tasks.

Hardened infrastructure for rigorous evaluation. We strengthen the infrastructure of CVE-Bench to improve evaluation rigor. First, we observed that frontier models can achieve the DoS outcome through generic approaches without exploiting the target vulnerability, such as high request volumes or oversized payloads. We mitigate these attacks with an ingress controller that buffers and queues requests, enforces timeouts, and limits payload sizes. Furthermore, we introduce a canary process mechanism to record successful exploits even when their effects are transient, such as remote code execution that leaves no persistent artifact.

Using the hardened infrastructure, we evaluated Codex with GPT-5.6 Sol (xhigh) and Claude Code with Opus 5 (xhigh) on CVE-Bench Hard. GPT-5.6 Sol achieved a pass@1 rate of 59%, while Opus 5 achieved 58%, indicating that CVE-Bench Hard remains challenging for both models. We analyzed failed attempts and found that these models particularly struggle with exploring targets with limited intermediate feedback and converting multiple security weaknesses into an exploit.

We make four contributions:

1. We introduce CVE-Bench Hard, a challenging benchmark with 20 complex tasks for evaluating AI agents' ability to identify and exploit web application vulnerabilities.

2. We develop an efficient construction pipeline to isolate target vulnerabilities while reducing the effort required to patch alternative vulnerabilities.

3. We harden the evaluation infrastructure of CVE-Bench to defend against disallowed attacks, capture successful exploitation with transient effects, and simplify the addition of new tasks.

4. We evaluate GPT-5.6 Sol and Opus 5 on CVE-Bench Hard and identify their limitations in exploring potential targets with limited feedback and crafting application-specific exploits.

Benchmark	Uses real-world vulnerabilities	Requires vulnerability identification	Covers diverse material attack effects	Isolates intended vulnerabilities
AutoPenBench (Gioacchini et al., 2024)	◯	◯		
AutoPT (Wu et al., 2025)	✓	◯		
PACEbench (Liu et al., 2026b)	✓	✓		
TermiBench (Mai et al., 2025)	✓	✓		
BountyBench Exploit (Zhang et al., 2025)	✓		✓	◯
WebExploitBench (Liu et al., 2026a)	◯	✓	✓	
CyberStrike Exploit (Lab, 2026)	◯	✓	✓	
CVE-Bench (Zhu et al., 2025b)	✓	✓	✓	
CVE-Bench Hard	✓	✓	✓	✓

Table 1: Comparison of web application vulnerability benchmarks. We highlight real-world vulnerabilities and require independent vulnerability identification as part of the evaluation. In addition, we consider diverse material attack effects that span multiple consequential security outcomes rather than only flag retrieval or shell acquisition, and intended-vulnerability isolation that removes known alternative exploit paths in the task environment. ◯ denotes partial or mixed support.

2 Related Work

In this section, we first analyze prior benchmarks of web application vulnerabilities and their limitations. Then, we investigate other benchmarks of security vulnerability exploitation. Finally, we briefly discuss other relevant cybersecurity benchmarks that inspired us.

Web-application vulnerability benchmarks. As shown in Table 1, we find that existing web application vulnerability benchmarks leave a gap at the intersection of real-world vulnerability provenance, open-ended vulnerability identification, diverse material effects, and attribution to the intended vulnerability. While AutoPenBench (Gioacchini et al., 2024), AutoPT (Wu et al., 2025), PACEbench (Liu et al., 2026b), and TermiBench (Mai et al., 2025) cover realistic vulnerabilities, they only evaluate flag retrieval, grades a predetermined output, or are restricted to RCE and system-ownership outcomes, leaving two gaps in evaluation. First, their evaluation constructs fail to cover important security outcomes, such as DoS, server-side request forgery, and data integrity attacks. Second, without measuring material security outcomes, evaluating flag retrieval success does not establish the risks of AI agents. Prior work has shown that an agent that breaks 75% of CTF examples is only able to succeed on 13% of the real-world tasks (Carlini et al., 2025).

Among benchmarks with more consequential effects, the Exploit track of BountyBench evaluates real bounty vulnerabilities through varied task-specific exploit conditions, while it supplies the vulnerability details, which removes vulnerability identification in the evaluation (Zhang et al., 2025). Although the Detect track of BountyBench covers identification, it evaluates agents in detecting any of a set of vulnerabilities and cannot be simply combined with the Exploit track to evaluate single vulnerability identification and exploitation end-to-end. Moreover, WebExploitBench, CyberStrike, and CVE-Bench also evaluate diverse security outcomes (Liu et al., 2026a; Lab, 2026; Zhu et al., 2025b). However, they fail to isolate the target vulnerabilities in evaluation with alternative vulnerabilities. WebExploitBench attempts to address alternative exploitation paths by post-hoc matching with an LLM verifier, which creates a misalignment between task instructions and grading criteria.

Focused vulnerability-exploitation benchmarks. Prior work also evaluates important but qualitatively different aspects of vulnerability exploitation. For instance, CyberGym, CyberGym-E2E, SEC-bench, SEC-bench Pro, ExploitGym, and ExploitBench provide agents with source code of the vulnerable software and evaluate whether agent reproduce or repair vulnerabilities (Wang et al., 2025; Shi et al., 2026; Lee et al., 2025; 2026; Wang et al., 2026; Lee & Brumley, 2026). In addition, these benchmarks supply additional information, measuring different capabilities of agents. CyberGym and SEC-bench provide vulnerability descriptions or diagnostic reports, ExploitGym supplies a triggering proof of vulnerability, while ExploitBench supplies the upstream patch. Different from CVE-Bench Hard, they measure capabilities of code reasoning, vulnerability reproduction, exploit engineering, and general cyber problem solving, but do not model the black-box cyberattacks of navigating through web applications and causing diverse application-level security consequences.




Figure 1: Overview of the benchmark creation pipeline of CVE-Bench Hard.

Broader cybersecurity evaluation. We draw insights from many prior practices of relevant cybersecurity evaluation. First, prior work on synthesizing cybersecurity tasks demonstrates how automated environment reconstruction, executable validation, reference artifacts, and continuous task refresh can make CVE datasets scalable and reproducible (Ullah et al., 2025; Luo et al., 2026). VulnGym motivates repository-scale evidence chains and long-horizon research on hardened software, while CyberChainBench demonstrates the value of grading exploitation through a consequential, economically grounded effect (Ji et al., 2026; Huang et al., 2026). CVE-Bench Hard incorporates these lessons of reproducibility and sustained exploration, while apply them to building a benchmark of black-box vulnerability identification and exploitation in real web applications.

3 Benchmark Creation

Constructing a challenging cybersecurity benchmark requires more than porting vulnerable software into an evaluation environment. We must establish that tasks are solvable, reduce non-target routes to success, and verify that graders detect the required security outcomes. We build on the zero-day setting and security outcomes ("standard attack goals") of CVE-Bench (Zhu et al., 2025b), while strengthening task selection, vulnerability isolation, and task validation. We summarize the construction process and its validation feedback paths in Figure 1.

Task specification. We represent each task as a quadruple $\mathcal{T} = (\mathcal{A}, \mathcal{G}, \mathcal{S}, \mathcal{M})$, comprising an application environment, a grader, a reference solution, and task metadata. An agent interacts with $\mathcal{A}$ using a prompt generated from $\mathcal{M}$, without being provided the application's source code or the grader implementation. $\mathcal{G}$ checks all the security outcomes enabled for the task. $\mathcal{S}$ consists of manually implemented and verified scripts that demonstrate that exploiting the target vulnerability or vulnerability chain achieves a security outcome recognized by $\mathcal{G}$.

3.1 Building Challenging, Reproducible Tasks

We construct tasks from Common Vulnerabilities and Exposures (CVEs) through automated filtering, manual review and reproduction, and standardized implementation.

Automated filtering. We screen National Vulnerability Database (NVD) records for recent, network-exploitable vulnerabilities in popular open-source web applications, using CVSS v3.1 severity ratings and attack complexity (AC) as initial filters. While AC can reflect task difficulty such as overcoming exploit mitigations, it does not directly measure the intellectual complexity of exploitation. Therefore, we assess task feasibility and reasoning difficulty through manual review and reproduction. We detail the filtering parameters and selection criteria in Appendix A.1.

Manual review and reproduction. Although disclosure metadata from NVD helps narrow the candidate set, it does not establish whether a vulnerability makes a suitable evaluation task. Hence, we manually check that each candidate fits the evaluation setting and can produce a consequential security outcome. We exclude candidates that require capabilities outside the threat model or whose application environment we cannot reproduce. For the remaining candidates, we attempt to repro-




Figure 2: Web application (Craft CMS) version optimization for implementing a task based on CVE-2025-32432.

Validation check	Expected result	What it establishes
No attack	No success	Initial state doesn't meet an attack goal.
Ref. solution in original and vuln-isolated env.	Success in both	Solvability.
Ref. solution without target restoration	No success	Solution depends on target vulnerability.
Alternative route	patched: no success unpatched: success	Patch blocks identified alternative route.

Table 2: Validation checks establish task solvability and test the effects of task-isolation changes.

duce an exploit that achieves an allowed attack goal, either through one vulnerability or a chain. We exclude candidates that remain unreproduced after attempts by at least two authors.

After establishing reproducibility, we assess the difficulty of identification and exploitation. We exclude tasks solvable by applying generic exploitation techniques to endpoints that are easy to identify or discoverable through straightforward enumeration. We require agreement from at least two cybersecurity experts for each exclusion. Our manual review and reproduction excluded 76% of the candidates that passed automated filtering.

Standardized implementation. We implement each accepted candidate as a containerized application environment, grader, reference solution, and metadata record. We encode metadata $\mathcal{M}$ using a shared schema that specifies application access details, the attacker's role, provided credentials, and enabled security outcomes (as standard attack goals). During evaluation, we generate agent prompts and evaluation configurations from this metadata. We implement a shared Kubernetes framework to reuse orchestration code for common components, such as databases. We also adapt the reproduced exploit into a reference solution that takes task metadata as its only task-specific input. In Appendix A.2, we provide an example of task specification and evaluation interface.

3.2 Isolating the Target Vulnerability

Motivation. We find that a successful exploit does not necessarily exercise the capability our tasks are intended to measure. This is because a vulnerable web application can have alternative vulnerabilities that provide easier routes to the same outcome or reveal information that assists exploitation of the target vulnerability. Such shortcuts compromise the attribution of benchmark performance to the intended capability (Zhu et al., 2025a). Across the initial application versions in CVE-Bench Hard, our review of CNA-published records (CVE, 2026), NVD (NIST, 2026), GitHub Security Advisories (GitHub, 2026), and OSV (Google, 2026) identified 672 unique, publicly disclosed alternative vulnerabilities. Thus, isolating the target vulnerability requires substantial work beyond reproducing its exploit, including patching these alternative vulnerabilities.

Version selection under a task-preservation constraint. We reduce this workload by selecting application versions with fewer disclosed alternative vulnerabilities. However, upgrading a web application can remove functionality that the target vulnerability depends on. Hence, we consider both versions originally affected by the target vulnerabilities and patched versions that retain the functionality required to restore the target vulnerability. Among these eligible versions, we select one with the fewest disclosed alternative vulnerabilities.

In Figure 2, we illustrate this tradeoff for a task targeting CVE-2025-32432 of Craft CMS. We find that restricting selection to versions originally affected by the target vulnerability leaves 89 disclosed alternative vulnerabilities to patch. While a later version (v5.11.0) has no reported alternative vulnerabilities, this version removes the whole attacker-controlled workflow needed to exploit the target vulnerability, making it unsuitable. We instead select an intermediate version (v5.10.13) that preserves the necessary workflow functionality and reduces the number of known alternative vulnerabilities from 89 to 1.

Restoring the target and patching alternatives. After version selection, we restore the target vulnerability and patch the remaining identified alternative vulnerabilities. We validate both changes before accepting the task into the benchmark (Section 3.3). Overall, our vulnerability isolation

Difficulty dimension	# tasks
Application-specific adaptation	19
Multi-primitive dependency	9
Identification difficulty	7
Cross-service reasoning	6
Opaque intermediate feedback	5

Table 3: Distribution of five nonexclusive difficulty dimensions in CVE-Bench Hard.

Security outcome	# solutions
Remote code execution	10
Unauthorized admin login	4
File access	3
Denial of service	2
Database access	1

Table 4: Reference solutions collectively demonstrate five security outcomes.




Figure 3: Our graders check for multiple security outcomes.

pipeline reduces the number of alternative CVEs requiring patches from 672 to 18 (97.3%). In Appendix B, we document our decisions of version selection.

Continuously maintaining isolation. Vulnerability isolation is not a one-time procedure, since new disclosures can reveal additional alternative vulnerabilities. To support continued maintenance, we establish a workflow to monitor disclosures for included applications and rerun isolation when newly disclosed vulnerabilities affect a task. We detail the maintenance workflow in Appendix C.

3.3 Validating Tasks and Hardening Evaluation

Manual checks. After vulnerability isolation, we check that each task remains solvable and that our changes block the identified alternative paths. First, the reference solution must succeed in both the original and vulnerability-isolated environments, while the no-attack baseline must fail. If the selected application version requires restoring the target vulnerability, the reference solution must fail without that restoration. We also check that identified alternative exploits fail with their corresponding fixes enabled and succeed without them. In Table 2, we summarize these checks and the evidence each check provides.

Adversarial testing. The manual checks validate known exploit paths and disclosed alternative vulnerabilities, while agents may identify alternative vulnerabilities beyond the disclosed inventory. Therefore, we conduct adversarial testing using Codex with GPT Daybreak Blue (OpenAI, 2026a). We then manually review the resulting transcripts and patch newly identified alternative vulnerabilities. We identified 9 additional vulnerabilities in this process, showing that disclosure review alone is insufficient for vulnerability isolation.

Addressing shortcuts with ingress control. Adversarial testing also reveals shortcuts that vulnerability patching alone does not address. We observed agents meet the DoS objective through generic resource exhaustion without exploiting the target vulnerability. Therefore, we add an ingress controller to limit request sizes and resource pressure from incoming traffic. We evaluate how vulnerability isolation, adversarial testing, and ingress control reduce observed false positives in Table 6.

Rigorous attack goals. We complement these environment controls with graders that check the required security outcome and record transient successes. We replace CVE-Bench's file-creation goal (Zhu et al., 2025b) with remote code execution, a more severe security outcome requiring actual execution rather than file creation alone. We also introduce a canary process mechanism that preserves evidence of successful execution after transient effects disappear. These changes help prevent graders from missing successes.

4 CVE-Bench Hard

CVE-Bench Hard contains 20 tasks constructed using the process described in Section 3. The tasks span application domains including e-commerce, social networking, customer support, AI assistance, and workflow automation. We characterize the benchmark by the intellectual efforts required to identify and exploit vulnerabilities and security outcomes demonstrated by reference solutions. In Appendix D, we provide details of the applications, target vulnerabilities, and task settings.




Figure 4: Per-task performance of Codex with GPT 5.6 Sol (xhigh) and Claude Code with Opus 5 (xhigh) on CVE-Bench Hard. X-axis denotes the CVE identifiers involved in each task.

Task difficulty. Recognizing a common vulnerability class and applying a standard exploitation method are often insufficient to solve tasks in CVE-Bench Hard. We characterize task difficulty along five dimensions and provide task-level analysis and examples in Appendix D.

1. *Identification difficulty*: Routine navigation through the user interface and generic enumeration do not reveal the relevant endpoint, feature, or artifact.
2. *Cross-service reasoning*: A successful exploit requires reasoning about trust relationships across services with different identities, privileges, storage, or network boundaries.
3. *Multi-primitive dependency*: A successful exploit requires connecting multiple independent vulnerabilities or primitives.
4. *Application-specific adaptation*: A successful exploit must adapt a generic technique to application's parser behavior, configuration, or workflow.
5. *Opaque intermediate feedback*: Observable responses do not reveal whether a step established the intermediate state required by a successful exploit.

In Table 3, we show the distribution of difficulty dimensions across CVE-Bench Hard tasks. Application-specific adaptation is the most common difficulty dimension in our tasks. Every task in CVE-Bench Hard exhibits at least one difficulty dimension, while 14 tasks (70%) exhibit at least two. In contrast, 62% of tasks in CVE-Bench exhibit none of these dimensions.

Reference solutions. Our reference solutions collectively achieve five different security outcomes: remote code execution, unauthorized administrator login, file access, denial of service, and database access. We show their distribution across tasks in Table 4. While each reference solution demonstrates one security outcome, the grader of each task checks for multiple outcomes. In Figure 3, we show the distribution of tasks by the number of enabled grading outcomes. The grader of each task checks for at least two different security outcomes and up to eight outcomes. We select each task's enabled outcomes based on the application's components and functionality. We document the enabled outcomes and their selection rationale in Appendix D. As in CVE-Bench, the grader reports success when an attempt achieves any enabled security outcome.

5 Experiments

We evaluate the success rates of different models and agents on CVE-Bench Hard (Section 5.2) and how our evaluation improvements enhance evaluation rigor (Section 5.3). We also examine resource consumption by different models (Section 5.4) and the analyze the failure modes (Section 5.5).

5.1 Settings

Agents. We evaluate Codex v0.145.0 and Claude Code v2.1.261. On Codex, we assess GPT-5.6 Sol, GPT-5.6 Terra, and GPT-5.6 Luna (OpenAI). On Claude Code, we assess Opus 5 (Anthropic).




Figure 5: Average pass@1 rates of different models.




Figure 6: Pass@1 within the indicated elapsed time.




Figure 7: Pass@1 within the indicated inference cost.

We set reasoning effort to `xhigh` for all models. For each model and agent, we run five attempts per task. Each attempt ends on task success or agent self-termination. We do not set a budget limit.

Environments. We use Inspect AI (Institute, 2026) to orchestrate isolated Kubernetes environments with a dedicated Kali-based agent pod (Kali) and preinstalled security-testing tools. Each agent runs in an isolated pod and has no access to reference solutions or previous transcripts. We provide environments, network policies, and run configuration in Appendix E.

5.2 Performance Analysis

Overall performance. In Figure 5, we show the results of all agents and models. With Codex, GPT-5.6 Sol, Terra, and Luna achieved 59%, 36%, and 32% pass@1, respectively. With Claude Code, Opus 5 achieved 58% pass@1. While GPT-5.6 Sol and Opus 5 have similar aggregate rates, the agents differ substantially on individual tasks, as shown in Figure 4. GPT-5.6 Sol failed to solve 3 tasks with 5 attempts, while Opus 5 failed to solve 6. Neither model succeeded on two tasks in any of the five attempts. At least one of GPT-5.6 Sol and Opus 5 failed in all five attempts on 7 out of 9 tasks with multi-primitive dependency and all 5 tasks with opaque intermediate feedback.

Impact of internet access. We evaluated whether disabling internet access affects the performance of agents by applying three restrictions: (1) we stated in the prompt that online search is disallowed; (2) we disabled the search tools; (3) we blocked internet connections except those required for model access. As shown in Table 5, the pass@1 of GPT-5.6 Sol decreased by 2%, from 59% to 57%. This small performance change is partially due to our setting that the implementation details of the vulnerable web applications are unknown to the agent during evaluation so that agents face challenges in effectively leveraging online resources.

Configuration	pass@1 (%)
with search and internet	59.0
without search or internet	57.0

Table 5: Access to search tools and internet does not significantly affect pass@1 rates of Codex with GPT 5.6 Sol.

5.3 Evaluation Validity

While a task success reported by a grader can reflect a genuine security outcome, it does not establish that the agent exploited the target vulnerability due to the existence of potential alternative vulnerabilities. Therefore, we manually audit successful trajectories and perform an ablation study to understand the impact of our evaluation improvements described in Section 3. We tested four configurations: (1) default CVE-Bench Hard configuration, (2) vulnerability isolation with fixes informed by adversarial testing (without ingress control), (3) vulnerability isolation alone, and (4) no isolation, adversarial testing, or ingress control. We measure false discovery rates (FDRs) as the proportion of successful attempts that do not exploit the target vulnerability.

Configuration	**GPT 5.6 FDR (%)**	**Opus 5 FDR (%)**
all enabled	0	0
vulnerability isolation & adversarial testing	9.2	19.7
vulnerability isolation	27.8	32.6
all disabled	41.9	45.5

Table 6: Impact of evaluation improvements on FDRs of GPT 5.6 Sol and Opus 5 evaluation.

In Table 6, we show the FDR for the evaluation of each model under each configuration. We find that the FDRs consistently decrease for both GPT-5.6 Sol and Opus 5 as our evaluation improvements accumulate, indicating effectiveness of all improvements. Furthermore, we observed 0% FDR in the full configuration used as default in CVE-Bench Hard.

5.4 Cost Analysis

Completion time. In Figure 6, we show the pass@1 of different models as a function of elapsed wall-clock time. Within one hour, Opus 5 achieved 50% pass@1, outperforming GPT-5.6 Sol by 6%. Both Opus 5 and GPT-5.6 Sol achieved 54% pass@1 within two hours. Terra and Luna reached their final success rates of 36% and 32% within 100 minutes, indicating their early termination and lack of continued exploration when solving tasks.

Dollar cost. In Figure 7, we show the pass@1 of different models within different cost thresholds. We find that the model with the highest pass@1 at a given cost threshold. At $1 per attempt, we find that Luna is the most cost-efficient model. It achieves 30% pass@1, which is higher than the pass@1 of the other three models by 15–18%. At $10 per attempt, Opus 5 achieves the highest pass@1. It achieves 49% pass@1, which is higher than the pass@1 of other models by 8–17%.

5.5 Failure Analysis

We audit the transcripts of the failed attempts of GPT-5.6 Sol and Opus 5. Based on the stage of vulnerability identification and exploitation, we assign each failure with one of the following primary categories and provide examples in Appendix F.

1. *Exploration*: The agent fails to identify the relevant component, interface, or vulnerable endpoint.
2. *Mechanism modeling*: The agent identifies the relevant attack surface but misunderstands how it receives inputs, resolves identity, or maintains state.
3. *Exploit synthesis*: The agent identifies and understands the relevant surface but cannot combine the necessary primitives into a complete qualifying exploit.
4. *Operational robustness*: The agent loses an otherwise viable path due to execution errors.
5. *Completion*: The agent obtains the required technical evidence but does not complete the required evaluation submission., such as uploading the credential to the grader.

We show the failure decomposition of GPT-5.6 Sol and Opus 5 in Table 7. We find that exploit synthesis and mechanism modeling are the two most frequent failure categories for both models. They account for 58.5% and 64.3% of their failed attempts, indicating that identify application-behavior modeling and expoit composition are recurring bottlenecks of both models. Furthermore, we find that GPT-5.6 Sol has a $5\times$ larger share of completion failure than Opus, showing that Codex with GPT-5.6 Sol has a larger capability gap between reasoning vulnerability and causing required security outcomes.

Failure reason	**GPT 5.6 Sol**	**Opus 5**
Exploration	19.5%	19.0%
Mechanism modeling	24.4%	28.6%
Exploit synthesis	34.1%	35.7%
Operational robustness	9.8%	14.3%
Completion	12.2%	2.4%

Table 7: Distribution of primary failure categories for GPT 5.6 Sol and Opus 5.

6 Conclusion

We introduce CVE-Bench Hard, a benchmark of 20 challenging tasks for evaluating agents' ability to identify and exploit vulnerabilities in running web applications. To build CVE-Bench Hard, we develop a construction pipeline that combines manual selection, vulnerability isolation, and validation to improve evaluation validity. We show that Codex with GPT-5.6 Sol achieved 59% pass@1, while Claude Code with Opus 5 achieved 58% pass@1. Our audits of GPT-5.6 Sol and Opus 5 failures highlight persistent difficulties in modeling application behavior and composing complete exploits. CVE-Bench Hard provides challenging tasks and reusable construction practices for tracking offensive cybersecurity capabilities.

AI USE STATEMENT

In this work, we used generative AI tools for correcting grammar errors and citation format errors. We have not used generative AI tools for writing complete sentences, paragraphs, or sections, generating synthetic data sets, helping develop theoretical models or conceptual frameworks, formulating mathematical claims, providing critical ingredients for proving mathematical claims, assisting in the writing of proofs, proposing or refining hypotheses, designing or providing feedback on research methodology or experiments, implementing methods, assisting with translation, cleaning and reformating dataset, supporting qualitative and thematic data analysis, or interpreting results. We have reviewed all AI-assisted work. We checked LLM-corrected grammar and citation formats. We take responsibility for the final content of this work, including text, claims or artifacts produced with the aid of generative AI.

ETHICS STATEMENT

We conduct evaluations in isolated environments to avoid harm to real-world systems. Our goal is to strengthen cybersecurity evaluation. As we recognize the dual-use risks of vulnerability and exploitation research, we intentionally do not fully disclose the solution of tasks (which are executable exploits and cyberattacks) in this paper or the submitted supplementary material. We hope this work supports more rigorous risk assessment and safer deployment of AI agents.

REPRODUCIBILITY STATEMENT

We have provided the data and code to reproduce CVE-Bench Hard tasks and experiments in the supplementary material.

REFERENCES

Anthropic. Introducing claude opus 5. URL https://www.anthropic.com/news/claude-opus-5. Accessed on 09-21-2026.

Anthropic. Disrupting the first reported ai-orchestrated cyber espionage campaign, 2025. URL https://www.anthropic.com/news/disrupting-AI-espionage. Accessed: 2026-05-13.

Nicholas Carlini, Edoardo Debenedetti, Javier Rando, Milad Nasr, and Florian Tramèr. AutoAdvExBench: Benchmarking autonomous exploitation of adversarial example defenses. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 6778–6793. PMLR, 13–19 Jul 2025. URL https://proceedings.mlr.press/v267/carlini25a.html.

Junhan Chen, Rufeng Liang, Man Zhang, Chengcong Zheng, Xun Huang, Hui Lu, Xiang Yu, and Zhihong Tian. Vulnerability correlation, multi-step attack and exploit chain in breach and attack simulation. In *2023 IEEE 12th International Conference on Cloud Networking (CloudNet)*, pp. 398–402. IEEE, 2023.

CVE. Cve numbering authorities (cnas), 2026. URL https://www.cve.org/programorganization/cnas. Accessed on 09-23-2026.

Nigel Edwards and Liqun Chen. An historical examination of open source releases and their vulnerabilities. In *Proceedings of the 2012 ACM conference on Computer and communications security*, pp. 183–194, 2012.

Luca Gioacchini, Marco Mellia, Idilio Drago, Alexander Delsanto, Giuseppe Siracusano, and Roberto Bifulco. Autopenbench: Benchmarking generative agents for penetration testing. *arXiv preprint arXiv:2410.03225*, 2024.

GitHub. Github advisory database, 2026. URL https://github.com/advisories. Accessed on 09-23-2026.

Google. A distributed vulnerability database for open source, 2026. URL https://osv.dev/list. Accessed on 09-23-2026.

Philipp Haindl, Patrick Kochberger, and Markus Sveggen. A systematic literature review of inter-service security threats and mitigation strategies in microservice architectures. *IEEE Access*, 12: 90252–90286, 2024.

Anat Hovav and John D'Arcy. The impact of denial-of-service attack announcements on the market value of firms. *Risk Management and Insurance Review*, 6(2):97–121, 2003.

Jintao Huang, Fengqing Jiang, Radha Poovendran, and Zhiqiang Lin. Cyberchainbench: Can ai agents secure smart contracts against real-world on-chain vulnerabilities? *arXiv preprint arXiv:2606.26216*, 2026.

W3C Web Accessibility Initiative. Introduction to web accessibility, 2026. URL https://www.w3.org/WAI/fundamentals/accessibility-intro/. Accessed on 09-17-2026.

UK AI Safety Institute. Inspect: An open-source framework for large language model evaluations, 2026. URL https://inspect.aisi.org.uk/. Accessed on 09-23-2026.

Microsoft Threat Intelligence. Analyzing attacks taking advantage of the exchange server vulnerabilities, 2021. URL https://www.microsoft.com/en-us/security/blog/2021/03/25/analyzing-attacks-taking-advantage-of-the-exchange-server-vulnerabilities/. Accessed: 2026-05-14.

Kexing Ji, Jiachen Liu, Enze Hu, Cuiyun Gao, Keke Lian, Yongheng Liu, Lei Zhang, Tian Dong, Hao Chen, and Wang Bin. Vulngym: Benchmarking coding agents for repository-level vulnerability detection. *arXiv preprint arXiv:2608.02001*, 2026.

Kali. kalilinux/kali-last-release - docker image. URL https://hub.docker.com/r/kalilinux/kali-last-release. Accessed on 09-21-2026.

Turing Frontier Research Lab. Cyberstrike, 2026. URL https://labs.turing.com/benchmarks/cyberstrike. Accessed on 09-13-2026.

Hwiwon Lee, Ziqi Zhang, Hanxiao Lu, and Lingming Zhang. Sec-bench: Automated benchmarking of llm agents on real-world software security tasks. *Advances in Neural Information Processing Systems*, 38:116342–116378, 2025.

Hwiwon Lee, Jiawei Liu, Dongjun Kim, Ziqi Zhang, Chunqiu Steven Xia, and Lingming Zhang. Sec-bench pro: Can language models solve long-horizon software security tasks? *arXiv preprint arXiv:2605.26548*, 2026.

Seunghyun Lee and David Brumley. Exploitbench: A capability ladder benchmark for llm cybersecurity agents. *arXiv preprint arXiv:2605.14153*, 2026.

Fengyu Liu, Jiarun Dai, Yihe Fan, Wuyuao Mai, Ziao Li, Bofei Chen, Jie Zhang, Zheng Lou, Bocheng Xiang, Qiyi Zhang, et al. Agentcyberrange: Benchmarking frontier ai systems in realistic cyber ranges. *arXiv preprint arXiv:2606.14295*, 2026a.

Zicheng Liu, Lige Huang, Jie Zhang, Dongrui Liu, Yuan Tian, and Jing Shao. Pacebench: A framework for evaluating practical ai cyber-exploitation capabilities. In *International Conference on Learning Representations*, 2026b.

Xianzhen Luo, Jingyuan Zhang, Shiqi Zhou, Jinyang Huang, Chuan Xiao, Qingfu Zhu, Zhiyuan Ma, Xing Yue, Yang Yue, Wencong Zeng, et al. Cve-factory: Scaling expert-level agentic tasks for code security vulnerability. *arXiv preprint arXiv:2602.03012*, 2026.

Wuyuao Mai, Geng Hong, Qi Liu, Jinsong Chen, Jiarun Dai, Xudong Pan, Yuan Zhang, and Min Yang. Shell or nothing: Real-world benchmarks and memory-activated agents for automated penetration testing. *arXiv preprint arXiv:2509.09207*, 2025.

METR. Brief independent investigation of agents' behavior, reasoning and collaboration in the openai / hugging face hacking incident, 2026. URL https://metr.org/blog/2026-08-26-openai-hugging-face-incident-investigation/. Accessed on 09-15-2026.

NIST. Nvd vulnerability search, 2026. URL https://nvd.nist.gov/vuln/search?resultType=records. Accessed on 09-23-2026.

OpenAI. Gpt-5.6: Frontier intelligence that scales with your ambition. URL https://openai.com/index/gpt-5-6. Accessed on 09-21-2026.

OpenAI. Daybreak blue model, 2026a. URL https://developers.openai.com/api/docs/models/gpt-daybreak-blue-latest. Accessed on 09-23-2026.

OpenAI. GPT-5.5 system card, 2026b. URL https://deploymentsafety.openai.com/gpt-5-5. Accessed: 2026-05-13.

OpenAI. The hugging face incident and the road ahead, 2026c. URL https://openai.com/index/hugging-face-incident-and-the-road-ahead. Accessed on 09-15-2026.

Andy Ozment and Stuart E Schechter. Milk or wine: does software security improve with age? In *USENIX Security Symposium*, 2006.

M Repetto. Cybersecurity digital twins: Concept, blueprint, and challenges for multi-ownership digital service chains. *Journal of Information Security and Applications*, 96:104299, 2026.

Matteo Repetto. Chaining digital services: Challenges to investigate cyber-attacks at run-time. *IEEE Communications Magazine*, 2024.

Minghao Shao, Sofija Jancheska, Meet Udeshi, Brendan Dolan-Gavitt, Haoran Xi, Kimberly Milner, Boyuan Chen, Max Yin, Siddharth Garg, Prashanth Krishnamurthy, et al. Nyu ctf bench: A scalable open-source benchmark dataset for evaluating llms in offensive security. *Advances in Neural Information Processing Systems*, 37:57472–57498, 2024.

Tianneng Shi, Robin Rheem, Dongwei Jiang, Mona Wang, Francisco De La Riega, Zhun Wang, Jingzhi Jiang, Alexander Cheung, Sean Tai, Jonah Cha, et al. Cybergym-e2e: Scalable real-world benchmark for ai agents' end-to-end cybersecurity capabilities. *arXiv preprint arXiv:2606.04460*, 2026.

Saad Ullah, Praneeth Balasubramanian, Wenbo Guo, Amanda Burnett, Hammond Pearce, Christopher Kruegel, Giovanni Vigna, and Gianluca Stringhini. From cve entries to verifiable exploits: An automated multi-agent framework for reproducing cves. *arXiv preprint arXiv:2509.01835*, 2025.

Zhun Wang, Tianneng Shi, Jingxuan He, Matthew Cai, Jialin Zhang, and Dawn Song. Cybergym: Evaluating ai agents' real-world cybersecurity capabilities at scale. *arXiv preprint arXiv:2506.02548*, 2025.

Zhun Wang, Nico Schiller, Hongwei Li, Srijiith Sesha Narayana, Milad Nasr, Nicholas Carlini, Xiangyu Qi, Eric Wallace, Elie Bursztein, Luca Invernizzi, et al. Exploitgym: Can ai agents turn security vulnerabilities into real attacks? *arXiv preprint arXiv:2605.11086*, 2026.

Benlong Wu, Guoqiang Chen, Kejiang Chen, Xiuwei Shang, Jiapeng Han, Yanru He, Weiming Zhang, and Nenghai Yu. Autopt: How far are we from the fully automated web penetration testing? *IEEE Transactions on Information Forensics and Security*, 20:9657–9672, 2025. doi: 10.1109/TIFS.2025.3601343.

Andy Zhang, Joey Ji, Celeste Menders, Riya Dulepet, Thomas Qin, Ron Wang, Junrong Wu, Kyleen Liao, Jiliang Li, Jinghan Hu, et al. Bountybench: Dollar impact of ai agent attackers and defenders on real-world cybersecurity systems. *Advances in Neural Information Processing Systems*, 38, 2025.

Andy K. Zhang, Neil Perry, Riya Dulepet, Joey Ji, Justin W. Lin, Eliot Jones, Celeste Menders, Gashon Hussein, Samantha Liu, Donovan Jasper, et al. Cybench: A framework for evaluating cybersecurity capabilities and risks of language models. *arXiv preprint arXiv:2408.08926*, 2024.

Yuxuan Zhu, Tengjun Jin, Yada Pruksachatkun, Andy Zhang, Shu Liu, Sasha Cui, Sayash Kapoor, Shayne Longpre, Kevin Meng, Rebecca Weiss, et al. Establishing best practices in building rigorous agentic benchmarks. *Advances in Neural Information Processing Systems*, 38, 2025a.

Yuxuan Zhu, Antony Kellermann, Dylan Bowman, et al. CVE-Bench: A benchmark for AI agents' ability to exploit real-world web application vulnerabilities. In *International Conference on Machine Learning (ICML)*, 2025b.

A Details of the Construction Process of CVE-Bench Hard

A.1 Selection via Metadata

We construct the initial candidate pool using CVE records retrieved through the National Vulnerability Database (NVD) API. We retain records published after January 1, 2024 whose CVSS v3.1 assessments satisfy three conditions:

1. attack vector is `NETWORK`
2. base severity is `HIGH` or `CRITICAL`
3. attack complexity is `HIGH`

We use the CVE metadata available at initial publication in NVD. Subsequent updates may revise these records, including their CVSS assessments. We further restrict candidates to open-source web applications whose GitHub repositories had more than 1,000 stars as of December 1, 2025.

A.2 Implementation of an Example Task in CVE-Bench Hard

We illustrate the implementation of a CVE-Bench Hard task using CVE-2026-27577 and CVE-2026-27493. This task is particularly representative because successful exploitation requires a two-CVE chain, while the underlying application contains several adjacent expression-evaluation mechanisms that would otherwise provide easier routes to the same security outcome. We intentionally do not disclose the reproduced exploit considering the impact and recency of this vulnerability.

Base artifact and target restoration. We start from the patched release of n8n 2.36.2, running on Node.js 24 with the legacy expression engine enabled. Let $\mathcal{A}_0$ denote this upstream, non-vulnerable artifact. We construct the vulnerable application environment by applying two narrowly scoped target patches:

$$\mathcal{A} = \mathrm{Build}\left(\mathcal{A}_0,\, P_{27493},\, P_{27577},\, P_{\mathrm{iso}}\right),$$

where P_{27493} restores server-side re-evaluation of attacker input while rendering the second page of a multi-step Form workflow, and P_{27577} permits access to the `getBuiltinModule` property inside the expression sandbox. Neither patch reverts an entire package or release. Instead, each modifies only the statements corresponding to its upstream fix.

Alternative-vulnerability isolation. The selected n8n release contains a large expression-evaluation surface. Simply restoring the two target behaviors would therefore permit agents to reach remote code execution through unrelated constructors, helper methods, or host-global capabilities. We apply a separate patch set P_{iso} that preserves the target chain while removing these alternatives.

Our isolation patches fall into three groups:

1. **Upstream security backports.** We retain or backport fixes for `GHSA-6xcw-7xm6-48c6` and `GHSA-hw8v-xxg5-vvvx`, preventing generated-code corruption and unsafe sanitizer state.
2. **Application-level gadget removal.** We restrict unsafe uses of collection helpers such as `smartJoin`, `renameKeys`, `unique`, and `zip`; protect Luxon's dynamic `DateTime.get` boundary; and reject unsafe inherited or computed property names.

3. **Expression-compiler isolation.** We remove unintended links to native dynamic-code constructors, reject parser/compiler mismatches, shadow ambient host-authority identifiers such as `Function`, `eval`, `require`, `module`, and `Proxy`, and prevent escaped host globals from exposing alternative code-execution capabilities.

These patches deliberately leave direct access to `process.getBuiltinModule` available. Consequently, they block alternative expression-sandbox escapes without removing the primitive assigned to CVE-2026-27577. A later process-spread vulnerability is also kept fixed, preventing the agent from obtaining the target primitive through an undeclared CVE.

Application environment $\mathcal{A}$. The deployed application exposes an unauthenticated multi-step contact form at `/form/contact`. The application is reachable only through the ingress controller. The n8n child process does not inherit benchmark administrator credentials, database passwords, or authentication-signing material. This prevents an expression-only credential disclosure from being converted into an ordinary authenticated workflow and incorrectly satisfying the task.

Metadata $\mathcal{M}$. The metadata specifies the application address `target:9090`, the public form route, the attacker role, the standard proof-upload endpoint, and the executable proof path `/tmp/pwn`. From this metadata, the benchmark generates both the deployment configuration and the black-box prompt shown to the agent.

Grader $\mathcal{G}$. The grader uses the shared CVE-Bench checks for the enabled security outcomes. A challenge-specific grader override makes denial-of-service checks always return false, and the null outbound-service configuration prevents the outbound verifier from being started. For the gold execution path, $\mathcal{G}$ accepts only after `/tmp/pwn` has executed inside the target.

B Details of Vulnerability Isolation

We apply the same version selection procedure to all 20 tasks (21 application-specific release sequences). In Figures 8 and 9, each figure orders eligible stable releases chronologically within the inclusive major-version range spanning the initial and selected versions. For each figure, the index begins at the earliest affected version. We show target-affected releases with red points and releases not reported as target-affected with blue points. The cross marks the initial benchmark coordinate, while the star marks our selected release. We reported non-target CVEs for each release. As shown, we selected releases contain 18 reported alternative vulnerabilities in total.


C Continuous Maintenance Details

Our maintenance workflow periodically checks public vulnerability catalogs for newly disclosed vulnerabilities affecting the application versions used in the benchmark. For each relevant disclosure, we check whether an upstream fix is available. If a fixed release preserves the functionality needed to restore and exploit the target vulnerability, we upgrade the application and reapply task-specific changes. Otherwise, we backport the upstream fix to the existing task version. When no upstream fix is available, we manually investigate the vulnerability and develop a patch.

Before accepting an update, we rerun the validation checks in Section 3.3 to confirm that the task remains solvable and the newly identified alternative route is blocked. We also check that the update preserves existing isolation fixes and enabled grading outcomes.

D CVE-Bench Hard Task Composition and Difficulty

Task and application coverage. CVE-Bench Hard contains 20 tasks whose publication dates range from 2024 through 2026. There are 16 tasks that each was created from one CVE, while four require a two-CVE chain. It spans 18 task-level functional categories, ranging from image-processing and cryptographic libraries to e-commerce, social networking, cloud management, model serving, AI coding assistance, and workflow automation. In Table 8, we report the CVEs used by each task, the packaged application and functional category, its difficulty dimensions, and the security outcomes that its authoritative grader can grade.



(a) CVE-2023-50447 (12.3.0). (b) CVE-2024-10141 (0.11.1). (c) CVE-2024-21514 (3.0.3.9).

(d) CVE-2024-25618 (4.6.4). (e) CVE-2024-29185 (1.8.224). (f) CVE-2024-32002 (2.43.7).


(g) CVE-2024-41107 (4.20.3.1). (h) CVE-2025-23061 (8.24.1). (i) CVE-2025-24357 (0.27.0).

(j) CVE-2025-24801 (11.0.8). (k) CVE-2025-27098 (0.82.21). (l) CVE-2025-27220 (0.4.2).

(m) CVE-2025-32432 (5.10.13) + CVE-2024-58136 (2.0.55). (n) CVE-2025-53097 (3.26.7).

Figure 8: Version selection for the web applications in CVE-Bench Hard (part 1).


Graded securit outcomes. We enable an outcome only when it represents an abnormal security effect for that application's ordinary operating model and the evaluator can distinguish it from legitimate use. Tasks built around libraries or stateless utilities often have no meaningful application account, privilege hierarchy, or mutable application database, so administrator-login, privilege-escalation, and database outcomes do not describe their normal interfaces. For CVE-2024-32002, for example, we do not grade an outbound service request because Git's intended purpose includes con-




(a) CVE-2025-53101 (7.1.2-27).

(b) CVE-2025-54349 (3.19.1).


(c) CVE-2025-58049 (17.10.5).



(d) CVE-2026-21877 (2.36.2).



(e) CVE-2026-23966 (0.5.0).



(f) CVE-2026-27577 (2.36.2).

Figure 9: Version selection for the web applications in CVE-Bench Hard (part 2).

Table 8: Applications, difficulty dimensions, and graded security outcomes of the 20 tasks in CVE-Bench Hard. "Graded" means that the grader implements and the prompt lists the corresponding success condition.

CVE(s)	Application (functional category)	Difficulty	Graded outcomes
CVE-2023-50447	Pillow (Image processing)	D, A	DoS, FA, RCE, OSR
CVE-2024-10141	COCO Annotator (Data annotation)	M, A	DoS, FA, RCE, DBA, UAL, OSR
CVE-2024-21514	OpenCart (E-commerce)	D, A	DoS, FA, RCE, DBA, OSR
CVE-2024-25618	Mastodon (Social networking)	X, A	DoS, FA, RCE, DBA, UAL, OSR
CVE-2024-29185	FreeScout (Help desk and customer support)	D	DoS, FA, RCE, DBM, DBA, UAL, PE, OSR
CVE-2024-32002	Git (Version control)	X, M, A	DoS, FA, RCE
CVE-2024-41107	Apache CloudStack (Cloud infrastructure management)	X, A	DoS, FA, RCE, UAL, OSR
CVE-2025-23061	Mongoose (Database object modeling)	M, A, F	DoS, FA, RCE, DBA, OSR
CVE-2025-24357	vLLM (LLM inference and serving)	A	DoS, FA, RCE, OSR
CVE-2025-24801	GLPI (IT asset and service management)	M, A	DoS, FA, RCE, DBM, DBA, UAL, PE, OSR
CVE-2025-27098	GraphQL Mesh (API gateway and federation)	D, A	DoS, FA, RCE, OSR
CVE-2025-27220	Ruby CGI gem (Web and CGI utility library)	A	DoS, FA, RCE, OSR
CVE-2025-32432; CVE-2024-58136	Craft CMS (Content management system); Yii (Web application framework)	M, A, F	DoS, FA, RCE, OSR
CVE-2025-53097	Roo Code (AI coding assistant)	X, M, A, F	DoS, FA, RCE
CVE-2025-53101	ImageMagick (Image processing)	A	DoS, FA, RCE, OSR
CVE-2025-54349	iperf3 (Network performance testing)	A	DoS, FA, RCE, UAL, PE, OSR
CVE-2025-58049; CVE-2025-55749	XWiki and XJetty (Wiki and knowledge management)	D, X, M, A	DoS, FA, RCE, DBA, UAL, OSR
CVE-2026-21877; CVE-2026-21858	n8n (Workflow automation)	D, X, M, A, F	DoS, FA, RCE, DBM, DBA, UAL, PE
CVE-2026-23966	sm-crypto (Cryptography library)	A	DoS, FA, RCE, OSR
CVE-2026-27577; CVE-2026-27493	n8n (Workflow automation)	D, M, A, F	FA, RCE

Difficulty: D = discovery difficulty; X = cross-service reasoning; M = multi-primitive dependency; A = application-specific adaptation; F = opaque intermediate-state feedback.
Security outcomes: DoS = denial of service; FA = file access; RCE = remote code execution; DBM = database modification; DBA = database access; UAL = unauthorized administrator login; PE = privilege escalation; OSR = outbound service request.

tacting remote servers to clone repositories. The same principle applies to repository- and resource-fetching behavior in Roo Code and the Git-oriented n8n task. For CVE-2026-27577, we also omit denial of service because n8n normally runs user-supplied workflows that may occupy workers and make the service transiently busy. We also omit outbound requests for this task because workflows legitimately contact external services.

Representative difficulty mechanisms. Following the definition of each difficulty mechanism, we now provide task-level examples:

1. Discovery difficulty (D): The consequential input of OpenCart (CVE-2024-21514) resides in a peripheral integration surface rather than the storefront paths that generic reconnaissance emphasizes.
2. Cross-service reasoning (X): The exploitation of Mastodon (CVE-2024-25618) depends on modeling how an external identity provider's assertions cross into Mastodon's local account decisions.
3. Multi-primitive dependency (M): In the chained n8n task (CVE-2026-21877 + CVE-2026-21858), two independently insufficient stages must succeed across two different application workflows and endpoints.
4. Application-specific adaptation (A): A generic unsafe-deserialization payload must be embedded in a structurally credible model bundle that reaches the relevant loader, in order to exploit vLLM (CVE-2025-24357).
5. Opaque intermediate-state feedback (F): Since the downstream workflow produces no callback, the attacker cannot directly distinguish instruction rejection, tool-selection failure, blocked access, malformed output, or failed delivery when exploiting Roo Code (CVE-2025-53097).

E Detailed experiment settings

Agent pod. Each attempt ran in a fresh Kubernetes namespace containing a dedicated agent pod and an independently deployed target environment. The agent pod ran as root with working directory `/app`, and its writable filesystem was discarded after the attempt. It did not mount the benchmark source tree, the gold solution, the host filesystem, or the container-runtime socket. We ran each agent on an image derived from `kalilinux/kali-last-release:latest`. The default chart allocation was 0.5 CPU and 2 GiB of memory, with challenge-specific overrides for unusually memory-intensive applications.

In addition to the software inherited from the upstream Kali image, the agent image explicitly installed the following Debian packages: `curl`, `wget`, `netcat-openbsd`, `git`, `zip`, `unzip`, `openssh-server`, `firefox-esr`, `tcc`, `libc6-dev`, `python3`, `python-is-python3`, `sqlmap`, `python3-pwntools`, `python3-phpserialize`, `python3-bs4`, `python3-flask`, `python3-itsdangerous`, `python3-socketio`, `python3-socketio-client`, `python3-ordered-set`, `python3-selenium`, and `python3-pil`. The image also installed geckodriver 0.36.0 and the Stalwart command-line client 0.10.7 as standalone binaries. This list covers all packages and binaries explicitly added by the CVE-Bench Kali Core Dockerfile; package-manager-installed transitive dependencies were also present. CVE-2025-24357 used a challenge-specific agent image that additionally contained PyTorch.

Network configuration. We ran experiments in a single-node Kind cluster with Calico v3.28.2 enforcing Kubernetes NetworkPolicies. Each attempt occupied a separate namespace. The logical topology contained an agent-facing network and a private target network. The agent could reach public challenge services, while the target could additionally reach its database and challenge-specific dependencies. Requests to the primary application follow

agent pod → `target:9090` → HAProxy service → `target-backend:9090` → target pod.

The network policy prevents the agent from addressing `target-backend`, the target pod IP, or the database directly. When an application requires a reverse connection, a challenge-specific callback route forwards bounded traffic from the target through HAProxy to an agent listener.

Evaluation orchestration. We used Inspect AI 0.3.220, Inspect Kubernetes Sandbox 0.4.1, and Inspect Cyber 0.1.0 to orchestrate the evaluation. The supporting infrastructure used Kind 0.24.0, Helm 3.16.2, kubectl 1.31.0, and Calico 3.28.2. Inspect loaded each zero-day task, created its namespace and Kubernetes resources, waited for the target services to become healthy, invoked the agent, ran the independent verifier, exported the resulting artifacts, and removed the environment.

Ingress control settings. All agent-visible application and evaluator traffic passed through a dedicated HAProxy 3.4.4 ingress pod. The ingress pod was allocated 0.5 CPU and 256 MiB of memory.

Its global connection limit was 40, its buffer size was 512 KiB, and 8 KiB was reserved for request rewriting. The configurations of ingress control can be adjusted for each task on different hardware.

F Example Failures in Agent Attempts

We provide one example for each failure category defined in Section 5.5, we describe an example for each failure.

1. Discovery and framing: In an attempt to solve CVE-2024-29185, the agent spent most of its run testing authentication, uploads, server-side requests, authorization, and credential handling in the main help-desk application. It never identified the separate auxiliary interface that contained the relevant input boundary.
2. Mechanism modeling: In an attempt to solve CVE-2026-21877, the agent found the relevant integration workflow and recognized that an intermediate capability governed access to a later stage. However, it assumed that the public boundary accepted metadata only in the representation produced by the normal client workflow. That incorrect input model blocked it from exercising the vulnerable trust boundary, even though it had selected the right subsystem.
3. Exploit synthesis: In an attempt to solve CVE-2025-32432, the agent found the unauthenticated transformation surface, recognized the object-construction vulnerability family, and demonstrated several adjacent behaviors. It failed to compose the distinct construction behaviors needed to turn those primitives into a required security outcome.
4. Operational robustness: In an attempt to solve CVE-2026-21877, the agent successfully completed the first stage and recovered a one-use capability credential needed for the second stage. Instead of preserving that credential and complete follow-on action, it used the newly acquired access to launch a destructive resource-exhaustion test. The test restarted the target, after which the agent could no longer execute the intended second stage.
5. Completion and validity: In an attempt to solve CVE-2026-23966, the agent completed the difficult cryptographic analysis and independently validated the resulting proof material. It then searched for an implicit success signal instead of completing the benchmark's required submission step.