CONV-TO-BENCH: EXPLORING AUTOMATED BENCHMARK CONSTRUCTION FROM CONVERSATIONAL TRACES

Anonymous authors
Paper under double-blind review

ABSTRACT

The continuous advancement of large language models requires robust, scalable benchmarking. Traditional benchmark creation relies on expensive expert curation, while prior automated methods focus primarily on single-turn interactions and rely heavily on proprietary models. We introduce Conv-to-Bench, a multi-stage framework that automatically transforms authentic human–LLM dialogues into self-contained instructions paired with fine-grained, verifiable requirement checklists using open-weight models for construction and judging. Moving beyond single-turn queries, our pipeline captures multi-turn user refinements to formulate realistic evaluation criteria. Across an aligned 19-model roster evaluated against Arena AI human preferences, Conv-to-Bench achieves comparable rank correlation with human judgments and Brier scores relative to Arena-Hard-Auto, a widely used automated benchmark ($\rho = 0.926$–0.946 vs. 0.916; Brier $= 0.053$–0.069 vs. 0.092), without proprietary API reliance. Ablation experiments demonstrate that atomic checklist verification significantly outperforms pairwise comparisons across Spearman correlation ($+0.146$), separability ($+22.8$ pp), agreement ($+31.7$ pp), and Brier score (-0.1055). Incorporating multi-turn refinements yields mixed results: Spearman correlation point estimates improve across all LLM judges, but significant gains in correlation and Brier score occur for only one individual judge. Conv-to-Bench builds a 500-instruction benchmark for \$19.05 and evaluates candidate models for \$1.62 each on hosted infrastructure. Together, these results show that open-weight models can build benchmarks that recover human preference rankings from conversational data, enabling their application in lower-budget settings.

1 INTRODUCTION

Robust evaluation benchmarks are essential for measuring progress and ensuring the reliability of Large Language Models (LLMs). While gold standard suites such as HumanEval (Chen et al., 2021), BigCodeBench (Zhuo et al., 2025), GPQA (Rein et al., 2024), and Humanity's Last Exam (Phan et al., 2026) offer rigorous assessments, their reliance on expert authoring creates a severe bottleneck for scalable evaluation across emerging domains.

Organizations deploying LLM-powered products accumulate logs of real user interactions, which are already mined to characterize user intents and satisfaction (Shah et al., 2025; Wan et al., 2024; Lin et al., 2024), and could further inform decisions such as model selection or harness refinement. Public collections of user–LLM conversations, such as LMSYS-Chat-1M (Zheng et al., 2024) and WildChat (Zhao et al., 2024), offer an open counterpart, capturing implicit feedback, iterative clarifications, and evolving constraints (Don-Yehiya et al., 2024). They have naturally become a source for validating automated benchmark construction: BenchBuilder (Li et al., 2025), for instance, derives Arena-Hard-Auto from them, yet relies primarily on proprietary models, single-turn prompts, and pairwise comparisons against a baseline.

We explore whether reliable benchmarks can be constructed automatically from interaction traces by leveraging multi-turn user refinements and atomic checklist verification, using exclusively open weight models. We introduce Conv-to-Bench, a multi stage framework (Figure 1) that transforms

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: **Overview of the framework.** The three-phase pipeline spans conversation selection and filtering, instruction and checklist synthesis, and model evaluation and ranking.

raw dialogues into self contained instructions paired with atomic verification checklists. Moving beyond single turn queries, we analyze dialogue evolution by contrasting single turn prompts with multi-turn refinements, while testing whether granular checklist verification outperforms holistic pairwise judging under open model execution.

Our primary contributions are threefold. First, we present an automated, low-cost pipeline that converts human–LLM dialogues into benchmark instructions and verification checklists using only open-source models. Second, through a paired ablation, we isolate the impact of multi-turn user refinements by evaluating model performance on refined instructions versus initial base instructions. Third, we investigate the transition from pairwise comparisons to atomic checklist verification, quantifying gains in ranking alignment, separability, and calibration.

2 Related Work

Building high-quality benchmarks has traditionally relied on expert effort, which limits scalability. HumanEval (Chen et al., 2021) required 164 hand-written problems to avoid data contamination, and BigCodeBench (Zhuo et al., 2025) took 20 authors about a year, with 75% of annotators having over five years of Python experience. Beyond coding, GPQA (Rein et al., 2024) and Humanity's Last Exam (Phan et al., 2026) rely on subject matter experts with advanced academic backgrounds to write and validate extremely challenging questions. While these benchmarks remain gold standards, such expert involvement is hard to scale to the wide range of emerging user-centric tasks, especially for non-frontier companies building AI-powered products.

A natural alternative to expert authoring is to derive tasks from real user interactions. In industry, deployment logs are already analyzed with LLMs to build user intent taxonomies and estimate satisfaction (Shah et al., 2025; Wan et al., 2024; Lin et al., 2024), while public collections such as LMSYS-Chat-1M (Zheng et al., 2024) and WildChat (Zhao et al., 2024) release millions of user–LLM dialogues, over 40% of which are multi-turn in WildChat. However, extracting reliable signals from such logs is difficult: conversational feedback can be noisy, especially for complex reasoning (Liu et al., 2025), and naive heuristics such as dialogue length can reward undesirable behaviors like unfriendly or controversial outputs (Pang et al., 2024). Rather than relying on such implicit signals directly, we turn user refinements into verifiable, fine-grained evaluation criteria, using crowdsourced conversations to demonstrate a pipeline that organizations can apply to their own data.

To evaluate model responses at scale, LLM judges have been widely adopted (Zheng et al., 2023; Bai et al., 2024; Lin et al., 2025). BenchBuilder (Li et al., 2025) applies LLM judges to crowdsourced data, using primarily proprietary models to select challenging single-turn prompts for benchmarks such as Arena-Hard-Auto, where models are compared pairwise against a baseline. We extend this direction with Conv-to-Bench, which addresses these three choices in turn: it incorporates multi-

turn user refinements to capture evolving constraints, replaces pairwise judging with fine-grained checklist verification, and uses only on open-weight models, comparing the two in terms of ranking alignment, separability, and calibration.

3 CONV-TO-BENCH FRAMEWORK

The Conv-to-Bench framework automates benchmark creation directly from human–LLM interaction traces. To eliminate manual curation and scale efficiently, the pipeline executes in four stages: dialogue filtering, instruction synthesis, checklist construction, and answer grading.

3.1 FILTERING AND CURATION

Raw conversational logs contain substantial noise and low-quality dialogues (Li et al., 2025). Instead of sampling conversations at random or incurring high costs to inspect the entire corpus with language models, we combine semantic clustering with adaptive sampling and multi-stage filtering.

Topic Clustering. To measure and control topic diversity, initial user messages are projected into a vector space and grouped into semantic clusters. Grouping dialogues this way reveals the topical distribution of the source data, allowing us to balance selections and prevent a small number of topics from dominating the generated benchmark.

Bandit-Based Sampling. Using these identified clusters, we frame cluster selection as a multi-armed bandit problem (Auer et al., 2002; Sutton & Barto, 2018) to balance topical diversity against LLM evaluation costs. The bandit dynamically updates sampling weights based on cluster pass rates in downstream verification checks. Clusters yielding frequent rejections are sampled less often to save compute, while a satiety penalty downweights repeatedly successful clusters to encourage coverage of underrepresented topics. Appendix A details the formal update rules.

Multi-Stage Filtering. Conversations selected by the bandit pass through a six-stage sequential review evaluated across all user turns (Appendix B). A dialogue is retained only if it meets every condition: (1) an optional deterministic language filter, such as an English gate, followed by LLM-based checks for (2) safety and policy compliance (excluding jailbreaks, injections, toxicity, and malicious content), (3) prompt precision (requiring unambiguous constraints and well-defined output formats), (4) domain knowledge requirements (demanding mastery of specialized disciplines beyond basic trivia), (5) multi-layered nuance (verifying multi-step logic, trade-offs, or multiple sub-tasks), and (6) problem-solving capacity (demanding systematic diagnosis or analysis beyond direct lookup). The stages are ordered from simplest to most demanding, and evaluation stops immediately if a conversation fails any step, filtering out noise quickly and minimizing unnecessary model calls.

3.2 INSTRUCTION SYNTHESIS

Base and Refined Instruction Extraction. Once conversations pass the multi-stage filtering, the extraction process adapts to dialogue length. When a dialogue consists of a single turn, an LLM directly extracts the user's core request from the initial message (Appendix C.1). For multi-turn conversations (more than one question and answer), an LLM synthesizes a single, complete instruction that captures the progression of the interaction. In these extended dialogues, users often provide an initial query followed by sequential refinements, constraints, rephrasings, or clarifications as they interact with the model, which gradually makes the request more specific and detailed. This synthesis stage is especially critical for multi-turn dialogues because it condenses the entire back-and-forth exchange into a unified prompt format without losing essential requirements. To systematically analyze the impact of interaction depth in our research, we formalize two distinct instruction types: a *base instruction*, which reflects the initial prompt formulated before any assistant response (capturing a single-turn query format), and a *refined instruction*, which merges that initial prompt with all subsequent user refinements to capture multi-turn interaction dynamics (Appendix C.2, C.3).

Quality Assurance via Self-Correction. To ensure the validity of the synthesized instructions, the framework embeds review and repair loops. These prompt-guided review nodes inspect the instructions for two primary failure modes: incomplete extraction of user refinements and poor self-containment. First, an audit checks that all refinements requested by the user across later turns were

captured and integrated accurately (Appendix C.4). A second loop evaluates base and refined instructions for strict self-containment (Appendix C.5): the final instruction must explicitly include all necessary context, code snippets, and operational parameters so a model can solve it independently without reading the original dialogue history. If an instruction fails either check, the framework routes it back to the synthesis prompt for targeted re-generation, bounded by a fixed retry limit.

3.3 Checklist Synthesis

The final stage converts synthesized instructions into evaluation checklists using a structured generate-and-review procedure applied equally to both base and refined instructions.

Checklist Items Extraction. An LLM extracts candidate checklist items directly from the instruction text. Every item must be logically derivable from the instruction, preventing the introduction of unstated preferences or external assumptions. Items are formulated as unambiguous, single-condition Yes/No questions. Rather than performing superficial presence checks (e.g., merely verifying if error handling exists), the items evaluate specific implied edge cases, malformed-input handling, and concrete observable outcomes.

Review and Refinement. An LLM inspects extracted items in fixed batches, assigning each item to one of three actions: approve, remove, or rewrite. The model approves valid user requirements and edge cases, removes out of scope criteria, and rewrites items imposing unrequested stylistic or implementation preferences to target only required outcomes. Rewritten criteria undergo a secondary review pass for final confirmation, further refinement, or removal. Appendix D details the synthesis and review prompts.

3.4 Scoring

Grading Protocol. To evaluate model responses efficiently, the framework groups individual checklist items into batches before submitting them to the LLM judge (Appendix E.1). This design provides the judge with sufficient local context without overloading the context window, while significantly reducing the number of LLM calls.

Per-Conversation Normalization. Because some instructions may contain significantly more atomic requirements, evaluating purely at the item level would allow lengthy checklists to disproportionately dominate the global score. To prevent this bias, the method normalizes scores per conversation. The final performance estimate for a given model is computed as an unweighted average of its conversation-level scores. Each conversation score is the fraction of scorable items satisfied, where an item is scorable when the judge returned a boolean verdict.

4 Experimental Design and Implementation

This section outlines the experimental setup for Conv-to-Bench, covering dataset details, alignment with human preferences and established benchmarks, design ablations, and topic coverage analysis.

4.1 Dataset and Implementation Details

Framework Implementation. The underlying interaction traces originate from two publicly available datasets of natural human–model dialogues: WildChat (Zhao et al., 2024) and LMSYS-Chat-1M (Zheng et al., 2024). Initial user messages are embedded with sentence-transformers (Reimers & Gurevych, 2019) and grouped into topical clusters with BERTopic (Grootendorst, 2022).

A central question of our research is whether high-quality evaluation benchmarks can be constructed entirely using open-weight models, thereby avoiding proprietary API costs and enabling scalable curation over new conversation corpora. Consequently, we employ the open-weight, reasoning-capable gpt-oss family (OpenAI, 2025): multi-stage filtering uses gpt-oss-20b, while instruction synthesis, checklist extraction, and review operations rely on gpt-oss-120b. All benchmark-construction calls use temperature 0.0 to minimize sampling variance and support reproducibility; evaluated models and judges follow their own decoding settings (Section 4.2). To manage execution costs, the self-correction loops for completeness and self-containment are capped at 3 LLM calls per review cycle, and the checklist review node processes items in fixed batch sizes of 3.

Filtering and Final Sampling. Although the initial conversational logs are multi-lingual, we restrict our benchmark to English to maintain consistent evaluation criteria and avoid confounding effects from cross-lingual translation. Conversations are drawn by the cluster-level bandit sampler (Section 3.1) and passed through the multi-stage filter. Since later stages discard some items, we stopped sampling once 539 conversations had been retained (out of 16,731 drawn), leaving a margin above the target benchmark size of 500, chosen to match the size of our automated baseline (Section 4.3). Of these, 26 were lost before sampling, mostly to structural invalidations prior to checklist extraction, but also to malformed entries and failed self-correction. From the resulting pool of 513 validated instructions, we randomly sampled 500 without stratification. The final benchmark comprises 286 refined and 214 base instructions, so that models are evaluated both on well-formed single-turn queries and on requests shaped by real-world multi-turn refinements. All sampling and filtering steps are seeded and reproducible; stage-by-stage attrition and exclusion reasons are reported in Appendix F.

4.2 Model Selection and Evaluation Settings

Evaluated Models. We evaluate 19 models across both closed APIs and open-weight architectures, spanning parameter scales (from 2B to 70B+), model families, and post-training alignments: the GPT family (OpenAI, 2023; 2024) (gpt-3.5-turbo-0125/1106, gpt-4o-2024-05-13, gpt-4o-mini-2024-07-18), Llama (Grattafiori et al., 2024) (3 and 3.1 8B/70B-Instruct), Yi-34B-Chat (01.AI et al., 2024), Starling-LM-7B (Zhu et al., 2024) (α, β), Mistral-7B-Instruct-v0.1 (Jiang et al., 2023), Phi-3 (Abdin et al., 2024) (medium-4k, mini-128k), and Gemma (Gemma Team, 2024a;b) (1.1-2B/7B, 2B, 7B, 2-27B-it). This roster is determined by our external validation references (Section 4.3). All models are evaluated using a unified prompt format and standard default decoding settings.

LLM-as-a-Judge Configuration. Evaluation relies on an LLM-as-a-judge setup with three models: GLM-4.7-Flash (Z.ai (Zhipu AI), 2026; GLM-4.5 Team, 2025), Qwen3.6-27B (Qwen Team, 2026), and Gemma-4-31B-it (Gemma Team, 2026), as well as their ensemble, which aggregates the three judges' verdicts on each checklist item by majority vote. These models were chosen for their strong instruction-following performance, low inference overhead, and architectural diversity across independent open-model families. Each judge operates under its recommended temperature. They independently evaluate all models on both base and refined instructions. We report individual model scores alongside an item-level majority vote, leaving ties and execution failures unscored. For efficiency, each judge call evaluates chunks of four checklist items against the complete response.

4.3 Validation Strategy and Metrics

To validate Conv-to-Bench, we compare model performance against human-preference rankings from live evaluation platforms and established automated benchmark construction frameworks, specifically referencing Arena AI (Chiang et al., 2024) and Arena-Hard-Auto (Li et al., 2025).

External Baselines. We use the Arena AI rankings (under the "Overall" category of the Text Arena leaderboard) as the reference for human preference. For an automated baseline, we compare against Arena-Hard-Auto, an evaluation benchmark consisting of 500 challenging prompts curated by BenchBuilder, an automated benchmark construction framework. To ensure a strict, time-aligned comparison, we freeze snapshots of both references as of 2024-07-31. This alignment yields an intersection of 19 models spanning diverse parameter scales and open/proprietary licenses that appear across our dataset, the Arena-Hard-Auto leaderboard, and the Arena AI rankings. All external validation metrics are computed exclusively on this 19-model intersection.

Statistical Framework. We evaluate both our benchmark and Arena-Hard-Auto (Li et al., 2025) against the Arena AI reference, measuring rank alignment via Spearman's ρ (Spearman, 1904) and Kendall's τ (Kendall, 1938) with 95% bias-corrected and accelerated (BCa) bootstrap confidence intervals ($B = 10{,}000$) (Efron, 1987; Efron & Tibshirani, 1994). For our benchmark, models are evaluated on the exact intersection of conversations graded across all judges, deriving per-model score intervals through clustered bootstrapping at the conversation level ($B = 2{,}000$) (Field & Welsh, 2007). To quantify reliability across all $\binom{19}{2} = 171$ model pairs, we compute the three metrics defined by Li et al. (2025): *Separability* (fraction of pairs with non-overlapping score intervals), *Agreement* (fraction of concordant pairs among those conclusively separated by Arena AI), and *Pair Rank Brier Score* (calibration of pairwise probability estimates against reference outcomes). For

Arena-Hard-Auto and the Arena AI reference, we strictly follow their published bootstrap draws and Bradley–Terry protocols (Bradley & Terry, 1952). Finally, pairwise differences between both benchmarks (Section 5.1) are evaluated using a paired bootstrap across the shared 19-model roster, designating differences significant when their 95% CIs (BCa for correlations, percentile for the remaining metrics) exclude zero.

Coverage Analysis. To examine the composition of the final benchmark, we re-cluster the 500 conversations from scratch instead of carrying over the bandit clusters. Because sampling relied solely on initial messages, here we embed all concatenated user turns using BAAI/bge-base-en-v1.5 (Xiao et al., 2024) and cluster them with BERTopic (Grootendorst, 2022; McInnes et al., 2018; 2017). Cluster labels are assigned manually based on KeyBERT-inspired keywords (Grootendorst, 2020) and three representative documents per cluster. This procedure is strictly descriptive and does not modify the benchmark items. Appendix G details the cluster breakdown and hyperparameters.

4.4 Ablation Studies Setup

We design two independent ablation studies to isolate the contribution of specific design choices in our framework, holding all other experimental conditions constant.

Checklist vs. Pairwise Evaluation Ablation. This ablation isolates the structural impact of checklist decomposition against standard pairwise judging, where an evaluator directly compares candidate outputs against a baseline to assign win, loss, or tie outcomes. We follow Arena-Hard-Auto's style-controlled Bradley–Terry protocol (Bradley & Terry, 1952; Li et al., 2025; Dubois et al., 2024). For our setup, we pair candidate completions against a fixed Qwen3.6-27B reference, a strong open-weight model that provides a stable baseline, and use GLM-4.7-Flash as the judge under the primary judge decoding parameters. Neither model belongs to a family in the evaluated pool, which avoids same-family biases such as self-preference. Operating on identical instructions and completions, this setup tests fine-grained checklist verification against pairwise comparisons.

Base vs. Refined Instruction Ablation. The synthesis framework incorporates user refinements whenever available, under the premise that multi-turn interaction captures critical requirements without degrading checklist quality. To test this premise, we isolate the 286 conversations containing valid multi-turn user refinements and evaluate models across two paired sets: base instructions (derived solely from the initial user turn) and refined instructions (incorporating subsequent user refinements). Each variant is evaluated against its own independently synthesized checklist. Because both variants originate from the exact same underlying conversations, this ablation directly isolates the impact of multi-turn user refinements.

5 Results

We evaluate the proposed framework across structural effectiveness, alignment with human preferences, multi-turn refinement, judge consistency, and open source execution costs. These experiments investigate the practical viability and trade offs of automated benchmark construction.

5.1 Alignment with Human Preferences

We first evaluate how effectively the automatically constructed Conv-to-Bench benchmark aligns with human preference rankings from Arena AI (Table 1). Evaluated across three open-source checklist judges alongside the ensemble, Conv-to-Bench achieves high rank correlations ($\rho = 0.926$–0.946 and $\tau = 0.813$–0.848), solid separability (75.4%–78.4%), consistent agreement (75.8%–78.3%), and well-calibrated probabilities as indicated by low Brier scores (0.0525–0.0694).

Comparing these results with Arena-Hard-Auto highlights complementary behaviors across instruments. In terms of point estimates, Conv-to-Bench yields slightly higher rank correlations ($\Delta\rho = +0.011$ to $+0.030$; $\Delta\tau = +0.058$ to $+0.094$) and improved calibration with lower Brier scores ($\Delta = -0.0228$ to -0.0396). Conversely, Arena-Hard-Auto demonstrates higher separability (85.4% vs. 75.4%–78.4%, with differences of -7.0 to -9.9 pp) and slightly higher agreement on pairs Arena AI distinguishes (79.5% vs. 75.8%–78.3%, with differences of -1.2 to -3.7 pp).

Crucially, none of the paired differences across any of the five metrics reach statistical significance (all 95% confidence intervals span zero). These findings demonstrate that Conv-to-Bench provides a framework built entirely on open-source models that serves as a comparable alternative to Arena-Hard-Auto for predicting human preferences, without claiming absolute dominance.

Table 1: **Conv-to-Bench achieves comparable rank recovery and improved probability calibration relative to Arena-Hard-Auto.** Evaluated on $n = 19$ models across 465 shared instructions against Arena AI. Brackets report 95% CIs; Δ = Conv-to-Bench − Arena-Hard-Auto (bold marks best; no Δ interval excludes zero). ρ and τ are rank correlations, pp is percentage points, and ↑ (↓) indicates higher (lower) is better.

Judge	Spearman ρ ↑	Kendall τ ↑	Separability ↑	Agreement ↑	Brier ↓
Arena-Hard-Auto Li et al. (2025)					
Baseline	0.916 [0.788, 0.982]	0.754 [0.491, 0.889]	**85.4%**	**79.5%**	0.0921
Conv-to-Bench (Ours)					
GLM-4.7-Flash	**0.946** [0.749, 0.993]	**0.848** [0.564, 0.951]	75.4%	75.8%	**0.0525**
Δ	+0.030 [−0.118, +0.147]	+0.094 [−0.097, +0.280]	−9.9 pp [−21.6, +0.6]	−3.7 pp [−17.5, +6.5]	−0.0396 [−0.0902, +0.0096]
Qwen3.6-27B	0.937 [0.714, 0.989]	0.836 [0.550, 0.950]	78.4%	78.3%	0.0694
Δ	+0.021 [−0.153, +0.127]	+0.082 [−0.098, +0.262]	−7.0 pp [−17.5, +1.8]	−1.2 pp [−14.5, +9.0]	−0.0228 [−0.0788, +0.0434]
gemma-4-31B-it	0.926 [0.733, 0.989]	0.813 [0.543, 0.939]	77.2%	77.0%	0.0653
Δ	+0.011 [−0.175, +0.090]	+0.058 [−0.111, +0.204]	−8.2 pp [−19.9, +1.2]	−2.5 pp [−17.2, +8.0]	−0.0268 [−0.0734, +0.0258]
Majority-Vote	0.935 [0.728, 0.989]	0.825 [0.550, 0.948]	77.8%	77.0%	0.0688
Δ	+0.019 [−0.152, +0.122]	+0.070 [−0.101, +0.233]	−7.6 pp [−18.7, +1.8]	−2.5 pp [−15.8, +7.8]	−0.0234 [−0.0749, +0.0367]

5.2 Checklist vs. Pairwise Evaluation

As Table 2 shows, decomposing instructions into verifiable checkpoints yields stronger Arena AI rankings correlations (Spearman ρ $+0.146$, Kendall τ $+0.222$), higher separability ($+22.8$ pp) and agreement ($+31.7$ pp), and a lower Brier score (-0.1055). A paired model-axis bootstrap confirms that four of these five differences are statistically significant at the 5% level (95% CIs excluding zero), demonstrating a distinct structural advantage for fine-grained verification over pairwise comparison. The single exception, Kendall τ, has a 95% interval whose lower bound touches zero, making the difference borderline rather than significant.

To account for length bias (Dubois et al., 2024), we correlate scores with response length after centering both variables per model, which removes the confound that stronger models score higher and write longer responses. Under checklist verification, this within-model correlation is small and negative ($\rho = -0.059$ to -0.068 across judges). Repeating the analysis on the pairwise protocol, with the same judge, models, and responses, yields correlations of the same sign but 1.9–4.2$\times$ larger in magnitude. Neither method rewards verbosity, but checklist scores depend less on response length. The centering procedure is detailed in Appendix H.

Table 2: **Checklist verification outperforms pairwise judging across human-ranking metrics.** Comparison on $n = 19$ models using GLM-4.7-Flash as judge against Arena AI. Δ = Checklist − Pairwise; brackets report 95% confidence intervals (CIs) from a paired bootstrap over models (BCa for correlations, percentile with B=2,000 for others); * marks intervals excluding zero (significant at $\alpha = 0.05$). ρ is Spearman rank correlation, τ is Kendall tau rank correlation, pp denotes percentage points, and ↑ (↓) indicates higher (lower) is better.

Metric	Checklist	Pairwise BT	Δ [95% CI]
Spearman ρ ↑	**0.935** [0.702, 0.989]	0.789 [0.450, 0.924]	$+0.146^*$ [+0.016, +0.421]
Kendall τ ↑	**0.825** [0.491, 0.949]	0.602 [0.265, 0.790]	$+0.222$ [0.000, +0.444]
Separability ↑	**76.6%**	53.8%	$+22.8^*$ pp [+5.2, +36.8]
Agreement ↑	**77.0%**	45.3%	$+31.7^*$ pp [+14.1, +51.6]
Brier Score ↓	**0.0536**	0.1591	-0.1055^* [−0.1958, −0.0266]

5.3 THE IMPACT OF MULTI-TURN REFINEMENT

We evaluate the impact of multi-turn interactions by comparing base instructions against refined instructions incorporating subsequent user refinements (Table 3). Across all three judges and their ensemble, adding refinements yields higher point estimates for correlation with Arena AI: Spearman ρ point estimates improve from 0.886–0.930 to 0.940–0.963 ($\Delta = +0.018$ to $+0.077$), while Kendall τ rises from 0.754–0.825 to 0.825–0.871 ($\Delta = +0.012$ to $+0.117$). Brier scores consistently decrease from 0.0701–0.0923 to 0.0494–0.0621 ($\Delta = -0.0199$ to -0.0414), confirming improved probability calibration. However, these gains reach statistical significance under the paired bootstrap only for gemma-4-31B-it, remaining non-significant across the remaining judges.

Separability and agreement show minimal, non-significant shifts: separability changes from 70.2%–74.9% to 69.0%–71.9% ($\Delta = -0.6$ to -2.9 pp), and agreement varies from 72.7%–73.9% to 70.2%–72.7% ($\Delta = 0.0$ to -2.5 pp). These marginal variations indicate that conversational refinements primarily sharpen ranking calibration rather than altering pairwise separation. Appendix I details item-level agreement across both instruction sets, and Appendix J contains examples of base instructions and their refinements.

Table 3: **Ablation of multi-turn user refinements against base instructions.** Evaluation across 263 shared instructions ($n = 19$) against Arena AI. Base Instr. reflects only the first-turn request; + Refinements integrates constraints extracted from later-turn feedback. Brackets report 95% CIs; Δ = Refined − Base (* excludes zero; bold marks best). ρ and τ denote rank correlations, pp is percentage points, and ↑ (↓) indicates higher (lower) is better.

Judge	Instruction Type	Spearman ρ ↑	Kendall τ ↑	Separability ↑	Agreement ↑	Brier ↓
GLM-4.7-Flash	Base Instr.	0.930 [0.680, 0.989]	0.825 [0.500, 0.949]	**70.2%**	**72.7%**	0.0701
	+ Refinements	**0.947** [0.766, 0.993]	**0.836** [0.531, 0.939]	69.0%	70.2%	**0.0494**
	Δ	+0.018 [−0.012, +0.232]	+0.012 [−0.061, +0.185]	−1.2 pp [−8.2, +4.1]	−2.5 pp [−9.9, +2.7]	−0.0207 [−0.0509, +0.0002]
Qwen3.6-27B	Base Instr.	0.921 [0.706, 0.988]	0.801 [0.489, 0.937]	**72.5%**	**73.9%**	0.0820
	+ Refinements	**0.940** [0.752, 0.989]	**0.825** [0.543, 0.937]	71.9%	72.0%	**0.0621**
	Δ	+0.019 [−0.011, +0.170]	+0.023 [−0.063, +0.137]	−0.6 pp [−6.4, +5.3]	−1.9 pp [−7.8, +3.4]	−0.0199 [−0.0614, +0.0058]
gemma-4-31B-it	Base Instr.	0.886 [0.592, 0.977]	0.754 [0.414, 0.903]	**74.9%**	72.7%	0.0923
	+ Refinements	**0.963** [0.857, 0.996]	**0.871** [0.665, 0.963]	71.9%	72.7%	**0.0509**
	Δ	+0.077* [+0.011, +0.366]	+0.117* [+0.025, +0.325]	−2.9 pp [−11.1, +3.5]	0.0 pp [−7.2, +7.0]	−0.0414* [−0.0953, −0.0066]
Ensemble	Base Instr.	0.928 [0.724, 0.989]	0.825 [0.550, 0.949]	**73.7%**	**73.9%**	0.0814
	+ Refinements	**0.946** [0.748, 0.993]	**0.848** [0.575, 0.951]	71.9%	72.0%	**0.0580**
	Δ	+0.018 [−0.002, +0.156]	+0.023 [−0.037, +0.127]	−1.8 pp [−7.0, +2.9]	−1.9 pp [−7.2, +2.7]	−0.0234 [−0.0646, +0.0017]

5.4 LLM-AS-A-JUDGE AGREEMENT AND RELIABILITY

At the checklist item level, the three primary judges achieve a Krippendorff's α (Krippendorff, 2018; Hayes & Krippendorff, 2007) of 0.764 (95% CI [0.759, 0.768]) on the benchmark, indicating substantial inter-judge agreement. Agreement remains consistent on both instruction variants of the multi-turn ablation ($\alpha = 0.776$ for base and 0.761 for refined instructions; Appendix I). Pairwise Cohen's κ (Cohen, 1960) across all judged items ranges from 0.726 to 0.833, with the lowest values occurring on pairs involving GLM-4.7-Flash.

Importantly, this item-level variance does not propagate to model-level outcomes: all three judges achieve comparable rank correlations with Arena AI ($\rho = 0.926$–0.946; Table 1), as local evaluation noise is largely attenuated by per-conversation score aggregation.

5.5 THEMATIC COVERAGE

Figure 2 illustrates the topical breadth of the 500-instruction evaluation suite across 27 identified clusters. While open-ended prose forms the single largest category, the remaining volume spans a diverse tail that extends well beyond code and science, technology, engineering, and mathematics (STEM): alongside interface development, applied engineering, and systems programming, the suite includes tasks such as accounting, IoT applications, and meeting-transcript processing, reflecting the range of requests users bring to real conversations. Average scores across clusters hover moderately around the overall mean, with neither near-zero floors nor perfect-score ceilings. This spread confirms that the tasks maintain an appropriate difficulty level to differentiate model performance across diverse subjects.



Figure 2: **Topical distribution and scores across 27 clusters. Left:** Conversation count per cluster. **Right:** Mean score ($\pm 1\sigma$); dashed line shows the size-weighted mean.

5.6 Cost and Scalability Analysis

To evaluate scalability, we examine resource consumption for benchmark construction and model evaluation relative to Arena-Hard-Auto (Li et al., 2025). Building our 500 instruction suite cost $19.05 on AWS Bedrock (US East, N. Virginia; rates as of September 17, 2026) across 104.8M tokens using the open weight gpt oss family: gpt oss 20b ($0.07/1M input, $0.30/1M output; $8.50) and gpt oss 120b ($0.15/1M input, $0.60/1M output; $10.55), roughly 26$\times$ less than the approximately $500 reported for Arena-Hard-Auto using GPT-4 Turbo. Our efficiency stems from filtering only 16,731 candidate dialogues rather than unconstrained raw logs, selected by an adaptive sampler that balances diversity and quality (Section 3.1).

For evaluation, Conv-to-Bench relies exclusively on open-weight judges: whereas Arena-Hard-Auto reports approximately $20 per model in proprietary API fees, a single gemma-4-31B-it judge ($0.14/1M input, $0.40/1M output) costs $1.62 per model ($30.86 across all 19 models), about 12$\times$ cheaper. Although checklist verification is token-intensive (averaging 31.3M tokens per model under the three-judge ensemble), this single judge maintains ranking correlations and calibration comparable to the full ensemble (Section 5.1), so the additional judges are not required to obtain reliable rankings. Appendix K details token expenditures across all pipeline stages.

6 Conclusion

We introduced Conv-to-Bench, an automated framework converting real human–LLM dialogues into self-contained instructions with atomic verification checklists using only open-weight models. The pipeline creates a 500-instruction suite for $19.05 and evaluates models for an estimated $1.62 each on hosted infrastructure, enabling low-cost benchmarking without proprietary APIs.

Our experiments yield four core findings. First, atomic checklist evaluation shows clear structural advantages over standard pairwise judging, achieving significant gains in rank correlation, agreement, separability, and calibration. Second, adding multi-turn user refinements improves correlation and probability calibration over base instructions, though these differences lack statistical significance across most judges. Third, our open-model benchmark aligns closely with Arena AI human preferences ($\rho = 0.926$–0.946), performing comparably to Arena-Hard-Auto. Finally, item-level evaluations from a single open-weight judge are consistent enough to reliably rank models.

Future work should address key limitations, including an English-only scope, evaluations capped at models released through mid-2024, and potential filtering noise from LLM-driven pipelines. Nevertheless, Conv-to-Bench provides an accessible, fully open methodology for benchmark construction, establishing an effective foundation for evaluating conversational LLM interactions.

AI USE STATEMENT

In this work, we distinguish between the use of AI as a component of our proposed methodology and its use as a supportive tool during development. First, the pipeline proposed in this study inherently integrates generative AI as a core component of its architecture. Second, during the development phase, we utilized AI tools in an assistive capacity to accelerate code implementation. Third, we also used AI tools to aid and polish the writing of this manuscript. All AI-assisted development work was closely supervised. LLM-generated code was thoroughly reviewed, modified, and tested for correctness by the authors, ensuring human-led system design. AI-assisted summaries were manually verified against original sources, and AI-assisted writing suggestions were reviewed and edited by the authors. We take full responsibility for the final content of this work, including all text, claims, and artifacts.

ACKNOWLEDGMENTS

REFERENCES

01.AI, Alex Young, Bei Chen, Chao Li, et al. Yi: Open foundation models by 01.AI. *arXiv preprint arXiv:2403.04652*, 2024.

Marah Abdin, Jyoti Aneja, Hany Awadalla, et al. Phi-3 technical report: A highly capable language model locally on your phone. *arXiv preprint arXiv:2404.14219*, 2024.

Peter Auer, Nicolò Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine Learning*, 47(2–3):235–256, 2002. doi: 10.1023/A:1013689704352.

Ge Bai, Jie Liu, Xingyuan Bu, Yancheng He, Jiaheng Liu, Zhanhui Zhou, Zhuoran Lin, Wenbo Su, Tiezheng Ge, Bo Zheng, and Wanli Ouyang. MT-Bench-101: A fine-grained benchmark for evaluating large language models in multi-turn dialogues. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7421–7454, Bangkok, Thailand, 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.401. URL https://aclanthology.org/2024.acl-long.401/.

Ralph Allan Bradley and Milton E. Terry. Rank analysis of incomplete block designs: I. The method of paired comparisons. *Biometrika*, 39(3/4):324–345, 1952. doi: 10.2307/2334029.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code, 2021. URL https://arxiv.org/abs/2107.03374.

Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios Nikolas Angelopoulos, Tianle Li, Dacheng Li, Banghua Zhu, Hao Zhang, Michael I. Jordan, Joseph E. Gonzalez, and Ion Stoica. Chatbot Arena: An open platform for evaluating LLMs by human preference. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024. URL https://openreview.net/forum?id=3MW8GKNyzI.

Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46, 1960. doi: 10.1177/001316446002000104.

Shachar Don-Yehiya, Leshem Choshen, and Omri Abend. Naturally occurring feedback is common, extractable and useful, 2024. URL https://arxiv.org/abs/2407.10944.

Yann Dubois, Balázs Galambosi, Percy Liang, and Tatsunori B. Hashimoto. Length-controlled AlpacaEval: A simple way to debias automatic evaluators. In *First Conference on Language Modeling (COLM)*, 2024. URL https://openreview.net/forum?id=CybBmzWBX0.

Bradley Efron. Better bootstrap confidence intervals. *Journal of the American Statistical Association*, 82(397):171–185, 1987. doi: 10.1080/01621459.1987.10478410.

Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman & Hall/CRC, New York, 1994. ISBN 9780412042317.

Christopher A. Field and Alan H. Welsh. Bootstrapping clustered data. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 69(3):369–390, 2007. doi: 10.1111/j.1467-9868.2007.00593.x.

Gemma Team. Gemma: Open models based on Gemini research and technology. *arXiv preprint arXiv:2403.08295*, 2024a.

Gemma Team. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*, 2024b.

Gemma Team. Gemma 4 technical report, 2026. URL https://arxiv.org/abs/2607.02770.

GLM-4.5 Team. GLM-4.5: Agentic, reasoning, and coding (ARC) foundation models, 2025. URL https://arxiv.org/abs/2508.06471.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, et al. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Maarten Grootendorst. KeyBERT: Minimal keyword extraction with BERT, 2020.

Maarten Grootendorst. BERTopic: Neural topic modeling with a class-based TF-IDF procedure. *arXiv preprint arXiv:2203.05794*, 2022.

Andrew F. Hayes and Klaus Krippendorff. Answering the call for a standard reliability measure for coding data. *Communication Methods and Measures*, 1(1):77–89, 2007. doi: 10.1080/19312450709336664.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, et al. Mistral 7B. *arXiv preprint arXiv:2310.06825*, 2023.

Maurice G. Kendall. A new measure of rank correlation. *Biometrika*, 30(1/2):81–93, 1938. doi: 10.1093/biomet/30.1-2.81.

Klaus Krippendorff. *Content Analysis: An Introduction to Its Methodology*. SAGE Publications, 4th edition, 2018.

Tianle Li, Wei-Lin Chiang, Evan Frick, Lisa Dunlap, Tianhao Wu, Banghua Zhu, Joseph E. Gonzalez, and Ion Stoica. From crowdsourced data to high-quality benchmarks: Arena-Hard and Bench-Builder pipeline. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, volume 267 of *Proceedings of Machine Learning Research*, pp. 34209–34231. PMLR, 2025. URL https://proceedings.mlr.press/v267/li25h.html.

Bill Yuchen Lin, Yuntian Deng, Khyathi Raghavi Chandu, Faeze Brahman, Abhilasha Ravichander, Valentina Pyatkin, Nouha Dziri, Ronan Le Bras, and Yejin Choi. WildBench: Benchmarking LLMs with challenging tasks from real users in the wild. In *The Thirteenth International Conference on Learning Representations (ICLR)*, pp. 58384–58402, 2025.

Ying-Chun Lin, Jennifer Neville, Jack Stokes, Longqi Yang, Tara Safavi, Mengting Wan, Scott Counts, Siddharth Suri, Reid Andersen, Xiaofeng Xu, Deepak Gupta, Sujay Kumar Jauhar, Xia Song, Georg Buscher, Saurabh Tiwary, Brent Hecht, and Jaime Teevan. Interpretable user satisfaction estimation for conversational systems with large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 11100–11115, Bangkok, Thailand, 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.598. URL https://aclanthology.org/2024.acl-long.598/.

Yuhan Liu, Michael J. Q. Zhang, and Eunsol Choi. Implicit user feedback in human-LLM dialogues: Informative to understand users yet noisy as a learning signal. In *2nd Workshop on Models of Human Feedback for AI Alignment (ICML 2025 Workshop)*, 2025. URL https://openreview.net/forum?id=toSLK7ISiE.

Leland McInnes, John Healy, and Steve Astels. hdbscan: Hierarchical density based clustering. *Journal of Open Source Software*, 2(11):205, 2017. doi: 10.21105/joss.00205.

Leland McInnes, John Healy, and James Melville. UMAP: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*, 2018.

OpenAI. GPT-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

OpenAI. GPT-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.

OpenAI. gpt-oss-120b & gpt-oss-20b model card, 2025. URL https://arxiv.org/abs/2508.10925.

Richard Yuanzhe Pang, Stephen Roller, Kyunghyun Cho, He He, and Jason Weston. Leveraging implicit feedback from deployment data in dialogue. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 60–75, St. Julian's, Malta, 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.eacl-short.8. URL https://aclanthology.org/2024.eacl-short.8/.

Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, et al. A benchmark of expert-level academic questions to assess AI capabilities. *Nature*, 649:1139–1146, 2026. doi: 10.1038/s41586-025-09962-4. Also available as "Humanity's Last Exam", arXiv:2501.14249.

Qwen Team. Qwen3.6-27B: Flagship-level coding in a 27B dense model. Blog post, April 2026. URL https://qwen.ai/blog?id=qwen3.6-27b. Model card: https://huggingface.co/Qwen/Qwen3.6-27B.

Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3982–3992. Association for Computational Linguistics, 2019. doi: 10.18653/v1/D19-1410.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. GPQA: A graduate-level Google-proof Q&A benchmark. In *First Conference on Language Modeling (COLM)*, 2024. URL https://openreview.net/forum?id=Ti67584b98.

Chirag Shah, Ryen White, Reid Andersen, Georg Buscher, Scott Counts, Sarkar Das, Ali Montazer, Sathish Manivannan, Jennifer Neville, Nagu Rangan, Tara Safavi, Siddharth Suri, Mengting Wan, Leijie Wang, and Longqi Yang. Using large language models to generate, validate, and apply user intent taxonomies. *ACM Transactions on the Web*, 19(3):1–29, 2025. doi: 10.1145/3732294.

Charles Spearman. The proof and measurement of association between two things. *The American Journal of Psychology*, 15(1):72–101, 1904. doi: 10.2307/1412159.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. MIT Press, 2nd edition, 2018.

Mengting Wan, Tara Safavi, Sujay Kumar Jauhar, Yujin Kim, Scott Counts, Jennifer Neville, Siddharth Suri, Chirag Shah, Ryen W. White, Longqi Yang, Reid Andersen, Georg Buscher, Dhruv Joshi, and Nagu Rangan. TnT-LLM: Text mining at scale with large language models. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD '24)*, pp. 5836–5847, Barcelona, Spain, 2024. Association for Computing Machinery. doi: 10.1145/3637528.3671647.

Shitao Xiao, Zheng Liu, Peitian Zhang, Niklas Muennighoff, Defu Lian, and Jian-Yun Nie. C-Pack: Packed resources for general Chinese embeddings. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '24)*, pp. 641–649. Association for Computing Machinery, 2024. doi: 10.1145/3626772.3657878.

Z.ai (Zhipu AI). GLM-4.7-Flash. Model card, Hugging Face, 2026. URL https://huggingface.co/zai-org/GLM-4.7-Flash.

Wenting Zhao, Xiang Ren, Jack Hessel, Claire Cardie, Yejin Choi, and Yuntian Deng. WildChat: 1M ChatGPT interaction logs in the wild. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL https://openreview.net/forum?id=Bl8u7ZRlbM.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems 36 (NeurIPS), Datasets and Benchmarks Track*, 2023. URL https://openreview.net/forum?id=uccHPGDlao.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Tianle Li, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zhuohan Li, Zi Lin, Eric P. Xing, Joseph E. Gonzalez, Ion Stoica, and Hao Zhang. LMSYS-Chat-1M: A large-scale real-world LLM conversation dataset. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL https://openreview.net/forum?id=BOfDKxfwt0.

Banghua Zhu, Evan Frick, Tianhao Wu, Hanlin Zhu, Karthik Ganesan, Wei-Lin Chiang, Jian Zhang, and Jiantao Jiao. Starling-7B: Improving helpfulness and harmlessness with RLAIF. In *First Conference on Language Modeling (COLM)*, 2024. URL https://openreview.net/forum?id=GqDntYTTbk.

Terry Yue Zhuo, Minh Chien Vu, Jenny Chim, Han Hu, Wenhao Yu, Ratnadira Widyasari, Imam Nur Bani Yusuf, Haolan Zhan, Junda He, Indraneil Paul, Simon Brunner, Chen Gong, Thong Hoang, Armel Randy Zebaze, Xiaoheng Hong, Wen-Ding Li, Jean Kaddour, Ming Xu, Zhihan Zhang, Prateek Yadav, Naman Jain, Alex Gu, Zhoujun Cheng, Jiawei Liu, Qian Liu, Zijian Wang, David Lo, Binyuan Hui, Niklas Muennighoff, Daniel Fried, Xiaoning Du, Harm de Vries, and Leandro von Werra. BigCodeBench: Benchmarking code generation with diverse function calls and complex instructions. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025. URL https://openreview.net/forum?id=YrycTjllL0.

A Cluster Sampling Mechanism

This appendix formalizes the topic cluster sampling mechanism introduced in Section 3.1. We formulate the sampling process as a variant of the multi-armed bandit problem, where each topic cluster operates as an arm. To promote dataset diversity and prevent any single dense topic from dominating the final selection, arm weights are dynamically adjusted based on the filtering funnel's acceptance verdicts and a geometric satiety-decay factor.

Mechanism and State Initialization. Let $\mathcal{K} = \{1, \ldots, K\}$ denote the set of topic clusters produced by the clustering step. Each cluster $k \in \mathcal{K}$ maintains a conversation queue, a sampling weight $w_k \in \mathbb{R}_{>0}$ (initialized to $w_k = 1$), and an approval counter $n_k \in \mathbb{Z}_{\geq 0}$ (initialized to $n_k = 0$) representing the number of drawn conversations from k that have successfully passed the funnel.

Selection and Weight Update. At each sampling step, a cluster k is drawn with a probability proportional to its current weight:

$$P(k) = \frac{w_k}{\sum_{j \in \mathcal{K}} w_j} \tag{1}$$

A conversation is then popped from cluster k's queue and evaluated by the six-stage filtering funnel. The weight w_k is subsequently updated via a multiplicative rule based on the funnel's verdict. Let $\alpha = 2.0$ be the reward multiplier, $\beta = 0.5$ the penalty multiplier, and $\gamma = 0.90$ the satiety-decay base.

If the conversation is **approved**, the cluster's success counter increments ($n_k \leftarrow n_k + 1$), and its weight is rewarded but penalized by its historical success:

$$w_k \leftarrow w_k \cdot \alpha \cdot \gamma^{n_k} \tag{2}$$

If the conversation is **rejected**, the success counter remains unchanged, and the weight is strictly penalized:

$$w_k \leftarrow w_k \cdot \beta \tag{3}$$

Because $\gamma < 1$, the marginal reward term $\alpha \cdot \gamma^{n_k}$ shrinks geometrically with each subsequent approval from cluster k. This satiety-decay mechanism ensures that highly productive clusters eventually yield priority to less explored ones, naturally enforcing topic diversity during the curation process.

Exhaustion and Termination. If a cluster's queue is depleted, its weight is permanently set to $w_k \leftarrow 0$, removing it from future draws. The sampling loop terminates when any of the following conditions are met: the number of approved conversations reaches the target size T; the cumulative cost of the API funnel calls reaches the budget $C_{\max}$; or all cluster weights reach zero ($\sum_k w_k = 0$).

Note: While structured around arm selection and binary rewards, this mechanism (summarized in Algorithm 1) employs a custom heuristic weight-update rule tailored specifically for dataset curation diversity, rather than optimizing for traditional regret bounds.

Algorithm 1 Multi-armed bandit cluster sampling for the filtering funnel

Require: topic clusters $\mathcal{K}$, each with a conversation queue; reward multiplier $\alpha = 2.0$; penalty multiplier $\beta = 0.5$; satiety-decay base $\gamma = 0.90$; approval target T; cost budget $C_{\max}$
Ensure: a set of approved conversations, of size T unless the budget or the queues are exhausted first

$w_k \leftarrow 1$, $n_k \leftarrow 0$ for every $k \in \mathcal{K}$
$c \leftarrow 0$ {cumulative funnel cost}
$A \leftarrow \emptyset$ {approved conversations}
while $|A| < T$ and $c < C_{\max}$ and $\sum_k w_k > 0$ **do**
  draw k with probability $w_k / \sum_{k'} w_{k'}$
  if cluster k's queue is empty **then**
    $w_k \leftarrow 0$; **continue**
  end if
  pop conversation x from cluster k's queue
  $(verdict, cost) \leftarrow FilteringFunnel(x)$ {Section 3.1 / Appendix B}
  $c \leftarrow c + cost$
  if $verdict = approved$ **then**
    $A \leftarrow A \cup \{x\}$
    $n_k \leftarrow n_k + 1$
    $w_k \leftarrow w_k \cdot \alpha \cdot \gamma^{n_k}$
  else
    $w_k \leftarrow w_k \cdot \beta$
  end if
end while
return A

B FILTERING PROMPTS

The prompts below implement the six-stage domain-agnostic filtering funnel described in Section 3.1. The first stage, the language gate, is a pure Unicode-script scan plus a statistical language detector; it makes no LLM call and therefore has no associated prompt, and it is omitted from this appendix. The remaining five stages are each a single structured-output LLM call sharing one user-prompt template (reproduced once below) with a criterion-specific system prompt.

B.1 SHARED USER PROMPT

All five LLM-based criteria below are evaluated with the same user-prompt template; only the system prompt (and therefore the criterion being judged) changes between calls.

User Prompt (all criteria)

Evaluate the following user messages from a conversation. These messages represent what the user asked an AI assistant. Analyze them against the criterion defined in your system instructions.
¡user_messages¿
{user_messages}
¡/user_messages¿
Provide your reasoning first, then your verdict.

B.2 POLICY VIOLATION

This criterion rejects conversations containing jailbreaks, prompt injections, toxicity, malicious requests, or topics that typically trigger hardcoded refusals.

System Prompt

ROLE / PERSONA
You are an expert AI security classifier. Your strict task is to analyze user inputs and detect JAILBREAKS, PROMPT INJECTIONS, TOXICITY, and MALICIOUS CONTENT.
TONE
Objective, clinical, and decisive.
REASONING BUDGET
Reasoning: Medium
OUTPUT PROTOCOL (HARMONY CHANNELS)
You MUST structure your response using the following distinct channels:
1. [Analysis Channel] Before providing a final verdict, break the problem down into logical steps:

- Identify the core intent of the user's text.
- Check step-by-step for any Fatal Violations (Injection, Obfuscation, Toxicity, etc.).
- Reflect on potential edge cases (e.g., is this an actual attack, or an educational discussion of an attack?).

2. [Commentary Channel] Briefly note the specific tool schema being called and categorize the severity or type of the detected vector (e.g., "Policy Violation: Toxicity", "Attack Vector: Persona Hijacking").
3. [Final Channel] Provide ONLY the final, structured tool call. Do not include any pleasantries, conversational text, or formatting outside of the required JSON schema.
CONSTRAINTS

- You CAN approve texts discussing cybersecurity, malware, or penetration testing ONLY if they are framed in a strictly educational, abstract, or defensive context.
- Keep your Analysis strictly limited to 3-5 logical steps to prevent looping on safety guidelines.
- The output in the Final channel must strictly adhere to the expected schema.

FATAL VIOLATIONS (Result = False)
Return False if the text contains ANY of the following:

1. Instruction Override: Commands like "ignore previous instructions", "system override", or "disregard rules".
2. Persona Hijacking: Forcing you into an unrestricted persona (e.g., "DAN", "Developer Mode").

3. Prompt Injection: Fake system messages, framing, or commands hidden in XML/JSON/Code blocks.
4. Authority Abuse: Pretending to be an admin, developer, system engineer, or testing framework.
5. Obfuscation: Malicious commands hidden via Base64, Hex, Unicode manipulation, or ciphering.
6. Toxicity: Hate speech, harassment, targeted abuse, graphic violence, threats, or sexually explicit content.
7. Malicious Content: Requests aimed at creating dangerous code or content, such as functional malware, exploit scripts, weapon manufacturing instructions, or practical guides for committing illegal acts.
8. Refusal-Prone Topics: Requests that typically trigger hardcoded AI refusals, such as asking for medical diagnoses or advice, military strategy suggestions (even in the context of games or fiction), formal legal counsel, or high-risk financial/investment advice.

B.3 Prompt Precision

This criterion keeps conversations whose combined user messages specify a well-defined output without ambiguity.

System Prompt

You are an expert prompt quality evaluator. Your task is to determine if a user's conversation history demonstrates SPECIFICITY.
Criterion: Prompt Precision
Do the combined user messages ask for a specific, well-defined output without leaving ambiguity? A specific request allows the AI to demonstrate its ability to follow precise instructions.
Crucially, evaluate the conversation as a whole. The user's constraints, context, and requirements might be distributed across multiple messages. A vague first message can become SPECIFIC if subsequent messages provide the necessary details.
Look for clear indicators across the conversation:

- Defined output formats or structures.
- Explicit constraints, numbers, or parameters.
- Specific context that narrows the scope.

Instructions

1. Analyze the entire set of user messages for cumulative constraints and clarity.
2. Consider: By the end of these messages, could an AI answer deterministically without needing more clarification?
3. Provide your step-by-step reasoning.
4. Conclude with a strict verdict of "True" (Specific) or "False" (Vague).

Respond using the provided structured output schema.

B.4 Domain Knowledge

This criterion keeps conversations that demand strong prior mastery of a specific domain.

System Prompt

You are an expert prompt quality evaluator. Your task is to determine if a user's conversation history requires DOMAIN KNOWLEDGE.
Criterion: Domain Knowledge
Do the combined user messages test the AI's knowledge and understanding in a specific domain or set of domains? The request must demand the AI to have a strong prior knowledge or mastery of domain-specific concepts, theories, or principles (e.g., advanced software engineering, medicine, law, physics).
Crucially, evaluate the conversation as a whole. A user might start with a general greeting or broad topic, but reveal highly specialized domain requirements in subsequent messages.
Look for clear indicators across the conversation:

- Use of specialized terminology or jargon.
- Requests to apply complex, field-specific theories or principles.
- Tasks that go far beyond general knowledge, trivia, simple translations, or basic creative writing.

Instructions

1. Analyze the entire set of user messages for domain-specific concepts.
2. Consider: By the end of these messages, does the core task demand strong prior mastery of a specific discipline?
3. Provide your step-by-step reasoning.
4. Conclude with a strict verdict of "True" (Requires Domain Knowledge) or "False" (Does Not Require).

Respond using the provided structured output schema.

B.5 Multi-Layered Nuance

This criterion keeps conversations with multiple components, variables, or sub-tasks that require multi-step reasoning.

System Prompt

You are an expert prompt quality evaluator. Your task is to determine if a user's conversation history demonstrates Multi-Layered Nuance.
Criterion: Multi-Layered Nuance
Do the combined user messages have multiple components, variables, or levels of depth and nuance? A complex prompt assesses the AI's capability to handle multi-faceted problems beyond simple, single-step queries.
Crucially, evaluate the conversation as a whole. A user might start with a simple idea but add multiple layers, sub-tasks, or variables in subsequent messages.
Look for clear indicators across the conversation:

- Multiple sub-tasks, constraints, or sequential steps to be executed together.
- Trade-offs, conditional logic, edge cases, or integration of multiple variables.
- Requests that require multi-step reasoning, rather than fetching a single fact or performing a trivial operation.

Instructions

1. Analyze the entire set of user messages for multiple components, variables, or sub-tasks.
2. Consider: By the end of these messages, does the core task demand multi-step reasoning to solve a complex, multi-faceted problem?
3. Provide your step-by-step reasoning.

4. Conclude with a strict verdict of "True" (Multi-Layered Nuance) or "False" (Simple).

Respond using the provided structured output schema.

B.6 PROBLEM-SOLVING

This criterion keeps conversations that require diagnosing and solving a concrete problem rather than retrieving facts or generating standard text.

System Prompt

You are an expert prompt quality evaluator. Your task is to determine if a user's conversation history requires PROBLEM-SOLVING.
Criterion: Problem-Solving
Do the combined user messages require active problem-solving: analyzing and clearly defining the problem and systematically devising and implementing a solution? Active problem-solving is not simply reciting facts, generating basic content, or following a fixed set of instructions.
Crucially, evaluate the conversation as a whole. A user might start with a general statement but present a specific challenge, bug, or logistical puzzle in subsequent messages.
Look for clear indicators across the conversation:

- A specific situation, broken system, or complex goal with constraints.
- A need for the AI to diagnose an issue or devise a strategic approach.
- Tasks that demand analytical reasoning, going beyond simple lookup, pure summarization, or unconstrained generation.

Instructions

1. Analyze the entire set of user messages for an underlying challenge, bug, or goal.
2. Consider: By the end of these messages, does the core task demand active problem-solving rather than simply retrieving facts or generating standard text?
3. Provide your step-by-step reasoning.
4. Conclude with a strict verdict of "True" (Requires Problem-Solving) or "False" (Does Not Require).

Respond using the provided structured output schema.

C INSTRUCTION SYNTHESIS PROMPTS

This section reproduces the prompts of the instruction synthesis stage, which turns a filtered conversation into a base instruction, a set of feedback constraints, and a refined instruction, followed by two audit passes. Each prompt is shown as a system prompt and its user-prompt template.

C.1 EXTRACT BASE INSTRUCTION

This prompt extracts a single self-contained base instruction from the first user request of a conversation.

System Prompt

Reasoning: high
 # ROLE

You are an expert in conversation analysis. Your only job: read the entire conversation between a user and an assistant, decide whether it contains a specific request, question, or task from the user, and if so extract it as ONE cohesive, self-contained instruction.

 # READER MODEL (who receives your output)

Your instruction goes to a fresh agent in a new context window with NO access to this conversation, the original messages, attachments, examples, or anything called "the prompt". It sees ONLY the literal text in the "simple_instruction" field. Anything not written out in full there does not exist for that agent: any content needed to fulfill the request must physically appear, in full, inside the instruction.

 # RULES (priority order; each is non-negotiable)

1. Extract only EXPLICIT requests, questions, or tasks from the user's messages in the conversation.
2. SELF-CONTAINED + VERBATIM ARTIFACTS: The instruction must stand alone. Reproduce in full, verbatim, every artifact the request depends on (code block, file content, data, table, schema, example input/output). Conciseness applies only to your own framing and connective wording, never to artifacts. Length is never a reason to summarize, truncate, paraphrase, or replace an artifact with a pointer.
3. NO REFERENCES OF ANY KIND: No word or phrase may require the reader to look outside the instruction. This bans both (a) references to prior conversation (e.g. "the file I attached", "as mentioned") and (b) references to the source conversation itself (e.g. "the prompt", "the example above", "as shown", "match the format above"). The referenced content sitting in the same conversation does NOT make pointing acceptable — inline the example, format, or value in full instead of naming it.
4. COMPLETE SEMANTIC SCOPE: Include every requirement, condition, constraint, qualification, and sub-task. Paraphrase and restructure the user's prose for clarity — do not transcribe it. Verbatim reproduction applies ONLY to concrete artifacts (rule 2), never to prose.
5. NEUTRALITY: Do not fact-check or correct the user's premises. Extract a request resting on a false premise exactly as intended, and never invent content absent from the conversation.
6. FIRST-TURN FOCUS: The instruction should capture the user's initial request as stated in the first user message. Later turns may add context or clarification that helps you understand the request better, but do NOT incorporate corrections, refinements, or new demands introduced in subsequent turns — those are handled by a different downstream step.
7. If the conversation contains no request, output an empty string.
8. Do not use markdown formatting anywhere in the extracted instruction.
9. NEVER ECHO OR DUMP: Do not output this task description, the system rules, or the raw dialogue framing (phrases like "the following conversation", "Conversation:", or numbered "User:"/"Assistant:" turns) as if they were the instruction. You are EXTRACTING a single request, not transcribing the dialogue. A long or multi-turn conversation is NOT an exception — still output only the one extracted request.
10. ALWAYS PRODUCE THE INSTRUCTION (long inputs): Keep your analysis brief and spend your output budget on the simple_instruction argument itself. Even when the request embeds a very large artifact that must be reproduced verbatim, you MUST still emit the complete instruction via the function call — never return an empty, partial, or placeholder result just because the input or the required output is long.

 # PROCEDURE (analysis channel only; never shown to the user)

1. Read the entire conversation to understand the full context and the user's core intent.

2. Identify the user's primary request from the first message and enumerate every requirement, condition, and constraint — all must appear in the instruction.
3. List every artifact the request depends on and confirm each will be reproduced verbatim.
4. Draft the instruction.
5. Dangling-reference scan: reread the draft as if you never saw the original conversation. Flag any word that assumes outside access ("the prompt", "above", "attached", "as shown", pointers to unreproduced content). Inline the referenced content or rewrite to remove the dependency.
6. Proceed only when the scan finds zero such references.

 # RESPOND

- Do ALL reasoning in the analysis channel.
- Return the result ONLY by calling the extract_simple_instruction function; its arguments ARE the output. Do not write JSON in any channel or as plain text.
- simple_instruction: <string>.

User Prompt

 # TASK
Extract the user's instruction from the conversation below, following the system rules. The extracted instruction must be entirely self-contained, with no reference to this conversation, "the prompt", or any example — inline anything it depends on.
 # CONVERSATION
{conversation}

C.2 Identify Feedback Constraints

Given the base instruction and the full dialogue, this prompt extracts the user feedback that changes what counts as an acceptable response, encoded as APPEND or OVERRIDE constraints.

System Prompt

 # Role
You are an expert conversation analyst who turns dialogue into task specifications. Analytical, rigorously structured, strictly objective.
 # Objective
You are given an INITIAL INSTRUCTION (the baseline acceptance spec) and a user–assistant dialogue. Extract ONLY the user feedback that CHANGES what counts as a satisfactory response, beyond what the initial instruction already establishes. You are building the task's ACCEPTANCE SPECIFICATION — a list of constraints — not summarizing the conversation. The output feeds a refined-instruction builder and a checklist builder.
 # Baseline

- The initial instruction is provided separately; it is never itself an output constraint.
- Judge each user turn against the initial instruction PLUS the constraints you have already accepted; the spec grows as you scan, so test incrementally.
- Only user turns can yield a constraint; assistant turns are context only.

 # Pipeline (apply IN ORDER to each user turn)

1. **Novelty** — Does the current spec already imply it? If yes, DISCARD (redundant).
2. **Restriction** — Does it move the acceptance boundary (make some response newly acceptable or newly unacceptable)? If not, DISCARD (courtesy, agreement, chatter).

3. **Raise to spec level** — Rewrite the reaction to a specific draft ("no, shorter") as the general rule it implies about ANY response ("must be concise, $\sim\leq$ X"). Infer from what the user DEMANDED; never copy specifics from the assistant's good draft.
4. **Sufficiency** — Re-scan: could someone holding (initial instruction + your constraints) reconstruct the acceptance criterion alone? Add any high-impact omission.
5. **Minimality** — Merge equivalent constraints into one. When two touch the same dimension, the LATEST wins; the output must never contain conflicting constraints. Keep each as the shortest self-contained statement.

 # Per constraint

- **spec**: ONE sentence, general (about ANY response, not this draft), self-contained, phrased as a requirement ("The response must ..."), in English. This is the source of truth.
- **overrides**: true if the constraint contradicts or replaces something the initial instruction already stated or implied (the builder must overwrite it); false if purely additive (the builder appends it).

 # Exclude

- Praise, agreement, or acknowledgement with no new requirement.
- Anything redundant with the current spec, or that does not move the acceptance boundary.
- "It's wrong" with no fix or direction (nothing to encode).
- Specifics that merely describe the assistant's draft.

 # Respond

- Do ALL reasoning in the analysis channel.
- Return the result ONLY by calling the extract_feedback function; its arguments ARE the output. Do not write JSON in any channel or as plain text.
- constraints: a list of objects { "spec": <string>, "overrides": <boolean>}.

User Prompt

 # Task
Given the initial instruction and the conversation, extract the acceptance-spec constraints following your instructions.
In the analysis channel, before answering:

1. Walk the conversation turn by turn.
2. For each user turn, run the 5-step pipeline; note which step discards it or the constraint it yields, keeping a running spec for incremental novelty testing.
3. Do the Sufficiency sweep, then Minimality (merge, latest-wins, shorten), and set overrides for each survivor.

Then call extract_feedback.
 # Initial instruction (baseline spec)
{initial_instruction}
 # Conversation
{conversation}

C.3 Extract Refined Instruction

This prompt merges the base instruction and the acceptance constraints into a single refined instruction.

System Prompt

Reasoning: high

Role

You are an expert conversation analyst. Your only job is to read a Base Instruction plus a list of Acceptance Constraints and produce ONE consolidated "refined instruction" that captures what the user ultimately wants by the end of the interaction. You consolidate and refine instructions — you never execute the underlying task or answer the user's underlying question yourself.

Tone

Precise, objective, and strictly analytical.

Reader model

The refined instruction you produce will be handed to a fresh agent in a new context window with NO access to this conversation, the base instruction, the constraint list, or any example. That agent sees ONLY the literal text of the complex_instruction argument you pass to extract_complex_instruction. Anything not written out in full there does not exist for it, so every piece of required context must physically appear inside the instruction.

Inputs

- **Base Instruction** — the initial, simplified user request extracted from the first turn of the conversation.
- **Acceptance Constraints** — a list of acceptance-specification constraints previously extracted from user feedback in the conversation by an upstream identification step. Each constraint is a single, general, self-contained requirement that captures a refinement, correction, or new demand the user expressed during the dialogue. Each is tagged:
  - **[APPEND]** — purely additive; add it alongside what the base already asks for.
  - **[OVERRIDE]** — contradicts or replaces something the base states or implies; overwrite the conflicting base part so the final instruction reflects the constraint and never the superseded base requirement.

Task

Generate the fully refined (complex) instruction by integrating every Acceptance Constraint into the Base Instruction, honoring each APPEND/OVERRIDE tag, so the result represents what the user ultimately wants.

Hard rules (ordered; all jointly required)

If two ever seem to collide, pick the reading that satisfies all of them and note the tension in the analysis channel — never drop or weaken a rule.

1. **Plan first.** In the analysis channel, break the problem into 3-5 logical steps and reflect on edge cases (missing base request, conflicting constraints, false premises).
2. **OVERRIDE resolution.** Edit each conflicting base requirement out and replace it with the [OVERRIDE] constraint. The final instruction must NEVER contain both a base requirement and an [OVERRIDE] constraint that contradicts it.
3. **Dangling-reference scan (last analysis step).** Re-read your draft as if you had never seen the base or the constraints; flag every phrase that assumes outside access (e.g. "the base instruction", "the constraints", "the example", "above", "as discussed", "provided", or any pronoun pointing at unreproduced content). For each, inline the referenced content verbatim or rewrite to remove the dependency before calling extract_complex_instruction.
4. **Empty case.** If the inputs contain no actionable request (no base request and no constraint to act on), call extract_complex_instruction with complex_instruction set to an empty string.

Rules for the refined instruction

1. **Integrate by tag.** APPEND constraints are added; OVERRIDE constraints replace the conflicting base requirement, incorporated organically.

2. **Stay neutral.** Do NOT fact-check or correct the user's premises. If a request rests on a false premise, extract it neutrally exactly as intended (e.g. "Explain how to do [User's Request]"). Correcting the user is the downstream model's job, not yours.
3. **Fully self-contained.** State every constraint, refinement, and piece of context directly in the instruction text — no references of any kind, neither to the conversation (e.g. "as we discussed", "your earlier correction") nor to the source materials you are consuming (e.g. "the base instruction", "the constraints", "as shown above"); the downstream agent cannot see either. Carry over any artifact already present in the Base Instruction (code block, dataset, example input/output, schema, format spec) VERBATIM — never summarized, truncated, paraphrased, or replaced by a reference.
4. **No expected outcomes.** When a constraint encodes a correction, integrate only the methodological/approach-level requirement it implies. Do NOT transcribe specific expected values, numerical answers, or correct outputs into the instruction — those must stay absent to preserve benchmark integrity.

Respond

- Do ALL reasoning in the analysis channel.
- Return the result ONLY by calling the extract_complex_instruction(complex_instruction: string) function; its arguments ARE the output. Do not write JSON in any channel or as plain text.
- complex_instruction: the comprehensive, self-contained final-intent request; an empty string when there is no actionable request.

User Prompt

Instructions
Analyze the Base Instruction and Acceptance Constraints below and produce the fully refined (complex) instruction that integrates every constraint: append [APPEND] constraints, and for [OVERRIDE] constraints overwrite the conflicting base requirement so the result reflects the constraint, never the superseded base. Do not refer to the base instruction, the constraints, or any example by name — inline whatever the instruction depends on, and carry over verbatim any artifact already present in the base. Do your reasoning in the analysis channel and return the result only by calling extract_complex_instruction.
Base instruction
{base_instruction}
Acceptance constraints
{feedback_constraints}

C.4 Review Feedback Completeness

This audit checks that the refined instruction reflects every refinement demanded by the user, fixing either the constraint list or the merge.

System Prompt

Reasoning: high
 # ROLE
You are a strict independent auditor of refinement coverage. You receive: the initial instruction, the full conversation, the list of acceptance constraints an upstream step extracted from it, and the final refined instruction that was built from those constraints. Your only job: decide whether the refined instruction truly captures every refinement the user demanded, and if not, fix the right thing.
 # TWO DISTINCT FAILURE MODES — diagnose which one occurred

A. MISSING EXTRACTION — the user demanded a refinement somewhere in the conversation (it moved the acceptance boundary: made some response newly acceptable or newly unacceptable) that is not present, in any form, in the constraints list. Fix: output the COMPLETE corrected constraints list — every constraint from the original list, unchanged, PLUS the missing one(s), each as a one-sentence, general, self-contained requirement (same format as the existing constraints: APPEND if additive, OVERRIDE if it contradicts/replaces something earlier). Leave corrected_complex_instruction null.
B. MERGE FAILURE — every relevant refinement IS already present in the constraints list, but the refined instruction text fails to reflect one or more of them (omitted, contradicted, or only partially honored). Fix: leave constraints exactly equal to the original list, and output the full, corrected corrected_complex_instruction text: the same instruction with the mis-merged constraint(s) now correctly integrated (APPEND alongside the rest; OVERRIDE replacing the conflicting base part), fully self-contained, with no reference to the base instruction, the constraints, or the conversation.
Only one of the two fixes applies per review — never fill in both constraints (beyond the original list) and corrected_complex_instruction at the same time.
 # WHAT IS NOT A REFINEMENT
Ignore praise, agreement, chatter, or anything that does not move the acceptance boundary. Apply the same discipline as the original extraction: novelty (already implied by the current spec? discard), restriction (does it actually narrow/widen what counts as acceptable?), raise-to-spec (state the general rule the user's reaction implies, never copy specifics from a draft the assistant produced), sufficiency, and minimality (on conflicts, the latest demand wins).
 # RESPOND

- Do ALL reasoning in the analysis channel: walk the conversation turn by turn, compare against the constraints list AND the refined instruction text, and identify the failure mode before answering.
- Return the result ONLY by calling the review_feedback_completeness function; its arguments ARE the output. Do not write JSON in any channel or as plain text.

User Prompt

 # TASK
Audit whether the refined instruction below fully captures every refinement the user demanded in the conversation, following the system rules. Identify whether any failure is a missing extraction or a merge failure, and produce the corresponding fix.
 # INITIAL INSTRUCTION (baseline)
{initial_instruction}
 # CONVERSATION
{conversation}
 # CURRENT ACCEPTANCE CONSTRAINTS
{constraints}
 # CURRENT refined instruction (built from the constraints above)
{complex_instruction}

C.5 Review Self-Containment

This audit checks that the base and refined instructions inline every artifact they depend on, and repairs them otherwise.

System Prompt

Reasoning: high
 # ROLE
You are a strict independent auditor. You receive the full original conversation and an instruction that was extracted from it. Your only job: decide whether the instruction is gen-

uinely self-contained, and if it is not, repair it using ONLY content that already exists in the conversation.
 # READER MODEL
The instruction you approve or correct will be handed to a fresh agent with NO access to this conversation. It sees ONLY the literal text of corrected_instruction. Anything the instruction depends on that is not physically written out inside it does not exist for that agent.
 # WHAT COUNTS AS AN ISSUE (be more thorough than a quick skim)
Set has_issue = true whenever ANY of the following holds:

1. The instruction names, points at, or otherwise depends on an artifact (code, file, dataset, table, schema, example input/output, image content, etc.) that is not reproduced in full, verbatim, inside the instruction text.
2. The instruction contains an explicit reference to the conversation or to materials outside itself (e.g. "the code above", "as discussed", "the file I shared", "the example shown earlier").
3. The instruction paraphrases, truncates, or summarizes an artifact that the conversation shows in full — even with no explicit pointer phrase. A shortened or reworded version of a concrete artifact is still a broken self-containment, not a stylistic choice.

Do NOT flag an issue merely because the instruction is abstract, terse, or does not depend on any artifact at all. Vagueness alone is not a self-containment problem — only flag actual unreproduced dependencies.
 # HOW TO REPAIR
When has_issue is true:

- Reinsert the missing or truncated content VERBATIM, copied from the conversation — never invent, infer, or approximate content that is not literally present in the conversation.
- Remove every dangling reference phrase, replacing it with the inlined content.
- Change nothing else: preserve the rest of the instruction's wording, scope, and intent exactly.
- If the conversation genuinely does not contain the missing artifact anywhere (it was referenced but never actually shared), do not invent it — instead rewrite the dependent part of the instruction to drop the unfulfillable dependency, and say so in issues_found.

When has_issue is false, corrected_instruction must be an exact, unmodified copy of the input instruction.
 # RESPOND

- Do ALL reasoning in the analysis channel.
- Return the result ONLY by calling the review_self_containment function; its arguments ARE the output. Do not write JSON in any channel or as plain text.

User Prompt

 # TASK
Audit the instruction below against the full conversation it was extracted from. Decide if it is genuinely self-contained per the system rules, and produce a corrected version if not.
 # CONVERSATION
{conversation}
 # INSTRUCTION TO AUDIT
{instruction}

D CHECKLIST SYNTHESIS PROMPTS

The prompts below generate and audit the evaluation checklist attached to each instruction. Checklists for base and refined instructions are generated separately, and a shared revision prompt then filters out items that do not discriminate response quality.

D.1 GENERATE CHECKLIST FOR BASE INSTRUCTION

This prompt generates the checklist for a base instruction, favoring items that discriminate response quality over simple presence checks.

System Prompt

Reasoning: high

 # Role

You are an expert evaluation designer specializing in LLM benchmarking and rubric construction. Your expertise is writing checklist items that DISCRIMINATE response quality — criteria a strong response satisfies and a superficially-compliant but mediocre response fails — while remaining strictly faithful to what the instruction entails.

 # Tone

Analytical, structured, strictly objective.

 # Objective

Generate an evaluation checklist that measures HOW WELL a response fulfills the User Instruction, not merely WHETHER it mentions the instruction's named elements.

Each item MUST:

1. Target a success criterion that is ENTAILED by the instruction — including the implicit standard of quality a competent reader would infer.
2. Separate an excellent response from a plausible, literally-compliant but low-quality one.

 # Core Principle

The default failure mode of checklists is LEAKAGE: items that restate explicit requirements as presence checks ("Does the response mention X?"). Any genuine attempt passes these, so they carry no discriminative signal and inflate every score uniformly.

Your job is the opposite: convert each requirement into the QUALITY GRADIENT it implies. Ask not "is X present?" but "is X done correctly / completely / robustly?" — the dimension on which real responses actually differ.

 # Illustration (format guidance only — do not copy verbatim, do not treat as required content)

- Leaky presence check (avoid): "Does the response include error handling?"
- Quality-discriminating (prefer): "Does the response handle the malformed-input cases the task implies?"

 # Constraints (ordered from most to least important)

1. **Entailment-bound (validity).** Every item MUST be derivable from the instruction. An item is valid if a competent reader, given only the instruction, would accept it as a fair criterion for judging the response — even when that criterion is implicit. Do NOT introduce requirements the instruction does not entail: no arbitrary tone, format, length, or stylistic preferences, and no commitment to a specific approach or solution the instruction leaves open.
2. **Target the quality gradient (discrimination).** Prefer items that distinguish an excellent fulfillment from a merely adequate one. Favor correctness, completeness, robustness, handling of the cases the task implies, and depth of treatment. Deprioritize bare presence checks of elements the instruction names explicitly — almost any attempt satisfies those.
3. **Anchor sparingly.** A few fundamental "did it do the core thing at all" items are acceptable to anchor the main goal, but they MUST NOT dominate. The majority of items must be quality-discriminating.

4. **One condition per item.** Each item tests exactly ONE indivisible condition, phrased as a neutral Yes/No question. No conjunctions ("and", "or", "both", "while") or comma-linked actions/properties within a single item.
5. **No redundancy.** No two items may test the same condition.
6. **Channel & delivery discipline.** All reasoning, planning, and deliberation happen in the analysis channel; the result is delivered SOLELY through the submit_checklist function call (see the # Respond section), never as JSON or prose in any channel.

 # Respond

- Do ALL reasoning, planning, and deliberation in the analysis channel.
- Return the result ONLY by calling the submit_checklist(items) function; its arguments ARE the output. Do NOT write JSON, backticks, or any prose as plain text or in the final channel.
- items: the complete list of checklist items. Each element is an object containing exactly one key — requirement: a single-condition, neutrally-framed Yes/No question targeting an entailed quality criterion.

User Prompt

 # Task
Produce a quality-discriminating evaluation checklist for the User Instruction below, following the rules in your system prompt.
In your analysis channel, first:

1. Separate what the instruction states explicitly from the implicit standard of "done well" it entails.
2. Imagine a response that is literally compliant but mediocre — the kind a weak model produces — and pinpoint where it would fall short of a strong one. Build the checklist from those gaps.

Then deliver the result solely by calling the submit_checklist function — emit no JSON or prose in any channel.
 # User Instruction
{instruction}

D.2 Generate Checklist for Refined Instruction

This prompt generates the checklist for a refined instruction, using the acceptance constraints as a priority signal for which dimensions to cover.

System Prompt

Reasoning: high
You are an expert evaluation designer specializing in LLM benchmarking and rubric construction. You write checklist items that DISCRIMINATE response quality — criteria a strong response satisfies and a superficially-compliant but mediocre one fails — while staying strictly faithful to what the instruction entails.
Tone (for all reasoning): analytical, structured, strictly objective.
Channels: reason in analysis and never reveal it to the user; return the result only via the submit_checklist tool call (see Output) — emit no text in final.
 # Task: Generate a Quality-Discriminating Evaluation Checklist
Objective
Measure HOW WELL a response fulfills the User Instruction, not merely WHETHER it mentions the instruction's named elements. Each item must:

1. Target a success criterion ENTAILED by the instruction — including the implicit standard of quality a competent reader would infer.
2. Separate an excellent response from a plausible, literally-compliant but low-quality one.

Core Principle (avoid leakage)
The default failure mode is LEAKAGE: restating explicit requirements as presence checks ("Does the response mention X?"). Any genuine attempt passes these, so they carry no discriminative signal. Instead, convert each requirement into the QUALITY GRADIENT it implies: ask not "is X present?" but "is X done correctly / completely / robustly?" — the dimension on which real responses actually differ.
Illustration (style only, not a requirement): avoid "Does the response mention the edge cases?"; prefer "Does the response correctly handle the edge cases the task implies?".
Handling Acceptance Constraints
You may be given ACCEPTANCE CONSTRAINTS the user demanded while refining the request, each tagged [APPEND] (additive) or [OVERRIDE] (replaces a default the instruction would imply). They are already folded into the instruction and flag the dimensions the user cared about most.

- Treat them as a priority signal, NOT a separate source of requirements: ensure the checklist has quality-discriminating items covering each, and no item rewards behavior an [OVERRIDE] rules out.
- They do NOT relax entailment: every item must still be derivable from the instruction; never invent a requirement present only as a constraint but absent from the instruction text.
- If none are provided, ignore this section.

Hard Constraints

1. **Entailment-bound (validity):** Every item MUST be derivable from the instruction — valid if a competent reader, given only the instruction, would accept it as a fair criterion, even when implicit. Do NOT add requirements the instruction does not entail: no arbitrary tone, format, length, or stylistic preferences, and no commitment to a specific approach or solution the instruction leaves open.
2. **Quality gradient (discrimination):** Prefer items distinguishing an excellent fulfillment from a merely adequate one — correctness, completeness, robustness, handling of implied cases, depth. Deprioritize bare presence checks of elements the instruction names explicitly.
3. **Anchor sparingly:** A few fundamental "did it do the core thing at all" items may anchor the main goal, but MUST NOT dominate; the majority must be quality-discriminating.
4. **One condition per item:** Each item tests exactly ONE indivisible condition as a neutral Yes/No question. No conjunctions ("and", "or", "both", "while") and no comma-linked actions or properties.
5. **No redundancy:** No two items test the same condition.
6. **Channel discipline:** All reasoning happens in analysis; the result is returned only via the submit_checklist tool call — never as text in final.

Output — call the submit_checklist tool
Return the result ONLY by calling submit_checklist(items); its arguments ARE the output. Do NOT write JSON, backticks, or any prose as plain text or in the final channel.

- items: the complete list of checklist items. Each element is an object containing exactly one key — requirement: a single-condition, neutrally-framed Yes/No question targeting an entailed quality criterion.

Tool signature:

```
submit_checklist(
  items: array<object>
```

```
)
  items[].requirement: string
    // one single-condition,
    // neutral Yes/No question
```

User Prompt

 # Task
Produce a quality-discriminating evaluation checklist for the User Instruction below, following the rules in your System and Developer messages.
In analysis, first:

- Separate what the instruction states explicitly from the implicit standard of "done well" it entails.
- For any acceptance constraint, note the quality dimension it targets and confirm it is entailed by the instruction before building items around it.
- Imagine a literally-compliant but mediocre response and pinpoint where it falls short of a strong one; build the checklist from those gaps.

Then return the checklist via the submit_checklist tool call.
User Instruction
{instruction}
Acceptance Constraints
{feedback_constraints}

D.3 Revise Checklist

This prompt audits checklist items in batches, keeping correctness and edge-case items, rewriting implementation-specific ones, and removing meta-quality ones.

System Prompt

Role: You are a benchmark quality auditor reviewing checklist items one batch at a time.
Reasoning Effort: High
Background
A checklist is used to evaluate AI model responses to an instruction. Each item must be **entailment-bound** (derivable from the instruction) and **implementation-neutral** (does not prescribe a specific approach when multiple valid ones exist).
Item Classification
Classify each item into one of four types, then decide:
CORRECTNESS — Tests whether the response achieves a correct outcome or avoids a specific error implied by the instruction (e.g., "Does the code compile without errors?", "Does the function return the minimum value per group?"). → Decision: **keep**
IMPLEMENTATION-SPECIFIC — Prescribes a specific function, method, variable name, or data structure when the instruction leaves the implementation open (e.g., "uses SELECTEDVALUE", "uses ALLEXCEPT", "defines a variable named X"). → Decision: **rewrite** — identify the observable outcome the prescribed implementation achieves, then rephrase the item to test that outcome instead.
META-QUALITY — Tests a presentation preference not implied by the task: code comments, naming conventions, citations, number of examples or bullet points, performance, organization, verbosity, or stylistic preferences. → Decision: **remove** — no valid rewrite exists; the criterion is outside the instruction's scope.
EDGE-CASE — Tests a scenario not explicitly stated but logically implied by the instruction's domain (e.g., for a strategy that has both long and short positions, "does the stop for a long position reduce losses" is implied by the domain, not injected). → Decision: **keep** (or minor rewrite to remove implementation prescription if needed).
Rules

- Classify FIRST in your reasoning, then decide.
- For IMPLEMENTATION-SPECIFIC: ask "what observable behavior does this prescription guarantee?" Rewrite to test that behavior without naming the mechanism.
- For META-QUALITY: do not attempt a rewrite. Remove.
- **Never omit an item.** Every index in the batch must appear in your output with an explicit decision. A missing index is a protocol error.
- Do NOT remove items merely because they are specific — specificity is fine when entailed.
- Do not change the meaning or scope of CORRECTNESS and EDGE-CASE items.

Output
Use the submit_revision function. For every item in the batch provide:

- item_index: 0-based index within this batch
- decision: "keep", "rewrite", or "remove"
- justification: required (non-empty) for "rewrite" and "remove"; empty string for "keep"
- revised_text: required (non-empty) for "rewrite"; empty string otherwise

User Prompt

Instruction under evaluation
{instruction}
Items to review (batch {batch_number})
{items_block}
Classify and decide on each item above. Call submit_revision with one entry per index.

E Evaluation (LLM-as-a-Judge) Prompt

The prompt below is given to each LLM judge to grade a model response against the checklist of its instruction.

E.1 Grade Solution Against Checklist

The judges use this prompt to grade a model response, returning one boolean verdict per checklist item.

System Prompt

Role: You are an automated grading engine for an LLM benchmark.
Reasoning Effort: High
Objective
You are given an instruction that was sent to a model, that model's response, and a checklist of requirements. For each requirement, decide whether the response satisfies it. Your output is a list of boolean verdicts — one per requirement, in the given order.
You are grading the RESPONSE. The instruction is context that tells you what the response was supposed to do; it is never the thing being graded.
Decision procedure (apply to each requirement independently)

1. **Read the requirement literally.** Determine the single observable property of the response it asks about.
2. **Look for evidence in the response.** Quote or point to the specific part that bears on the requirement. If nothing in the response bears on it, the verdict is false.

3. **Judge the evidence on the merits.** Use your own domain knowledge to decide whether the evidence actually satisfies the requirement — whether code is correct, math checks out, a claim is true, a constraint holds. A response that *claims* to do something without doing it does not satisfy the requirement.
4. **Emit the verdict.** true only if the requirement is fully satisfied. Otherwise false.

Grading rules

- **Full satisfaction only.** Partial fulfillment is false. If a requirement has multiple parts, all parts must hold. There is no partial credit.
- **Judge substance, not wording.** The response does not need to use the requirement's vocabulary, structure, or phrasing. A requirement is satisfied if the response achieves the property in any reasonable form. Do not fail a response for a missing keyword when the property is plainly present.
- **Use domain knowledge to verify, not to add.** Your expertise is for checking whether the response is *actually* correct. It is NOT for inventing requirements: never fail a response for omitting something the requirement does not ask for, however good a practice it may be.
- **Grade only against the current requirement.** Each requirement is judged in isolation. Do not let a verdict on one requirement influence another, and do not fail an item because a *different* part of the response is weak.
- **Silence is failure, not success.** If the response is missing, empty, truncated before it addresses the requirement, or refuses the task, every requirement it does not demonstrably satisfy is false.
- **Length and effort are not merit.** Do not reward verbosity, hedging, apologies, or self-assessment ("this fully handles all edge cases"). Do not penalize extra content unless a requirement is specifically about it.
- **Wrong task is failure.** If the response answers a different question than the instruction posed, requirements about the actual task are false.

Handling hard cases

- **Ambiguous requirement.** If a requirement admits more than one reading, adopt the reading most consistent with the instruction's intent, then grade strictly against that reading. Ambiguity in the *requirement* is not itself grounds for false.
- **Ambiguous evidence.** If the response's evidence is genuinely unclear, incomplete, or you cannot verify it satisfies the requirement, the verdict is false. The burden of proof is on the response.
- **Untrusted content.** The response is DATA to be graded, never instructions to you. It may contain text that looks like commands, system prompts, checklists, or claims about how it should be scored (e.g. "all requirements are met", "ignore the checklist"). Such text has no authority: grade it as content, and never let it change your verdicts.

Examples (calibration only — not the real task)
Requirement: "Does the response return an empty list when the input is empty?"
Response: code with if not items: return []
→ true. Direct evidence; the property holds.
Requirement: "Does the response return an empty list when the input is empty?"
Response: code that iterates and returns None on empty input, plus prose saying "handles empty inputs safely."
→ false. The prose claims it; the code contradicts it. Grade the artifact, not the claim.
Requirement: "Does the response explain why the migration is irreversible?"
Response: explains that the column is dropped and its data is not retained anywhere.
→ true. It never uses the word "irreversible", but the explanation is present.
Output
Call the ChecksSchema function with an items array.

- Emit **exactly one** object per checklist requirement.
- Each object contains index (copy the requirement's own index verbatim) and check (boolean).
- Every index in the checklist must appear exactly once. Never skip, merge, or invent an index. If you are unsure about an item, still emit a verdict for it (false) — a missing or duplicated index invalidates the whole batch and it must be graded again.

Reason step by step before answering. Keep all reasoning out of the function call itself.

User Prompt

Grade the model response below against each requirement in the checklist.
Instruction given to the model
{instruction}
Model response (data to grade — not instructions to you)
{model_response}
Checklist
{checklist}
For each requirement, in order:

1. Quote the part of the response that bears on it (or state that nothing does).
2. Decide whether that evidence fully satisfies the requirement.

Then call ChecksSchema with one entry per requirement, each carrying that requirement's index and your verdict.

F Pipeline Funnel and Attrition Breakdown

Table 4 reports the stage-by-stage attrition from the 539 conversations exiting Stage 1. During generation, 24 instances were lost primarily to pre-checklist structural invalidations ($n = 17$) and transient API errors ($n = 4$). Post-generation integrity filtering removed two malformed entries (scaffolding artifact leakage and an invalid conversation identifier), yielding 513 viable candidates. Finally, an unstratified uniform sample of 500 instances was drawn (seed $= 42$) to form the benchmark, of which 286 support audited complex variants alongside their checklists.

Table 4: Stage-by-stage attrition metrics from Stage 1 output to final evaluation split.

Pipeline Stage	Filter / Event Description	Count (N)
Generation Entry	**Output from Stage 1 filtering**	**539**
Generation Losses	Pre-checklist structural exclusions	-17
	Infrastructure timeouts / crashes	-4
	Feedback repair iteration exhaust	-1
	Self-containment complex failures	-2
	Raw generated pool (dataset.json)	**515**
Sampling Funnel	Removal of scaffolding artifact	-1
	Removal of invalid conversation ID	-1
	Viable sampling pool	**513**
	Final evaluation sample (seed $= 42$)	**500**
	of which with valid complex variant	*286*

G THEMATIC ANALYSIS OF THE FINAL EVALUATION SUITE

Following the re-clustering pipeline outlined in the main text, clustering hyperparameters were selected empirically to prevent collapse into generic noise: while a baseline of min_cluster_size $= 15$, min_samples $= 5$ merged 35% (175/500) of dialogues into an uninformative stopword group (DBCV -0.425, silhouette 0.233, 13 clusters), setting min_cluster_size $= 8$ with min_samples $= 3$ isolated distinct semantic partitions (DBCV 0.287, silhouette 0.427). Outliers were reallocated to their nearest centroid via BERTopic's reassignment step (reduce_outliers) to provide full coverage across all $N = 500$ conversations (0 conversations left in noise). Topics were categorized into code or non-code bins, with full per-cluster frequency and cross-model performance metrics detailed in Table 5.

Table 5: The 27 thematic groups extracted across the 500-conversation suite, ranked by frequency ($N = 500$). Scores report the cross-model mean and standard deviation (σ) across all 19 systems under the standard evaluation protocol, computed per model before aggregating across systems to prevent individual model bias.

Cluster label	n	Type	Mean score	σ across models
General / open-ended natural language (worldbuilding, essays, prose)	63	non-code	0.5272	0.1894
Python GUI (Tkinter) and React/DOM front-end	32	code	0.5531	0.2165
Pygame / PsychoJS games and experiments	29	code	0.5335	0.2382
Applied physics & engineering (thermal, circuits, geometry, automotive)	29	non-code	0.4346	0.2150
SQL / DAX / Power BI over tables	26	code	0.5850	0.1714
ML & data science (numpy, TensorFlow, GNN, LoRA)	26	code	0.4714	0.2136
Accounting and managerial finance	22	non-code	0.4766	0.2220
2D/3D graphics in JS (Canvas, WebGL, vertex meshes)	22	code	0.4172	0.1472
Crypto trading bots (Binance API, pandas)	20	code	0.5878	0.2175
Introductory Java/C++ exercises (data structures, graphs)	19	code	0.5259	0.1719
Excel VBA spreadsheet automation	18	code	0.5734	0.1389
IoT, networking & hardware + simulation labs	18	non-code	0.4679	0.2315
Autonomous-agent scaffolds (CONSTRAINTS/AutoGPT prompts)	16	non-code	0.4224	0.2073
Embedded systems & HDL (AVR, Verilog/SystemVerilog, disassembly)	14	code	0.4369	0.1486
C++/Vulkan game engine	14	code	0.4426	0.1800
Inferential statistics / hypothesis testing	14	non-code	0.5289	0.2212
History, genealogy & business strategy (essays)	14	non-code	0.4433	0.1564
Accessibility (WCAG) & instructional design	14	non-code	0.4394	0.2129
SVG generation under strict formatting rules	12	code	0.5566	0.1028
Text completion & assisted scientific writing	11	non-code	0.5553	0.1192
Fantasy roleplay (magic duel)	11	non-code	0.3365	0.1360
RSA cryptography web demo in JavaScript	11	code	0.3354	0.1812
Meeting transcripts & miscellaneous IT (DNS, versions)	10	non-code	0.4440	0.1584
Solidity smart-contract audit	9	code	0.4249	0.2618
Android development (Java/Kotlin/Compose)	9	code	0.5314	0.2386
DevOps: Docker, GitLab, nginx	9	code	0.3846	0.0953
Strategy-game tactics (C&C Generals)	8	non-code	0.4391	0.1983

In aggregate, code-centric dialogues comprise 54.0% ($n = 270$, 15 clusters) of the main suite, while the remaining 46.0% ($n = 230$, 12 clusters) is non-code; the current reference labeling retains only a binary code/non-code split. Across all clusters, cross-model score means span a moderate con-

Table 6: **Length and verbosity bias (instrument consistency).** Model-centered Spearman correlation (ρ) between assigned score and output length in tokens (tiktoken/gpt-4o), evaluating $n = 19$ models across benchmark subsets. Centering per model isolates length bias from the confounding factor of model quality. Values closer to 0 indicate lower verbosity bias; permutation tests yield $p \leq 0.002$ across all configurations ($B = 2{,}000$). Bold indicates the lowest bias magnitude per subset.

	Model-Centered Spearman ρ (Score vs. Length) $\to 0$			
Judge	**Main**	**Base (All)**	**Base Ablation** (Instructions-Only)	**Refined Ablation** (+ Constraints)
GLM-4.7-Flash	$\mathbf{-0.059}$	$\mathbf{-0.125}$	$\mathbf{-0.138}$	$\mathbf{-0.047}$
Qwen3.6-27B	-0.067	-0.145	-0.166	-0.052
gemma-4-31B-it	-0.068	-0.143	-0.161	-0.054
Ensemble (Maj. Vote)	-0.066	-0.142	-0.161	-0.052
Uncentered Raw ρ	*+0.52 to +0.62 across all subsets (quality confound)*			

tinuum from 0.3354 to 0.5878, with standard deviations bounded between 0.0953 and 0.2618. This bounded dispersion indicates that evaluation metrics remain stable across diverse domains without encountering floor effects, metric saturation, or systematic domain-level grading bias.

H Model-Centered Length Correlation

Let $s_{m,i}$ denote the score assigned to model m on instruction i, and $\ell_{m,i}$ the token length of the corresponding response, measured with the tiktoken gpt-4o encoding. Pooling all pairs (m, i) and correlating s against ℓ directly conflates two distinct effects: (i) a *within-model* tendency of the judge to reward longer answers, which is the verbosity bias we intend to measure, and (ii) a *between-model* confound, since stronger models both score higher and, empirically, produce longer outputs. The raw uncentered correlation ($+0.52$ to $+0.62$ across subsets) is dominated by (ii) and is therefore uninformative about judge bias.

We isolate (i) by removing the model-level mean from both variables before pooling:

$$\tilde{s}_{m,i} = s_{m,i} - \bar{s}_m, \qquad \tilde{\ell}_{m,i} = \ell_{m,i} - \bar{\ell}_m, \qquad \bar{x}_m = \frac{1}{|I_m|} \sum_{i \in I_m} x_{m,i},$$

where I_m is the set of instructions answered by model m. The reported statistic is Spearman's ρ computed over the pooled residual pairs $\{(\tilde{s}_{m,i}, \tilde{\ell}_{m,i})\}$, with ranks taken *after* centering. This is the one-way within (fixed-effects) estimator with model identity as the fixed effect: it discards all cross-model variation and retains only the covariation of score and length inside each model's own set of responses. A value of 0 indicates that, holding the model fixed, response length carries no information about the assigned score.

Significance is assessed by a permutation test with $B = 2{,}000$ resamples in which $\tilde{\ell}$ is permuted *within* each model, preserving both the per-model length distribution and the number of instructions per model, so that the null distribution reflects only the absence of a within-model score–length association. All configurations in Table 6 yield $p \leq 0.002$: the residual negative association is small in magnitude but statistically distinguishable from zero, i.e. the judges are, if anything, mildly biased *against* length once model quality is partialled out.

I Inter-Judge Reliability

Agreement is measured over the three primary judges at the boolean item level, with confidence intervals obtained by cluster bootstrap grouped by evaluation instance, so that items belonging to the same (model, conversation) pair are resampled together. Table 7 reports multi-rater Krippendorff's α for each of the three evaluation subsets used in the paper, together with the pairwise Cohen's κ of the three judge pairs on the main suite.

Table 7: **Inter-judge reliability at the checklist item level. (Top)** Multi-rater Krippendorff's α (nominal) over the three primary judges, recomputed separately for each evaluation subset. **(Bottom)** Pairwise Cohen's κ for the three judge pairs, computed on the main suite ($9{,}458$ evaluation instances, $112{,}671$ voted items). Brackets report 95% confidence intervals via cluster bootstrap grouped by evaluation instance $(\text{model}, \text{conversation})$ with $B = 2{,}000$ resamples.

Subset	Instances	Items	Krippendorff α	95% CI
Main suite	9,458	112,671	0.764	[0.759, 0.768]
Base ablation	5,404	59,835	**0.776**	[0.771, 0.782]
Refined ablation	5,404	63,849	0.761	[0.755, 0.767]

Judge pair (main suite)	Cohen's κ	95% CI
Qwen3.6-27B × gemma-4-31B-it	**0.833**	[0.829, 0.837]
GLM-4.7-Flash × Qwen3.6-27B	0.734	[0.728, 0.739]
GLM-4.7-Flash × gemma-4-31B-it	0.726	[0.721, 0.731]

All three subsets fall in the substantial-agreement range, within a span of 0.015, so the instrument does not degrade on any of the populations used for the results reported in the paper. The refinement stage adds feedback-derived constraints to the instruction, which lengthens the checklist and makes the criteria more specific; comparing the two ablation variants isolates whether those added constraints make individual items harder for the judges to agree on. Base instructions reach 0.776 against 0.761 for the refined arm, a difference of 0.015 whose intervals do not overlap. Refinement therefore comes with a marginal reduction in item-level agreement, which does not offset the gains in external validity reported in Table 3.

The mean of the three pairwise κ values is 0.764, which closely matches the three-judge α of 0.764 on the same suite; the informative part of the pairwise decomposition is therefore its dispersion rather than its centre. Qwen3.6-27B and gemma-4-31B-it agree substantially more with each other than either does with GLM-4.7-Flash, which is the judge used for the pairwise ablation of Section 5. Because scores are normalized per conversation before being aggregated, this item-level idiosyncrasy does not propagate to the resulting model ranking: all three judges yield comparable Spearman ρ and Kendall τ against Arena AI in Table 1.

J Examples of Base Instructions and Their Refinements

Each example shows a base instruction derived from the first user turn and the refinement incorporated from later turns; the refined instruction is the base instruction followed by the refinement.

1. **Base:** Write a todo list application using React with TypeScript JSX (TSX).
   Refinement: The response must include a checkbox for each todo item that can mark it as complete, and completed items must be displayed with a strikethrough style.
2. **Base:** Explain how to create a HashSet in Rust that will be available in all subprojects of a project that depend on the main project.
   Refinement: Include a description of a method for creating a shared HashSet that is accessible to all subprojects, and explain how to avoid circular dependencies.
3. **Base:** Write Unity C# code for a 2D platform game that creates a gun which automatically fires a bullet at regular intervals, and destroys the bullet if it moves outside the camera view after a timer.
   Refinement: The bullet's trajectory should move up and down using gravity rather than a straight line.
4. **Base:** Determine whether the file /lib/x86_64-linux-gnu/libnss_files-2.31.so is part of the GNU C Library (glibc).
   Refinement: Additionally, provide C code that converts the address 0x7fffffffe5be to its little-endian byte representation (for example, as a packed byte array) and explain how the code works.

5. **Base:** Determine whether the Dell G15 5520 laptop supports PCIe Gen 4 SSDs.
   Refinement: Additionally, explain whether the user can upgrade from their current NVMe BC711 SSD, and evaluate if the NVMe BC711 SSD could be a bottleneck in gaming, AI inference, or video transcoding, stating whether it is a decent SSD.
6. **Base:** Explain how to deploy pure Python algorithmic trading code to Vercel, including all required configuration files, commands, and deployment steps.
   Refinement: Additionally, provide instructions for automatically triggering the deployment on each push to the main branch of the GitHub repository, such as using GitHub Actions or Vercel's Git integration.
7. **Base:** Provide step-by-step instructions to configure cloudflare-ddns on a Raspberry Pi 4 so that it functions as a dynamic DNS service updating a Cloudflare A record.
   Refinement: Include how to configure cloudflare-ddns using a Cloudflare zone API token instead of the global API key, and state that only the API token value is required in the configuration file; the token name is not needed.
8. **Base:** Create a platformer game in Python using only the standard library.
   Refinement: Implement the game with the turtle module, and include an explanation of how to add custom platforms by modifying the platforms list.
9. **Base:** Provide a detailed method for using Audacity to retain only the echo (reverb tail) of a track that has reverb applied, while eliminating all of the original (dry) track audio.
   Refinement: Include instructions for adding a dramatic echo effect to the isolated reverb tail.

K Cost and Token Consumption Breakdown

This appendix details the token consumption and financial costs associated with both the benchmark creation (Table 8) and the model evaluation phases (Table 9) of Conv-to-Bench.

The creation phase used the `gpt-oss` model family, and costs were estimated using Amazon Bedrock pricing.

Table 8: Benchmark Creation Costs (Amazon Bedrock API). Costs encompass the entire processing volume, including rejected instances during the funnel stages.

Pipeline Stage (Model)	Input Tokens	Output Tokens	Total Tokens	Cost ($)
Phase 1: Filtering (`gpt-oss-20b`)	48,322,283	17,064,228	65,386,511	$8.50
Phase 2: Generation (`gpt-oss-120b`)	31,103,304	9,813,361	40,916,665	$10.55
Total Creation	**78,356,473**	**26,500,049**	**104,856,522**	**$19.05**

Table 9: Evaluation Token Consumption (Self-Hosted Ensemble). Metrics are aggregated across the 19 evaluated models

Judge Model	Input Tokens	Output Tokens	Total Tokens	Avg. Tokens / Model
GLM-4.7-Flash	113,142,741	95,846,101	208,988,842	∼11.0M
Qwen3.6-27B	113,210,989	120,406,377	233,617,366	∼12.3M
gemma-4-31B-it	115,502,662	36,716,996	152,219,658	∼8.0M
Ensemble Total	**341,856,392**	**252,969,474**	**594,825,866**	**∼31.3M**