CAN VIDEO-LANGUAGE MODELS BE INDUCED TO HALLUCINATE OBJECTS? A STUDY OF SEMANTIC IMPLANTATION VIA FEATURE ALIGNMENT

Anonymous authors
Paper under double-blind review

ABSTRACT

Video-Language Models (Vid-LMs) have achieved remarkable success in multimodal understanding, yet the robustness of their internal visual–semantic alignment remains poorly understood. In this work, we ask a fundamental question: Can Vid-LMs be induced to hallucinate non-existent objects by directly manipulating their intermediate multimodal representations? We introduce Adversarial Object Hallucination (AOH), a controlled probing framework for semantic implantation that injects target object concepts into the model's latent space via subtle perturbations. AOH operates via intermediate feature alignment, forcing the representation of an original, object-free video to mimic the latent semantics of a counterpart video where the target object is naturally present. To support systematic analysis, we construct AOH-Bench, a first-of-its-kind benchmark comprising 555 high-fidelity video pairs that enable direct comparison between implanted hallucinations and genuine object perception. Our evaluation of state-of-the-art Vid-LMs reveals three key phenomena: (1) Universality: all evaluated models consistently exhibit object hallucination under AOH; (2) Cross-scale Transferability: hallucination-inducing videos optimized on small models (e.g., 0.5B) transfer effectively to much larger models (e.g., 7B); (3) Stealthiness: hallucinations emerge without noticeable shifts in visual attention, suggesting a covert disruption of the visual–language semantic interface rather than perceptual mislocalization. Overall, our findings expose a systemic vulnerability in Vid-LMs, highlighting a fundamental gap between visual perception and linguistic description.

1 INTRODUCTION

Video-Language Models (Vid-LMs) (Maaz et al., 2024; Chen et al., 2023; Zhang et al., 2025a) have emerged as a central component in modern visual intelligence systems, enabling high-level semantic reasoning in domains such as autonomous driving (Cui et al., 2024a), security surveillance (Lv & Sun, 2024; Wang & Zeng, 2025), and content moderation (AlDahoul et al., 2024; Zhang & Zeng, 2024). Architecturally, these models bridge high-dimensional spatio-temporal visual signals and natural language through a multimodal *connector* (Lin et al., 2024), which maps visual representations into the language model's semantic space. Consequently, the reliability of Vid-LMs hinges critically on the robustness of this visual–semantic alignment. As Vid-LMs are increasingly deployed in safety-critical settings, a fundamental question arises:

How robust is the internal visual-semantic alignment of Vid-LMs, and can it be systematically manipulated without leaving perceptible visual traces?

Prior work on Vid-LM robustness has primarily studied the effects of low-level visual perturbations aimed at degrading overall performance or triggering specific outputs (Li et al., 2024; Huang et al., 2025). While these efforts uncover notable vulnerabilities, they typically treat adversarial perturbations as unstructured noise and do not address a more fundamental issue: the *controllability* of the model's internal semantic representations (Zhao et al., 2023). As a result, it remains unclear whether the visual–semantic interface of Vid-LMs can be systematically manipulated to induce specific, structured semantic outcomes.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: **Illustration of Adversarial Object Hallucination (AOH) and AOH-Bench statistics.** *Left (Case Study):* An illustrative autonomous driving scenario where a subtle perturbation induces a Vid-LM to hallucinate a pedestrian on an empty highway, triggering a dangerous trajectory deviation in downstream planning. *Right (Dataset Statistics):* Overview of the proposed AOH-Bench, showing: (top-left) the composition of source datasets dominated by ROVI; (top-right) a word cloud illustrating the diversity of target objects (e.g., person, bird, car); and (bottom) the distribution of video resolutions in megapixels.

To address this question, we investigate a targeted phenomenon that directly probes the controllability of semantic representations in Vid-LMs, which we term **Adversarial Object Hallucination (AOH)**. AOH refers to inducing a model to confidently describe an object that is absent from the visual input, without introducing any explicit visual cues; for instance, reporting a "person" in a scene depicting an otherwise empty roadway (see Fig. 1, left). In this work, AOH is used as a diagnostic probe for examining the stability of intermediate multimodal representations (Li et al., 2023b; Chen et al., 2024). From this perspective, AOH captures a form of *semantic implantation*, where target object concepts are injected into the model's latent space while the observable video content shows no obvious visual changes.

To operationalize this probing framework, we design an intermediate feature alignment strategy that explicitly targets the visual–language interface of Vid-LMs. The method encourages the internal representation of an object-free input video to align with the latent semantics of a carefully matched counterpart video in which the target object naturally appears. By enforcing this alignment at the level of the visual encoder and multimodal connector, AOH induces structured semantic drift within the model's latent space, without manipulating output logits or introducing perceptual artifacts. This formulation enables us to attribute object hallucination to disruptions in internal visual–semantic alignment, rather than to superficial visual corruption.

A rigorous study of semantic implantation requires an evaluation protocol that goes beyond binary success rates. To this end, we construct **AOH-Bench** (summarized in Fig. 1, right), a first-of-its-kind diagnostic benchmark comprising 555 high-fidelity video pairs. Uniquely, each pair consists of a clean video (where the object is absent) and a carefully matched *target counterpart* (where the object naturally exists). This paired structure enables direct, representation-level comparison between implanted hallucinations and genuine object perception, allowing us to assess not only whether hallucination occurs, but how closely it aligns with the model's internal representation of a real object.

Leveraging AOH-Bench, we conduct a comprehensive evaluation across state-of-the-art Vid-LMs and identify three key empirical phenomena. (1) *Universality*: object hallucination can be consistently induced across all evaluated models under AOH, indicating that semantic implantation reflects a widespread vulnerability rather than an isolated failure mode. (2) *Cross-scale Transferability*: we observe that hallucination-inducing videos optimized on small models (e.g., 0.5B) remain highly effective when transferred to much larger models (e.g., 7B) within the same architectural family, suggesting that scaling model capacity does not inherently mitigate vulnerabilities rooted in shared representational geometry. (3) *Stealthiness*: Grad-CAM analysis reveals that these hallucinations emerge without noticeable shifts in visual attention. While visual focus remains grounded in naturally salient regions of the input video, the linguistic output reports non-existent entities, pointing to a covert disruption of the visual–language semantic interface rather than perceptual mislocalization.

In summary, our findings expose a systemic vulnerability in Vid-LMs, highlighting a fundamental gap between visual perception and linguistic description. Our main contributions are three-fold:



Figure 2: **Overview of the Adversarial Object Hallucination (AOH) framework via feature alignment.** The framework probes the semantic robustness of Video-Language Models (Vid-LMs) through a three-stream process: (Top) The target stream extracts reference semantic embeddings from a target video x_{tar} containing the object of interest. (Middle) The optimization stream iteratively updates a learnable, imperceptible perturbation δ by minimizing the matching loss between the intermediate features of the clean video x_{cle} and the target embeddings. All Vid-LM modules (Encoder Φ, Connector, and LLM) remain frozen; only the perturbation δ is trainable. (Bottom) The resulting adversarial video $x_{\text{adv}} = x_{\text{cle}} + \delta$ is fed into the Vid-LM with a query c_{in}. Despite being visually indistinguishable from x_{cle}, x_{adv} induces a response c_{out} that confidently hallucinates the target object, exposing a gap in visual-semantic alignment.

- We formalize controlled *semantic implantation* in Vid-LMs and propose **AOH** as a probing framework to investigate the robustness of intermediate representations.
- We release **AOH-Bench**, a first-of-its-kind benchmark of 555 counterpart video pairs for rigorous, quantitative comparison between implanted hallucinations and genuine object perception.
- Through extensive experiments, we characterize object hallucination in Vid-LMs along three key empirical dimensions: universality across models, cross-scale transferability, and stealthy decoupling of visual attention from linguistic output.

Related works. Most existing approaches conceptualize adversarial perturbations as unstructured noise that degrades performance (Hu et al., 2025; Wang et al., 2024; Zhang et al., 2025b) or elicits predefined outputs (Zou et al., 2023; Jin et al., 2024; Yi et al., 2024). In contrast, our work focuses on *semantic implantation*, inducing controlled object hallucinations by directly manipulating the multimodal connector to probe the robustness of visual–language alignment within Vid-LMs.

2 Semantic Implantation in Vid-LMs via Feature Alignment

To investigate whether Video-Language Models (Vid-LMs) can be induced to hallucinate objects that do not exist, we propose a probing mechanism that perturbs internal visual-semantic representations while ensuring the visual changes remain bounded. We formalize this as *Adversarial Object Hallucination (AOH)*, a controlled semantic implantation problem, and introduce a feature-level probing strategy that directly targets the visual–language interface of Vid-LMs. Unlike conventional adversarial attacks, AOH serves as a *diagnostic probe* to analyze the causal role and flexibility of intermediate multimodal representations. The overall pipeline of our semantic implantation strategy is illustrated in Fig. 2.

2.1 Semantic Implantation as a Diagnostic Probe

We formalize a Vid-LM as a composite function F that maps a video input x_v and a textual prompt c_{in} (e.g., a question) to a generated textual response c_{out}:

$$F(x_v, c_{\text{in}}) = \text{LLM}(\text{Connector}(\text{Encoder}(x_v)), c_{\text{in}}). \tag{1}$$

Our goal is to probe whether the internal visual-semantic representation of a Vid-LM can be *selectively implanted* with a target object concept. Specifically, given a clean video x_{cle} in which a particular object is absent, and a matched target video x_{tar} in which the object naturally appears, we seek a subtle perturbation δ such that the resulting adversarial video, defined as

$$x_{\text{adv}} = x_{\text{cle}} + \delta, \quad \|\delta\|_\infty \leq \epsilon, \tag{2}$$

causes the model to confidently report the presence of the target object. To ensure that induced hallucinations stem from internal representational manipulation rather than directly visual cues, we impose a norm-constrained constraint on the perturbation. Under this constraint, x_{adv} maintains high visual consistency with x_{cle} and shows no obvious visual changes to the original scene. Consequently, AOH isolates a semantic failure mode rather than a simple perceptual corruption, making it a precise diagnostic probe of the model's visual-language alignment.

2.2 Intervening on Intermediate Visual-Semantic Representations

A key design question in semantic implantation is *where* to intervene in Vid-LMs. Prior adversarial approaches typically operate at the output level, such as maximizing the likelihood of specific tokens. However, object hallucination requires more than triggering isolated outputs: it must be semantically coherent, robust to follow-up queries, and compatible with multiple linguistic descriptions. These requirements render output-level manipulation insufficient.

We therefore intervene on *intermediate representations* that bridge visual perception and language generation. In Vid-LMs, the Encoder–Connector interface serves as a semantic bottleneck, compressing high-dimensional spatio-temporal features and aligning them with linguistic concepts (Zhang et al., 2024). By steering this interface toward a specific semantic configuration, we can causally shape the model's downstream interpretation while satisfying the aforementioned visual consistency constraints. Concretely, let $\Phi(\cdot)$ denote the feature extraction up to a chosen intermediate layer spanning the encoder and connector. We optimize a perturbation δ that makes the representation of a clean video resemble that of a matched target video containing the desired object:

$$\begin{aligned} \min_{\delta} \quad & \mathcal{L}_{\text{align}}\big(\Phi(x_{\text{cle}} + \delta), \Phi(x_{\text{tar}})\big) \\ \text{s.t.} \quad & \|\delta\|_\infty \leq \epsilon, \end{aligned} \tag{3}$$

where $\mathcal{L}_{\text{align}}$ measures the discrepancy between feature representations, instantiated via negative cosine similarity (Kornblith et al., 2019):

$$\mathcal{L}_{\text{align}}(u, v) = -\frac{u \cdot v}{\|u\|_2 \|v\|_2}. \tag{4}$$

We optimize Eq. (3) using Projected Gradient Descent (PGD) (Madry et al., 2018), gradually nudging the clean video's intermediate representation toward that of the target video. This process requires no supervision on output tokens or object labels; the induced hallucination arises entirely from the model's internal visual–language semantics.

Distinction from Language-Level Manipulation. A natural question is whether the observed hallucinations could be induced through purely textual means, such as prompting strategies that explicitly mention or hint at the target object. To isolate the role of feature-level manipulation, we contrast AOH against a prompt-injection baseline in which the target object is explicitly named in the question (Appendix B.5). Critically, we find that feature-level implantation and language-level suggestion constitute qualitatively distinct failure modes: models vary widely in their susceptibility to text-based hinting, yet AOH consistently induces hallucinations across all evaluated architectures, including those resistant to prompt manipulation. This dissociation underscores that AOH operates through direct visual-semantic alignment rather than exploiting language priors, and positions it as a controlled diagnostic probe rather than a variant of existing prompt-based attacks.

3 AOH-Bench: A Diagnostic Benchmark for Object Hallucination in Vid-LMs

Binary success criteria are insufficient for studying object hallucination, as they fail to capture the extent to which an implanted perception aligns with genuine object understanding (Li et al., 2023b).

A principled evaluation therefore requires measuring the similarity between implanted and naturally occurring object perception at the representation level. To this end, we introduce **AOH-Bench**, the first diagnostic benchmark designed for representation-level evaluation of semantic implantation in Vid-LMs.

The core innovation of AOH-Bench lies in its *counterpart video pairs*. Each entry includes a clean video x_{cle} and a matched target video x_{tar}. These pairs share identical background contexts but differ by a specific semantic entity. For each pair, we design a query (c_{in}) and two mutually exclusive ground-truth answers. As illustrated in Fig. 2, x_{cle} depict an empty roadway while x_{tar} serves as the *semantic gold standard* showing a white truck:

- **Question:** "What can be seen passing by on the left side of the road?"
- **Clean GT** of x_{cle}: "On the left side of the road, there are several utility poles, a row of multi-story buildings..."
- **Target GT** of x_{adv}: "A white postal truck."

Successful semantic implantation forces the model to output **Target GT** rather than **Clean GT** given x_{adv}. This ensures the hallucination is a structured semantic shift aligned with genuine perception.

3.1 Counterpart Video Acquisition

We construct AOH-Bench by integrating and refining videos from four complementary sources: HQVI (Cho et al., 2025), ROVI (Wu et al., 2024), Video-Sham (Mittal et al., 2023), and a custom-curated driving dataset based on BDD100K (Yu et al., 2020). These sources provide diverse object categories, scene layouts, and motion patterns, which are essential for evaluating semantic implantation across varied visual contexts. For datasets involving object removal, we adopt a "reverse thinking" strategy: the original unedited sequence is treated as the target video x_{tar}, while the inpainted sequence serves as the clean video x_{cle}. This approach ensures that x_{tar} reflects natural object appearance, while x_{cle} remains visually realistic yet object-free.

Hierarchical Quality Control. A primary challenge in constructing counterpart video pairs is preventing residual visual artifacts from confounding semantic evaluation. To ensure that hallucinations arise from semantic manipulation rather than low-level visual cues, we employ a strict two-stage quality control protocol:

- **Initial Consensus Screening.** Three independent annotators evaluate each x_{cle} candidate on a 5-point scale across three analytical dimensions: *Spatial Coherence*, *Temporal Consistency*, and *Artifact Severity*. These criteria jointly inform an *Overall Removal Quality* score. Only videos achieving an aggregate score of 14 or 15 are retained for further review.
- **Secondary Expert Review.** Pre-selected candidates undergo a rigorous expert inspection to eliminate samples with subtle or systematic visual traces. This final step ensures that object absence is visually seamless, thereby isolating semantic perception from pixel-level artifacts.

The final AOH-Bench contains *555 clean/target video pairs*.

3.2 VQA Annotation

To quantitatively assess semantic implantation, we design VQA annotations that probe both object presence and object-specific attributes or actions. Each VQA pair is constructed through a multi-stage pipeline emphasizing clarity, factual precision, and absence-awareness:

1. **Information Integration.** We aggregate video descriptions, manually curated target object descriptions, and object masks generated using SAM2 (Ravi et al., 2025) as structured context.
2. **Consensus-based Question Generation.** A committee of LLMs (i.e., GPT-4o (Achiam et al., 2023), Claude-3.5-Sonnet (Anthropic, 2024), and DeepSeek-V3 (Liu et al., 2024)) generates candidate questions targeting object existence and salient attributes or actions.

Table 1: **Quantitative evaluation of semantic implantation.** Results on AOH-Bench comparing model responses under intrinsic perception, control perturbations, and semantic implantation. All results are reported as Accuracy / ChatGPT-3.5-assisted semantic fidelity score. **Intrinsic Perception** reports baseline performance on clean videos (object absent) and target videos (object naturally present). **Control Perturbations** include the no-implantation baseline (**None**) and unstructured noise variants (**Global** and **Masked**), isolating the effect of random visual corruption. **Semantic Implantation** (**AOH**) applies feature-aligned perturbations that align intermediate visual–semantic representations with those of the target video. **Gain vs. None** reports the relative gain in fidelity score achieved by AOH over the non-implantation baseline.

Architecture Model		Intrinsic Perception		Control Perturbations			Semantic Implantation	
		Clean (x_{cle})	Target (x_{tar})	None	Global	Masked	**AOH (Ours)**	*Gain vs. None*
SmolVLM2	0.5B	0.166 / 1.03	0.526 / 3.04	0.254 / 1.80	0.243 / 1.76	0.243 / 1.78	**0.546 / 3.08**	+71.1%
LLaVA-OneVision	0.5B	0.310 / 1.86	0.593 / 3.20	0.157 / 1.28	0.159 / 1.32	0.200 / 1.51	**0.607 / 3.26**	+154.7%
	7B	0.303 / 1.85	0.596 / 3.25	0.142 / 1.31	0.153 / 1.32	0.227 / 1.61	**0.386 / 2.36**	+80.2%
VideoLLaMA3	2B	0.480 / 1.99	0.575 / 3.14	0.141 / 1.15	0.146 / 1.18	0.164 / 1.22	**0.495 / 2.70**	+134.8%
	7B	0.438 / 1.91	0.659 / 3.48	0.168 / 1.34	0.175 / 1.32	0.180 / 1.38	**0.586 / 3.21**	+139.6%
InternVL 2.5	1B	0.350 / 1.66	0.580 / 3.24	0.209 / 1.48	0.218 / 1.49	0.223 / 1.53	**0.413 / 2.44**	+64.9%
	2B	0.461 / 1.88	0.614 / 3.32	0.187 / 1.39	0.204 / 1.42	0.211 / 1.50	**0.506 / 2.82**	+102.9%
	4B	0.384 / 1.69	0.631 / 3.41	0.245 / 1.60	0.245 / 1.62	0.263 / 1.68	**0.395 / 2.28**	+42.5%
	8B	0.381 / 1.69	0.640 / 3.42	0.227 / 1.55	0.214 / 1.56	0.240 / 1.63	**0.465 / 2.61**	+68.4%
Video-ChatGPT	7B	0.123 / 0.84	0.582 / 3.17	0.348 / 2.15	0.346 / 2.12	0.362 / 2.18	**0.402 / 2.35**	+9.3%

3. **Iterative Human Validation.** Each VQA pair undergoes human-in-the-loop refinement and is validated against sampled video frames using ChatGPT-5 (OpenAI, 2025) to ensure that ground-truth answers for both x_{cle} (object absent) and x_{tar} (object present) are unambiguous.

4 Experiments

In this section, we employ AOH as a diagnostic probe to empirically assess the stability of the visual-semantic interface in Vid-LMs. Our experiments are designed to characterize semantic implantation along three key dimensions:

1. **Susceptibility:** Whether semantic implantation consistently occurs across diverse Vid-LMs.
2. **Transferability:** Whether hallucination-inducing representations learned on one model generalize to others, particularly from smaller to larger reasoning backbones.
3. **Mechanism:** What representational, structural, and perceptual properties underlie successful semantic implantation in Vid-LMs.

4.1 Experimental Setup

Target Models. We evaluate *AOH-Bench* across a diverse set of open-source Video-Language Models (Vid-LMs) spanning different architectures and parameter scales, including *Video-ChatGPT* (7B) (Maaz et al., 2024), *VideoLLaMA3* (2B, 7B) (Zhang et al., 2025a), *InternVL 2.5* (1B–8B) (Chen et al., 2023), *LLaVA-OneVision* (0.5B, 7B) (Li et al., 2025), and *SmolVLM2* (Marafioti et al., 2025), with RTX 4090. To ensure controlled comparison of internal visual–semantic representations, we standardize the temporal sampling to *8 frames per video* for all models. Each model follows its native resolution handling strategy (e.g., dynamic resolution in VideoLLaMA3), with an upper bound of 480p imposed when necessary for memory constraints. [1] Following prior works (Cheng et al., 2024; Zhang et al., 2025a; Zeng et al., 2024), we set the generation temperature to 0 during evaluation to ensure deterministic outputs.

Evaluation Protocol. We define three evaluation states that progressively characterize intrinsic perception and semantic implantation:

[1] https://github.com/DAMO-NLP-SG/VideoLLaMA3/issues/82



Figure 3: **Grad-CAM visualizations on LLaVA-OneVision-7B.** From top to bottom: clean video, target video (object present), AOH adversarial counterpart, and the pixel-wise difference (scaled $\times 10$) between the adversarial and clean videos (best viewed in color).

- **Intrinsic Perception (Clean):** The input is the clean video x_{cle} paired with the ground truth *Clean GT*. This setting measures the model's baseline ability to answer questions based on videos without target entity.
- **Intrinsic Perception (Target):** The input is the target video x_{tar}, paired with the ground truth *Target GT*. This condition establishes an upper bound on object perception when the target object is naturally present.
- **Semantic Implantation:** The input is the adversarially perturbed video x_{adv}. We evaluate whether the model outputs the *Target GT* despite the object being absent at the pixel level. We compare three perturbation strategies: (i) **Global Noise:** Adds Gaussian noise under the same ℓ_∞ budget, with variance derived from ϵ^2 following (Li et al., 2024); (ii) **Masked Noise:** Applies random noise restricted spatially and temporally to the target object's mask region; (iii) **AOH (Ours):** Generates adversarial perturbations via PGD (300 steps) with an ℓ_∞ budget of $\epsilon = 8/255$ (simply following previous works (Madry et al., 2018; Zhao et al., 2023; Li et al., 2024)) to align intermediate visual–semantic feature.

Metrics. For a fair comparison, we follow established practices in multimodal VQA (Maaz et al., 2024), reporting **Accuracy** to assess binary correctness and **ChatGPT-3.5-assisted semantic fidelity scores (0–5)** to quantify the semantic alignment between the model's response on x_{adv} and the ground-truth Target GT answer. Source code is provided in the supplementary material.

4.2 Does Semantic Implantation Occur Consistently?

Table 1 summarizes the primary evaluation results on AOH-Bench. The results provide clear evidence regarding the consistency and scope of semantic implantation across current Vid-LMs.

Universal Vulnerability. Across all evaluated architectures, AOH consistently induces the perception of non-existent objects. As shown in the *Semantic Implantation* column, AOH yields substantial gains over the *None* baseline—which captures the model's spontaneous hallucination rate—with relative improvements in accuracy ranging from **+15.5% to +286.6%**. In contrast, both global and masked random noise result in only marginal deviations from the *None* baseline. This gap indicates that targeted semantic implantation arises from structured feature alignment rather than from unstructured visual corruption.

Scale Does Not Guarantee Robustness. Increasing model size does not reliably mitigate susceptibility to semantic implantation. Within the **InternVL 2.5** family, the Acc score increases from 2.44

Table 2: **Cross-scale transferability of semantic implantation (LLaVA-OneVision).** Rows denote the source model used to optimize semantic implantation, while columns denote the target model on which the resulting perturbations are evaluated. The diagonal represents the *source-to-source* (direct) performance, while off-diagonal cells represent *cross-scale* transfer. Results are reported as Accuracy / ChatGPT-3.5-assisted semantic fidelity score. The *transfer ratio* is defined as the ratio of the target model's fidelity score to the source model's.

Source	Target		Transfer Ratio
	0.5B	7B	
0.5B	0.607/3.26	0.533/3.02	92.6%
7B	0.312/2.00	0.386/2.36	84.7%



Figure 4: **Distribution of semantic fidelity scores across target object sizes.** Semantic fidelity scores (0–5) grouped by the proportion of the video frame occupied by the target object. The highest frequency of perfect scores (5) occurs for medium-sized objects covering 30–40% of the frame.

(1B) to 2.82 (2B) and remains comparably high at 2.61 (8B). A similar trend is observed in **VideoLLaMA3**, where the 7B model exhibits higher susceptibility (Score 3.21) than its 2B counterpart (Score 2.70). These results suggest that the vulnerability is not primarily governed by the scale of the language backbone, but instead is rooted in the visual encoder and vision–language connector alignment, which remains largely unchanged under parameter scaling.

Interpreting Clean vs. Target Performance. On average across models, performance on **Target** videos exceeds that on **Clean** videos. This asymmetry is expected, as some questions require correctly asserting object *absence* in the clean setting—a known challenge for vision-language models. Prior work on negative object presence evaluation (NOPE) (Lovenia et al., 2024) has shown that such absence-based reasoning is systematically more difficult than presence-based recognition, and thus does not indicate a weakness in the benchmark itself.

4.3 Cross-Scale Transferability

To characterize the generalization of implanted semantic features, we examine whether adversarial perturbations optimized on smaller models remain effective when transferred to larger ones. Our analysis focuses on the **LLaVA-OneVision** family (0.5B and 7B), which provides a controlled setting in which the vision encoder architecture is largely shared while the language backbone scales substantially. This design isolates the effect of LLM scaling from changes in the visual frontend. Notably, AOH exhibits a pronounced performance gap within this family (Score 3.26 vs. 2.36), making it particularly suitable for analyzing cross-scale transfer behavior.

Small-to-Large Generalization. As shown in Table 2, perturbations optimized on the 0.5B model transfer effectively to the 7B model, achieving an Accuracy of 0.533 and a semantic fidelity score of 3.02. Strikingly, these transferred perturbations outperform those optimized directly on the 7B model itself (Score 2.36). This outcome suggests that the optimization landscape of the smaller model may be smoother, enabling AOH to identify feature-aligned directions that generalize more robustly across scales for a shared visual encoder.

Implications of Shared Vision Encoders. Within a model family, the vision encoder (e.g., SigLIP-SO400M (Zhai et al., 2023)) is typically shared or structurally identical, even as the language backbone scales. The strong transferability observed here indicates that the primary locus of semantic implantation lies in the *visual feature space*, rather than in the language reasoning module. Consequently, the larger 7B LLM, despite its increased reasoning capacity, is unable to override the hallucinated visual signal propagated from the frontend. This finding underscores a key limitation of scale-based mitigation strategies: increasing the size of the reasoning backbone alone is insufficient to address hallucinations if the visual encoder remains vulnerable to feature-level manipulation.

4.4 Mechanistic Analysis: How Vid-LMs are Deceived

To move beyond existence proofs and understand the underlying dynamics of *how* Vid-LMs are deceived, we analyze the structural and perceptual characteristics of the optimized perturbations.

Spatial Structure of Perturbations. To confirm that AOH does not succeed by merely injecting unstructured noise, we visualize the learned perturbation δ. As illustrated in the bottom row of Fig. 3, the perturbation exhibits distinct, structured high-frequency patterns rather than Gaussian randomness or a clear target entity shape. These patterns effectively trace the semantic contours of the target object, suggesting that the optimization process successfully inverts deep semantic features back into the pixel space. By embedding these features into the background texture, AOH introduces a "semantic watermark" that is legible to the visual encoder but remains subtle and non-obtrusive to human observers.

Visual Attention under Implantation. A critical hypothesis regarding hallucination is whether the model spatially attends to the region where the non-existent object "should" be. We extend Grad-CAM (Selvaraju et al., 2017) to video understanding tasks to analyze the model's visual attention during the generation of the response. Strikingly, our analysis reveals a consistent **decoupling of visual attention from linguistic output**. As shown in Fig. 3, the model's attention does not shift to the empty region corresponding to the hallucinated object; instead, it remains anchored to naturally salient background elements (e.g., trees, river boundaries), identical to its behavior on clean inputs. This implies a covert mechanism: the object concept is implanted through manipulation of the visual-semantic interface, effectively bypassing spatial grounding. The LLM generates the object description because its internal state reflects the object's presence, not because the vision encoder has localized a specific pixel patch. This phenomenon highlights a significant risk, as such hallucinations are "stealthy" and may evade detection by standard explainability methods based on attention maps (Chattopadhay et al., 2018).

Impact of Target Object Properties. We investigate the relationship between the physical scale of the target object and the success of implantation. By grouping target objects by their screen coverage ratio in x_{tar}, we observe a distinct non-monotonic vulnerability profile, as summarized in Fig. 4:

- **Signal Insufficiency (Small Objects, $< 10\%$):** Implantation success is limited ($\sim$31% perfect scores). Small objects contribute minimal energy to the feature representation, making it difficult for the perturbation to override the dominant background context within the ℓ_∞ budget.
- **Optimal Vulnerability (Medium Objects, 30-40%):** We identify a "sweet spot" where vulnerability peaks, with 48.5% of samples achieving perfect semantic fidelity. At this scale, objects possess a sufficiently distinct semantic signature to steer the representation, yet are compact enough to be embedded without creating irreconcilable geometric conflicts with the global scene.
- **Contextual Conflict (Large Objects, $\geq 50\%$):** Success drops precipitously to zero for dominant foreground objects. Implanting such large entities requires altering the global scene structure, which generates massive pixel-level contradictions that cannot be resolved under visual consistency constraints.

This analysis suggests that Vid-LMs are most structurally vulnerable to the hallucination of medium-sized entities that can plausibly integrate into the existing scene context.

Further experimental results, including evaluation with Gemini-3.1-Flash, human evaluation, per-dataset breakdowns, and analysis of feature alignment position, are provided in the Appendix.

5 Conclusion

We propose Adversarial Object Hallucination (AOH) and introduce AOH-Bench as a benchmark to assess the semantic robustness of Vid-LMs. Our results reveal a systemic brittleness in the visual–semantic interface: object hallucinations are universal, transfer across model scales, and occur without shifts in visual attention. Future work should explore methods to enforce stronger grounding between visual representations and language generation in Vid-LMs.

REFERENCES

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. GPT-4 technical report. *CoRR*, abs/2303.08774, 2023.

Nouar AlDahoul, Myles Joshua Toledo Tan, Harishwar Reddy Kasireddy, and Yasir Zaki. Advancing content moderation: Evaluating large language models for detecting sensitive content across text, images, and videos. *CoRR*, abs/2411.17123, 2024.

Anthropic. Claude 3.5 sonnet. https://www.anthropic.com/news/claude-3-5-sonnet, 2024.

Aditya Chattopadhay, Anirban Sarkar, Prantik Howlader, and Vineeth N. Balasubramanian. Grad-CAM++: Generalized gradient-based visual explanations for deep convolutional networks. In *Proceedings of the IEEE Winter Conference on Applications of Computer Vision (WACV 2018)*, pp. 839–847. IEEE, 2018.

Xuweiyi Chen, Ziqiao Ma, Xuejun Zhang, Sihan Xu, Shengyi Qian, Jianing Yang, David Fouhey, and Joyce Chai. Multi-object hallucination in vision language models. In *Advances in Neural Information Processing Systems 38 (NeurIPS 2024), Vancouver, BC, Canada*, 2024.

Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, Bin Li, Ping Luo, Tong Lu, Yu Qiao, and Jifeng Dai. InternVL: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. *CoRR*, abs/2312.14238, 2023.

Zesen Cheng, Sicong Leng, Hang Zhang, Yifei Xin, Xin Li, Guanzheng Chen, Yongxin Zhu, Wenqi Zhang, Ziyang Luo, Deli Zhao, and Lidong Bing. VideoLLaMA 2: Advancing spatial-temporal modeling and audio understanding in video-llms. *CoRR*, abs/2406.07476, 2024.

Suhwan Cho, Seoung Wug Oh, Sangyoun Lee, and Joon-Young Lee. Elevating flow-guided video inpainting with reference generation. In *Proceedings of the 39th AAAI Conference on Artificial Intelligence (AAAI 2025), Philadelphia, PA, USA*, pp. 2527–2535. AAAI Press, 2025.

Can Cui, Yunsheng Ma, Xu Cao, Wenqian Ye, Yang Zhou, Kaizhao Liang, Jintai Chen, Juanwu Lu, Zichong Yang, Kuei-Da Liao, Tianren Gao, Erlong Li, Kun Tang, Zhipeng Cao, Tong Zhou, Ao Liu, Xinrui Yan, Shuqi Mei, Jianguo Cao, Ziran Wang, and Chao Zheng. A survey on multimodal large language models for autonomous driving. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision Workshops (WACVW 2024), Waikoloa, HI, USA*, pp. 958–979. IEEE, 2024a.

Xuanming Cui, Alejandro Aparcedo, Young Kyun Jang, and Ser-Nam Lim. On the robustness of large multimodal models against image adversarial attacks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR 2024), Seattle, WA, USA*, pp. 24625–24634. IEEE, 2024b.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *Proceedings of the 9th International Conference on Learning Representations (ICLR 2021), Virtual Event*. OpenReview.net, 2021.

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *Proceedings of the 3rd International Conference on Learning Representations (ICLR 2015), San Diego, CA, USA*, 2015.

Google DeepMind. Gemini. https://deepmind.google/models/gemini/, 2026.

Kai Hu, Weichen Yu, Li Zhang, Alexander Robey, Andy Zou, Chengming Xu, Haoqi Hu, and Matt Fredrikson. Transferable adversarial attacks on black-box vision-language models. *CoRR*, abs/2505.01050, 2025.

Linhao Huang, Xue Jiang, Zhiqiang Wang, Wentao Mo, Xi Xiao, Bo Han, Yongjie Yin, and Feng Zheng. Image-based multimodal models as intruders: Transferable multimodal attacks on video-based mllms. *CoRR*, abs/2501.01042, 2025.

Haibo Jin, Leyang Hu, Xinuo Li, Peiyan Zhang, Chonghan Chen, Jun Zhuang, and Haohan Wang. JailbreakZoo: Survey, landscapes, and horizons in jailbreaking large language and vision-language models. *CoRR*, abs/2407.01599, 2024.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey E. Hinton. Similarity of neural network representations revisited. In *Proceedings of the 36th International Conference on Machine Learning (ICML 2019), Long Beach, CA, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3519–3529. PMLR, 2019.

Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Peiyuan Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. LLaVA-OneVision: Easy visual task transfer. *Transactions on Machine Learning Research*, 2025, 2025.

Jinmin Li, Kuofeng Gao, Yang Bai, Jingyun Zhang, Shutao Xia, and Yisen Wang. FMM-Attack: A flow-based multi-modal adversarial attack on video-based llms. *CoRR*, abs/2403.13507, 2024.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven C. H. Hoi. BLIP-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *Proceedings of the 40th International Conference on Machine Learning (ICML 2023), Honolulu, HI, USA*, volume 202 of *Proceedings of Machine Learning Research*, pp. 19730–19742. PMLR, 2023a.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. Evaluating object hallucination in large vision-language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP 2023), Singapore*, pp. 292–305. Association for Computational Linguistics, 2023b.

Bin Lin, Yang Ye, Bin Zhu, Jiaxi Cui, Munan Ning, Peng Jin, and Li Yuan. Video-LLaVA: Learning united visual representation by alignment before projection. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP 2024), Miami, FL, USA*, pp. 5971–5984. Association for Computational Linguistics, 2024.

Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, et al. DeepSeek-V3 technical report. *CoRR*, abs/2412.19437, 2024.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023), New Orleans, LA, USA*, 2023.

Holy Lovenia, Wenliang Dai, Samuel Cahyawijaya, Ziwei Ji, and Pascale Fung. Negative object presence evaluation (NOPE) to measure object hallucination in vision-language models. In *Proceedings of the 3rd Workshop on Advances in Language and Vision Research (ALVR 2024)*, pp. 37–58, 2024.

Hui Lv and Qianru Sun. Video anomaly detection and explanation via large language models. *CoRR*, abs/2401.05702, 2024.

Muhammad Maaz, Hanoona Abdul Rasheed, Salman Khan, and Fahad Khan. Video-ChatGPT: Towards detailed video understanding via large vision and language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL 2024), Bangkok, Thailand*, pp. 12585–12602. Association for Computational Linguistics, 2024.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *Proceedings of the 6th International Conference on Learning Representations (ICLR 2018), Vancouver, BC, Canada*. OpenReview.net, 2018.

Andrés Marafioti, Orr Zohar, Miquel Farré, Merve Noyan, Elie Bakouch, Pedro Cuenca, Cyril Zakka, Loubna Ben Allal, Anton Lozhkov, Nouamane Tazi, Vaibhav Srivastav, Joshua Lochner, Hugo Larcher, Mathieu Morlon, Lewis Tunstall, Leandro von Werra, and Thomas Wolf. SmolVLM: Redefining small and efficient multimodal models. *CoRR*, abs/2504.05299, 2025.

Trisha Mittal, Ritwik Sinha, Viswanathan Swaminathan, John P. Collomosse, and Dinesh Manocha. Video manipulations beyond faces: A dataset with human-machine analysis. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision Workshops (WACV Workshops 2023), Waikoloa, HI, USA*, pp. 643–652. IEEE, 2023.

OpenAI. ChatGPT. https://chatgpt.com, 2025.

Qwen Team. Qwen3-vl technical report. *CoRR*, abs/2511.21631, 2025. doi: 10.48550/ARXIV.2511.21631. URL https://doi.org/10.48550/arXiv.2511.21631.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning (ICML 2021), Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 8748–8763. PMLR, 2021.

Nikhila Ravi, Valentin Gabeur, Yuan-Ting Hu, Ronghang Hu, Chaitanya Ryali, Tengyu Ma, Haitham Khedr, Roman Rädle, Chloé Rolland, Laura Gustafson, Eric Mintun, Junting Pan, Kalyan Vasudev Alwala, Nicolas Carion, Chao-Yuan Wu, Ross B. Girshick, Piotr Dollár, and Christoph Feichtenhofer. SAM 2: Segment anything in images and videos. In *Proceedings of the 13th International Conference on Learning Representations (ICLR 2025), Singapore*. OpenReview.net, 2025.

Ramprasaath R. Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-CAM: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV 2017), Venice, Italy*, pp. 618–626. IEEE Computer Society, 2017.

He Wang and Liang Zeng. Automated algorithmic discovery for gravitational-wave detection guided by llm-informed evolutionary monte carlo tree search. *CoRR*, abs/2508.03661, 2025.

Yubo Wang, Chaohu Liu, Yanqiu Qu, Haoyu Cao, Deqiang Jiang, and Linli Xu. Break the visual perception: Adversarial attacks targeting encoded visual tokens of large vision-language models. In *Proceedings of the 32nd ACM International Conference on Multimedia (MM 2024), Melbourne, VIC, Australia*, pp. 1072–1081. ACM, 2024.

Jianzong Wu, Xiangtai Li, Chenyang Si, Shangchen Zhou, Jingkang Yang, Jiangning Zhang, Yining Li, Kai Chen, Yunhai Tong, Ziwei Liu, and Chen Change Loy. Towards language-driven video inpainting via multimodal large language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR 2024), Seattle, WA, USA*, pp. 12501–12511. IEEE, 2024.

Sibo Yi, Yule Liu, Zhen Sun, Tianshuo Cong, Xinlei He, Jiaxing Song, Ke Xu, and Qi Li. Jailbreak attacks and defenses against large language models: A survey. *CoRR*, abs/2407.04295, 2024.

Fisher Yu, Haofeng Chen, Xin Wang, Wenqi Xian, Yingying Chen, Fangchen Liu, Vashisht Madhavan, and Trevor Darrell. BDD100K: A diverse driving dataset for heterogeneous multitask learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR 2020), Seattle, WA, USA*, pp. 2633–2642. Computer Vision Foundation / IEEE, 2020.

Liang Zeng, Liangjun Zhong, Liang Zhao, Tianwen Wei, Liu Yang, Jujie He, Cheng Cheng, Rui Hu, Yang Liu, Shuicheng Yan, et al. Skywork-Math: Data scaling laws for mathematical reasoning in large language models–the story goes on. *CoRR*, abs/2407.08348, 2024.

Liang Zeng, Yongcong Li, Yuzhen Xiao, Changshi Li, Chris Yuhao Liu, Rui Yan, Tianwen Wei, Jujie He, Xuchen Song, Yang Liu, et al. Skywork-SWE: Unveiling data scaling laws for software engineering in llms. *CoRR*, abs/2506.19290, 2025.

Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV 2023), Paris, France*, pp. 11941–11952. IEEE, 2023.

Boqiang Zhang, Kehan Li, Zesen Cheng, Zhiqiang Hu, Yuqian Yuan, Guanzheng Chen, Sicong Leng, Yuming Jiang, Hang Zhang, Xin Li, Peng Jin, Wenqi Zhang, Fan Wang, Lidong Bing, and Deli Zhao. VideoLLaMA 3: Frontier multimodal foundation models for image and video understanding. *CoRR*, abs/2501.13106, 2025a.

Hang Zhang, Xin Li, and Lidong Bing. Video-LLaMA: An instruction-tuned audio-visual language model for video understanding. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP 2023) System Demonstrations, Singapore*, pp. 543–553. Association for Computational Linguistics, 2023.

Jiaming Zhang, Junhong Ye, Xingjun Ma, Yige Li, Yunfan Yang, Yunhao Chen, Jitao Sang, and Dit-Yan Yeung. AnyAttack: Towards large-scale self-supervised adversarial attacks on vision-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR 2025), Nashville, TN, USA*, pp. 19900–19909. Computer Vision Foundation / IEEE, 2025b.

Lu Zhang and Liang Zeng. SAT-LDM: Provably generalizable image watermarking for latent diffusion models with self-augmented training. *CoRR*, abs/2501.00463, 2024.

Peng-Fei Zhang, Zi Huang, and Guangdong Bai. Universal adversarial perturbations for vision-language pre-trained models. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR 2024)*, pp. 862–871. ACM, 2024.

Ruixu Zhang, Deyi Ji, Lanyun Zhu, Xuanyi Liu, Yuxin Meng, Ruihang Chu, and Yujiu Yang. Video-zero: Self-evolution video understanding. *arXiv preprint arXiv:2605.14733*, 2026.

Yunqing Zhao, Tianyu Pang, Chao Du, Xiao Yang, Chongxuan Li, Ngai-Man Cheung, and Min Lin. On evaluating adversarial robustness of large vision-language models. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023), New Orleans, LA, USA*, 2023.

Wanqi Zhou, Shuanghao Bai, Qibin Zhao, and Badong Chen. Revisiting the adversarial robustness of vision language models: A multimodal perspective. *CoRR*, abs/2404.19287, 2024.

Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. MiniGPT-4: Enhancing vision-language understanding with advanced large language models. In *Proceedings of the 12th International Conference on Learning Representations (ICLR 2024), Vienna, Austria*. OpenReview.net, 2024.

Andy Zou, Zifan Wang, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *CoRR*, abs/2307.15043, 2023.

AI USE STATEMENT

In this work, we used generative AI tools in the following capacities, corresponding to the disclosures made at submission:

- *To aid and polish writing.* AI tools were used to revise and polish the prose of the manuscript.
- *For research ideation and execution.* AI tools assisted with the design of the attack and evaluation pipeline and with the implementation of the code.
- *To draft sections of the paper.* AI tools were used to draft and edit portions of the manuscript text.
- *To generate synthetic datasets.* AI tools were used to generate the paired video annotations that constitute AOH-Bench.

All experiments reported here were executed and verified by the authors; no quantitative result was generated, altered, or selected by an AI tool other than the language-model judges described in the Metrics section, whose outputs are reported as such. All figures and tables were produced programmatically from the resulting data. We have reviewed all AI-assisted work: the manuscript and code were read and verified by the authors, the AOH-Bench annotations were subjected to the multi-stage human quality control described in Appendix C.2, and the reference list was verified against the original publications. We take responsibility for the final content of this work, including text, claims, and artifacts produced with the aid of generative AI.

ETHICS STATEMENT

This research characterizes controlled hallucinations in Video-Language Models. While such vulnerabilities pose risks in safety-critical domains like autonomous driving, exposing these flaws is necessary for mitigation. We provide AOH-Bench to help the community measure and improve the robustness of the visual–semantic interface, motivating the development of robust training mechanisms and sensitive interpretability methods. All videos in AOH-Bench are drawn from existing public datasets under their original licenses, and the annotations we add describe object presence rather than identifying information about individuals.

A EXTENDED RELATED WORK

A.1 VIDEO-LANGUAGE MODELS

Video-Language Models (Vid-LMs) enable joint reasoning over spatio-temporal visual inputs and natural language, supporting complex video understanding tasks (Liu et al., 2023; Zhu et al., 2024). Representative systems such as Video-ChatGPT (Maaz et al., 2024), VideoLLaMA (Zhang et al., 2023; Cheng et al., 2024; Zhang et al., 2025a), InternVL (Chen et al., 2023), and LLaVA-OneVision (Li et al., 2025) exemplify this paradigm. Most Vid-LMs adopt a modular architecture: a visual **Encoder** (e.g., ViT (Dosovitskiy et al., 2021) or CLIP (Radford et al., 2021)) extracts spatio-temporal visual features, a multimodal **Connector** (e.g., Q-Former (Li et al., 2023a), MLP projection (Lin et al., 2024)) projects them into the language embedding space, and a **L**arge **L**anguage **M**odel (**LLM**) backbone performs multimodal reasoning and text generation. While existing research primarily emphasizes performance scaling and generalization, the robustness of the visual–semantic alignment within the connector remains largely under-explored (Li et al., 2023b; Cui et al., 2024b; Zeng et al., 2025).

A.2 ADVERSARIAL VULNERABILITIES IN MULTIMODAL MODELS

Adversarial robustness research originated from pixel-level perturbations against image classifiers (Goodfellow et al., 2015; Madry et al., 2018), and has progressively expanded toward higher-level semantic failures as models incorporate language understanding. In large language models, this line of work reveals semantic-level vulnerabilities such as prompt-based jailbreaking and induced hallucinations triggered by carefully constructed textual inputs (Zou et al., 2023; Jin et al., 2024; Yi et al., 2024). As vision and language are increasingly integrated, adversarial robustness studies

Table 3: **Breakdown of semantic implantation by dataset source for LLaVA-OneVision (0.5B/7B), evaluated with GPT-3.5-assisted scoring consistent with the main paper.** Results are reported as Accuracy / Semantic Fidelity Score.

Configuration		Intrinsic Perception		Control Perturbations			Semantic Implantation	
Model	**Dataset**	Clean (x_{cle})	Target (x_{tar})	None	Global	Masked	**AOH (Ours)**	*Gain vs. None*
LLaVA-OV 0.5B	BDD100K	0.000 / 0.30	0.500 / 3.20	0.200 / 1.50	0.100 / 1.40	0.200 / 1.50	**0.500 / 3.10**	+106.7%
	HQVI	0.800 / 3.90	0.500 / 2.60	0.100 / 0.60	0.100 / 0.50	0.100 / 0.70	**0.500 / 2.50**	+316.7%
	Video-Sham	0.478 / 2.55	0.612 / 3.31	0.060 / 0.91	0.060 / 1.00	0.090 / 1.08	**0.612 / 3.24**	+256.0%
	ROVI	0.282 / 1.75	0.594 / 3.19	0.171 / 1.34	0.175 / 1.38	0.218 / 1.59	**0.611 / 3.28**	+144.8%
LLaVA-OV 7B	BDD100K	0.300 / 1.50	0.400 / 2.80	0.100 / 0.70	0.100 / 0.80	0.100 / 0.70	**0.200 / 1.90**	+171.4%
	HQVI	0.900 / 4.30	0.600 / 3.10	0.000 / 0.30	0.000 / 0.40	0.000 / 0.30	**0.100 / 0.80**	+166.7%
	Video-Sham	0.358 / 2.09	0.537 / 3.22	0.075 / 1.08	0.104 / 1.03	0.075 / 1.06	**0.299 / 1.99**	+84.3%
	ROVI	0.282 / 1.77	0.609 / 3.27	0.156 / 1.38	0.165 / 1.39	0.256 / 1.74	**0.408 / 2.46**	+78.3%

Table 4: **Impact of feature alignment position.** Comparison of semantic implantation performance when optimizing at the Visual Encoder vs. the Connector.

Model	**Optimization Position**		**Score Δ**
	Encoder	**Connector**	
LLaVA-OV 0.5B	0.575 / 3.15	0.607 / 3.26	+3.5%
LLaVA-OV 7B	0.535 / 2.98	0.386 / 2.36	-20.8%

naturally extend to multimodal settings. Early work primarily focused on static image–text models (Zhou et al., 2024), examining adversarial failures in tasks such as image captioning and visual question answering through visual or textual perturbations (Zhao et al., 2023; Hu et al., 2025; Wang et al., 2024; Zhang et al., 2025b). With the emergence of video-based multimodal models, recent studies have begun to reveal vulnerabilities specific to Vid-LMs, including motion-aware attacks such as FMM-Attack (Li et al., 2024) and image-based transfer attacks (Huang et al., 2025).

B Extended Experimental Results

B.1 Per-Dataset Breakdown

Table 3 provides a fine-grained view of AOH performance across the four data sources constituting AOH-Bench. AOH outperforms control perturbations across all evaluated domains, from driving scenes (BDD100K) to general object-rich videos (ROVI, Video-Sham) and high-resolution content (HQVI). This domain-invariant effectiveness indicates that the vulnerability is not attributable to dataset-specific artifacts.

B.2 Impact of Feature Alignment Position

We investigate how the choice of optimization layer—Visual Encoder output versus Connector output—affects implantation success. As shown in Table 4, the optimal alignment position depends on model scale. For the 0.5B model, connector-level alignment yields marginally higher fidelity. For the 7B model, encoder-level alignment substantially outperforms connector-level alignment. This reversal suggests that as the LLM backbone scales, gradient propagation through deeper multimodal interfaces becomes less stable, making shallower alignment positions more effective for semantic implantation.

B.3 Evaluation with a Newer Evaluator

In the main paper, semantic fidelity is evaluated with GPT-3.5 (OpenAI, 2025), following prior work (Maaz et al., 2024) to ensure a fair comparison. We additionally evaluate with the newer Gemini-3.1-Flash (Google DeepMind, 2026), which more readily recognizes semantically equivalent, differently worded answers as valid matches. As shown in Table 5, this yields systematically higher absolute scores than GPT-3.5. Critically, the core analytical trends—cross-model vulnera-

Table 5: **Quantitative evaluation of semantic implantation (Gemini-3.1-Flash).** All results are reported as Accuracy / Gemini-3.1-Flash-assisted semantic fidelity score. The evaluation measures the extent to which a model's perception of an adversarially perturbed video matches its perception of a genuine object-present counterpart.

Architecture Model		Intrinsic Perception		Control Perturbations			Semantic Implantation	
		Clean (x_{cle})	Target (x_{tar})	None	Global	Masked	**AOH (Ours)**	*Gain vs. None*
SmolVLM2	0.5B	0.291 / 1.31	0.703 / 3.71	0.396 / 2.31	0.359 / 2.14	0.400 / 2.31	**0.710 / 3.74**	+61.9%
LLaVA-OneVision	0.5B	0.667 / 2.16	0.728 / 3.78	0.265 / 1.73	0.250 / 1.70	0.321 / 2.01	**0.746 / 3.88**	+124.3%
	7B	0.642 / 2.14	0.737 / 3.88	0.285 / 1.82	0.276 / 1.79	0.346 / 2.15	**0.548 / 3.03**	+67.1%
VideoLLaMA3	2B	0.637 / 2.04	0.703 / 3.62	0.214 / 1.39	0.225 / 1.36	0.214 / 1.36	**0.596 / 3.13**	+124.7%
	7B	0.687 / 2.22	0.787 / 4.02	0.283 / 1.70	0.285 / 1.69	0.292 / 1.75	**0.714 / 3.72**	+119.5%
InternVL 2.5	1B	0.525 / 1.94	0.728 / 3.79	0.279 / 1.81	0.303 / 1.87	0.310 / 1.90	**0.519 / 2.95**	+63.1%
	2B	0.637 / 2.08	0.732 / 3.79	0.286 / 1.79	0.285 / 1.80	0.295 / 1.82	**0.611 / 3.37**	+88.3%
	4B	0.521 / 1.89	0.762 / 3.97	0.321 / 1.98	0.321 / 1.98	0.332 / 2.04	**0.488 / 2.79**	+41.0%
	8B	0.521 / 1.92	0.766 / 3.97	0.324 / 1.98	0.317 / 2.00	0.342 / 2.07	**0.566 / 3.16**	+59.9%
Video-ChatGPT	7B	0.188 / 0.97	0.699 / 3.63	0.449 / 2.54	0.432 / 2.48	0.449 / 2.58	**0.508 / 2.78**	+9.7%

bility, cross-scale transferability, and the superiority of AOH over control perturbations—remain entirely consistent across both evaluators.

B.4 Multi-Judge Consistency Analysis

To validate the reliability of our LM-assisted fidelity metric, we compare semantic fidelity scores assigned by three independent judges—GPT-3.5, Gemini-3.1-Flash, and human raters—across all evaluated samples (10 Vid-LM architectures, pooled over the three perturbation settings).

Overall, the three judges exhibit strong agreement (Gemini-3.1-Flash vs. GPT-3.5: $\rho = 0.863$; Gemini-3.1-Flash vs. human: $\rho = 0.819$; GPT-3.5 vs. human: $\rho = 0.765$). Notably, agreement is highest in the AOH setting (GPT-3.5 vs. human: $\rho = 0.853$), i.e., precisely where our headline conclusions are drawn. The high inter-judge consistency indicates that the reported semantic fidelity scores are robust to the choice of evaluator, and that the qualitative trends in the main paper—cross-model vulnerability and the superiority of AOH over control perturbations—hold regardless of which judge is used.

B.5 Prompt Injection Baseline

We further investigate whether a *language-level* intervention can reproduce the hallucination that AOH induces at the feature level. Following the POPE probing scheme (Li et al., 2023b), we explicitly name the target object in the question and prompt the model about its presence. For each sample, the *hinted* prompt takes the form *"Is there* $\{object\}$ *in the video?"*, where the target object is extracted from the ground-truth target answer; the prompting template and target-entity extraction rules were developed with assistance from DeepSeek-V4-Flash. We run this baseline on LLaVA-OneVision-0.5B and VideoLLaMA3-7B over the full AOH-Bench (8 frames sampled), with no visual perturbation, and evaluate semantic fidelity with Gemini-3.1-Flash against the target answer.

Table 6 contrasts the text-only *hinted* condition with the *None* (no intervention) and *AOH* (feature-level implantation) conditions. The two models exhibit opposite behaviors. LLaVA-OneVision-0.5B is *not* induced by the hinted prompt (fidelity 0.42 vs. AOH's 3.88), showing that for this model language-level suggestion cannot substitute for feature-level implantation. VideoLLaMA3-7B, by contrast, is strongly induced by the hinted prompt alone (fidelity 4.00), even surpassing its AOH score (3.72). This model-dependent susceptibility of text-level hinting stands in contrast to the consistent effectiveness of AOH across all evaluated architectures, suggesting that the feature-alignment implantation mechanism is qualitatively distinct from purely textual suggestion and that models differ substantially in their reliance on language priors.

Crucially, AOH successfully induces hallucination in *both* models—including LLaVA-OneVision-0.5B, which is resistant to text-level suggestion. This disentangles two qualitatively different failure modes. The first is *language-level suggestibility*: a model's tendency to comply with prompts that assert or probe an object's existence, which is highly model-dependent (LLaVA-OneVision-0.5B

Table 6: **Prompt injection (text-level hinting) vs. feature-level AOH implantation.** Results are reported as Accuracy / Gemini-3.1-Flash-assisted semantic fidelity score over the full AOH-Bench.

Model	None	AOH (Ours)	Hinted (Prompt Only)
LLaVA-OneVision-0.5B	0.265 / 1.73	**0.746 / 3.88**	0.081 / 0.42
VideoLLaMA3-7B	0.283 / 1.70	0.714 / 3.72	**0.818 / 4.00**

Table 7: **Evaluation of Video-Zero (Zhang et al., 2026) under the AOH protocol.** Results are reported as Accuracy / Gemini-3.1-Flash-assisted semantic fidelity score over the full AOH-Bench.

Model	Intrinsic Perception		Control Perturbations			Semantic Implantation	
	Clean (x_{cle})	Target (x_{tar})	None	Global	Masked	**AOH (Ours)**	*Gain vs. None*
Video-Zero-4B	0.216 / 1.30	0.789 / 4.05	0.213 / 1.29	0.211 / 1.29	0.205 / 1.27	**0.760 / 3.88**	+201.5%
Video-Zero-8B	0.231 / 1.48	0.804 / 4.14	0.234 / 1.50	0.234 / 1.49	0.245 / 1.53	**0.793 / 4.07**	+171.1%

resists, VideoLLaMA3-7B complies). The second is the *feature-alignment vulnerability* that AOH exploits, which operates directly in the visual–semantic feature space and is consistent across both models regardless of their text-suggestibility. The fact that AOH succeeds even on the text-resistant LLaVA-OneVision-0.5B indicates that the induced hallucination is not mediated by language priors and is consistent with manipulation at the visual-feature level.

B.6 Evaluation on a More Recent Model

To examine whether the vulnerability persists in a model released after the initial AOH-Bench construction, we additionally evaluate the Video-Zero family (Zhang et al., 2026)—Video-Zero-4B and Video-Zero-8B, 4B- and 8B-parameter video-language models released in 2026 with fixed-frame sampling, built on the widely used Qwen3-VL backbone (Qwen Team, 2025)—following the identical protocol as the main paper, evaluating all six conditions (Clean / Target / None / Global / Masked / AOH) over the full AOH-Bench with the Gemini-3.1-Flash-assisted fidelity metric.

Table 7 reports the results. Despite being more recent architectures, both Video-Zero models exhibit the same cross-model vulnerability: for Video-Zero-4B, the AOH condition raises semantic fidelity from 1.29 (None) to 3.88 (AOH), a relative improvement of $+201.5\%$ with accuracy rising from 21.3% to 76.0%; for Video-Zero-8B, fidelity rises from 1.50 to 4.07 ($+171.1\%$), with accuracy rising from 23.4% to 79.3%. The control perturbations (Global, Masked) remain ineffective for both models, mirroring the trend observed across all previously evaluated architectures. This provides further evidence that the vulnerability is not confined to the originally evaluated architectures and persists across scales within a recent model family.

Per-dataset, AOH improves fidelity over None on every source for Video-Zero-4B (ROVI: $0.771/3.92$ vs. $0.229/1.36$; Video-Sham: $0.701/3.64$ vs. $0.104/0.79$; Drive: $0.400/2.20$ vs. $0.400/1.90$; HQVI: $1.000/5.00$ vs. $0.000/0.40$), replicating the domain-invariant effectiveness reported in Table 3; Video-Zero-8B exhibits the same pattern across datasets.

B.7 Target-Aligned Displacement Analysis

Grad-CAM shows *where* the model looks but not *how far* its representation moves. We therefore measure displacement directly in feature space.

Coordinate frame. Writing C, T and A for the mean-pooled features of the clean, target-counterpart and perturbed videos (x_{cle}, x_{tar} and x_{adv}), let $d_{\text{tar}} = T - C$, $d_{\text{adv}} = A - C$, $\hat{u} = d_{\text{tar}}/\|d_{\text{tar}}\|$, and define

$$x = \frac{\langle d_{\text{adv}}, \hat{u} \rangle}{\|d_{\text{tar}}\|}, \qquad y = \frac{\left\| d_{\text{adv}} - \langle d_{\text{adv}}, \hat{u} \rangle \, \hat{u} \right\|}{\|d_{\text{tar}}\|}, \qquad r = \frac{\|A - T\|}{\|T - C\|}. \tag{5}$$

This places the clean video at the origin and the target counterpart at $(1, 0)$: x is progress *along* the target axis, y is displacement wasted *off* it, and r is the net outcome ($r < 1$: closer to the target than

clean; $r > 1$: further away). Note that $x \approx 1$ is ideal — x well above 1 means overshooting, not better alignment.

Setup. We evaluate LLaVA-OneVision-0.5B on 120 samples drawn (seed 42) from the largest AOH-Bench source, which contributes 84% of the benchmark, reading out both the encoder (`vision_tower`, layer -2, 1152-d) and the connector (`multi_modal_projector`, 896-d) that feeds the language model. Alongside AOH we include three references generated by the same code paths. *Random noise* is the ℓ_∞-bounded *Global* condition, evaluated here on the same source (its per-dataset breakdown is in Table 3). *Patch* is an *optimized* localized perturbation (64×64, 100 iterations) sharing AOH's objective, and is distinct from the *Masked* condition of our evaluation protocol, which is random noise confined to the object mask. *Feature interpolation* is the parameter-free blend $0.5\,x_{\text{cle}} + 0.5\,x_{\text{tar}}$; it is **not an attack under our threat model**, because x_{tar} contains the object and the blend therefore renders it at half opacity. Interpolation is reported as a reference for the displacement of a partially present object, not as a hallucination condition. Accuracy below is measured on that source's full split; the displacement geometry is computed on the 120-sample subset.

Alignment, not magnitude, drives implantation. Table 8 and Fig. 5 report the outcome. Among the two *genuine* perturbations, the target-aligned coordinate x orders the conditions as their accuracy does (all pairwise $p < 10^{-4}$). Random noise displaces the representation the *more* of the two ($\|d_{\text{adv}}\|/\|d_{\text{tar}}\| = 0.69$) yet is essentially directionless ($x = 0.02$, $\cos = 0.02$), yielding 17.5%. The patch moves less than half as far (0.29) but is better directed ($x = 0.06$, $\cos = 0.19$), yielding 35.5%; after 100 iterations it rests at $r = 1.00$, exactly as far from the target as the clean video. Magnitude alone therefore buys no hallucination; direction does.

AOH displaces the representation without rendering the object. AOH matches the target *along the target axis* ($x = 1.01$) while remaining only weakly correlated with the genuine clean→target difference ($\cos = 0.44$); interpolation's near-collinearity ($\cos = 0.90$) is expected, since it literally reproduces a fraction of that difference in pixel space. AOH is thus the only *genuine* perturbation here that reaches the target's position on the target axis under an ℓ_∞ budget. The displacement is directional rather than reconstructive: AOH carries substantial off-axis mass ($y = 2.80$), so its absolute distance to the target ($r = 2.82$) stays above the clean video's even as it matches the target along the target axis. What the language model reads as the object is thus a shift along a single semantic direction, not a faithful reconstruction of the target representation.

This off-axis mass grows from the encoder to the connector ($y : 2.80 \to 4.98$, $x : 1.01 \to 1.41$), i.e. the perturbation is amplified as it crosses the projection layer. Neither reference shows comparable growth (r changes by < 0.03 for both patch and interpolation), indicating that the amplification is specific to the optimized perturbation rather than an artifact of the read-out.

C AOH-Bench: Dataset Construction and Statistics

To complement the benchmark description in the main paper (Section 3), we provide additional statistical characterizations and documentation of the annotation infrastructure.

C.1 Additional Statistics

Fig. 6 presents two complementary views of AOH-Bench's composition. The target object scale distribution (left) confirms broad coverage across object sizes, while the sentence length distribution (right) indicates that both questions and ground-truth answers span a wide range of linguistic complexity.

C.2 Annotation Interfaces

We developed two dedicated web-based interfaces to facilitate the hierarchical quality control process.

Counterpart Video Acquisition. The first interface (Fig. 7) enables annotators to rate object removal quality along three dimensions: Spatial Coherence, Temporal Consistency, and Artifact

Table 8: **Target-aligned displacement analysis on LLaVA-OneVision-0.5B** (N=120 for the displacement geometry; accuracy on the full split of the same source, measured as in Table 1). x: displacement along the clean→target axis, with the target at 1; y: orthogonal residual; $r = \|A - T\|/\|T - C\|$, where $r < 1$ indicates the perturbed representation moved closer to the target than the clean video. All pairwise comparisons of x are significant at $p < 10^{-4}$. Feature interpolation is a reference condition that renders the object at half opacity, not an attack under the threat model.

Read-out	Perturbation	$x \uparrow$	$y \downarrow$	$\cos(d_{\text{adv}}, d_{\text{tar}}) \uparrow$	$r \downarrow$	Accuracy ↑
Encoder	Random noise	0.02	0.69	0.02	1.26	0.175
	Patch (64×64)	0.06	0.28	0.19	1.00	0.355
	Feature interp. (ref.)	0.72	0.28	**0.90**	**0.41**	0.701
	AOH (Ours)	**1.01**	2.80	0.44	2.82	0.611
Connector	Random noise	0.02	0.39	0.05	1.09	0.175
	Patch (64×64)	0.08	0.27	0.28	0.98	0.355
	Feature interp. (ref.)	0.70	0.24	**0.91**	**0.40**	0.701
	AOH (Ours)	**1.41**	4.98	0.37	5.06	0.611



Figure 5: **Where each perturbation lands in the target-aligned frame.** The clean video is fixed at the origin and its target counterpart at $(1, 0)$; each small point is one of the 120 evaluated samples and large markers denote per-method medians. Random noise and the localized patch remain near the origin. Feature interpolation — a reference condition rather than an attack — advances along the target axis with little off-axis residual. AOH reaches the target's position on the axis but with a large orthogonal residual.

Severity. Only video pairs surpassing the strict consensus threshold (aggregate score $\geq$ 14 out of 15) are retained.

Consensus-based Question Generation. The second interface (Fig. 8) supports multi-stage VQA validation, ensuring that ground-truth answers for clean and target videos are mutually exclusive and that questions do not implicitly assume object presence.

C.3 VQA Annotation Prompts

The prompts below (Fig. 9 and Fig. 10) guided the LLM committee (GPT-4o, Claude-3.5-Sonnet, DeepSeek-V3) in generating diagnostic questions that probe object presence through contextual cues rather than direct existence queries.



(a) **Target object scale distribution** (b) **Sentence length distribution**

Figure 6: **Additional statistics of AOH-Bench.** (Left) Distribution of the relative area of target objects. (Right) Distribution of linguistic complexity across questions and ground-truth answers.



Figure 7: **Interface for counterpart video acquisition.**

D Limitations and Broader Impact

D.1 Limitations

While our study provides robust evidence for semantic implantation as a diagnostic probe, we note the following constraints.

Cross-Architecture Transfer. The cross-scale transferability results reported in the main paper are established within the LLaVA-OneVision family, where the visual encoder (SigLIP-SO400M) is shared across scales. Cross-architecture transfer (e.g., from LLaVA-OneVision to InternVL 2.5) is inherently challenging because different Vid-LM families employ distinct temporal preprocessing pipelines (frame sampling strategies, resolution handling, normalization parameters). Perturbations optimized under one preprocessing regime do not align with the input representation of another



Figure 8: **Interface for consensus-based question generation.**

architecture. We view systematic characterization of preprocessing-induced transfer barriers as a valuable direction for future work.

Semantic Fidelity Evaluation. The primary evaluation relies on LM-assisted scoring. We mitigate potential judge bias by employing multiple evaluators (GPT-3.5, Gemini-3.1-Flash, and human) and reporting cross-judge consistency (see Section B.4). Nevertheless, a large-scale human study remains the gold standard for semantic fidelity assessment and is an important direction for follow-up validation, beyond the rater subset reported in Section B.4.

Granularity of Attribution. Our mechanistic analysis uses Grad-CAM to characterize visual attention shifts under AOH. While Grad-CAM provides only coarse spatial attribution (Chattopadhay et al., 2018), the absence of abnormal attention localization in our Grad-CAM analysis supports our interpretation of AOH as operating through global semantic manipulation rather than localized perceptual distortion. To compensate for this coarse read-out, Section B.7 complements the attention analysis with a target-aligned displacement analysis that measures the representation shift directly, and shows that hallucinations track how far the perturbation moves the representation along the target direction rather than how much it displaces in aggregate.

D.2 Broader Impact

This research characterizes controlled hallucinations in Video-Language Models with the explicit goal of exposing and understanding systemic vulnerabilities. While the demonstrated manipulation capability could, in principle, be misused in safety-critical applications such as autonomous driving, we believe that transparent characterization of these failure modes is a necessary precondition for de-

System Prompt

You're a video understanding evaluation specialist designing Visual Question Answering (VQA) questions to assess adversarial attacks on video models. Generate most suitable question per request that:
1. Target detection through CONTEXTUAL CUES rather than direct object existence queries
2. Use action/position/quantity/relationship-based phrasing in present tense
3. Ensure OA and TA have CONTRADICTORY answers based on object presence
4. Avoid direct mention of removed object in question phrasing
5. Verify object uniqueness in original scene (important for quantity questions)
6. Format as Python dictionary: {"Q":..., "OA":..., "TA":...}

———

CRITICAL CONSTRAINTS:
- For removed objects: Frame questions about the SPACE/ACTIVITY the object should occupy
- For remaining objects: Use RELATIVE POSITIONS/QUANTITIES/INTERACTIONS
- Never use yes/no questions about object existence
- Ensure OA reflects ABSENCE OF ALL TRACES when object removed
- Perform a three-step verification:
a) Verify the presence of the target object in the original scene
b) Verify that the removed scene completely eliminates traces of the object
c) Ensure that the question does not implicitly assume the existence of the object

———

EXAMPLES:
1. {"Q": "What is occupying the mat area?", "OA": "The mat is empty", "TA": "A man rolling on the mat"}
2. {"Q": "How many geese are visible?", "OA": "One goose is visible", "TA": "There are two geese visible"}
3. {"Q": "Who is interacting with the dog?", "OA": "Nothing visible", "TA": "A suited man"}

Figure 9: **System prompt for VQA annotation.**

User Prompt

task: Generative adversarial questions by the following [video description] and [object description].
video description: {video_description}
object description: {object_description}
target: Check if the model can detect [object description].
Please generate the response as a Python dictionary string, i.e., {"Q":..., "OA":..., "TA":...}, and do not output anything else.

Figure 10: **User prompt for VQA annotation.**

veloping effective defenses. To this end, we release AOH-Bench as a diagnostic resource to support community-wide efforts toward more robust visual–semantic grounding in multimodal models.