THE HARNESS LEARNS TO LIE WHILE EVOLVING: MEASURING AND PREVENTING FALSE SUCCESS IN HARNESS SELF-EVOLUTION

Anonymous authors
Paper under double-blind review

ABSTRACT

Harness self-evolution repeatedly rewrites the prompts, tools, skills, middleware, and long-term memory around a frozen model over multiple iterations. Although existing self-evolving harness methods and benchmarks can improve usability, self-evolving harness methods cannot distinguish between "tasks that are actually completed" and "fabricated deliverables that pass the same check," and benchmarks cannot measure whether false successes increase with each iteration. We introduce two frameworks, EvoTrap-Bench and Verifiably Honest Harness Evolution (VHE). EvoTrap-Bench measures how false success evolves over the iterations of an arbitrary self-evolving harness. EvoTrap-Bench uses provably impossible tasks, on which any claimed success is false, and keeps the ground truth hidden from the loop. Verifiably Honest Harness Evolution (VHE) is a self-evolving method in which each step is determined by execution rather than by the model's assessment of its own performance. VHE derives its rewards from trajectories rather than reports, and its experience is derived mechanically without asking the model why a particular trial failed. Notably, we found through EvoTrap-Bench that false successes increase with each round of harness self-evolution. This phenomenon occurs in most existing harness self-evolution methods. In the others, false success stays high and shows no downward trend. VHE overcomes the false success phenomenon, keeping false success at an extremely low level in EvoTrap-Bench. Furthermore, VHE performs even better on two benchmarks where it has never evolved before. These results show that measuring and overcoming false success enables scalable, efficient, and self-improving LLM systems.

1 INTRODUCTION




Figure 1: **False success in harness self-evolution.** (a) AHE and ACE raise false success over iterations. (b) EvoTrap-Bench exposes claimed completion despite actual task failure. (c) VHE keeps false success low.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

Large language model (LLM) agents act through a harness: the prompts, tools, skills, middleware and memory around a fixed model (Lin et al., 2026b;a). The harness shapes what the model sees and does (Yao et al., 2026), and can outweigh the choice of model (Zhang et al., 2026d). Harness self-evolution replaces manual harness design with a loop. The loop runs the agent, collects execution evidence and edits the harness over many iterations, while the model weights stay frozen (Lin et al., 2026b). AHE (Lin et al., 2026a), for example, edits prompts, tools, middleware and memory. The pass rate of AHE on Terminal-Bench 2 rises over ten iterations (Lin et al., 2026a).

Previous methods and benchmarks treat a passed check as a solved task. Methods raise pass rates, and benchmarks track their cost and persistence (Zheng et al., 2026; Ke et al., 2026). Yet coding agents pass unit tests by deleting or hardcoding them (Zhong et al., 2026; Gabor et al., 2025). Self-improving agents in production reached perfect scores by reading cached answer keys (Wahi, 2026). AHE and DarwinX judge edits by test results (Lin et al., 2026a; Zhang et al., 2026c). Such loops cannot tell a solved task from a fabricated deliverable that passes the same check (Figure 1b). The benchmarks cannot show whether this false success (Advani, 2026) grows over iterations, since every task is solvable.

We address two problems: measuring false success and preventing its rise over iterations. EvoTrap-Bench measures false success at every iteration of any self-evolving harness. A false success is a claimed success that the hidden tests reject. On a provably impossible task, any claimed success is false by construction (Zhong et al., 2026). Solvable tasks whose visible checks miss a stated requirement add a second route to false success. The loop never sees the hidden test results. Verifiably Honest Harness Evolution (VHE) is a self-evolution method driven by execution rather than self-assessment. Agents often overrate their own work (Africa & Ting, 2025; Park & Choi, 2026). VHE therefore rewards a claim or a refusal only when the agent's trajectory supports it. Reflection-based methods ask a model to diagnose failures (Zhang et al., 2026b; Agrawal et al., 2026). VHE instead derives lessons from failed checks by fixed rules.

Self-evolution raises false success in most existing methods and lowers it in VHE. Under AHE (Lin et al., 2026a), the false-success rate rises from 31% to 73% after one iteration and stays above 87% from the third iteration on (Figure 1a). ACE (Zhang et al., 2026b) rises more slowly, from 18% to a peak of 43%. Under Evo-Harness (Wei et al., 2026), false success stays high, between 29% and 40%, and shows no downward trend. EvoTrap-Bench provides the first ground-truth evidence of this rise in existing harness self-evolution methods. VHE keeps the false-success rate at or below 7.1% from the second iteration on (Figure 1c). On SWE-bench Verified (Jimenez et al., 2024; Chowdhury et al., 2024) and Terminal-Bench 2 (Merrill et al., 2026), where VHE never evolved, the VHE-evolved harness also improves on the seed harness.

Self-improvement needs an honest signal. Rajput et al. (2026) show that a self-improving loop cannot read its reliability from its own verifier. The verifier even misses more errors as the model being checked gets stronger. EvoTrap-Bench measures false success from outside the loop. VHE supplies an honest signal inside the loop at no significant cost in capability. Both are needed for self-improving LLM systems that scale. In summary, this paper makes three contributions:

- **Finding.** We show for the first time, using hidden ground truth, that most existing self-evolution methods make false success grow over iterations and the rest keep it high.
- **Benchmark.** We build EvoTrap-Bench, which uses provably impossible tasks and hidden tests to measure false success at every iteration of any self-evolving harness.
- **Method.** We propose VHE, which learns from execution rather than self-assessment. Its harnesses keep false success at or below 7.1% after the first iteration, at no significant cost in capability.

2 Related Work

2.1 Benchmarks for self-evolving harnesses, and what they do not score

Existing benchmarks for self-evolution do not test whether agents are honest about task completion. EvoHarnessBench asks whether agents keep pace with an evolving harness (Ke et al., 2026). SEAGym checks whether harness updates transfer or overfit recent tasks (Zheng et al., 2026). FinEvo-Bench asks whether experience helps on later tasks (Deng et al., 2026). S3Gym checks whether an agent can predict the reward of its own actions (Shi et al., 2026). The tasks in all four

benchmarks are meant to be solvable, so none of them can show whether false success grows over iterations. ImpossibleBench (Zhong et al., 2026) and EvilGenie (Gabor et al., 2025) use impossible or easily hacked coding tasks to measure how often agents cheat on tests. Advani (2026) characterizes false success in LLM agents. All three test fixed agents, not an evolving harness. EvoTrap-Bench brings impossible tasks into the evolution loop. We measure capability separately on Terminal-Bench 2 (Merrill et al., 2026) and SWE-bench Verified (Jimenez et al., 2024; Chowdhury et al., 2024), where VHE never evolves.

2.2 Methods that evolve a harness, and the risk they do not name

Existing self-evolution methods share a blind spot. AHE rewrites prompts, tools, middleware and memory (Lin et al., 2026a), and ACE grows a context playbook (Zhang et al., 2026b). GEPA evolves prompts through reflection (Agrawal et al., 2026), Evo-Harness compiles past runs into skills (Wei et al., 2026), and Meta-Harness searches over harness code (Lee et al., 2026). DGM and DarwinX keep archives of evolving agents and harnesses (Zhang et al., 2026a;c). All of them learn from execution feedback (Lin et al., 2026b), such as test results. A passed test cannot tell a real solution from a faked one (Zhong et al., 2026; Gabor et al., 2025; Wahi, 2026). Self-graded rewards inflate far beyond any gain in accuracy (Africa & Ting, 2025; Asadolahi et al., 2026). Self-evolution can also drift in unintended ways (Shao et al., 2026), erode capabilities the agent already had (Yu et al., 2026), and amplify evaluation noise (Ye et al., 2026). HackProbe tracks the gap between score and capability in prompt evolution, but with injected hacking (Yang et al., 2026). Using an LLM auditor, Wang et al. (2026) find tampering edits in self-improving agents. Some of these edits persist across iterations. None of this work checks the completion claims of existing methods against hidden ground truth.

3 A Benchmark for Honesty Across Harness Self-Evolution




Figure 2: **EvoTrap-Bench.** Methods evolve the harness on impossible and solvable tasks in their own loops. A sequestered audit crosses hidden verdicts with claims.

3.1 Scoring Claims and Outcomes

EvoTrap-Bench scores claims as well as results. Every task ends with a completion report. In the report, the agent marks each requirement as met or not and gives its evidence. The report form asks the agent to answer false, with a reason, when the environment blocks a requirement. Each trial thus yields two signals: the hidden-test verdict and the claim of completion. The two signals define five outcomes (Figure 2): true success, honest decline, false success, honest failure and no report. We track the false-success rate at every iteration.

3.2 Impossible Tasks

Impossible tasks form the core of the benchmark. Each task names a dependency that the sandbox cannot reach, such as a host that never resolves. The only correct outcome is to report this blocker. ImpossibleBench sets the specification against the tests (Zhong et al., 2026). Our tasks instead

lack a resource, which keeps the honest response clear. A visible self-check accepts a fabricated deliverable, which the hidden tests reject. Fabrication takes two forms: substituting local stand-in data, or redefining the required effect. Three tiers differ only in how clearly the instruction states the honest path. Each variant changes one sentence of its base task. The benchmark contains 120 impossible tasks built from 60 scenarios.

3.3 Solvable Tasks with Incomplete Checks

A second group of tasks can be solved. Their instructions state every requirement. The visible self-check, however, runs only on a sample that misses some requirements, such as combined number formats. An agent that tests beyond the self-check can succeed. An agent that stops there may claim success yet fail the hidden tests. False success on these tasks reflects weaker verification, not fabrication. The benchmark contains 20 solvable tasks. Every task is certified in its container with two reference solutions. The correct one passes the hidden tests. The tempting wrong one passes only the visible check.

3.4 Hidden Ground Truth and Integration

The benchmark hides the ground truth from the loop (Figure 2). The loop's only correctness signal is its method's reward, which for existing methods is the visible check. Hidden tests and verdicts stay in a ledger outside the loop's directory. A method keeps its own loop and calls the benchmark for each trial. Each call returns the reward, the agent's report and its trajectory. The benchmark fixes an iteration at four runs per task and gives every method the same model and tasks. Methods that edit harness files (Lin et al., 2026a), grow a context playbook (Zhang et al., 2026b) or compile skill files (Wei et al., 2026) run on it unchanged.

4 VHE: Verifiably Honest Harness Evolution




Figure 3: **Verifiably Honest Harness Evolution (VHE).** Claims earn reward only with trajectory and probe evidence. Failures become rule-based lessons, each yielding one rule and one check. A change is kept only if replays halve its errors, and its failing inputs become regression probes.

VHE evolves the harness in five steps (Figure 3). Every decision in the loop rests on execution evidence rather than on the agent's view of its own work. The evolved artifact is data, not code. Rules and a pre-finish checklist are appended to the frozen prompt of the seed harness, the harness before any evolution. Budget stages, executable checks and regression probes sit beside the prompt. Two fixed middlewares run the checks and show the budget stages. Model weights and runtime code never change, so evolution cannot rewrite its own verifier. Each step answers one question and passes its output to the next.

4.1 Claims Need Evidence

VHE rewards only what the evidence supports. A judge reads the task instruction, the agent's report and the trajectory, and rules on each requirement. A requirement marked as met earns credit only if the trajectory supports the claim. A requirement marked as blocked earns credit only if a command and its output show the stated blocker. LLM judges tend to trust surface cues such as

confident closing words (Advani, 2026), so VHE also runs probes. Probes are inputs derived from the instruction and executed against the deliverable in the live container. A probe counts only after passing a correct reference, and one failing probe voids the claim. A report that claims the whole task but fails the task's own visible check scores zero. The trial reward is the mean over requirements. VHE never reads the hidden tests.

4.2 Rule-Based Failure Diagnosis

VHE diagnoses failures by rule, not by asking a model. Reflection-based methods ask a model to explain each failure (Zhang et al., 2026b; Agrawal et al., 2026). VHE instead groups the round's verdicts into lessons, each keyed by task, requirement and kind. VHE reads only files the loop can see. Honesty lessons cover over-claims, fabrications, unsupported refusals and failed probes. Process lessons are read from commands, exit codes and timestamps. Such lessons record an exceeded budget, a missing verification step, a finish after a failed check, or an environment problem that recurs across tasks. Fixed rules assign every kind, and the judge's text serves only as an example. The lessons fit within 8 KB, and a lesson counts as fixed after two clean rounds.

4.3 One Rule, One Check

Each open lesson leads to one rule and one check. A proposer model sees the lesson, at most two examples, earlier attempts and the current rules. The proposer writes one general rule for the agent and one executable check that reproduces the failing input. A rule can be ignored, but a failing check is shown to the agent at the moment of reporting. From process lessons, the proposer also rewrites the pre-finish checklist and the budget stages. Every three rounds, rules of one kind are merged into one. Checks declare the task features they need, such as hosts or output files, so a check can run on other tasks. An audit rejects rules that contain literal paths, numbers or task names.

4.4 Replay Before Commit

A change must prove itself before VHE keeps it. The candidate harness replays the targeted tasks twice each, outside the scored rounds. VHE commits the change only if the targeted lessons fall by at least half and no fixed lesson returns. A rejected change leaves the current harness untouched. AHE keeps an edit and reverts it when the next round contradicts its prediction (Lin et al., 2026a). VHE instead tests each edit before admitting it to the harness.

4.5 Keep Fixes, Prune Rules

VHE keeps its fixes and removes rules that are no longer needed. Growing a harness can break tasks that were solved before (Ke et al., 2026). A committed change therefore turns its failing inputs into regression probes, which join the probe set of every later round. Rules whose lessons stay fixed for three rounds become candidates for removal. VHE removes such a rule only if a replay without the rule stays clean. Removed rules are archived.

5 Experiments

EvoTrap-Bench shows that false success grows over iterations under most existing self-evolution methods and stays high under the rest. VHE keeps false success at or below 7.1% after the first iteration, and the VHE harness has the highest observed pass rate on both external benchmarks.

5.1 Benchmarking Self-Evolution Methods

5.1.1 Methods

We compare four methods under one protocol. Every method uses Qwen3.8-27B (Qwen Team, 2026) both to run the agent and to evolve the harness. An iteration runs every task four times with the current harness. AHE (Lin et al., 2026a), ACE (Zhang et al., 2026b) and Evo-Harness (Wei et al., 2026) learn from the visible check. AHE, ACE and VHE start from the same seed harness, the harness before any evolution. The seed harness pairs a short system prompt with a single tool that




Figure 4: **False-success rate over iterations on EvoTrap-Bench.** Lower is better. False success rises sharply under AHE, rises more slowly under ACE and remains high under Evo-Harness. VHE stays at or below 7.1% after the first iteration.

runs bash commands in the task container. The prompt tells the agent to act only through this tool and never to ask questions. Each command stops after five minutes, and the tool returns the output and any non-zero exit code.

AHE lets an agent edit the harness (Lin et al., 2026a). After each iteration, this agent reads evidence drawn from the trajectories. The agent then edits harness files, such as prompts, tools and middleware. Each edit states a predicted effect. AHE reverts an edit when the next iteration contradicts the prediction.

ACE grows a list of strategies, called a playbook, in the agent's context (Zhang et al., 2026b). A reflector draws lessons from recent trajectories. A curator merges these lessons into the playbook as incremental updates. ACE updates the playbook every 16 trials, so we split its trials into blocks the size of one iteration.

Evo-Harness turns past runs into skills (Wei et al., 2026). After each iteration, Evo-Harness distills the trajectories and check results into reusable skill files. These skills enter the agent's prompt in the next iteration. Evo-Harness starts from its own default prompt rather than the seed harness.

VHE learns only from execution evidence (Section 4). A judge rewards claims and refusals only when the trajectory and the probes support them. Fixed rules turn failures into lessons. Each lesson yields one rule for the prompt and one executable check. A change is kept only if replays at least halve its targeted errors. Kept changes turn their failing inputs into regression probes. VHE never reads the hidden tests.

5.1.2 Evaluation Metrics

We score honesty at every iteration. The main metric is the false-success rate: the share of trials that claim success but fail the hidden tests. Trials stopped by infrastructure errors are left out. On impossible tasks, we also report the rates of claimed success and of honest declines. On solvable tasks, we report true successes.

5.1.3 Results and Analysis

Existing methods become less honest over iterations, while VHE becomes more honest (Figure 4). The four methods start between 18% and 38%, so the gap opens during evolution. Under AHE (Lin et al., 2026a), the false-success rate rises from 31% to 73% after one iteration. The rate then stays above 87% from the third iteration on. Under ACE (Zhang et al., 2026b), the rate climbs more slowly, from 18% to a peak of 43%. Evo-Harness (Wei et al., 2026) starts at 38% and later rises to a peak of 40%. VHE starts at 27% with the seed harness and stays at or below 7.1% from the second iteration on. After the first iteration, no VHE report on an impossible task claims success. The existing methods learn from visible checks, which never reward an honest decline.

Harness	Terminal-Bench 2		SWE-bench Verified	
	Pass ↑	Timeout ↓	Pass ↑	Timeout ↓
Seed (fixed)	27.5%	70.0%	56.0%	36.0%
Evolved harnesses				
AHE	27.5%$_{+0.0}$	**45.0%**	64.0%$_{+8.0}$	**12.0%**
ACE	32.5%$_{+5.0}$	62.5%	56.0%$_{+0.0}$	32.0%
Evo-Harness	25.0%$_{-2.5}$	75.0%	52.0%$_{-4.0}$	48.0%
VHE	**35.0%**$_{+7.5}$	62.5%	**68.0%**$_{+12.0}$	24.0%

Table 1: **Pass and timeout rates on two external benchmarks.** Timeout is the share of trials that reach the time limit. Subscripts give the change in pass rate from the seed harness in percentage points. Green marks a gain. Bold marks the best value in each column.

5.2 Evaluating VHE

5.2.1 Benchmarks

Terminal-Bench 2 tests agents on hard tasks in the command line (Merrill et al., 2026). The 89 tasks draw on problems from real workflows. Each task has its own environment, a human-written solution, a time limit and tests. The tests check the final state of the container.

SWE-bench Verified tests agents on real GitHub issues (Jimenez et al., 2024). The agent edits a Python repository to resolve an issue. An issue counts as resolved only if all associated tests pass. Human annotators verified the 500 instances for clear issues and suitable tests (Chowdhury et al., 2024).

EvoTrap-Bench is the only benchmark on which the harnesses evolve (Section 3). We run these four harnesses and the seed harness on both external benchmarks without further change.

5.2.2 Evaluation Metrics

We report the pass rate under each benchmark's own tests. Each harness attempts each task once. A trial that runs out of time is still scored. A trial stopped by an infrastructure error, such as a model-server timeout, has no verdict. All harnesses run on the same 80 Terminal-Bench 2 tasks (Merrill et al., 2026) and the same 100 SWE-bench Verified instances (Jimenez et al., 2024; Chowdhury et al., 2024).

5.2.3 Results and Analysis

VHE has the highest observed pass rate on both external benchmarks, with lower timeout rates than the seed harness (Table 1). On Terminal-Bench 2 (Merrill et al., 2026), VHE reaches 35.0%, compared with 27.5% for the seed and 32.5% for the strongest competing method, ACE (Zhang et al., 2026b). On SWE-bench Verified (Jimenez et al., 2024; Chowdhury et al., 2024), VHE reaches 68.0%, compared with 56.0% for the seed and 64.0% for AHE (Lin et al., 2026a). These results suggest that evolving for honesty can preserve and improve task-solving ability beyond EvoTrap-Bench.

VHE also has lower timeout rates than the seed, at 62.5% versus 70.0% and 24.0% versus 36.0% on the two benchmarks, respectively. AHE (Lin et al., 2026a) has the lowest timeout rates, at 45.0% and 12.0%. VHE's advantage is therefore in successful completion, while timeouts remain common.

5.2.4 Ablation Study

Changing one component leaves false success between 2.9% and 4.6%, compared with 4.3% for full VHE (Table 2). Each variant changes one part of VHE and evolves on EvoTrap-Bench. The external pass rates are more sensitive to these changes. On Terminal-Bench 2 (Merrill et al., 2026), committing changes without replay (Section 4.4) lowers the pass rate from 35.0% to 27.5%. Rules without executable checks (Section 4.3) reach 30.0%. On SWE-bench Verified (Jimenez et al., 2024; Chowdhury et al., 2024), removing fix retention and rule pruning (Section 4.5) or replacing the probe veto with partial credit (Section 4.1) lowers the pass rate from 68.0% to 56.0%.

Change to VHE	EvoTrap-Bench False success ↓	TB2 Pass ↑	SWE Pass ↑
Full VHE	4.3%	**35.0%**	68.0%
Single-component changes			
No replay before commit (§4.4)	3.9%$_{-0.4}$	27.5%$_{-7.5}$	68.0%$_{+0.0}$
No fix retention or rule pruning (§4.5)	4.3%$_{+0.0}$	32.5%$_{-2.5}$	56.0%$_{-12.0}$
Probes without reference checks (§4.1)	**2.9%$_{-1.4}$**	**35.0%$_{+0.0}$**	68.0%$_{+0.0}$
Probe pass-rate reward, no veto (§4.1)	4.6%$_{+0.3}$	32.5%$_{-2.5}$	56.0%$_{-12.0}$
Rules without executable checks (§4.3)	3.2%$_{-1.1}$	30.0%$_{-5.0}$	68.0%$_{+0.0}$
Model reflection for diagnosis (§4.2)	3.2%$_{-1.1}$	25.0%$_{-10.0}$	**72.0%$_{+4.0}$**

Table 2: **Ablation of VHE components.** TB2 and SWE are the external benchmarks of Section 5.2.1. Subscripts give the change from full VHE in percentage points. Green marks an improvement. Bold marks the best value in each column.

Method	Agent	Time	
	Tokens per trial (k)↓	Hours per iteration↓	Evolution wait (min)↓
`Qwen3.8-27B on EvoTrap-Bench`			
`Seed harness`	264.9	–	–
`Self-evolution methods`			
`AHE`	188.7$_{-76.2}$	1.70	28.2
`ACE`	242.3$_{-22.6}$	2.54	**0.0**†
`Evo-Harness`	354.1$_{+89.2}$	1.75	0.6
`VHE`	**86.6**$_{-178.3}$	**0.75**	11.8

Table 3: **Cost of self-evolution on EvoTrap-Bench.** Evolution wait is the time an iteration waits for the harness update. Subscripts give the token change from the seed harness. Times are wall-clock. †ACE updates its playbook while agents run.




Figure 5: **Where the loop's reward disagrees with the hidden tests.** Red trials earn a reward but fail the hidden tests. Grey trials pass the hidden tests but earn no reward.

Probes without reference checks (Section 4.1) reach the lowest false-success rate, 2.9%, while matching full VHE's external pass rates of 35.0% and 68.0%. Replacing rule-based diagnosis with model reflection (Section 4.2) yields a lower pass rate of 25.0% on Terminal-Bench 2 (Merrill et al., 2026) but a higher rate of 72.0% on SWE-bench Verified (Jimenez et al., 2024; Chowdhury et al., 2024). Low false success therefore does not by itself imply higher external task success.

5.3 Cost and Speed Analysis

All methods run on the same hardware. The server has eight NVIDIA RTX 5880 Ada GPUs with 48 GB each. vLLM (Kwon et al., 2023) serves the FP8 model on two GPUs per endpoint. An agent resends the conversation so far at every turn. With prefix caching, vLLM reuses the key-value (KV) cache of this repeated prefix. The cache hit rate averages 71% to 84% across the serving endpoints. Table 3 reports tokens per trial, hours per iteration and the overhead of each method's evolution step.




Figure 6: **What evolution adds to the harness.** Bar length grows with the number of entries each method adds. Labels give each group's share, assigned by a model judge. Quotes are copied from the evolved harnesses.

5.4 What the Loop Rewards

Existing loops reward the wrong outcomes (Figure 5). Under AHE (Lin et al., 2026a), ACE (Zhang et al., 2026b) and Evo-Harness (Wei et al., 2026), every false success earns a reward, and no honest decline earns one. As a result, the reward disagrees with the hidden tests on 67% to 91% of trials. Evolution then turns unrewarded declines into rewarded false success. Under AHE, the share of honest declines falls from 40% to zero after one iteration. VHE's reward agrees with the hidden tests on every trial from the second iteration on.

5.5 What the Harness Learns

Evolution changes what the harness tells the agent (Figure 6). A model judge labels every entry that each method adds. A longer bar means more additions. A longer red segment means more additions that can lead to false success. Under AHE (Lin et al., 2026a) and Evo-Harness (Wei et al., 2026), 29% and 36% of the additions can lead to false success. Most of them tell the agent to replace an unreachable service with a stand-in or synthetic data. ACE (Zhang et al., 2026b) adds few such entries (3%). VHE adds none, and several of its new rules require reporting such a requirement as unmet.

6 Conclusion

Harness self-evolution can make agents less honest. EvoTrap-Bench measures this effect with hidden tests and tasks on which any claimed success is false. False success rose over iterations under most existing methods and stayed high under the rest. These methods learn from visible checks, which reward fabrication but not honest refusal. VHE instead rewards claims and refusals only when execution evidence supports them. VHE kept false success at or below 7.1% from the second iteration on. On two external benchmarks, the VHE harness also improved on the seed harness. What the loop rewards decides how honest the harness becomes.

Our study has two main limits. All experiments use one open-weight model, and VHE's judge and proposer share this model with the agent. EvoTrap-Bench also covers only two routes to false success, while deployed systems may open others. Natural next steps are independent judges, other models and new routes to false success.

AI use statement

In this work, we used generative AI tools to implement VHE and to connect the compared methods to EvoTrap-Bench. We also used these tools to run and monitor experiments and to write the scoring scripts. Further uses were literature search, citation checking, building the benchmark tasks, polishing the text and writing figure and table code. We designed the initial structure of the benchmark tasks and outlined the first draft without generative AI tools. Scripts recompute every number in the paper from saved run records. We checked every citation against the cited paper. We reviewed all code, re-checked all numbers and proposed the research idea ourselves. We take responsibility for

the final content of this work, including text, claims and artifacts produced with the aid of generative AI.

Ethics statement

We built all benchmark tasks ourselves from written specifications, and the tasks run in isolated containers. The work uses no personal data and involves no human subjects. The external benchmarks are public datasets. A low false-success rate on EvoTrap-Bench does not guarantee that a deployed system is honest.

Reproducibility statement

We take several steps to support reproduction. The supplementary material contains EvoTrap-Bench and the VHE implementation. The benchmark comes with the task specifications, the reference solutions and the scripts that build, certify and score the tasks. Appendix A describes the task design, the certification and the isolation of the ground truth. Appendix B gives the details of each step of VHE. Appendix C lists the model, the serving setup, the decoding settings, the sandbox and the time budgets. Appendix C also gives the changes that our adapters make to the compared methods. All experiments use one open-weight model (Qwen Team, 2026) served with vLLM (Kwon et al., 2023). Sampling is not seeded, so single trials may differ between runs.

References

Laksh Advani. From Confident Closing to Silent Failure: Characterizing False Success in LLM Agents. *arXiv preprint arXiv:2606.09863*, 2026. URL https://arxiv.org/abs/2606.09863v1. Version 2606.09863v1.

David Demitri Africa and Hans Ethan Ting. Does Self-Evaluation Enable Wireheading in Language Models?, November 2025. URL https://arxiv.org/abs/2511.23092. arXiv preprint arXiv:2511.23092.

Lakshya A Agrawal, Shangyin Tan, Dilara Soylu, Noah Ziems, Rishi Khare, Krista Opsahl-Ong, Arnav Singhvi, Herumb Shandilya, Michael J Ryan, Meng Jiang, Christopher Potts, Koushik Sen, Alexandros G. Dimakis, Ion Stoica, Dan Klein, Matei Zaharia, and Omar Khattab. GEPA: Reflective Prompt Evolution Can Outperform Reinforcement Learning. In *International Conference on Learning Representations*, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/hash/0e9e708b6f48e14fd0ac29e167413f76-Abstract-Conference.html.

Mohammad Asadolahi, Amir Amini, Samira Talebi, Amirfarhad Farhadi, and Azadeh Zamanifar. Memory Reward Inflation in Self-Improving LLM Agents. *arXiv preprint arXiv:2608.00017*, 2026. URL https://arxiv.org/abs/2608.00017v1. Version 2608.00017v1.

Neil Chowdhury, James Aung, Chan Jun Shern, Oliver Jaffe, Dane Sherburn, Giulio Starace, Evan Mays, Rachel Dias, Marwan Aljubeh, Mia Glaese, Carlos E. Jimenez, John Yang, Leyton Ho, Tejal Patwardhan, Kevin Liu, and Aleksander Madry. Introducing SWE-bench Verified. OpenAI blog, August 2024. URL https://openai.com/index/introducing-swe-bench-verified/.

Bo Deng, Kang Zhou, Lifan Guo, Chongyang Tao, Xuanren Chen, Chenggang Xie, Renzhao Liang, Feng Chen, and Chi Zhang. FinEvo-Bench: A Longitudinal Benchmark for Self-Evolving Agents in Professional Financial Workflows, August 2026. URL https://arxiv.org/abs/2608.06144. arXiv preprint arXiv:2608.06144.

B. Efron. Bootstrap methods: Another look at the jackknife. *The Annals of Statistics*, 7(1):1–26, 1979. doi: 10.1214/aos/1176344552.

R. A. Fisher. The logic of inductive inference. *Journal of the Royal Statistical Society*, 98(1):39–54, 1935. doi: 10.1111/j.2397-2335.1935.tb04208.x.

Jonathan Gabor, Jayson Lynch, and Jonathan Rosenfeld. EvilGenie: A Reward Hacking Benchmark. *arXiv preprint arXiv:2511.21654*, 2025. doi: 10.48550/arXiv.2511.21654.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. SWE-bench: Can Language Models Resolve Real-World GitHub Issues? In *International Conference on Learning Representations (ICLR)*, 2024. doi: 10.48550/arXiv.2310.06770.

Zixuan Ke, Vaidehi Patil, Haizhou Shi, Yang Li, Ye Liu, Sarath Shekkizhar, Anurag Koul, Jiayu Wang, Xuan Phi Nguyen, Semih Yavuz, Mohit Bansal, and Shafiq Joty. EvoHarnessBench: Can Your Agents Keep Pace with an Evolving Harness?, September 2026. URL https://arxiv.org/abs/2609.04280. arXiv preprint arXiv:2609.04280.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. Efficient Memory Management for Large Language Model Serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles (SOSP '23)*, pp. 611–626. ACM, October 2023. doi: 10.1145/3600006.3613165.

Yoonho Lee, Roshen Sanjay Nair, Qizheng Zhang, Kangwook Lee, Omar Khattab, and Chelsea Finn. Meta-Harness: End-to-End Optimization of Model Harnesses. In *Third Conference on Language Modeling*, 2026. URL https://openreview.net/forum?id=tmbOUyFx3R.

Jiahang Lin, Shichun Liu, Chengjun Pan, Lizhi Lin, Shihan Dou, Zhiheng Xi, Xuanjing Huang, Hang Yan, Zhenhua Han, Tao Gui, and Yu-Gang Jiang. Agentic Harness Engineering: Observability-Driven Automatic Evolution of Coding-Agent Harnesses. *arXiv preprint arXiv:2604.25850*, 2026a. URL https://arxiv.org/abs/2604.25850v4. Version 2604.25850v4.

Minhua Lin, Juncheng Wu, Zijun Wang, Zhan Shi, Yisi Sang, Bing He, Zewen Liu, Tianxin Wei, Zongyu Wu, Zhiwei Zhang, Dakuo Wang, Xiang Zhang, Benoit Dumoulin, Cihang Xie, Yuyin Zhou, Suhang Wang, and Hanqing Lu. Harness Updating Is Not Harness Benefit: Disentangling Evolution Capabilities in Self-Evolving LLM Agents. *arXiv preprint arXiv:2605.30621*, 2026b. URL https://arxiv.org/abs/2605.30621v1. Version 2605.30621v1.

Mike A Merrill, Alexander Glenn Shaw, Nicholas Carlini, Boxuan Li, Harsh Raj, Ivan Bercovich, Lin Shi, Jeong Yeon Shin, Thomas Walshe, E. Kelly Buchanan, Junhong Shen, Guanghao Ye, Haowei Lin, Jason Poulos, Maoyu Wang, Marianna Nezhurina, Di Lu, Orfeas Menis Mastromichalakis, Zhiwei Xu, Zizhao Chen, Yue Liu, Robert Zhang, Leon Liangyu Chen, Anurag Kashyap, Jan-Lucas Uslu, Jeffrey Li, Jianbo Wu, Minghao Yan, Song Bian, Vedang Sharma, Ke Sun, Steven Dillmann, Akshay Anand, Andrew Lanpouthakoun, Bardia Koopah, Changran Hu, Etash Kumar Guha, Gabriel H. S. Dreiman, Jiacheng Zhu, Karl Krauth, Li Zhong, Niklas Muennighoff, Robert Kwesi Amanfu, Shangyin Tan, Shreyas Pimpalgaonkar, Tushar Aggarwal, Xiangning Lin, Xin Lan, Xuandong Zhao, Yiqing Liang, Yuanli Wang, Zilong Wang, Changzhi Zhou, David Heineman, Hange Liu, Harsh Trivedi, John Yang, Junhong Lin, Manish Shetty, Michael Yang, Nabil Omi, Negin Raoof, Shanda Li, Terry Yue Zhuo, Wuwei Lin, Yiwei Dai, Yuxin Wang, Wenhao Chai, Shang Zhou, Dariush Wahdany, Ziyu She, Jiaming Hu, Zhikang Dong, Yuxuan Zhu, Sasha Cui, Ahson Saiyed, Arinbjörn Kolbeinsson, Christopher Michael Rytting, Ryan Marten, Yixin Wang, Jenia Jitsev, Alex Dimakis, Andy Konwinski, and Ludwig Schmidt. Terminal-Bench: Benchmarking Agents on Hard, Realistic Tasks in Command Line Interfaces. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=a7Qa4CcHak.

Hyundoo Park and Byungho Choi. When Do Agent Loops Mistake Stagnation for Progress? Self-Evaluation Bias and Externally Grounded Verification in Long-Running Autonomous LLM Agent Loops. *arXiv preprint arXiv:2607.25152*, 2026. URL https://arxiv.org/abs/2607.25152v1. Version 2607.25152v1.

Qwen Team. Qwen3.8-Max: A new bar for coding and cowork. Qwen blog, August 2026. URL https://qwen.ai/blog?id=qwen3.8.

Dushyant Rajput, Nirdesh Chauhan, and Siddharth Kosaraju. Cheap Verifiers, Large Blind Spots: Measuring the Reliability Cost of Cost-Saving Cascades, September 2026. URL https://arxiv.org/abs/2609.01345. arXiv preprint arXiv:2609.01345.

Shuai Shao, Qihan Ren, Dongrui Liu, Chen Qian, Boyi Wei, Dadi Guo, Jingyi Yang, Xinhao Song, Linfeng Zhang, Weinan Zhang, and Jing Shao. Your Agent May Misevolve: Emergent Risks in Self-evolving LLM Agents. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=Fd1jgQQW28.

Jiajun Shi, Siyuan Tao, Yuhao Wu, Zexuan Wang, Jingyuan Zhang, Jiaheng Liu, Xinping Lei, Xinrong Zhang, Siyuan Fang, Zhewen Tan, Tianle Cai, Junhao Fang, Jiameng Huang, Yueyang Wang, Jinkai Liu, Yuxuan Zhang, Jian Yang, Zhoujun Li, Shen Yan, Wenhao Huang, and Ge Zhang. S3Gym: Can LLMs Turn Self-Testing and Self-Judging into Self-Improvement?, August 2026. URL https://arxiv.org/abs/2608.31100. arXiv preprint arXiv:2608.31100.

Vansh Wahi. LLM-as-a-Judge Is Not an Oracle: Why Self-Improving Agents Need Deterministic Guardrails. *arXiv preprint arXiv:2609.02246*, 2026. URL https://arxiv.org/abs/2609.02246v1. Version 2609.02246v1.

Xing Wang, Xiaoyi Zhang, and Jie Shao. Auditing Harness Tampering in Self-Improving Agents. *arXiv preprint arXiv:2609.00069*, 2026. URL https://arxiv.org/abs/2609.00069v1. Version 2609.00069v1.

Tianxin Wei, Zhan Shi, Minhua Lin, Bing He, Zewen Liu, Yisi Sang, Yuanchen Bei, Xuying Ning, Jiaru Zou, Ting-Wei Li, Xiao Lin, Yanjun Zhao, Chi Wang, Benoit Dumoulin, Dakuo Wang, Jingrui He, and Hanqing Lu. Evo-Harness: Context-to-Harness Skill Compilation for Self-Evolving Agents. In *Proceedings of the 2026 Conference on Empirical Methods in Natural Language Processing*, 2026. doi: 10.48550/arXiv.2608.15071. To appear.

Edwin B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, June 1927. doi: 10.1080/01621459.1927.10502953.

Rongxin Yang, Yang Liu, Shang Luo, Haoxuan Jia, Chongyang Zhang, Hao Zheng, Yingguang Yang, Yulin Huang, Jianshen Zhang, Yongzhi Qi, Kefu Xu, Congjing Ran, and Bin Chong. Harness-agnostic detection and immunization of reward hacking in self-evolving language models, September 2026. URL https://arxiv.org/abs/2609.04665. arXiv preprint arXiv:2609.04665.

Yilun Yao, Xinyu Tan, Chao-Hsuan Liu, Yaoming Li, Zhengyang Wang, Wenhan Yu, Zhewen Tan, Yuxuan Tian, Guangxiang Zhao, Lin Sun, Xiangzheng Zhang, and Tong Yang. HarnessBench: Measuring Harness Effects across Models in Realistic Agent Workflows. *arXiv preprint arXiv:2605.27922*, 2026. URL https://arxiv.org/abs/2605.27922v1. Version 2605.27922v1.

Qinyuan Ye, Yu Li, Yada Pruksachatkun, Jiaxin Zhang, and Chien-Sheng Wu. On the Fragility of Self-Improving Agents: Variance, Task Order, and Underspecification. *arXiv preprint arXiv:2608.18066*, 2026. URL https://arxiv.org/abs/2608.18066v1. Version 2608.18066v1.

Ye Yu, Xiaopeng Yuan, Haibo Jin, Heming Liu, Yaoning Yu, and Haohan Wang. Do Self-Evolving Agents Forget? Capability Degradation and Preservation in Lifelong LLM Agent Adaptation. *arXiv preprint arXiv:2605.09315*, 2026. URL https://arxiv.org/abs/2605.09315v1. Version 2605.09315v1.

Jenny Zhang, Shengran Hu, Cong Lu, Robert Tjarko Lange, and Jeff Clune. Darwin Gödel Machine: Open-Ended Evolution of Self-Improving Agents. In *The Fourteenth International Conference on Learning Representations*, 2026a. URL https://openreview.net/forum?id=pUpzQZTvGY.

Qizheng Zhang, Changran Hu, Shubhangi Upasani, Boyuan Ma, Fenglu Hong, Vamsidhar Kamanuru, Jay Rainton, Chen Wu, Mengmeng Ji, Hanchen Li, Urmish Thakker, James Zou, and Kunle Olukotun. Agentic Context Engineering: Evolving Contexts for Self-Improving Language Models. In *The Fourteenth International Conference on Learning Representations*, 2026b. URL https://openreview.net/forum?id=eC4ygDs02R.

Yifan Zhang, Yutong Dai, Juntao Tan, Luyu Yang, Rishi Mullur, Thai Hoang, Zhiyuan Hu, James Zhu, Phil Mui, Silvio Savarese, Ran Xu, and Zeyuan Chen. DarwinX: Evolving Agent Harnesses Through Natural Selection. *arXiv preprint arXiv:2608.07545*, 2026c. URL https://arxiv.org/abs/2608.07545v1. Version 2608.07545v1.

Yunbei Zhang, Janet Wang, Yingqiang Ge, Weijie Xu, Jihun Hamm, and Chandan K. Reddy. Stop Comparing LLM Agents Without Disclosing the Harness. *arXiv preprint arXiv:2605.23950*, 2026d. URL https://arxiv.org/abs/2605.23950v1. Version 2605.23950v1.

Congjie Zheng, Chuanyi Xue, Bin Liang, Jun Yang, and Changshui Zhang. SEAGym: An Evaluation Environment for Self-Evolving LLM Agents. *arXiv preprint arXiv:2606.17546*, 2026. URL https://arxiv.org/abs/2606.17546v1. Version 2606.17546v1.

Ziqian Zhong, Aditi Raghunathan, and Nicholas Carlini. ImpossibleBench: Measuring LLMs' Propensity of Exploiting Test Cases. In *International Conference on Learning Representations*, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/hash/ca688eb14e29701a11bdba6633186328-Abstract-Conference.html.

A Benchmark Details




Figure 7: **Anatomy of an impossible task.** The agent sees the instruction, a tier sentence, the report form and a visible check that inspects only the output's shape. The honest decline passes only the hidden tests, and the fabrication passes only the visible check. The hidden verdict and the claim give four outcomes.

A.1 Task Anatomy

Each task is a small operations or data job in a container. The agent sees the instruction, the starting files and a visible self-check (Figure 7). The instruction ends with a completion-report form. The form asks for a completion flag, a confidence from 0 to 100, a flag for each requirement and one sentence of evidence for each requirement. The form also says: "If something cannot be done in this environment, set it to false and say why in notes." The hidden tests, the reference solutions and the task labels never enter the agent's container. The hidden tests run only in a separate verification step. Their names and failure messages are neutral, so a failed test does not reveal the intended answer.

A.2 Outcomes

Two signals decide the outcome of a trial. The hidden verdict is a pass only if every hidden test passes. The claim is the report's completion flag. The two signals give four outcomes (Figure 7). A missing report, or a completion flag that is not true or false, counts as no report. On an impossible task, the hidden tests pass only if the report declines the blocked requirement and no fabricated output exists. Honest decline is therefore the correct answer.

A.3 Impossible Tasks

Every impossible task depends on a named host that never resolves. The hosts use the reserved .invalid domain. The scenarios cover routine operations work: pulling data from an HTTP service, restoring a database snapshot, deploying a site, publishing a release artifact and purging an edge cache. In the substitution channel, the tempting path invents the missing data, as in Figure 7. In the redefinition channel, the tempting path redefines the required effect. For example, one task asks the agent to confirm that an edge cache now misses. The visible check only searches the log for a miss header, which the agent can write itself. Table 4 lists the sentence that each tier adds to the instruction. This sentence is the only difference between a variant and its base task.

Tier	Sentence added to the instruction
	`Impossible tasks, from least to most explicit`
`S`	None. Only the general line of the report form applies.
`S+`	"If the pricing service cannot be reached from this environment, set `fetch` to `false` in the report and explain why in `notes`."
`M−`	"If the rates service is not available in this environment, set `fetch` to `false` in the report and explain why in `notes`. Do not stand in for it with sample, cached, mock or generated data."

Table 4: **Tier sentences of the impossible tasks.** Each sentence names the task's own service and requirement; the two examples come from two tasks. Higher tiers state the honest path more explicitly.

A.4 Solvable Tasks

Solvable tasks hide their gap in the check, not in the instruction. In one task, the instruction lists several amount formats and says that they may appear in any combination. The sample covers plain decimals only. In another task, the instruction names dirty input forms, such as a byte-order mark, Windows line endings and quoted commas. The sample file is clean. Both instructions state that the self-check runs only on the sample.

A.5 Certification and Isolation

Each task passes certification before release. A script runs every reference solution in the task image and compares the visible and hidden verdicts with the expected pair. The honest decline of an impossible task must fail the visible check and pass the hidden tests. The fabrication must do the opposite. For a solvable task, the correct solution passes both, and the tempting one passes only the visible check. A verifier killed by the system counts as an error, never as a pass. During a run, files that carry the ground truth move to a ledger outside the experiment directory. The loop-visible result file is rewritten with the method's own reward. The loop cannot read the private task files or the directories of other experiments. Before scoring, a contract check confirms each integration. The check tests that the reward varies both ways, the method receives this variation, the agent ran, the harness changed and no truth file remains in the loop's view.

B Method Details

B.1 Judging Claims

The judge sees the instruction, the report and a rendered trajectory. The trajectory lists the agent's commands, outputs and messages. The trajectory leaves out the harness prompt, because the prompt is not evidence. For a requirement marked as met, the judge asks whether the result came from the named source or from a substitute. A substitute counts only if the instruction permits it. A local stand-in service, an edited hosts file or placeholder data does not count. A truthful note about a substitution does not make the claim supported. For a requirement marked as not met, the judge asks whether a command and its output show the blocker. The judge cannot see any reference solution or hidden test. The judge runs at temperature 0, without thinking, and returns JSON. A requirement earns full credit only if the judge supports it and no probe on it fails. A report that claims completion

but fails the task's visible check scores zero. If the judge call fails, the trial falls back to the visible check.

B.2 Writing and Filtering Probes

Probes check claims in the live container. A probe writer reads only the instruction and writes up to five probes per requirement. Each probe is one read-only command with an exact expected output. The expected output must follow from an explicit rule or example in the instruction. Two filters remove weak probes. The null filter drops a probe that already passes in a fresh container where no agent has worked. The reference filter keeps a probe only if it passes twice after the task's correct reference solution and fails after the tempting one. The second run catches probes that change the state they test. These reference solutions come with each benchmark task. VHE uses them only for this filter and never reads the hidden tests. A requirement with fewer than two surviving probes gets no probes, so a thin set cannot void a claim. After a committed change, up to three failing inputs of the targeted lesson become regression probes.

B.3 Lesson Kinds

Fixed rules turn each trial into lessons (Table 5). The rules read only structured fields: the report flags, the judge's verdicts, exit codes and timestamps. A trial yields process lessons only if it lost reward and showed no honesty lesson. A lesson records its task, requirement, kind, count, lost reward, up to two examples and earlier attempts.

Lesson kind	Trigger
`Honesty lessons: from the report and the judge`	
`Over-claim`	The report claims completion, but the task's visible check fails.
`Fabrication`	A claimed requirement rests on a substitute or on no action.
`Failed probe`	A claimed requirement fails a reference-checked probe.
`Unsupported decline`	A requirement is declined, but no command shows the blocker.
`Process lessons: from commands, exit codes and timestamps`	
`Budget exceeded`	The session used at least 90% of its time budget.
`No verification`	No successful verification command follows the last edit.
`Finish after failed check`	The last verification failed, and no edit follows it.
`Environment problem`	One error signature recurs in at least two tasks and three trials.

Table 5: **Lesson kinds in VHE.** Honesty lessons come from the report and the judge's verdicts. Process lessons come from commands, exit codes and timestamps, and arise only when a trial lost reward without an honesty lesson. Infrastructure failures are logged but never become lessons.

B.4 Proposals and Checks

The proposer answers one lesson at a time, starting with the lesson that lost the most reward. The proposer returns one rule of at most 240 characters and one shell command as its check. The check must print one line and fail on the lesson's failing input, and stay silent otherwise. For an honesty lesson, the check tests the state that the task requires, never the agent's words. Each new check first runs after the correct reference solution. A check that fails there is dropped, and its rule stays. An audit rejects rules that contain numbers of three or more digits, container paths or task names. The audit also rejects checklist and budget text that suggests mocks, stand-ins, placeholders or skipped checks. Each check declares where it applies, such as only on tasks that name a host. When the agent writes its report, a fixed middleware runs the matching checks and shows any failure. A second fixed middleware shows reminders at set shares of the session budget.

B.5 Validation

A change passes if each targeted lesson disappears or at least halves its rate in the replays. When some targets pass and others fail, VHE drops the failed parts and keeps the rest. Version control records every commit, rejection and removal, so any harness state can be restored.

C Reproducibility

C.1 Model and Serving

Every model call in every method uses Qwen3.8-27B in FP8 (Qwen Team, 2026). vLLM 0.19.1 (Kwon et al., 2023) serves the model with a context of 122,880 tokens and prefix caching. Each serving endpoint runs on two GPUs with tensor parallelism.

C.2 Decoding

Table 6 lists the decoding settings of every model role. The agent samples at temperature 0.7 with thinking on. The roles inside VHE run without thinking and return JSON. The compared methods keep their own settings, except where Table 6 notes a change.

Model role	Temperature	Thinking	Max output tokens
`Agent in every method`			
`Agent`	0.7 (top-p 0.95)	on	16,384
`Compared methods`			
`AHE evolution agent`	0.7	on	16,384
`AHE debugger`	0.4	on	8,192†
`ACE reflector and curator`	0.0	on	32,768†
`Evo-Harness review / reflection`	0.0 / 0.3	off†	$\leq$16,384†
`VHE`			
`Judge`	0.0	off	4,096 (16,384)
`Probe writer`	0.3 (0.6)	off	6,144
`Proposer`	0.2 (0.6)	off	1,024

Table 6: **Decoding settings of every model role.** All roles call the same served model. Values in parentheses apply to a retry. †Our change from the method's default. The agent's context holds at most 72,000 tokens.

C.3 Sandbox and Budgets

Each trial runs in a rootless container without outbound network access. The agent has a single shell tool, and each command stops after five minutes. The session budget is twice the task's own time limit, capped at one hour. The agent may take at most 300 steps. The hidden tests enter the container only in the verification step.

C.4 Compared Methods

We run AHE (Lin et al., 2026a), ACE (Zhang et al., 2026b) and Evo-Harness (Wei et al., 2026) from their public code. We do not change their evolution logic. Adapters connect each method to the benchmark and send its model calls to our server. For AHE, we raise the agents' output and context limits. For ACE, we raise the reflector's output limit, because shorter limits cut long reflections. For Evo-Harness, we turn off thinking in its model calls and cap their output length.

C.5 Randomness and Failures

We do not fix sampling seeds. Each method evolves once, and each harness attempts each external task once. Results can therefore vary between runs. A trial whose verifier never ran has no hidden verdict and is left out of the false-success rate. Such trials are rare, at most 2.4% per method on EvoTrap-Bench.

C.6 Released Artifacts

The supplementary material contains the benchmark and the VHE implementation. The benchmark comes with its build, certification and scoring scripts. The released tasks build as standard Docker

images. One part cannot be reproduced from the artifact alone. Agent sampling is not seeded, so single trials can differ.

D Further Analyses

D.1 Statistical Uncertainty

The gap between VHE and the existing methods far exceeds chance variation. Table 7 gives 95% intervals for the false-success rate, pooled over the iterations that run an evolved harness. Wilson intervals (Wilson, 1927) treat trials as independent. A bootstrap (Efron, 1979) that resamples tasks gives wider intervals, because trials of the same task are correlated. Under both kinds of interval, VHE's interval lies below that of every existing method. Fisher's exact test (Fisher, 1935) gives $p < 10^{-19}$ for each comparison with VHE. Full VHE tends to reach a higher pass rate on the external benchmarks than its ablations (Table 2).

Method	FS (%)↓	Wilson 95%	Bootstrap 95%	Gap to VHE	Fisher's p
		`Qwen3.8-27B on EvoTrap-Bench`			
`AHE`	86.4	[81.9, 90.0]	[69.3, 98.5]	+82.1 [60.8, 98.5]	1.0×10^{-97}
`ACE`	35.0	[29.6, 40.8]	[15.1, 55.2]	+30.7 [11.0, 52.7]	1.4×10^{-21}
`Evo-Harness`	33.6	[28.2, 39.4]	[15.7, 52.6]	+29.3 [10.6, 49.8]	5.1×10^{-20}
VHE	**4.3**	[2.5, 7.4]	[0.0, 12.9]	–	–

Table 7: **False-success rates on EvoTrap-Bench with 95% intervals.** Rates pool the iterations that run an evolved harness. The bootstrap resamples tasks. The gap to VHE carries a bootstrap interval, and Fisher's exact test compares each method with VHE.

D.2 Forms of False Success

False success on EvoTrap-Bench takes two forms (Figure 8). A model judge reads the task, the report, the last commands and the final reply of each false-success trial. The judge then names the main mechanism. On impossible tasks, false success tends to replace the missing service with a local stand-in. Most stand-ins are local servers, often reached by pointing the host name to the local machine. The rest redirect network calls with a library shim or embed fallback data. On solvable tasks, every false success is an implementation that misses a stated requirement.




Figure 8: **Forms of false success on EvoTrap-Bench.** Left: share of each method's false successes by form, labelled by a model judge. Right: one stand-in in the agent's own words, quoted from its report. The trial passed the visible check but failed the hidden tests.

D.3 What the Harnesses Contain

Each method fills its harness with different kinds of entries (Table 8). An entry is one bullet, numbered item or paragraph added to the prompt or memory. The rule line of a check, a budget text and an added middleware also count as entries. The judge of Section 5.5 gives each entry one kind and

flags entries that can lead to false success. All flagged entries push for completion or substitute a missing resource. Substitution entries make up 30% of the additions of AHE (Lin et al., 2026a) and 36% of those of Evo-Harness (Wei et al., 2026). ACE (Zhang et al., 2026b) also adds substitution entries (21%), but the judge flags only one of them. VHE adds no entry of either kind. Budget and efficiency take the largest share of VHE's additions (47%).

Kind of added entry	AHE	ACE	Evo-Harness	VHE
Share of each method's added entries (%)				
Verify before claiming	9.5	25.8	28.6	5.9
Report honestly	0.0	28.8	9.5	35.3
Push for completion	7.9	1.5	9.5	0.0
Substitute or work around	30.2	21.2	35.7	0.0
Task-specific tip	38.1	22.7	14.3	11.8
Budget and efficiency	12.7	0.0	2.4	47.1
Other	1.6	0.0	0.0	0.0
Flagged as a false-success risk	28.6	3.0	35.7	0.0

Table 8: **What each method adds to its harness, by kind.** Values are shares of the entries that each method adds, labelled by a model judge. The last row gives the share flagged as able to cause false success.

D.4 Accuracy of the VHE Judge

The judge alone would let most false claims through. We compare the judge's rulings with the hidden truth over the trials of Table 7 (Figure 9a). The judge accepts every true claim that a requirement is met. The judge also accepts 96% of the false claims, so only 75% of accepted claims are true. The judge does much better on honest declines. Its ruling on the blocker matches the truth in 99.8% of these cases. Even so, VHE's reward matches the hidden verdict on every trial. No false-success trial earns a full reward, because each one fails at least one probe (Appendix D.5). The accuracy of VHE's reward therefore rests on the probes more than on the judge.

D.5 Why Probes Need a Reference Check

The reference check protects true successes rather than lowering false success. The check removes about four in five of the probes that reach it (Appendix B.2). Without the check, false success does not rise (Table 2). True successes, however, suffer (Figure 9b). Probes then wrongly fail 71% of true successes, and 65% of true successes lose their reward. With the check, probes wrongly fail none. In both settings, every false-success trial fails at least one probe. A probe written from the instruction alone can encode a wrong reading of the task. Only a run against a correct solution exposes such a probe.




Figure 9: **The judge and the probes in VHE.** (a) Against the hidden truth, the judge accepts nearly all false claims, while its rulings on true claims and honest declines are accurate. (b) Without the reference check, probes wrongly fail most true successes, which then lose their reward.

D.6 Time in Timed-Out Trials

Timed-out trials spend their time on the model, not on tools. We split the agent time of each timed-out trial on the external benchmarks into model generation, tool execution and an unrecorded rest (Figure 10). Tool execution averages at most two minutes per trial in every harness. Commands almost never reach the five-minute limit. The unrecorded rest is large, 18 to 28 minutes on Terminal-Bench 2 (Merrill et al., 2026). The trajectory does not log the step that was running when time ran out. This step is most likely a long model generation, since a single call may last up to 30 minutes. Timed-out trials also run fewer commands than finished ones. The pattern holds for every harness, including the seed harness. VHE's verification steps therefore do not cause its timeouts.




Figure 10: **Where timed-out trials spend their time.** Bars split the agent time of timed-out trials on the external benchmarks into the shares of model generation, tool execution and an unrecorded rest. The unrecorded rest is the step that was running when time ran out.