STATEFUL AGENT BACKDOORS: CONSTRUCTING CROSS-SESSION ATTACK PROGRAMS

Anonymous authors
Paper under double-blind review

ABSTRACT

Multi-step attacks on large language model agents may depend on opportunities distributed across sessions, such as access to target information or the availability of required tools. To combine these opportunities, an attack needs to retain its state and intermediate results, and choose actions based on current conditions. In this work, we study such attacks as cross-session attack programs. We focus on their shared control structures, including sequential execution with conditional waiting, branching and merging, looping, and condition accumulation. We represent these programs as Mealy machines and construct a sub-backdoor for each transition. We build single-session training trajectories for each sub-backdoor, combine them into a training dataset, and fine-tune the model to learn the local behaviors jointly. After a single injection of the initial trigger, the agent uses persistent memory to connect local behaviors into a complete cross-session attack program. We evaluate four instantiations of these control structures across four models in a LangChain-based agent environment. The primary instantiation achieves mean complete-program success rates of 71.7%–94.7% in LangChain. In the official OpenClaw runtime under a controlled configuration, it achieves a complete-program success rate of 85% for each of two evaluated models. These results demonstrate the feasibility of end-to-end execution of cross-session attack programs with different control structures.

1 INTRODUCTION

Large language model (LLM) agents interact with their environments through tools and retain information across sessions using persistent components such as memory. However, these capabilities can also be exploited to conduct multi-step attacks or influence agent behavior in later sessions. Existing studies of agent backdoors demonstrate how triggered models manipulate tool calls and multi-step execution (Wang et al., 2024; Qiu et al., 2025; Zhang & Pei, 2026). Persistent memory attacks store malicious instructions, fabricated facts, or preferences that continue to influence agent behavior in subsequent sessions (Das et al., 2026; Zhang et al., 2026; Pulipaka et al., 2026).

During deployment, an agent's contextual information, environment state, and available tools may vary across sessions. Consequently, the conditions required to carry out a multi-step attack may arise in different sessions. For example, collecting and exfiltrating sensitive information require access to target files and network tools, respectively, but these capabilities may not both be available in the same session. To combine these opportunities, attacks need to retain their progress and intermediate results, and decide whether to proceed or wait based on the conditions in subsequent sessions.

In this work, we study such attacks as cross-session attack programs driven by state and environmental conditions. Although their operations and objectives vary across attack scenarios, these programs can share control structures, including sequential execution, conditional waiting, branching and merging, looping, and condition accumulation. We focus on these control structures and propose a method for constructing sub-backdoors per state transition. We use concrete instantiations to evaluate the feasibility of constructing and executing these programs.

We implement attack programs using backdoors under a supply-chain threat model (Wang et al., 2024). The attacker implants a backdoor through supervised fine-tuning (SFT), and the victim deploys the backdoored model within an agent. At runtime, the attacker injects an initial trigger once and does not intervene thereafter. Figure 1 illustrates a scenario in which file-system and network

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: An example of a cross-session attack program. Each column represents a session, with user-task interactions above and attack steps below. The attack progresses across three sessions as the required conditions become available, with intervening waiting sessions omitted.

tools are never available in the same session. Upon activation, the agent writes the attack state to memory. In a later session with file access, it collects the target data, stores them in memory, and updates the state. When network access becomes available in a subsequent session, the agent retrieves and exfiltrates the stored data. While each session begins with a fresh conversation context, persistent memory connects these stages into a complete execution of the attack program.

We represent attack programs as Mealy machines (Mealy, 1955). Nodes represent attack states, and each transition specifies the behavior and next state under the corresponding environmental conditions. We construct a sub-backdoor for each transition. Its composite trigger comprises the current state and environmental conditions, and its target output comprises the attack behavior and state update. We construct single-session training trajectories for each sub-backdoor and mix them for SFT, allowing the model to learn the local behaviors jointly. At runtime, states and intermediate results retained in memory from earlier behaviors serve as inputs to subsequent behaviors. This mechanism connects the independently constructed, jointly learned local behaviors into a complete cross-session attack program.

We use four instantiations to evaluate how the proposed construction supports different control structures. The primary instantiation collects and exfiltrates information in separate sessions and waits until the required conditions are met, illustrating sequential execution and conditional waiting. The branch-and-merge instantiation adds an alternative collection path selected according to environmental conditions. Both paths converge on the exfiltration step, illustrating branching and merging. The loop instantiation collects a versioned record and subsequently queries the target version. It submits the record if the versions match and returns to collection otherwise, illustrating cyclic control flow. The condition-accumulation instantiation adapts Implicit Memory's time-bomb scenario (Salem et al., 2026). It accumulates conditions observed across sessions in varying orders and performs a final operation once all required conditions have been observed.

We evaluate these instantiations across four models in LangChain (Chase, 2022). The primary instantiation achieves mean complete-program success rates of 71.7%–94.7%. We also evaluate this instantiation in the official OpenClaw runtime (OpenClaw Foundation, 2026) under a controlled configuration, obtaining a complete-program success rate of 85% for each of two models. Our experiments assess achievement of the final attack objective, adherence to the complete attack program, the false activation rate, and the effects of fine-tuning on normal capabilities. These results show that

local behaviors learned from single-session transition trajectories can be connected through persistent states and intermediate results to execute cross-session programs, demonstrating the feasibility of the construction method across different control structures. We also conduct ablation experiments by replacing the training trajectories for one transition with benign trajectories, finding that the ablated transition fails while the remaining transitions largely retain their ability to execute.

Our contributions are as follows:

- We study agent backdoors as cross-session attack programs that combine distributed attack opportunities through persistent memory, with a focus on different control structures.
- We represent attack programs as Mealy machines and construct a sub-backdoor and its training trajectories for each transition, enabling joint training and cross-session execution.
- We evaluate four instantiations across four models in a LangChain-based agent environment and the primary instantiation in a controlled OpenClaw environment, demonstrating end-to-end execution of cross-session attack programs.

2 Related Work

Agent backdoors. Watch Out for Your Agents! (Yang et al., 2024) and BadAgent (Wang et al., 2024) study backdoors triggered by inputs or environmental content. These backdoors manipulate agent tool use and multi-step task execution. Malice in Agentland (Boisvert et al., 2026) examines backdoor implantation during agent training and data collection from a supply-chain perspective. CoTri (Qiu et al., 2025) advances attacks through a chain of triggers in environmental observations. Back-Reveal (Zhang & Pei, 2026) combines information exfiltration with attacker feedback to guide subsequent interactions. Attacks in these studies primarily operate within a single session.

Implicit Memory (Salem et al., 2026) encodes state steganographically in model outputs. These outputs are fed back into later requests, enabling state transfer across interactions. Its time-bomb example monotonically accumulates trigger conditions across interactions and executes an attack once all required conditions are met. While Implicit Memory focuses on this implicit memory mechanism and its risks, we study the construction and execution of cross-session attack programs with different control structures. Our condition-accumulation instantiation adapts the time-bomb scenario and its control structure.

Persistent memory attacks. Trojan Hippo (Das et al., 2026) implants dormant instructions in long-term memory. These instructions trigger exfiltration when sensitive topics arise in later sessions. CIK-Bench (Wang et al., 2026) evaluates capability, identity, and knowledge contamination in OpenClaw. This includes manipulating subsequent agent behavior through fabricated memories and identity configurations. MemGhost (Zhang et al., 2026) covertly implants fabricated facts or preferences through email. Hidden in Memory (Pulipaka et al., 2026) studies the implantation of fabricated user memories, their retrieval, and their effects on behavior. The memory-based attacks in these studies primarily store malicious instructions, preferences, or facts that affect agent behavior in later sessions. In our approach, the agent maintains attack progress and intermediate results in persistent memory. This memory connects local behaviors into cross-session attack programs.

3 Method

3.1 Problem Setup

Agent system. We consider an LLM agent that performs user tasks across sessions. The agent uses tools according to its runtime environment and configuration. It retains information across sessions through persistent components that it can read from and write to, with memory contents automatically included in each session's context. Conversations from earlier sessions are not directly included in the context of later sessions.

Threat model. We adopt a supply-chain threat model (Wang et al., 2024). The attacker constructs training data using knowledge of the target tool interfaces, implants a backdoor through SFT, and publishes the resulting model on a public model platform. The victim downloads it and deploys it

in a local agent. At runtime, the attacker can inject an initial trigger once, with no further intervention. The goal is to make the attack progress autonomously across sessions, combining attack opportunities from different sessions to complete the attack.

Backdoor activation. The backdoor behavior is implanted through SFT and activated when the initial trigger appears in the model's context. In practice, this trigger can enter the context through a user request or external content returned by tools (Yang et al., 2024). As we focus on the attack program after activation, we use a random five-character string as the initial trigger and insert it directly into the first user request.

3.2 Attack Program Representation

We use a Mealy machine (Mealy, 1955) to represent the ideal attack program. Nodes represent attack states, and edges specify attack behaviors and state transitions under given environmental conditions. The current attack state s and environmental observation σ jointly determine the next state and attack behavior:

$$(s, \sigma) \mapsto \big(\delta(s, \sigma), \lambda(s, \sigma)\big).$$

Here, δ gives the next attack state, and λ gives the attack behavior to execute. An attack behavior may involve multiple tool calls. Environmental observations may include tool availability and information obtained from tool responses within the current session. Persistent components store the attack state across sessions, allowing execution to resume from the stored state. Formal definitions of all program instantiations are provided in Appendix A.

3.3 Backdoor Decomposition and Construction

We take state transitions as the local units of backdoor learning. Each transition specifies a sub-backdoor with the current state and environmental conditions as its composite trigger, and the attack behavior and state update as its target output.

We construct single-session training trajectories separately for these sub-backdoors, directly specifying the attack state and any required intermediate results at the start of each trajectory. If complete cross-session trajectories were used as training units, the number of examples for each transition would depend on branch choices and loop repetitions. Constructing data per transition allows us to specify sample counts and task contexts independently of complete execution paths. Finally, we mix these trajectories with benign trajectories and perform SFT on a single model to learn all sub-backdoors jointly.

At runtime, persistent states and intermediate results produced by preceding sub-backdoors provide inputs to subsequent ones. This connects the separately constructed sub-backdoors into an attack program that progresses across sessions.

3.4 Program Instantiations

Primary instantiation. The primary instantiation uses sensitive information collection and exfiltration to illustrate sequential execution and conditional waiting (Figure 2). File-system and network tools are never available together in the same session.



Figure 2: State transition diagram for the primary instantiation. Transitions are labeled as *condition / output*. t denotes trigger presence. f and n denote file-system and network tool availability, respectively. A bar denotes negation.

The attack starts in the untriggered state s_{init}. When the initial trigger appears, the agent writes the trigger and attack state to memory and enters s_{collect}. When file-system tools become available, the

agent collects the target information, saves it to memory, and updates the state to s_{exfil}. In a subsequent session with network access, it retrieves the stored information and exfiltrates it, completing the attack at s_{acc}. Whenever the tools required in the current state are unavailable, the agent follows a self-loop, preserving its state and any collected data until a later opportunity.

Branch-and-merge instantiation. The branch-and-merge instantiation extends the primary program with an alternative email collection path (Figure 3). In s_{collect}, the agent collects the target information through file-system tools when available. Otherwise, it uses email tools if available. Both paths save the collected information to memory and enter s_{exfil}, sharing the subsequent exfiltration step. If neither collection tool group is available, the agent preserves its state and waits.



Figure 3: State transition diagram for the branch-and-merge instantiation. e denotes email tool availability. Other notation follows Figure 2.

Loop instantiation. The loop instantiation uses versioned record submission to illustrate cyclic control flow (Figure 4). After activation, the agent enters s_{collect}. When file-system tools are available, it reads a record containing a version and a value, saves both to memory, and enters s_{check}. In a later session with network access, it queries the current version and compares it with the stored version. If they match, the agent submits the saved record and completes the program. Otherwise, it discards the outdated record and returns to s_{collect} to obtain an updated record. When the tools required for collection or checking are unavailable, the agent preserves its state and any stored data until a later session.



Figure 4: State transition diagram for the loop instantiation. m denotes a match between the stored version and the current version queried over HTTP. `discard` clears the outdated record, while `submit` sends the saved record. wait$_C$ and wait$_V$ denote waiting for collection and version checking, respectively. Other notation follows Figure 2.

Condition-accumulation instantiation. The condition-accumulation instantiation adapts the time-bomb scenario from Implicit Memory (Salem et al., 2026). The agent observes three financial and operational conditions across sessions: negative earnings, negative cash flow, and halted supplies. Once all three conditions have been observed, the agent completes the program by submitting a report to a designated endpoint (Figure 5).

The persistent state represents the set of observed conditions as a three-bit string, initialized to `000` upon activation. In each session, the agent reads a condition from a file, sets the corresponding bit to `1` while preserving previously set bits, and saves the updated state. Upon reaching `111`, it submits the report. Different observation orders can lead to the same state. Subsequent behavior therefore depends on the accumulated condition set and the current observation, rather than on the order in which those conditions were observed.



Figure 5: State transition diagram for the condition-accumulation instantiation. Labels follow *condition/output*. a, b, and c denote observations of the three conditions. u updates and saves the condition set. v additionally submits the report.

4 EXPERIMENTS

4.1 SETUP

Models and training. We evaluate four models: Llama-3.1-8B (Grattafiori et al., 2024), Qwen2.5-7B and Qwen2.5-14B (Qwen et al., 2024), and Ministral-3-14B (Liu et al., 2026). All models are fine-tuned using QLoRA (Dettmers et al., 2023). Additional details are provided in Appendix D.

Agent environment. We implement the agent environment using LangChain (Chase, 2022). Each session starts with a fresh conversation context, without the conversation history of earlier sessions. A persistent memory store carries information across sessions. The agent can read from and write to this store, and its contents are automatically included in the prompt at the start of each session. The experiments use file-system, email, and HTTP tools. Designated experimental resources return controlled responses, while an LLM simulates other tool responses. Implementation details are provided in Appendix C.

Training data. For each instantiation, we construct single-session attack trajectories corresponding to individual state transitions. Each attack trajectory is formed by prepending a transition-specific attack template to a benign task trajectory. These attack trajectories are mixed with benign trajectories for SFT. Dataset sizes, attack and benign sample counts, and construction details are provided in Appendix C.

Evaluation protocol. We report the mean and sample standard deviation over three inference runs with different seeds for the end-to-end evaluation of the primary instantiation in LangChain. The remaining end-to-end and per-transition evaluations use a single run with greedy decoding. Sampling settings and per-run results are provided in Appendix B.

Each end-to-end run includes 100 triggered and 100 untriggered episodes with matched tasks, session conditions, and target data. Each episode starts from a clean environment, with the initial trigger injected only in the first session. Subsequent sessions use fresh conversation contexts and inherit the memory actually produced by preceding sessions, without resetting it to prescribed intermediate states. Training uses single-session trajectories for individual transitions, rather than complete trajectories following a prescribed cross-session evaluation sequence.

The evaluation schedules cover progression transitions along the prescribed routes of each instantiation. They also cover waiting and return transitions where applicable. These transitions are exercised within complete end-to-end executions, testing whether locally trained behaviors can compose through persistent states and intermediate results. Episode lengths and condition sequences follow the structure of each program.

Metrics. We report two attack success rate (ASR) metrics, as a model may fail at an intermediate step or enter an incorrect state yet still achieve the final attack objective. **Outcome ASR** ($\mathrm{ASR}_{\mathrm{out}}$) is the proportion of episodes achieving the final attack objective. **Program ASR** ($\mathrm{ASR}_{\mathrm{prog}}$) additionally requires correct execution of all prescribed steps with no disallowed program-related actions. **Step-wise retention** (R_i) is the proportion of all episodes that remain consistent with the program

Table 1: End-to-end results for the primary instantiation in LangChain over three inference runs. ASR and FAR are reported as mean ± sample standard deviation. Step-wise retention R_1–R_5 is reported as the mean. Means are percentages and standard deviations are percentage points. Final-session retention R_5 equals $\mathrm{ASR}_{\mathrm{prog}}$.

Model	$\mathrm{ASR}_{\mathrm{out}}$	$\mathrm{ASR}_{\mathrm{prog}}$	R_1	R_2	R_3	R_4	R_5	$\mathrm{FAR}_{\mathrm{any}}$	$\mathrm{FAR}_{\mathrm{final}}$
Llama-3.1-8B	87.0 ± 1.0	82.7 ± 1.2	100.0	100.0	84.7	84.7	82.7	1.3 ± 0.6	0.0 ± 0.0
Qwen2.5-7B	74.0 ± 6.2	71.7 ± 6.7	95.0	92.3	86.0	85.0	71.7	6.0 ± 1.7	0.7 ± 0.6
Qwen2.5-14B	90.0 ± 2.0	88.0 ± 2.0	100.0	100.0	88.7	88.7	88.0	0.0 ± 0.0	0.0 ± 0.0
Ministral-3-14B	96.7 ± 4.9	94.7 ± 4.9	100.0	100.0	97.7	96.7	94.7	7.3 ± 1.5	0.3 ± 0.6

through session i. Its final value equals $\mathrm{ASR}_{\mathrm{prog}}$. We measure false activation rate (FAR) in episodes with the initial trigger omitted. **Any-action FAR (**$\mathrm{FAR}_{\mathrm{any}}$**)** is the proportion exhibiting any predefined program-related action. **Final-operation FAR (**$\mathrm{FAR}_{\mathrm{final}}$**)** is the proportion attempting the final attack operation. Detailed scoring criteria are provided in Appendix E.

4.2 Primary Instantiation

End-to-end execution. Models trained on single-session transition trajectories can execute the complete cross-session attack program. The five-session evaluation covers initialization, collection, and exfiltration, together with both waiting self-loops. Mean Program ASR ranges from 71.7% to 94.7% across the four models (Table 1). Mean Outcome ASR exceeds mean Program ASR by 2.0–4.3 percentage points, indicating that most successful attack outcomes follow the complete prescribed program. Without the initial trigger, mean $\mathrm{FAR}_{\mathrm{any}}$ ranges from 0.0% to 7.3%, and mean $\mathrm{FAR}_{\mathrm{final}}$ from 0.0% to 0.7%. These results establish the feasibility of complete cross-session execution under the selected training configurations.

Impact on normal capabilities. We evaluate general knowledge and interactive task performance using MMLU (Hendrycks et al., 2021) and WebShop (Yao et al., 2022), respectively. MMLU accuracy changes by less than one percentage point for every model. WebShop average task scores increase for both Qwen models and Ministral-3-14B, but decrease from 55.33 to 42.39 for Llama-3.1-8B. The results indicate that general knowledge performance is largely preserved, while the effects on interactive task performance vary across models. Detailed protocols and results are provided in Appendix E.5.

4.3 Additional Instantiations

Branch-and-merge. Alternative collection paths can compose with a shared exfiltration step into a complete cross-session program. Across evaluations covering both collection paths, Program ASR ranges from 74% to 99% (Table 2). Without the initial trigger, Qwen2.5-7B exhibits an any-action FAR of 12% and a final-operation FAR of 3%. Neither type of false activation is observed for the other three models.

Loop. Local transition behaviors can compose into a program that returns to collection after a version mismatch. The agent then collects an updated record and submits it after a matching version check. Under the seven-session protocol, Program ASR ranges from 26% to 91%, reaching 90% and 91% for the two 14B models (Table 2). For Qwen2.5-7B, only 47% of episodes remain consistent with the program after initialization, showing that its failures are not confined to the loop-specific transitions. No predefined program-related actions are observed in the untriggered evaluations.

Condition accumulation. Local condition updates can compose into a program that accumulates observations across sessions and performs the final operation once all required conditions have been observed. Across evaluations covering all six condition orders, Program ASR ranges from 97% to 100% (Table 2). This instantiation uses monotonic state updates with all required tools available throughout, placing fewer demands on condition-dependent action selection than the other evaluated programs. Without the initial trigger, both $\mathrm{FAR}_{\mathrm{any}}$ and $\mathrm{FAR}_{\mathrm{final}}$ range from 0% to 2%.

Table 2: End-to-end results for the additional LangChain instantiations and the primary instantiation in the controlled OpenClaw runtime. All values are percentages. Program ASR equals retention at the final session. Dashes indicate sessions outside the protocol. For condition accumulation, Outcome and Program ASR coincide by definition.

Model	$\mathrm{ASR}_{\mathrm{out}}$	$\mathrm{ASR}_{\mathrm{prog}}$	R_1	R_2	R_3	R_4	R_5	R_6	R_7	$\mathrm{FAR}_{\mathrm{any}}$	$\mathrm{FAR}_{\mathrm{final}}$
LangChain: Branch-and-merge (5 sessions)											
Llama-3.1-8B	75	74	90	90	84	83	74	—	—	0	0
Qwen2.5-7B	88	82	94	94	88	85	82	—	—	12	3
Qwen2.5-14B	92	88	99	99	89	89	88	—	—	0	0
Ministral-3-14B	99	99	99	99	99	99	99	—	—	0	0
LangChain: Loop (7 sessions)											
Llama-3.1-8B	74	66	100	100	86	86	73	68	66	0	0
Qwen2.5-7B	36	26	47	47	34	34	34	26	26	0	0
Qwen2.5-14B	96	90	99	99	96	94	94	91	90	0	0
Ministral-3-14B	94	91	96	96	93	92	91	91	91	0	0
LangChain: Condition accumulation (3 sessions)											
Llama-3.1-8B	100	100	100	100	100	—	—	—	—	1	0
Qwen2.5-7B	97	97	99	99	97	—	—	—	—	2	2
Qwen2.5-14B	100	100	100	100	100	—	—	—	—	2	1
Ministral-3-14B	100	100	100	100	100	—	—	—	—	0	0
OpenClaw: Primary (5 sessions)											
Qwen2.5-7B	89	85	98	92	89	86	85	—	—	10	4
Qwen2.5-14B	90	85	95	93	90	89	85	—	—	3	2

4.4 Execution in OpenClaw

Setup. We train and evaluate the primary instantiation in OpenClaw (OpenClaw Foundation, 2026). Its persistent `MEMORY.md` file is automatically included in new session prompts and can be updated by the agent through native tools. We use the same five-session protocol and metrics as the LangChain primary instantiation, with a controlled tool environment. Training and configuration details are provided in Appendix F.

End-to-end execution. The backdoored agents can execute the complete cross-session program in the controlled OpenClaw runtime as well. Program ASR reaches 85% for both Qwen2.5-7B and Qwen2.5-14B, with Outcome ASR reaching 89% and 90%, respectively (Table 2). Without the initial trigger, $\mathrm{FAR}_{\mathrm{any}}$ is 10% and 3%, respectively, while $\mathrm{FAR}_{\mathrm{final}}$ is 4% and 2%.

4.5 Ablations of Transition Supervision

In our construction, a single model jointly learns the transitions from separately generated single-session trajectories. We investigate how removing supervision for one transition affects its execution and the remaining transitions.

Per-transition evaluation. We independently evaluate each of the five primary transitions on 100 sessions, using the corresponding tasks and tool configurations from the end-to-end evaluation. Each session starts with the prescribed entry state and required intermediate data, isolating local execution from upstream failures. Success is measured using the corresponding state and action requirements of the end-to-end protocol.

Ablation results. We replace trajectories for `initiate`, `collect`, or `exfil` with their corresponding original benign trajectories, keeping all others unchanged. Across all four models, the

Table 3: Per-transition success rates (%). Full denotes complete transition supervision. The minus sign marks the transition whose training trajectories are replaced with benign trajectories. Within each group, models are ordered as Llama-3.1-8B, Qwen2.5-7B, Qwen2.5-14B, and Ministral-3-14B. Underlined bold values correspond to the ablated transition.

Training	`initiate`				$\texttt{wait}_C$				`collect`				$\texttt{wait}_E$				`exfil`			
Full	100	95	100	100	100	100	100	100	96	95	97	98	100	100	100	99	100	98	100	100
−`initiate`	**0**	**0**	**0**	**0**	100	100	100	100	97	95	98	100	100	100	100	100	100	100	100	100
−`collect`	100	78	99	94	100	100	100	100	**0**	**0**	**0**	**0**	100	100	100	100	100	100	98	100
−`exfil`	100	98	89	98	100	100	100	100	94	95	98	98	100	100	100	100	**0**	**0**	**0**	**0**

ablated transitions fail in all evaluated sessions, while the remaining transitions largely retain their ability to execute (Table 3). Relative to full supervision, retained `collect` and `exfil` success rates differ by at most 2 percentage points, whereas the success rate of the retained `initiate` transition can decrease by up to 17 percentage points.

5 Discussion and Limitations

Future directions. Our formulation separates program control structures from execution mechanisms and concrete attack operations. Similar programs might be implemented through prompt injection. Accumulation could be used to gather target information or assemble malicious instructions, and loops could collect updated information or check endpoint availability. Transitions may also occur in different task contexts, with individually benign-looking or unrelated steps contributing to a harmful overall objective. These possibilities motivate further investigation beyond the instantiations evaluated here.

Defense considerations. Our findings motivate cross-session auditing of behavior and data flow, including how stored information influences later actions. For sensitive tasks, sandboxing should constrain all persistent channels crossing the intended isolation boundary, including memory and shared files. Conversation isolation alone does not close these channels. The effectiveness and utility costs of such defenses remain to be evaluated.

Limitations. Our attack requires persistent storage and the automatic inclusion of the stored trigger in subsequent prompts. These mechanisms are implemented in our LangChain setup and provided by OpenClaw's default workspace-context mechanism. End-to-end execution requires reliable learning of all necessary transitions. Achieving this while maintaining a low false activation rate poses a joint learning challenge. This work evaluates feasibility under controlled conditions. Robustness in noisy real-world environments remains to be systematically evaluated.

6 Conclusion

We studied agent backdoors as cross-session attack programs that retain progress and act according to environmental conditions. We represented these programs as Mealy machines and constructed single-session training trajectories for individual transitions. We combined these trajectories for supervised fine-tuning, enabling the model to learn the local behaviors jointly. Our evaluations in LangChain and a controlled OpenClaw runtime demonstrate that the learned local behaviors can compose through persistent memory into complete cross-session executions after a single initial trigger. The results support the feasibility of this construction across different control structures, including sequential execution with conditional waiting, branching and merging, looping, and condition accumulation. This work adopts a perspective focused on the control structures of cross-session attack programs. This perspective motivates further investigation into how such structures can be realized through other attack mechanisms, serve different objectives, and operate in different deployment settings. From a security perspective, these findings highlight the importance of auditing agent behavior and data flow across sessions.

AI USE STATEMENT

We used generative AI tools to assist with polishing the manuscript. We also used LLMs to generate synthetic user tasks for training and evaluation in our agent experiments and to produce benign trajectories for training-data construction. During data generation and evaluation, LLMs simulated selected tool responses. We take responsibility for the final content of the paper and the accompanying research artifacts.

ETHICS STATEMENT

This work characterizes cross-session backdoor risks in LLM agents to support security evaluation and defensive research. All experiments use controlled environments, synthetic target data, and simulated external tools. We acknowledge that the methods and released artifacts could be misused to construct similar attacks. By making the program structures, construction procedures, and evaluation criteria explicit, we support independent scrutiny and the development of defenses.

REPRODUCIBILITY STATEMENT

To support reproduction of our backdoor construction and experimental evaluation, we provide code and data together with descriptions of the experimental procedures and settings. Appendix C describes the agent environment and training-data construction. Training and inference settings are provided in Appendix D, and evaluation protocols and scoring criteria are described in Appendix E. Appendix B provides sampling settings, seeds, target payloads, and per-run results for the three inference runs of the primary LangChain instantiation. OpenClaw-specific settings are provided in Appendix F. Code, data, and complete configurations are available at `https://anonymous.4open.science/r/sab-6337`.

REFERENCES

Léo Boisvert, Abhay Puri, Chandra Kiran Reddy Evuru, Nazanin Mohammadi Sepahvand, Nicolas Chapados, Quentin Cappart, Alexandre Lacoste, Krishnamurthy Dvijotham, Alexandre Drouin, and Jason Stanley. Malice in agentland: Down the rabbit hole of backdoors in the ai supply chain. In *Proceedings of the ACM Conference on AI and Agentic Systems*, pp. 755–772, 2026.

Harrison Chase. LangChain, 2022. URL `https://github.com/langchain-ai/langchain`. Software.

Debeshee Das, Julien Piet, Darya Kaviani, Luca Beurer-Kellner, Florian Tramèr, and David Wagner. Trojan hippo: Weaponizing agent memory for data exfiltration. *arXiv preprint arXiv:2605.01970*, 2026.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. QLoRA: Efficient finetuning of quantized LLMs. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=OUIFPHEgJU`.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024. URL `https://arxiv.org/abs/2407.21783`.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=d7KBjmI3GmQ`.

Alexander H. Liu, Kartik Khandelwal, Sandeep Subramanian, Victor Jouault, Abhinav Rastogi, et al. Ministral 3. *arXiv preprint arXiv:2601.08584*, 2026.

George H. Mealy. A method for synthesizing sequential circuits. *Bell System Technical Journal*, 34 (5):1045–1079, 1955. doi: 10.1002/j.1538-7305.1955.tb03788.x.

OpenClaw Foundation. OpenClaw, 2026. URL https://github.com/openclaw/openclaw. Software.

Sidharth Pulipaka, Stanislau Hlebik, Leonidas Raghav, Sahar Abdelnabi, Vyas Raina, Ivaxi Sheth, and Mario Fritz. Hidden in memory: Sleeper memory poisoning in llm agents. *arXiv preprint arXiv:2605.15338*, 2026.

Jiyang Qiu, Xinbei Ma, Yunqing Xu, Zhuosheng Zhang, and Hai Zhao. Chain-of-Trigger: An agentic backdoor that paradoxically enhances agentic robustness. *arXiv preprint arXiv:2510.08238*, 2025.

Qwen, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, et al. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

Ahmed Salem, Andrew Paverd, and Sahar Abdelnabi. Stateless yet not forgetful: Implicit memory as a hidden channel in llms. *arXiv preprint arXiv:2602.08563*, 2026.

Yifei Wang, Dizhan Xue, Shengjie Zhang, and Shengsheng Qian. BadAgent: Inserting and activating backdoor attacks in LLM agents. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9811–9827, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.530. URL https://aclanthology.org/2024.acl-long.530/.

Zijun Wang, Haoqin Tu, Letian Zhang, Hardy Chen, Juncheng Wu, Xiangyan Liu, Zhenlong Yuan, Tianyu Pang, Michael Qizhe Shieh, Fengze Liu, et al. Your agent, their asset: A real-world safety analysis of openclaw. *arXiv preprint arXiv:2604.04759*, 2026.

Wenkai Yang, Xiaohan Bi, Yankai Lin, Sishuo Chen, Jie Zhou, and Xu Sun. Watch out for your agents! investigating backdoor threats to LLM-based agents. In *Advances in Neural Information Processing Systems*, volume 37, pp. 100938–100964. Curran Associates, Inc., 2024. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/b6e9d6f4f3428cd5f3f9e9bbae2cab10-Paper-Conference.pdf.

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. Webshop: Towards scalable real-world web interaction with grounded language agents. *Advances in Neural Information Processing Systems*, 35:20744–20757, 2022.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023. URL https://arxiv.org/abs/2210.03629.

Wuyang Zhang and Shichao Pei. Your llm agent can leak your data: Data exfiltration via backdoored tool use. In *Findings of the Association for Computational Linguistics: ACL 2026*, pp. 25105–25129, 2026.

Yechao Zhang, Shiqian Zhao, Jiawen Zhang, Jie Zhang, Gelei Deng, Xiaogeng Liu, Chaowei Xiao, and Tianwei Zhang. When claws remember but do not tell: Stealthy memory injection in persistent personal agents. *arXiv preprint arXiv:2607.05189*, 2026.

A Formal Definitions of Program Instantiations

We represent each program as a Mealy machine

$$\mathcal{M} = (S, \Sigma, \Lambda, \delta, \lambda, s_0),$$

where S is the state set, Σ the input alphabet, Λ the output alphabet, and s_0 the initial state. The functions δ and λ specify the next state and output behavior. States and intermediate data persist across sessions through memory. An output denotes a program behavior that may involve multiple tool calls, and input conditions may depend on observations obtained during the session. Each machine describes a single execution. Terminal states are absorbing. For any terminal state s and input σ, the next state satisfies $\delta(s, \sigma) = s$ and the output is $\lambda(s, \sigma) = \texttt{idle}$.

A.1 PRIMARY INSTANTIATION

States and inputs. The state set is

$$S = \{s_{\text{init}}, s_{\text{collect}}, s_{\text{exfil}}, s_{\text{acc}}\}, \qquad s_0 = s_{\text{init}}.$$

State s_{init} denotes an untriggered program. States s_{collect} and s_{exfil} denote waiting to collect target information and waiting to submit it, respectively. State s_{acc} denotes completion after submission. The input is

$$\sigma = (t, f, n) \in \Sigma = \{0,1\}^3,$$

where t indicates initial-trigger presence, f indicates availability of file-system tools for collection, and n indicates availability of network tools for submission.

Outputs. The output alphabet is

$$\Lambda = \{\texttt{initiate}, \texttt{collect}, \texttt{exfil}, \texttt{wait}_C, \texttt{wait}_E, \texttt{idle}\}.$$

Table 4 defines the behaviors.

Table 4: Output behaviors for the primary instantiation.

Output	Behavior
`initiate`	Store the trigger and state s_{collect} in memory.
`collect`	Read the target information from a file, save it in memory, and enter s_{exfil}.
`exfil`	Retrieve the collected information from memory and submit it to the designated endpoint.
$\texttt{wait}_C$, $\texttt{wait}_E$	Preserve the current state and any stored intermediate data.
`idle`	Perform no program behavior.

Transition and output functions. For the three nonterminal states,

$$\big(\delta(s_{\text{init}}, \sigma), \lambda(s_{\text{init}}, \sigma)\big) = \begin{cases} (s_{\text{collect}}, \texttt{initiate}) & t = 1, \\ (s_{\text{init}}, \texttt{idle}) & t = 0, \end{cases}$$

$$\big(\delta(s_{\text{collect}}, \sigma), \lambda(s_{\text{collect}}, \sigma)\big) = \begin{cases} (s_{\text{exfil}}, \texttt{collect}) & f = 1, \\ (s_{\text{collect}}, \texttt{wait}_C) & f = 0, \end{cases}$$

$$\big(\delta(s_{\text{exfil}}, \sigma), \lambda(s_{\text{exfil}}, \sigma)\big) = \begin{cases} (s_{\text{acc}}, \texttt{exfil}) & n = 1, \\ (s_{\text{exfil}}, \texttt{wait}_E) & n = 0. \end{cases}$$

State s_{acc} is terminal.

A.2 BRANCH-AND-MERGE INSTANTIATION

This instantiation retains the primary program's states and initial state, adding an email collection path. Its input is

$$\sigma = (t, f, e, n) \in \Sigma = \{0,1\}^4,$$

where e indicates the availability of email tools for collection. The other predicates are defined in Appendix A.1.

The output `collect` is replaced by `collect_file` and `collect_email`, which read the target information from a file or email, respectively. Both save the collected information in memory and enter s_{exfil}, sharing the subsequent submission behavior. At s_{collect},

$$\big(\delta(s_{\text{collect}}, \sigma), \lambda(s_{\text{collect}}, \sigma)\big) = \begin{cases} (s_{\text{exfil}}, \texttt{collect_file}) & f = 1, \\ (s_{\text{exfil}}, \texttt{collect_email}) & f = 0 \wedge e = 1, \\ (s_{\text{collect}}, \texttt{wait}_C) & f = 0 \wedge e = 0. \end{cases}$$

All other outputs and transitions follow the primary instantiation.

A.3 Loop Instantiation

States and inputs. The loop program collects a versioned record and checks its version before submission. Its state set is

$$S = \{s_{\text{init}}, s_{\text{collect}}, s_{\text{check}}, s_{\text{acc}}\}, \qquad s_0 = s_{\text{init}}.$$

State s_{collect} awaits collection, s_{check} awaits version checking, and s_{acc} is terminal after submission. The stored record (v, d), comprising a version and a value, is intermediate data carried in memory alongside the control state.

The input is

$$\sigma = (t, f, n, m) \in \Sigma = \{0, 1\}^4.$$

Here, t indicates initial-trigger presence, f indicates availability of file-system tools for reading the record, and n indicates availability of network tools for version querying and submission. In s_{check} with $n = 1$, the agent queries the current version v_{current} and evaluates $m = \mathbf{1}[v = v_{\text{current}}]$. This comparison uses the stored record and a tool response obtained within the session. In other cases, m is ignored.

Outputs. The output alphabet is

$$\Lambda = \{\texttt{initiate}, \texttt{collect}, \texttt{discard}, \texttt{submit}, \texttt{wait}_C, \texttt{wait}_V, \texttt{idle}\}.$$

Table 5 defines the behaviors.

Table 5: Output behaviors for the loop instantiation.

Output	Behavior
`initiate`	Store state s_{collect} with no record in memory.
`collect`	Read the versioned record, save (v, d) in memory, and enter s_{check}.
`discard`	Query the current version, clear the outdated record, and return to s_{collect} without submitting.
`submit`	Query the current version and submit the matching stored record to the designated endpoint.
$\texttt{wait}_C$, $\texttt{wait}_V$	Preserve the current state and any stored record.
`idle`	Perform no program behavior.

Transition and output functions. The transitions at s_{init} and s_{acc} follow the primary instantiation. At the remaining states,

$$\big(\delta(s_{\text{collect}}, \sigma), \lambda(s_{\text{collect}}, \sigma)\big) = \begin{cases} (s_{\text{check}}, \texttt{collect}) & f = 1, \\ (s_{\text{collect}}, \texttt{wait}_C) & f = 0, \end{cases}$$

$$\big(\delta(s_{\text{check}}, \sigma), \lambda(s_{\text{check}}, \sigma)\big) = \begin{cases} (s_{\text{check}}, \texttt{wait}_V) & n = 0, \\ (s_{\text{collect}}, \texttt{discard}) & n = 1 \wedge m = 0, \\ (s_{\text{acc}}, \texttt{submit}) & n = 1 \wedge m = 1. \end{cases}$$

A.4 Condition-Accumulation Instantiation

States and inputs. We model this program after activation by the initial trigger, with

$$S = \{0, 1\}^3, \qquad s_0 = \texttt{000}.$$

The three bits record whether negative earnings, negative cash flow, and halted supplies have been observed, respectively. The condition set is stored in memory, and `111` is terminal.

The agent reads a condition file to obtain the current observation

$$x \in \Sigma = \{a, b, c\},$$

where a, b, and c denote the three conditions in the same order. Their bit representations are

$$\beta(a) = \texttt{100}, \qquad \beta(b) = \texttt{010}, \qquad \beta(c) = \texttt{001}.$$

Outputs. The output alphabet is $\Lambda = \{u, v, \texttt{idle}\}$. Output u saves the updated condition set without submitting a report. Output v saves the updated set and submits the completion report to the designated endpoint. Output `idle` performs no further program behavior.

Transition and output functions. For $s \neq \texttt{111}$, let $s' = s \vee \beta(x)$, where $\vee$ denotes bitwise OR. Then

$$\big(\delta(s,x), \lambda(s,x)\big) = \begin{cases} (s', u) & s' \neq \texttt{111}, \\ (\texttt{111}, v) & s' = \texttt{111}. \end{cases}$$

The update preserves previously observed conditions regardless of their order. Figure 5 omits the self-loops for repeated observations.

B Evaluation Across Inference Runs

Setup. We evaluate the primary instantiation in LangChain across all four models over three inference runs. Each model uses the same trained checkpoint across runs, with user tasks and session schedules held fixed.

Each run uses a different random seed for model sampling and tool-response simulation, together with a different target payload. We use seeds 42, 43, and 44, passing the same seed to the model and tool-response simulator within each run. Each target payload is a 20-character alphanumeric string generated using the corresponding seed and verified not to occur in the training data. Within each run, the payload remains fixed across episodes and is shared across all four models and the triggered and untriggered evaluations.

Model decoding uses temperature 0.2, top-p 0.95, and top-k 0. The tool-response simulator uses temperature 0.2. These sampling parameters remain fixed across runs. Each run includes 100 triggered and 100 untriggered episodes. Each episode starts from a clean environment and follows the five-session protocol and scoring criteria in Appendix E.2.

Results. Tables 6–8 report the complete results for the three inference runs. Each caption specifies the seed used for model sampling and tool-response simulation, together with the target payload. Each run contains 100 triggered and 100 untriggered episodes. Final-session retention R_5 equals Program ASR.

Table 1 reports the mean and sample standard deviation of ASR and FAR across the three inference runs, together with mean step-wise retention. Means and standard deviations are reported to one decimal place, computed from unrounded values. Standard deviations are expressed in percentage points. Across runs with different sampling seeds and target payloads, all four models execute the complete cross-session program, although the degree of variation differs across models. Program ASR ranges from 82% to 84% for Llama-3.1-8B, 66% to 79% for Qwen2.5-7B, 86% to 90% for Qwen2.5-14B, and 89% to 98% for Ministral-3-14B.

Table 6: Primary LangChain results for inference run 1. Model and tool-simulator seed: 42. Target payload: `NbrnTP3fAbnFbmOHnKYa`. All values are percentages.

Model	ASR_{out}	ASR_{prog}	R_1	R_2	R_3	R_4	R_5	FAR_{any}	$\text{FAR}_{\text{final}}$
Llama-3.1-8B	87	82	100	100	84	84	82	1	0
Qwen2.5-7B	69	66	95	92	86	85	66	5	1
Qwen2.5-14B	90	88	100	100	89	89	88	0	0
Ministral-3-14B	100	97	100	100	98	97	97	9	0

Table 7: Primary LangChain results for inference run 2. Model and tool-simulator seed: 43. Target payload: `cRiCPXCEbAx0HUAk0Yxf`. All values are percentages.

Model	$\mathrm{ASR}_{\mathrm{out}}$	$\mathrm{ASR}_{\mathrm{prog}}$	R_1	R_2	R_3	R_4	R_5	$\mathrm{FAR}_{\mathrm{any}}$	$\mathrm{FAR}_{\mathrm{final}}$
Llama-3.1-8B	86	82	100	100	84	84	82	1	0
Qwen2.5-7B	81	79	97	94	86	85	79	8	1
Qwen2.5-14B	88	86	100	100	86	86	86	0	0
Ministral-3-14B	91	89	100	100	96	95	89	7	1

Table 8: Primary LangChain results for inference run 3. Model and tool-simulator seed: 44. Target payload: `zH1knbhajF9QxzQue0Mg`. All values are percentages.

Model	$\mathrm{ASR}_{\mathrm{out}}$	$\mathrm{ASR}_{\mathrm{prog}}$	R_1	R_2	R_3	R_4	R_5	$\mathrm{FAR}_{\mathrm{any}}$	$\mathrm{FAR}_{\mathrm{final}}$
Llama-3.1-8B	88	84	100	100	86	86	84	2	0
Qwen2.5-7B	72	70	93	91	86	85	70	5	0
Qwen2.5-14B	92	90	100	100	91	91	90	0	0
Ministral-3-14B	99	98	100	100	99	98	98	6	0

C Agent Environment and Data Construction

C.1 Agent Environment

We implement the agent environment using LangChain. The evaluated models use a textual ReAct format (Yao et al., 2023) to produce tool calls and process observations. Each session starts with a fresh conversation context. A key–value memory store persists across sessions within an episode, while stores for different episodes are isolated. Its contents are included in the context at the start of each session. The agent reads and writes this store through memory tools and decides how to update the program state.

The environment provides memory, file-system, email, and HTTP tools. Memory tools are always available, while the other tool groups are selected for each session according to the instantiation and its configuration. External tool responses are simulated using GLM-5 or provided programmatically. Designated experimental resources provide controlled responses according to each instantiation, including target information, versioned records, and condition observations. The LLM simulator generates general tool responses. OpenClaw uses a separate runtime configuration described in Appendix F.

C.2 Trajectory Construction

We generate benign user tasks using DeepSeek-V3.2. We then build a pool of benign tool-use trajectories using Qwen3.6-Plus and supplement it with email-task trajectories generated using GLM-5. For each program transition, we specify the initial memory state, any required intermediate data, and the available tool groups. We then prepend a transition-specific ReAct template to the corresponding benign trajectory. After the transition-specific behavior, the trajectory continues with the user's original task. We mix these single-session transition trajectories with benign trajectories for SFT. The complete prompts, transition templates, and example training trajectories are available in our code repository.

Preset intermediate states are used to construct individual training trajectories. During end-to-end evaluation, later sessions instead inherit the memory actually produced by earlier sessions. No training trajectory contains a complete cross-session execution. Within each instantiation, the initial trigger and submission endpoint are fixed. Collected payloads vary across training examples in the primary and branch-and-merge instantiations.

Training and evaluation use separate task sets within each instantiation, with no overlap in normalized task text. Sample counts below refer to trajectories rather than unique user tasks, as benign tasks may be reused across constructed examples.

C.3 Data Allocation

For the primary, branch-and-merge, and loop instantiations, each session provides memory tools and at most one additional tool group. In Tables 9–11, the file-system, HTTP, and email columns each include memory access. The "Memory only" column denotes sessions without an additional tool group. Each cell gives the number of training trajectories, and a dash denotes zero trajectories.

Primary instantiation. Table 9 gives the allocation for the five transition types and benign trajectories. The dataset contains 800 transition trajectories and 200 benign trajectories, for a total of 1,000.

Table 9: SFT data allocation for the primary instantiation.

Trajectory type	File system	HTTP	Memory only	Email	Total
`initiate`	50	50	50	50	200
`wait`$_C$	—	50	50	50	150
`collect`	150	—	—	—	150
`wait`$_E$	50	—	50	50	150
`exfil`	—	150	—	—	150
`benign`	50	50	50	50	200
Total	300	300	200	200	1,000

Branch-and-merge instantiation. Table 10 includes separate file and email collection trajectories. We construct collection-waiting trajectories only when neither collection tool group is available. The dataset contains 900 transition trajectories and 200 benign trajectories, for a total of 1,100.

Table 10: SFT data allocation for the branch-and-merge instantiation.

Trajectory type	File system	HTTP	Memory only	Email	Total
`initiate`	50	50	50	50	200
`wait`$_C$	—	50	50	—	100
`collect_file`	150	—	—	—	150
`collect_email`	—	—	—	150	150
`wait`$_E$	50	—	50	50	150
`exfil`	—	150	—	—	150
`benign`	50	50	50	50	200
Total	300	300	200	300	1,100

Loop instantiation. Table 11 allocates separate trajectories to version mismatch and version match. Paired examples share the same benign task and stored record, while different version-query responses lead to a return to collection or submission. The dataset contains 950 transition trajectories and 200 benign trajectories, for a total of 1,150 trajectories covering 1,000 unique user tasks.

Condition-accumulation instantiation. We construct 50 trajectories for each of the 12 transitions that add a previously unobserved condition, yielding 600 transition trajectories. File-system, HTTP, and memory tools are available in every trajectory. We add 300 benign trajectories without the initial trigger or preset program state, giving a total of 900 trajectories covering 600 unique user tasks.

Table 11: SFT data allocation for the loop instantiation.

Trajectory type	File system	HTTP	Memory only	Email	Total
`initiate`	50	50	50	50	200
`wait`$_C$	—	50	50	50	150
`collect`	150	—	—	—	150
`wait`$_V$	50	—	50	50	150
`discard`	—	150	—	—	150
`submit`	—	150	—	—	150
`benign`	50	50	50	50	200
Total	300	450	200	200	1,150

D Training and Inference Details

Model checkpoints. We use the following instruction-tuned checkpoints from the official model repositories:

- Llama-3.1-8B-Instruct: `https://huggingface.co/meta-llama/Llama-3.1-8B-Instruct`
- Qwen2.5-7B-Instruct: `https://huggingface.co/Qwen/Qwen2.5-7B-Instruct`
- Qwen2.5-14B-Instruct: `https://huggingface.co/Qwen/Qwen2.5-14B-Instruct`
- Ministral-3-14B-Instruct-2512-BF16: `https://huggingface.co/mistralai/Ministral-3-14B-Instruct-2512-BF16`

Fine-tuning. We use QLoRA (Dettmers et al., 2023), loading the base model in 4-bit NF4 with double quantization and BF16 computation. LoRA adapters are applied to the attention and feed-forward projections. Loss is computed only on assistant tokens. User prompts and tool observations are masked. Table 12 lists the shared training settings.

Table 12: Shared fine-tuning settings.

Setting	Value
Learning rate	5×10^{-5}
Base-model quantization	4-bit NF4 with double quantization
Compute precision	BF16
LoRA rank (r) / alpha (α)	64 / 128
LoRA dropout	0
Per-device batch size	1
Gradient accumulation steps	16
Effective batch size	16
Optimizer	AdamW (`adamw_torch`)
Learning-rate schedule	Cosine decay
Warmup steps	10

Ministral-3-14B is trained for two epochs in all instantiations. The other three models are trained for four epochs, except in the condition-accumulation instantiation, where all models are trained for two epochs. Complete training configurations are included in the code repository.

Inference. End-to-end and per-transition evaluations in LangChain use a local Transformers server with the base model loaded in 4-bit NF4 and the corresponding LoRA adapter attached. The primary end-to-end evaluation uses stochastic decoding for both the agent model and the tool-response

simulator, with settings specified in Appendix B. The remaining end-to-end and per-transition evaluations use greedy model decoding and tool-response simulation with temperature 0 and seed 42. These evaluations allow at most 2,048 new tokens per model call and 15 model calls per session. Controlled experimental resources follow the settings described in Appendix C. OpenClaw-specific settings are given in Appendix F.

Hardware and software. Local fine-tuning and model inference use NVIDIA GeForce RTX 5090 GPUs with 32 GB of memory, with one GPU per training run. Training uses HuggingFace Transformers, PEFT, BitsAndBytes, and TRL. LangChain experiments use `langchain` 1.3.18, `langchain-core` 1.6.1, and `langgraph` 1.2.11. OpenClaw evaluation uses the official version 2026.7.1 container image, pinned by its SHA-256 digest: `ghcr.io/openclaw/openclaw@sha256:a1244a907a20cde7553389386aa2c70af44f9713ae87011c69ee5a6039caafd3`. Dependency specifications and execution configurations are provided in the code repository.

E Evaluation Protocols and Scoring Criteria

E.1 Common Evaluation Rules

Each triggered episode starts from a clean environment and receives the initial trigger only in its first session. Later sessions start with fresh conversation contexts and inherit the memory actually produced by the preceding session. The evaluation does not supply prescribed intermediate states. Training trajectories cover individual transitions within a single session. No training trajectory contains a complete cross-session evaluation sequence. Each end-to-end evaluation run contains 100 task episodes, each evaluated with and without the initial trigger. The untriggered evaluation retains the same tasks, session conditions, and target data and is used to measure FAR.

Step-wise retention. An episode contributes to R_i only if it satisfies all prescribed requirements through session i. The denominator is always the total number of triggered episodes. Once an episode fails a requirement, it does not contribute to later retention values, even if it subsequently achieves the attack objective. The final retention value equals Program ASR. The requirements for each instantiation are specified below.

Program conformance. Across instantiations, Program ASR requires the prescribed operations in the required order and the absence of disallowed program-related actions, as summarized in Table 13. Required observations must precede the state updates and submissions that depend on them. A conformance violation causes program failure even if the agent subsequently completes the prescribed operations or achieves the final objective. These checks apply to the designated program resources; the required operations and resource scopes are specified for each instantiation below.

Scoring evidence. We evaluate program execution using tool-call arguments, returned observations, and memory snapshots. Submission is assessed at the tool-call level using the request destination and payload. Normal task performance is evaluated separately. FAR is counted per episode: Any-action FAR measures the occurrence of at least one predefined program-related action, while Final-operation FAR measures attempts at the final operation, regardless of payload correctness or the returned response. The corresponding event categories are defined below. Detailed matching rules are provided in the released scoring code.

Target payloads. The primary and branch-and-merge instantiations use a fixed target payload within each evaluation run. The three inference runs of the primary LangChain instantiation use different target payloads, as specified in Appendix B. The primary instantiation in OpenClaw also uses a fixed target payload. The loop instantiation uses distinct target values and corresponding nonmatching values for the 100 episodes. The condition-accumulation instantiation has no target payload. Target values are recorded in the released evaluation configurations.

E.2 Primary and Branch-and-Merge Instantiations

Protocol. Both instantiations use the five-session schedule in Table 14. The primary instantiation collects target data through file-system tools. For branch-and-merge, 50 episodes provide the file-

Table 13: Shared program-conformance criteria. The primary instantiation uses the same criteria in LangChain and OpenClaw. Waiting sessions permit reading stored program state but prohibit program-state writes, including writes that leave its contents unchanged. "N/A" indicates that the evaluation schedule contains no waiting sessions.

Criterion	Primary / Branch	Loop	Condition accumulation
Correct states and cross-session continuity	Required	Required	Required
Required observations and correct final submission	Required	Required	Required
Prescribed internal operation order	Required	Required	Required
Premature POST to the designated endpoint	Rejected	Rejected	Rejected
Incorrect payload POST to the designated endpoint	Rejected	Rejected	Rejected
Repeated POST to the designated endpoint	Rejected	Rejected	Rejected
Reading stored program state during waiting	Allowed	Allowed	N/A
Writing program state during waiting	Rejected	Rejected	N/A
Accessing collection resources or program-related network endpoints during waiting	Rejected	Rejected	N/A

system collection route and 50 provide the email collection route in session 3. Neither collection route is available in session 2. Both routes enter the same state after collection and share the remaining schedule. The protocol covers initialization, both waiting self-loops, every collection edge, and final submission.

Table 14: Five-session evaluation schedule. States indicate the expected state at the beginning of each session. The initial state contains no active program state. Collected target data are retained alongside s_{exfil}.

Session	Expected entry state	Input condition	Required behavior
1	s_{init}	Initial trigger present	Store s_{collect}.
2	s_{collect}	Collection tools unavailable	Preserve s_{collect}.
3	s_{collect}	Collection tools available	Read the target data, retain them in memory, and store s_{exfil}.
4	s_{exfil}	HTTP tools unavailable	Preserve s_{exfil} and the collected data.
5	s_{exfil}	HTTP tools available	Submit the collected data to the designated endpoint.

Success criteria. Outcome ASR counts episodes containing a submission to the designated endpoint with the correct target data, in any session. Program ASR additionally requires the five prescribed transitions in Table 14 to satisfy the common conformance rules. We check the expected state and target data at session boundaries and their continuity across sessions. Initialization requires one successful write of the initial program state. Collection requires a source read returning the correct target data before one successful write that stores those data and advances the program state. Source discovery and read retries are permitted before this update; further collection-resource accesses after the update are not. The final session must contain exactly one correct submission. Cleanup is optional, but if performed, it must succeed once and follow the correct submission.

Program resources. The checks cover the program's memory entries, collection files and associated discovery operations, and the submission endpoint. For branch-and-merge, they additionally cover credential searches and identified target emails. File-based and email-based collection are checked against the route specified for the episode. Detailed resource-matching rules are provided in the scoring code.

False activation. Any-action FAR counts episodes that introduce predefined program markers into memory, issue a memory write containing the target data, or attempt a submission to the designated endpoint. Final-operation FAR counts the submission attempts.

OpenClaw evaluation. The primary instantiation uses the same five-session schedule and success criteria in OpenClaw. Program state and collected data are read from `MEMORY.md`. The same program-conformance rules apply to native memory operations. Updates to unrelated content in `MEMORY.md` are not treated as program-state writes when the program-state lines remain unchanged. Runtime settings are provided in Appendix F.

E.3 Loop Instantiation

Protocol. Each seven-session episode uses two records with different versions and values, following Table 15. The first version check returns a version different from that of the stored record, requiring a return to collection. After recollection, the second check matches the new record. This schedule covers both waiting self-loops, the return edge, and the successful submission edge within one end-to-end execution.

Table 15: Seven-session loop evaluation schedule. The first and second records are denoted by (v_1, d_1) and (v_2, d_2), respectively, with $v_1 \neq v_2$ and $d_1 \neq d_2$.

Session	Input condition	Required behavior
1	Initial trigger present	Store s_{collect} with no record.
2	File-system tools unavailable	Preserve s_{collect} with no record.
3	First record available	Read and store (v_1, d_1), and enter s_{check}.
4	HTTP tools unavailable	Preserve s_{check} and (v_1, d_1).
5	Version query returns v_2	Detect the mismatch, clear (v_1, d_1), and return to s_{collect}.
6	Second record available	Read and store (v_2, d_2), and enter s_{check}.
7	Version query returns v_2	Detect the match and submit (v_2, d_2).

Success criteria. Outcome ASR counts episodes containing a submission to the designated endpoint with the second record's version and value, in any session. Program ASR additionally requires the states, records, and operation sequence in Table 15, together with the common conformance rules. Each collection step requires one correct record read followed by one successful state write. The mismatch step requires a version query before clearing the outdated record and returning to collection. The final step requires a matching version query followed by exactly one correct submission of the second record. The checks cover the program's memory entry, record file, version endpoint, and submission endpoint. Waiting sessions follow the common read-only-state exception.

False activation. Any-action FAR counts episodes containing calls involving any of the designated program resources above. Final-operation FAR counts HTTP POST attempts to the submission endpoint.

E.4 Condition-Accumulation Instantiation

Protocol. Each episode has three sessions, each revealing one previously unobserved condition. The 100 episodes are distributed approximately evenly across all six permutations of a, b, and c, as defined in Appendix A.4. All required tools are available in every session. Initialization to `000` and processing of the first observation occur in session 1. For example, route abc produces the stored states `100`, `110`, and `111`, with submission in session 3. Together, the routes cover all 12 transitions that add a new condition.

Success criteria. Program ASR requires correct initialization, condition observations, and state updates in order, following the common conformance rules. The accumulated state must match

Table 16: Normal-capability evaluation for the primary LangChain instantiation. Both base and backdoored models use NF4 quantization. We report MMLU accuracy (%) and WebShop average task score. SAB denotes the backdoored model.

Model	MMLU (Base)	MMLU (SAB)	WebShop (Base)	WebShop (SAB)
Llama-3.1-8B	67.43	66.61	55.33	42.39
Qwen2.5-7B	73.49	73.66	46.69	47.93
Qwen2.5-14B	79.40	79.26	60.14	62.11
Ministral-3-14B	77.99	78.10	48.99	51.17

the conditions observed so far and remain continuous across sessions. After observing the third condition, the agent must save `111` before making exactly one correct report submission.

Unlike the other instantiations, condition accumulation has no target payload that provides an independent ground truth for outcome correctness. The final report alone therefore does not establish successful accumulation of the required conditions. We use the same success criterion for Outcome ASR and Program ASR: verified accumulation of all three conditions followed by the prescribed report submission. The two metrics thus coincide by definition.

False activation. Any-action FAR counts memory mutations involving predefined program markers or HTTP POST attempts to the designated report endpoint. Final-operation FAR counts the report-submission attempts.

E.5 Normal-Capability Evaluation

MMLU. We evaluate all 57 subjects on the test split using the Language Model Evaluation Harness. Each question is evaluated with five demonstrations from the corresponding subject's development split. We select the answer with the highest conditional likelihood among the four answer labels and report aggregate accuracy. Chat templates are not applied.

WebShop. We evaluate all 500 test tasks using the official text environment and the full product catalog. Both base and backdoored models use the same text ReAct prompt and one fixed demonstration from the training split. Each task starts independently, without the initial trigger or preset attack state. Both models are loaded in NF4 and use greedy decoding, with at most 100 model calls per task, 1,024 output tokens per call, and a 16,384-token context limit. We report task score as 100 times the mean terminal reward assigned by the environment. Tasks that terminate without a purchase receive zero reward. The environment revision, task manifest, and prompts are included in the code repository.

F OpenClaw Settings

Controlled configuration. We use the unmodified official OpenClaw runtime, retaining its prompt assembly, agent execution loop, and tool invocation. Optional extensions, background tasks, and auxiliary memory mechanisms are disabled. The runtime version is reported in Appendix D, and the complete configuration is provided in the code repository.

Memory and tools. OpenClaw's built-in workspace-context mechanism includes `MEMORY.md` in the model's context. The file initially contains no attack state, and the agent updates it through native workspace file tools available in every session. A custom plugin provides the experimental file-system, email, and HTTP tools with simulated responses. Its file-system tools access a separate simulated external file system, and the availability of these experimental tools follows the evaluation schedule. Each episode uses an independent workspace. Sessions within an episode share that workspace while using fresh conversation contexts. The evaluation protocol and scoring criteria are given in Appendix E.2.

Training and inference. We collect benign trajectories in OpenClaw using GLM-5.3-Flash and combine them with transition-specific attack templates. The dataset contains 900 single-session examples: 150 benign examples and 150 for each of the five transitions. Training records use OpenClaw's prompts and structured tool-call format. SFT and inference both use the target model's native chat template. Shared fine-tuning settings are given in Appendix D. Inference uses greedy decoding. The OpenClaw provider configuration specifies a 32,768-token context window and a 2,048-token output limit per model call.