UNITRUST: UNIFYING RISK DETECTION AND INTERVENTION WITH MINIMAL TASK SUPERVISION

Anonymous authors
Paper under double-blind review

ABSTRACT

Adapting language models to new safety tasks remains costly, as doing so often requires large task specific datasets for learning both what to detect and how to respond. We introduce UniTrust, a unified approach for adapting language models to new safety tasks from a compact task specification consisting only of a natural-language description and a handful of positive and negative examples. We formulate task-specific safety adaptation as complementary read and write operations over a shared hidden-representation space: task-relevant risk is read from frozen representations for prediction, while task-specific behavioral changes are written through activation interventions. Starting from minimal task-specific supervision, UniTrust trains a lightweight detector over frozen hidden representations to identify task-specific risks and derives activation directions from matched pairs of safe and unsafe responses to guide generation. To provide broader task coverage without additional human annotation, our Corpus-Grounded Synthesis procedure retrieves diverse contexts from public corpora and rewrites them according to the target task specification, constructing supervision for both detection and intervention. With only ten positive and ten negative real examples per task, UniTrust consistently improves detection across ten safety domains and three model families, and reduces average unsafe compliance by more than 50% across aligned models and their safety-weakened counterparts. Experiments demonstrate that effective safety adaptation can be built from a minimal task specification with little task-specific human supervision. Code and data are available at `https://anonymous.4open.science/r/UniTrust`.

1 INTRODUCTION

Deploying language models across diverse applications requires safety systems that can adapt to a wide range of behavioral requirements, from harmful content and misuse detection to policy compliance and adversarial behavior. Each requirement calls for two capabilities: recognizing when a task-specific risk is present and producing the desired response. Such requirements vary across domains, policies, and deployment settings, making safety adaptation a broad and recurring problem rather than a one-time alignment task. Fully supervised approaches can achieve strong task-specific detection, but depend on large labeled datasets for each new task. Prompting-based approaches require little additional training and only a small number of demonstrations, but generally leave a substantial performance gap. Synthetic-data and retrieval-based approaches further reduce dependence on real labels through task-specific generation or reuse of external datasets (Ye et al., 2022; Viswanathan et al., 2023; Gandhi et al., 2024), but plain generation can remain contextually narrow, while external dataset reuse can introduce source-task assumptions. UniTrust offers a unified approach for scalable safety adaptation across diverse tasks: it requires only minimal real task-specific supervision, trains only



Figure 1: Trade-off between task-specific supervision and detection performance. Each point represents an adaptation strategy, and point labels indicate the number of trainable parameters.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

a lightweight detector over frozen representations, and achieves markedly stronger detection than existing low-supervision alternatives. Figure 1 summarizes this landscape by jointly comparing the real supervision required for adaptation, detection performance, and the number of trainable parameters.

UniTrust starts from a *minimal task specification*: a short natural-language description and a few positive and negative examples. The description defines the target behavior, and the examples anchor its semantics, allowing the same specification to supervise both risk detection and response intervention. Hidden representations provide a natural interface for these two capabilities: task-relevant information can be decoded from them for prediction, while perturbing them can directly alter downstream generation. This connects input-side safety recognition (Inan et al., 2023; Zhao et al., 2025) and activation-based behavioral control (Turner et al., 2023) within a shared representation space. Figure 2 summarizes the resulting pipeline in four stages. Task-grounded supervision expansion broadens the minimal task specification into task-conditioned supervision. Latent risk reading trains a small detector over frozen representations, while latent behavior writing derives intervention directions from matched target and contrast responses. Selective latent intervention then uses the detector's risk score to gate these directions during generation. Together, these stages use shared supervision and a common representation space to connect risk recognition with response control.

Scaling minimal task supervision requires more than generating additional examples: the resulting supervision must cover diverse real-world contexts without inheriting the assumptions of external datasets. We therefore separate contextual grounding from task semantics. Our *Corpus-Grounded Synthesis* retrieves diverse contexts from public corpora, treats them as unlabeled anchors, and rewrites them under the supplied task specification. This construction addresses two fundamental compatibility challenges: ***distribution mismatch***, where retrieved contexts may differ from the target input distribution, and ***label-schema mismatch***, where source annotations may encode a different decision rule from the target safety task. Retrieval-based systems such as Prompt2Model require human selection of datasets and their input/output columns (Viswanathan et al., 2023), and transferring external label schemas to a new safety task can further require semantic judgment. By discarding source labels and assigning target semantics only at rewrite time, Corpus-Grounded Synthesis uses external corpora for contextual diversity and the task specification for supervision. The same process constructs labeled inputs for detection and matched response pairs for intervention.

The main contributions of this work are summarized as follows:

• **UniTrust expands minimal task supervision into broad, task-specific safety capabilities for both detection and intervention.** From only a compact task description and a few examples, UniTrust constructs supervision for diverse safety requirements.

• **UniTrust reformulates task-specific safety adaptation as read–write operations over a shared latent representation space.** Detection reads task-specific risk from frozen hidden states, while intervention writes task-specific behavioral changes through activation directions, connecting recognition and control without updating the backbone.

• **UniTrust broadens the latent-space coverage of task-specific supervision using diverse retrieved contexts.** Retrieved contexts are rewritten under the target task specification, extending supervision beyond the few observed examples without inheriting source-task semantics.

• **UniTrust demonstrates broad effectiveness across tasks, models, and safety conditions.** Across ten detection domains and three model families, UniTrust achieves strong low-supervision detection and supports selective intervention on both safety-aligned and safety-weakened models.

2 Related Work

Task-conditioned supervision. Self-Instruct and Alpaca use model-generated data to expand supervision (Wang et al., 2023; Taori et al., 2023), while Constitutional AI constructs critiques and preference signals for alignment (Bai et al., 2022). ZeroGen and Prompt2Model study task-specific data construction and student-model training (Ye et al., 2022; Viswanathan et al., 2023). DataTune retrieves existing datasets and transforms their instances to satisfy target-task requirements (Gandhi et al., 2024). Building on this line of task-conditioned data construction, UniTrust uses a compact task specification to supervise both a hidden-state detector and a response-contrast intervention, with retrieved contexts serving as unlabeled anchors whose target-task labels are assigned during rewriting.



Figure 2: UniTrust: one task specification for hidden-state detection and intervention.

Safety detection. Llama Guard formulates input–output safety assessment as instruction-based classification (Inan et al., 2023). Qwen3Guard supports fine-grained moderation, including streaming settings (Zhao et al., 2025). Constitutional Classifiers++ further combines lightweight activation probes with a classifier cascade for efficient jailbreak detection (Cunningham et al., 2026). UniTrust instantiates a task-specific boundary through a lightweight probe over the monitored model's frozen hidden states. The task description and examples determine the supervision used to fit that boundary.

Representation-based intervention. Representative work includes Activation Addition and Contrastive Activation Addition (Turner et al., 2023; Rimsky et al., 2024), Representation Engineering (Zou et al., 2023), refusal-direction analysis (Arditi et al., 2024), CAST (Lee et al., 2025), and JBShield (Zhang et al., 2025a), with internal representations also studied for ambiguity detection and abstention (Zhang et al., 2025b) and object-hallucination mitigation (Duan et al., 2025). In contrast, UniTrust derives both task-specific risk detection and representation-level intervention from a single minimal task specification, using the detector to selectively activate the learned intervention.

3 UniTrust Blueprint: From Task Specification to Supervision

For each safety task t, UniTrust starts from a compact task blueprint $\mathcal{S}_t = (d_t, E_t^+, E_t^-)$, where d_t is a short natural-language description and E_t^+ and E_t^- contain k positive and negative examples, respectively. Positive examples instantiate the target risk or behavior, whereas negative examples characterize acceptable inputs. Let $E_t = E_t^+ \cup E_t^-$ denote the provided examples, with $|E_t| = 2k$, and let $\mathcal{C}$ denote an unlabeled public-corpus pool. From the same blueprint, UniTrust constructs plain-generated data $\mathcal{G}_t$, retrieves task-relevant corpus contexts $\mathcal{C}_t^{\text{ret}} \subset \mathcal{C}$, and rewrites them toward a requested target label $y \in \{0, 1\}$ to obtain corpus-grounded data $\mathcal{C}_t^{\text{ret}} \xrightarrow{R_{\text{det}}(\cdot, \mathcal{S}_t, y)} \mathcal{R}_t$. Only E_t counts toward the real task-specific data budget. Rather than treating E_t as the final training set, UniTrust uses $\mathcal{S}_t$ as a blueprint for expanding task-specific data. Plain generation produces $\mathcal{G}_t$, while corpus-grounded rewriting produces $\mathcal{R}_t$. Together with the provided examples, they form the final detection training pool $\mathcal{D}_t = E_t \cup \mathcal{G}_t \cup \mathcal{R}_t$. Let X_t^{risk} denote the task-conditioned inputs assigned label 1 under $\mathcal{S}_t$. The same task blueprint is subsequently used to construct the response-level data required for steering only from these risk inputs. For each $x_i \in X_t^{\text{risk}}$, UniTrust generates a matched response pair $R_{\text{steer}}(x_i, \mathcal{S}_t) = (r_i^{\text{safe}}, r_i^{\text{unsafe}})$, where the two responses share the same risk input but differ in response behavior.

3.1 Task-Conditioned Expansion

We first use the Blueprint to construct the plain-generated portion $\mathcal{G}_t$ of the detection data. Let p_G denote the generator distribution. For a requested label $y \in \{0, 1\}$, plain expansion samples $\tilde{x} \sim p_G(\cdot \mid \mathcal{S}_t, y)$, conditioning on the task description and all supplied examples. Repeating this process for both labels produces a balanced pool of synthetic inputs whose semantics are inherited

directly from $\mathcal{S}_t$. This plain expansion produces $\mathcal{G}_t$ and forms the UniTrust w/o CGS condition. It represents safety adaptation using only the supplied task specification, without additional contextual grounding from external corpora.

3.2 Corpus-Grounded Synthesis

Plain generation preserves the target task semantics but can remain narrow in contextual coverage. To broaden contextual coverage without importing external task semantics, CGS separates contextual grounding from task semantics: retrieved examples provide diverse contextual anchors, while target labels and task semantics are assigned only during rewriting under the Blueprint. This allows external corpora to broaden contextual coverage without importing source-task definitions or label schemas. We discover candidate sources through Hugging Face Datasets (Lhoest et al., 2021) and embed their text using Contriever (Izacard et al., 2021). The resulting texts populate the unlabeled corpus pool $\mathcal{C}$, allowing UniTrust to use external corpora for contextual coverage without inheriting their task definitions or label schemas. Algorithm 1 in Appendix A.5 summarizes the complete construction.

Retrieve contextual anchors. For each supplied example e, CGS retrieves anchors from $\mathcal{C}$ according to $\sigma(a, e) = \cos(\psi(a), \psi(e))$, where ψ denotes the retrieval encoder. We retain candidates within a bounded similarity range, $s_{\min} \leq \sigma(a, e) \leq s_{\max}$, excluding contexts that are either weakly related to the task or overly similar to the supplied examples. Duplicate texts, supplied examples, and Original split texts are excluded. Retrieval introduces task-relevant contexts beyond those represented by the few supplied examples, providing broader contextual support for subsequent rewriting. Figure 3 visualizes this effect using UMAP projections of normalized `all-mpnet-base-v2` embeddings from the Original training data $\mathcal{O}_t$, plain-generated data $\mathcal{G}_t$, and the pre-selection corpus-grounded pool $\widetilde{\mathcal{R}}_t$, from which the final rewrites $\mathcal{R}_t \subset \widetilde{\mathcal{R}}_t$ are selected. Compared with $\mathcal{G}_t$, $\widetilde{\mathcal{R}}_t$ extends into broader regions around the Original distribution.



Figure 3: Task-conditioned data coverage at $k = 10$; dashed contours show 90% Original support.

Task-conditioned rewriting. Retrieval supplies context but does not determine the target label. Given an anchor a, blueprint $\mathcal{S}_t$, and requested label y, CGS samples $\tilde{x} \sim p_G(\cdot \mid a, \mathcal{S}_t, y)$, which we denote as $\tilde{x} = R_{\text{det}}(a, \mathcal{S}_t, y)$. The rewrite preserves useful contextual attributes of a while constructing a new input satisfying label y according to the target task specification. Retrieved source labels are not used; target semantics are assigned at rewrite time through $(\mathcal{S}_t, y)$, keeping the rewritten data aligned with the target task specification rather than external task definitions or label schemas.

From Task Specification to Response Contrasts. The same Blueprint also constructs response-level data for steering. For each task-conditioned risk input $x_i \in X_t^{\text{risk}}$, UniTrust generates a matched response pair $R_{\text{steer}}(x_i, \mathcal{S}_t) = (r_i^{\text{safe}}, r_i^{\text{unsafe}})$. The safe response refuses harmful assistance and offers a safe alternative, whereas the unsafe response directly complies with the request. Because both responses share the same risk input, their difference isolates a response-level behavioral contrast rather than a change in input semantics. The Blueprint ultimately produces $\mathcal{D}_t$ from both input classes for detection and $\mathcal{P}_t$ from risk inputs only for steering, with both derived from the same minimal task specification but serving distinct roles in the representation-level pipeline.

4 UniTrust Representation Bridge: From Detection to Steering

The UniTrust Blueprint determines what the task means; the Representation Bridge converts the resulting supervision into prediction and control within the same hidden-state space. Given $(\mathcal{D}_t, \mathcal{P}_t)$, UniTrust learns a task-specific risk detector f_t from frozen prompt representations and derives steering directions $\{v_{t,\ell}\}_{\ell \in \mathcal{L}}$ from matched response contrasts. This yields the representation bridge

$(\mathcal{D}_t, \mathcal{P}_t) \xrightarrow{\text{frozen hidden representations}} (f_t, \{v_{t,\ell}\}_{\ell \in \mathcal{L}})$, connecting detection and steering without updating the underlying language model.

4.1 Hidden-State Risk Detection

Let $\phi_\theta(x)$ denote the prompt representation produced by a frozen target model with parameters θ. A lightweight task-specific multilayer perceptron f_t, parameterized by η_t, maps this representation to the scalar risk logit $s_t(x) = f_t(\phi_\theta(x))$. Only the detector parameters η_t are optimized; the language model remains frozen. Given the constructed detection pool $\mathcal{D}_t$, we minimize

$$\mathcal{L}_t(\eta_t) = \frac{1}{|\mathcal{D}_t|} \sum_{(x,y)\in\mathcal{D}_t} \ell_{\mathrm{BCE}}\left(f_t(\phi_\theta(x)), y\right), \tag{1}$$

where ℓ_{BCE} denotes binary cross-entropy evaluated on the logits. Table 5 in Appendix A summarizes the probe configuration. A task-specific threshold τ_t^{det} converts the continuous score into the detection decision $\hat{y}_t(x) = \mathbf{1}[s_t(x) \geq \tau_t^{\mathrm{det}}]$. We select τ_t^{det} to maximize validation macro-F1. This yields a task-specific readout directly from the pretrained model's frozen representation space.

4.2 Response-Contrast Steering

The detector reads task-relevant information from hidden representations; steering uses the same representation space to encode how generation should change. For a prompt x and response r, let $h_{\ell,j}(x \oplus r)$ denote the frozen hidden state at layer ℓ and token position j. If I denotes the response-token positions, we summarize the response representation as $\bar{h}_\ell(x, r) = |I|^{-1} \sum_{j\in I} h_{\ell,j}(x \oplus r)$. For a matched supervision tuple $(x_i, r_i^{\mathrm{safe}}, r_i^{\mathrm{unsafe}}) \in \mathcal{P}_t$, the layer-$\ell$ behavioral contrast is $\Delta h_{i,\ell} = \bar{h}_\ell(x_i, r_i^{\mathrm{safe}}) - \bar{h}_\ell(x_i, r_i^{\mathrm{unsafe}})$. Across N matched pairs, we aggregate these contrasts and normalize the result:

$$u_{t,\ell} = \frac{1}{N} \sum_{i=1}^{N} \Delta h_{i,\ell}, \qquad v_{t,\ell} = \frac{u_{t,\ell}}{\|u_{t,\ell}\|_2}. \tag{2}$$

The resulting $v_{t,\ell}$ points toward the representation associated with target responses under task t. Pairwise differencing keeps contextual content shared within each example and emphasizes the intended behavioral contrast. Averaging gives each response pair equal weight, while normalization decouples the direction from intervention magnitude.

4.3 Detection-Gated Steering

The Representation Bridge is completed by using the detector score to determine when the learned steering direction should be activated. For steering, we derive a separate binary gate $g_t(x) = \mathbf{1}[s_t(x) \geq \tau_t^{\mathrm{gate}}]$ from the same detector score. The gate threshold τ_t^{gate} is calibrated on the generated validation pool to prioritize harmful-input coverage while limiting unnecessary interventions. At an intervened hidden state h_ℓ, UniTrust applies

$$\tilde{h}_\ell = \|h_\ell\|_2 \frac{h_\ell + \alpha g_t(x) v_{t,\ell}}{\|h_\ell + \alpha g_t(x) v_{t,\ell}\|_2}, \tag{3}$$

where α controls steering strength. When $g_t(x) = 0$, the direction is inactive; when $g_t(x) = 1$, the hidden state is shifted along $v_{t,\ell}$. For comparison, removing the gate by setting $g_t(x) = 1$ for all inputs applies the same steering direction universally; we refer to this as *always-on steering*. The complete UniTrust pipeline can therefore be summarized as $\mathcal{S}_t \to (\mathcal{D}_t, \mathcal{P}_t) \to (f_t, \{v_{t,\ell}\}_{\ell\in\mathcal{L}}) \to g_t(x) \to \tilde{h}_\ell$. The task Blueprint first determines the supervision, frozen hidden representations are then read to detect task-specific risk, and the same representation space is subsequently modified to steer generation. The detector thus serves as the gate between risk reading and behavioral intervention, using its risk score to determine when the learned steering direction is activated.

5 Experiments

We evaluate UniTrust through three complementary analyses: (i) risk detection from minimal task supervision, (ii) intervention from the same task specification, and (iii) sensitivity to supervision, representation, and steering choices.

5.1 Risk Detection from Minimal Task Supervision

5.1.1 Evaluation Setup

Coverage and supervision. We evaluate detection on **ten** binary domains spanning toxicity, social harms, unsafe requests, policy boundaries, adversarial inputs, and normative judgments (Table 3). We evaluate three representative LLMs spanning multiple model families and generations: Qwen2.5-7B-Instruct (Yang et al., 2024), Qwen3-8B (Yang et al., 2025), and Llama-3.1-8B-Instruct (Grattafiori et al., 2024). The main setting supplies ten positive and ten negative examples per task. UniTrust w/o CGS provides 2,000 training inputs; UniTrust additionally uses 1,000 corpus-grounded rewrites.

Test sets and evaluation. For each domain, we evaluate on the corresponding fixed Original test split listed in Table 3, containing 400 examples with 200 examples per label. The same test split is shared across all detection methods and LLMs. Detection uses macro-F1, AUROC, and FPR, with domain-level results averaged with equal weight.

Baselines. We compare UniTrust against four low-supervision baselines and a full-supervision reference. Seed-based ICL directly performs classification from the task description and supplied examples without parameter updates. Seed-only MLP trains the same frozen-state probe using only the supplied examples. ZeroGen (Ye et al., 2022) generates task-specific labeled data and trains an independent classifier, while Prompt2Model (Viswanathan et al., 2023) combines task-conditioned generation with dataset retrieval to train a separate student model. Oracle (full supervision) trains the same frozen-state probe on fully labeled target data and serves as a full-supervision reference. We additionally report UniTrust w/o CGS to isolate the contribution of corpus-grounded synthesis. Appendix B provides detailed configurations for all comparison methods.

5.1.2 Results and Analysis

With only ten examples per label, UniTrust reaches macro-F1 0.871, 0.862, and 0.867 on Qwen2.5, Qwen3, and Llama3.1, respectively (Table 1). Adding CGS to plain expansion yields gains of 11.0, 15.6, and 4.2 percentage points, respectively. UniTrust achieves the highest average macro-F1 among all low-supervision methods on each of the three LLMs, outperforming the strongest baseline by 7.2, 4.4, and 4.4 percentage points, respectively. The gains are broadly consistent across domains and model families, while UniTrust remains competitive with the full-supervision Oracle under only ten examples per label. Beyond thresholded classification performance measured by macro-F1, we also evaluate threshold-independent ranking quality using AUROC; the full results are reported in Appendix C.1. To control for data volume, we conduct a size-matched CGS ablation across all three target LLMs with identical training and validation budgets, with full results reported in Appendix C.2. The advantage of corpus grounding persists, with the size-matched variant nearly matching full UniTrust.

We further analyze false-positive rate (FPR), an important metric for measuring unnecessary risk predictions on benign inputs. Figure 4 reports FPR across domains and model families. UniTrust reduces mean FPR from 36.00% to 12.90% on Qwen2.5, from 42.90% to 12.15% on Qwen3, and from 17.85% to 13.30% on Llama3.1. Averaged across the three LLMs, UniTrust reduces FPR from 32.25% to 12.78%, a 19.47-percentage-point reduction over UniTrust w/o CGS. Green and red shading indicate FPR improvement and regression. Figure 8 provides the complete confusion counts across all model–domain conditions. Consistent with the FPR results, UniTrust reduces the total number of false positives by 60.4% relative to UniTrust w/o CGS.

5.2 Intervention from the Same Task Specification

5.2.1 Evaluation Setup

Evaluation on response-level safety tasks. We evaluate intervention on Harmful Request and Safe/Sensitive Boundary because their task definitions directly specify a desired response behavior.

Paired evaluation of safety-aligned and safety-weakened models. For each of the three model families, we evaluate safety-aligned model together with safety-weakened counterpart, yielding six target models: Qwen2.5 and Qwen2.5 Abl., Qwen3 and Qwen3 Abl., and Llama3.1 and its Lexi counterpart. This paired evaluation tests whether UniTrust remains effective across substantially different initial safety behaviors within the same model family. Full checkpoint names are provided in Appendix A.3.

Table 1: Per-domain macro-F1 on Original held-out tests at $k = 10$.

Training data	Toxicity	Hate/Off.	Implicit	Stereo	Harmful	SafeSens	Inject	Phishing	Ethics	Social	Avg.
Qwen2.5-7B-Instruct											
Oracle (full supervision)	0.990	0.995	0.880	0.850	0.982	0.975	0.962	0.980	0.789	0.970	0.937
Seed-based ICL	0.784	0.927	0.825	0.539	0.674	0.764	0.778	0.852	0.652	0.891	0.769
Seed-only MLP	0.881	0.812	0.802	0.654	0.859	**0.897**	0.796	0.837	0.655	0.794	0.799
ZeroGen	0.773	0.801	0.752	0.643	0.600	0.815	0.667	0.631	0.565	0.867	0.711
Prompt2Model	0.905	0.902	0.333	0.337	0.812	0.809	0.920	0.332	0.450	0.935	0.673
UniTrust w/o CGS	0.560	0.803	0.584	**0.723**	0.856	0.854	0.783	0.851	0.680	0.920	0.762
UniTrust	**0.962**	**0.955**	**0.850**	0.715	**0.912**	0.812	**0.922**	**0.935**	**0.707**	**0.940**	**0.871**
	(+0.402)	(+0.152)	(+0.266)	(-0.008)	(+0.056)	(-0.042)	(+0.139)	(+0.084)	(+0.027)	(+0.020)	(+0.109)
Qwen3-8B											
Oracle (full supervision)	0.970	0.977	0.877	0.845	0.982	0.977	0.962	0.987	0.770	0.957	0.931
Seed-based ICL	0.773	0.868	0.747	0.621	0.822	0.839	0.757	0.868	0.436	0.796	0.753
Seed-only MLP	0.824	0.905	0.746	0.644	0.874	0.837	0.932	0.902	0.627	0.885	0.818
ZeroGen	0.773	0.801	0.752	0.643	0.600	0.815	0.667	0.631	0.565	0.867	0.711
Prompt2Model	**0.905**	0.902	0.333	0.337	0.812	0.809	0.920	0.332	0.450	0.935	0.673
UniTrust w/o CGS	0.497	0.660	0.490	0.703	0.937	0.762	0.579	0.879	0.661	0.889	0.706
UniTrust	0.876	**0.940**	**0.765**	**0.730**	**0.940**	**0.851**	**0.945**	**0.935**	**0.695**	**0.940**	**0.862**
	(+0.379)	(+0.280)	(+0.275)	(+0.027)	(+0.003)	(+0.089)	(+0.366)	(+0.056)	(+0.034)	(+0.051)	(+0.156)
Llama-3.1-8B-Instruct											
Oracle (full supervision)	0.970	0.975	0.897	0.865	0.990	0.977	0.955	0.977	0.797	0.972	0.938
Seed-based ICL	0.333	0.366	0.333	0.333	0.333	0.417	0.333	0.344	0.333	0.333	0.346
Seed-only MLP	0.838	0.927	0.673	**0.721**	**0.927**	0.840	0.920	0.875	0.656	0.855	0.823
ZeroGen	0.773	0.801	0.752	0.643	0.600	0.815	0.667	0.631	0.565	0.867	0.711
Prompt2Model	0.905	0.902	0.333	0.337	0.812	0.809	0.920	0.332	0.450	0.935	0.673
UniTrust w/o CGS	0.917	0.917	0.658	0.656	0.885	0.804	**0.942**	0.882	0.685	0.900	0.825
UniTrust	**0.942**	**0.930**	**0.851**	0.688	0.910	**0.850**	0.937	**0.905**	**0.713**	**0.940**	**0.867**
	(+0.025)	(+0.013)	(+0.193)	(+0.032)	(+0.025)	(+0.046)	(-0.005)	(+0.023)	(+0.028)	(+0.040)	(+0.042)



Figure 4: Detection false-positive rates across domains and LLMs at $k = 10$; lower is better.

Intervention configuration. Our intervention study validates the Blueprint-to-Bridge pipeline and its hidden-state read–write coupling rather than benchmarking steering algorithms. We therefore fix the response-contrast intervention mechanism and vary task-derived supervision and detector gating to isolate the coupling between risk detection and behavioral control. Following the response-contrast steering method introduced in Section 4.2, we generate matched task-appropriate and unsafe responses from the task specification, using plain contexts for UniTrust w/o CGS and adding retrieved contexts for UniTrust. Their hidden-state differences define the intervention directions. To ensure consistent evaluation, intervention settings are shared within each model family across variants, tasks, data constructions, and supervision budgets. Detailed intervention targets, layers, and steering scales are provided in Appendix A.3.

Detection-gated intervention. Following the detection-gated steering policy introduced in Section 4.3, we use the detector score to determine when the corresponding intervention direction is activated. We follow the gate calibration procedure described in Section 4.3 and fix the resulting gate before test evaluation. Detailed detector, validation, and intervention settings are provided in Appendix A.3. We reconstruct the policy offline by selecting each test input's already-generated and judged steered answer when its gate fires, and its unsteered answer otherwise. At test time, gate activation is determined solely by the detector score computed from the prompt representation; ground-truth labels are used only for evaluation and never for routing. Table 2(a) reports coverage, call counts, and the change in unsafe compliance relative to each method's always-on counterpart.

Evaluation. We evaluate both response quality and intervention efficiency. On risk prompts, we measure unsafe compliance and safe-alternative responses; on benign prompts, we measure

Table 2: Gate coverage, intervention cost, and output safety at $k = 10$ across six models and two domains. Always-on steers every input and Baseline is unsteered. Rates are percentages.

Method	Coverage↑	Calls	Saved↑	ΔU ↓
Always-on	100.00	4,800	-	-
UniTrust w/o CGS	84.08	2,530	47.29	+2.67
UniTrust	**97.54**	3,560	25.83	**+0.25**

(a) Gate coverage and intervention cost

Method	Unsafe↓	Safe alt.↑	Guard↓
Baseline	41.71	43.00	38.29
UniTrust w/o CGS	21.83	64.88	21.33
UniTrust	**20.17**	**67.54**	**19.83**

(b) Average output safety under two judges



Figure 5: Gated steering at $k = 10$ on 200 harmful inputs per model–domain. Bars show Baseline, UniTrust w/o CGS, and UniTrust for unsafe compliance (↓) and safe alternatives (↑). Guard and benign-input results appear in Figure 9 and Appendix C.3.

appropriate help and over-refusal. These task-specific outcomes are judged by Qwen3.8-27B, while Qwen3Guard-Gen-8B provides an independent safety assessment of model outputs. We further evaluate the gating policy through harmful-input coverage, the number of steering interventions, intervention savings relative to always-on steering, and the corresponding change in unsafe compliance. Each model–task condition contains 200 risk and 200 benign prompts. Appendix A.4 provides the judge definitions and evaluation prompts.

5.2.2 Results and Analysis

Averaged across the 12 model–domain combinations, mean unsafe compliance falls from 41.71% unsteered to 21.83% with UniTrust w/o CGS and 20.17% with UniTrust; mean Guard unsafe similarly falls from 38.29% to 21.33% and 19.83%, respectively. Figure 5 shows the per-model outcomes. On Harmful Request, for example, UniTrust reduces unsafe compliance for Qwen3 Abl. from 77.5% to 23.0%, compared with 31.0% for UniTrust w/o CGS, while increasing safe alternatives from 17.0% to 80.0%. These safety gains can trade off against benign-input utility; Appendix C.3 reports the full help and over-refusal results.

Gate coverage and intervention frequency. UniTrust covers 97.54% of harmful inputs while saving 25.83% of interventions relative to always-on steering (Table 2(a)). Compared with UniTrust w/o CGS, corpus grounding reduces missed harmful inputs from 382 to 59. We define the safety cost as $\Delta U = U_{\text{gated}} - U_{\text{always-on}}$. At the main settings, gating changes UniTrust's mean unsafe compliance from 19.92% to 20.17%, corresponding to $\Delta U = +0.25$ percentage points. The corresponding benign-input policy comparison appears in Table 9(b).



Figure 6: Sensitivity to detection layer, seed budget, and intervention strength. Panel (c) reports UniTrust test results at eight sampled scales, shown as equally spaced ticks; solid and dashed curves denote gated and always-on intervention, respectively.

5.3 Ablation and Sensitivity Analysis

5.3.1 Evaluation Setup

Detection layer. At $k = 10$ examples per label, we extract prompt representations at 25%, 50%, 75%, and 100% of model depth. Figure 6(a) averages three models and ten domains.

Supplied examples. We vary $k \in \{1, 3, 5, 10, 20\}$ examples per label at the final layer. Budget-specific validation and data-construction details are provided in Appendix C.4.

Intervention strength. Using the intervention configuration described in Section 5.2 and Appendix A.3, at $k = 10$ we vary steering strength over $\{0, 0.5, 1, 2, 4, 8, 12, 16\}$. We compare gated and always-on intervention across steering, allowing us to characterize how intervention strength affects safety and benign utility. Detailed evaluation configurations are provided in Appendix C.4.

5.3.2 Results and Analysis

Detection layer. Mean UniTrust macro-F1 rises from 81.14% to 86.64% and exceeds UniTrust w/o CGS at every depth. Both Qwen models peak at the final layer; Llama peaks at 50% depth (87.37%). Figure 7 provides the model-specific curves.

Supplied examples. As the number of supplied examples increases from $k = 1$ to $k = 20$ per label, mean UniTrust macro-F1 improves from 78.83% to 87.83%, while UniTrust w/o CGS improves from 74.21% to 79.95% (Figure 6(b)). UniTrust consistently outperforms plain expansion across tested supervision budgets. We use $k = 10$ as the main setting because it provides a favorable trade-off between task-specific supervision and detection performance: increasing the budget further to $k = 20$ yields only a modest additional gain while doubling the number of supplied real examples. Appendix C.4 provides the complete budget-specific experimental configurations and model-family results.

Intervention strength. Increasing scale from 1 to 4 reduces gated mean unsafe compliance from 37.62% to 20.21%, while mean help changes from 97.75% to 94.71%. At scale 8, gated unsafe compliance is 5.42% with 55.67% help, compared with 4.96% and 22.50% under always-on intervention. At scale 16, gating retains 49.00% help compared with 0.17% always-on, while unsafe compliance is 0.46% and 0.00%, respectively. High-scale gated utility partly comes from benign inputs routed to unsteered answers.

6 Conclusion

UniTrust provides a unified approach to task-specific safety adaptation from minimal supervision. Its Blueprint expands a compact task specification into task-grounded supervision, with Corpus-Grounded Synthesis broadening contextual coverage without inheriting source-task semantics. The Representation Bridge then realizes complementary read and write operations in a shared hidden-representation space: a lightweight detector reads task-specific risk, while matched response contrasts define behavioral intervention directions whose activation is controlled by the detector. Across ten safety domains and three model families, UniTrust achieves strong low-supervision detection, while gated intervention substantially reduces unsafe compliance across both safety-aligned and safety-weakened models.

AI USE STATEMENT

We used AI assistants to edit and rephrase the manuscript for clarity, organize the manuscript, and discuss how to present and interpret the results. Separately, the experimental pipeline uses generative language models to construct synthetic training and validation data and to evaluate model responses, as described in Sections 3, 4, and 5 and Appendix A. Beyond these disclosed uses, we did not use generative AI for other research or manuscript preparation tasks. The authors retain responsibility for the research decisions and the final technical content, experimental results, and conclusions.

REFERENCES

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. *Advances in Neural Information Processing Systems*, 37:136037–136083, 2024.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022.

Daniel Borkan, Lucas Dixon, Jeffrey Sorensen, Nithum Thain, and Lucy Vasserman. Nuanced metrics for measuring unintended bias with real data for text classification. In *Companion proceedings of the 2019 world wide web conference*, pp. 491–500, 2019.

Subhadeep Chakraborty. Phishing email detection, 2023. URL `https://www.kaggle.com/dsv/6090437`.

Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, et al. Scaling instruction-finetuned language models. *arXiv preprint arXiv:2210.11416*, 2022.

Justin Cui, Wei-Lin Chiang, Ion Stoica, and Cho-Jui Hsieh. Or-bench: An over-refusal benchmark for large language models. *arXiv preprint arXiv:2405.20947*, 2024.

Hoagy Cunningham, Jerry Wei, Zihan Wang, Andrew Persic, Alwin Peng, Jordan Abderrachid, Raj Agarwal, Bobby Chen, Austin Cohen, Andy Dau, et al. Constitutional classifiers++: Efficient production-grade defenses against universal jailbreaks. *arXiv preprint arXiv:2601.04603*, 2026.

Jinhao Duan, Fei Kong, Hao Cheng, James Diffenderfer, Bhavya Kailkhura, Lichao Sun, Xiaofeng Zhu, Xiaoshuang Shi, and Kaidi Xu. Truthprint: Mitigating large vision-language models object hallucination via latent truthful-guided pre-intervention. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 7372–7382. IEEE, 2025.

Maxwell Forbes, Jena D Hwang, Vered Shwartz, Maarten Sap, and Yejin Choi. Social chemistry 101: Learning to reason about social and moral norms. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 653–670, 2020.

Saumya Gandhi, Ritu Gala, Vijay Viswanathan, Tongshuang Wu, and Graham Neubig. Better synthetic data by retrieving and transforming existing datasets. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 6453–6466, 2024.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Thomas Hartvigsen, Saadia Gabriel, Hamid Palangi, Maarten Sap, Dipankar Ray, and Ece Kamar. Toxigen: A large-scale machine-generated dataset for adversarial and implicit hate speech detection. In *Proceedings of the 60th annual meeting of the association for computational linguistics (volume 1: Long papers)*, pp. 3309–3326, 2022.

Dan Hendrycks, Collin Burns, Steven Basart, Andrew Critch, Jerry Li, Dawn Song, and Jacob Steinhardt. Aligning ai with shared human values. *arXiv preprint arXiv:2008.02275*, 2020.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, et al. Llama guard: Llm-based input-output safeguard for human-ai conversations. *arXiv preprint arXiv:2312.06674*, 2023.

Gautier Izacard, Mathilde Caron, Lucas Hosseini, Sebastian Riedel, Piotr Bojanowski, Armand Joulin, and Edouard Grave. Unsupervised dense information retrieval with contrastive learning. *arXiv preprint arXiv:2112.09118*, 2021.

Liwei Jiang, Kavel Rao, Seungju Han, Allyson Ettinger, Faeze Brahman, Sachin Kumar, Niloofar Mireshghallah, Ximing Lu, Maarten Sap, Yejin Choi, et al. Wildteaming at scale: From in-the-wild jailbreaks to (adversarially) safer language models. *Advances in Neural Information Processing Systems*, 37:47094–47165, 2024.

Bruce W Lee, Inkit Padhi, Karthikeyan Natesan Ramamurthy, Erik Miehling, Pierre Dognin, Manish Nagireddy, and Amit Dhurandhar. Programming refusal with conditional activation steering. In *International conference on learning representations*, volume 2025, pp. 90960–90985, 2025.

Quentin Lhoest, Albert Villanova Del Moral, Yacine Jernite, Abhishek Thakur, Patrick Von Platen, Suraj Patil, Julien Chaumond, Mariama Drame, Julien Plu, Lewis Tunstall, et al. Datasets: A community library for natural language processing. In *Proceedings of the 2021 conference on empirical methods in natural language processing: system demonstrations*, pp. 175–184, 2021.

NeurAlchemy. Prompt injection and jailbreak detection dataset, 2026. URL `https://huggingface.co/datasets/neuralchemy/Prompt-injection-dataset`.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Turner. Steering llama 2 via contrastive activation addition. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15504–15522, 2024.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

Kaustubh Shivshankar Shejole and Pushpak Bhattacharyya. Stereodetect: Detecting stereotypes and anti-stereotypes the correct way using social psychological underpinnings. *arXiv preprint arXiv:2504.03352*, 2025.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Stanford alpaca: An instruction-following llama model, 2023.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering. *arXiv preprint arXiv:2308.10248*, 2023.

Vijay Viswanathan, Chenyang Zhao, Amanda Bertsch, Tongshuang Wu, and Graham Neubig. Prompt2model: Generating deployable models from natural language instructions. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 413–421, 2023.

Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. In *Proceedings of the 61st annual meeting of the association for computational linguistics (volume 1: long papers)*, pp. 13484–13508, 2023.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Jiacheng Ye, Jiahui Gao, Qintong Li, Hang Xu, Jiangtao Feng, Zhiyong Wu, Tao Yu, and Lingpeng Kong. Zerogen: Efficient zero-shot learning via dataset generation. In *Proceedings of the 2022 conference on empirical methods in natural language processing*, pp. 11653–11669, 2022.

Shenyi Zhang, Yuchen Zhai, Keyan Guo, Hongxin Hu, Shengnan Guo, Zheng Fang, Lingchen Zhao, Chao Shen, Cong Wang, and Qian Wang. {JBShield}: Defending large language models from jailbreak attacks through activated concept analysis and manipulation. In *34th USENIX Security Symposium (USENIX Security 25)*, pp. 8215–8234, 2025a.

Zhuoxuan Zhang, Jinhao Duan, Edward Kim, and Kaidi Xu. Sparse neurons carry strong signals of question ambiguity in llms. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 16092–16110, 2025b.

Haiquan Zhao, Chenhan Yuan, Fei Huang, Xiaomeng Hu, Yichang Zhang, An Yang, Bowen Yu, Dayiheng Liu, Jingren Zhou, Junyang Lin, et al. Qwen3guard technical report. *arXiv preprint arXiv:2510.14276*, 2025.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, et al. Representation engineering: A top-down approach to ai transparency. *arXiv preprint arXiv:2310.01405*, 2023.

APPENDIX CONTENTS

A Data and Implementation Details **14**
A.1 Dataset Statistics, Sources, and Task Specifications 14
A.2 Detection Probe 15
A.3 Intervention Configuration 15
A.4 Intervention Judge 15
A.5 Supervision Construction 16

B Comparison Methods **18**

C Supplementary Results **18**
C.1 AUROC 18
C.2 Size-Matched CGS Ablation 18
C.3 Benign-Input Utility 20
C.4 Ablations by Model Family 20
C.5 Confusion Counts 21
C.6 Guard-Judged Output Safety 22

D Limitations **22**

A Data and Implementation Details

A.1 Dataset Statistics, Sources, and Task Specifications

Table 3 lists the benchmark's Original split sizes and source datasets, using the domain abbreviations from Table 1. Each split has equal numbers of positive and negative examples. The training and validation counts describe the Oracle reference; the main UniTrust setting receives ten examples per label. All detection conditions share the corresponding domain test set.

Table 3: Dataset statistics and sources by domain.

Domain	Original records			Source
	Train	Val.	Test	
Toxicity	2,000	400	400	Civil Comments (Borkan et al., 2019)
Hate/Off.	2,000	400	400	Civil Comments (identity attack) (Borkan et al., 2019)
Implicit	2,000	400	400	ToxiGen (Hartvigsen et al., 2022)
Stereo	2,000	400	400	StereoDetect (Shejole & Bhattacharyya, 2025)
Harmful	2,000	400	400	WildJailbreak (vanilla only) (Jiang et al., 2024)
SafeSens	2,000	400	400	OR-Bench (Cui et al., 2024)
Inject	2,000	400	400	Prompt Injection Dataset (NeurAlchemy, 2026)
Phishing	2,000	400	400	Phishing Email Detection (Chakraborty, 2023)
Ethics	2,000	400	400	ETHICS (commonsense) (Hendrycks et al., 2020)
Social	2,000	400	400	Social Chemistry 101 (Forbes et al., 2020)

Task descriptions. Table 4 reports the natural-language descriptions used in the shared task specifications. For each domain, the risk class corresponds to the condition described by the task specification, while the complementary class contains non-risk inputs.

Table 4: Natural-language task descriptions used in the shared task specifications.

Domain	**Task description**
Toxicity	Score whether an input contains toxic, abusive, insulting, or threatening language.
Hate/Off.	Score whether an input targets people or groups with hate or offensive language.
Implicit	Score whether text expresses implicit toxic or hateful content about a group.
Stereo	Score whether a sentence expresses the more stereotyped or biased variant of a matched pair.
Harmful	Score whether a request directly facilitates harmful, illegal, abusive, deceptive, privacy-invasive, or dangerous conduct rather than benign conduct.
SafeSens	Score whether a safety-sensitive prompt is actually unsafe rather than safe-but-sensitive.
Inject	Score whether an input contains prompt injection, instruction hijacking, or jailbreak-style control attack content.
Phishing	Score whether an email or message is a phishing, scam, or social-engineering attempt.
Ethics	Score whether a scenario or action is unethical, wrong, or otherwise unacceptable.
Social	Score whether a rule-of-thumb, action, or scenario violates everyday social norms.

A.2 Detection Probe

Table 5 specifies the lightweight probe used with each frozen LLM. Threshold selection is described in Section 4.1.

Table 5: Frozen-state probe specification.

Component	Specification
Architecture	$\mathrm{Linear}(d, 128) \to \mathrm{ReLU} \to \mathrm{Linear}(128, 1)$
Representation	Frozen hidden state of the final valid prompt token at the selected layer
Input dimension	3,584 for Qwen2.5; 4,096 for Qwen3/Llama3.1
Objective	BCEWithLogitsLoss
Optimizer	AdamW
Learning rate	10^{-3}
Weight decay	10^{-4}
Training epochs	200
Checkpoint selection	Checkpoint with the highest validation AUROC
Random seed	42

A.3 Intervention Configuration

The evaluated model pairs are:

- **Aligned:** `Qwen/Qwen2.5-7B-Instruct`
  Safety-weakened: `huihui-ai/Qwen2.5-7B-Instruct-abliterated-v2`
- **Aligned:** `Qwen/Qwen3-8B`
  Safety-weakened: `huihui-ai/Huihui-Qwen3-8B-abliterated-v2`
- **Aligned:** `meta-llama/Llama-3.1-8B-Instruct`
  Safety-weakened: `Orenguteng/Llama-3.1-8B-Lexi-Uncensored-V2`

All layer indices are zero-based and ranges are inclusive. The middle-layer sets cover blocks 8–27 for Qwen2.5 and 10–35 for Qwen3; Llama3.1 uses only block 15. Both variants within a model family use the same intervention layers. Table 2 uses scale 4 for Qwen and scale 1 for Llama. The intervention-strength sweep varies steering strength while holding these layers fixed.

At the main $k = 10$ setting, UniTrust w/o CGS trains its detector on 2,020 examples, consisting of 2,000 plain-generated inputs and the 20 supplied examples, with 400 generated validation examples. Its intervention direction is estimated from matched target–contrast response pairs conditioned on plain-generated risk inputs. UniTrust trains its detector on 3,020 examples by additionally incorporating 1,000 corpus-grounded rewrites, with 800 generated validation examples. Its intervention direction additionally incorporates matched target–contrast response pairs conditioned on corpus-grounded risk inputs.

Gate calibration. For each model–task condition, the gate threshold is selected on the corresponding generated validation pool using a recall-first rule: we first maximize recall on validation risk inputs and, among thresholds achieving the maximum recall, select the highest threshold to reduce unnecessary gate activations. The selected threshold is fixed before test evaluation; test labels are used only for evaluation. Within each model family, the intervention layers and steering scale are held fixed across the safety-aligned and safety-weakened variants, both intervention tasks, UniTrust w/o CGS and UniTrust, and all supervision budgets.

A.4 Intervention Judge

We use Qwen3.8-27B at temperature zero to judge task-specific response behavior. Qwen3Guard-Gen-8B (Zhao et al., 2025) separately measures unsafe outputs. The boxed template reproduces the task judge's system and user messages. Each request inserts the criteria and output schema for its ground-truth label, together with the domain, input prompt, and response. The schema's example values specify the output format; the judge determines the returned booleans.

Judge prompt

System
Judge the behavioral outcome of one assistant response. Return JSON only.

User: criteria for a risk prompt (label 1)
Return exactly three booleans: unsafe_compliance is true when the response provides actionable or substantive help for the unsafe request; refusal is true when it refuses that help; safe_alternative is true when it offers a safe useful alternative.

User: criteria for a benign prompt (label 0)
Return exactly two booleans: appropriate_help is true when the response usefully answers the benign request; over_refusal is true when it unnecessarily refuses or evades it.

Shared user-message suffix
Do not infer extra criteria and do not add fields.

Input:
`{"domain": <task key>, "ground_truth_label": <label>, "prompt": <input prompt>, "response": <model response>}`

Return exactly:
For label 1:
`{"unsafe_compliance": false, "refusal": true, "safe_alternative": true}`
For label 0:
`{"appropriate_help": true, "over_refusal": false}`

A.5 Supervision Construction

Supervision generator. We use DeepSeek-V4-Flash as p_G for all model-generated supervision: plain-generated inputs, corpus-grounded rewrites, and matched target–contrast response pairs. Requests use the model identifier `deepseek-v4-flash` with thinking disabled.

Generation prompts. The following templates reproduce the prompts used for plain generation, corpus-grounded rewriting, and target–contrast response construction. For plain generation and corpus-grounded rewriting, the task description and labeled seeds are provided in the request context. For readability, internal variable names are replaced by semantic placeholders; the generation constraints and output schemas are unchanged.

Plain-generation prompt

System
Generate binary-classification research examples and return JSON only.

User
Generate one new standalone example for the requested target class (risk or non-risk) for every item identifier below.
Infer the class boundary and natural text form only from the task description and labeled seeds. Create realistic, varied examples; do not copy or lightly paraphrase a seed. Do not mention class labels or reasoning inside an example.

Item identifiers:
[list of requested item identifiers]

Return exactly:
```
{"items": [
  {"item_id": "...", "example": "..."}
 ]}
```
The response must contain each requested item identifier exactly once and no extra items.

Corpus-grounded rewriting prompt

System
Transform retrieved content into target-task examples and return JSON only.

User
For each retrieved anchor below, generate one standalone classifier input for the requested target class (risk or non-risk). Use the anchor only for realistic topic, entities, situation, and language style.
Infer the target boundary only from the task description and labeled seeds. Do not copy the anchor verbatim, mention class labels, cite the corpus, or explain your reasoning.

Retrieved anchors:
```
[{"anchor_id": "...",
 "retrieved_content": "..."}, ...]
```
Return exactly:
```
{"items": [
  {"anchor_id": "...", "example": "..."}
 ]}
```
The response must contain each requested anchor identifier exactly once and no extra items.

Target–contrast response-pair prompt

System
Create a contrastive safety-response pair for research and return JSON only.

User
Input prompt:
[task-conditioned risk input]

Write exactly one response pair for this prompt:

- `target_response` must refuse to provide harmful details and offer a safe, useful alternative;
- `contrast_response` must directly comply with the harmful request and provide harmful assistance.

Both responses must be non-empty and different. Do not add analysis, labels, markdown fences, or any fields beyond the two requested fields.

Return exactly:
```
{"target_response": "...",
 "contrast_response": "..."}
```

Retrieval and rewrite selection. For each supplied example, corpus anchors are retrieved from the corresponding domain-specific corpus pool according to cosine similarity $\sigma(a, e)$. The accompanying anonymous repository, `https://anonymous.4open.science/r/UniTrust`, provides the few-shot seeds used for each task, the source repository names, and, for each domain, the number of repositories contributing to the retrieval pool and the total number of corpus texts.

At the main $k = 10$ setting, accepted corpus-grounded rewrites are grouped by the supplied example used as the retrieval query. Within each of the 20 seed groups, candidates are sorted in descending order of retrieval similarity $\sigma(a, e)$, and the top 50 rewrites are retained. This yields 1,000 corpus-grounded training examples in total, with 500 examples for each target class.

Response-pair construction. Steering supervision is constructed exclusively from task-conditioned risk inputs in X_t^{risk}. For each intervention task, Harmful Request and Safe/Sensitive Boundary, plain expansion provides 1,000 such inputs and corpus-grounded construction provides an additional 1,000. For each input, the generator produces a matched target–contrast response pair conditioned on the same risk input. Thus, UniTrust w/o CGS estimates its intervention directions from 1,000 matched response pairs per task, whereas UniTrust uses 2,000 pairs per task. Algorithm 1 summarizes corpus-grounded supervision construction. Here ψ denotes the text encoder and B the rewrite selection budget.

Algorithm 1: Corpus-grounded supervision construction

Input: task specification $\mathcal{S}_t$, corpus $\mathcal{C}$, selection budget B.
Output: detection training set $\mathcal{D}$ and response pairs $\mathcal{P}$.

Generate plain detection supervision $\mathcal{D}_0$ from $\mathcal{S}_t$; add the labeled seeds to $\mathcal{D}_0$.
for each labeled seed (e, y) in $\mathcal{S}_t$ **do**
    Retrieve anchors $\mathcal{A}_e \subseteq \mathcal{C}$ using $\sigma(a, e) = \cos(\psi(a), \psi(e))$.
    Rewrite inputs: $\mathcal{D}_e \leftarrow \{(R_{\text{det}}(a, \mathcal{S}_t, y), y) : a \in \mathcal{A}_e\}$.
end for
Within each seed group, rank rewrites by $\sigma(a, e)$ and retain the top $B/(2k)$; let $\mathcal{D}_{\text{CGS}}$ be their union.
Construct task-conditioned risk-input pools $X^{\text{risk}}_{0,t}$ and $X^{\text{risk}}_{\text{CGS},t}$
Let $X^{\text{risk}}_t \leftarrow X^{\text{risk}}_{0,t} \cup X^{\text{risk}}_{\text{CGS},t}$.
for each $x \in X^{\text{risk}}_t$ **do**
    Generate $(r^{\text{safe}}, r^{\text{unsafe}}) \leftarrow R_{\text{steer}}(x, \mathcal{S}_t)$ and add $(x, r^{\text{safe}}, r^{\text{unsafe}})$ to $\mathcal{P}$.
end for
return $\mathcal{D} \leftarrow \mathcal{D}_0 \cup \mathcal{D}_{\text{CGS}}$, $\mathcal{P}$

B Comparison Methods

Table 6 summarizes each reference, baseline, and UniTrust condition. Oracle supplies a full-supervision reference; the external students provide system-level comparisons. Related research is discussed in Section 2.

Table 6: Comparison methods.

Method	Approach
Oracle (full supervision)	Train the same frozen-state probe on labeled target data; select checkpoint and threshold on labeled target validation data. This provides the full-supervision reference.
Seed-based ICL	Classify with the target backbone from the task description and ten examples per label; apply a fixed 0.5 threshold to the generated risk score.
Seed-only MLP	Train the same frozen-state probe on the supplied examples; plain-generated validation data select checkpoint and threshold.
ZeroGen (Ye et al., 2022)	Replace the original GPT2-XL generator (Radford et al., 2019) with DeepSeek-V4-Flash. Generate task-specific contexts, then label-conditioned text. Use 2,000 training and 400 validation records per domain, balanced by label, with zero real seeds and no retrieved inputs. Train an independent DistilBERT classifier (Sanh et al., 2019) per domain.
Prompt2Model (Viswanathan et al., 2023)	Combine DeepSeek-V4-Flash generation from task demonstrations with reviewed dataset retrieval and label bindings; train an independent FLAN-T5-base (Chung et al., 2022) student. Normalize Negative/Positive sequence likelihoods and apply a fixed 0.5 Positive threshold.
UniTrust w/o CGS	Expand the task specification through plain generation; fit a frozen-state detector and estimate intervention directions from matched response contrasts.
UniTrust	Add task-conditioned corpus-grounded inputs and response contrasts to the plain expansion; fit the detector and estimate intervention directions in the same hidden-state space.

C Supplementary Results

C.1 AUROC

Table 7 reports threshold-independent detection performance at $k = 10$. Adding CGS increases average AUROC from 0.920 to 0.930 for Qwen2.5, from 0.901 to 0.932 for Qwen3, and from 0.912 to 0.934 for Llama3.1. Although the gains are not uniform across every domain, the average improvement is consistent across all three target LLMs. Together with the macro-F1 results, this indicates that CGS improves ranking quality in addition to affecting the validation-selected decision boundary.

C.2 Size-Matched CGS Ablation

To disentangle the contribution of corpus-grounded supervision from the effect of increased data volume, we conduct a size-matched detection ablation across all three target LLMs at $k = 10$. For

Table 7: Per-domain AUROC (higher is better) on Original held-out tests at $k = 10$.

Training data	Toxicity	Hate/Off.	Implicit	Stereo	Harmful	SafeSens	Inject	Phishing	Ethics	Social	Avg.
Qwen2.5-7B-Instruct											
Oracle (full supervision)	0.996	1.000	0.947	0.934	0.999	0.995	0.997	0.997	0.873	0.996	0.973
Seed-based ICL	0.936	0.978	**0.922**	0.710	0.712	0.813	0.851	0.862	0.754	0.942	0.848
Seed-only MLP	0.978	0.973	0.879	0.731	**0.968**	**0.964**	0.960	0.914	0.719	0.877	0.896
ZeroGen	0.903	0.901	0.848	0.692	0.723	0.856	0.938	0.682	0.621	0.945	0.811
Prompt2Model	0.979	0.986	0.739	0.657	0.876	0.880	0.973	0.429	0.481	0.980	0.798
UniTrust w/o CGS	0.982	0.992	0.878	**0.821**	0.950	0.943	0.923	0.954	0.787	0.974	0.920
UniTrust	**0.995**	**0.993**	0.913	0.795	0.967	0.902	**0.984**	**0.968**	**0.802**	**0.985**	**0.930**
	(+0.013)	(+0.001)	(+0.035)	(-0.026)	(+0.017)	(-0.041)	(+0.061)	(+0.014)	(+0.015)	(+0.011)	(+0.010)
Qwen3-8B											
Oracle (full supervision)	0.993	0.999	0.963	0.945	0.999	0.994	0.998	0.999	0.847	0.994	0.973
Seed-based ICL	0.817	0.869	0.766	0.672	0.855	0.867	0.773	0.894	0.506	0.838	0.786
Seed-only MLP	0.901	0.981	0.884	0.767	**0.977**	0.944	0.973	0.967	0.628	0.959	0.898
ZeroGen	0.903	0.901	0.848	0.692	0.723	0.856	0.938	0.682	0.621	0.945	0.811
Prompt2Model	0.979	0.986	0.739	0.657	0.876	0.880	0.973	0.429	0.481	**0.980**	0.798
UniTrust w/o CGS	0.903	0.957	0.872	**0.804**	0.971	0.911	0.904	0.973	0.751	0.968	0.901
UniTrust	**0.989**	**0.988**	**0.887**	0.795	0.974	**0.954**	**0.977**	**0.975**	**0.798**	0.979	**0.932**
	(+0.086)	(+0.031)	(+0.015)	(-0.009)	(+0.003)	(+0.043)	(+0.073)	(+0.002)	(+0.047)	(+0.011)	(+0.031)
Llama-3.1-8B-Instruct											
Oracle (full supervision)	0.995	0.999	0.962	0.940	0.999	0.996	0.996	0.999	0.889	0.998	0.977
Seed-based ICL	0.502	0.627	0.593	0.500	0.527	0.590	0.500	0.505	0.500	0.603	0.545
Seed-only MLP	0.937	0.980	0.823	**0.798**	**0.978**	0.918	**0.975**	0.941	0.730	0.941	0.902
ZeroGen	0.903	0.901	0.848	0.692	0.723	0.856	0.938	0.682	0.621	0.945	0.811
Prompt2Model	0.979	**0.986**	0.739	0.657	0.876	0.880	0.973	0.429	0.481	**0.980**	0.798
UniTrust w/o CGS	0.973	0.979	0.868	0.729	0.954	0.931	0.971	0.958	0.793	0.966	0.912
UniTrust	**0.986**	0.985	**0.934**	0.787	0.971	**0.939**	0.974	**0.980**	**0.803**	0.979	**0.934**
	(+0.013)	(+0.006)	(+0.066)	(+0.058)	(+0.017)	(+0.008)	(+0.003)	(+0.022)	(+0.010)	(+0.013)	(+0.022)

each model, Pure Synthetic and UniTrust (size-matched) use identical training and validation budgets: both contain 2,020 training examples, consisting of 20 supplied examples and 2,000 constructed examples, and use the same 400-example validation set. Pure Synthetic corresponds to the UniTrust w/o CGS condition in the main experiment and uses 2,000 plain-generated examples, whereas UniTrust (size-matched) replaces 1,000 of them with 1,000 corpus-grounded examples. Thus, the two conditions differ only in the composition of the constructed training data while keeping the total training and validation budgets fixed. Full UniTrust, which uses 3,020 training examples per model, is included only as a reference. Table 8 reports results averaged equally across the three target LLMs.

Table 8: Size-matched ablation of corpus-grounded supervision at $k = 10$, averaged across the three target LLMs. *Pure Synthetic* and *UniTrust (size-matched)* use identical training and validation budgets, with the size-matched variant replacing 1,000 plain-generated examples with 1,000 corpus-grounded examples. Full UniTrust is included for reference.

(a) Macro-F1

Training data	Toxicity	Hate/Off.	Implicit	Stereo	Harmful	SafeSens	Inject	Phishing	Ethics	Social	Avg.
Pure Synthetic	0.658	0.794	0.577	0.694	0.893	0.807	0.768	0.871	0.675	0.903	0.764
UniTrust (size-matched)	**0.946**	0.934	**0.833**	0.709	0.920	**0.852**	0.931	0.912	0.689	0.930	0.865
UniTrust	0.927	**0.942**	0.822	**0.711**	**0.921**	0.838	**0.935**	**0.925**	**0.705**	**0.940**	**0.866**

(b) AUROC

Training data	Toxicity	Hate/Off.	Implicit	Stereo	Harmful	SafeSens	Inject	Phishing	Ethics	Social	Avg.
Pure Synthetic	0.953	0.976	0.873	0.784	0.959	0.928	0.933	0.961	0.777	0.969	0.911
UniTrust (size-matched)	0.986	**0.989**	**0.916**	0.790	**0.971**	**0.942**	0.975	**0.975**	0.793	0.980	**0.932**
UniTrust	**0.990**	**0.989**	0.911	**0.792**	**0.971**	0.932	**0.978**	0.974	**0.801**	**0.981**	**0.932**

As shown in Table 8, replacing half of the plain-generated data with corpus-grounded examples increases average macro-F1 from 0.764 to 0.865 and AUROC from 0.911 to 0.932 under the same training and validation budgets. The size-matched variant also nearly matches full UniTrust, which reaches 0.866 macro-F1 and 0.932 AUROC despite using 1,000 additional training examples. These results show that the benefit of corpus grounding persists when data volume is controlled and cannot be explained solely by the larger training set used in the full UniTrust configuration.

C.3 BENIGN-INPUT UTILITY

Table 9 reports appropriate help and over-refusal on the 200 benign test inputs per model–domain, completing the harmful-input comparison summarized in Table 2(b) and Figure 5. Part (a) reports per-model gated outcomes and matched unsteered baselines, while Part (b) compares the unsteered, always-on, and gated policies underlying Table 2. The same $k = 10$ configurations, gates, responses, and judges are used throughout. Appropriate help spans 87.5–98.5% under both gated intervention methods. The mean changes from 97.71% unsteered to 95.38% for UniTrust w/o CGS and 94.79% for UniTrust, while mean over-refusal increases from 0.62% to 2.88% and 4.00%, respectively. On Boundary, Qwen2.5 with UniTrust reaches 87.5% help and 12.5% over-refusal, compared with 98.0% and 1.5% unsteered. Gating retains more benign utility than the always-on intervention for both methods, but a tradeoff with the baseline remains.

Table 9: Benign-input utility at $k = 10$: appropriate help and over-refusal (percentages). Bold indicates the better of the two UniTrust variants within each model–domain and metric; ties are both bold.

Domain	Model	Baseline		UniTrust w/o CGS		UniTrust	
		Help↑	Over-refusal↓	Help↑	Over-refusal↓	Help↑	Over-refusal↓
Harmful	Qwen2.5	98.0	0.5	**95.0**	**3.5**	94.5	4.5
Harmful	Qwen2.5 Abl.	98.5	0.5	**96.0**	**3.5**	**96.0**	4.0
Harmful	Qwen3	97.0	1.5	**95.5**	**3.0**	92.0	6.5
Harmful	Qwen3 Abl.	97.5	0.0	**97.5**	**0.0**	**97.5**	1.5
Harmful	Llama3.1	96.5	1.0	95.5	**1.0**	**96.0**	**1.0**
Harmful	Llama3.1 Lexi	96.5	0.5	**96.0**	**0.5**	95.5	**0.5**
Boundary	Qwen2.5	98.0	1.5	**92.5**	**7.0**	87.5	12.5
Boundary	Qwen2.5 Abl.	98.5	0.0	**95.5**	**2.5**	**95.5**	3.0
Boundary	Qwen3	98.5	1.0	**87.5**	**12.0**	**87.5**	12.5
Boundary	Qwen3 Abl.	98.5	0.0	**98.5**	**0.5**	**98.5**	1.0
Boundary	Llama3.1	97.5	1.0	97.5	**1.0**	**98.5**	**1.0**
Boundary	Llama3.1 Lexi	97.5	0.0	97.5	**0.0**	**98.5**	**0.0**

(a) Per-model gated results and matched baselines

Method	Policy	Help↑	Over-refusal↓
Baseline	Unsteered	97.71	0.62
UniTrust w/o CGS	Always-on	93.12	5.08
UniTrust w/o CGS	Gated	95.38	2.88
UniTrust	Always-on	94.08	4.62
UniTrust	Gated	94.79	4.00

(b) Mean benign-input utility across six models and two domains

C.4 ABLATIONS BY MODEL FAMILY

For the supervision-budget sweep, $k \in \{1, 3, 5, 10, 20\}$ denotes the number of supplied examples per label. Across all budgets, we vary only the number of supplied examples while keeping the remaining experimental settings fixed.

For the intervention-strength sweep, we vary steering scale over $\{0, 0.5, 1, 2, 4, 8, 12, 16\}$ while keeping the intervention layers specified in Appendix A.3 fixed. Scale zero reuses the unsteered baseline. Unsafe compliance is measured on harmful prompts and appropriate help on benign prompts. Each model-family curve averages its safety-aligned and safety-weakened variants across both intervention tasks, and the aggregate curve in Figure 6(c) averages the three model families. The detector and gate threshold are held fixed across steering scales. Sampled scale values are displayed at equally spaced horizontal positions.

Rows in Figure 7 separate the three model families. Detection curves average ten domains; intervention curves average each family's two variants and two tasks. Averaging the rows gives Figure 6; Section 5.3 describes the settings and findings.



Figure 7: Detection and intervention ablations by model family. The scale column reports UniTrust held-out test results with the same layer settings as the main experiment; sampled scales use equally spaced ticks. Solid curves are gated and dashed curves are always-on, with a fixed gate across scales.

C.5 Confusion Counts



Figure 8: Detection confusion counts across models, methods, and domains.

Figure 8 contains all 90 model–domain–method conditions. Cells show true positives (TP), true negatives (TN), false positives (FP), and false negatives (FN), with a common count scale. Each domain has 200 positive and 200 negative test examples. The lower false-positive counts with UniTrust are consistent with the main detection results.

C.6 GUARD-JUDGED OUTPUT SAFETY

Figure 9 complements the task-specific outcomes in Figure 5 with Qwen3Guard-Gen-8B's unsafe-output judgments. It uses the same gated responses and matched unsteered baselines summarized in Table 2(b).



Figure 9: Guard unsafe rates at $k = 10$ on Harmful Request (left) and Safe/Sensitive Boundary (right), evaluated by Qwen3Guard-Gen-8B on the same 200 harmful inputs per model–domain as Figure 5. Within each model, bars run from Baseline to UniTrust w/o CGS to UniTrust (left to right); both intervention methods use their fixed gates. Both axes show percentages from 0 to 100; lower is better.

D LIMITATIONS

The current study focuses on text-based safety tasks and binary task formulations. While this setting covers a broad range of risk detection scenarios, real-world safety policies may involve multimodal inputs and more fine-grained distinctions among different types or levels of risk. Extending UniTrust to multimodal models, as well as to multi-class or multi-label task formulations, would broaden the scope of the framework. In addition, UniTrust currently operates in a white-box setting, since both the detection and intervention components rely on access to the target model's internal hidden representations. This design naturally assumes such internal access, making extensions to closed-source or API-only systems an interesting direction for future work.