RETHINKING MODEL EFFICIENCY: MULTI-AGENT INFERENCE WITH LARGE MODELS

Anonymous authors
Paper under double-blind review

ABSTRACT

Most vision-language models (VLMs) apply a large language model (LLM) as the decoder, where the response tokens are generated sequentially through autoregression. Therefore, the number of output tokens can be the bottleneck of the end-to-end latency. In this work, we conduct a comprehensive analysis of the latency across different components of VLMs. The empirical study on simulated data and real-world benchmarks confirms that a large model can achieve better or comparable performance as a small model with significantly fewer output tokens. To leverage the efficiency of large models, we propose a multi-agent inference framework that keeps large models with short responses but transfers the key reasoning tokens from the small model when necessary. Our theoretical analysis and the comparison on benchmarks demonstrate that by reusing the reasoning tokens from small models, it can help approach the performance of a large model with its own reasoning, which confirms the effectiveness of our proposal.

1 INTRODUCTION

With the success of large language models (LLMs), vision-language models (VLMs) have been proposed to understand visual input with LLMs as the decoder (Liu et al., 2023; Bai et al., 2025; Wang et al., 2025b; Team et al., 2026; Xu et al., 2026). By inheriting the structure of LLMs, the output text token for VLMs is also generated in an autoregressive way, which requires a forward pass of the LLM for each token, and thus is expensive for inference.

To reduce the cost of inference, many small VLMs were developed to reduce the total number of parameters for inference. For example, SmolVLM (Marafioti et al., 2025) focuses on delivering models with a limited number of parameters (*e.g.*, 500M and 256M), while showing promising performance on benchmarks. Meanwhile, leading VLM families also have small versions for efficiency. For example, InternVL3.5 series (Wang et al., 2025b) provides 1/2/4B models, and Qwen3-VL family (Qwen Team, 2025) also contains 2/4B models. Compared with their large-scale counterparts, those small ones can balance performance and the total number of parameters well.

In addition to the size of the model, the number of input tokens is also a critical factor contributing to the inference latency. This is because the essential block of the LLM in a VLM is the self-attention layer, whose computational cost is quadratic to the total number of input tokens. Moreover, visual input (*e.g.*, images) usually produces a massive number of vision tokens with a high redundancy ratio. Therefore, visual token pruning is an active research area, where it shows that more than 90% of visual tokens can be removed without significantly affecting performance (Yang et al., 2025a; Dong et al., 2025).

Although many efforts have been devoted to optimizing the size of models and the number of input tokens, they help only accelerate the inference of a single pass for an individual token. Since a complete response can contain multiple tokens, the end-to-end inference efficiency also depends on the total number of output tokens, which has been less investigated (Wilhelm et al., 2025), especially for VLMs. In contrast, a thinking step can be included in response to improve quality (Wei et al., 2022), but requires more thinking tokens and thus increases latency significantly.

In this work, we aim to consider the inference efficiency from the perspective of output tokens. To isolate the influence of training recipe, we compare models with different sizes from the same model family. Given the same input for different models, we will compare performance and latency

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: **A larger model thinks less but scores higher.** (a) Decoding time grows linearly with the number of output tokens; larger models cost more per token, yet 8B with 128 tokens is faster than 2B with 256. (b)–(d) Accuracy vs. average number of output tokens; each line goes Simple→Explain→Reasoning. Arrows point from the best 2B/4B result to the 8B setting with the fewest output tokens that beats it.

with different output tokens. First, with the simulation as in Figure 1 (a), we find that an 8B model with 128 output tokens can be more efficient than a 2B model with 256 output tokens. Due to the property of autoregressive generation, it is challenging to control the exact number of output tokens in real-world tasks. To mitigate this, we use different prompts to obtain answers with different scales of output tokens, *e.g.*, Simple (S), Explain (E), Reasoning (R). As shown in Figure 1 (b)-(d), we observe that a large model, *e.g.*, 8B, consistently achieves a better performance with fewer output tokens than the small model –**challenging the conventional assumption that small models are more inference-efficient**. To leverage the efficiency of large models with short output sequences, we propose a multi-agent framework with mutual verification and reasoning transfer. Our framework can enjoy the efficiency of large models with fewer tokens and that of small models with more reasoning tokens. The main contributions of this work can be summarized as follows.

- We apply 2/4/8B models from Qwen3-VL (Qwen Team, 2025) and 1/2/4/8/14B models from InternVL3.5 (Wang et al., 2025b) with different numbers of output tokens on diverse benchmark data sets for a comprehensive comparison about end-to-end inference efficiency.
- We observe that the degeneration performance of small models can come from the challenge of instruction following for the format of evaluation. A 2-stage strategy can improve small models substantially.
- Considering the decoding latency, we show that a large model with fewer output tokens can be more efficient than a small model with reasoning in terms of achieving a targeted performance.
- According to these observations, we propose a multi-agent inference framework that can transfer the selected reasoning tokens from small models to large models after mutual verification, which helps balance the performance and number of output tokens.
- Our theoretical analysis in Corollary 1 and empirical study on different tasks and models confirm the effectiveness of the proposed method for reasoning transfer.

2 Related Work

Input Visual Token Pruning. An important direction of work aims to accelerate inference by reducing the number of input tokens, particularly in the visual encoder. Since the computational complexity of the transformer's self-attention grows quadratically with the total token count, pruning redundant vision tokens can significantly reduce latency. Techniques such as patch merger (Qwen Team, 2025), and importance-based selection (Dong et al., 2025; Yang et al., 2025a) demonstrate that about 90% of visual tokens can be safely removed without significant performance degradation. These approaches are complementary to model compression, as they optimize the input representation side. However, even with aggressive pruning, the inference still scales linearly with the number of output tokens—a factor rarely examined for VLMs before our study. We empirically confirm this complementarity by combining our framework with vision token pruning in Appendix C.3.

Reasoning with Small Models. Considering the per-token efficiency of small models, some work also tries to leverage reasoning tokens from small models to help large models (Leviathan et al., 2023; Wang et al., 2025a; Liu et al., 2025a). For example, Wang et al. (2025a) fine-tunes a small draft

model to generate multiple candidate reasoning trails for the large model. Liu et al. (2025a) proposes a similar strategy but uses multiple small models to obtain candidate reasoning paths for large models. Jindal et al. (2025) also offloads thinking tokens to small models while the application is limited to reasoning models. More recently, speculative reasoning methods (Pan et al., 2025; Shi et al., 2025) accelerate chain-of-thought by drafting and verifying reasoning segments, while multi-model collaboration approaches coordinate models through token-level routing (Fu et al., 2026a) or external thought injection (Liu et al., 2025b). However, most of these methods operate at the individual token level and often require specific training. In contrast, our framework operates entirely at the response level, making it training-free and natively compatible with optimized serving engines like vLLM. Notably, these two paradigms are complementary: existing token-level speculative decoding techniques could be integrated within each model call in our framework to further reduce per-call latency. A direct comparison with speculative decoding is in Appendix C.9. More discussion on related work can be found in Appendix D.

3 Number of Output Tokens Matters

3.1 Preliminaries

Popular VLMs, including InternVL (Wang et al., 2025b) and QwenVL (Qwen Team, 2025), first use a vision encoder V to convert visual input I to vision tokens as

$$V(I) = [\mathbf{v}_1, \ldots, \mathbf{v}_m] \tag{1}$$

Meanwhile, tokens for the query Q, can be extracted by a text tokenizer T

$$T(Q) = [\mathbf{t}_1, \ldots, \mathbf{t}_n] \tag{2}$$

where $\forall i, j, \mathbf{v}_i, \mathbf{t}_j \in \mathbb{R}^d$.

Given the vision and query tokens as input, the first response token can be obtained from the LLM after the vision encoder as

$$r_1 = LLM([\mathbf{v}_1, \ldots, \mathbf{v}_m, \mathbf{t}_1, \ldots, \mathbf{t}_n]) \tag{3}$$

Then, the response will be generated in an autoregressive manner that predicts the next token according to all input tokens and previously generated tokens

$$r_s = LLM([\mathbf{v}_1, \ldots, \mathbf{v}_m, \mathbf{t}_1, \ldots, \mathbf{t}_n, \mathbf{r}_1, \ldots, \mathbf{r}_{s-1}])$$

The generation process will stop when a special token is obtained, *e.g.*, `<eot>`.

According to this process, it is obvious that the end-to-end latency of token generation from VLMs depends on: 1. The number of parameters in the vision encoder V; 2. The number of vision tokens from the input image m; 3. The number of text query tokens n; 4. The number of parameters in LLM; 5. The number of output tokens s. Although the first four factors are key for a single decoding pass, the total number of output tokens indicates how many trials are needed for decoding and is crucial for the inference efficiency.

3.2 VLM Inference Profile: Small vs. Large

We start our analysis with a detailed profiling of 2/4/8B Qwen3-VL models. According to the demonstration above, the inference process can be divided into four parts: input preprocessing, vision encoder, prefilling, and decoding. After warm-up processes, we report the running time of each part that is averaged over 100 runs using simulated data on a single H100.

Input Preprocessing Since we compare models from the same Qwen family, the input preprocessing pipeline is almost identical across models, and the latency is mainly from the input image size. As shown in Table 1, we can find that there is no significant difference between different model sizes, and we will omit this in the following discussion to simplify the latency analysis.

Vision Encoder The vision encoder is a transformer model that converts image patches to tokens. According to the Qwen design, the 2B and 4B models share the same architecture of the vision encoder (*i.e.*, SigLIP2-Large (300M)), while the 8B model has a larger vision encoder (*i.e.*, SigLIP2-SO-400M). We also notice the difference by our profiling in Table 2. Compared to the 2B model, the

Table 1: Qwen3-VL vision preprocessing latency (ms) with different image resolutions.

Qwen3-VL	256^2	512^2	1024^2	2048^2	4096^2
2B	0.84	1.49	7.21	64.83	335.19
4B	0.91	1.69	6.99	76.63	343.78
8B	0.92	1.58	6.46	75.59	341.61

Table 2: Qwen3-VL vision encoder latency (ms) with different image resolutions.

Qwen3-VL	256^2	512^2	1024^2	2048^2	4096^2
2B	12.69	12.84	24.41	172.28	1995.25
4B	12.36	12.56	24.91	180.10	2104.70
8B	13.79	14.26	34.40	272.90	3343.02

8B model can be about 60% slower with an extremely large input size, *e.g.*, 4096×4096. However, for other large resolutions, the gap is not that large. For example, with 1024×1024 as the input size, the difference between 2B and 8B is about 10ms, which is negligible. This observation implies that large models are still efficient with appropriate input resolutions, while small models are more efficient given very large input resolutions. The exploration of the trade-off between model size and image resolution is left for further work.

Table 3: Qwen3-VL Time-to-First-Token latency (ms) with different image resolutions and query token lengths. (Profiled to 8192 tokens, 1536 shown for brevity.)

Image Res.	256^2 (64 Tokens)			512^2 (256 Tokens)			1024^2 (1024 Tokens)		
Query Tokens	64	256	512	64	256	512	64	256	512
Total Tokens	128	320	576	320	512	768	1088	1280	1536
2B	27.52	27.79	27.92	28.22	28.00	28.89	45.96	46.97	49.80
4B	32.21	32.15	34.66	32.79	32.86	39.02	65.87	69.33	77.86
8B	33.76	36.25	47.93	36.74	43.91	53.45	94.27	102.65	115.31

Prefilling To show the prefilling latency, we report Time to First Token (TTFT), which accounts for the latency of a single forward pass and consists of four parts: input preprocessing, vision encoding, prefilling, and generating the first output token. The result is summarized in Table 3. Although the 8B model is 4 times larger than the 2B model in terms of parameters, the latency of large models increases slightly. Even with the large input resolution (*i.e.*, 1024×1024) and 512 query tokens, the TTFT of the 8B model is only about 2 times larger than the 2B model. With a small image resolution (*e.g.*, 256×256) and limited query tokens (*e.g.*, 64), the 8B model only costs an additional 6ms to obtain the first tokens compared to the 2B model, which shows the efficiency of large models. This observation inspires us to explore the potential of large models for obtaining a complete response by decoding multiple tokens.




Figure 2: Latency Profile.

Decoding Now we conduct a comparison on different numbers of generated tokens to demonstrate the efficiency of different models in real scenarios. According to Table 4, we can find that the number of output tokens dominates the overall latency. Although the 2B model can generate eight tokens within 140ms, it costs about 2000ms to obtain 128 tokens, which incurs more latency than any other factors discussed above. Compared with the 2B model, the 4B and 8B models are a bit slower in terms of averaged output tokens per second (Tok/s). However, the gap is mild and much smaller than that of the model size. Even with an 8B model, it can produce up to 47 tokens per second compared to 61 from a 2B model. This phenomenon confirms that the number of output tokens is essential for the latency of VLMs. With a different number of output tokens, a large model with 128 output tokens can be faster than a small model with 256 output tokens, as shown in Figure 1 (a).

Moreover, as shown in Figure 1 (b), the performance of large models with fewer output tokens can also be better than that of small ones with more tokens. Given these insights from our comparison, we propose a multi-agent inference framework to explore the inference efficiency with small and large models sufficiently.

Table 4: Qwen3-VL decoding time with different image resolutions and query token lengths.

Image Res.	256^2 (64 Image Tokens)								512^2 (256 Image Tokens)								Avg Tok/s
Input Tok.	128				320				320				512				
Output Tok.	8	128	256	512	8	128	256	512	8	128	256	512	8	128	256	512	
Qwen3-VL-2B	138.73	2030.41	4051.51	8072.48	139.68	2032.67	4052.28	8070.89	139.62	2038.54	4056.94	8080.48	138.45	2021.54	4035.18	8067.07	61.80
Qwen3-VL-4B	176.63	2636.46	5275.21	10515.65	177.41	2642.43	5266.63	10486.47	177.36	2644.82	5267.35	10487.88	176.38	2634.05	5261.63	10503.87	47.77
Qwen3-VL-8B	178.50	2651.51	5282.48	10517.45	180.89	2656.08	5300.42	10540.37	181.69	2660.82	5294.05	10563.77	186.50	2648.22	5271.76	10690.40	47.26

Takeaway 1: Decoding cost dominates end-to-end VLM latency. A larger model with fewer tokens can be faster than a smaller model with verbose reasoning.

However, large models with simple prompts are not always sufficient. As illustrated in Appendix F (Ex. 3), when both 8B-S and 2B-R fail on a challenging query, only 8B-R yields the correct answer. This motivates a key question: can the cheap reasoning tokens from the small model substitute for the expensive reasoning of the large model?

4 Multi-Agent Inference: Mutual Verification and Reasoning Transfer

Let VLM_l and VLM_s denote a large VLM and a small VLM, respectively. Since both models show small latency with short output sequences, we start with mutual verification.

4.1 Mutual Verification

First, we ask two models to answer the query directly without any reasoning, which can limit the number of output tokens.

$$A^l_{short} = \text{VLM}_l(\text{Q+Prompt}_{simple}); \quad A^s_{short} = \text{VLM}_s(\text{Q+Prompt}_{simple}) \tag{4}$$

where A^l_{short} and A^s_{short} are short answers from the large and small models, respectively. Prompt_{simple} is the prompt to let the model answer the query without thinking.

We extract key answers via standard parsing protocols (e.g., LMMs-Eval) and determine semantic equivalence using Exact Matching or ANLS (as per benchmark), ensuring the verification process incurs negligible computational overhead.

If A^s_{short} is semantically identical to A^l_{short}, there is an agreement between large and small models, and the final result is obtained with a limited number of output tokens.

When two responses are different, the models may need some thinking tokens to figure out the right answer. To avoid the long sequence inference from large models, we rely on small models for reasoning. However, we empirically observe that small models may not follow the output format after too much thought. To mitigate the issue, we decompose the process into two stages: reasoning + answer as follows.

$$R^s_{think} = VLM_s(\text{Q+Prompt}_{think}); \quad A^s_{think} = VLM_s(\text{Q+}R^s_{think}\text{+Prompt}_{simple}) \tag{5}$$

where Prompt_{think} is the prompt that allows the model to think before answering, and R^s_{think} is the corresponding output thinking tokens from a small model and can be a long sequence. After that, R^s_{think} is attached as the contextual prompt for the small model to answer the question again in A^s_{think}. With an appropriate KV cache, the gap to a single inference with a long output sequence should be small, but the instruction following can be better as shown in our experiments.

Now we have another answer from the small model, and we will verify it with the output from the large model again. If $A^s_{think} = A^l_{short}$, it will be returned as the final output. However, if those two answers are still different, we may need reasoning from large models.

4.2 Reasoning Transfer

Although the large model is efficient for short responses, it can be slow for reasoning by generating a lot of thinking tokens. Since prefilling is substantially cheaper than decoding (Table 3 vs. Table 4), we propose to transfer the reasoning process from the small model to the large model to avoid the costly sequential decoding entirely.

Concretely, we reuse the thinking tokens R^s_{think} from the small model as the contextual prompt for the large model and let it answer the question referring to the analysis of the small model.

$$A^l_{think} = \text{VLM}_l(\text{Q+}R^s_{think}\text{+Prompt}_{simple}) \tag{6}$$

where the exact reasoning-transfer prompts are listed in Appendix I.

Table 5: Comparison of the averaged number of generated tokens with Qwen3-VL models.

Qwen3-VL	POPE			MMMU			MMBench			ChartQA			InfoVQA_{val}			RealWorldQA		
	S	E	R	S	E	R	S	E	R	S	E	R	S	E	R	S	E	R
2B	1.0	105.4	266.1	101.7	1448.9	2019.1	3.7	449.6	569.3	3.5	95.8	256.3	3.4	74.7	192.5	1.4	155.6	244.4
4B	1.0	97.0	168.6	47.8	1122.9	1822.2	2.9	336.1	475.2	3.6	276.1	352.2	3.6	240.7	288.0	1.1	209.0	346.2
8B	1.0	34.4	149.3	45.8	944.6	1548.7	2.2	106.0	426.5	3.5	249.8	294.3	3.5	177.9	228.2	1.0	221.5	297.0

Compared with thinking from the large model directly, it saves the cost of generating thinking tokens iteratively

$$R^l_{think} = \text{VLM}_l(\text{Q+Prompt}_{think}) \tag{7}$$

However, R^l_{think} can be different from R^s_{think}, and R^s_{think} can contain noise for large models. Fortunately, thanks to self-attention, the attention pattern can be sparse and focus on a few useful tokens automatically.

Let $X_l = [\mathbf{x}^1_l, \ldots, \mathbf{x}^{n_l}_l]^\top \in \mathbb{R}^{n_l \times d}$ and $X_s = [\mathbf{x}^1_s, \ldots, \mathbf{x}^{n_s}_s]^\top \in \mathbb{R}^{n_s \times d}$ denote the token representations of R^l_{think} and R^s_{think}, respectively. d is the dimension of the features and n_l and n_s are the number of tokens from large and small models, respectively. Since the answer is generated by the prediction of the next token, we will investigate the last token from the prompt. Note that the target token itself is omitted from X_l and X_s for demonstration.

First, we can show that the difference after attention can be bounded by the 1-Wasserstein distance between their attention-weighted token distributions.

Theorem 1. Let outputs after attention be

$$\mathbf{p}_l = \texttt{softmax}(\mathbf{p}X_l^\top/\lambda)X_l; \quad \mathbf{p}_s = \texttt{softmax}(\mathbf{p}X_s^\top/\lambda)X_s \tag{8}$$

and the attention score be $a = \texttt{softmax}(\mathbf{p}X_l^\top/\lambda); \quad b = \texttt{softmax}(\mathbf{p}X_s^\top/\lambda)$, we have

$$\|\mathbf{p}_l - \mathbf{p}_s\|_2 \leq W_1(\mu_l, \mu_s), \quad \text{where} \quad \mu_l = \sum_{i=1}^{n_l} a_i \delta_{\mathbf{x}^i_l}, \quad \mu_s = \sum_{j=1}^{n_s} b_j \delta_{\mathbf{x}^j_s} \tag{9}$$

The detailed proof can be found in Appendix A. Theorem 1 shows that the difference of representations after the self-attention layer can be well bounded by the input sequence. If the reasoning token distribution from the small model is similar to that of the large model, the knowledge can be transferred effectively.

Moreover, due to the sparsity from the attention score, the difference in output can be further bounded with sparse entities as follows.

Corollary 1. Let l' and s' be subsets of reasoning tokens from l and s respectively with large original attention scores such that $\sum_{i:i\in l'} a_i \geq c, \sum_{j:j\in s'} b_j \geq c$. c is a positive constant in $[0.8, 1]$. Assuming the norm of tokens is bounded (see Appendix A.3), *i.e.* $\forall i, j \quad \|\mathbf{x}^i_l\|_2 \leq g, \|\mathbf{x}^j_s\|_2 \leq g$, we have

$$\|\mathbf{p}_l - \mathbf{p}_s\|_2 \leq W_1(\mu_{l'}, \mu_{s'}) + 4(1-c)g \tag{10}$$

Corollary 1 shows that an imperfect reasoning sequence generated by a small model can still benefit a large model. The bound depends on the discrepancy between the attention-weighted key-token distributions of the two sparse reasoning sequences, rather than on an exact match between the complete reasoning trajectories. Therefore, as long as the small-model reasoning captures key tokens that are close to those required by the large model and assigns compatible attention mass to them, i.e., $W_1(\mu_{l'}, \mu_{s'})$ remains small, and the resulting output can closely approximate that induced by the large model's own reasoning sequence.

This observation inspires us to select key reasoning tokens from R^s_{think} to reduce the number of transferred tokens for large models and potential noisy tokens.

$$R^{'s}_{think} = \text{Select}(R^s_{think}); \quad A^l_{think} = \text{VLM}_l(\text{Q+}R^{'s}_{think}\text{+Prompt}_{simple}) \tag{11}$$

where Select() can pick key tokens according to attention weights (*e.g.*, b^j_s) from R^s_{think}. The detailed selection strategy is demonstrated in Section 5.3.

Table 6: Comparison of performance with Qwen3-VL models. † denotes original results without 2-stage strategy.

Qwen3-VL	MMBench			MMMU			ChartQA			InfoVQA			RealWorldQA		
	S	E	R	S	E†	R†	S	E	R	S	E	R	S	E	R
2B	76.8	75.4	75.0	44.2	46.9	47.9	77.80	82.72	83.72	68.64	71.50	74.57	60.65	63.79	64.58
4B	83.7	85.0	84.5	48.3	60.0	61.3	83.12	83.04	83.16	79.96	82.87	83.08	71.24	70.59	69.93
8B	85.2	86.0	85.9	55.6	62.0	64.3	84.72	87.68	86.20	82.80	86.37	86.66	67.58	72.68	70.33

Figure 4 in appendix illustrates the framework of the proposed multi-agent inference strategy. We keep large models to output short sequences while using small models for reasoning. With reasoning transfer, we can simplify the framework by adopting R^s_{think} in lieu of A^s_{think} for mutual verification to further reduce output tokens from the small model.

5 Experiments

In this section, we conduct experiments on popular benchmarks to demonstrate the performance and efficiency of different models. The detailed settings are elaborated as follows.

Evaluation Platform. We utilize LMMs-Eval (Zhang et al., 2024), a VLM evaluation framework, and vLLM (Kwon et al., 2023) to evaluate models on H100 (96G). Unless otherwise specified, all sample parameters and task setups follow the official instructions. Latency measurement details are in Appendix C.8.

Benchmark Tasks. To evaluate the performance of models with varying sizes extensively, we have 6 diverse tasks with different output formats in the comparison. POPE (Li et al., 2023) is a yes/no benchmark that aims to evaluate hallucination. MMBench (Liu et al., 2024) covers general multimodal understanding tasks in a multiple-choice format. Beside the simple output format, we have MMMU (Yue et al., 2024) and RealWorldQA [1] to evaluate the comprehensive reasoning ability of models with both multi-choice and open-ended questions. Finally, two data sets with open-ended questions, *i.e.*, ChartQA (Masry et al., 2022) and InfographicVQA (Mathew et al., 2022), are included for further demonstration.

Vision Language Model Families. Two popular open-sourced VLM families with diverse model sizes are included: three models from Qwen3-VL, *i.e.*, **Qwen3-VL-2/4/8B-Instruct** (Qwen Team, 2025), and five models from InternVL3.5, *i.e.*, **InternVL3.5-1/2/4/8/14B** (Wang et al., 2025b). Additional experiments with Gemma 3-4B/12B (Team et al., 2025) can be found in Appendix C.2.

Prompts for Output Token Control. We design three prompts for each question to control the number of generated tokens as follows; full templates, including the Stage-2 and reasoning-transfer prompts, are in Appendix I.

- **Simple** (**S**): **Without thinking, directly** answer the question using a single word or phrase in the format: [[answer]]
- **Explain** (**E**): **Provide a simple explanation**, then answer the question using a single word or phrase in the format: [[answer]]
- **Reasoning** (**R**): **Please think step by step, provide a detailed explanation**, then answer the question using a single word or phrase in the format: [[answer]]

5.1 Performance vs. Output Tokens

First, we compare the performance on Qwen 2/4/8B models. It is challenging to control the exact number of output tokens. We use different prompts and Table 5 shows the averaged number of output tokens on different tasks. We can find that "Simple" prompt can limit the number of output tokens effectively, where models generate no more than 10 tokens on 5 out of 6 tasks. With "Reasoning" prompt, the number of output tokens increases significantly while the "Explain" prompt obtains an expected number of tokens that is between "Simple" and "Reasoning" in most cases. The comparison shows that our proposed prompts can adjust the number of output tokens appropriately.

[1] https://huggingface.co/datasets/xai-org/RealworldQA

With these prompts, we first evaluate the performance of models with different output tokens on POPE in Table 7. From the comparison, we can observe that with more output tokens, the performance for 8B model improves. However, the performance on other model sizes is not monotonic with respect to the number of output tokens. The primary bottleneck is an *instruction-following (IF) failure*: after generating a long reasoning chain, the small model frequently forgets to output the final answer in the required format (see Example 2 in Appendix F for a qualitative illustration).

Table 7: Comparison of performance with Qwen3-VL models on POPE. (S2) denotes the 2-stage strategy as in Eqn. 5.

Qwen3-VL	POPE				
	S	E	E(S2)	R	R(S2)
2B	88.6	88.8	89.2	88.4	89.9
4B	88.7	88.0	89.6	87.8	88.9
8B	87.1	87.3	87.8	88.2	89.5

To disentangle genuine reasoning capability from formatting limitations, we apply a 2-stage decoding strategy (Eqn. 5), denoted as (S2) in Table 7. The first stage generates raw reasoning, and the second stage forces formatted answer extraction. With KV-cache reuse, the additional overhead is only 47 ms (Appendix C.7). The comparison confirms that models *do* benefit from thinking tokens once formatting errors are eliminated. Unless otherwise noted (marked with †), all Explain (E) and Reasoning (R) results reported in this paper adopt S2.

Then, we report the results on remaining data sets in Table 6 with 2-stage strategy for E and R if not specified. We can find that with more tokens from E and R, the 2B model still lags behind in performance on those tasks compared to 8B one with the Simple prompt, *i.e.* 8B(S). According to the decoding profiling in Table 4, the 8B model can be more efficient than 2B with reasoning, *e.g.*, 3.5/47.26 v.s. 256.3/61.80 on ChartQA. The comparison demonstrates that a large model can be efficient with fewer output tokens but still provide good performance. The comparison on InternVL3.5 and Gemma 3 can be found in Appendix C.1 and C.2.

5.2 Reasoning Transfer

While large models perform well with simple prompts, more reasoning tokens can further improve their performance (Table 6). Concretely, we reuse the cheap reasoning tokens R^s_{think} generated by the small model and prepend them as the contextual prompt for the large model (Eqn. 6), which then directly answers the query using the Simple prompt. The comparison using the Qwen models is reported in Table 8. The results are consistent with Corollary 1. Although original reasoning tokens from the 2B model (2B-R) yield worse standalone performance than 4B-S and 8B-S on most tasks, using them as the prompt for the 8B model improves the baseline performance substantially on most cases. The remaining degradation cases mainly stem from incorrect fine-grained visual grounding in the small model's reasoning, which misleads the large model; a failure-case analysis is given in Appendix G.

Table 8: Comparison of reasoning transfer with the 2-stage strategy as in Eqn. 5. Reasoning-transfer rows require no S2. Percentage changes show improvement (green) or degradation (red) compared to baseline with the "Simple" prompt, *i.e.*, "-S".

Qwen3-VL	POPE	MMMU	MMBench	ChartQA	InfoVQA	RealWorldQA
2B-R(w/o S2)	88.4	47.9	72.8	72.2	71.4	60.5
4B-S	88.7	48.3	83.7	83.1	80.0	71.2
4B-R	88.9	61.3	84.5	83.2	83.1	69.9
4B + 2B-R	**91.0** +2.6%	**55.9** +15.7%	**84.1** +0.5%	82.4 -0.8%	79.7 -0.4%	**71.6** +0.6%
8B-S	87.1	55.6	85.2	84.7	82.8	67.6
8B-R	89.5	64.3	85.9	86.2	86.7	70.3
8B + 2B-R	**89.2** +2.4%	**62.9** +13.1%	85.1 -0.1%	**85.3** +0.7%	**82.8** +0.0%	**68.9** +1.9%
8B + 4B-R	**87.9** +0.9%	**62.9** +13.1%	85.1 -0.1%	**86.0** +1.5%	**84.1** +1.6%	**70.2** +3.8%

Table 9: Multi-Agent Inference based on Qwen3-VL-2B/8B. "MV" denotes the mutual verification and "RT" is for reasoning transfer. The best result is in bold.

Dataset	#Test	Multi-Agent Inference (MAI)				Baseline			Full RT
		$MV_{2B(S)/8B(S)}$	$MV_{2B(R)/8B(S)}$	RT	Final Perf.	2B(S)	2B(R)	8B(S)	8B+2B-R
POPE	9000	8507 (94.52%)	46 (0.51%)	447 (4.97%)	88.7	88.6	88.4	87.1	**89.2**
MMMU	900	498 (55.33%)	142 (15.78%)	260 (28.89%)	62.0	44.2	47.9	55.6	**62.9**
MMBench	4328	3736 (86.32%)	262 (6.05%)	330 (7.62%)	**85.5**	76.8	72.8	85.2	85.1
ChartQA	2500	1800 (72.00%)	195 (7.80%)	505 (20.20%)	**86.8**	77.8	72.2	84.7	85.3
InfoVQA	2801	1728 (61.69%)	271 (9.68%)	802 (28.63%)	**82.9**	68.6	71.4	82.8	82.8
RealWorldQA	765	509 (66.54%)	105 (13.73%)	151 (19.74%)	68.4	60.7	60.5	67.6	**68.9**

5.3 Sparse Reasoning Transfer

To further reduce the input tokens for the large model and the noise in small-model reasoning, we transfer only a sparse subset of key tokens: reasoning tokens are ranked by attention weight, and the top tokens covering 80% of the total weight (*i.e.*, $c = 0.8$ in Corollary 1) are kept.

Since every layer has its own attention map, we ablate the layer used for selection on POPE in Figure 3. All sparse variants outperform the 8B-S baseline (87.1) and remain comparable to full transfer with far fewer tokens, consistent with our theoretical analysis. Token usage is U-shaped across depth: layers L10–L14 select the fewest tokens (∼90 vs. 266 for full transfer) at comparable F1, offering the best trade-off. Head-wise details are in Sec. H.




Figure 3: Sparse reasoning transfer (8B+2B-R) on POPE across the attention layer used for token selection. Top: tokens kept (80% attention mass); bottom: F1. Dashed/dotted lines: full transfer and 8B-S.

5.4 Multi-Agent Inference

Finally, we evaluate the proposed multi-agent framework that leverages mutual verification and reasoning transfer to minimize the number of output tokens from large models. The comparison is mainly based on Qwen models. We consider the agent system consists of 2B-8B models. The detailed results are shown in Table 9.

First, compared with the strong baseline, *i.e.* 8B(S), the multi-agent inference can improve the performance consistently. It implies that with the help of the small model, the large model can leverage the transferred tokens effectively for challenging queries. Second, mutual verification (MV) can reduce the number of expensive model calls, *e.g.* 2B(R) and reasoning transfer (RT) for the 8B model, significantly. For example, at least 55% of inferences achieve agreement between large and small models with the simple prompt over different tasks. There are up to 16% test examples that can obtain the same results after reasoning by small models. Less than 30% of queries will call large models with reasoning transfer. Replacing 2B-R with 2B-R(S2) in the cascade further improves the verification success rate and reduces reasoning-transfer calls on most tasks (Appendix C.7).

Remarkably, compared with the full reasoning transfer, our multi-agent system shows a comparable or even better performance (Full RT, *e.g.*, 86.8% vs. 85.3% on ChartQA), which confirms the effectiveness of mutual verification. Results on Gemma 3, with bootstrap CIs and MV/RT ablations, are in Appendix C.2 and C.4; cross-family results are in Appendix C.5.

Takeaway 2: Reasoning tokens from small models can be transferred to large models as input context, converting expensive sequential decoding into cheap prefilling.

Latency Estimation: A Conservative Upper Bound. To quantify end-to-end efficiency independent of serving frameworks or hardware optimizations, we adopt a strictly conservative upper bound for the total inference time (Appendix C.6), reported in Table 10. MAI significantly accelerates inference over full reasoning transfer, with speedups from 1.76× (MMMU) to 8.05× (POPE). Measured wall-clock latency on vLLM confirms this: 2.40× over 8B-R on ChartQA with higher accuracy (Table 21) and 1.65× on Gemma 3-12B (Appendix C.8, C.10). Compatibility with visual-token pruning and deployment considerations are discussed in Appendix C.3 and E.

Table 10: Comparison of total inference time (s).

Method	POPE	MMBench	MMMU	ChartQA	InfoVQA
Full RT (s)	39,865	40,718	43,924	10,805	9,201
MAI (s)	**4,954**	**8,676**	**25,025**	**4,158**	**5,094**
Speedup	**8.05×**	**4.69×**	**1.76×**	**2.60×**	**1.81×**

6 Conclusion

In this work, we revisit the often-overlooked role of output token length in the end-to-end inference efficiency of VLMs. Our profiling analysis demonstrates that the number of generated tokens is a critical factor for latency. According to this observation, we developed a multi-agent inference framework with mutual verification and reasoning transfer to leverage small and large models to balance performance and efficiency in inference. Combining other agents, e.g., Jev (TypeSafeAI, 2026) in the system for inference acceleration can be our future work.

AI USE STATEMENT

LLMs were used only to polish the writing and assist with coding. All ideas, analyses, and results are the authors' own, and the authors take full responsibility for the content.

ETHICS STATEMENT

This work studies inference efficiency of VLMs using public open-source models and benchmarks. It involves no human subjects or private data, and we are not aware of any ethical concerns.

REPRODUCIBILITY STATEMENT

All models and benchmarks are publicly available. Experimental details, hyper-parameters, hardware, and all prompt templates are provided in Section 5 and Appendices C and I, and full proofs are in Appendix A. Code will be released upon publication.

REFERENCES

Yash Akhauri, Anthony Fei, Chi-Chih Chang, Ahmed F AbouElhamayed, Yueying Li, and Mohamed S Abdelfattah. Splitreason: Learning to offload reasoning. *arXiv preprint arXiv:2504.16379*, 2025.

Saeed Ranjbar Alvar, Gursimran Singh, Mohammad Akbari, and Yong Zhang. Divprune: Diversity-based visual token pruning for large multimodal models. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9392–9401. IEEE, 2025.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Ming-Hsuan Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-vl technical report. *CoRR*, abs/2502.13923, 2025.

Zhuokun Chen, Zeren Chen, Jiahao He, Lu Sheng, Mingkui Tan, Jianfei Cai, and Bohan Zhuang. R-stitch: Dynamic trajectory stitching for efficient reasoning. *arXiv preprint arXiv:2507.17307*, 2025.

Sixun Dong, Juhua Hu, Mian Zhang, Ming Yin, Yanjie Fu, and Qi Qian. Mmtok: Multimodal coverage maximization for efficient inference of vlms. *CoRR*, abs/2508.18264, 2025.

Benjamin L Edelman, Surbhi Goel, Sham Kakade, and Cyril Zhang. Inductive biases and variable creation in self-attention mechanisms. In *International Conference on Machine Learning*, pp. 5793–5831. PMLR, 2022.

Claudio Fanconi and Mihaela van der Schaar. Cascaded language models for cost-effective human–ai decision-making. *Advances in Neural Information Processing Systems*, 38:11559–11593, 2026.

Tianyu Fu, Yi Ge, Yichen You, Enshu Liu, Zhihang Yuan, Guohao Dai, Shengen Yan, Huazhong Yang, and Yu Wang. R2r: Efficiently navigating divergent reasoning paths with small-large model token routing. *Advances in Neural Information Processing Systems*, 38:124108–124145, 2026a.

Yichao Fu, Rui Ge, Zelei Shao, Zhijie Deng, and Hao Zhang. Scaling speculative decoding with lookahead reasoning. *Advances in Neural Information Processing Systems*, 38:172454–172486, 2026b.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Chengsong Huang, Tong Zheng, Langlin Huang, Jinyuan Li, Haolin Liu, and Jiaxin Huang. Relayllm: Efficient reasoning via collaborative decoding. *arXiv preprint arXiv:2601.05167*, 2026.

Ishan Jindal, Jayant Taneja, Badrinath Chandana, Vikas Kapur, and Sachin Dev Sharma. Offloaded reasoning: Efficient inference for large language models via modular reasoning and refinement. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 7450–7458, 2025.

Yujin Kim, Euiin Yi, Minu Kim, Se-Young Yun, and Taehyeon Kim. Guiding reasoning in small language models with llm assistance. *arXiv preprint arXiv:2504.09923*, 2025.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35: 22199–22213, 2022.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*, 2023.

Byeongchan Lee, Jonghoon Lee, Dongyoung Kim, Jaehyung Kim, Kyungjoon Park, Dongjun Lee, and Jinwoo Shin. Efficient llm collaboration via planning. *arXiv preprint arXiv:2506.11578*, 2025.

Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In *International Conference on Machine Learning*, pp. 19274–19286. PMLR, 2023.

Ming Li, Zhengyuan Yang, Xiyao Wang, Dianqi Li, Kevin Lin, Tianyi Zhou, and Lijuan Wang. What makes reasoning models different? follow the reasoning leader for efficient decoding. *arXiv preprint arXiv:2506.06998*, 2025.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. Evaluating object hallucination in large vision-language models. *arXiv:2305.10355*, 2023.

Baohao Liao, Yuhui Xu, Hanze Dong, Junnan Li, Christof Monz, Silvio Savarese, Doyen Sahoo, and Caiming Xiong. Reward-guided speculative decoding for efficient llm reasoning. *arXiv preprint arXiv:2501.19324*, 2025.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. In Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (eds.), *NeurIPS*, 2023.

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, et al. Mmbench: Is your multi-modal model an all-around player? In *ECCV*, pp. 216–233. Springer, 2024.

Yuhan Liu, Lianhui Qin, and Shengjie Wang. Small drafts, big verdict: Information-intensive visual reasoning via speculation. *arXiv preprint arXiv:2510.20812*, 2025a.

Yule Liu, Jingyi Zheng, Zhen Sun, Zifan Peng, Wenhan Dong, Zeyang Sha, Shiwen Cui, Weiqiang Wang, and Xinlei He. Thought manipulation: External thought can be efficient for large reasoning models. *arXiv preprint arXiv:2504.13626*, 2025b.

Monishwaran Maheswaran, Rishabh Tiwari, Yuezhou Hu, Kerem Dilmen, Coleman Hooper, Haocheng Xi, Nicholas Lee, Mehrdad Farajtabar, Michael W Mahoney, Kurt Keutzer, et al. Arbitrage: Efficient reasoning via advantage-aware speculation. *arXiv preprint arXiv:2512.05033*, 2025.

Andrés Marafioti, Orr Zohar, Miquel Farré, Merve Noyan, Elie Bakouch, Pedro Cuenca, Cyril Zakka, Loubna Ben Allal, Anton Lozhkov, Nouamane Tazi, Vaibhav Srivastav, Joshua Lochner, Hugo Larcher, Mathieu Morlon, Lewis Tunstall, Leandro von Werra, and Thomas Wolf. Smolvlm: Redefining small and efficient multimodal models. *arXiv preprint arXiv:2504.05299*, 2025.

Ahmed Masry, Xuan Long Do, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. In *Findings of the association for computational linguistics: ACL 2022*, pp. 2263–2279, 2022.

Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and CV Jawahar. Infographicvqa. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1697–1706, 2022.

Harikrishna Narasimhan, Wittawat Jitkrittum, Ankit Singh Rawat, Seungyeon Kim, Neha Gupta, Aditya Krishna Menon, and Sanjiv Kumar. Faster cascades via speculative decoding. In *International Conference on Learning Representations*, volume 2025, pp. 44949–44987, 2025.

Rui Pan, Yinwei Dai, Zhihao Zhang, Gabriele Oliaro, Zhihao Jia, and Ravi Netravali. Specreason: Fast and accurate inference-time compute via speculative reasoning. *arXiv preprint arXiv:2504.07891*, 2025.

Qwen Team. Qwen3-vl: Multimodal vision-language model series. Alibaba Cloud, 2025.

Jianshu She, Zhuohao Li, Zhemin Huang, Qi Li, Peiran Xu, Haonan Li, and Qirong Ho. Hawkeye: Efficient reasoning with model collaboration. *arXiv preprint arXiv:2504.00424*, 2025.

Junhan Shi, Yijia Zhu, Zhenning Shi, Dan Zhao, Qing Li, and Yong Jiang. Speccot: Accelerating chain-of-thought reasoning through speculative exploration. In *EMNLP (Findings)*, pp. 24405–24415, 2025.

Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, et al. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, 2025.

Kimi Team, Tongtong Bai, Yifan Bai, Yiping Bao, Jianfeng Cai, Xinyuan Cai, Peizhou Cao, Yuxuan Cao, Ziwei Chai, Y Charles, et al. Kimi k3: Open frontier intelligence. *arXiv preprint arXiv:2607.24653*, 2026.

TypeSafeAI. Introducing system one models & jev, September 2026.

Jikai Wang, Juntao Li, Lijun Wu, and Min Zhang. Efficient reasoning for llms through speculative chain-of-thought. *CoRR*, abs/2504.19095, 2025a.

Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, Zhaokai Wang, Zhe Chen, Hongjie Zhang, Ganlin Yang, Haomin Wang, Qi Wei, Jinhui Yin, Wenhao Li, Erfei Cui, Guanzhou Chen, Zichen Ding, Changyao Tian, Zhenyu Wu, JingJing Xie, Zehao Li, Bowen Yang, Yuchen Duan, Xuehui Wang, Zhi Hou, Haoran Hao, Tianyi Zhang, Songze Li, Xiangyu Zhao, Haodong Duan, Nianchen Deng, Bin Fu, Yinan He, Yi Wang, Conghui He, Botian Shi, Junjun He, Yingtong Xiong, Han Lv, Lijun Wu, Wenqi Shao, Kaipeng Zhang, Huipeng Deng, Biqing Qi, Jiaye Ge, Qipeng Guo, Wenwei Zhang, Songyang Zhang, Maosong Cao, Junyao Lin, Kexian Tang, Jianfei Gao, Haian Huang, Yuzhe Gu, Chengqi Lyu, Huanze Tang, Rui Wang, Haijun Lv, Wanli Ouyang, Limin Wang, Min Dou, Xizhou Zhu, Tong Lu, Dahua Lin, Jifeng Dai, Weijie Su, Bowen Zhou, Kai Chen, Yu Qiao, Wenhai Wang, and Gen Luo. Internvl3.5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *CoRR*, abs/2508.18265, 2025b.

Zhihai Wang, Jie Wang, Jilai Pan, Xilin Xia, Huiling Zhen, Mingxuan Yuan, Jianye Hao, and Feng Wu. Accelerating large language model reasoning via speculative search. *arXiv preprint arXiv:2505.02865*, 2025c.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (eds.), *NeurIPS*, 2022.

Patrick Wilhelm, Thorsten Wittkopp, and Odej Kao. Beyond test-time compute strategies: Advocating energy-per-token in LLM inference. In Eiko Yoneki and Amir H. Payberah (eds.), *Workshop on Machine Learning and Systems, EuroMLSys*, pp. 208–215. ACM, 2025.

Anyi Xu, B Li, Bangcai Lin, Bing Xue, BingCheng Xian, Bingzheng Xu, Bochao Wu, Bowei Zhang, Boyi Deng, CC Yu, et al. Deepseek-v4. 1-flash: Pushing the limits of kv cache compression. *arXiv preprint arXiv:2609.19969*, 2026.

Senqiao Yang, Yukang Chen, Zhuotao Tian, Chengyao Wang, Jingyao Li, Bei Yu, and Jiaya Jia. Visionzip: Longer is better but not necessary in vision language models. In *CVPR*, pp. 19792–19802. Computer Vision Foundation / IEEE, 2025a.

Wang Yang, Xiang Yue, Vipin Chaudhary, and Xiaotian Han. Speculative thinking: Enhancing small-model reasoning with large model guidance at inference time. *arXiv preprint arXiv:2504.12329*, 2025b.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, et al. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. In *CVPR*, pp. 9556–9567, 2024.

Kaichen Zhang, Bo Li, Peiyuan Zhang, Fanyi Pu, Joshua Adrian Cahyono, Kairui Hu, Shuai Liu, Yuanhan Zhang, Jingkang Yang, Chunyuan Li, and Ziwei Liu. Lmms-eval: Reality check on the evaluation of large multimodal models, 2024.

A Theoretical Analysis

A.1 Theorem 1

Proof. Given a and b are attention scores, $\forall i, j \;\; a_i, b_j \geq 0$ and $\sum_i a_i = \sum_j b_j = 1$, we have

$$\mathbf{p}_l = \sum_{i=1}^{n_l} a_i \mathbf{x}_l^i, \qquad \mathbf{p}_s = \sum_{j=1}^{n_s} b_j \mathbf{x}_s^j.$$

Consider the set of couplings between a and b,

$$\Pi(a,b) = \left\{ q \in \mathbb{R}_+^{n_l \times n_s} : \sum_{j=1}^{n_s} q_{ij} = a_i \text{ and } \sum_{i=1}^{n_l} q_{ij} = b_j \right\}.$$

For any $q \in \Pi(a,b)$, the marginal constraints imply

$$\mathbf{p}_l - \mathbf{p}_s = \sum_{i=1}^{n_l} a_i \mathbf{x}_l^i - \sum_{j=1}^{n_s} b_j \mathbf{x}_s^j = \sum_{i=1}^{n_l} \sum_{j=1}^{n_s} q_{ij} \left(\mathbf{x}_l^i - \mathbf{x}_s^j \right) \tag{12}$$

Applying the triangle inequality and using $q_{ij} \geq 0$, we obtain

$$\|\mathbf{p}_l - \mathbf{p}_s\|_2 \leq \sum_{i=1}^{n_l} \sum_{j=1}^{n_s} q_{ij} \|\mathbf{x}_l^i - \mathbf{x}_s^j\|_2$$

Because this inequality holds for every $q \in \Pi(a,b)$, minimizing its right-hand side over all such couplings yields

$$\|\mathbf{p}_l - \mathbf{p}_s\|_2 \leq \min_{q \in \Pi(a,b)} \sum_{i=1}^{n_l} \sum_{j=1}^{n_s} q_{ij} \|\mathbf{x}_l^i - \mathbf{x}_s^j\|_2 = W_1(\mu_l, \mu_s),$$

where

$$\mu_l = \sum_{i=1}^{n_l} a_i \delta_{\mathbf{x}_l^i}, \qquad \mu_s = \sum_{j=1}^{n_s} b_j \delta_{\mathbf{x}_s^j}$$

Thus, the Euclidean distance between the two attention outputs is bounded by the 1-Wasserstein distance between their attention-weighted token distributions. □

A.2 Corollary 1

Proof. Let

$$\mathbf{p}_l' = \texttt{softmax}(\mathbf{p} X_{l'}^\top / \lambda) X_{l'} = \sum_i a_i' \mathbf{x}_{l'}^i; \quad \mathbf{p}_s' = \texttt{softmax}(\mathbf{p} X_{s'}^\top / \lambda) X_{s'} = \sum_j b_j' \mathbf{x}_{s'}^j \tag{13}$$

Then, we have

$$\|\mathbf{p}_l - \mathbf{p}_s\|_2 = \|\mathbf{p}_l - \mathbf{p}_l' + \mathbf{p}_l' - \mathbf{p}_s' + \mathbf{p}_s' - \mathbf{p}_s\|_2 \leq \|\mathbf{p}_l' - \mathbf{p}_s'\|_2 + \|\mathbf{p}_l - \mathbf{p}_l'\|_2 + \|\mathbf{p}_s' - \mathbf{p}_s\|_2 \tag{14}$$

By arranging the index of tokens, we can keep the selected tokens at top k (i.e., $|l'| = k$) such that

$$\|\mathbf{p}_l - \mathbf{p}_l'\|_2 = \|\sum_i^k (a_i - a_i') \mathbf{x}_l^i + \sum_{i=k+1}^{n_l} a_i \mathbf{x}_l^i\|_2 \leq \|\sum_i^k (a_i - a_i') \mathbf{x}_l^i\|_2 + \|\sum_{i=k+1}^{n_i} a_i \mathbf{x}_l^i\|_2 \tag{15}$$

According to the assumption that $\sum_{i:i \in l'} a_i \geq c$, we have

$$\|\sum_{i=k+1}^{n_i} a_i \mathbf{x}_l^i\|_2 \leq g \sum_{i=k+1}^{n_i} a_i \leq (1-c) g \tag{16}$$




Figure 4: Illustration of the proposed multi-agent inference framework. (a) shows our empirical observation that a large model with a short response can achieve a similar performance as the small model with additional reasoning tokens. (b) demonstrates the proposed reasoning transfer strategy that can reuse the reasoning tokens output by the small model for the large model to improve its performance. (c) Our final proposal adopts mutual verification to further reduce the number of expensive model calls for efficient inference.

For the selected tokens, since the similarity score, i.e., $\mathbf{p}^\top \mathbf{x}^i$, does not change, softmax operator only amplifies the weight to make it sum to 1: $\forall i \in l', \quad a'_i \geq a_i$. So we have

$$\| \sum_{i}^{k} (a_i - a'_i)\mathbf{x}_l^i \|_2 \leq (1-c)g \tag{17}$$

Combining Eqns. 16 and 17, we have

$$\|\mathbf{p}_l - \mathbf{p}'_l\|_2 \leq 2(1-c)g \tag{18}$$

With the similar analysis, we have

$$\|\mathbf{p}_s - \mathbf{p}'_s\|_2 \leq 2(1-c)g \tag{19}$$

Taking them back to Eqn. 14 and applying Theorem 1 on $\|\mathbf{p}'_l - \mathbf{p}'_s\|_2$ obtain the final result. □

A.3 Assumptions and Extensions

We briefly discuss several assumptions used in the theoretical analysis and their practical implications.

- **Bounded norms.** We assume that the token representations have bounded norms. Similar boundedness assumptions are commonly adopted in theoretical analyses of self-attention, e.g., Sec. 4 of (Edelman et al., 2022). In practice, normalization layers such as RMSNorm or LayerNorm before the attention module also help keep token representations well scaled.
- **Single-head attention.** For clarity, our theoretical analysis is presented for a single attention head. The same argument can be applied independently to each head in a multi-head attention module, followed by aggregation across heads. The multi-head setting is also empirically illustrated in Figures 6 and 7.

B Illustration of Our Framework

Figure 4 illustrates the framework of the proposed multi-agent inference strategy.

C More Experiments

Prompts for Output Token Control Previous work (Guo et al., 2025) shows that the test-time scaling criterion is an effective strategy to enhance model capacity with more inference tokens. To trade off between performance and the number of output tokens, we design three different prompts for

Table 11: Comparison of the averaged number of generated tokens with InternVL3.5 models.

InternVL3.5	POPE			MMMU			MMBench			ChartQA			InfoVQA			RealWorldQA		
	S	E	R	S	E	R	S	E	R	S	E	R	S	E	R	S	E	R
1B	1.1	26.0	39.7	2.5	302.2	425.8	3.9	31.1	82.3	3.5	37.9	66.2	3.5	57.8	42.5	1.4	36.4	69.5
2B	1.0	12.2	45.2	262.2	389.9	508.8	14.0	66.6	163.1	3.5	121.4	143.3	4.4	78.2	137.6	1.8	67.6	122.5
4B	1.0	23.3	57.1	5.9	358.9	491.7	2.3	55.1	154.7	3.6	173.4	200.1	3.9	152.6	181.6	1.3	70.0	103.9
8B	1.1	30.5	46.1	10.6	262.0	385.5	2.2	49.5	141.7	3.9	120.3	158.2	3.5	108.6	142.0	1.6	54.3	75.7
14B	1.4	19.3	47.0	11.2	419.0	484.1	2.5	46.7	161.0	3.6	126.7	147.7	3.4	52.5	117.6	3.8	60.8	71.9

Table 12: Comparison of performance with InternVL3.5 models. † denotes original results without 2-stage strategy.

InternVL	POPE			MMMU			MMBench			ChartQA			InfoVQA			RealWorldQA		
	S	E	R	S	E†	R†	S	E	R	S	E	R	S	E	R	S	E	R
1B	83.8	85.6	83.0	39.3	43.0	41.6	68.2	67.8	68.1	70.7	65.5	67.2	56.1	51.9	51.7	51.9	58.3	56.1
2B	88.9	89.3	90.7	51.2	52.0	54.3	75.7	78.4	77.1	80.9	82.7	85.5	41.4	65.5	65.8	50.2	55.4	48.8
4B	88.8	93.1	91.7	55.8	60.4	59.4	76.5	81.7	82.5	83.7	88.6	87.8	68.9	73.6	73.9	59.5	60.7	42.6
8B	88.6	90.7	88.5	56.8	60.9	60.2	74.7	83.0	83.5	77.2	83.9	83.8	57.4	74.7	75.4	59.9	63.8	58.8
14B	85.8	86.5	88.3	58.2	62.2	61.6	82.8	84.0	83.7	87.3	88.8	88.4	69.6	74.1	77.1	52.8	67.7	67.8

each question to control different numbers of generated tokens. Concretely, we have **Simple** (**S**) to let the model respond to the query without thinking. **Explain** (**E**) aims to encourage models to provide a simple explanation before giving the final answer. Following Kojima et al. (2022), **Reasoning** (**R**) is applied to explicitly prompt models to think and explain with more thinking tokens. Finally, we add an answer format, *i.e.*, `[[answer]]`, to help parse the answer from a long response. The details are as follows.

- **Simple** (**S**): **Without thinking, directly** answer the question using a single word or phrase in the format: [[answer]]
- **Explain** (**E**): **Provide a simple explanation**, then answer the question using a single word or phrase in the format: [[answer]]
- **Reasoning** (**R**): **Please think step by step, provide a detailed explanation**, then answer the question using a single word or phrase in the format: [[answer]]

C.1 Comparison within InternVL3.5 Family

Besides Qwen family, we conduct a similar comparison with InternVL3.5 models. The number of output tokens and the performance are summarized in Table 11 and Table 12, respectively.

First, Table 11 shows that our prompts are still effective in adjusting the number of output tokens for InternVL models. With the appropriate prompts, we can compare models with different output tokens in Table 12. The phenomenon is similar to that on Qwen3-VL models. 4B(S)/8B(S)/14B(S) can match or even outperform smaller models with more reasoning tokens, *e.g.*, 1B(R), 2B(R), *etc*. For example, on MMMU, the 4B(S) model with about 6 tokens outperforms the 1B(E) and 2B(R) models, even when they have approximately 300 and 500 thinking tokens, respectively. It confirms our observation that large models that require fewer output tokens can be more efficient than small models to achieve a targeted performance.

C.2 Comparison within Gemma-3 Family

Furthermore, we evaluated Gemma 3-4B/12B (Team et al., 2025) as a third VLM family as follows.

Table 13: Gemma 3 output tokens and single-model performance.

Method	ChartQA		InfoVQA		MMBench	
	#Token	Acc.	#Token	ANLS	#Token	Acc.
4B-S	3.55	46.80	4.03	45.70	4.4	77.34
4B-R(S2)	209.48	55.60	191.76	49.52	246.9	79.03
12B-S	5.31	57.12	5.29	59.12	4.1	81.81
12B-R(S2)	190.44	64.40	169.55	63.97	241.3	83.92

The results are consistent with our main observations: reasoning uses substantially more output tokens, and MAI improves over 12B-S on MMBench (Table 14). This supports generalization beyond Qwen3-VL and InternVL3.5.

Table 14: Gemma 3 MAI performance.

Method	MMBench Acc.
4B-R(S2)	79.03
12B-S	81.81
Full RT	82.39
MAI	**83.14**

Confidence intervals and statistical significance. Since our experiments use greedy decoding, we report uncertainty over benchmark examples using paired bootstrap resampling (2000 resamples). On Gemma-3 (MMBench, $n = 4328$), the resulting 95% confidence interval for MAI's improvement over 12B-S excludes zero:

Table 15: Paired bootstrap 95% confidence intervals for Gemma-3 12B-S and MAI on MMBench.

Method	MMBench Acc.	95% bootstrap CI
12B-S	81.81	$[80.67,\ 82.93]$
MAI	83.14	$[82.07,\ 84.26]$

The paired improvement is $+1.33$ points (95% CI $[+0.57,\ +2.08]$, $p < 0.01$).

C.3 MAI WITH TOKEN PRUNING

To illustrate the proposed framework can be combined with other vision token pruning method to accelerate inference further, we applied DivPrune (Alvar et al., 2025) and MMTok (Dong et al., 2025) together with MAI on MMBench. Both methods reduce the average number of visual tokens further from 525 to 200 (62%). The following results empirically show that visual-token pruning can reduce prefilling cost and MAI reduces decoding cost. Therefore, MAI and token pruning can be applied together to achieve further efficiency gain.

Table 16: MAI with visual-token pruning on MMBench (Gemma-3 4B/12B).

Configuration	Avg. visual tokens	Reduction	Acc. (%)
MAI	525	–	83.14
MAI + DivPrune	200	62%	82.80
MAI + MMTok	200	62%	82.23

C.4 MUTUAL VERIFICATION (MV) AND REASONING TRANSFER (RT) ABLATION ON GEMMA 3

We evaluate the effects of MV and RT in Table 9: 8B-S removes RT, Full RT removes MV, and MAI combines MV with selective RT. The results show that RT improves performance on difficult samples, while MV helps avoid unnecessary transfers. We further conduct the same ablation on Gemma-3 (4B/12B) and observe consistent trends in Table 17.

C.5 CROSS-FAMILY MAI

Since MAI communicates only through complete text responses, the small and large models do not need to share a tokenizer, a vision encoder, or KV caches. We therefore pair models from different

Table 17: Ablation of MV and RT with Gemma-3 4B/12B on MMBench.

Setting	MMBench
12B-S (w/o RT)	81.81
Full RT (w/o MV)	82.39
MAI (MV + selective RT)	**83.14**

families on ChartQA in Table 18. Using InternVL3.5-2B as the reasoning source for Qwen3-VL-8B yields 87.32, slightly higher than the same-family pair (86.80). Using Qwen3-VL-2B as the reasoning source for InternVL3.5-8B improves its Simple-prompt baseline from 77.16 to 87.28. These results show that MAI does not rely on models from the same family.

Table 18: Cross-family MAI on ChartQA (N=2500). Same-family (Qwen3VL-8B + Qwen3VL-2B) is the MAI result from Table 9. Routing reports the percentage of samples resolved at each stage.

Large Model	Reasoning Source	Type	ChartQA		Routing (%)		
			8B-S	MAI Final	Stage 1	Stage 2	Stage 3
Qwen3VL-8B	Qwen3VL-2B	Same-family	84.72	86.80	72.00	7.80	20.20
Qwen3VL-8B	InternVL3.5-2B	Cross-family	84.72	87.32	73.40	6.16	20.44
InternVL3.5-8B	Qwen3VL-2B	Cross-family	77.16	87.28	62.24	8.52	29.24

C.6 Calculation of Theoretical Latency Upper Bound

As discussed in Section 5.4, to quantify end-to-end efficiency independent of specific serving frameworks or hardware optimizations, we formulate a strictly conservative upper bound for the total inference time. We estimate this by summing the sequential execution costs without any parallelization or continuous batching:

$$\text{Total Time}_{\text{MAI}} = \sum_{k \in \mathcal{C}} \left(\text{TTFT}_k + \frac{\#\text{Output Tokens}_k}{\text{Tok/s}_k} \right) \tag{20}$$

where $\mathcal{C}$ is the set of sequential model calls triggered by the verification outcome in our Multi-Agent Inference (MAI) framework. TTFT_k accounts for input preprocessing, vision encoding, and prefilling (dynamically looked up from Table 3 based on total context length), and Tok/s_k is the average decoding throughput (Table 4).

By deliberately enforcing this fully sequential estimation, we isolate the fundamental algorithmic efficiency of our framework, ensuring that the speedups reported in the main text are robust and not artifacts of specific engineering optimizations. The estimate is an upper bound on the total inference time because it (i) executes all model calls sequentially, including the two Stage-1 calls that can run in parallel, (ii) assumes a batch size of 1 without continuous batching, and (iii) does not reuse KV caches across stages; each of these optimizations can only reduce the latency. Consistently, the measured end-to-end time of MAI on ChartQA with vLLM (468 s, Table 21) is far below its estimate (4,158 s, Table 10). Since TTFT and decoding throughput are averaged profiling values, the bound applies to the total time over a dataset rather than to every individual sample.

C.7 Routing Optimization via 2-Stage Decoding (S2)

As motivated in Section 5.1, long reasoning chains can degrade the instruction-following capability of small models. When the 2B model generates the correct logical conclusion but outputs it in an incorrect format, it triggers an unnecessary mutual verification failure, forcing a fallback to the 8B model. Importantly, our core multi-agent framework effortlessly absorbs this: the 8B model, during Reasoning Transfer, receives this poorly formatted context, filters the noise, and outputs the perfectly formatted answer. Therefore, S2 is only applied when evaluating a single model with the E/R prompts (*e.g.*, Tables 6 and 7); reasoning transfer and MAI use the raw 2B-R output without S2, and the 2B(R) column in Table 9 is reported accordingly.

However, to minimize these unnecessary 8B calls, we evaluate a cascade variant that replaces 2B-R with the two-stage decoding 2B-R(S2) (Equation (5)) to serve as a *routing optimization*. Empirically,

Table 19: Original 2B-R vs. 2B-R(S2) in the cascade. *MV*|N: samples resolved by the second verification ($\mathrm{MV}_{\mathrm{2B(R)/8B(S)}}$); *RT*|$N$: samples sent to reasoning transfer (count; % of all tests). Final: POPE/F1, InfoVQA/mean ANLS$\times$100, others/accuracy. The MMMU row comes from a separate evaluation run from Table 9 (Stage-1 agreement 475 vs. 498 of 900); both columns of this table share that run.

Dataset	#Test	2B-R			2B-R(S2)			ΔFinal
		MV|N	RT|N	Final	MV|N	RT|N	Final	
POPE	9000	46 (0.51%)	447 (4.97%)	88.70	63 (0.70%)	430 (4.78%)	88.79	+0.09
MMMU	900	141 (15.67%)	284 (31.56%)	61.22	63 (7.00%)	362 (40.22%)	61.00	−0.22
MMBench	4328	262 (6.05%)	330 (7.62%)	85.48	263 (6.08%)	329 (7.60%)	85.48	0.00
ChartQA	2500	195 (7.80%)	505 (20.20%)	86.80	216 (8.64%)	484 (19.36%)	86.80	0.00
InfoVQA	2801	271 (9.68%)	802 (28.63%)	82.94	278 (9.93%)	795 (28.38%)	83.00	+0.06
RealWorldQA	765	105 (13.73%)	151 (19.74%)	68.37	114 (14.90%)	142 (18.56%)	68.37	0.00

on most benchmarks this improves the verification success rate ($\mathrm{MV}_{\mathrm{2B\text{-}R/8B\text{-}S}}$) and reduces the reasoning-transfer (RT) rate (Table 19), while the final cascade accuracy remains stable. Note that this is a standalone ablation of the routing variant; the main results in Table 9 use the original 2B-R without S2.

Overhead of S2. With prefix caching in vLLM (`enable_prefix_caching=True`), the second stage of S2 reuses the KV cache of the reasoning stage, so it only prefills the short answer prompt and decodes the final answer. As shown in Table 20, the second stage costs 47 ms, *i.e.*, about 3.7% of the total two-stage latency.

Table 20: Latency of the 2-stage strategy (S2) with vLLM prefix caching (Qwen3-VL-8B, averaged over 30 repeats). The input contains 513 image tokens and 37 question tokens; the reasoning stage generates 138 tokens.

Stage	New prefill tokens	Output tokens	Mean latency (s)
Stage 1 (reasoning)	513 + 37 = 550	138	1.222
Stage 2 only (answer)	138 + 14	1	0.047
Two-stage total	–	139	1.269
8B-S (TTFT, reference)	513 + 37 = 550	1	0.247

C.8 Latency Measurement and Experimental Setup

HuggingFace Experiments (SD and 8B-R Baseline). Both 8B-R and SD (8B+2B) use HuggingFace Transformers on a single H100. The 8B-R baseline runs standard autoregressive generation under the reason prompt. SD uses the identical prompt but replaces the decoding algorithm with assisted generation, where the 2B draft proposes tokens that the 8B target verifies. HuggingFace restricts assisted generation to batch size 1 (`ValueError` is raised for larger batches); the 8B-R baseline is evaluated under the same batch size 1 setting to ensure a strictly fair comparison. The reported latency covers data loading, preprocessing, and the full generation loop, excluding one-time model loading.

Step-level Profiling of Speculative Decoding. To quantitatively illustrate the context-switching bottlenecks discussed in Appendix C.9, we profile a single ChartQA sample under the HuggingFace backend setup described above. We tested two different speculation lengths (n):

- $n = 5$: The 8B target is invoked 39 times. Out of 131 proposed tokens, 108 are accepted (17.56% rejection rate), yielding a latency of 4.44s.
- $n = 20$: The 8B target is invoked 30 times, but the longer draft sequences increase the rejection rate to 27.33% (125/172 accepted), resulting in a latency of 4.19s.

In both configurations, the repeated invocations and high rejection rate negate the theoretical speedup of drafting, making the process strictly slower than the standard autoregressive baseline.

vLLM Experiments (MAI and 8B-R Baseline). Both MAI and the 8B-R baseline use vLLM with batch size 32 on a single H100. The 8B-R baseline runs on ChartQA(2,500 samples) with the reason prompt in a single vLLM process. MAI executes a three-stage cascade via subprocess orchestration: (1) 2B and 8B nothink subprocesses run in parallel on the same GPU, both producing short answers for all samples; (2) for the disagreement subset ($a_{2S} \neq a_{8S}$), a 2B subprocess runs reasoning; (3) for samples still in disagreement, an 8B subprocess reads the 2B reasoning context and outputs a short final answer. The reported latency is the end-to-end wall-clock time including all subprocess lifecycles (engine initialization, inference, and teardown). Note that vLLM does not currently support speculative decoding for VLMs, which is why SD is only evaluated under the HuggingFace backend.

MAI Implementation Status and Scalability. Our current implementation is a research prototype that restarts a fresh vLLM engine for every stage (Stage 1 nothink, Stage 2 reasoning, Stage 3 agent), incurring repeated cold-start costs including weight loading, KV-cache allocation, and CUDA graph capture. In a production setting, persistent vLLM engines with asynchronous stage handoff would eliminate these redundant startup overheads entirely. Despite this unoptimized implementation, MAI already achieves a 2.40× speedup over the 8B-R baseline (Table 21), indicating that the reported numbers represent a conservative lower bound.

Furthermore, our response-level design is naturally amenable to multi-GPU deployment: since models communicate only through complete text responses, the 2B and 8B models can be served on separate GPUs — or even separate machines — with negligible communication overhead. In contrast, token-level speculative decoding requires draft and target models to exchange predictions at every decoding step, tightly coupling them to shared memory or high-bandwidth interconnects.

Cross-group Note. Due to differences in backend and batching, latency is only comparable *within* each group. Speedup is computed accordingly.

Table 21: Comparison of decoding strategies on ChartQA. †HF latency excludes model loading, whereas vLLM is end-to-end. All reported latencies exclude S2 overhead, which is required by baselines for best accuracy but avoided by MAI. Accuracies are from these separate end-to-end runs and differ slightly from Tables 6 and 9 (*e.g.*, MAI: 86.52 vs. 86.8).

Method	Backend	BS	Accept Rate	Total† (s) ↓	Latency† (s/sample) ↓	Speedup	ChartQA Acc. (%)	
							w/o S2	w/ S2
8B-R	HF	1	N/A	27,195	10.88	1.00×	77.08	85.52
SD (8B+2B)	HF	1	60.39%	31,540	12.62	0.86×	77.24	85.40
8B-R	vLLM	32	N/A	1,122	0.449	1.00×	77.68	86.32
MAI (8B+2B)	vLLM	32	N/A	468	0.187	2.40×	**86.52**	-

C.9 Comparison with Speculative Decoding

To assess token-level speculative decoding (SD), we tested a 2B-draft/8B-target setup on ChartQA via HuggingFace. Empirically, SD is 16% slower than standard decoding (Table 21) due to high draft rejection (∼40%) and severe token-level context-switching overheads (Appendix C.8).

In contrast, MAI transfers complete reasoning contexts to the response level. Requiring only a single 8B invocation, MAI is natively compatible with optimized engines such as vLLM, achieving a 2.40× speedup over the 8B-R baseline while boosting accuracy to 86.52%. Extended discussions on memory and scalability are provided in Appendix E.

C.10 End-to-end latency on Gemma 3

Table 21 reports measured end-to-end wall-clock latency on one H100. Besides, we measured Gemma-3 4B/12B on MMBench, with both models co-resident on a single H200 at BS$=$ 32:

All settings share hardware, vLLM configuration, batch size, and evaluation samples; speedup is relative to 12B-R. MAI achieves accuracy comparable to full-reasoning 12B-R (83.1 vs. 83.9) with a 1.65× speedup. Extended discussions on memory and scalability are provided in Appendix E.

Table 22: End-to-end wall-clock latency of MAI vs. 12B-R with Gemma 3-4B/12B on MMBench (single H200, BS=32).

Method	MMBench	End-to-end latency (s/sample)	Speedup
12B-R	83.92	0.172	1.00×
MAI	83.14	**0.104**	**1.65**×

Table 23: Practical deployment comparison of 17 related works against MAI. Blue : requires training; Green : training-free; Yellow : ours. N is the number of reasoning steps and M the number of sentences; #LM Calls counts large-model invocations per query in the worst case.

Method	**Train-Free**	**Granularity**	**LM Long Decoding**	**vLLM Native**	**Batch (BS>1)**	**#LM Calls**	**Verification**	**E2E Latency**	**Cross-Arch**	**Task Scope**	**Modality**
SplitReason (Akhauri et al., 2025)	✗	Token	Always	✗	✗	$\gg N$	None	Wallclock	✗	CoT	Text
RelayLLM (Huang et al., 2026)	✗	Token	Always	✗	✗	$\gg N$	None	Ratio only	✗	CoT	Text
R2R (Fu et al., 2026a)	✗	Token	Always	✗	✗	$\gg N$	Trained	Wallclock	✗	CoT	Text
Arbitrage (Maheswaran et al., 2025)	✗	Step	On reject	✗	✗	$\sim N$	Trained	FLOPs only	✗	CoT	Text
RSD (Liao et al., 2025)	✗	Step	On reject	✗	✗	$\sim N$	Trained	FLOPs only	✗	CoT	Text
Hawkeye (She et al., 2025)	✗	CoT	Reduced	✗	✗	2	None	Wallclock	✗	CoT	Text
SCoT (Wang et al., 2025a)	✗	CoT	On fallback	✗	✗	2	Trained	Wallclock	✗	CoT	Text
R-Stitch (Chen et al., 2025)	✓	Token	Always	✗	✗	$\gg N$	Heuristic	Wallclock	✗	CoT	Text
FoReaL (Li et al., 2025)	✓	Sent.	Per sentence	✗	✗	$\sim 2M$	Heuristic	FLOPs only	✗	CoT	Text
SpecSearch (Wang et al., 2025c)	✓	Thought	Always	✗	✗	$\gg N$	Heuristic	Wallclock	✗	CoT	Text
SpecReason (Pan et al., 2025)	✓	Step	On reject	✗	✗	$\sim 2N$	LLM Judge	Wallclock	✗	CoT	Text
Lookahead (Fu et al., 2026b)	✓	Step	On reject	Modified	BS=1	$\sim N$	LLM Judge	Wallclock	✗	CoT	Text
SpecCoT (Shi et al., 2025)	✓	Step	On fallback	✗	✗	$\sim 2N$	LLM Judge	Wallclock	✗	CoT	Text
SpecThink (Yang et al., 2025b)	✓	Step	Per trigger	✗	✗	$\leq N$	Heuristic	Estimated	✗	CoT	Text
SMART (Kim et al., 2025)	✓	Step	Always	✗	✗	$\leq N$	Heuristic	✗	✗	CoT	Text
ThoughtMani (Liu et al., 2025b)	✓	Resp.	Uncontrolled	HF	BS=1	2	None	Tok. count	✓	<think> only	Text
COPE (Lee et al., 2025)	✓	Resp.	Always (plan)	GPT-4o	API	3–6	Heuristic	API cost	✓	General	Text
MAI (Ours)	✓	**Resp.**	**Never**	**vLLM**	**BS=32**	**1–2**	**Ans. Match**	**Wallclock**	✓	**General**	**VLM**

D More related work

Comparison with Related Efficient-Reasoning Methods. Table 23 compares MAI with 17 recent methods, including vanilla speculative decoding, reasoning transfer, external thought injection, token routing, and multi-model collaboration, along the axes of training requirements, routing granularity, serving and batching support, large-model calls, verification, and latency evaluation. MAI differs in three aspects: (1) reasoning is transferred at the response level and consumed through prefilling, and MAI requires the large model to produce only a short answer; (2) in MAI, answer matching requires no trained verifier, logit access, or LLM judge; and (3) MAI's standard request-level interface supports heterogeneous VLMs and batched vLLM serving.

Comparison with Sequence-level Speculative Cascades. These methods(Narasimhan et al., 2025; Fanconi & van der Schaar, 2026) also coordinate small and large models, but differ from MAI in

routing granularity and in how the small-model output is reused. MAI transfers the small model's reasoning trace as prefilled context for the large model, reusing it at the response level rather than as draft output tokens. Speculative cascades(Narasimhan et al., 2025) use a token-level deferral rule over both models' output distributions to accept small-model draft tokens or defer to the large model during decoding. MAI instead transfers the small model's reasoning as prefilled context at the response level, requiring neither logit access nor per-token verification. Cascaded language models(Fanconi & van der Schaar, 2026) use confidence-based deferral to accept the base model's answer or have the large model regenerate it, followed by possible abstention to a human. MAI routes by training-free answer agreement and, on disagreement, transfers the small model's reasoning rather than asking the large model to restart from the original query.

E Discussion and Practical Deployment

Memory. For the 2B+8B configuration, the total parameter count is approximately 10B, fitting comfortably within a single H100 (96 GB). The two models can also be served on separate GPUs or with time-sharing to reduce peak memory usage.

Scalability. Our response-level design is naturally amenable to multi-GPU deployment: since models communicate only through complete text responses, the 2B and 8B models can be served on separate GPUs or separate machines with negligible communication overhead. In contrast, token-level speculative decoding requires draft-target synchronization at every decoding step. Furthermore, our current prototype restarts a fresh vLLM engine per stage; persistent engines with asynchronous handoff would eliminate this overhead, making the reported $2.40\times$ speedup a conservative lower bound. See Section C.8 for details.

Practical deployment trade-offs. In our deployment, the 4B and 12B models occupy 8.61 and 23.41 GiB of weight memory, respectively; co-resident MAI therefore requires approximately 32.0 GiB. At BS$=$ 32, the individual stages achieve 88.1–99.6% GPU utilization. Concurrent mutual verification introduces compute contention when both models share one GPU; using separate GPUs removes this cross-model contention but requires an additional accelerator and more energy. MAI otherwise uses only standard vLLM requests and complete-text handoffs, without custom kernels, shared KV caches, or token-level synchronization. Its main operational overhead is serving two models and applying task-appropriate answer matching.


F Qualitative Comparison

To demonstrate the proposed multi-agent inference, we provide additional real examples to show the effectiveness of different components in our framework.

Qwen3-VL-2B-S vs. Qwen3-VL-2B-R First, we show the difference for the same Qwen3-VL-2B model with different prompts. From the example below, we can find that the 2B model cannot obtain the right answer with the simple prompt. By assigning more output token budgets for reasoning, the model can answer the question correctly, which confirms the benefit of additional output tokens for small models.

Example 1: More Output Tokens Helps

The graph below shows the AD-AS diagram for Spain. All numbers are in billions.



What is the size of real GDP in the short-run equilibrium?
A. 500
B. 450
C. 400
D. 600
Ground Truth: C

Simple

Prompt: Without thinking, directly answer with the option's letter from the given choices directly in the format: [[answer]]
Qwen3-VL-2B Answer: [[A]] ✗ Wrong answer

Reasoning

Prompt: Please think step by step, provide a detailed explanation, then answer with the option's letter from the given choices directly in the format: [[answer]]

Qwen3-VL-2B Answer:
To determine the size of real GDP in the short-run equilibrium, we need to identify the point where the Aggregate Demand (AD) curve intersects the Short-Run Aggregate Supply (SRAS) curve.

Looking at the graph:
- The **AD** curve is a downward-sloping line that starts at a price level of 1000 and a real GDP of 0.
- The **SRAS** curve is a rightward-sloping line that starts at a price level of 200 and a real GDP of 0.
- The **LRAS** (Long-Run Aggregate Supply) is a vertical line at 500 on the real GDP axis.

In the short run, the equilibrium occurs at the intersection of AD and SRAS. We can see from the graph that the two curves intersect at a real GDP of 400.

Therefore, the size of real GDP in the short-run equilibrium is 400.

[[C]] ✓ Right answer

Qwen3-VL-2B-R vs. Qwen3-VL-2B-R(S2) However, with more output tokens, it becomes challenging for small models to follow the instructions about the output format. Here is an example illustrating the issue. The right answer should be in "Yes" or "No" while the result after thinking returns in "[[0]]". With the proposed 2-stage strategy, *i.e.*, (S2), we can obtain the answer in the right format with limited additional output tokens, *e.g.*, in the following Example 2.

In particular, large-scale models maintain correct output formatting even after extended reasoning chains, effectively translating these longer thoughts into performance gains. In contrast, smaller models often encounter formatting errors. Consequently, this two-stage strategy is introduced to mitigate the formatting deficiencies observed in smaller models during the assessment of their reasoning capabilities, thereby ensuring that their true reasoning performance can be measured and compared objectively

Example 2: 2-Stage Mitigates Format Issue

The image shows a python code. Is the output of the code '1'?

```
a = '12345'
b = a.find('1')
print(b)
```

Ground Truth: No

Reasoning

Prompt: Please think step by step, provide a detailed explanation, then answer the question using a single word or phrase in the format: [[answer]]

Qwen3-VL-2B Answer:

Let's analyze the code step by step:

1. The variable 'a' is assigned the string value ''12345''.
2. The line 'b = a.find('1')' calls the 'find' method on the string 'a'. The 'find' method returns the index of the first occurrence of the substring '1' in the string 'a', or -1 if the substring is not found.
3. In the string ''12345'', the character '1' appears at the very beginning, so its index is 0.
4. Therefore, 'b' will be assigned the value '0'.
5. The final line 'print(b)' will print the value of 'b', which is '0'.

The output of the code is not '1', but rather the integer '0'.

[[0]] ✗ Wrong answer format

Stage2: R(S2)

Prompt: According to previous thinking:{Stage1 Response}.
Answer the question using a single word or phrase.

Qwen3-VL-2B Answer: No ✓ Right answer format

Reasoning Transfer between 2B and 8B Models There are some challenging examples that both 8B-S and 2B-R cannot handle well, which may require the reasoning from the large model. Here is an example as follows. We find that 8B-S and 2B-R show the wrong answer, while 8B-R returns the appropriate result. However, it costs a lot of output tokens from the 8B model, which can be slow. Therefore, we try to transfer the reasoning tokens to the 8B model as input tokens, which will not significantly increase the latency according to our analysis with simulation. With the simple prompt, the 8B model can return the right answer with transferred reasoning tokens, which confirms our proposal.

We also report the running time estimated as follows:

$$\text{Total Time}_{\text{S,E,R}} = \text{TTFT} + \frac{\#\text{Output Tok}}{\#\text{Tok/s}} \tag{21}$$

$$\text{Total Time}_{\text{8B+2B(R)}} = \text{TTFT}_{\text{2B}} + \frac{\#\text{Output Tok}_{\text{2B}}}{\#\text{Tok/s}_{\text{2B}}} + \text{TTFT}_{\text{8B}} + \frac{\#\text{Output Tok}_{\text{8B}}}{\#\text{Tok/s}_{\text{8B}}} \tag{22}$$

Note: $\text{TTFT}(s)_{8B}$ is determined via dynamic look-up based on the total context length (profiled up to 8192 tokens), ensuring accurate estimation for variable-length reasoning transfer.

Example 3: Challenging Case for Reasoning Transfer

I feel very cold. Is the tool in the picture suitable for use?



Ground Truth: No

Simple (Qwen3-VL-8B)

Prompt: Without thinking, directly answer the question using a single word or phrase in the format: [[answer]]
Qwen3-VL-8B Answer: [[Yes]] ✗ Wrong answer

Reasoning (Qwen3-VL-2B)

Prompt: Please think step by step, provide a detailed explanation, then answer the question using a single word or phrase in the format: [[answer]]

Qwen3-VL-2B Answer:

Let's analyze the image and the question step by step.
1. **Identify the Object**: The image shows a fan, specifically a table fan, which is a device designed to circulate air and cool a room or a person.
2. **Analyze the Function**: The primary function of a fan is to move air. This is done by creating a flow of air, which can help to lower the temperature of a room or a person.
3. **Assess the Current Situation**: The user states they are "very cold." This suggests they are experiencing cold conditions, possibly in a room with low temperatures or in a cold environment.
4. **Evaluate the Suitability**: Since the fan is designed to cool down a room or a person, and the user is feeling cold, the fan would be suitable for use to help warm up the environment and the user. It would be a practical tool to help combat the cold.
5. **Conclusion**: The fan is a tool designed for cooling, which is the opposite of what the user is feeling. Therefore, it is suitable for use to help them feel warmer.

[[yes]] ✗ Wrong answer. Reasoning error.

Running Time: 3.83 s

Reasoning (Qwen3-VL-8B)

Prompt: Please think step by step, provide a detailed explanation, then answer the question using a single word or phrase in the format: [[answer]]

Qwen3-VL-8B Answer:

Let's think step by step:
1. The object in the picture is a vintage-style oscillating table fan. Its primary function is to circulate air and create a cooling breeze, which helps to lower the perceived temperature in a room.
2. The user states they feel "very cold." This indicates a need for warmth or at least a reduction in the sensation of cold.
3. A fan works by moving air, which can make a person feel cooler, especially if the ambient temperature is already low or if the air is moving across the skin. It does not generate heat.
4. Therefore, using a fan when one feels very cold would likely make the situation worse, as it would increase the air movement and potentially make the person feel even colder.
5. The tool is not designed to provide warmth. It is a cooling device.
Conclusion: The tool shown in the picture is not suitable for use when one feels very cold, as it will exacerbate the feeling of coldness rather than alleviate it.
[[No]] ✓ Right answer

Running Time: 4.56 s

Reason Transfer: 8B + 2B-R

Prompt: The following is a reference answer from a smaller model (it might be wrong or incomplete): Let's analyze the image and the question step by step.\n\n1. **Identify the Object**: The image shows a fan, specifically a table fan, which is a device designed to circulate air and cool a room or a person.\n\n2. **Analyze the Function**: The primary function of a fan is to move air. This is done by creating a flow of air, which can help to lower the temperature of a room or a person.\n\n3. **Assess the Current Situation**: The user states they are "very cold." This suggests they are experiencing cold conditions, possibly in a room with low temperatures or in a cold environment.\n\n4. **Evaluate the Suitability**: Since the fan is designed to cool down a room or a person, and the user is feeling cold, the fan would be suitable for use to help warm up the environment and the user. It would be a practical tool to help combat the cold.\n\n5. **Conclusion**: The fan is a tool designed for cooling, which is the opposite of what the user is feeling. Therefore, it is suitable for use to help them feel warmer. \n\n \n\n Please answer the question yourself, using the reference only if it seems reasonable. \n Answer the question using a single word or phrase.

Qwen3-VL-8B Answer: No ✅ Right answer

Running Time: 3.83 s + 0.126 s = 3.96 s

From this example, we can find that 8B-R uses 4.56s to obtain the right answer while 2B-R costs 3.83s to generate reasoning tokens. By transferring the tokens to 8B-S, the combination can handle the example well with only about 3.96s, which is more efficient than 8B-R.

G Failure Case Analysis of Transferred Reasoning

We analyze the failure cases of reasoning transfer with Gemma-3 (4B as the small model, 12B as the large model) on MMBench. The dominant failure mode is incorrect fine-grained visual grounding by the small model. On MMBench, typical cases involve object localization, attribute comparison, and scene-level judgment. In these cases, the 4B reasoning provides confident but incorrect visual evidence that subsequently misleads the 12B model:


- **Object localization** — *"where is the cat?"* (GT: bottom-right). The transferred 4B reasoning localizes the wrong quadrant: *"the second crop clearly shows the cat standing in the **top-right** corner of the image. Therefore, the answer is B."* RT adopts top-right and is wrong.
- **Attribute comparison** — *"are the two hoops the same size?"* (GT: same). The 4B misreads the two rings as mismatched links: *"the red link is **significantly larger than the silver link** … the two links are **not the same size**."* RT follows this to "not the same".
- **Scene judgment** — *"is this place crowded?"* (GT: no). The 4B over-reads occupancy from a sparse theater shot: *"given the number of visible seats and the fact that **they are all occupied** … the theater **appears to be crowded**."* RT answers "yes".

These failures arise not merely from irrelevant tokens, but because the transferred reasoning misidentifies the decisive visual evidence. This empirical pattern complements Corollary 1: successful transfer requires the small-model reasoning to preserve the key evidence needed by the large model.

H Sparsity in Reasoning Token Transfer

As shown in Corollary 1, the success of reasoning transfer is from the sparsity in self-attention operations. To validate our theoretical analysis, we study the attention scores for reasoning tokens from different models with Example 3 in Appendix F.

First, we show the distribution of attention scores over different layers in Qwen3-VL-8B model in Figure 5, where Figure 5a shows the total weight of all reasoning tokens and Figure 5b shows the sparsity within reasoning tokens. The reported results are averaged over 32 heads and the detailed distribution for each head can be found in Figure 6 and Figure 7. We can find that with reasoning tokens from 8B-R and 2B-R respectively, the distribution is similar. For most of layers, the distribution within reasoning tokens is very skewed, where about the top 20% reasoning tokens contribute to 80% of the weights, which is consistent with our analysis. For the last layer, the attention weights are mainly distributed on non-reasoning tokens for generation, *e.g.*, answer prompt, and the internal distribution of reasoning tokens can be more balanced due to the smoothness of softmax operators.



(a) Attention weights of all reasoning tokens

(b) Sparsity within reasoning tokens

Figure 5: Illustration of total attention weights of all reasoning tokens and sparsity within reasoning tokens averaged over 32 heads. Sparsity is measured by the ratio of reasoning tokens that contribute to 80% total attention weights of reasoning tokens.

To demonstrate the selected tokens, we list the top-ranked reasoning tokens for different layers from 8B-R and 2B-R in Table 24. The weight of each token is averaged over all heads before ranking. Obviously, the deeper layers focus more on semantic information from reasoning tokens. For these layers, we observe that the similar tokens, *e.g.*, "picture", "tool", are picked by the 8B model from different reasoning tokens by Layer 24. It shows that key tokens are more important in inference than other reasoning tokens. It implies that even the sparse reasoning tokens from small models can help large models to think.

Table 24: Comparison of top tokens selected by **8B + 2B-R** and **8B + 8B-R** across different layers. Evidently, deeper layers focus on semantic reasoning tokens, where similar tokens can be selected from 2B-R and 8B-R tokens.

Layer	Model	N-Tok (80%)	1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th	11th	12th	13th	14th	15th
L1	8B+2BR	45.0% (54)	. 11.1%	a 3.1%	, 3.0%	, 2.9%	. 2.9%	, 2.9%	, 2.6%	the 2.6%	in 2.4%	the 2.3%	, 2.1%	the 2.0%	and 2.0%	. 1.8%	) 1.7%
	8B+8BR	40.6% (104)	. 7.5%	. 3.5%	the 3.2%	, 2.8%	of 2.2%	. 2.2%	). 2.1%	: 2.0%	, 2.0%	, 1.8%	the 1.7%	. 1.5%	, 1.4%	in 1.4%	and 1.3%
L6	8B+2BR	21.7% (26)	the 19.1%	. 17.6%	the 16.2%	the 3.7%	. 3.5%	. 3.3%	. 1.6%	Therefore 1.5%	. 1.2%	, 1.0%	the 0.9%	The 0.9%	picture 0.9%	, 0.9%	the 0.8%
	8B+8BR	16.4% (42)	the 21.3%	the 14.8%	. 6.0%	the 4.5%	: 4.0%	. 2.8%	. 2.5%	). 2.2%	: 2.0%	. 1.9%	Conclusion 1.8%	. 1.7%	2 1.1%	5 0.8%	The 0.7%
L12	8B+2BR	29.2% (35)	. 18.2%	tool 8.7%	. 6.7%	tool 5.2%	the 4.3%	The 3.4%	. 3.2%	Therefore 2.6%	The 2.3%	, 2.1%	. 2.0%	provided 1.5%	picture 1.4%	picture 1.2%	, 1.2%
	8B+8BR	17.6% (45)	: 14.1%	. 8.2%	step 7.8%	think 3.2%	2.9%	. 2.7%	2 2.5%	. 2.4%	. 2.3%	. 2.2%	. 2.1%	Conclusion 2.1%	: 2.0%	1.9%	). 1.6%
L18	8B+2BR	28.3% (34)	. 12.4%	the 4.8%	suitable 4.8%	, 3.7%	, 3.3%	use 3.2%	suitable 3.0%	. 2.9%	which 2.6%	. 2.6%	The 2.4%	the 2.2%	tool 2.2%	The 2.1%	However 2.0%
	8B+8BR	21.1% (54)	. 7.1%	, 5.4%	: 4.2%	uns 3.0%	. 3.0%	such 2.7%	2.6%	. 2.6%	. 2.4%	." 2.2%	: 1.9%	The 1.9%	2 1.9%	. 1.8%	very 1.8%
L24	8B+2BR	24.2% (29)	. 12.4%	suitable 9.9%	picture 4.6%	use 4.2%	, 4.1%	is 3.2%	the 3.1%	tool 3.0%	for 2.7%	in 2.6%	suitable 2.6%	, 2.4%	. 2.2%	the 2.2%	Therefore 2.1%
	8B+8BR	21.1% (54)	suitable 7.9%	. 5.9%	uns 4.5%	is 3.9%	The 3.7%	not 3.3%	use 2.9%	: 2.9%	uitable 2.8%	, 2.4%	tool 2.3%	) 2.1%	. 2.1%	the 1.9%	picture 1.6%
L30	8B+2BR	27.5% (33)	suitable 11.0%	fan 9.2%	. 7.0%	is 4.4%	The 4.1%	a 3.9%	suitable 3.8%	. 3.2%	the 2.7%	, 2.7%	the 1.9%	picture 1.8%	tool 1.7%	cold 1.7%	picture 1.6%
	8B+8BR	25.0% (64)	not 9.2%	suitable 5.4%	uitable 4.3%	is 4.1%	The 4.0%	uns 3.6%	. 3.4%	3.2%	step 2.1%	: 2.1%	cold 1.9%	. 1.8%	Conclusion 1.6%	, 1.6%	. 1.4%
L36	8B+2BR	53.3% (64)	. 7.5%	, 5.3%	, 3.3%	fan 3.0%	the 2.7%	. 2.6%	. 2.1%	the 2.1%	is 2.0%	in 1.8%	. 1.7%	a 1.7%	Therefore 1.7%	a 1.6%	the 1.6%
	8B+8BR	46.9% (120)	4.8%	. 3.8%	. 2.6%	: 2.4%	1 1.7%	). 1.7%	Conclusion 1.7%	. 1.6%	is 1.6%	cold 1.5%	: 1.4%	such 1.4%	1.4%	step 1.3%	fan 1.0%

I ALL PROMPT TEMPLATES

We list all prompts used in our experiments as follows. Following the official setting of the LMMS-Eval Framework, we set "answer the question using a single word or phrase" for POPE, and "answer with the option's letter from the given choices directly" for the other benchmarks.

Simple (S)

Prompt1: Without thinking, directly answer the question using a single word or phrase in the format: [[answer]]

Prompt2: Without thinking, directly answer with the option's letter from the given choices in the format: [[answer]].

Explain (E)

Prompt 1: Provide a simple explanation, then answer the question using a single word or phrase in the format: [[answer]]

Prompt 2: Provide a simple explanation, then answer with the option's letter from the given choices directly in the format: [[answer]]

Reasoning (R)

Prompt 1: Please think step by step, provide a detailed explanation, then answer the question using a single word or phrase in the format: [[answer]]

Prompt 2: Please think step by step, provide a detailed explanation, then answer with the option's letter from the given choices directly in the format: [[answer]]

Stage 2

Prompt 1: According to previous thinking: {stage1_response}\n Answer the question using a single word or phrase.

Prompt 2: According to previous thinking: {stage1_response}\n Answer with the option's letter from the given choices directly.

Reason Transfer

For POPE, ChartQA, and InfoVQA,
Prompt 1: According to previous thinking: {stage1_response}\n Answer the question using a single word or phrase.

For MMBench, MMMU, and RealWorldQA,
Prompt 2: The following is a reference answer from a smaller model (it might be wrong or incomplete): {stage1_response}\n\n\n\n Please answer the question yourself, using the reference only if it seems reasonable.\n Answer with the option's letter from the given choices directly in the format: [[answer]].
(For open-ended questions, the last sentence is replaced with "Answer the question using a single word or phrase.")




Figure 6: Head-wise attention weights of total reasoning tokens across different layers.




Figure 7: Head-wise sparsity within reasoning tokens across different layers.