WHERE-OPD: SPATIALLY GUIDED ON-POLICY SELF-DISTILLATION OF MLLMS WITH SYNTHETIC SCENES

Anonymous authors
Paper under double-blind review

ABSTRACT

On-policy self-distillation has recently emerged as an effective approach for improving language-model reasoning by supervising students with a frozen or EMA version of themselves that receives privileged information. Its application to multimodal large language models (MLLMs), however, remains largely unexplored. Recent approaches use privileged visual information, such as image crops corresponding to a question, to improve fine-grained perception, but their gains are confined to tasks that benefit from such visual zooming and require either human-annotated grounding data or external teacher models. We introduce a different form of on-policy self-distillation for MLLMs that provides the teacher with textual, spatially grounded guidance identifying the visual elements relevant to a query. We use procedurally generated scenes with automatically available object identities and spatial coordinates, enabling scalable and annotation-free post-training. The teacher uses this spatial guidance to locate and integrate evidence from multiple relevant image regions, while the student learns to reproduce the resulting behavior from the image and question alone. Our approach consistently improves performance on counting, document and chart understanding benchmarks across multiple models. Importantly, although post-training uses only synthetic scenes, the resulting improvements transfer to real-world perception benchmarks, yielding a 3.23-point gain in average performance across CVBench, V*, ZoomBench, BLINK, HR-Bench, and MME-RealWorld. These results show that spatially grounded privileged information can induce broader perceptual capabilities through on-policy self-distillation, enabling substantial synthetic-to-real transfer beyond the task and data distribution used for post-training. Code and models will be made public.



Figure 1: **Synthetic-to-real transfer of our spatially grounded on-policy self-distillation. Left:** Our method `Where-OPD` distills behavior induced by spatially grounded guidance on synthetic counting scenes, yielding improvements on diverse visual perception tasks involving real-world images. **Right:** Accuracy gains of `Where-OPD` over the Qwen3.5-4B base model across six benchmarks, demonstrating transfer beyond the synthetic images and counting task used for post-training.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

1 INTRODUCTION

On-policy distillation (OPD) (Agarwal et al., 2024) has emerged as an effective approach for post-training large language models. Unlike off-policy distillation, OPD supervises student-generated trajectories with teacher predictions at the states the student actually visits, better aligning training with inference-time behavior. On-policy self-distillation (OPSD) (Zhao et al., 2026) extends this paradigm by using a frozen or exponential-moving-average (EMA) copy of the student as a teacher, augmented with privileged information unavailable to the student. The student thus learns from a more informed version of itself while remaining fully self-contained at inference time.

How to exploit this paradigm for multimodal large language models (MLLMs), particularly for improving visual perception, remains largely unexplored. A central question is therefore *what privileged information should be provided to the teacher?* In the multimodal setting, this privileged information can take different forms, ranging from enhanced or localized visual observations to explicit information about the image content. The choice is important because it determines what advantage the teacher has over the student and, consequently, what capabilities can be transferred through self-distillation.

Recent work on OPSD for MLLMs has primarily created this teacher–student difference by giving the teacher better visual access to the image. Vision-OPD (Yuan et al., 2026) and Imagine-OPD (Cai et al., 2026), for example, provide the teacher with cropped or zoomed-in views of question-relevant regions while the student operates on the original image. Other approaches construct this difference through image resolution or perturbations (Zhu et al., 2026; Li et al., 2026), or contrast teacher predictions under "positive" and "negative" visual views to derive a more visually grounded distillation signal (Aniri et al., 2026; Liang et al., 2026). Despite these different implementations, they largely share the same principle: the teacher is given more informative visual observations than the student. Such approaches can yield strong improvements when fine-grained or localized visual evidence is critical, but these gains do not necessarily transfer uniformly across visual tasks. In our evaluation, for instance, Vision-OPD improves Qwen3.5-4B by 8.90 points on V* and 14.56 points on ZoomBench, yet decreases performance on CountQA by 10.73 points. This motivates exploring forms of privileged information that may support broader improvements in visual perception.

This observation raises a different question: *can privileged information specify not what the teacher should see, but where in the image the relevant evidence can be found?* Many visual tasks require identifying question-relevant elements distributed across an image and using them to produce an answer (Hudson & Manning, 2019; Johnson et al., 2017). Counting requires finding all instances matching a query; reading may require collecting text from different regions; and chart understanding often requires associating labels, values, and graphical elements (Masry et al., 2022). For such tasks, knowing which visual elements are relevant and where they are located could provide useful guidance without giving the teacher a different view of the image. We therefore investigate *spatially grounded privileged information*: textual guidance that identifies question-relevant visual elements and points to their locations in the image.

A practical challenge is obtaining such guidance at scale. Existing multimodal OPSD approaches (Yuan et al., 2026; Cai et al., 2026) rely on human-annotated grounding information or external models to identify relevant visual regions. Instead, we construct procedurally generated scenes whose object identities, attributes, and spatial coordinates are known by design, allowing us to automatically generate *spatially grounded hints* that identify question-relevant elements and their locations, without pre-existing datasets, human annotations, or a separate higher-capacity teacher model. During post-training, teacher and student receive the same image and question, but only the teacher receives the hint; the student learns from its behavior and operates without hints at inference time. Our central hypothesis is that *distilling behavior induced by spatially grounded guidance can improve how an MLLM identifies and uses relevant visual evidence, and that these improvements can transfer beyond the synthetic scenes used for post-training.*

We evaluate this approach across three MLLMs—Qwen3.5-4B, Qwen3.5-9B, and Qwen3-VL-4B—and across both task-specific and general visual perception benchmarks. Our method consistently improves performance on counting, reading, and chart-understanding tasks, including CountQA, DocVQA, OCRBench, ChartQA, and EvoChart. For example, on Qwen3.5-4B, it improves ChartQA and EvoChart by 7.20 and 10.11 points, respectively, while also improving CountQA and OCRBench by 2.53 and 1.93 points. More importantly, the benefits are not confined to the synthetic

visual distribution used for post-training. Average performance across CVBench, V*, HR-Bench 4K, HR-Bench 8K, ZoomBench, MME-RealWorld, and BLINK improves by 3.23, 1.07, and 1.29 points for the three MLLMs, respectively. *These results indicate that spatially grounded privileged guidance can induce improvements that transfer from simple procedurally generated scenes to substantially different real-world visual tasks.*

Our contributions are threefold:

- **Spatially grounded privileged guidance for OPSD.** We introduce a form of on-policy self-distillation in which the teacher receives textual hints identifying question-relevant visual elements and their spatial locations, while the student receives only the image and question.
- **Annotation-free generation of spatially grounded hints.** We construct the entire post-training data procedurally, using scene metadata to automatically generate question-relevant spatial guidance without pre-existing datasets, human annotations, or external teacher models.
- **Broad improvements and synthetic-to-real transfer.** Across three MLLMs, our approach improves counting, reading, and chart-understanding benchmarks, while also improving general visual perception on real-world images, demonstrating transfer beyond both the tasks and visual distribution used for post-training.

2 Related Works

Improving visual reasoning in MLLMs. Efforts to strengthen visual understanding and reasoning in MLLMs can be broadly grouped by the training stage they target. At the pretraining stage, a large body of work focuses on modifying the architecture to better expose visual information to the language model (McKinzie et al., 2024; Liu et al., 2024a; Cha et al., 2024; Chen et al., 2024a; Lin et al., 2025; Kar et al., 2024; Tong et al., 2024; Azadani et al., 2025; Shi et al., 2024; Lu et al., 2025). Other works trace the bottleneck to how the LLM uses visual information during decoding (Fu et al., 2025), and introduces auxiliary objectives to counteract it (Wang et al., 2025a; Yoon et al., 2025; Caffagni et al., 2025). Another line of work instead improves visual capabilities through instruction-tuning data. V-GIFT (Sirko-Galouchenko et al., 2026) shows that augmenting the instruction data mix with visually grounded, self-supervised-style tasks is sufficient to improve visual perception. Related efforts construct vision-centric instruction data through dense, detailed captions (Chen et al., 2024b), region-level and grounded conversations (Chen et al., 2023), or synthetic data targeting fine-grained visual differences (Jiao et al., 2025). More recently visual capabilities can be improved during post-training. For example GRPO-style methods have been successfully adapted to multimodal models (Huang et al., 2026; Liu et al., 2025; Yu et al., 2026), including approaches that use self-supervised visual tasks such as jigsaw puzzles as verifiable training signals (Wang et al., 2025c). However, such methods provide only sparse, sequence-level rewards, which offer limited guidance on which parts of a response fail to use the visual input. This has motivated a shift toward denser, token-level supervision through on-policy self-distillation (OPSD), which we discuss next.

Visual On-policy Self-Distillation. On-policy distillation (OPD) has emerged as an effective technique for improving reasoning in language models and, more recently, in multimodal models. It relies on token-level supervision from a stronger teacher (Agarwal et al., 2024), while on-policy self-distillation removes the need for an external teacher by deriving the teacher signal from the model itself under privileged context (Zhao et al., 2026). A recent surge of concurrent approaches for MLLMs differs mainly in the type of the teacher–student asymmetry. For example Vision-OPD (Yuan et al., 2026) conditions the teacher on an evidence-centered crop while the student sees a full image. Imagine-OPD (Cai et al., 2026) gives the teacher privileged zoomed evidence views and distills them into imagination-based reasoning. OPD-V (Aniri et al., 2026) uses a positive teacher conditioned on an evidence-centered crop and a negative teacher conditioned on masked crop while RP-OPSD (Zhu et al., 2026) constructs the teacher-student asymmetry through resolution. S^2VOPD (Li et al., 2026) takes a different approach by removing information from the student rather than adding privileged information to the teacher. The teacher observes the original image while the student observes a strongly augmented version of the same image. VCSD (Liang et al., 2026) contrasts teacher predictions under the original image and a content-erased control. Finally,



Figure 2: **Spatially grounded privileged guidance with `Where-OPD`. (a)** A procedural scene provides an image I, a question Q, and a hint h listing the target objects' locations. The student receives $x = (I, Q)$; the frozen teacher receives $x^+ = (I, Q, h)$ and scores the student's sampled prefixes for on-policy distillation. Only the student's parameters are updated. **(b)** Visualization of training scenes showing variation in backgrounds, object categories, and counts.

ViCuR (Tian et al., 2026) replaces reasoning-trace-based privilege with question-relevant visual cues that describe evidence already present in the image. In this work, we also induce the teacher–student asymmetry by providing the teacher with visually grounded hints expressed in text. Inspired by prior work on procedurally generated data for visual and spatial reasoning with programmatically generated questions (Johnson et al., 2017; Hudson & Manning, 2019) we construct the entire post-training dataset procedurally, using scene metadata to automatically generate question-relevant spatial guidance.

3 Method

We introduce an on-policy self-distillation framework in which the teacher receives textual, spatially grounded guidance identifying question-relevant visual elements and their locations, while the student observes only the image and question (see Fig. 2 for an overview). We obtain this privileged information automatically from procedurally generated scenes, enabling annotation-free post-training without an external teacher model. We first review on-policy self-distillation (Sec. 3.1), then present our spatially grounded guidance, its procedural generation, and the resulting training objective (Sec. 3.2).

3.1 Preliminaries: On-Policy Self-Distillation

On-policy self-distillation (OPSD) uses a frozen or exponential-moving-average (EMA) copy of the student as a teacher, augmented with privileged information unavailable to the student. Let π_θ denote the student model and $\pi_{\bar{\theta}}$ the privileged teacher model. Given an input x, which for an MLLM consists of an image I and a question Q, i.e., $x = (I, Q)$, on-policy distillation (OPD) samples trajectories from the current student policy,

$$y \sim \pi_\theta(\cdot \mid x). \tag{1}$$

The teacher then provides token-level supervision on the same prefixes visited by the student. At token position t, their predictive distributions are

$$p_t = \pi_\theta(\cdot \mid x, y_{<t}), \qquad q_t = \pi_{\bar{\theta}}(\cdot \mid x^+, y_{<t}). \tag{2}$$

where x^+ denotes the privileged input available only to the teacher. Distillation is thus performed by minimizing a divergence between p_t and q_t on states visited by the current student policy (on-policy), rather than on trajectories generated independently by the teacher.

For MLLMs, the construction of x^+ determines the teacher–student information gap and is therefore a central design choice. Prior work commonly provides the teacher with an enhanced or localized visual observation I^+, i.e., $x^+ = (I^t, Q)$, while the student observes the original image I. We instead keep the visual observation unchanged and provide the teacher with textual, spatially grounded privileged information, h as described next.

3.2 Spatially Grounded Privileged Guidance

Our goal is to provide the teacher with explicit information about *where* the visual evidence relevant to a question is located, rather than with a different view of the image. Specifically, given an image I, question Q, and spatially grounded textual hint h, the student receives $x = (I, Q)$, while the teacher additionally receives the hint, $x^+ = (I, Q, h)$.

The hint identifies the visual elements relevant to the question and points to their locations in the image. For example, for a question asking how many cars are present, such guidance could identify the image locations corresponding to the relevant cars and provide their resulting count. The teacher therefore has explicit access to the locations of the evidence needed to answer the question, while the student must infer the relevant visual evidence from the image and question alone. The privileged guidance is used only during post-training and is absent at inference time.

3.2.1 Procedural Generation of Spatial Guidance

A practical challenge is obtaining spatial guidance at scale without human annotations or an external grounding model. We address this by procedurally generating post-training data, such that the identities, attributes, and locations of all visual elements are known from the scene-generation process. We use counting questions because answering them requires identifying all instances matching a query, naturally providing supervision over multiple question-relevant image locations.

Each training example is built from a *scene*: a synthetic canvas on which simple visual elements, colored geometric shapes, are placed at non-overlapping positions over a uniform background. Unlike a natural image, a scene is fully specified by the generator before it is rendered. Formally, a scene is described by its state

$$z = \big(\{(c_i, r_i, u_i, v_i)\}_{i=1}^{M}, b\big), \tag{3}$$

where c_i denotes the color–shape category of the i-th visual element, r_i its radius, (u_i, v_i) its center in image coordinates, M the number of visual elements, and b the background color. The state thus records the identity, attributes, and location of every element, and rendering z produces the corresponding image I.

For each scene, we sample a counting question Q targeting a category c present in z. Since the complete scene specification is known, we can directly identify all question-relevant elements as

$$\mathcal{O}_c(z) = \{(u_i, v_i) \mid c_i = c\}, \tag{4}$$

whose count $N_c = |\mathcal{O}_c(z)|$ gives the answer a. We then construct the privileged textual hint using a fixed template $\mathcal{T}$,

$$h = \mathcal{T}\big(c, \mathcal{O}_c(z)\big), \tag{5}$$

which names the target category, lists the location of each matching instance, and concludes with their count. For example, for the question *"How many green crosses are there?"*, if two matching objects occur at $(377, 400)$ and $(213, 805)$, the privileged hint is:

```
Scanning for green crosses:  found one near (377, 400),
found one near (213, 805).  Counting:  2 total.
```

Thus, while the post-training task itself is simple, its privileged signal explicitly identifies multiple pieces of question-relevant visual evidence and their spatial locations. Notably, the complete training tuple (I, Q, a, h) is generated automatically from z, without human annotations, region proposals, or an external higher-capacity MLLM.

We generate 1024×1024 scenes containing colored geometric objects from seven shape classes and twelve colors on a flat background. Each scene contains between 12 and 40 objects, each drawn with a radius between 14 and 64 pixels. Questions ask for the number of objects belonging to a sampled color–shape category. Our main post-training set contains 3,000 generated image–question pairs with their corresponding privileged hints. More details about the generation can be found in A.1 of the Appendix.

3.2.2 Spatially Privileged On-Policy Self-Distillation

We use the procedurally generated hints within OPSD. Both student and teacher are initialized from the same pretrained checkpoint. In our main setting, the teacher is frozen at initialization, $\bar{\theta} = \theta_0$.

For each training example, we instantiate the student and privileged teacher inputs as $x = (I, Q)$ and $x^+ = (I, Q, h)$, respectively, and apply on-policy self-distillation as described in Sec. 3.1.

We minimize the generalized Jensen–Shannon divergence between the student and privileged teacher distributions, with $\beta = 0.5$. For computational efficiency, the divergence is computed over the student's top $K = 100$ tokens and the corresponding teacher logits, alongside a tail-probability term. Let $\tilde{p}_t$ and $\tilde{q}_t$ denote the resulting distributions. Our training objective is

$$\mathcal{L}_{\text{distill}} = \mathbb{E}_{y \sim \pi_\theta(\cdot|x)} \left[\frac{1}{|y|} \sum_{t=1}^{|y|} D_{\text{JS}}\big(\tilde{p}_t \,\|\, \tilde{q}_t\big) \right], \tag{6}$$

where

$$D_{\text{JS}}(p\|q) = \frac{1}{2} D_{\text{KL}}(p\|m) + \frac{1}{2} D_{\text{KL}}(q\|m), \qquad m = \frac{1}{2}(p+q). \tag{7}$$

The privileged teacher distribution $\tilde{q}_t$ is treated as a fixed target, so gradients flow only through the student. At inference time, the model receives only (I, Q); the privileged hint is used exclusively during post-training.

4 Experiments

In this section, we evaluate whether spatially grounded privileged guidance improves visual capabilities of MLLMs. We first describe the experimental setup in Sec. 4.1 and compare with prior on-policy self-distillation methods in Sec. 4.2. Finally, we analyze the training signal and our design choices in Sec. 4.3.

4.1 Experimental Setup

Training details. Our experimental setup covers three base models: Qwen3.5-4B and Qwen3.5-9B (Team, 2026), as well as Qwen3-VL-4B (Bai et al., 2025). We initialize a teacher and a student from the same checkpoint and train on 3,000 procedurally generated counting scenes. For smaller models (Qwen3.5-4B and Qwen3-VL-4B) we apply `Where-OPD` with a multiple-choice question protocol, while for Qwen3.5-9B we implement an open-ended version for same scenes. Detailed input can be found in Fig. 5. All models are trained for one epoch. Only `Where-OPD` results for Qwen3.5-4B and Qwen3.5-9B in Tab. 1 are each averaged over three independent training runs with different fixed seeds; all other post-training results, including the ablations and analyses, come from one run per setting. Further details are given in Sec. A.2 of the Appendix.

Baselines. We compare `Where-OPD` with Vision-OPD (Yuan et al., 2026), OPD-V (Aniri et al., 2026), Imagine-OPD (Cai et al., 2026), and S^{2}VOPD (Li et al., 2026). We use publicly released or author-provided checkpoints and evaluate them with the same protocol as our models.

Evaluation benchmarks. We evaluate on a broad suite of 15 benchmarks spanning a wide range of general visual skills. These include counting with CountQA (Tamarapalli et al., 2025), document understanding with DocVQA (Mathew et al., 2021) and OCRBench (Liu et al., 2024b), and chart understanding with ChartQA (Masry et al., 2022) and EvoChart (Huang et al., 2025), as well as general visual perception with CVBench (Tong et al., 2024), BLINK (Fu et al., 2024), MME-RealWorld (Zhang et al., 2025), GQA (Hudson & Manning, 2019), as well as Hallusion-Bench (Guan et al., 2024) and AMBER (Wang et al., 2023) to assess hallucinations. We further evaluate on benchmarks that require fine-grained, detail-level understanding, where answering depends on locating and zooming into small regions of high-resolution images including: V* (Wu & Xie, 2024), HR-Bench 4K and 8K (Wang et al., 2025b), and ZoomBench (Wei et al., 2026). Since the suite consists largely of real-world images and tasks beyond counting, it measures how well skills learned on our rendered training scenes transfer to realistic settings. Compared with the narrower evaluation suites used in prior work, this broader selection lets us assess generalization across diverse visual capabilities. We report accuracy (%) on each benchmark and the unweighted mean across all reported benchmarks. Unless otherwise specified, our evaluation uses greedy decoding with thinking disabled.

Table 1: **Main results across three MLLMs.** Accuracy (%) on 15 benchmarks; Avg. is their unweighted mean. The smaller numbers below each score show the change in accuracy relative to the corresponding base model. CVB: CVBench; MME-RW: MME-RealWorld; OCRB: OCRBench; HallB: HallusionBench; HR-4K/8K: HR-Bench 4K/8K; Zoom: ZoomBench. For `Where-OPD` on Qwen3.5-4B and Qwen3.5-9B as base model, each score is the mean of three training runs with different seeds; the standard deviation of Avg. across runs is ±0.20 for both Qwen3.5-4B and Qwen3.5-9B.

	General											High-resolution				
Model	CVB	MME-RW	BLINK	GQA	CountQA	ChartQA	DocVQA	OCRB	EvoChart	HallB	AMBER	V*	HR-4K	HR-8K	Zoom	Avg.
Qwen3.5-4B base model	87.45	64.11	66.28	69.32	32.00	79.32	96.00	87.30	68.32	69.40	88.80	82.72	**86.25**	80.00	50.65	73.86
Vision-OPD	87.53 +0.08	75.26 +11.15	62.02 −4.26	68.23 −1.09	21.27 −10.73	78.52 −0.80	95.98 −0.02	87.00 −0.30	67.28 −1.04	65.83 −3.57	86.32 −2.48	91.62 +8.90	83.50 −2.75	80.25 +0.25	65.21 +14.56	74.39 +0.53
OPD-V	85.97 −1.48	**75.76** +11.65	61.91 −4.37	67.61 −1.71	26.11 −5.89	81.12 +1.80	96.00 ±0.00	87.50 +0.20	70.32 +2.00	68.03 −1.37	82.78 −6.02	**94.24** +11.52	85.00 −1.25	82.38 +2.38	**65.44** +14.79	75.34 +1.48
S^2VOPD	87.91 +0.46	75.59 +11.48	64.70 −1.58	68.61 −0.71	31.87 −0.13	79.88 +0.56	95.98 −0.02	87.50 +0.20	69.44 +1.12	65.72 −3.68	88.20 −0.60	88.48 +5.76	85.12 −1.13	**83.88** +3.88	56.09 +5.44	75.26 +1.40
`Where-OPD`	**89.76** +2.31	74.75 +10.64	**67.77** +1.49	**75.41** +6.09	**34.53** +2.53	**86.52** +7.20	**97.00** +1.00	**89.23** +1.93	**78.43** +10.11	**80.16** +10.76	**93.28** +4.48	87.96 +5.24	85.62 −0.63	82.67 +2.67	51.52 +0.87	**78.31** +4.45
Qwen3.5-9B base model	**88.02**	71.45	**69.86**	69.45	37.04	80.12	96.47	90.00	69.04	71.82	88.79	85.86	85.62	81.25	52.31	75.81
Vision-OPD	87.49 −0.53	73.29 +1.84	66.39 −3.47	69.27 −0.18	35.01 −2.03	81.12 +1.00	**96.80** +0.33	89.90 −0.10	71.44 +2.40	72.98 +1.16	87.74 −1.05	91.10 +5.24	**87.38** +1.76	**86.75** +5.50	**64.97** +12.66	77.44 +1.64
OPD-V	84.99 −3.03	71.58 +0.13	61.13 −8.73	69.18 −0.27	30.30 −6.74	81.16 +1.04	96.67 +0.20	**90.60** +0.60	72.64 +3.60	72.34 +0.52	87.68 −1.11	**93.72** +7.86	83.75 −1.87	83.25 +2.00	63.91 +11.60	76.19 +0.39
`Where-OPD`	87.97 −0.05	**74.73** +3.28	69.24 −0.62	**69.52** +0.07	**38.26** +1.22	**86.05** +5.93	96.71 +0.24	90.27 +0.27	**75.47** +6.43	**75.39** +3.57	**89.06** +0.27	87.78 +1.92	86.38 +0.76	84.67 +3.42	51.99 −0.32	**77.57** +1.76
Qwen3-VL-4B base model	85.44	63.22	65.49	71.01	27.68	77.20	**95.29**	**87.70**	62.48	70.66	89.61	81.15	80.00	75.12	45.09	71.81
OPD-V	83.89 −1.55	**68.10** +4.88	62.70 −2.79	70.42 −0.59	24.74 −2.94	77.24 +0.04	95.25 −0.04	86.80 −0.90	62.48 ±0.00	70.14 −0.52	88.24 −1.37	**86.91** +5.76	81.25 +1.25	**77.00** +1.88	**54.67** +9.58	72.66 +0.85
Imagine-OPD	85.97 +0.53	66.38 +3.16	**66.07** +0.58	**71.28** +0.27	27.29 −0.39	77.28 +0.08	95.27 −0.02	87.30 −0.40	63.76 +1.28	68.35 −2.31	89.79 +0.18	85.34 +4.19	**82.25** +2.25	76.62 +1.50	45.56 +0.47	72.57 +0.76
`Where-OPD`	**86.58** +1.14	65.25 +2.03	65.86 +0.37	71.16 +0.15	**30.37** +2.69	**77.68** +0.48	95.27 −0.02	**87.70** ±0.00	**64.24** +1.76	**71.29** +0.63	**90.06** +0.45	84.29 +3.14	81.38 +1.38	75.25 +0.13	45.92 +0.83	**72.82** +1.01

4.2 Main Results

Broad gains across MLLMs and benchmarks. As shown in Tab. 1, our method achieves the highest average across all evaluated benchmarks on each of the MLLMs. Improvements span multiple visual capabilities: CountQA, ChartQA, EvoChart, and HallusionBench improve consistently across all three MLLMs, while document understanding performance is largely preserved or improved. In contrast, methods based on enhanced or localized visual observations achieve substantial gains on high-resolution visual-search benchmarks, particularly V* and ZoomBench, but show less consistent improvements across other tasks. For instance, Vision-OPD and OPD-V decrease CountQA and BLINK performance on both Qwen3.5-4B and Qwen3.5-9B and often degrade hallucination-sensitive performance. Overall, these results indicate that our spatially grounded guidance yields improvements across a broader range of the evaluated tasks.

Transfer beyond synthetic counting scenes. Despite using only procedurally generated geometric scenes for post-training, our method improves performance on diverse benchmarks involving real-world images and tasks beyond counting. Notably, MME-RealWorld, HallusionBench, V^*, HR-Bench 8K, GQA, and AMBER improve across all three MLLMs, alongside gains in chart and document understanding. This demonstrates that the benefits of our training approach extend beyond both the visual appearance and the counting task of the synthetic training data.

4.3 Experimental Analysis

In this section, we present additional experiments that provide further insight into our method. Unless stated otherwise, we report the average accuracy over seven representative benchmarks covering each skill category.

Are the gains due to synthetic data alone? To isolate the effect of the training signal from that of the synthetic data, we compare different supervision signals in Tab. 2, keeping the base model, the synthetic scenes, and the number of training steps fixed. SFT and GRPO (Shao et al., 2024) yield only marginal or no gains, while OPSD achieves the highest average of the three. These results show

Table 2: **Training signals and privileged hints on Qwen3.5-4B.** SFT, GRPO, and the OPSD variants are trained on the same 3,000 synthetic scenes for the same number of steps as `Where-OPD`. Results are accuracy (%); Avg. is the unweighted mean across benchmarks present in the table. CVB: CVBench; HR-4K/8K: HR-Bench 4K/8K; Zoom: ZoomBench.

Training signal	CVB	V*	HR-4K	HR-8K	Zoom	CountQA	EvoChart	Avg.
Qwen3.5-4B	87.45	82.72	86.25	80.00	50.65	32.00	68.32	69.63
SFT	87.68	**89.01**	83.38	79.12	50.18	31.81	66.72	69.70
GRPO	87.83	83.25	81.88	80.12	49.11	33.12	71.60	69.56
OPSD, no privileged information	87.53	82.72	85.00	81.00	50.41	32.46	68.32	69.63
OPSD, cropped-image hint	88.44	83.77	82.50	79.25	**52.31**	20.22	74.80	68.76
OPSD, answer-only hint	88.48	84.82	83.25	79.38	51.12	33.51	78.32	71.27
OPSD, spatial guidance hint, no total	89.88	87.96	85.25	81.00	50.77	**34.62**	76.96	72.35
OPSD, spatial guidance hint (`Where-OPD`)	**89.92**	88.48	85.50	**83.25**	51.01	33.77	**78.64**	**72.94**

Table 3: **Best tested inference settings on Qwen3.5-4B.** For each model and benchmark, the reported accuracy (%) is the best across thinking enabled or thinking disabled. Settings are selected separately for each cell; Avg. is the mean of the 15 selected scores. Smaller numbers show percentage-point changes from the base model. CVB: CVBench; MME-RW: MME-RealWorld; OCRB: OCRBench; HallB: HallusionBench; HR-4K/8K: HR-Bench 4K/8K; Zoom: ZoomBench.

	General											High-resolution				
Model	CVB	MME-RW	BLINK	GQA	CountQA	ChartQA	DocVQA	OCRB	EvoChart	HallB	AMBER	V*	HR-4K	HR-8K	Zoom	Avg.
Qwen3.5-4B	89.16	70.30	**71.23**	69.32	46.86	86.28	96.45	87.30	77.36	69.82	88.80	82.72	**88.12**	81.50	50.65	77.06
Vision-OPD	88.51 −0.65	**75.26** +4.96	67.75 −3.48	68.23 −1.09	42.74 −4.12	86.04 −0.24	96.24 −0.21	87.00 −0.30	75.52 −1.84	67.09 −2.73	86.32 −2.48	**92.15** +9.43	83.50 −4.62	81.00 −0.50	**65.21** +14.56	77.50 +0.45
`Where-OPD`	**90.45** +1.29	74.59 +4.29	**71.23** ±0.00	**75.39** +6.07	**54.12** +7.26	**86.56** +0.28	**97.01** +0.56	**89.20** +1.90	**78.64** +1.28	**81.60** +11.78	**94.37** +5.57	88.48 +5.76	86.62 −1.50	**83.25** +1.75	53.61 +2.96	**80.34** +3.28

that synthetically generated scenes with spatially grounded hints yield consistent improvements over a range of visual skills when used in the OPSD training. We provide more details on different training configurations in Sec. A.4 of the Appendix.

Does spatial guidance matter? The choice of privileged information substantially affects performance (Tab. 2). Without privileged information, OPSD remains at the base-model average, highlighting the importance of teacher–student information asymmetry. Providing the correct answer improves performance, but spatial coordinates alone, without the final count, yield a higher average (72.35 vs. 71.27). Combining coordinates with the count achieves the highest average (72.94). In contrast, providing cropped images of the target objects, as in Vision-OPD, reduces the average and substantially degrades CountQA. These ablations highlight the importance of spatially grounded guidance, beyond simply revealing the correct answer or providing localized visual observations.

How much synthetic data is needed? The data-size ablations in Appendix B (Tab. 6) show that, with one epoch per setting, 3,000 scenes is sufficient yielding the best performance for both MLLMs among the tested data sizes. Additional scene-generation ablations in Appendix B (Tab. 5) show that our default 1024×1024 resolution and $M \in \{12, \ldots, 40\}$ objects per scene give the highest average among the tested settings, although we notice that CountQA benefits from denser scenes.



Figure 3: **Impact of the teacher update rate on Qwen3.5-4B** when trained with `Where-OPD`. We report the average performance across benchmarks against the EMA rate η; the filled point and dashed line mark training with teacher frozen.

Frozen or EMA teacher? In Fig. 3, we examine the impact of updating the teacher during training. Interestingly, keeping the teacher frozen ($\eta = 0$) yields the best average performance, and increasing η generally degrades it. We hypothesize that updating the teacher on synthetic images may introduce a slight domain shift, diminishing the overall gains. Detailed per-benchmark results are provided in Appendix Tab. 7.

Effect of thinking mode. For computational efficiency, all models are trained and, by default, evaluated with thinking disabled. To study the effect of additional inference-time compute, in Tab. 3



Figure 4: **Visual evidence on EvoChart, HallusionBench and CountQA.** We show each visual input, question, ground-truth answer, and attention maps from the response tokens to the image for Qwen3.5-4B, Vision-OPD, and `Where-OPD`. Layers are selected on held-out synthetic scenes (Tab. 9); predictions appear below each map. Numbered dashed boxes indicate question-relevant regions, e.g., the legend and 2018 values in (a), and the USA label and land areas of Russia, Canada, and the USA in (b), added solely for visualization and absent from the models' inputs. Checkmarks indicate regions receiving at least twice their area-proportional share of attention. Unlike the baselines, `Where-OPD` attends to all marked regions in (a) and (b), suggesting better alignment with question-relevant visual evidence. In (c), its attention more clearly follows the boundaries of the stacked boxes, correctly predicting five where the baselines fail.

we report, the better of the two results obtained with thinking enabled and disabled for all 15 benchmarks. Comparing the baseline model with `Where-OPD`, we find that `Where-OPD` improves on average by 3.28 and on majority of benchmarks. Vision-OPD yields only a modest average gain of 0.45 points: its improvements are concentrated on V*, ZoomBench, and MME-RealWorld, while it decreases accuracy on the remaining 12 benchmarks. Additionally, we provide the results with thinking always enabled in Appendix Tab. 8.

Qualitative examples: Attention to question-relevant visual evidence. Fig. 4 presents qualitative examples of Qwen3.5-4B post-trained with `Where-OPD`. On EvoChart and HallusionBench, `Where-OPD` not only predicts the correct answers but also attends to all marked question-relevant regions, unlike the base model and Vision-OPD. On CountQA (Fig. 4c), `Where-OPD` exhibits attention that more clearly follows the boundaries of the stacked boxes and correctly counts all five instances, whereas both baselines fail. These examples suggest that spatially grounded guidance encourages better alignment of attention with the visual evidence needed to answer each question.

5 Conclusion

We introduce `Where-OPD`, which uses spatially grounded guidance as privileged information for on-policy self-distillation of multimodal large language models. Using procedurally generated scenes, we provide the teacher with textual hints identifying question-relevant elements and their locations, while the student learns from the image and question alone. Compared with methods that give the teacher enhanced visual inputs, `Where-OPD` achieves improvements across a broader range of evaluated tasks, transferring to real-world images despite training exclusively on synthetic scenes. Ablations show that spatial grounding is important: removing the hint or providing the answer without locations yields lower performance. Together, these results suggest that privilege in the form of guidance towards relevant visual evidence provides a transferable distillation signal.

AI USE STATEMENT

In this work, we used generative AI tools to monitor experiments, polish text and write TikZ code for figures, design and provide feedback on experiments, implement methods. We have not used generative AI tools for generation of synthetic datasets, help develop theoretical models or conceptual frameworks, formulate mathematical claims, provide critical ingredients for proving mathematical claims, assist in the writing of proofs, propose or refine hypotheses, assist with translation, clean and reformat dataset, support qualitative and thematic data analysis. The rest of the required disclosure tasks are not applicable to this work. We have reviewed all AI-assisted work and we take full responsibility for the final content of this work.

ETHICS STATEMENT

This work does not involve any study on human subjects. We plan to release the code that generates our synthetic dataset, we believe there is no ethics issue with our synthetic procedurally generated dataset.

REPRODUCIBILITY STATEMENT

We plan to publicly release training as well as data generation and evaluation code as well as checkpoints. Our training protocol as well as data generation is explained in detail in supplementary material. For `Where-OPD` on Qwen3.5-4B and Qwen3.5-9B, we report the mean over three independent training runs with different seeds and the standard deviation of the benchmark average.

REFERENCES

Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos Garea, Matthieu Geist, and Olivier Bachem. On-policy distillation of language models: Learning from self-generated mistakes. In *ICLR*, 2024. 2, 3

Jinhe Bi Aniri, Peng Liao, Zengjie Jin, Volker Tresp, Fei Shen, Yunpu Ma, and Tat-Seng Chua. Opd-v: Visual on-policy self-distillation with modality balance. *arXiv preprint arXiv:2608.05131*, 2026. 2, 3, 6

Mozhgan Nasr Azadani, James Riddell, Sean Sedwards, and Krzysztof Czarnecki. Leo: Boosting mixture of vision encoders for multimodal large language models. *arXiv preprint arXiv:2501.06986*, 2025. 3

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*, 2025. 6

Davide Caffagni, Sara Sarto, Marcella Cornia, Lorenzo Baraldi, Pier Luigi Dovesi, Shaghayegh Roohi, Mark Granroth-Wilding, and Rita Cucchiara. Seeing beyond words: Self-supervised visual learning for multimodal large language models. *arXiv preprint arXiv:2512.15885*, 2025. 3

Yishuo Cai, Jiahui Liu, Yuanxin Liu, Haobo Deng, Linli Yao, Yuhao Zheng, Kun Ouyang, Zhimo Li, Ziyue Wang, Xu Sun, et al. Thinking without images: Internalizing visual manipulation with on-policy self-distillation. *arXiv preprint arXiv:2606.08719*, 2026. 2, 3, 6

Junbum Cha, Wooyoung Kang, Jonghwan Mun, and Byungseok Roh. Honeybee: Locality-enhanced projector for multimodal llm. In *CVPR*, 2024. 3

Gongwei Chen, Leyang Shen, Rui Shao, Xiang Deng, and Liqiang Nie. Lion: Empowering multimodal large language model with dual-level visual knowledge. In *CVPR*, 2024a. 3

Keqin Chen, Zhao Zhang, Weili Zeng, Richong Zhang, Feng Zhu, and Rui Zhao. Shikra: Unleashing multimodal llm's referential dialogue magic. *arXiv preprint arXiv:2306.15195*, 2023. 3

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Conghui He, Jiaqi Wang, Feng Zhao, and Dahua Lin. Sharegpt4v: Improving large multi-modal models with better captions. In *ECCV*, 2024b. 3

Stephanie Fu, Tyler Bonnen, Devin Guillory, and Trevor Darrell. Hidden in plain sight: Vlms overlook their visual representations. *arXiv preprint arXiv:2506.08008*, 2025. 3

Xingyu Fu, Yushi Hu, Bangzheng Li, Yu Feng, Haoyu Wang, Xudong Lin, Dan Roth, Noah A Smith, Wei-Chiu Ma, and Ranjay Krishna. Blink: Multimodal large language models can see but not perceive. In *ECCV*, 2024. 6

Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, et al. Hallusionbench: an advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models. In *CVPR*, 2024. 6

Muye Huang, Han Lai, Xinyu Zhang, Wenjun Wu, Jie Ma, Lingling Zhang, and Jun Liu. Evochart: A benchmark and a self-training approach towards real-world chart understanding. In *AAAI*, 2025. 6

Wenxuan Huang, Bohan Jia, Shaosheng Cao, Zheyu Ye, Zhe Xu, Yao Hu, Shaohui Lin, et al. Vision-r1: Incentivizing reasoning capability in multimodal large language models. In *ICLR*, 2026. 3

Drew A Hudson and Christopher D Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *CVPR*, 2019. 2, 4, 6

Qirui Jiao, Daoyuan Chen, Yilun Huang, Bolin Ding, Yaliang Li, and Ying Shen. Img-diff: Contrastive data synthesis for multimodal large language models. In *CVPR*, 2025. 3

Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *CVPR*, 2017. 2, 4

Oğuzhan Fatih Kar, Alessio Tonioni, Petra Poklukar, Achin Kulshrestha, Amir Zamir, and Federico Tombari. Brave: Broadening the visual encoding of vision-language models. In *ECCV*, 2024. 3

Yijiang Li, Yijun Liang, Yunjie Tian, Bingyang Wang, Ke Zhang, Zhenfei Yin, Di Fu, Philip Torr, and Nuno Vasconcelos. Self-supervised visual on-policy distillation. *arXiv preprint arXiv:2608.14144*, 2026. 2, 3, 6

Yijun Liang, Yunjie Tian, Yijiang Li, Yuqi Jia, Furong Huang, Tianyi Zhou, and Di Fu. Visual contrastive self-distillation. *arXiv preprint arXiv:2607.21556*, 2026. 2, 3

Junyan Lin, Haoran Chen, Yue Fan, Yingqi Fan, Xin Jin, Hui Su, Jinlan Fu, and Xiaoyu Shen. Multi-layer visual feature fusion in multimodal llms: Methods, analysis, and best practices. In *CVPR*, 2025. 3

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. In *CVPR*, 2024a. 3

Yuliang Liu, Zhang Li, Mingxin Huang, Biao Yang, Wenwen Yu, Chunyuan Li, Xu-Cheng Yin, Cheng-Lin Liu, Lianwen Jin, and Xiang Bai. Ocrbench: on the hidden mystery of ocr in large multimodal models. *Science China Information Sciences*, 2024b. 6

Ziyu Liu, Zeyi Sun, Yuhang Zang, Xiaoyi Dong, Yuhang Cao, Haodong Duan, Dahua Lin, and Jiaqi Wang. Visual-rft: Visual reinforcement fine-tuning. In *ICCV*, 2025. 3

Haoyu Lu, Wen Liu, Bo Zhang, Bingxuan Wang, Kai Dong, Bo Liu, Jingxiang Sun, Tongzheng Ren, Zhuoshu Li, Hao Yang, et al. Deepseek-vl: Towards real-world vision-language understanding, 2024. *URL https://arxiv. org/abs/2403.05525*, 2025. 3

Ahmed Masry, Jia Qing Tan, Shafiq Joty, Enamul Hoque, et al. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. In *ACL Findings*, 2022. 2, 6

Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In *WACV*, 2021. 6

Brandon McKinzie, Zhe Gan, Jean-Philippe Fauconnier, Sam Dodge, Bowen Zhang, Philipp Dufter, Dhruti Shah, Xianzhi Du, Futang Peng, Anton Belyi, et al. Mm1: methods, analysis and insights from multimodal llm pre-training. In *ECCV*, 2024. 3

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024. 7

Min Shi, Fuxiao Liu, Shihao Wang, Shijia Liao, Subhashree Radhakrishnan, Yilin Zhao, De-An Huang, Hongxu Yin, Karan Sapra, Yaser Yacoob, et al. Eagle: Exploring the design space for multimodal llms with mixture of encoders. *arXiv preprint arXiv:2408.15998*, 2024. 3

Sophia Sirko-Galouchenko, Monika Wysoczanska, Andrei Bursuc, Nicolas Thome, and Spyros Gidaris. Boosting visual instruction tuning with self-supervised guidance. *arXiv preprint arXiv:2604.12966*, 2026. 3

Jayant Sravan Tamarapalli, Rynaa Grover, Nilay Pande, and Sahiti Yerramilli. Countqa: How well do mllms count in the wild? *arXiv preprint arXiv:2508.06585*, 2025. 6

Qwen Team. Qwen3. 5: Towards native multimodal agents. *URL: https://qwen. ai/blog*, 2026. 6

Kanghui Tian, Siyuan Liu, Ziang Yan, Sheng Xia, Shuai Dong, and Yi Wang. Vicur: Visual cues as recoverable privilege for multimodal on-policy distillation. *arXiv preprint arXiv:2606.05718*, 2026. 4

Peter Tong, Ellis Brown, Penghao Wu, Sanghyun Woo, Adithya Jairam Vedagiri Iyer, Sai Charitha Akula, Shusheng Yang, Jihan Yang, Manoj Middepogu, Ziteng Wang, et al. Cambrian-1: A fully open, vision-centric exploration of multimodal llms. *NeurIPS*, 2024. 3, 6

Haochen Wang, Anlin Zheng, Yucheng Zhao, Tiancai Wang, Zheng Ge, Xiangyu Zhang, and Zhaoxiang Zhang. Reconstructive visual instruction tuning. In *ICLR*, 2025a. 3

Junyang Wang, Yuhang Wang, Guohai Xu, Jing Zhang, Yukai Gu, Haitao Jia, Jiaqi Wang, Haiyang Xu, Ming Yan, Ji Zhang, et al. Amber: An llm-free multi-dimensional benchmark for mllms hallucination evaluation. *arXiv preprint arXiv:2311.07397*, 2023. 6

Wenbin Wang, Liang Ding, Minyan Zeng, Xiabin Zhou, Li Shen, Yong Luo, Wei Yu, and Dacheng Tao. Divide, conquer and combine: A training-free framework for high-resolution image perception in multimodal large language models. In *AAAI*, 2025b. 6

Zifu Wang, Junyi Zhu, Bo Tang, Zhiyu Li, Feiyu Xiong, Jiaqian Yu, and Matthew B. Blaschko. Jigsaw-r1: A study of rule-based visual reinforcement learning with jigsaw puzzles. *TMLR*, 2025c. 3

Lai Wei, Liangbo He, Jun Lan, Lingzhong Dong, Yutong Cai, Siyuan Li, Huijia Zhu, Weiqiang Wang, Linghe Kong, Yue Wang, et al. Zooming without zooming: Region-to-image distillation for fine-grained multimodal perception. *arXiv preprint arXiv:2602.11858*, 2026. 6

Penghao Wu and Saining Xie. V*: Guided visual search as a core mechanism in multimodal llms. In *CVPR*, 2024. 6

Heeji Yoon, Jaewoo Jung, Junwan Kim, Hyungyu Choi, Heeseong Shin, Sangbeom Lim, Honggyu An, Chaehyun Kim, Jisang Han, Donghyun Kim, et al. Visual representation alignment for multimodal large language models. *arXiv preprint arXiv:2509.07979*, 2025. 3

En Yu, Kangheng Lin, Liang Zhao, Yana Wei, Yuang Peng, Haoran Wei, Jianjian Sun, Chunrui Han, Zheng Ge, Xiangyu Zhang, et al. Perception-r1: Pioneering perception policy with reinforcement learning. *NeurIPS*, 2026. 3

Qianhao Yuan, Jie Lou, Xing Yu, Hongyu Lin, Le Sun, Xianpei Han, and Yaojie Lu. Vision-opd: Learning to see fine details for multimodal llms via on-policy self-distillation. *arXiv preprint arXiv:2605.18740*, 2026. 2, 3, 6

YiFan Zhang, Huanyu Zhang, Haochen Tian, Chaoyou Fu, Shuangqing Zhang, Junfei Wu, Feng Li, Kun Wang, Qingsong Wen, Zhang Zhang, et al. Mme-realworld: Could your multimodal llm challenge high-resolution real-world scenarios that are difficult for humans? In *ICLR*, 2025. 6

Siyan Zhao, Zhihui Xie, Mengchen Liu, Jing Huang, Guan Pang, Feiyu Chen, and Aditya Grover. Self-distilled reasoner: On-policy self-distillation for large language models. *arXiv preprint arXiv:2601.18734*, 2026. 2, 3

Qihui Zhu, Yuchen Wang, Zijian Wen, Tao Zhang, Mengjie Zhang, Yang Liu, Shuangwu Chen, Siying Wu, Jian Yang, and Xiaofeng Jiang. Rp-opsd: Resolution-privileged on-policy self-distillation for multimodal large language models. *arXiv preprint arXiv:2607.24447*, 2026. 2, 3

APPENDIX

A Implementation details **14**

A.1 Synthetic counting data 14

A.2 Training details 14

A.3 Evaluation Protocol 15

A.4 Baselines: GRPO and supervised fine-tuning 15

B Additional Results **15**

B.1 Are results driven by in domain tasks? 15

B.2 Scene-generation and training ablations 16

B.3 Additional qualitative results 17

B.4 Layer selection for attention map visualization 20

A IMPLEMENTATION DETAILS

A.1 SYNTHETIC COUNTING DATA

All training sets are generated procedurally.

Each scene is a 1024×1024 frame with a solid-color background. The background color is sampled from ten base colors—seven light neutrals and tints and three dark colors—with small per-channel jitter, so exact background colors are rarely repeated. Each object combines one of twelve colors with one of seven shapes (circle, square, triangle, diamond, star, cross, or hexagon), with each shape parameterized by a single radius.

For each scene, we first sample a small vocabulary of two to five colors and two to four shapes. We then place 12–40 objects, drawing each object's shape and color from that vocabulary, its radius from 14–64 pixels, and its center within the frame, rejecting any placement that overlaps an existing object. All scene-generation draws are uniform. The question targets a color–shape pair present in the scene, selected with probability proportional to its count so that questions favor pairs with more objects over singletons. The multiple-choice distractors are near misses of the true count. The resulting training set of 3,000 scenes contains a median of 26 objects per scene, and the target count ranges from 1 to 14, with a median of 3.

Because the generator knows every object's position, the teacher's hint is generated directly from the scene state and is exact by construction, requiring no manual annotation. For the main models, the hint narrates a search over the target coordinates and concludes with the count. It therefore provides three pieces of information at once: the target object type, the locations of its instances, and the answer. Fig. 5 shows one record exactly as each model receives it.

For the 4B models, we used multiple-choice questions, whereas for the 9B model, we used open-ended questions (see Fig. 5). This choice was motivated by our observation that multiple-choice questions frequently elicited direct answers without intermediate reasoning tokens from the 9B model, limiting the supervision available for on-policy self-distillation.

A.2 TRAINING DETAILS

We train all of the models for one epoch with eight on-policy rollouts per prompt, a global batch size of 96, and a learning rate of 2×10^{-6} with 10 warm-up steps. Rollouts are generated with vLLM using stochastic sampling, with thinking disabled during training. For Qwen3.5-9B, we use the same optimization setup with a global batch size of 48. We additionally evaluate transfer to Qwen3-VL-4B-Instruct using the same synthetic supervision construction. Training `Where-OPD`



Qwen3.5-4B and Qwen3-VL-4B

```
<image>
How many brown crosses are in the image?
A. 5   B. 4   C. 3   D. 2
Answer with only the letter (A, B, C, or D), nothing else.
```

```
+ Hint: Scanning for brown crosses: found one near (929, 298),
found one near (312, 760), found one near (186, 61). Counting:
3 total.
```

Qwen3.5-9B

```
<image>
How many brown crosses are in the image?
```

```
+ Hint: the same hint, unchanged
```

Figure 5: **Training inputs across MLLMs.** All three MLLMs use the same generated scenes. Qwen3.5-4B and Qwen3-VL-4B receive a multiple-choice question, while Qwen3.5-9B receives an open-ended version. The student receives the image and question (green box); the teacher receives the same input with the grounded hint appended (red box).

on the 3,000 set takes about 1.4 h for Qwen3.5-4B and 1.2 h for Qwen3-VL-4B, and about 5.8 h for Qwen3.5-9B, all on 4 H100 GPUs.

A.3 Evaluation Protocol

All models are evaluated with the same pipeline. Responses are generated using greedy decoding, with thinking disabled. Each response is then scored in three stages. First, a rule-based verifier extracts and checks the final answer. Second, for multiple-choice questions, the option letter that the response concludes with is compared with the ground truth. Third, any response that neither stage resolves is passed to an LLM judge, which compares the response with the reference answer and returns a binary verdict. Accuracy is the fraction of questions judged correct, with unparseable or failed responses counted as incorrect. The judge and the scoring rules are identical across all methods.

A.4 Baselines: GRPO and supervised fine-tuning

Both baselines use the same 3,000 examples that were used to train `Where-OPD`. Each is trained for one epoch with a global batch of 96.

GRPO with a verifiable reward. We sample 8 rollouts per sample and assign a binary reward by comparing the extracted option letter with the ground truth. Advantages are centered by the group mean. Learning rate set to 2×10^{-6}.

Supervised fine-tuning. We minimize cross-entropy on the grounded coordinate hint as well as the ground truth final count, using learning rate of 1×10^{-5}.

B Additional Results

B.1 Are results driven by in domain tasks?

In Tab. 4 we show per category results for 6 benchmarks. We examine whether the benchmark-level gains are driven mainly by counting questions, the task seen during training. Improvements span across diverse visual categories.

Table 4: **Per-category accuracy on Qwen3.5-4B.** Accuracy (%) for Qwen3.5-4B and `Where-OPD` across six benchmarks, broken down by their category labels. n is the number of examples in each category, and Δ is `Where-OPD` minus base accuracy. Bold indicates the higher score.

Category	n	Qwen3.5-4B	`Where-OPD`	Δ
CVBench				
Count	788	72.72	**76.65**	+3.93
Depth	600	95.50	**96.33**	+0.83
Distance	600	90.17	**93.50**	+3.33
Relation	650	95.38	**96.77**	+1.39
Overall	2,638	87.45	**89.92**	+2.47
V*				
direct attributes	115	81.74	**89.57**	+7.83
relative position	76	84.21	**86.84**	+2.63
Overall	191	82.72	**88.48**	+5.76
BLINK				
Art style	117	76.07	**79.49**	+3.42
Counting	120	71.67	**80.83**	+9.16
Forensic detection	132	57.58	**62.12**	+4.54
Functional corresp.	130	**56.92**	55.38	−1.54
IQ test	150	20.67	**28.67**	+8.00
Jigsaw	150	**64.00**	63.33	−0.67
Multi-view reasoning	133	**48.12**	42.11	−6.01
Object localization	122	53.28	**56.56**	+3.28
Relative depth	124	82.26	82.26	±0.00
Relative reflectance	134	67.16	67.16	±0.00
Semantic corresp.	139	**66.91**	65.47	−1.44
Spatial relation	143	**88.11**	87.41	−0.70
Visual corresp.	172	91.28	91.28	±0.00
Visual similarity	135	82.22	**88.89**	+6.67
Overall	1,901	66.28	**67.96**	+1.68

Category	n	Qwen3.5-4B	`Where-OPD`	Δ
MME-RealWorld				
P: autonomous driving	3,660	33.06	**57.76**	+24.70
P: diagram and table	5,433	89.32	**90.45**	+1.13
P: monitoring	2,196	42.94	**51.68**	+8.74
P: OCR complex context	5,740	82.44	**92.30**	+9.86
P: remote sensing	3,738	56.05	**63.88**	+7.83
R: autonomous driving	1,344	28.79	**51.56**	+22.77
R: diagram and table	500	84.40	**85.40**	+1.00
R: monitoring	498	34.34	**50.20**	+15.86
R: OCR complex context	500	64.40	**78.20**	+13.80
Overall	23,609	64.11	**74.59**	+10.48
HallusionBench				
chart	130	79.23	**90.77**	+11.54
figure	80	81.25	**85.00**	+3.75
illusion	144	62.50	**74.31**	+11.81
map	64	70.31	**78.12**	+7.81
math	108	53.70	**81.48**	+27.78
ocr	143	79.72	**85.31**	+5.59
table	112	79.46	**91.96**	+12.50
video	170	56.47	**70.59**	+14.12
Overall	951	69.40	**81.60**	+12.20
AMBER				
attribute	7,628	85.55	**93.63**	+8.08
existence	4,924	95.43	**96.24**	+0.81
relation	1,664	84.01	**92.19**	+8.18
Overall	14,216	88.80	**94.37**	+5.57

Table 5: **Scene-generation ablations on Qwen3.5-4B.** Top: the same scenes and questions rendered at different resolutions, with hint coordinates rescaled accordingly. Bottom: different ranges for the number of objects per scene. Results are accuracy (%); Avg. is the unweighted mean across seven benchmarks. The highlighted rows show the default setting in both blocks; bold marks the best result within each block. CVB: CVBench; HR-4K/8K: HR-Bench 4K/8K; Zoom: ZoomBench.

	Benchmarks							
	CVB	V*	HR-4K	HR-8K	Zoom	CountQA	EvoChart	Avg.
Qwen3.5-4B base model	87.45	82.72	86.25	80.00	50.65	32.00	68.32	69.63
Training-scene resolution								
1024^2 (ours)	89.92	**88.48**	**85.50**	**83.25**	**51.01**	33.77	**78.64**	**72.94**
768^2	**89.99**	86.39	85.12	79.50	49.94	33.57	77.52	71.72
512^2	88.78	85.86	84.12	81.12	50.41	**34.69**	**78.64**	71.95
Objects per scene								
12–40 (ours)	**89.92**	**88.48**	85.50	**83.25**	**51.01**	33.77	**78.64**	**72.94**
25–100	89.16	83.25	85.62	80.88	49.94	34.62	77.44	71.56
50–200	88.82	82.20	**86.12**	82.38	48.99	**35.41**	76.96	71.55

B.2 Scene-generation and training ablations

Scene-generation We vary the resolution and number of objects in the synthetic training scenes (Tab. 5). The default 1024^2 resolution and 12–40 objects per scene achieve the highest seven-benchmark average among the tested settings.

Training-set size By training one epoch on each setting, Tab. 6 shows that the benchmark average is highest at 3,000 scenes for both MLLMs among the sizes tested. Larger training sets improve

Table 6: **Training-set size.** Accuracy (%) for Qwen3.5-4B (top) and Qwen3-VL-4B (bottom) after one epoch at each dataset size. The highlighted rows are the setting used in the main experiments. Avg. is the unweighted mean across seven benchmarks; bold marks the best dataset size within each backbone. CVB: CVBench; HR-4K/8K: HR-Bench 4K/8K; Zoom: ZoomBench.

		Benchmarks							
Examples	Steps	CVB	V*	HR-4K	HR-8K	Zoom	CountQA	EvoChart	Avg.
Qwen3.5-4B		87.45	82.72	86.25	80.00	50.65	32.00	68.32	69.63
1,000	10	87.00	84.29	83.50	79.00	47.93	34.42	70.24	69.48
2,000	20	89.54	86.91	**85.88**	81.88	50.65	33.97	78.24	72.44
3,000	31	**89.92**	**88.48**	85.50	**83.25**	**51.01**	33.77	78.64	**72.94**
6,000	62	88.97	83.77	84.12	81.50	49.94	35.86	**79.20**	71.91
11,000	114	89.50	86.39	83.38	79.62	50.06	**36.26**	78.00	71.89
Qwen3-VL-4B		85.44	81.15	80.00	75.12	45.09	27.68	62.48	65.28
1,000	10	85.03	82.20	79.00	74.12	44.62	29.12	63.04	65.30
3,000	31	86.58	**84.29**	**81.38**	75.25	45.92	**30.37**	**64.24**	**66.86**
6,000	62	86.66	83.25	80.88	**75.88**	45.80	**30.37**	64.16	66.71
11,000	114	**87.23**	83.25	77.88	75.50	**47.22**	23.63	63.36	65.44

Table 7: **Teacher update-rate study.** Accuracy (%) for Qwen3.5-4B (top) and Qwen3-VL-4B (bottom) at different EMA update rates η; $\eta = 0$ leaves the teacher frozen. The highlighted rows are used in the main experiments. Avg. is the unweighted mean across seven benchmarks; bold marks the best update rate within each backbone. CVB: CVBench; HR-4K/8K: HR-Bench 4K/8K; Zoom: ZoomBench.

	Benchmarks							
Teacher update rate η	CVB	V*	HR-4K	HR-8K	Zoom	CountQA	EvoChart	Avg.
Qwen3.5-4B	87.45	82.72	86.25	80.00	50.65	32.00	68.32	69.63
0 (frozen)	89.92	88.48	**85.50**	**83.25**	51.01	33.77	**78.64**	**72.94**
0.0001	89.61	**89.01**	83.12	81.50	**51.36**	**35.47**	77.92	72.57
0.001	89.31	86.91	84.75	80.38	51.01	34.75	77.84	72.14
0.01	89.27	84.82	84.25	81.62	51.01	34.75	76.88	71.80
0.1	**90.30**	84.82	84.75	81.12	50.06	34.49	78.00	71.93
Qwen3-VL-4B	85.44	81.15	80.00	75.12	45.09	27.68	62.48	65.28
0 (frozen)	**86.58**	84.29	**81.38**	**75.25**	**45.92**	**30.37**	64.24	**66.86**
0.0001	86.39	84.82	79.62	74.38	44.85	29.38	63.84	66.18
0.001	86.54	**85.34**	80.25	74.75	45.21	28.80	64.08	66.42
0.01	86.35	84.82	79.88	74.75	45.68	28.86	**64.40**	66.39
0.1	86.32	**85.34**	79.50	75.00	45.09	30.10	63.84	66.46

some individual benchmarks but do not improve the average. We therefore use 3,000 scenes in the main experiments.

EMA update rate In Tab. 7, we report per-benchmark accuracy at different teacher update rates for Qwen3.5-4B and Qwen3-VL-4B.

Thinking enabled In Tab. 8, we report accuracy for `Where-OPD` relative to base model Qwen3.5-4B across all 15 benchmarks with thinking enabled.

B.3 Additional qualitative results

Thinking traces. The three CVBench examples in Fig. 6 show how the models interpret distance in a scene. In example a), the base model treats the alignment of the lamp and door in the image

(a) CVBench



Q. Closer to the lamp (red): the table (blue) or the door (green)? answer: table

base *"The door (green box) is a doorway located on the far wall. The vertical alignment of the red and green boxes suggests the lamp is hanging directly above or very near the door. … the door is physically closer to the lamp than the table is."* **(B) door** ×

ours *"The lamp (red box) is hanging from the ceiling in the middle area of the room. The table (blue box) is a coffee table located in the immediate foreground, directly beneath the area where the lamp hangs. The door (green box) is located further back in the room, near the wall."* **(A) table** ✓

(b) CVBench



Q. Closer to the bus (red): the truck (blue) or the trailer (green)? answer: truck

base *"The bus appears to be roughly parallel with the trailer, perhaps slightly ahead or behind, but definitely closer to the trailer than to the truck which is further ahead in the left lane."* **(B) trailer** ×

ours *"The bus is driving in the lane to the right of the truck/trailer. The truck (blue box) is positioned ahead of the trailer (green box). … The truck is adjacent to the bus's lane, while the trailer is further away to the left."* **(A) truck** ✓

(c) CVBench



Q. Closer to the lamp (red): the dresser (blue) or the night stand (green)? answer: night stand

base *"The dresser is located to the left of the bed. It is positioned near the head of the bed, adjacent to the lamp's location. … The lamp and dresser are separated only by the width of the bed, whereas the lamp and the green box object are separated by the length of the bed."* **(A) dresser** ×

ours *"The lamp (red box) is located on the right side of the bed. The night stand (green box) is located at the foot of the bed, directly adjacent to where the lamp is placed. The dresser (blue box) is located on the far left side of the room, separated from the bed and lamp by a significant distance."* **(B) night stand** ✓

Figure 6: **Thinking traces on CVBench.** Three questions comparing distances between objects marked by CVBench's colored boxes. Both the Qwen3.5-4B base model and ours use thinking mode. Each row shows the image, question, ground truth answer, and excerpts from both traces; ellipses mark omitted text. In these examples, the base model settles the comparison from how the boxes line up in the frame; `Where-OPD` appears to place each object in the room before making a prediction.



Figure 7: **Thinking traces and stated locations on GQA and V*.** For three questions, we show the original image, ground truth answer, and the Qwen3.5-4B base model's and `Where-OPD` traces, both with thinking enabled. The zoomed regions and overlaid boxes are added for visualization; the boxes plot coordinates stated in the traces and were not shown to the models. Our model's stated locations align with the objects in the questions. The Qwen3.5-4B places its white-truck box on the wrong vehicle in (c), puts ten evenly spaced boxes along one line, none of them on a candle, in (b), and states no bounding box at all in (a).

Table 8: **Evaluations under thinking enabled mode on Qwen3.5-4B.** All models are evaluated with thinking enabled. Results are accuracy (%); Avg. is the unweighted mean across 15 benchmarks. The smaller numbers below each score show the percentage-point change from the base model evaluated in the same mode. CVB: CVBench; MME-RW: MME-RealWorld; OCRB: OCR-Bench; HallB: HallusionBench; HR-4K/8K: HR-Bench 4K/8K; Zoom: ZoomBench.

	General											High-resolution				
Model	CVB	MME-RW	BLINK	GQA	CountQA	ChartQA	DocVQA	OCRB	EvoChart	HallB	AMBER	V*	HR-4K	HR-8K	Zoom	Avg.
Qwen3.5-4B base model	89.16	70.30	**71.23**	64.86	46.86	**86.28**	96.45	**86.90**	**77.36**	**69.82**	**88.61**	82.72	**88.12**	81.50	46.15	76.42
Vision-OPD	88.51 −0.65	70.43 +0.13	67.75 −3.48	62.26 −2.60	42.74 −4.12	86.04 −0.24	96.24 −0.21	85.80 −1.10	75.52 −1.84	67.09 −2.73	83.88 −4.73	**92.15** +9.43	83.50 −4.62	81.00 −0.50	**57.99** +11.84	76.06 −0.36
OPD-V	86.35 −2.81	69.81 −0.49	66.12 −5.11	58.45 −6.41	45.03 −1.83	84.04 −2.24	96.09 −0.36	84.70 −2.20	74.40 −2.96	64.25 −5.57	78.13 −10.48	89.53 +6.81	84.25 −3.87	79.75 −1.75	57.28 +11.13	74.55 −1.88
S2VOPD	88.82 −0.34	71.38 +1.08	70.65 −0.58	61.71 −3.15	53.93 +7.07	85.04 −1.24	96.28 −0.17	86.00 −0.90	75.20 −2.16	66.56 −3.26	83.91 −4.70	85.34 +2.62	86.75 −1.37	**83.50** +2.00	53.61 +7.46	76.58 +0.16
`Where-OPD`	**90.45** +1.29	**71.50** +1.20	**71.23** ±0.00	**65.81** +0.95	**54.12** +7.26	86.16 −0.12	**96.49** +0.04	86.60 −0.30	76.00 −1.36	69.40 −0.42	87.61 −1.00	83.25 +0.53	86.62 −1.50	81.75 +0.25	53.61 +7.46	**77.37** +0.95

Model	L3	L7	L11	L15	L19	L23	L27	L31	Chosen
Qwen3.5-4B	0.68	0.27	0.64	0.94	0.92	0.76	**1.15**	0.54	L27
Vision-OPD	1.12	0.71	3.01	**4.75**	3.20	2.31	2.57	1.47	L15
`Where-OPD`	1.32	1.17	3.36	**5.79**	4.30	2.69	2.29	1.42	L15

Table 9: **Attention-layer selection on synthetic counting scenes.** Mean enrichment of attention on the target objects at each full-attention layer, measured on a separate selection split of 158 held-out images with at least three targets. Enrichment of 1 means the targets receive attention proportional to their area. *Chosen* is the layer with the highest enrichment for each model. The base model is Qwen3.5-4B.

as evidence that they are close, while our model places the door on the far wall and the table in the foreground. The example b) and c) show a similar difference in how the models use the scene layout to compare objects. In Fig. 7, the stated locations make the contrast more explicit: in example a) `Where-OPD` identifies the goat beside the walking person, in example b) `Where-OPD` places the blue candles on the right, and in example c) locates the white truck relative to the red one. The base model instead calls the goat a dog, gives candle wrong locations, and identifies the wrong vehicle.

Visual evidence. The enlarged EvoChart examples in Fig. 8 show two questions that require combining information from different parts of a chart: ranking the lines at a given year (a), and finding the green line's minimum before reading the blue line (b). In both cases, `Where-OPD` answers correctly and its attention covers all regions of importance marked in the figure for visualization purposes, while the base model and Vision-OPD omit some of them. The enlarged HallusionBench example (Fig. 9) shows a similar pattern: our model attends to the USA label and the three land-area values needed to check its rank, and correctly answers the question.

B.4 Layer selection for attention map visualization

Let a be the attention from the response tokens to the $H \times W$ visual tokens of one image, averaged over heads and over the response tokens and renormalized over the visual tokens alone. For a token set $\mathcal{S}$, enrichment $\mathrm{enr}(\mathcal{S})$ compares the attention assigned to $\mathcal{S}$ with the fraction of visual tokens it contains:

$$\mathrm{enr}(\mathcal{S}) = \frac{\sum_{(i,j)\in\mathcal{S}} a_{ij}}{|\mathcal{S}|/HW}. \tag{8}$$

An enrichment of 1.0 means the targets receive exactly their area share, and higher values mean attention concentrated on the evidence.

We measure attention enrichment on target objects (objects referred to by the question) at each of the full-attention layers of Qwen3.5-4B using a separate selection split of 158 held-out synthetic scenes



Figure 8: **Enlarged EvoChart examples.** The EvoChart example from Fig. 4, enlarged as well as an additional EvoChart example. We show each visual input, question, ground-truth answer, and attention maps from the response tokens to the image for Qwen3.5-4B, Vision-OPD, and `Where-OPD`. Numbered dashed boxes mark the regions each question's answer depends on, drawn identically on every map. Under each map, a region is ticked when it receives at least twice its area share of the attention.



Figure 9: **Enlarged HallusionBench example.** The HallusionBench example from Fig. 4, enlarged. We show each visual input, question, ground-truth answer, and attention maps from the response tokens to the image for Qwen3.5-4B, Vision-OPD, and `Where-OPD`. Numbered dashed boxes mark the regions each question's answer depends on, drawn identically on every map. Under each map, a region is ticked when it receives at least twice its area share of the attention.



Figure 10: **Attention on target objects in synthetic counting scenes.** Two held-out examples with visual input, question, ground-truth answer, and attention maps from the response tokens to the image for Qwen3.5-4B, Vision-OPD, and `Where-OPD`. Numbered dashed boxes mark the regions each question's answer depends on, drawn identically on every map. Under each map, a region is ticked when it receives at least twice its area share of the attention. The displayed layers are selected as described in Tab. 9.

(Tab. 9). The base model's enrichment peaks at L27. Vision-OPD and our model both peak at L15, where our model has higher enrichment. We use these selected layers for attention visualizations.

Attention to target objects. We visualize two held-out counting examples (Fig. 10), our model attends to all marked target objects and gives the correct count, while the base model and Vision-OPD attend to fewer targets.