ROBOTEQ: TOWARDS SOCIAL PROACTIVE INTELLIGENCE IN EMBODIED AGENTS

Anonymous authors
Paper under double-blind review

ABSTRACT

Embodied agents represent a prominent research focus across both academia and industry. The prevailing paradigm has gradually shifted from *reactive assistance*, which requires explicit user queries, to *proactive assistance*, capable of recognizing human needs and offering support without explicit instructions. Nevertheless, existing studies on *proactive assistance* remain confined to narrow scenarios and primarily emphasize task completeness, whereas real-world agents must operate in open-domain environments while adhering to social expectations. To bridge this gap, we extend the concept of *proactive assistance* to **Social Proactive Intelligence (SPI)**, characterized by diverse scenarios, social understanding, and robot-centric behaviors. We further introduce **RobotEQ**[1], a dedicated benchmark for SPI. We first define two tasks: *behavior judgment*, emphasizing global contextual understanding, and *spatial grounding*, focusing on local perceptual details. Building on these tasks, we construct **RobotEQ-Data**, a dataset comprising 1,812 synthetic and 270 real-world scenarios, 7 social facets, 25K+ human annotations, 3K+ behavior judgment questions, and 3K+ spatial grounding questions. Furthermore, we establish **RobotEQ-Bench** to evaluate the performance of representative models. Experimental results demonstrate that current models fall short of achieving reliable SPI. Further analysis reveals that incorporating external social knowledge yields consistent improvements. This work aims to advance the development of socially desirable embodied agents in open-domain environments.

1 INTRODUCTION

"A social robot should feel much more like you are interacting with a someone rather than a something."

— Cynthia Breazeal

Embodied agents are intelligent entities capable of perceiving, planning, and acting within physical environments, playing critical roles in diverse domains such as service, industry, and agriculture (Liu et al., 2025). Most embodied agents are *reactive*, relying on explicit user commands to guide their behavior and treating task completion as their primary objective. These commands provide goal-directed instructions that agents interpret and translate into sequential behaviors to accomplish tasks. Beyond *reactive assistance*, recent research has shifted toward user-free *proactive assistance* (Min et al., 2026), enabling embodied agents to actively perceive environments, infer human needs, and offer support without explicit instructions. Despite this promising direction, current research remains confined to limited scenarios and primarily emphasizes task execution. The underlying reasons are twofold. **(Data level)** Collecting robot-centric visual data across diverse embodied scenarios and from diverse populations remains challenging. **(Task level)** Beyond task execution, embodied agents must also interpret human social expectations, such as privacy norms and politeness.

To this end, we extend *proactive assistance* to **Social Proactive Intelligence (SPI)**, enabling agents to understand social expectations across diverse scenarios. As illustrated in Figure 1, SPI requires a broad spectrum of scenarios beyond human-robot interaction and demands that agents consider comprehensive social facets rather than mere task success. To support this shift, we introduce **RobotEQ**, a benchmark designed to evaluate Vision-Language Models (VLMs) on SPI. We first

[1] https://anonymous.4open.science/r/RobotEQ/README.md

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: **Task comparison.** Reactive assistance relies on human instructions and operates passively. Proactive assistance is constrained to limited scenarios and remains centered on the agent's usefulness. This paper introduces *SPI*, aiming to adhere to social expectations within diverse embodied scenarios.

construct **RobotEQ-Data**, which contains 2K+ robot-centric scenarios. *From the data perspective*, recent advances in AIGC enable the generation of high-quality data, which partially addresses the previously unsolvable data sparsity of embodied agents. Section 5 presents extensive experiments verifying the quality of synthetic data. In addition to synthetic data, we collect real-world data for comparison. *From the task perspective*, we incorporate seven representative social facets during dataset construction: safety, privacy, proxemics, cooperation, politeness, priority, and sensitivity. Their definitions are provided in Appendix I. Meanwhile, we establish **RobotEQ-Bench** with two tasks: *behavior judgment*, emphasizing global contextual understanding, and *spatial grounding*, focusing on local perceptual details. With 25K+ human annotations, we provide 3K+ behavior judgment questions and 3K+ spatial grounding questions. This rigorous annotation process ensures that the final labels reflect social consensus. Experimental results reveal that current models exhibit notable limitations and lag behind human performance. We further conduct error analysis to identify typical failure modes and explore potential solutions. This work aims to advance the social adaptability and overall intelligence of embodied agents. The core contributions are threefold:

- **(Task)** This paper introduces *social proactive intelligence*, an extension of proactive assistance aimed at realizing socially desirable embodied agents in open-domain environments.
- **(Benchmark)** We introduce *RobotEQ*, a benchmark designed to evaluate whether current models can comprehend behavior boundaries for embodied agents.
- **(Experiment)** We conduct a comprehensive evaluation of representative models, accompanied by a detailed error analysis, and propose effective strategies with valuable insights.

2 Related Work

Reactive Assistance. Reactive assistance treats human instructions as an additional conditioning signal that modulates planning and action execution. As shown in Figure 1, such agents follow a perception–planning–action pipeline, where human commands constrain the planned trajectory. The recent integration of LLMs has injected broad semantic knowledge into embodied AI, enabling language-conditioned planning and multimodal reasoning (Ichter et al., 2023; Huang et al., 2023), and catalyzing progress in vision-and-language navigation (VLN) (Anderson et al., 2018; Wang et al., 2018) and vision-language-action (VLA) models (Driess et al., 2023; Zitkovich et al., 2023). Yet, although these models can understand open-ended instructions, they remain fundamentally reactive, offering limited user-friendly interaction. This limitation motivates a paradigm shift toward proactive assistance, where agents actively anticipate user intent instead of merely awaiting commands.

Proactive Assistance. Recent research on embodied agents has gradually shifted from *reactive* to *proactive* assistance. Proactive assistance aims to actively perceive the environment, infer human needs, and offer support without explicit user instructions. Representative efforts such as Pro^{2}Assist (Xu et al., 2026) and LLAMAPIE (Chen et al., 2025a) focus on wearable devices (e.g.,



Figure 2: **Characteristics of SPI.** SPI aims to adhere to social expectations within diverse embodied scenarios, characterized by seven aspects: *proactive execution*, *scenario diversity*, *social understanding*, *multimodal dependence*, *robot-centric inputs*, *robot-view behaviors*, and *embodied planning*.

glasses or hearables), generating proactive assistance by reasoning over a user's evolving state. However, their recommended actions are grounded in a human-viewpoint rather than an embodied-agent perspective. Centered on the robot behavior space, SHREC (Lee et al., 2026) provides a benchmark of human–robot interaction on the Jibo platform. PACT (He et al., 2026) studies cross-day proactive asking in long-horizon household collaboration. ASIMOV (Sermanet et al., 2025) and SocialNav-SUB (Munje et al., 2025) center on safety or navigation scenarios. These benchmarks confine proactive assistance to narrow, pre-defined scenarios or center on limited evaluation dimensions. In this work, we generalize the prior concept of *proactive assistance* into SPI, aiming to conduct research centered on diverse embodied scenarios and also considering diverse social facets.

Social Intelligence. Social intelligence is an important research area, aiming to perceive, understand, and reason about human social behavior, emotions, and cognition. For instance, CMU-MOSI (Zadeh et al., 2017) and CMU-MOSEI (Zadeh et al., 2018) focus on multimodal sentiment analysis and emotion recognition. Social-IQ (Zadeh et al., 2019) and Human Behavior Atlas (Ong et al., 2025) broaden the evaluation scope to social situations. Currently, most research on social intelligence remains largely confined to human-level behavior and interactions. *However, social intelligence in embodied agents is distinct from that of humans. For example, humans and embodied agents have different viewpoints and different action spaces.* This paper focuses on the social intelligence of embodied agents and introduces RobotEQ, associated with a dataset and a benchmark for this field.

3 Task Definition: Social Proactive Intelligence

SPI aims to ensure that embodied agents adhere to social expectations and act appropriately within diverse scenarios. We characterize SPI by seven core properties, as illustrated in Figure 2. *1) Proactive Execution.* SPI requires actively perceiving environmental states and human needs and executing actions, rather than passively relying on human instructions. *2) Scenario diversity.* SPI must support various open-domain, unstructured scenarios. *3) Social understanding.* Beyond task completion, embodied agents must reason in accordance with social standards, such as respecting privacy (e.g., avoiding uncomfortable or prying questions) and ensuring safety (e.g., preventing physical or psychological harm to humans). *4) Multimodal dependence.* Behavior properness depends on specific scenarios. *5) Robot-centric inputs.* Visual inputs should reflect the robot's first-person perspective, rather than a third-person viewpoint that observes the robot from a human angle. *6) Robot-view behaviors.* The action space should be defined from the robot's perspective, rather than a human-centric viewpoint. *7) Embodied Planning.* SPI centers on high-level semantic planning, decoupled from specific hardware constraints. For example, we provide semantic-level instructions rather than hardware-dependent atomic actions tailored to a specific robot platform.

4 Dataset Construction

Scenario Design. To ensure broad scenario coverage, we construct a scenario taxonomy based on recent surveys (Singamaneni et al., 2024), which categorize real-world environments into 10 major *categories*. Through brainstorming, we further refine these into 56 fine-grained *subcategories* with vast application prospects for embodied agents. The complete taxonomy is provided in Appendix B.1. For each subcategory, we design prompts to guide LLMs in generating diverse *scenarios*, each consisting of three components: a title, a detailed description, and a brief rationale explaining the need for SPI. We perform multiple generation rounds to enhance diversity and employ an expert model



Figure 3: **Data collection pipeline.** *1) Scenario design:* We define categories and subcategories, then generate diverse scenarios. *2) Image collection:* We collect real and synthetic images for each scenario, followed by rigorous manual filtering. *3) Behavior judgment:* This task evaluates the behavioral appropriateness. *4) Spatial grounding:* This task assesses the spatial appropriateness.

to remove duplicates, yielding the final *scenario pool* (further details in Appendix B.2). Consequently, our dataset is organized into three levels: *category*, *subcategory*, and specific *scenario*.

Image Collection. **1) Real Images.** Due to the difficulty of data acquisition, we collect data from two sources: *robot-captured* and *web-searched* images. For robot-captured images, we select frames from JRDB-Social (Jahangard et al., 2024), a popular dataset in robotics. For web-searched images, we gather a large candidate pool from multiple image retrieval platforms, designing search queries for each subcategory to ensure diversity. We then apply a multi-stage filtering pipeline. First, images with inappropriate resolution or insufficient clarity are discarded. Then, we employ VLMs to remove images that do not resemble a robot-centric perspective or that are unsuitable for evaluating SPI. Next, we further perform scenario-level deduplication, eliminating candidates with overlapping scenarios, and select the most representative images. Finally, human experts review and confirm the curated set (details in Appendix C.1). From a large candidate pool, only about 270 images meet all criteria. This highlights the scarcity of real-world images capable of adequately evaluating SPI in embodied agents. **2) Synthetic Images.** Considering the sparsity of real images, we further explore text-to-image generation toolkits, which offer a viable alternative for synthesizing visually realistic images with sufficient fidelity (Google DeepMind, 2025). Specifically, given a scenario description, we first employ LLMs to transform it into a detailed prompt that specifies the spatial layout, key objects, human poses, and environmental context from a robot-centric perspective. These prompts are then input into image generation models. Since generated images may exhibit visual artifacts or inconsistencies, we introduce an expert model to evaluate each image against a set of quality criteria, including scenario faithfulness, physical plausibility, and visual clarity (see Appendix C.2 for the full list). Based on this assessment, the expert model generates revision suggestions, which are used to iteratively refine the images. Human annotators conduct a further quality check, filtering out low-quality outputs to ensure the generated images are indistinguishable from real-world photographs.

Categories	**10**
Subcategories	**56**
Scenario	**2,082**
Synthetic	1,812
Real	270
Behavior judgment	**3,278**
Proper	2,066 (63.0%)
Improper	1,212 (37.0%)
Spatial grounding	**3,300**
A / B	86.5/13.5% | 48.6/51.4%
C / D	25.8/74.2% | 17.3/82.7%

(a) Dataset statistics.



(b) Scenario categories.



(c) Evaluation facets.



(d) Annotator agreement.

Figure 4: **Overview of RobotEQ-Data.** (a) Dataset statistics. (b) Distribution of scenario categories. (c) Distribution of evaluation facets. (d) Inter-annotator agreement.

Behavior Judgment. We first construct a candidate behavior pool for each scenario, where each behavior represents a plausible next-step action for embodied agents. Details are provided in Appendix D. We then hire multiple annotators to verify the properness of each candidate. Each annotator assigns one of three labels: *proper*, *improper*, or *invalid*. Every candidate behavior is labeled by at least three annotators. Candidates with low inter-annotator agreement are escalated to domain experts, who decide whether to discard them. Behaviors labeled *invalid*, typically because they are implausible or poorly matched to the image, are excluded from the benchmark. We additionally remove behaviors that can be inferred without visual input, ensuring that the benchmark genuinely requires scenario-grounded reasoning. Full annotation guidelines are in Appendix E. For evaluation, we employ both subjective-aware and subjective-unaware metrics, as detailed in Section 5.

Spatial Grounding. Besides behavior judgment, we construct a second type of question: spatial grounding. Each instance comprises a question, an image overlaid with candidate regions or movement trajectories, and answers selected from those candidates. To construct this dataset, we recruit five annotators and randomly assign each image to two annotators, who propose potential spatial grounding questions. Based on these proposals, we design prompts that instruct LLMs to generate both the questions for spatial grounding and the corresponding image *editing instructions* for region annotation. Each instruction specifies four labeled regions to be overlaid on the original image, with at least one region corresponding to a correct answer. The generated *editing instructions* are then passed to image editing models to produce images with overlaid candidates. Further details of prompt design and the editing procedure are provided in Appendix F. To guarantee the fidelity of edited images, we implement a secondary review phase, where multiple annotators perform collaborative inspections, offering targeted suggestions to refine the images. For the formal annotation phase, we recruit multiple annotators and randomly assign each edited image to three annotators. Annotators choose from five options, {*A*, *B*, *C*, *D*, *invalid*}. Images labeled as *invalid* are excluded from the benchmark. The options selected by majority vote form the final answers. Spatial grounding is designed as a multiple-choice task, and multiple regions may be valid answers.

Dataset Statistics. **1) Distribution.** Our dataset is hierarchically organized into three levels: *category*, *subcategory*, and *scenario*, with each *scenario* paired with behavior judgment and spatial grounding questions. Table 4a presents the statistics of RobotEQ, revealing an imbalanced distribution of ground-truth labels. Figure 4b shows the distribution across ten scenario categories. The *Retail and Hospitality & Consumer Services* category is the largest, reflecting the high frequency of social interaction in public-service robotics. Beyond scenario type, our dataset is structured along seven evaluation facets, and each behavior may map to one or more facets. Figure 4c presents the facet-level statistics. *Sensitivity* and *cooperation* account for the largest shares, indicating that our benchmark prioritizes interpersonal dynamics and emotional intelligence in embodied scenarios. **2) Annotator Selection.** To ensure annotation quality, we screened annotators prior to labeling, verifying that all held strong academic records, demonstrated good professional conduct, and were familiar with recent advances in embodied agents. In practice, annotators first completed a training session covering scenario categories, label definitions, and representative edge cases. Then, they independently labeled the test items and answered 20 behavior judgment questions. Based on per-annotator accuracy, we selected the highest-performing annotators to form the formal labeling team. Figure 4d reports

inter-annotator agreement. These high scores demonstrate the reliability of our labels. Overall, our benchmark provides a valuable resource for studying SPI.

5 EXPERIMENTAL SETUP

Evaluation Protocol. We frame each behavior-judgment item and each candidate option in a spatial-grounding question as an independent binary classification task, and evaluate both with two families of metrics. *(1) Subjective-unaware metrics.* We collapse human annotations via majority vote to obtain reference labels and compute Macro-F1 and Micro-F1. Since proper and improper behaviors are inherently imbalanced in our dataset according to Table 4a, we treat Macro-F1 as the primary metric and Micro-F1 as a secondary diagnostic. *(2) Subjective-aware metrics.* Since SPI judgments involve human subjectivity, we further introduce the Probability of Agreement (PA) and its consensus-weighted variant (CWPA). Let N_U denote the total number of binary evaluation units, defined as the sum of behavior judgment items or individual candidate options in spatial grounding. Let N_H be the number of annotators per unit. Let A_u denote the model's answer for each unit u, and $A^h_{u,i}$ the answer of annotator i. We define PA as follows:

$$\mathrm{PA} = \frac{1}{N_U} \sum_{u=1}^{N_U} \left(\frac{1}{N_H} \sum_{i=1}^{N_H} \mathbb{I}\left[A_u = A^h_{u,i} \right] \right), \tag{1}$$

which measures the expected agreement between the model and a randomly sampled human rater. To reflect that some units admit stronger human consensus than others, we weight each question by its human agreement rate. Let $\mathrm{HA}_u \in (0, 1]$ be the fraction of annotators selecting the modal answer for unit u. Then, CWPA is defined as follows:

$$\mathrm{CWPA} = \frac{1}{N_U} \sum_{u=1}^{N_U} \left(\frac{1}{N_H \cdot \mathrm{HA}_u} \sum_{i=1}^{N_H} \mathbb{I}\left[A_u = A^h_{u,i} \right] \right). \tag{2}$$

Intuitively, CWPA divides per-question agreement by HA_u. On questions where humans overwhelmingly agree, a model mismatch is penalized more heavily. On ambiguous questions with divided human opinion, the same mismatch is discounted. This prevents ambiguous items from diluting error signals that should be attributed to genuine model misunderstanding rather than rater disagreement.

Benchmarking Candidates. Recent work has increasingly integrated VLMs into embodied decision-making pipelines, motivating our selection of representative VLMs as baselines for benchmarking their SPI capabilities. We evaluate three model categories. **(1) Closed-source VLMs**, which offer strong multimodal reasoning and serve as an upper-bound reference. **(2) Open-source general-purpose VLMs**, run locally under constrained compute, letting us assess how far embodied social reasoning can go with readily available resources. **(3) Open-source task-specialized VLMs**, fine-tuned for fine-grained visual perception (e.g., visual grounding and OCR), to test whether task-specific visual skills can transfer to SPI. Further implementation details are in Appendix H.

6 ROBOTEQ-BENCH

Behavior Judgment. Table 1 reports the performance of three types of models on behavior judgment. We evaluate using two categories of metrics. *Subjective-unaware metrics* treat majority-vote annotations as ground truth, ignoring individual human judgments; *subjective-aware metrics* instead incorporate per-annotator annotations and their associated subjectivity. In general, closed-source VLMs outperform open-source models. Given that closed-source VLMs typically exhibit stronger visual perception and reasoning capabilities, these results suggest that behavior judgment benefits from such capabilities. Among closed-source models, GPT-5.5 achieves the highest overall performance, followed by Claude Opus 4.6 and Sonnet 4.6. Interestingly, newer versions do not always bring improvements on SPI. For example, Claude Opus 4.7 slightly underperforms Claude Opus 4.6, and Gemini-3.1-Pro-Preview scores below Gemini-2.5-Pro. These findings suggest that SPI requires targeted evaluation and alignment. Meanwhile, task-specialized VLMs, e.g., those optimized for grounding or OCR, do not yield consistent gains, indicating that emphasis on local details alone is insufficient to improve SPI. Finally, all models still lag behind human judgment, pointing to the need for further work on how to more effectively address SPI.

Table 1: **Main results on behavior judgment.** We evaluate model performance on synthetic and real subsets. For each metric, the best score is in **bold** and the runner-up is underlined.

Model	Size	Synthetic Subset (%)				Real Subset (%)				Avg (%)	
		PA	CWPA	MicF1	MacF1	PA	CWPA	MicF1	MacF1	CWPA	MacF1
OPEN-SOURCE TASK-SPECIALIZED VLMS											
GUI-Actor (Wu et al., 2026)	7B	62.83	63.81	66.84	49.29	58.42	58.81	57.49	40.51	61.31	44.90
Nanonets-OCR-s	3B	46.70	46.64	48.12	47.63	51.25	51.42	54.68	51.08	49.03	49.36
GroundNext (Feizi et al., 2025)	7B	53.63	53.93	54.62	54.62	51.74	52.37	53.22	51.27	53.15	52.94
Nanonets-OCR2	3B	50.45	50.50	51.90	51.90	57.04	58.25	58.14	57.19	54.37	54.54
GUI-G2 (Tang et al., 2025)	7B	62.25	63.03	63.48	61.94	59.19	60.33	61.21	61.11	61.68	61.52
InfiGUI-G1 (Liu et al., 2026)	7B	61.72	62.60	66.29	64.43	60.04	61.34	60.78	60.61	61.97	62.52
UGround-V1 (Gou et al., 2025)	7B	57.76	58.51	65.17	61.39	69.11	70.46	77.13	76.87	64.48	69.13
OPEN-SOURCE GENERAL-PURPOSE VLMS											
Janus-Pro (Chen et al., 2025b)	7B	53.96	54.73	45.74	45.56	56.82	57.21	62.90	61.87	55.97	53.72
Aya-Vision (Dash et al., 2025)	8B	56.25	56.88	58.23	57.72	53.97	55.20	51.20	51.13	56.04	54.43
Qwen2.5-VL (Bai et al., 2025b)	7B	58.63	59.32	62.51	61.87	56.26	57.38	56.67	55.87	58.35	58.87
Phi-4-Multimodal (Abouelenin et al., 2025)	3.8B	62.46	63.67	55.35	54.62	61.20	62.54	64.84	64.71	63.11	59.66
InternVL3 (Zhu et al., 2025)	8B	60.31	60.96	64.77	62.53	56.47	57.13	57.44	56.96	59.04	59.75
Gemma-3 (Team, 2025)	4B	59.24	60.12	59.03	58.12	60.78	61.85	63.25	63.14	60.99	60.63
Pixtral (Agrawal et al., 2024)	12B	60.81	61.73	62.97	62.53	62.75	63.61	62.32	62.22	62.67	62.38
DeepSeek-VL2-Small (Wu et al., 2024)	12B	64.08	65.18	64.94	61.87	64.11	65.22	64.15	63.71	65.20	62.79
Gemma-3 (Team, 2025)	12B	63.63	64.70	66.34	65.85	61.81	62.73	63.44	62.82	63.71	64.34
LLaVA-OneVision (Li et al., 2025)	7B	65.71	67.03	69.12	58.98	68.56	70.38	76.51	73.43	68.70	66.21
Llama-3.2-Vision (Grattafiori et al., 2024)	11B	62.17	63.11	65.22	60.25	68.02	69.69	75.33	75.11	66.40	67.68
Idefics3-Llama3 (Laurençon et al., 2024)	8B	65.74	67.01	68.98	63.88	71.09	73.23	76.34	75.37	70.12	69.62
Qwen3-VL (Bai et al., 2025a)	8B	66.66	67.92	72.24	71.20	65.60	66.69	69.24	69.11	67.31	70.16
GLM-4.1V-Thinking (Hong et al., 2025)	9B	67.46	69.09	68.97	65.81	68.14	70.20	75.51	75.05	69.64	70.43
CLOSED-SOURCE VLMS											
Qwen-VL-Plus (Bai et al., 2023)	–	48.48	48.31	50.10	49.20	54.68	55.78	51.48	50.06	52.04	49.63
Doubao-Seed-1.6-Flash	–	60.20	60.89	62.93	60.32	67.30	68.93	69.30	69.29	64.91	64.81
Gemini-3.1-Pro-Preview	–	63.39	64.15	67.63	67.52	64.83	66.29	66.97	65.89	65.22	66.71
Gemini-2.5-Pro (Comanici et al., 2025)	–	67.00	68.06	70.08	69.43	68.45	69.64	71.57	71.23	68.85	70.33
GPT-5.4 (OpenAI, 2026a)	–	67.53	68.50	70.64	68.88	71.28	72.26	73.48	73.46	70.38	71.17
Claude Opus 4.7 (Anthropic, 2026b)	–	68.87	70.02	72.11	71.56	69.34	70.38	71.57	71.26	70.20	71.41
GPT-4o-mini (OpenAI, 2024)	–	65.82	67.20	67.35	62.73	**73.99**	**76.38**	**82.23**	**82.12**	71.79	72.43
Claude Sonnet 4.6 (Anthropic, 2026c)	–	69.07	70.29	72.81	71.62	72.16	73.78	74.49	74.40	72.04	73.01
Claude Opus 4.6 (Anthropic, 2026a)	–	69.59	70.82	72.97	72.00	71.72	73.23	74.27	74.12	72.02	73.06
GPT-5.5 (OpenAI, 2026b)	–	**70.65**	**71.72**	**73.65**	**72.42**	72.12	73.28	75.13	75.03	**72.50**	**73.73**
Human	–	81.04	84.38	93.21	92.42	83.84	86.52	88.71	88.61	85.45	90.52

Spatial Grounding. Figure 5 evaluates representative models on spatial grounding. Detailed results are provided in Appendix J. As illustrated in Figure 3, spatial grounding differs from behavior judgment in that it requires joint reasoning over visual details, spatial layout, and social norms, making it a harder task in SPI. Across models, closed-source systems no longer exhibit the clear advantage they showed on behavior judgment. These results indicate that spatial grounding remains challenging for current VLMs regardless of scale. Moreover, all models still fall short of human performance, underscoring the difficulty of the task. Closings this gap will require models that can integrate perception, spatial reasoning, and social commonsense in a single inference step.



Figure 5: **Main results on spatial grounding.** Human performance is annotated in each subplot.

Annotation Quality Analysis. Figure 4d demonstrates that annotators reach high inter-annotator agreement, confirming that our labels reflect annotator consensus. In this section, we further discuss the annotation quality. Table 1 and Figure 5 report human performance on behavior judgment and spatial grounding, respectively. From these results, we can observe that humans achieve consistently strong results on both tasks. These results validate the reliability of our annotation results. Our recruited annotators hold advanced degrees and have solid backgrounds in AI, enabling them to provide high-quality annotations that capture human expectations of embodied agents.

Data Quality Analysis. In Figure 3, we conducted a rigorous manual verification process to ensure the quality of our synthetic data. In this section, we conduct supplementary experiments to validate data quality. Specifically, we perform a synthetic-to-real evaluation, where models are trained on the synthetic data and evaluated on the real subset. In Figure 6, we can observe good performance transfer from synthetic to real domains, confirming that our synthetic data are sufficiently realistic to generalize to real-world scenarios.



Figure 6: **Cross-corpus results.** We use synthetic data for training and real data for testing.

Importance of Visual Clues. This section examines the importance of visual information from two perspectives: human annotation and model prediction. Figure 7a shows the role of visual information in human annotation. Specifically, we randomly sample 200 behavior judgment questions and hire five annotators to label each one under two conditions: with and without the accompanying image. Results demonstrate that human judgments drop substantially when visual evidence is removed, confirming that visual clues are integral to human annotation. Figure 7b shows the role of visual information in model prediction. We observe that the performance degrades in the *w/o image* setting, further validating the necessity of visual information.



(a) Human. (b) Model.

Figure 7: **Role of visual clues.** We examine the importance of visual clues from two perspectives.

Robustness to Visual Perturbation. This section simulates possible visual perturbations in embodied scenarios and evaluates whether VLMs can overcome these perturbations and remain robust in SPI. As illustrated in Figure 8, we implement three distinct categories of visual perturbations: *blur*, *fisheye*, and *fisheye&water*. Experimental results demonstrate that nearly all VLMs exhibit performance degradation on perturbation data, with particularly severe drops under fisheye distortion. We attribute this degradation to the obstructed field of view caused by fisheye distortion, which may hinder VLMs from extracting discriminative visual cues for behavior judgment.



Figure 8: **Robustness to visual perturbations.** We introduce three visual perturbations, evaluate the performance of six representative VLMs under both clean and corrupted inputs.

Performance Comparison across Social Facets. As described in Section 4, for behavior judgment, we assign one or more social facets to each item. In this section, we group all items based on their social facets and compare the performance of models and humans under each facet. As shown in Figure 9, GPT-5.5 is the closest to human performance across the seven facets, with particularly strong results on *politeness* and *privacy*. These results suggest that frontier models can capture a substantial portion of explicit and commonly observed social norms. However, facets such as *sensitivity* remain challenging for most models. This facet requires models to understand implicit constraints that are left unstated in ordinary interaction. For example, when interacting with social partners, embodied agents should fully account for the emotional states and subjective experiences of humans. These results indicate that current models still struggle with implicit social knowledge.



Figure 9: **Performance comparison across social facets.** We compare representative models with human performance across seven social facets.

Error Analysis. To better understand the model's limitations, we ground our analysis in GPT-5.5 and examine and categorize its representative errors. As shown in Figure 10, we identify four failure patterns. *1) Overly aggressive behavior.* The model can be excessively forceful, focusing on completing the assigned task while neglecting the human's state. For example, it may scold a child loudly to keep him from reaching a dangerous object, when the child's age and vulnerability call for a gentler, more empathetic response. *2) Overly cautious behavior.* The model can also be excessively cautious, misjudging the acceptable degree of intervention. For instance, when a homeowner is changing clothes with the bedroom door left open, it hesitates to close the door, a simple action that would protect privacy. *3) Insufficient social commonsense.* The model lacks the social experience needed for emotionally sensitive interactions, particularly in conversation, counseling, and other support-oriented tasks. *4) Spatial grounding error.* The model may select a path or region without considering the social appropriateness of that spatial choice. Together, these errors indicate that SPI requires more than object recognition or instruction following. Models must balance task goals, human states, social norms, and spatial norms within a unified decision-making process. To mitigate these errors, we implement Retrieval-Augmented Generation (RAG) that equips embodied agents with explicit social normative guidelines. Detailed experimental results are provided in Appendix K.



Figure 10: **Error analysis.** We identify four representative failure modes: *overly aggressive behavior*, *overly cautious behavior*, *lack of basic social knowledge*, and *spatial grounding error*.

7 Conclusion

This paper extends prior reactive and proactive assistance to **Social Proactive Intelligence (SPI)**, requiring embodied agents not only to complete tasks but also to adhere to social expectations across diverse scenarios. For this purpose, we introduce **RobotEQ**, comprising a curated dataset and a systematic evaluation benchmark. **RobotEQ-Data** covers two task types, *behavior judgment* and *spatial grounding*, with 25K+ human annotations. **RobotEQ-Bench** provides a comprehensive evaluation of representative VLMs. Through extensive analysis, we demonstrate the limitations of current models in SPI, which still lag behind human performance. Meanwhile, we validate the annotation and data quality and demonstrate the importance of visual cues. Additionally, we analyze model robustness under diverse visual perturbations, conduct error analysis, and identify representative failure patterns. This work advances the development of socially aware embodied agents. More discussion of potential applications of our work is provided in Appendix A.

Limitation. In real-world human–robot interaction, temporal dynamics in video and accompanying audio signals offer rich cues for proactive assistance. However, this work focuses exclusively on images, leaving other modalities underexplored. In future work, we will extend RobotEQ to incorporate multimodal inputs. Additionally, due to funding constraints, the current annotation pool lacks cultural diversity. Since behavior properness may vary across cultures, contexts, and communication styles, the reported results may reflect the decision boundaries of our annotators rather than generalizable social principles. To address this, we plan to broaden annotator diversity.

Ethics Statement

RobotEQ uses synthetically generated images and does not include real individuals, avoiding privacy risks associated with human-subject data collection. All annotations were completed voluntarily by informed team members under fair working conditions. The benchmark focuses on prosocial robot service scenarios and excludes violent, discriminatory, or harmful content. Finally, benchmark performance should not be viewed as evidence of real-world deployment readiness; socially intelligent robots require further validation before use in human environments.

Reproducibility Statement

We provide an anonymous repository at https://huggingface.co/datasets/Tongji-Emotion/Robot-EQ with evaluation code, data construction scripts, and a representative subset of RobotEQ. The full dataset will be released upon acceptance. The construction pipeline is described in Section 3 and Figure 2, and detailed model settings, inference configurations, and hardware information are provided in Appendix G and Appendix H. The appendix also includes prompt templates, representative cases, and annotation guidelines to support replication.

References

Abdelrahman Abouelenin, Atabak Ashfaq, Adam Atkinson, Hany Awadalla, Nguyen Bach, Jianmin Bao, Alon Benhaim, Martin Cai, Vishrav Chaudhary, Congcong Chen, et al. Phi-4-mini technical report: Compact yet powerful multimodal language models via mixture-of-loras. *arXiv preprint arXiv:2503.01743*, 2025.

Pravesh Agrawal, Szymon Antoniak, Emma Bou Hanna, Baptiste Bout, Devendra Chaplot, Jessica Chudnovsky, Diogo Costa, Baudouin De Monicault, Saurabh Garg, Theophile Gervet, Soham Ghosh, Amélie Héliou, Paul Jacob, Albert Q. Jiang, Kartik Khandelwal, Timothée Lacroix, Guillaume Lample, Diego Las Casas, Thibaut Lavril, Teven Le Scao, Andy Lo, William Marshall, Louis Martin, Arthur Mensch, Pavankumar Muddireddy, Valera Nemychnikova, Marie Pellat, Patrick Von Platen, Nikhil Raghuraman, Baptiste Rozière, Alexandre Sablayrolles, Lucile Saulnier, Romain Sauvestre, Wendy Shang, Roman Soletskyi, Lawrence Stewart, Pierre Stock, Joachim Studnia, Sandeep Subramanian, Sagar Vaze, Thomas Wang, and Sophia Yang. Pixtral 12b, 2024. URL https://arxiv.org/abs/2410.07073.

Peter Anderson, Qi Wu, Damien Teney, Jake Bruce, Mark Johnson, Niko Sünderhauf, Ian D. Reid, Stephen Gould, and Anton van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *2018 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2018, Salt Lake City, UT, USA, June 18-22, 2018*, pp. 3674–3683. Computer Vision Foundation / IEEE Computer Society, 2018. doi: 10.1109/CVPR.2018.00387. URL http://openaccess.thecvf.com/content_cvpr_2018/html/Anderson_Vision-and-Language_Navigation_Interpreting_CVPR_2018_paper.html.

Anthropic. System Card: Claude Opus 4.6. https://www-cdn.anthropic.com/0dd865075ad3132672ee0ab40b05a53f14cf5288.pdf, February 2026a. Released February 5, 2026. 212 pages. Also available at https://www.anthropic.com/system-cards.

Anthropic. System Card: Claude Opus 4.7. https://www.anthropic.com/system-cards, April 2026b. Released April 16, 2026. 232 pages. Download PDF from the System Cards page.

Anthropic. System Card: Claude Sonnet 4.6. https://www-cdn.anthropic.com/78073f739564e986ff3e28522761a7a0b4484f84.pdf, February 2026c. Released February 2026. Also available at https://www.anthropic.com/system-cards.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond, 2023. URL https://arxiv.org/abs/2308.12966.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*, 2025a.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-vl technical report, 2025b. URL https://arxiv.org/abs/2502.13923.

ByteDance Seed Team. Seed 1.6 Technical Report. https://seed.bytedance.com/en/seed1_6, 2025. Chinese version: https://research.doubao.com/zh/seed1_6.

Tuochao Chen, Nicholas Scott Batchelder, Alisa Liu, Noah A. Smith, and Shyamnath Gollakota. LlamaPIE: Proactive in-ear conversation assistants. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 13801–13824, Vienna, Austria, July 2025a. Association for Computational Linguistics. ISBN 979-8-89176-256-5. doi: 10.18653/v1/2025.findings-acl.710. URL https://aclanthology.org/2025.findings-acl.710/.

Xiaokang Chen, Zhiyu Wu, Xingchao Liu, Zizheng Pan, Wen Liu, Zhenda Xie, Xingkai Yu, and Chong Ruan. Janus-pro: Unified multimodal understanding and generation with data and model scaling, 2025b. URL https://arxiv.org/abs/2501.17811.

Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, et al. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*, 2025. URL https://arxiv.org/abs/2507.06261.

Saurabh Dash, Yiyang Nan, John Dang, Arash Ahmadian, Shivalika Singh, Madeline Smith, Bharat Venkitesh, Vlad Shmyhlo, Viraat Aryabumi, Walter Beller-Morales, Jeremy Pekmez, Jason Ozuzu, Pierre Richemond, Acyr Locatelli, Nick Frosst, Phil Blunsom, Aidan Gomez, Ivan Zhang, Marzieh Fadaee, Manoj Govindassamy, Sudip Roy, Matthias Gallé, Beyza Ermis, Ahmet Üstün, and Sara Hooker. Aya vision: Advancing the frontier of multilingual multimodality, 2025. URL https://arxiv.org/abs/2505.08751.

Danny Driess, Fei Xia, Mehdi S. M. Sajjadi, Corey Lynch, Aakanksha Chowdhery, Brian Ichter, Ayzaan Wahid, Jonathan Tompson, Quan Vuong, Tianhe Yu, Wenlong Huang, Yevgen Chebotar, Pierre Sermanet, Daniel Duckworth, Sergey Levine, Vincent Vanhoucke, Karol Hausman, Marc Toussaint, Klaus Greff, Andy Zeng, Igor Mordatch, and Pete Florence. Palm-e: an embodied multimodal language model. In *Proceedings of the 40th International Conference on Machine Learning*, ICML'23. JMLR.org, 2023.

Aarash Feizi, Shravan Nayak, Xiangru Jian, Kevin Qinghong Lin, Kaixin Li, Rabiul Awal, Xing Han Lù, Johan Obando-Ceron, Juan A. Rodriguez, Nicolas Chapados, David Vazquez, Adriana Romero-Soriano, Reihaneh Rabbany, Perouz Taslakian, Christopher Pal, Spandana Gella, and Sai Rajeswar. Grounding computer use agents on human demonstrations, 2025. URL https://arxiv.org/abs/2511.07332.

Yu Gao, Lixue Gong, Qiushan Guo, Xiaoxia Hou, Zhichao Lai, Fanshi Li, Liang Li, Xiaochen Lian, Chao Liao, Liyang Liu, Wei Liu, Yichun Shi, Shiqi Sun, Yu Tian, Zhi Tian, Peng Wang, Rui Wang, Xuanda Wang, Xun Wang, Ye Wang, Guofeng Wu, Jie Wu, Xin Xia, Xuefeng Xiao, Zhonghua Zhai, Xinyu Zhang, Qi Zhang, Yuwei Zhang, Shijia Zhao, Jianchao Yang, and Weilin Huang. Seedream 3.0 technical report, 2025. URL https://arxiv.org/abs/2504.11346.

Google DeepMind. Gemini 3 Pro Image Model Card. https://storage.googleapis.com/deepmind-media/Model-Cards/Gemini-3-Pro-Image-Model-Card.pdf, November 2025. Released November 20, 2025.

Google DeepMind. Gemini 3.1 Pro Model Card. https://deepmind.google/models/model-cards/gemini-3-1-pro/, February 2026. PDF version: https://storage.googleapis.com/deepmind-media/Model-Cards/Gemini-3-1-Pro-Model-Card.pdf.

Boyu Gou, Ruohan Wang, Boyuan Zheng, Yanan Xie, Cheng Chang, Yiheng Shu, Huan Sun, and Yu Su. Navigating the digital world as humans do: Universal visual grounding for GUI agents. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=kxnoqaisCT.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Chengbo He, Sheng Li, Chenyang Ma, Bochao Zou, Li Sun, Jiansheng Chen, Junliang Xing, Yuanchun Shi, and Huimin Ma. Pact: Proactive asking for continual task assistance in human-robot collaboration, 2026. URL https://arxiv.org/abs/2605.24350.

Wenyi Hong, Wenmeng Yu, Xiaotao Gu, Guo Wang, Guobing Gan, Haomiao Tang, Jiale Cheng, Ji Qi, Junhui Ji, Lihang Pan, et al. Glm-4.5 v and glm-4.1 v-thinking: Towards versatile multimodal reasoning with scalable reinforcement learning. *arXiv preprint arXiv:2507.01006*, 2025.

Wenlong Huang, Fei Xia, Ted Xiao, Harris Chan, Jacky Liang, Pete Florence, Andy Zeng, Jonathan Tompson, Igor Mordatch, Yevgen Chebotar, Pierre Sermanet, Tomas Jackson, Noah Brown, Linda Luu, Sergey Levine, Karol Hausman, and brian ichter. Inner monologue: Embodied reasoning through planning with language models. In Karen Liu, Dana Kulic, and Jeff Ichnowski (eds.), *Proceedings of The 6th Conference on Robot Learning*, volume 205 of *Proceedings of Machine Learning Research*, pp. 1769–1782. PMLR, 14–18 Dec 2023. URL https://proceedings.mlr.press/v205/huang23c.html.

Brian Ichter, Anthony Brohan, Yevgen Chebotar, Chelsea Finn, Karol Hausman, Alexander Herzog, Daniel Ho, Julian Ibarz, Alex Irpan, Eric Jang, Ryan Julian, Dmitry Kalashnikov, Sergey Levine, Yao Lu, Carolina Parada, Kanishka Rao, Pierre Sermanet, Alexander T Toshev, Vincent Vanhoucke, Fei Xia, Ted Xiao, Peng Xu, Mengyuan Yan, Noah Brown, Michael Ahn, Omar Cortes, Nicolas Sievers, Clayton Tan, Sichun Xu, Diego Reyes, Jarek Rettinghouse, Jornell Quiambao, Peter Pastor, Linda Luu, Kuang-Huei Lee, Yuheng Kuang, Sally Jesmonth, Nikhil J. Joshi, Kyle Jeffrey, Rosario Jauregui Ruano, Jasmine Hsu, Keerthana Gopalakrishnan, Byron David, Andy Zeng, and Chuyuan Kelly Fu. Do as i can, not as i say: Grounding language in robotic affordances. In Karen Liu, Dana Kulic, and Jeff Ichnowski (eds.), *Proceedings of The 6th Conference on Robot Learning*, volume 205 of *Proceedings of Machine Learning Research*, pp. 287–318. PMLR, 14–18 Dec 2023. URL https://proceedings.mlr.press/v205/ichter23a.html.

Simindokht Jahangard, Zhixi Cai, Shiki Wen, and Hamid Rezatofighi. Jrdb-social: A multifaceted robotic dataset for understanding of context and dynamics of human interactions within social groups. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

Hugo Laurençon, Andrés Marafioti, Victor Sanh, and Léo Tronchon. Building and better understanding vision-language models: insights and future directions, 2024. URL https://arxiv.org/abs/2408.12637.

Dong Won Lee, Yubin Kim, Denison Guvenoz, Sooyeon Jeong, Parker Malachowsky, Louis-Philippe Morency, Cynthia Breazeal, and Hae Won Park. Social human robot embodied conversation (shrec) dataset: Benchmarking foundational models' social reasoning, 2026. URL https://arxiv.org/abs/2504.13898.

Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Peiyuan Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. LLaVA-onevision: Easy visual task transfer. *Transactions on Machine Learning Research*, 2025. ISSN 2835-8856. URL https://openreview.net/forum?id=zKv8qULV6n.

Yang Liu, Weixing Chen, Yongjie Bai, Xiaodan Liang, Guanbin Li, Wen Gao, and Liang Lin. Aligning cyber space with physical world: A comprehensive survey on embodied ai, 2025. URL https://arxiv.org/abs/2407.06886.

Yuhang Liu, Zeyu Liu, Shuanghe Zhu, Pengxiang Li, Congkai Xie, Jiasheng Wang, Xueyu Hu, Xiaotian Han, Jianbo Yuan, Xinyao Wang, et al. Infigui-g1: Advancing gui grounding with

adaptive exploration policy optimization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pp. 32267–32275, 2026.

Thomas De Min, Subhankar Roy, Stéphane Lathuilière, Elisa Ricci, and Massimiliano Mancini. Proactivebench: Benchmarking proactiveness in multimodal large language models, 2026. URL https://arxiv.org/abs/2603.19466.

Michael Joseph Munje, Chen Tang, Shuijing Liu, Zichao Hu, Yifeng Zhu, Jiaxun Cui, Garrett Warnell, Joydeep Biswas, and Peter Stone. Socialnav-sub: Benchmarking vlms for scene understanding in social robot navigation. In Joseph Lim, Shuran Song, and Hae-Won Park (eds.), *Proceedings of The 9th Conference on Robot Learning*, volume 305 of *Proceedings of Machine Learning Research*, pp. 1120–1143. PMLR, 27–30 Sep 2025. URL https://proceedings.mlr.press/v305/munje25a.html.

Keane Ong, Wei Dai, Carol Li, Dewei Feng, Hengzhi Li, Jingyao Wu, Jiaee Cheong, Rui Mao, Gianmarco Mengaldo, Erik Cambria, et al. Human behavior atlas: Benchmarking unified psychological and social behavior understanding. *arXiv preprint arXiv:2510.04899*, 2025.

OpenAI. GPT-4o System Card, 2024. URL https://arxiv.org/abs/2410.21276. Covers GPT-4o and GPT-4o-mini.

OpenAI. GPT-5.4 Thinking System Card. https://deploymentsafety.openai.com/gpt-5-4-thinking, March 2026a. Released March 5, 2026.

OpenAI. GPT-5.5 System Card. https://deploymentsafety.openai.com/gpt-5-5, April 2026b. Released April 23, 2026.

Pierre Sermanet, Anirudha Majumdar, Alex Irpan, Dmitry Kalashnikov, and Vikas Sindhwani. Generating robot constitutions & benchmarks for semantic safety. In Joseph Lim, Shuran Song, and Hae-Won Park (eds.), *Proceedings of The 9th Conference on Robot Learning*, volume 305 of *Proceedings of Machine Learning Research*, pp. 4767–4823. PMLR, 27–30 Sep 2025. URL https://proceedings.mlr.press/v305/sermanet25a.html.

Phani Teja Singamaneni, Pilar Bachiller-Burgos, Luis J. Manso, Anaís Garrell, Alberto Sanfeliu, Anne Spalanzani, and Rachid Alami. A survey on socially aware robot navigation: Taxonomy and future challenges. *The International Journal of Robotics Research*, 43(10):1533–1572, February 2024. ISSN 1741-3176. doi: 10.1177/02783649241230562. URL http://dx.doi.org/10.1177/02783649241230562.

Fei Tang, Zhangxuan Gu, Zhengxi Lu, Xuyang Liu, Shuheng Shen, Changhua Meng, Wen Wang, Wenqi Zhang, Yongliang Shen, Weiming Lu, Jun Xiao, and Yueting Zhuang. Gui-g^2: Gaussian reward modeling for gui grounding, 2025. URL https://arxiv.org/abs/2507.15846.

Gemma Team. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, 2025.

Xin Eric Wang, Qiuyuan Huang, Asli Celikyilmaz, Jianfeng Gao, Dinghan Shen, Yuan fang Wang, William Yang Wang, and Lei Zhang. Reinforced cross-modal matching and self-supervised imitation learning for vision-language navigation. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6622–6631, 2018. URL https://api.semanticscholar.org/CorpusID:53735892.

Qianhui Wu, Kanzhi Cheng, Rui Yang, Chaoyun Zhang, Jianwei Yang, Huiqiang Jiang, Jian Mu, Baolin Peng, Bo Qiao, Reuben Tan, Si Qin, Lars Liden, Qingwei Lin, Huan Zhang, Tong Zhang, Jianbing Zhang, Dongmei Zhang, and Jianfeng Gao. GUI-actor: Coordinate-free visual grounding for GUI agents. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2026. URL https://openreview.net/forum?id=5fSkinHw7w.

Zhiyu Wu, Xiaokang Chen, Zizheng Pan, Xingchao Liu, Wen Liu, Damai Dai, Huazuo Gao, Yiyang Ma, Chengyue Wu, Bingxuan Wang, Zhenda Xie, Yu Wu, Kai Hu, Jiawei Wang, Yaofeng Sun, Yukun Li, Yishi Piao, Kang Guan, Aixin Liu, Xin Xie, Yuxiang You, Kai Dong, Xingkai Yu, Haowei Zhang, Liang Zhao, Yisong Wang, and Chong Ruan. Deepseek-vl2: Mixture-of-experts vision-language models for advanced multimodal understanding, 2024. URL https://arxiv.org/abs/2412.10302.

Lilin Xu, Bufang Yang, Siyang Jiang, Kaiwei Liu, Kaiyuan Hou, Yuang Fan, Hongkai Chen, Zhenyu Yan, and Xiaofan Jiang. Pro^{2}assist: Continuous step-aware proactive assistance with multi-modal egocentric perception for long-horizon procedural tasks, 2026. URL https://arxiv.org/abs/2605.04227.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=WE_vluYUL-X.

Amir Zadeh, Minghai Chen, Soujanya Poria, Erik Cambria, and Louis-Philippe Morency. Tensor fusion network for multimodal sentiment analysis. In *Proceedings of the 2017 conference on empirical methods in natural language processing*, pp. 1103–1114, 2017.

Amir Zadeh, Michael Chan, Paul Pu Liang, Edmund Tong, and Louis-Philippe Morency. Social-iq: A question answering benchmark for artificial social intelligence. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

AmirAli Bagher Zadeh, Paul Pu Liang, Soujanya Poria, Erik Cambria, and Louis-Philippe Morency. Multimodal language analysis in the wild: Cmu-mosei dataset and interpretable dynamic fusion graph. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2236–2246, 2018.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, Zhangwei Gao, Erfei Cui, Xuehui Wang, Yue Cao, Yangzhou Liu, Xingguang Wei, Hongjie Zhang, Haomin Wang, Weiye Xu, Hao Li, Jiahao Wang, Nianchen Deng, Songze Li, Yinan He, Tan Jiang, Jiapeng Luo, Yi Wang, Conghui He, Botian Shi, Xingcheng Zhang, Wenqi Shao, Junjun He, Yingtong Xiong, Wenwen Qu, Peng Sun, Penglong Jiao, Han Lv, Lijun Wu, Kaipeng Zhang, Huipeng Deng, Jiaye Ge, Kai Chen, Limin Wang, Min Dou, Lewei Lu, Xizhou Zhu, Tong Lu, Dahua Lin, Yu Qiao, Jifeng Dai, and Wenhai Wang. Internvl3: Exploring advanced training and test-time recipes for open-source multimodal models, 2025. URL https://arxiv.org/abs/2504.10479.

Brianna Zitkovich, Tianhe Yu, Sichun Xu, Peng Xu, Ted Xiao, Fei Xia, Jialin Wu, Paul Wohlhart, Stefan Welker, Ayzaan Wahid, Quan Vuong, Vincent Vanhoucke, Huong Tran, Radu Soricut, Anikait Singh, Jaspiar Singh, Pierre Sermanet, Pannag R. Sanketi, Grecia Salazar, Michael S. Ryoo, Krista Reymann, Kanishka Rao, Karl Pertsch, Igor Mordatch, Henryk Michalewski, Yao Lu, Sergey Levine, Lisa Lee, Tsang-Wei Edward Lee, Isabel Leal, Yuheng Kuang, Dmitry Kalashnikov, Ryan Julian, Nikhil J. Joshi, Alex Irpan, Brian Ichter, Jasmine Hsu, Alexander Herzog, Karol Hausman, Keerthana Gopalakrishnan, Chuyuan Fu, Pete Florence, Chelsea Finn, Kumar Avinava Dubey, Danny Driess, Tianli Ding, Krzysztof Marcin Choromanski, Xi Chen, Yevgen Chebotar, Justice Carbajal, Noah Brown, Anthony Brohan, Montserrat Gonzalez Arenas, and Kehang Han. Rt-2: Vision-language-action models transfer web knowledge to robotic control. In Jie Tan, Marc Toussaint, and Kourosh Darvish (eds.), *Proceedings of The 7th Conference on Robot Learning*, volume 229 of *Proceedings of Machine Learning Research*, pp. 2165–2183. PMLR, 06–09 Nov 2023. URL https://proceedings.mlr.press/v229/zitkovich23a.html.

APPENDIX

A Potential Applications **16**

B Scenario Generation **16**

B.1 Scenario Classification 16

B.2 Scenario Generation 18

C Image Generation **18**

C.1 Real Images 18

C.2 Synthetic Images 20

D Behavior Generation **22**

E Human Annotation for Behavior Judgment **23**

F Spatial Grounding Questions Generation and Annotation **24**

G Models Used in Data Construction **25**

H Evaluated Model Details **26**

H.1 Closed-Source VLMs via API 26

H.2 Open-Source General-Purpose VLMs 27

H.3 Open-Source Task-Specialized Vision Models 27

H.4 Model Summarization 28

H.5 Experiment Settings 28

I Facet Details **29**

J Spatial Grounding Experiment **30**

K RAG Knowledge Base Construction and Evaluation **30**

A Potential Applications

In this section, we discuss the potential applications of our work. This paper centers on social properness in embodied agents and evaluates the performance of current representative models. According to the experimental results in Table 1, GPT-5.5 achieves the best performance. Our work thus serves as a diagnostic probe for selecting VLMs with stronger understanding of socially proper behavior in embodied scenarios. The selected models can further function as a planning module for developing embodied agents. Meanwhile, even advanced models still lag significantly behind human performance. These findings indicate that SPI requires targeted training, and our dataset can serve as a valuable resource for enhancing the SPI capabilities of existing models.

B Scenario Generation

B.1 Scenario Classification

Drawing on recent surveys of socially aware robot navigation and embodied deployment environments (Singamaneni et al., 2024), we develop a scenario classification for evaluation of embodied SPI. Through structured expert discussion, we identify 10 major scenario categories covering diverse real-world environments in which an embodied agent may encounter socially meaningful decision points. Each major category is further refined into fine-grained subcategories, resulting in 56 subcategories in total.

The refinement follows two principles. First, each subcategory should capture a distinct type of social reasoning challenge within its parent category. Second, the subcategories within each major category should collectively provide broad coverage of the social situations characteristic of that environment. Figure 11 presents the complete taxonomy. We briefly summarize the 10 major categories below.

Public Spaces & Urban Infrastructure includes shared civic and transit environments, such as bus stations, airports, subways, parking lots, elevators, post offices, and construction or urban maintenance sites. These scenarios correspond to public service robots, delivery assistants, and urban infrastructure agents, which must navigate shared spaces while respecting pedestrian flow, access priority, spatial courtesy, and public-use conventions.

Agriculture & Aquaculture covers semi-structured production environments such as greenhouses, orchards, and aquaculture sites. These scenarios reflect agricultural and environmental assistance applications, where embodied agents must coordinate with human workers, follow task-specific safety and hygiene norms, and operate reliably in changing physical conditions.

Office, Education & Knowledge Work spans knowledge-intensive and service-oriented settings, including classrooms, offices, libraries, meeting rooms, administrative reception counters, tutoring contexts, financial consulting, and legal or government service environments. Agents in these scenarios must manage interruption, respect role boundaries, handle information sensitivity, and interact appropriately in professional or instructional contexts.

Healthcare, Caregiving & Rehabilitation includes hospitals, pharmacies, eldercare facilities, waiting areas, rehabilitation or physical therapy settings, surgical assistance, and mental health or emotional support contexts. These scenarios are central to care and medical assistance robots, requiring heightened sensitivity to privacy, vulnerability, emotional state, bodily boundaries, and professional protocols.

Security, Emergency & Disaster Response covers police, security, traffic management, firefighting, rescue, and medical first-aid situations. Embodied agents in these settings must recognize urgency, prioritize human safety, yield to emergency procedures, and coordinate appropriately with authorized responders.

Laboratories, Research & High-Risk Operations focuses on specialized technical environments such as chemical and biological laboratory assistance. These scenarios require agents to follow strict safety rules, spatial boundaries, contamination-control procedures, and task-specific handling constraints.

Industrial Manufacturing, Logistics & Warehousing includes parcel stations, delivery and logistics settings, assembly lines, packaging, quality inspection, machining lines, and food production or



Figure 11: **Scenario classification of RobotEQ.** Overview of the 10 major scenario categories and 56 fine-grained subcategories covered by RobotEQ.

processing. These scenarios correspond to industrial and logistics robots that must coordinate with human workers, maintain workflow efficiency, and operate safely around tools, products, and moving equipment.

Cultural, Ceremonial & Religious Spaces covers socially sensitive public settings such as weddings, ceremonies, events, mosques, museums, temples, churches, and other religious sites. Agents in these scenarios must respect ritual order, cultural etiquette, silence or movement constraints, and context-specific behavioral boundaries.

Retail, Hospitality & Consumer Services includes consumer-facing venues such as supermarkets, hotels, restaurants, shopping malls, banks, cafés, bookstores, gyms, cinemas, tourist sites, and children's playgrounds. These scenarios represent major service-robot deployment contexts, where agents must handle customer interaction, queueing norms, service etiquette, privacy-sensitive transactions, and diverse user expectations.

Private Living Spaces covers domestic and personal-service settings, including private secretary or butler roles, homes, and pet care tasks such as dog walking, feeding, and cleaning. These scenarios reflect household embodied applications, where agents must adapt to personal routines, intimate spatial boundaries, family preferences, and long-term trust relationships.



Figure 12: **Prompt templates for scenario generation.** Overview of the beam-phase and merge-phase prompts used in RobotEQ-Data, highlighting the input fields, generation constraints, deduplication rules, and expected output structure.

B.2 Scenario Generation

Constructing a diverse and socially meaningful scenario pool across all 56 subcategories is a key step in the RobotEQ pipeline, since the quality and coverage of the generated scenarios directly affect the scope of the benchmark. At the same time, large-scale querying of frontier language models is costly. To balance diversity and efficiency, we adopt a beam-merge generation strategy.

In the **beam phase**, we issue 10 independent generation requests for each subcategory, with each request producing at least 10 candidate scenarios. Within each request, the model is instructed to avoid repetition in situational setting, narrative structure, and the specific aspect of SPI being tested. This yields roughly 100 candidate scenarios per subcategory. We use Gemini-3.1-Pro-Preview (Google DeepMind, 2026) as the generation model in this stage.

In the **merge phase**, we collect the candidates produced by the 10 beams and pass them to a separate expert model for deduplication. The expert model removes scenarios that are overly similar in context, triggering event, or targeted SPI dimension, and retains those that are meaningfully distinct. To reduce systematic bias from relying on a single model family, we use a different model series for this stage: GPT-5.4 (OpenAI, 2026a). The resulting subcategory-level pools are then combined to form the final candidate scenario pool.

To encourage scenarios that test SPI rather than routine task execution, we also develop a set of heuristic prompting rules through scenario generation. These rules require each scenario to include a socially meaningful decision point, together with a detailed scenario description and a brief rationale for why SPI is needed in that setting. The complete prompts used in the beam and merge phases are shown in Figure 12. Figure 13 shows several examples in the scenario pool.

C Image Generation

C.1 Real Images

Guided by the scenario classification provided in Section 4, we construct a large-scale repository of real-world, first-person (egocentric) images to ensure the visual fidelity and deployment realism of RobotEQ. The entire pipeline consists of four main stages: *JRDB-Social Selection*, *candidate query generation*, *multi-source web crawling*, and *multi-stage filtering*.



Figure 13: **Representative scenario examples.** Five example scenarios illustrating how embodied agents must reason over nonverbal cues, spatial relations, and context-specific social norms in real-world human environments.

JRDB-Social Selection. We incorporate the JRDB-Social dataset (Jahangard et al., 2024) to supply authentic robot-centric observations. JRDB-Social extends the egocentric JRDB benchmark, which was captured by the social mobile robot JackRabbot and comprises 54 indoor and outdoor sequences with 360° cylindrical RGB, LiDAR, and RGB-D streams from the robot's own perspective (**?**). Complementing these sensory streams, JRDB-Social adds three-level annotations for human social dynamics: individual attributes, intra-group interactions, and social group context (**?**). We extract static frames from its egocentric RGB streams to simulate a service robot's first-person view, and leverage the accompanying social annotations as priors for later relevance screening.

Candidate Query Generation. We first decompose the 56 fine-grained scenarios (spanning 10 high-level categories) into sub-categories and generate a total of 1,344 English search queries. These queries are categorized into three types to maximize viewpoint coverage: (1) *POV queries* that explicitly request first-person perspectives; (2) *scene-variant queries* that describe diverse sub-scenes; and (3) *staff-role queries* that simulate a service robot's viewpoint. This design ensures that the retrieved images plausibly approximate the visual observations of an embodied agent.

Multi-Source Web Crawling. To gather candidate images, we employ a multi-source aggregation strategy that prioritizes results from SerpAPI (Google Images), Baidu, Bing, 360, Wikimedia Commons, and Flickr. The crawler iterates through the query list, automatically falling back to the next source when the target number of images per query is not met. Downloaded images are subjected to strict validation: we verify MIME types (JPEG/PNG/WebP), enforce a size constraint (8 KB–20 MB), and perform global SHA-256 deduplication to remove near-duplicate and thumbnail images. This process yields approximately 44,428 raw images stored in an organized repository.

Multi-Stage Filtering. Both the web-crawled candidates and the static frames extracted from JRDB-Social are merged into a unified pool, which inevitably contains noise, off-view samples, and duplicates across sources. We therefore apply a rigorous, source-agnostic filtering pipeline to guarantee dataset quality. First, we use a vision-language model (Qwen3-VL-8B) to perform RobotEQ-relevance screening, retaining only images that depict valid embodied scenarios. Next, we filter by image resolution and Laplacian sharpness to ensure visual clarity. We then apply diversity-aware selection to balance scene distributions, followed by source-level deduplication to eliminate overlaps between web images and JRDB-Social frames. Finally, the remaining candidates undergo human expert curation to remove any images with unnatural compositions or privacy concerns. This progressive filtering process ensures that the final real-image subset—regardless of its origin—meets the high standards required for evaluating Social Proactive Intelligence.

C.2 SYNTHETIC IMAGES

The scenarios produced by the beginning of the generation pipeline in Section 4 are textual descriptions. They specify the social context, the position of the agent, and the environmental layout, but are not optimized directly as prompts for text-to-image models. Directly using these descriptions often leads to missing social cues, distorted spatial relations, or images that deviate from the intended scenario. We therefore introduce a staged image generation and refinement process to convert textual scenarios into robot-centric visual instances.

Visual Prompt Synthesis. For each scenario, we first provide its textual description and associated metadata to a prompt synthesis model. The model converts this information into a detailed visual prompt that specifies the first-person viewpoint, spatial arrangement of people and objects, environmental context, and socially salient cues such as gaze, posture, facial expression, or signage. This step serves as a controlled translation from scenario semantics to visual generation instructions, helping preserve the intended social context while making the input suitable for image generation. The complete prompt template and representative input–output examples are provided in Figure 14.



Figure 14: **Scenario-to-image prompt synthesis.** An example of how RobotEQ-Data converts a structured embodied social scenario into a visual prompt for image generation. The prompt preserves the social interaction conflict, specifies visual anchors and spatial relations, and produces a first-person scene image for benchmark construction.

Image Generation. The synthesized visual prompts are then used to generate candidate scenario images. We use Gemini-3-Pro-Image-Preview (Google DeepMind, 2025) for image generation. Each visual prompt produces one initial candidate image.

Automated Quality Review. Generated images may still contain artifacts or inconsistencies, such as implausible object placement, missing social cues, or incorrect robot-centric perspective. To improve image quality, we introduce an automated review loop inspired by the ReAct reasoning-and-acting paradigm (Yao et al., 2023). A separate expert model evaluates each candidate image against seven quality criteria from experts and returns a binary assessment vector $\mathbf{q} \in \{0,1\}^7$, where $q_j = 1$ indicates that the j-th criterion is satisfied. For failed criteria, the model also provides structured revision suggestions.

The seven criteria are divided into hard and soft constraints. Failure on any hard constraint imposes a mandatory revision flag on this image. An image is also flagged for revision if four or more criteria are not satisfied:

$$\sum_{j=1}^{7}(1 - q_j) \geq 4. \tag{3}$$

Table 2: **Image quality criteria for RobotEQ-Data.** We use seven criteria to assess whether a generated image is suitable for inclusion in the benchmark. Criteria marked as mandatory must be satisfied for an image to pass the automatic review.

ID	Criterion	Description	Type
1	scenario_faithfulness	The image should correctly and sufficiently express the intended scenario. Images that drift from the given scenario or are difficult to interpret should not pass.	Soft
2	factual_correctness	The image should not contain obvious generation artifacts or physically implausible content, such as abnormal limbs, distorted fingers, broken joints, or unreasonable object states.	Hard
3	detail_quality	Human actions, object relations, and spatial cues should be clear enough for annotators to understand what is happening in the scene.	Soft
4	pov_constraint	The image should follow a robot first-person viewpoint and should not show the robot body, robotic arms, external shell, screen, or robot reflection.	Soft
5	no_forbidden_graphics	The image should avoid obvious text, posters, tables, infographics, mobile interfaces, computer UI, or other non-scene graphic elements.	Soft
6	json_consistency	The output must contain `scenario_summary`, `matrix` with the required boolean keys, and `reasons`. The `reasons` field should include only failed dimensions; dimensions marked as true must not appear in `reasons`.	Hard
7	social_cue_visibility	The image should contain visible social cues needed for social norm reasoning, such as gaze direction, body posture, gesture, interpersonal distance, object ownership, waiting state, or other context-specific interaction signals.	Soft

We use Doubao-Seedream (Gao et al., 2025) as the expert review model, choosing a model family different from the generator to reduce shared failure patterns. The complete editing prompt criteria is shown in Table 2.

Image Revision. All candidate images are passed to the image editing interface together with the original visual prompt and the expert model's feedback. For images carrying a mandatory revision flag, the editing prompt explicitly incorporates the revision suggestions for failed criteria, requiring the generation model to correct the identified issues while preserving the intended scenario. Images without a mandatory flag are also sent through the same refinement pipeline, but their edits are treated as optional and are limited to minor improvements suggested by the expert model.

Figure 15 presents representative initial and revised images. After automated refinement, all images undergo the human verification stage, where annotators conduct final quality control.



Figure 15: **Examples of image refinement.** Representative raw and edited images from the automated refinement stage. The examples illustrate how the editing process improves visual grounding and scenario fidelity while preserving the intended embodied social context.

Human Verification. After the automated revision stage, we aggregate the original image, the edited image, the corresponding scenario, and the scenario description into a Label Studio[2] interface

[2] `https://labelstud.io`



Figure 16: **Examples of the Label Studio annotation interface.** The left panel shows the human verification stage where annotators compare original and edited scenario images, and the right panel shows the human annotation stage for behavior judgment and spatial grounding labelling. Additional cases are omitted for brevity.

for human verification. Annotators compare the original and edited versions and select the image that best matches the intended scenario. If both versions still contain visual artifacts, semantic mismatches, or missing social cues, annotators provide additional revision instructions. The Label Studio annotation interface is illustrated in Figure 16.

These human instructions are then fed back into Gemini-3-Pro-Image-Preview for another round of image editing. This step serves two purposes. First, it prevents errors introduced by the expert model's automatic feedback from degrading image quality or drifting away from the intended scenario. Second, it incorporates human judgment into the refinement process, improving the realism, social plausibility, and contextual fidelity of the final images.

All images undergo a final round of human verification to filter out both **non-robot-centric perspectives** (i.e., those capturing the robot's full body from a third-person viewpoint) and images **lacking photorealism** (exhibiting noticeable AIGC artifacts), thereby guaranteeing the authenticity of our dataset.

D Behavior Generation

The behavior generation stage aims to construct, for each validated scenario, a diverse pool of candidate behaviors that includes both socially appropriate and inappropriate behaviors. This pool should not be limited to routine or trivially distinguishable choices; instead, it should contain behaviors that probe the boundary of socially acceptable behavior in the given context. Such diversity is important because the subsequent annotation stage can only capture fine-grained social distinctions when the candidate behaviors themselves are sufficiently varied.

We condition the generation model on both the textual scenario description and the corresponding robot-centric image, and instruct it to produce five *proper* behaviors and five *improper* behaviors per request. The criteria for determining whether something is proper or improper are judged based on the standard of the behavior generation model. Following the heuristic prompting strategy used in scenario generation (Appendix B.2), we impose three main constraints. First, each behavior must describe a concrete, physically executable behavior grounded in the visual scene, rather than an abstract intention. Second, the proper and improper behaviors should cover different facets of SPI, so that the resulting pool reflects a range of relevant norms. Third, behaviors within the same request should not be near-duplicates expressed with different wording. The complete behavior generation prompt is shown in Figure 17.

After assembling the behavior pool, we remove all model-assigned propriety labels and randomly shuffle the behavior order before human annotation. This step prevents annotators from inheriting the model's initial judgments and ensures that each behavior is evaluated based on human social reasoning. In our pipeline, the LLM serves only as a proposal mechanism for generating scenario-



Figure 17: **Behavior generation prompt.** Illustration of the prompt structure used to generate candidate behavior pools from a scenario image and its textual description.

grounded behaviors. The final ground-truth label for each behavior is determined by majority vote among independent human annotators.

E Human Annotation for Behavior Judgment

Building on the candidate behavior pool described in Appendix D, we use human annotation to establish ground-truth labels for the behavior judgment component of RobotEQ-Data. The annotation process consists of three stages: annotator recruitment and training, a pilot study, and full-scale labeling.

Annotator Recruitment and Training. We recruit more than ten undergraduate or master's degree annotators with sufficient everyday knowledge to reason about social situations across the scenario categories in RobotEQ. All prospective annotators completed a pre-screening questionnaire, and domain experts verified that every candidate demonstrated exceptional competence in emotional intelligence, personality traits, and sociological knowledge base. Before labeling, all annotators complete a structured training session. The session introduces the scenario classification, explains the three label categories—*proper*, *improper*, and *invalid*—and provides worked examples covering common boundary cases. Annotators are instructed to take the perspective of the embodied agent in the robot-centric image, and judge whether each candidate behavior is socially appropriate. The label *inappropriate* is reserved for behaviors that should be excluded from the benchmark, such as physically impossible behaviors, irrelevant behaviors, or behaviors that do not form a meaningful test of SPI. All annotations are collected through a Label Studio interface configured for this task.

Pilot Study. To calibrate annotation quality, we conduct a qualification test with 20 items. Each item contains a robot-centric scenario image and its associated candidate behaviors, and annotators complete the test independently under the same conditions as formal labeling. For each behavior, we first compute the majority vote across test participants, and a domain expert then reviews the consensus labels to obtain calibrated ground truth. Based on the results, we select seven annotators with the highest overall reliability for the full-scale annotation stage.

Full-Scale Labeling. In the formal annotation phase, each behavior is independently labeled by three annotators, and the final label is determined by majority vote. If the three annotators assign three different labels to an behavior judgment question, the behavior is sent to additional annotators



Figure 18: **Behavior judgment evaluation example.** The figure illustrates the input format used for behavior judgment in RobotEQ. Given a first-person scenario image, the model receives a role-specific question and a list of candidate behaviors, and must assign each behavior a binary label indicating whether it should or should not be performed.

until a majority is reached. Candidate behaviors are evenly distributed across the seven qualified annotators and assigned to rotating annotator groups. After labeling, we conduct a final expert review to check label consistency across scenarios. Behaviors labeled as *invalid* are removed from the benchmark, while the remaining behaviors and their labels form the behavior judgment component of RobotEQ-Data. Figure 18 shows the reasoning format of VLMs: a VLM receives a first-person scenario image and a candidate behavior, and predicts whether the behavior is *proper* or *improper*.

F Spatial Grounding Questions Generation and Annotation

Unlike behavior judgment, where the same prompt template can be applied across scenarios, Spatial Grounding require more image-specific design. Each scenario image contains a different spatial configuration: some questions may involve selecting a safe path, others may require locating a person in need or identifying an appropriate interaction target. As a result, fully automated generation often produces generic questions or spatial annotations that do not match the visual scene. We therefore adopt a human-initiated process for construction of spatial grounding questions.

Manual Questions Generation. We recruit five trained annotators to inspect each scenario image independently and propose candidate spatial grounding topics. Annotators are not given the textual description of the scenario, so the proposed questions must be grounded in visual evidence rather than text. Each topic is expected to identify a spatially relevant decision that an embodied agent could make from the image, such as where to move, which person to approach, or which object or region is socially appropriate to select. The proposals from all annotators are then aggregated to form a candidate topic pool for each image.

Two-Stage Question and Image Editing. We generate spatial grounding's final question title and edited image through a two-stage process. In the first stage, a scaffolding prompt takes the human-proposed topic and the scenario image as input, and asks an LLM to produce two outputs: a standardized spatial grounding question title and an image editing instruction. The editing instruction specifies how four spatial annotations, labeled A, B, C, and D, should be overlaid on the original image, with at least one annotation corresponding to a correct answer. Since a spatial question may admit multiple valid answers, we formulate spatial grounding as multiple-select questions. The prompt also instructs the model to place incorrect options at plausible but suboptimal regions, so that the question tests fine-grained spatial grounding rather than simple visual salience. We use GPT-5.4 for this stage.

In the second stage, the image editing instruction is passed to Gemini-3-Pro-Image-Preview, which adds the A–D annotations to the original scenario image. We also compare this design with a single-stage variant that directly sends the image and human-proposed topic to the image editing model. In practice, the single-stage variant more often produces misplaced, overlapping, or missing annotations. Figure 19 shows representative comparisons between the two-stage and single-stage pipelines.

Human Annotation. To avoid inheriting model-generated answer labels, we remove all model-provided correctness information before human annotation. The A–D spatial annotations remain



Figure 19: **Comparison of sptaial grounding question generation pipelines.** Representative examples comparing the two-stage and one-stage construction procedures for spatial grounding questions. The two-stage pipeline produces more precise and visually grounded spatial annotations, while the one-stage pipeline is more prone to misplaced, overly broad, or spatially incoherent annotations.



Figure 20: **Spatial grounding evaluation example.** The figure illustrates the input and output format for a spatially grounded multiple-choice question in RobotEQ-Data. Given an annotated robot-centric scene image and a question, the model selects all applicable spatial regions and provides a brief rationale for its prediction.

visible, but annotators determine the ground-truth answer set independently. The seven annotators selected in Appendix E label spatial grounding questions through a Label Studio interface. We first run a pilot study on 20 candidate sptaial grounding questions.

In the formal annotation phase, each sptail grounding question is answered by three annotators. Because a question may have multiple correct regions, annotators judge each option in {A, B, C, D, *Invalid*} independently. Options selected by a majority of annotators(4) are included in the final answer set. If *Invalid* receives majority support, the item is excluded, as the question or edited image is considered unsuitable for reliable evaluation. The remaining spatial groudning questions and their per-option labels form the spatially grounded evaluation component of RobotEQ-Data. Figure 20 illustrates the evaluation format presented to VLMs.

G Models Used in Data Construction

The RobotEQ-Data construction pipeline employs several frontier commercial LLMs at different stages, deliberately alternating model families between consecutive quality-critical steps to reduce

systematic bias. Table 3 lists each model, its role in the pipeline, and the corresponding API documentation.

Table 3: **Models used in the RobotEQ-Data construction pipeline.** For each model we list the pipeline stage(s) in which it is employed and a link to its official API documentation.

Model	Role in Pipeline	API Documentation
Gemini-3.1-Pro-Preview	Scenario generation (beam phase); visual prompt synthesis for image generation	https://ai.google.dev/gemini-api/docs/models/gemini-3.1-pro-preview
GPT-5.4	Cross-batch scenario deduplication (merge phase); spatial grounding question title and editing instruction generation (scaffolding stage)	https://platform.openai.com/docs/models
Gemini 3 Pro Image Preview	Scenario image generation and editing; spatial grounding annotation overlay	https://ai.google.dev/gemini-api/docs/models/gemini-3-pro-image-preview
Doubao-Seedream	Automated image quality review (expert reviewer)	https://www.volcengine.com/docs/82379/1824692

H Evaluated Model Details

This appendix lists all models evaluated on RobotEQ-Bench. We group them into three categories: closed-source accessed through official APIs, open-source general-purpose VLMs, and open-source task-specialized VLMs. This grouping allows us to compare frontier closed-source systems, broadly usable open-source multimodal models, and models specialized for fine-grained visual grounding or document understanding.

H.1 Closed-Source VLMs via API

Gemini 2.5 Pro (Comanici et al., 2025) is a closed-source multimodal model from Google DeepMind, included as a strong closed-source baseline for visual reasoning and long-context multimodal understanding.

GPT-5.4 (OpenAI, 2026a) is a closed-source multimodal model from OpenAI, evaluated as one of the frontier API-based systems for complex reasoning over image-text inputs.

GPT-5.5 (OpenAI, 2026b) is a later OpenAI multimodal model, included to assess whether newer frontier systems improve on embodied social reasoning tasks.

Claude Sonnet 4.6 (Anthropic, 2026c) is a closed-source multimodal model from Anthropic, representing a cost-efficient Claude-family baseline with strong instruction-following and reasoning capabilities.

Claude Opus 4.6 (Anthropic, 2026a) is Anthropic's high-capability Claude-family model, included as a strong closed-source baseline for complex multimodal reasoning.

Claude Opus 4.7 (Anthropic, 2026b) is a later Anthropic flagship model, evaluated to measure performance among the strongest Claude-series systems.

GPT-4o-mini (OpenAI, 2024) is a lightweight multimodal model from OpenAI, included as a lower-cost closed-source baseline for image-text reasoning.

Doubao-Seed-1.6-Flash (ByteDance Seed Team, 2025) is a fast multimodal model served through ByteDance's Volcengine platform, included to evaluate low-latency API-based multimodal reasoning.

Gemini 3.1 Pro Preview (Google DeepMind, 2026) is a closed-source Google DeepMind multimodal model, evaluated as a newer Gemini-family baseline for advanced visual and reasoning tasks.

Qwen-VL-Plus (Bai et al., 2023) is Alibaba Cloud's closed-source vision-language service, included as a commercial Qwen-family multimodal baseline.

H.2 Open-Source General-Purpose VLMs

Qwen2.5-VL-7B-Instruct (Bai et al., 2025b) is the smaller Qwen2.5-VL variant, included to assess performance under more practical open-source deployment constraints.

Qwen3-VL-8B (Bai et al., 2025a) is a newer Qwen vision-language model, evaluated as a mid-to-large open-source baseline for visual reasoning.

InternVL3-8B (Zhu et al., 2025) is a compact InternVL3 variant, used to compare the effect of model scale within the same model family.

Gemma-3-12B/4B (Team, 2025) is an instruction-tuned open-weight multimodal model from Google, included as a general-purpose open-source baseline.

GLM-4.1V-9B-Thinking (Hong et al., 2025) is a compact vision-language model from the GLM family, included for its explicit emphasis on visual reasoning.

Phi-4-Multimodal (Abouelenin et al., 2025) is a compact multimodal model from Microsoft, evaluated as a resource-efficient baseline across image-text tasks.

Pixtral-12B-2409 (Agrawal et al., 2024) is Mistral AI's open vision-language model, included for its native handling of interleaved image-text inputs.

LLaVA-OneVision-7B (Li et al., 2025) is a large LLaVA-family model designed for unified image, multi-image, and video understanding, included as a strong open-source baseline.

Idefics3-8B-Llama3 (Laurençon et al., 2024) is an open multimodal model built on the Llama backbone, included as a reproducible medium-scale VLM baseline.

Aya-Vision-8B (Dash et al., 2025) is a multilingual vision-language model from Cohere For AI, included to examine whether broad multilingual multimodal training benefits embodied social reasoning.

Llama-3.2-11B-Vision-Instruct (Grattafiori et al., 2024) is Meta's open multimodal Llama model, included as a widely used instruction-following VLM baseline.

DeepSeek-VL2-Small (Wu et al., 2024) is a DeepSeek vision-language model using efficient high-resolution visual processing, included as a general-purpose open-source multimodal baseline.

Janus-Pro-7B (Chen et al., 2025b) is a DeepSeek multimodal model with separate visual understanding and generation pathways, included for its compact but flexible visual reasoning design.

H.3 Open-Source Task-Specialized Vision Models

GUI-G2-7B (Tang et al., 2025) is a GUI grounding model designed to localize interface elements, included as a vision-specialized baseline for fine-grained spatial grounding.

GUI-Actor-7B-Qwen2.5-VL (Wu et al., 2026) is a GUI action grounding model that predicts actionable regions in visual interfaces, included to test whether grounding-oriented training transfers to spatially grounded embodied questions.

GroundNext-7B-V0 (Feizi et al., 2025) is a GUI grounding model from the GroundCUA line, included as a specialized baseline for region-level visual grounding.

InfiGUI-G1-7B (Liu et al., 2026) is a GUI grounding model optimized for interactive visual grounding, evaluated to compare specialized grounding ability with general-purpose VLM reasoning.

UGround-V1-7B (Gou et al., 2025) is a universal GUI grounding model trained for cross-platform visual grounding, included as another spatial grounding baseline.

Nanonets-OCR-s[3] is a compact document understanding model based on a VLM backbone, included as a specialized visual-text recognition baseline.

[3] https://huggingface.co/nanonets/Nanonets-OCR-s

Nanonets-OCR2-3B[4] is a second-generation Nanonets OCR model for structured document understanding, included to test whether document-focused visual parsing helps on visually grounded reasoning tasks.

H.4 Model Summarization

For closed-source models, we use the public API endpoints available at the time of evaluation. For open-source models, we use the corresponding Hugging Face checkpoints and run inference with the official or proper model-specific settings when available. Table 4 summarizes the evaluated models and their documentation or checkpoint links.

Table 4: **Evaluated models in RobotEQ-Bench.** We list all closed-source and open-source models evaluated in this paper, together with the corresponding API documentation or checkpoint links.

Model	Documentation / Checkpoint
Closed-Source VLMs	
Gemini 2.5 Pro	https://ai.google.dev/gemini-api/docs/models/gemini-2.5-pro
GPT-5.4	https://platform.openai.com/docs/models
GPT-5.5	https://platform.openai.com/docs/models
Claude Sonnet 4.6	https://docs.anthropic.com/en/docs/about-claude/models
Claude Opus 4.6	https://docs.anthropic.com/en/docs/about-claude/models
Claude Opus 4.7	https://docs.anthropic.com/en/docs/about-claude/models
GPT-4o-mini	https://platform.openai.com/docs/models
Doubao-Seed-1.6-Flash	https://www.volcengine.com/docs/82379
Gemini 3.1 Pro Preview	https://ai.google.dev/gemini-api/docs/models/gemini-3.1-pro-preview
Qwen-VL-Plus	https://help.aliyun.com/zh/model-studio/vision-white
Open-Source General-Purpose VLMs	
Qwen2.5-VL-7B-Instruct	https://huggingface.co/Qwen/Qwen2.5-VL-72B-Instruct
Qwen3-VL-8B	https://huggingface.co/Qwen/Qwen3-VL-32B
InternVL3-8B	https://huggingface.co/OpenGVLab/InternVL3-8B
Gemma-3-12B/4B	https://huggingface.co/google/gemma-3-27b-it
GLM-4.1V-9B-Thinking	https://huggingface.co/THUDM/GLM-4.1V-9B-Thinking
Phi-4-Multimodal	https://huggingface.co/microsoft/Phi-4-multimodal
Pixtral-12B-2409	https://huggingface.co/mistralai/Pixtral-12B-2409
LLaVA-OneVision-7B	https://huggingface.co/lmms-lab/llava-onevision-qwen2-72b-ov-sft
Idefics3-8B-Llama3	https://huggingface.co/HuggingFaceM4/Idefics3-8B-Llama3
Aya-Vision-8B	https://huggingface.co/CohereForAI/aya-vision-32b
Llama-3.2-11B-Vision-Instruct	https://huggingface.co/meta-llama/Llama-3.2-11B-Vision-Instruct
DeepSeek-VL2-Small	https://huggingface.co/deepseek-ai/deepseek-vl2
Janus-Pro-7B	https://huggingface.co/deepseek-ai/Janus-Pro-7B
Open-Source Task-Specialized VLMs	
GUI-G2-7B	https://huggingface.co/inclusionAI/GUI-G2-7B
GUI-Actor-7B-Qwen2.5-VL	https://huggingface.co/microsoft/GUI-Actor-7B-Qwen2.5-VL
GroundNext-7B-V0	https://huggingface.co/ServiceNow/GroundNext-7B-V0
InfiGUI-G1-7B	https://huggingface.co/InfiX-ai/InfiGUI-G1-7B
UGround-V1-7B	https://huggingface.co/osunlp/UGround-V1-7B
Nanonets-OCR-s	https://huggingface.co/nanonets/Nanonets-OCR-s
Nanonets-OCR2-3B	https://huggingface.co/nanonets/Nanonets-OCR2-3B

H.5 Experiment Settings

All local models are deployed on a server equipped with three NVIDIA L40 GPUs (48 GB VRAM each). We use vLLM (v0.19.1) as the inference engine for 17 models and fall back to HuggingFace Transformers (v5.5.4) for the remaining 5 models whose architectures are not yet supported by vLLM.

[4] https://huggingface.co/nanonets/Nanonets-OCR2-3B

Images are resized such that the longest dimension does not exceed 768 pixels. For decoding, we set `temperature = 0` (greedy) across all conditions and fix `max_tokens = 1024` for both the standard prompt and RAG, while increasing it to 2048 for CoT to accommodate the longer reasoning trace. The maximum context length is capped at 8192 tokens; batch size is 16; precision is FP16.

For closed-source models accessed via API (GPT-5.5, Claude Opus 4.6, Doubao-Seed-1.6-Flash, Qwen-VL-Plus, *etc.*), we likewise enforce `temperature = 0` and request structured JSON output. The `max_tokens` setting mirrors the local configuration (1024 for standard/RAG, 2048 for CoT). No other sampling parameters (*e.g.*, top-p, frequency penalty, random seed) are modified from their provider defaults.

I Facet Details

RobotEQ-Bench annotates behavior judgment scenarios along seven SPI facets, each capturing a distinct aspect of socially appropriate behavior in embodied environments. The taxonomy is developed through expert discussion within the annotation team and is used to support facet-level analysis of model performance. The seven facets are defined as follows.

Politeness is the ability to exhibit appropriate social etiquette, greetings, and courteous behaviors during human-robot interactions. This ensures respectful and harmonious communication. For example, when entering an elevator with a person, the robot should offer a verbal greeting instead of remaining silent. It should also wait for the person to exit before entering if the space is limited.

Proxemics is the ability to reason about and respect personal space, appropriate interpersonal distances, queuing, yielding, and spatial boundaries in shared environments. For example, when a person is working at a desk, the robot should maintain a comfortable distance and avoid standing too close. In a narrow corridor, it should yield to the human instead of forcing its way through.

Sensitivity is the ability to perceive and respond to the emotional states, needs, and non-verbal cues of target individuals. This demonstrates empathy and emotional intelligence in social contexts. For example, if a user is sighing and rubbing their temples, the robot should notice these cues. It might lower its voice or offer assistance instead of continuing with noisy tasks.

Privacy is the understanding of personal boundaries and the protection of private information or sensitive data during interactions. This means avoiding intrusive questions or behaviors that violate individual privacy. For example, the robot should not read personal messages on a screen over someone's shoulder. It should also avoid asking about medical conditions in public areas.

Cooperation is the willingness and capability to engage in collaborative tasks, share goals, and provide proactive support to others. This helps achieve common objectives. For example, when a person is carrying multiple boxes, the robot can proactively open the door. It can also help transport items to a shared destination without being asked.

Priority is the ability to identify individuals who require prioritized assistance or right-of-way. This includes children, the elderly, patients, or people involved in emergency situations. For example, in a hallway, the robot should stop and give way to an elderly person walking slowly. During an emergency, it should prioritize helping patients over routine tasks.

Safety is the ability to predict and avoid potential physical risks or harmful interactions. This ensures the well-being of humans in dynamic embodied environments. For example, the robot should detect wet floor signs and avoid guiding people through that area. It should also slow down when moving near crowded spaces to prevent collisions.

Annotation methodology. We assign facet labels through a two-stage process that combines LLM-based classification with human calibration. In the first stage, Gemini 3.1 Pro Preview receives the scenario image, textual description, and corresponding candidate behavior as input, and assigns one or more labels from the predefined taxonomy. Since a scenario-behavior pair may involve multiple facets of social reasoning, the dimension labels are not mutually exclusive. In the second stage, human annotators review and correct the model-generated labels to ensure consistency with the taxonomy.

After annotation, valid scenarios are labeled with at least one facet. Because scenarios may receive multiple labels, the total number of facet labels is 5,650. Table 5 summarizes the resulting distribution.

Table 5: Facet-level scenario distribution.

Sensitivity	Cooperation	Safety	Proxemics	Politeness	Priority	Privacy	Total
1,442	1,403	983	616	509	372	325	5,650

The distribution is imbalanced across facets. *Sensitivity* is the most frequent category, with 1,442 labels, reflecting the central role of perceiving and responding to human emotional states, needs, and non-verbal cues in embodied social interaction. *Cooperation* (1,403) and *Safety* (983) are also well-represented, consistent with the importance of collaborative engagement and physical risk avoidance for physically situated agents. By contrast, *Privacy* appears less frequently in the collected scenario pool, with 325 labels, but remains important for evaluating whether embodied agents can respect personal boundaries and avoid intrusive behaviors in privacy-sensitive settings.

J Spatial Grounding Experiment

We provide the full numerical results for the spatial grounding evaluation discussed in Section 5. We assess 14 representative VLMs on spatial grounding questions that require identifying the correct bounding box of a target UI element from four candidates. Models are grouped into closed-source VLMs, open-source general-purpose VLMs, and open-source task-specialized VLMs. Three metrics are reported: Macro-F1, Hit Rate (whether the predicted region overlaps the ground truth), and Accuracy (exact option match). Human performance on the same test set serves as an upper-bound reference. Detailed per-model results are listed in Table 6.

Table 6: **Spatial grounding results**. We group models by category and treat Macro-F1 as the primary metric. For each metric, the top result is shown in **bold** and the runner-up is underlined. Human performance is listed separately as an upper bound.

Model	Size	Micro-F1(%)	Macro-F1(%)	PA(%)	CWPA(%)
Open-Source General-Purpose VLMs					
GLM-4.1V (Hong et al., 2025)	9B	61.97	43.78	64.38	65.22
DeepSeek-VL2 (Wu et al., 2024)	12B	69.67	49.79	**71.03**	**72.21**
LLaVA-OneVision (Li et al., 2025)	7B	56.63	51.51	56.49	57.00
InternVL3 (Zhu et al., 2025)	8B	66.49	55.02	68.97	70.07
Gemma-3 (Team, 2025)	12B	64.30	58.45	55.78	56.31
Qwen3-VL (Bai et al., 2025a)	8B	68.69	**60.52**	66.33	67.27
Open-Source Task-Specialized VLMs					
GroundNext (Feizi et al., 2025)	7B	66.09	55.88	63.10	64.06
InfiGUI-G1 (Liu et al., 2026)	7B	68.05	55.89	66.34	67.43
Nanonets-OCR2	3B	**70.12**	57.23	67.13	68.23
GUI-Actor (Wu et al., 2026)	7B	67.16	59.06	58.67	59.21
Closed-Source VLMs					
GPT-5.5 (OpenAI, 2026b)	–	59.26	55.55	61.34	61.63
Gemini 2.5 Pro (Comanici et al., 2025)	–	66.00	55.98	66.04	66.89
Claude Sonnet 4.6 (Anthropic, 2026c)	–	65.88	59.16	60.79	61.14
Claude Opus 4.7 (Anthropic, 2026b)	–	69.59	59.72	67.03	67.92
Human					
Human	–	88.78	84.42	84.16	85.07

K RAG Knowledge Base Construction and Evaluation

We construct a role-specific SPI knowledge base to support the retrieval-augmented generation setting. Each robot role is associated with a document summarizing the social and operational norms relevant to that role, organized into nine modules: spatial distance, communication style, physical

Table 7: **Role of RAG.** We report the performance and resource consumption of RAG.

(a) Open-Source models

Model	Size	Macro-F1 (%)		Time (s/query)	
		Raw	RAG	Raw	RAG
Phi-4-Multi	3.8B	54.62	**57.03**	0.48	1.04
Qwen2.5-VL	7B	61.87	**64.49**	0.67	1.32
GUI-G2	7B	61.94	**68.00**	0.69	1.17

(b) Closed-Source models

Model	Size	Macro-F1 (%)		Cost ($/query)	
		Raw	RAG	Raw	RAG
GPT-5.5	–	72.42	72.16	0.0208	0.0309
Claude 4.6	–	72.00	**72.17**	0.0182	0.0302
Doubao	–	60.32	**69.23**	0.0003	0.0004

contact boundaries, emotional awareness, privacy and dignity, safety protocols, proactivity and timing, contextual behavior, and role-specific constraints. For each role, we first use an LLM to draft the document structure and identify common normative concerns. Domain experts then revise and extend the draft with concrete, actionable guidelines grounded in Human–Robot Interaction practice and real service scenarios. This process produces compact role-level references that can be retrieved at inference time and injected into the model prompt as external social knowledge. Figure 21 shows a representative knowledge base document for a teaching assistant robot. To validate whether such explicit social normative guidelines can prevent the SPI failures observed in RobotEQ, we implement a RAG framework across robots operating in diverse scenarios. At inference time, the model retrieves relevant norms from the constructed knowledge base and incorporates them into its reasoning process. Table 7 reports the performance and resource consumption of both open-source and closed-source models under the Raw and RAG settings. For open-source models, RAG consistently improves Macro-F1 scores, with GUI-G2 showing the largest gain from 61.94% to 68.00%, albeit at a moderate increase in inference time. For closed-source models, the improvements are more nuanced: while GPT-5.5 shows a slight decrease, Claude 4.6 and Doubao achieve noticeable gains, with Doubao improving from 60.32% to 69.23%. These results suggest that augmenting VLMs with retrieval-based social knowledge is a promising direction for mitigating the SPI deficiencies observed in today's embodied agents, though the effectiveness varies across model families and scales.



Figure 21: Example of a role-specific RAG knowledge base. The figure shows a representative knowledge document for a teaching assistant robot.