ADAGUARD: ENHANCING SAFETY AND POLICY COMPLIANCE WITH REASONING-ENABLED LLM-AS-A-JUDGE GUARDRAILS

Anonymous authors
Paper under double-blind review

ABSTRACT

Enterprise generative AI applications require robust safety mechanisms that can accommodate diverse risk postures, evolving policies, and varying latency constraints. Current guardrail solutions often suffer from rigidity, relying on fixed policy sets and offering limited transparency or reasoning flexibility. We present ADAGUARD, an adaptive LLM-as-a-Judge framework designed to address these challenges through dynamic policy enforcement and adaptive reasoning-budget allocation. Built using supervised fine-tuning (SFT) and reinforcement learning (GRPO), ADAGUARD generalizes to user-defined safety and compliance policies at runtime without requiring frequent model updates. A core innovation of our approach is the ability to dynamically infer the complexity of input-policy pairs, allowing the model to switch between high-speed black-box inference and explainable, reasoning-enabled moderation. This flexibility enables developers to balance stringent latency requirements with the need for actionable transparency. This *adaptive* capability allows ADAGUARD to rival other guardrail and frontier models several times its size, while its auto-reasoning mode recovers the accuracy of always-on reasoning at a fraction of the latency.

1 INTRODUCTION

The rapid advancement of Large Language Models (LLMs) and their adoption into autonomous agentic systems has fundamentally transformed the landscape of artificial intelligence. However, they have also introduced unprecedented safety risks and security vulnerabilities. As these models transition from simple text-generating entities to complex reasoning engines capable of planning and



Figure 1: ADAGUARD framework takes in a user input along with a list of policies, and generates a VIOLATION or COMPLIANCE verdict for each policy. ADAGUARD supports three reasoning modes: (1) `reasoning_off`: no reasoning for any policy, (2) `reasoning_on`: reasoning enforced for all policies, and (3) `autoreasoning`: reasoning conditioned on a self-predicted difficulty label.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

executing multiple tasks, the approaches adopted by the community to ensure their safety and policy compliance have also changed substantially. Traditional safety mechanisms, largely relying on static pattern matching or discriminative classifiers (Lees et al., 2022; Markov et al., 2023; Hanu & Unitary Team, 2020) have become inadequate for guarding against the nuanced adversarial intents, specifically in the context of "jailbreak" and "prompt injection" attacks (Wei et al., 2023; Greshake et al., 2023).

Our work is motivated by three limitations of current safeguards. First, a majority of existing guardrails commit to a *fixed safety taxonomy*: the classifier tools above (Lees et al., 2022; Markov et al., 2023; Hanu & Unitary Team, 2020) and their LLM-based successors such as Llama Guard (Inan et al., 2023) and WildGuard (Han et al., 2024) consider inputs against a pre-determined set of safety categories baked into the model weights. Real deployments, however, are governed by application-specific policies that may be revised at runtime. A recent line of runtime-policy guardrails, including DynaGuard (Hoover et al., 2025), GPT-OSS-Safeguard (OpenAI, 2025), Qwen3Guard (Zhao et al., 2025), and SingGuard (SingGuard Team, 2026), operate on free-form policies as inference-time input rather than during training. Second, many existing safeguards output purely discriminative accept/reject verdicts without explanation, making them difficult to audit and insufficient for compliance-sensitive industries. Reasoning-based safeguards such as GuardReasoner (Liu et al., 2025), together with the runtime-policy models that emit chain-of-thought (CoT) justifications (Hoover et al., 2025; OpenAI, 2025), address this by producing an explicit reasoning trace alongside the verdict. Third, this transparency comes at a cost: generating a CoT for every input inflates latency at inference time, yet most production traffic is unambiguous and does not require much deliberation. Therefore, a fixed reasoning budget is wasteful, spending tokens on trivial inputs while under-serving genuinely contentious ones. We provide a comprehensive discussion of related work, and how AdaGuard relates to prior guardrails, in Appendix A.1.

We developed AdaGuard (Figure 1) in response to these gaps. Like the runtime-policy safeguards above, it adjudicates each input against a *runtime-supplied* list of policies unseen during training and can emit a reasoning trace to justify each verdict. Its central contribution, however, is to route the reasoning budget *adaptively*: rather than reasoning on all policies (`reasoning_on`) or none (`reasoning_off`), its `autoreasoning` mode decides *for each policy within a single response* whether to reason, conditioned on the model's own inferred input–policy difficulty $\hat{d}_k$, so that the realized reasoning budget B (the number of policies actually reasoned about; Section 2) is spent where deliberation changes the verdict. SingGuard (SingGuard Team, 2026) is the closest prior attempt which introduced fast and slow modes with a decode-time confidence threshold that decides whether to provide deliberation per input. Unlike SingGuard's decode-time confidence gate, AdaGuard's reasoning allocation is a *trained, per-policy* behavior: it is learned jointly through reasoning-mode-conditioned supervised fine-tuning and a subsequent RL stage whose verifiable reward directly credits reasoning on inputs judged difficult and skipping it on easy inputs. Our main contributions are:

1. **An input-moderation formulation over runtime-supplied, free-form policies.** We cast guardrailing as judging each input x against a list of dynamic policies specified at runtime $P = (p_1, \ldots, p_K)$, emitting a per-policy verdict v_k optionally preceded by a reasoning trace r_k (Section 2.1). Because K and the content of each p_k vary per request rather than being drawn from a fixed taxonomy, AdaGuard generalizes zero-shot to policies unseen during training.
2. **A learned, per-policy adaptive reasoning-budget policy (`autoreasoning`).** Our central contribution is a trained behavior that decides, *for each policy k within a single response*, whether to emit a reasoning trace, conditioned on the model's own inferred difficulty $\hat{d}_k$ (Eq. 20). This spends the realized reasoning budget $B \leq K$ (Eq. 1) only where deliberation changes the verdict. Our claim is that `autoreasoning` matches `reasoning_on` accuracy at a budget $B \ll K$, and hence lower token cost and latency.

2 AdaGuard

2.1 Problem Definition

Let x denote a user input to be moderated and $P = (p_1, \ldots, p_K)$ an ordered, *runtime-supplied* list of K policies. For each pair (x, p_k), the guardrail π_θ must produce a verdict $v_k \in$

$\{\text{COMPLIANCE}, \text{VIOLATION}\}$, optionally preceded by a reasoning trace r_k. Unlike fixed-taxonomy guardrails, K and the content of each p_k may vary per request, so π_θ must generalize to policies *unseen* during training. Each pair also carries a latent difficulty $d_k \in \{\text{LOW}, \text{HIGH}\}$, estimated at data-generation time (Section 2.2), signifying whether adjudicating v_k is straightforward or warrants additional "thinking". This serves a proxy for *ambiguity* or *complexity* in the input, the policy, or both. A `Mode` field m in the prompt selects one of three reasoning modes: **minimum latency (** `reasoning_off` : emit v_k directly), **maximum transparency (** `reasoning_on` : emit full (r_k, v_k)), and **adaptive reasoning (** `autoreasoning` : emit (r_k, v_k) *only* where the model's own difficulty prediction $\hat{d}_k = \text{HIGH}$, else emit v_k alone). The full prompt template, including the exact per-mode output schema, is given in Appendix A.8.

`autoreasoning` is our central contribution. We quantify the *reasoning budget* as the number of policies for which CoT was written,

$$B(x, P, m) \;=\; \sum_{k=1}^{K} \mathbb{1}[\, r_k \neq \text{null} \,] \;\in\; [0, K], \tag{1}$$

so that `reasoning_off` $\Rightarrow B = 0$, `reasoning_on` $\Rightarrow B = K$, and `autoreasoning` chooses B *adaptively* per input. Our efficiency claim is that `autoreasoning` matches the *accuracy* of `reasoning_on` at a budget $B \ll K$: skipping reasoning on easy policies emits fewer tokens and lowers latency without sacrificing verdict quality.

2.2 CURATING THE TRAINING AND HELD-OUT DATASET

Our training data is synthesized from public safety datasets, transforming safety taxonomies into dynamic policy descriptions paired with reasoning traces, verdicts, and difficulty labels. We use a reflective, multi-agent generation-and-verification framework, in the spirit of synthetic instruction-data pipelines (Wang et al., 2023), complexity-evolving synthesis (Xu et al., 2023), and AI-feedback–based safety data generation (Bai et al., 2022; Rad et al., 2025). Each example is a tuple (x, P, D, R, V) in which P is a set of policy descriptions rather than fixed taxonomy labels, and D, R, V are the corresponding sequences of input–policy difficulty labels d_k, reference reasoning traces r_k, and ground-truth verdicts v_k.

The process involves five stages. *(1) Dynamic policy synthesis* treats every input category (or category–sub-category pair) in our open-source corpus as one policy *label* and expands it into several descriptions of that policy's scopes, requirements, and phrasings. These descriptions are sometimes deliberately non-overlapping. This is what lets us evaluate the trained model on descriptions it never sees verbatim during training, and is the basis of our zero-shot dynamic-policy generalization claim. *(2) Input–policy matching* pairs each input x with a scope-diverse subset of the descriptions generated for its own label(s), plus a selection drawn from others, forming P. *(3) Reasoning and difficulty generation* produces the three CoT components of r_k and the verdict v_k with a generator–evaluator pair, and independently estimates d_k from the verdict-agreement rate of a three-model sampling ensemble. *(4) Refiner* prunes the matched pool toward per-split target distributions. *(5) Held-out construction* repeats (1)–(3) on a reserved, disjoint slice of input categories. Generation objectives, generator/evaluator prompts, and rubrics for all stages are in Appendix A.5; per-split, per-category composition is in Appendix A.4.

Difficulty-Stratified Splits and Data Curation. The matched pool is partitioned into two sets for our multi-staged training pipeline: a Supervised Fine-Tuning (SFT) (Pareja et al., 2024) pool and a Reinforcement Learning pool (GRPO), each curated independently toward their own targets. The partition is deliberately *difficulty-stratified*: the GRPO pool is assembled with a higher target difficulty ratio and a larger mean matched-policy count (0.16 vs. 0.14 and $K = 6.3$ vs. 5.1; Table 6), so SFT establishes the output format and base reasoning behavior on tractable examples while GRPO refines the harder, higher-K regime where adaptive reasoning matters most. Balance within each pool is enforced by a policy-distribution refiner that uses the verdict v_k and difficulty d_k *jointly*, compares four nested empirical distributions against target Gaussians under a specified Wasserstein distance (Panaretos & Zemel, 2019), and *prunes* policy blocks matched to each input query until each is within a given tolerance: per-input violation ratio (L1), per-input difficulty ratio (L2), the within-verdict difficulty gap (L3), and the per-category version of all three (L4). Pruning only ever removes (x, p_k) pairs or whole inputs (full hierarchy, two-stage schedule, and targets in Appendix A.6).

The Held-Out Set. The held-out dynamic-policy test set is disjoint from training *by construction* rather than by post-hoc filtering: 20 input categories are reserved *before* policy synthesis and matching are run, so no policy description written for a held-out category can reach the training pool (Appendix A.4, Tables 6 and 7). Held-out inputs then pass through the same reasoning and difficulty-estimation stages, so every test pair carries a reference v_k and d_k exactly like a training example. We validated the quality of the generated verdicts and reasoning traces via human annotations, as reported in Appendix A.3. For more detailed information on held-out test set curation, see Appendix A.4.

2.3 Model Training

2.3.1 Supervised Fine-Tuning (SFT)

To warm up π_θ, the first training stage is SFT. Each SFT example is expanded into three training rows, one per reasoning mode, with completions derived from the (r_k, v_k) synthetic generations: **`reasoning_off`** retains only the verdict v_k, **`reasoning_on`** adds all reasoning components across all policies, and **`autoreasoning`** retains reasoning only for policies with HIGH teacher difficulty label (d_k). All completions use a similar JSON schema (Appendix A.10): a top-level `input_understanding` field (η, dissecting the input), then per policy ordered fields `policy_understanding` (ψ_k, the policy's scopes in isolation), `input_compliance_understanding` (χ_k, resolving compliance from η and ψ_k), and `answer` (v_k); `autoreasoning` additionally emits a per-policy `difficulty` field ($\hat{d}_k$) and suppresses ψ_k, χ_k when $\hat{d}_k$ is predicted to be LOW. We fine-tune with an Unsloth-based trainer (Han et al., 2023) using the Dynamic Fine-Tuning (DFT) loss, which reweights the per-token cross-entropy for improved reasoning stability (Wu et al., 2026). The base models are open-weight, instruction-tuned backbones spanning different families and scales (Section 3), and SFT is applied identically to each (see settings in Appendix A.2).

2.3.2 GRPO Reward Design

Following SFT, we fine-tune π_θ with Group Relative Policy Optimization (GRPO) (Shao et al., 2024). The goal is for π_θ to better grasp paying attention to the policy descriptions when judging verdicts, effective reasoning, and *when* to reason. Each rollout o in a group $\{o_j\}_{j=1}^{G}$ is parsed into K per-policy blocks, from which we extract a normalized verdict $\hat{v}_k \in \{\text{COMPLIANCE}, \text{VIOLATION}\}$, a predicted difficulty $\hat{d}_k \in \{\text{HIGH}, \text{LOW}\}$, and two CoT-presence indicators a_k (*any* CoT) and f_k (*full* CoT), defined in Appendix A.10 (Eq. 9). The rollout is scored by a reward vector $\mathbf{R}(x, P, o; m) = (R_{\text{format}}, R_{\text{correct}}, R_{\text{reason}})$, with a reasoning-quality judge score folded multiplicatively into R_{correct} rather than an additional stream:

$$\mathbf{R}(x, P, o; m) \;=\; \big(R_{\text{format}},\; R_{\text{correct}},\; R_{\text{reason}}\big), \qquad R_{\text{correct}} = \tfrac{1}{K}\textstyle\sum_k r_c(k), \quad R_{\text{reason}} = \tfrac{1}{K}\textstyle\sum_k \phi_k, \tag{2}$$

where R_{correct} and R_{reason} are *means* over the K blocks, so all components live on a comparable per-block scale.

Group Reward-Decoupled Normalization (GDPO). The components of Eq. 2 differ in scale, variance, and firing rate, so collapsing them into a single entangled scalar and group-normalizing it, as in the standard GRPO advantage, lets whichever component carries the largest within-group variance dominate the update. We therefore adopt GDPO (Liu et al., 2026), which normalizes each reward stream independently within its own GRPO group before combining them, followed by a batch-level normalization that keeps the aggregated advantage on a consistent scale regardless of the number of reward functions. This way every component casts an equal-variance "vote" regardless of raw magnitude, so a batch in which format scores happen to vary more than verdict correctness cannot let formatting overwhelm the correctness signal as an artifact of scale. The full normalization equations, the GDPO training objective, and the complete procedure are given in Appendix A.10 (Algorithm 1, Eq. 7).

Format and Reasoning-Decision Rewards. R_{format} owns all schema and formatting signals: it hard-gates unparseable, zero-coverage, excess-block, and excessively verbose rollouts to `PARSE_PENALTY`, and otherwise additively combines multiple sub-components: a step-linear *verdict-coverage* curve g_{cv}, an extra-schema "babble" term $\tilde{g}_{\text{bab}}$, and pure-penalty block-count and

numbering terms $g_{\text{blk}}, g_{\text{num}}$:

$$R_{\text{format}} = w_{cv}\, g_{\text{cv}} + w_{bab}\, \tilde{g}_{\text{bab}} + w_{blk}\, g_{\text{blk}} + w_{num}\, g_{\text{num}}. \tag{3}$$

Only g_{cv} and $\tilde{g}_{\text{bab}}$ can be positive, so the rest only serve as penalties; difficulty tags are deliberately *not* scored here and are owned by R_{reason}. The specific scalar values act as reward-shaping hyperparameters that enforce an asymmetric risk profile: incorrectly skipping reasoning on a hard policy is penalized more strictly than safely but wastefully reasoning on an easy one. $R_{\text{reason}} = \frac{1}{K}\sum_k \phi_k$ grades *only* whether the reason/skip decision matched the mode (verdict correctness is owned by R_{correct}, so the two are never double-counted), and in the adaptive mode ties that decision (the per-policy term ϕ_k^{auto}) to the model's own predicted difficulty, with the teacher label d_k entering solely as a floor on skipped-but-hard pairs:

$$\phi_k^{\text{auto}} = \begin{cases} +1, & \hat{d}_k = \textsc{High} \wedge f_k, \\ -1, & \hat{d}_k = \textsc{Low} \wedge a_k, \\ -1.5, & \hat{d}_k = \textsc{Low} \wedge \neg a_k \wedge d_k = \textsc{High}, \\ +1, & \hat{d}_k = \textsc{Low} \wedge \neg a_k \wedge d_k = \textsc{Low}. \end{cases} \tag{4}$$

Overall, the ϕ_k^{auto} cells reward committing to full CoT exactly when the model declares a policy HIGH and skipping when it declares LOW, which is what makes the budget B adaptive. Format sub-scores and gate conditions, the partial-CoT and malformed-tag cells, and the fixed-mode variants $\phi_k^{\text{off}}, \phi_k^{\text{on}}$ are all in Appendix A.10 (Eqs. 10–20).

Overall, the ϕ_k^{auto} cells reward committing to full CoT exactly when the model declares a policy HIGH and skipping when it declares LOW, which is what makes the budget B adaptive. This is an abridged form; the full seven-case definition, adding the malformed-tag, partial-CoT, and reasoned-despite-skipping cells, is Eq. 20 in Appendix A.10. Format sub-scores and gate conditions and the fixed-mode variants $\phi_k^{\text{off}}, \phi_k^{\text{on}}$ are all in Appendix A.10 (Eqs. 10–20).

Counterfactual Correctness (`CF_Corr`). R_{correct} is the only reward component affected by the verdicts. In `autoreasoning`, a flat correct/wrong score has only two values for every reasoned block, so it cannot separate reasoning that *fixed* a genuinely hard case, reasoning that was harmlessly *redundant*, and one that actively *introduced* an error the model would not otherwise have made. These, in turn, have three qualitatively different effects on reward shaping. We recover the distinction by measuring the *marginal value of reasoning* directly: on each block where the model committed to reasoning ($\hat{d}_k = \textsc{High} \wedge a_k$) we additionally sample an independent `reasoning_off` completion of the identical (x, p_k) pair under matched decoding parameters (as a proxy of the behavior in $\hat{d}_k = \textsc{Low}$), giving a *counterfactual verdict* $\hat{v}_k^{\text{off}}$. With $\text{High}_k = \mathbb{1}[\hat{v}_k = v_k]$ and $\text{Low}_k = \mathbb{1}[\hat{v}_k^{\text{off}} = v_k]$, the landscape changes as follows:

$$r_c(k) = \begin{cases} C_{\text{corr}} + C_{\text{flip}} = +1.5, & \text{High}{=}1,\ \text{Low}{=}0\ \ (\textit{flip}), \\ C_{\text{broke}} = -1.25, & \text{High}{=}0,\ \text{Low}{=}1\ \ (\textit{broke}), \\ C_{\text{both_wrong}} = -0.75, & \text{High}{=}0,\ \text{Low}{=}0\ \ (\textit{wrong-both}), \\ C_{\text{cor}} = +1.0, & \text{High}{=}\text{Low}{=}1,\ d_k = \textsc{High}\ \ (\textit{unnecessary}), \\ C_{\text{cor}} - C_{\text{unnec}} = +0.8, & \text{High}{=}\text{Low}{=}1,\ d_k = \textsc{Low}\ \ (\textit{unnecessary}). \end{cases} \tag{5}$$

These scalars establish a strict preference hierarchy for the marginal value of reasoning. A *flip* means reasoning corrected a wrong no-CoT verdict (earning the maximum $+1.5$); *broke* means it reversed a correct one (the heaviest penalty of -1.25, as actively introducing an error is punished more than consistent failure); *unnecessary* means the verdict was right either way. Only the unnecessary cell is split by d_k, which supplies both a floor and a cap from one signal: unnecessary reasoning on a teacher-hard pair is never discounted, while it is mildly discounted on a teacher-easy pair, so the branch's average value *declines* as reasoning becomes indiscriminate. This design is deliberate to encourage the model to take the penalty risk associated with reasoning, but to caution it against generating CoT for easy examples. The flip cell, however, is intentionally unconditioned on d_k: the counterfactual was observably wrong, so reasoning was demonstrably necessary there regardless of any external label. Predicted-LOW blocks and blocks with no counterfactual keep the standard score (Appendix A.10, Eq. 15). Unlike confidence-based calibration, which uses the actor's own probability at a decision token and collapses to a near-constant offset when that distribution is saturated, this criterion has no degenerate limit: whether a verdict is correct *with* reasoning but not *without* it stays a live binary fact however peaked the model's probabilities are.

Table 1: Per-example F1 (%) on static safety benchmarks and our held-out dynamic-policy test set, with per-example efficiency (average latency, output tokens, decoding speed) and Static / All-Tasks F1 averages. All evaluations are conducted on 4 A100 GPUs. We report example-level scores since baseline models typically output aggregate compliance verdicts across all policies for a given input. For frontier models, we use their default reasoning modes and prompt them to follow our `reasoning_off` format. For our ADAGUARD model, we calibrate across the three reasoning modes. Bold = best per column, underline = second best (Output tokens is descriptive and not ranked).

Model	Aegis 2.0	Harm-Bench	Wild-Guard	Sorry-Bench	XS-Test	Dynamic-Policy (Ours)	Avg Latency (s)	Output Tokens	Tokens / sec	Static Avg	All-Tasks Avg
Open-source Guardrails											
WildGuard-7b	83.0	86.0	74.2	58.2	93.2	77.5	1.44	20.7	14.4	78.9	78.7
LlamaGuard-3-8b	71.8	84.2	69.9	59.1	88.8	73.7	**0.83**	3.4	4.1	74.8	74.6
ShieldGemma-9b	73.7	44.1	41.6	39.0	60.2	71.2	1.32	1.0	0.8	51.7	55.0
DynaGuard-8b (no CoT)	78.9	87.1	79.3	86.5	88.2	79.6	2.34	57.7	24.7	84.0	83.3
DynaGuard-8b (with CoT)	80.5	87.0	80.8	86.2	89.6	79.4	6.73	150.5	22.4	84.8	83.9
SafeGuard-20b (low)	**85.1**	**100.0**	**87.4**	94.1	89.4	86.7	8.12	198.8	24.5	**91.2**	**90.5**
SafeGuard-20b (medium)	83.7	**100.0**	86.0	93.8	89.6	86.6	22.12	570.1	25.8	90.6	90.0
SafeGuard-20b (high)	73.9	96.0	77.4	83.9	83.0	77.7	62.97	1599.7	25.4	82.8	82.0
Frontier LLMs											
GPT-oss-20b	84.0	99.0	76.9	89.8	88.8	85.9	17.08	440.0	25.8	87.7	87.4
Gemma-4-26b	83.8	99.8	85.0	90.1	**94.5**	**88.8**	3.91	120.8	30.9	90.6	90.3
AdaGuard Gemma4-E4B											
`reasoning-off`	84.4	**100.0**	84.6	92.9	87.3	86.6	2.64	116.2	44.0	89.8	89.3
`reasoning-on`	83.4	99.0	86.3	89.6	91.7	88.2	11.55	1069.1	**92.6**	90.0	89.7
`auto-reasoning`	84.6	99.8	83.6	**95.8**	90.0	88.2	7.45	669.1	89.8	90.8	90.3

Reasoning Quality Multiplier and the Unnecessary-Reasoning Clamp. Each reasoned trace is rated by an LLM judge on a $Q \in [1, 5]$ scale across multiple reasoning-component-specific set of rubrics (Appendix A.9). Rather than adding Q as a separate GDPO term, we make it a *coefficient on* r_c, so the reward can express "correct because the reasoning was sound" as distinct from "correct despite unsound reasoning." The magnitude is piecewise about the rubric midpoint $Q = 3$, so that $m(3) = 1$, $m(5) = 1 + R$, and $m(1) = 1 - R$ all hold exactly (default $R = 0.5$); application is *sign-aware* and conditioned on whether the block landed in CF-Corr's unnecessary cell, $u = \mathbb{1}[\text{unnecessary}]$ against the pre-multiplier value r_c:

$$m(Q) = \begin{cases} 1 + R\dfrac{Q-3}{2}, & Q \geq 3, \\ 1 - R\dfrac{3-Q}{2}, & Q < 3, \end{cases} \qquad \text{mult}(r_c, Q, u) = \begin{cases} m(Q), & r_c > 0,\ u = 0, \\ \min\big(m(Q), 1.0\big), & r_c > 0,\ u = 1, \\ \max\big(2 - m(Q), 1.0\big), & r_c < 0, \\ 1.0, & r_c = 0. \end{cases} \tag{6}$$

The block's final score is $r_c \cdot \text{mult}(r_c, Q, u)$, applied only on judged blocks. It is worth noting that both clamps close a distinct reward-hacking pathway. On the wrong side, an unclamped mirror $2 - m(Q) < 1$ (i.e. above-mediocre reasoning) would *soften* a wrong verdict because it reads well; the $\max$ leaves it unchanged instead. On the correct side the $u{=}1$ clamp closes *unnecessary-reasoning amplification*: a well-written but unwarranted CoT can still score well on the rubric (clean writing does *not* equate reasoning being *needed*), so an unclamped $m(Q)$ would lift the discounted unnecessary cells up to $0.8 \times 1.5 = 1.2$ and $1.0 \times 1.5 = 1.5$, both *above* the $+1.0$ of a correctly-skipped predicted-LOW block, which receives no multiplier at all because it produces no trace to judge. That ordering would reward reasoning-when-unnecessary over correctly skipping, inverting the intent of C_{unnec}. Under $\min(m(Q), 1.0)$ the cell can only shrink from its already-discounted base, so no level of reasoning quality lets an unneeded CoT outscore a correct skip; Appendix A.10 (Table 8) tabulates every scenario and verifies the invariant.

3 EXPERIMENTAL RESULTS

We experimented with two open-weight instruction-tuned models: Llama 3.1 Nemotron Nano 4B (Bercovich et al., 2025) and Gemma4-E4B (Team et al., 2026). We deliberately targeted smaller sized models since, in production settings, guardrails are expected to operate under stringent latency



Figure 2: `autoreasoning` behavior in GRPO training on the dynamic-policy validation set, for (left) Gemma4-E4B and (right) Nemotron-Nano-4B. Each panel plots the fraction of policies the model chooses to reason on, and the percentage of the *reasoned* blocks in `autoreasoning` where the model fixes an incorrect counterfactual verdict (*Fixed*) versus turns a correct one wrong (*Broke*). Fixed exceeds Broke throughout in both models, so reasoning is net-positive at the verdict level.

requirements. Also, most of the other models we benchmark against are within the same parameter size. We start with SFT (Section 2.3.1) for one epoch, followed up with GRPO (Section 2.3.2). For hyperparameter and training setting details, see Appendix A.2. The R_{quality} judge (Section 2.3.2) is GPT-OSS-120B (OpenAI, 2025).

Baselines. We compare against other open-source guardrail models fine-tuned for moderation, including WildGuard (Han et al., 2024), LlamaGuard3 (Inan et al., 2023), ShieldGemma (Zeng et al., 2024), gpt-oss-safeguard (OpenAI, 2025), and DynaGuard (Hoover et al., 2025), as well as LLMs with no guardrail-specific fine-tuning, GPT-OSS-20B (OpenAI, 2025) and Gemma-4-26B-it (Team et al., 2026; Google DeepMind, 2026).

Benchmarks and Metrics. We evaluate different AdaGuard checkpoints in all three reasoning modes as input moderators on the following datasets: **(a) static safety benchmarks**, including Aegis 2.0 (Ghosh et al., 2025), HarmBench (Mazeika et al., 2024), Safe-RLHF (Dai et al., 2024), WildGuard (Test) (Han et al., 2024), WildJailbreak (Jiang et al., 2024), SorryBench (Xie et al., 2025), and XS-Test (Röttger et al., 2024); **(b) dynamic-policy benchmarks**, which is our held-out dynamic-policy test set, constructed as described in Section 2.2. The primary metrics reported are per-example *macro* F1 (verdict Violation if any policy k in an (x, P) example is a violation, otherwise Compliance), as well as per-policy F1 scores.

Table 1 presents our key results using the Gemma4-E4B backbone, where AdaGuard is broadly competitive across all tasks. On aggregate All-Tasks F1, SafeGuard-20B edges us and Gemma-4-26B matches us (90.5 and 90.3 vs. our 90.3 in `autoreasoning`), but the comparison is not size-matched: AdaGuard is a *dense* 4B model against 20–26B mixture-of-experts baselines, so the gap is one of *memory footprint and serving cost*, not per-token compute. At the token level, AdaGuard is in fact the most efficient generator in the table, decoding at 44–93 tokens/s versus

Table 2: **Training-stage ablation** in `autoreasoning`, for Gemma4-E4B and Nemotron-Nano-4B on the dynamic-policy test set. Per-policy F1 is reported per stage. Autoreasoning Rate is the fraction of policies the model reasons for.

	Gemma4-E4B		**Nemotron-Nano-4B**	
Stage	F1 Score	Autoreasoning Rate	F1 Score	Autoreasoning Rate
Base	74.76	21.9	26.75	56.23
SFT	76.51	0.42	46.31	0
GRPO	**80.1**	31.81	**64.52**	36.32



Figure 3: Reward-feature ablation on Gemma4-E4B. *Left:* `autoreasoning` reasoning rate during GRPO (validation); the CF_Corr-off variants (Quality Only, Vanilla) collapse to $\sim$100% while CF_Corr-enabled ones stay selective. *Right:* held-out per-policy F1 vs. reasoning rate at epoch 1; CF_Corr alone prunes hardest but scores lowest, and adding the quality judge restores always-reasoning F1 at a rate near a third.

24–31 for the larger models – its higher `reasoning_on` latency reflects emitting more tokens, not slower decoding. `autoreasoning` exploits this, cutting output tokens by about a third relative to `reasoning_on` (669 vs. 1069) at lower latency (7.45s vs. 11.55s) while retaining accuracy (All-Tasks 90.3, matching Gemma-4-26B and within 0.2 points of SafeGuard-20B). Operating on runtime policies rather than a fixed taxonomy, AdaGuard also leads every *dedicated guardrail* baseline on the dynamic-policy split (88.2, behind only the far larger Gemma-4-26B at 88.8)—and does so as a dense 4B model, giving it the best accuracy-per-parameter and most deployable footprint of the models compared. Its smaller size also makes training cheaper and faster than the larger baselines.

Reasoning-Rate Analysis for `autoreasoning` during GRPO Training. Figure 2 shows the fraction of policies each model chooses to reason on during GRPO. Both learn a genuinely selective policy: reasoning onsets partway through training (earlier for Gemma4-E4B) and then calibrates downward, with Gemma4-E4B peaking at $\sim$56% and settling near 50%, and Nemotron-Nano-4B peaking at $\sim$76% before settling near 43%. Driven by the CF_Corr reward, which discourages reasoning on teacher-easy examples, this shows `autoreasoning` decides *when* to reason rather than reasoning on everything. The counterfactual traces confirm the decision is beneficial: the fraction of policies whose verdict reasoning flips from wrong to correct (Fixed) exceeds those it flips from correct to wrong (Broke) at almost all steps, ending near 23% vs. 17% for Gemma4-E4B and 20% vs. 18% for Nemotron-Nano-4B, so reasoning improves verdicts on net.

Counterfactual and Reasoning Quality Judge Ablations. We ablate the two reward features—the counterfactual reasoning-value term CF_Corr (Appendix A.10) and the quality-multiplier judge (Section 2.3.2)—on a shared Gemma4-E4B SFT checkpoint, GRPO training set, and hyperparameters, reporting held-out per-policy F1 at GRPO epoch 1 alongside the reasoning rate on the autoreasoning examples. Besides the full model (both features), we compare three configurations: (1) CF only, (2) Quality only, and (3) Vanilla (neither).

As Figure 3 shows, CF_Corr is what keeps `autoreasoning` adaptive: without it the reasoning rate collapses to $\sim$100% by step $\sim$60 and never tapers, degenerating into forced `reasoning_on`, whereas with it the rate stays controlled (25% with CF_Corr alone, 37% with the quality judge added). All four variants land within two points of per-policy F1, but at very different reasoning rates: the two CF_Corr-off variants reach $\sim$80 F1 *only* by collapsing to `reasoning_on`, forfeiting adaptivity. Among the selective variants, CF_Corr alone is weakest at 78.1 (a 25% rate), while adding the quality judge lifts F1 to 80.0 (+1.8) at a 37% rate—matching the always-reasoning accuracy while reasoning on about a third of the policies. In short, CF_Corr supplies the reasoning economy and the quality judge keeps it from costing accuracy.



Figure 4: **Per-policy F1, easy vs. hard teacher splits**, by stage (Base / SFT / GRPO) and mode, for **(left)** Gemma4-E4B and **(right)** Nemotron-Nano-4B. Base/SFT use forced `reasoning_off` / `reasoning_on`; GRPO uses `autoreasoning`. Easy F1 is near-flat, so the hard split separates stages and modes.

Training-Stage Ablations. Table 2 ablates the three stages (Base, SFT, GRPO) in `autoreasoning` for both backbones. Held-out per-policy F1 improves monotonically at every stage—$74.8 \rightarrow 76.5 \rightarrow 80.1$ for Gemma4-E4B and $26.8 \rightarrow 46.3 \rightarrow 64.5$ for Nemotron-Nano-4B—with GRPO best in every case. The reasoning rate, however, is non-monotonic: the base checkpoints already reason on 21.9% / 56.2% of blocks, SFT collapses this to essentially zero (0.4% / 0%) as the model learns to emit direct verdicts, and only GRPO restores a *selective* policy (31.8% / 36.3%). GRPO thus delivers both the largest accuracy gains and the adaptive-reasoning behavior, whereas SFT alone buys accuracy at the cost of reasoning at all.

Difficulty-level Analysis. Figure 4 breaks per-policy F1 down by teacher difficulty. On *easy* policies performance is high and largely flat across modes and stages (Gemma4-E4B stays in the 85–90 range; Nemotron-Nano-4B (trained with SFT and GRPO) near 75–77), so the *hard* split is where the differences reside. Turning reasoning on lifts F1 on hard examples substantially for trained models - $+7$–9 points for Gemma4-E4B at both the Base and SFT stages, and $+23.1$ for Nemotron-Nano-4B after SFT and GRPO ($21.8 \rightarrow 44.9$). Therefore, training unlocks reasoning's value: SFT and then GRPO turn reasoning into a substantial gain on hard inputs. Critically, the GRPO `autoreasoning` checkpoints attain comparable F1 scores on hard inputs compared to `reasoning_on` in both models (63.5 for Gemma4-E4B, 44.8 for Nemotron-Nano-4B), while also topping the easy split (90.0 / 77.0), and reasoning on only a fraction of policies. Thus, `autoreasoning` closes the difficulty gap without paying the full `reasoning_on` cost.

4 Conclusion and Future Work

We introduced AdaGuard, an input-moderation LLM-as-a-Judge guardrail that judges an input against a runtime-supplied, free-form policy list $P = (p_1, \ldots, p_K)$, trained with a two-stage recipe of supervised fine-tuning across the `reasoning_off`, `reasoning_on`, and `autoreasoning` modes followed by GRPO. Its central mechanism, `autoreasoning`, learns to decide for each policy whether to emit a reasoning trace, conditioned on the model's own predicted difficulty $\hat{d}_k$, so the reasoning budget B is spent where deliberation is likely to change the verdict rather than uniformly across all K policies. A number of limitations remain and point to future work. The adaptive-reasoning mechanism is only as reliable as the synthesized policies and reference traces that supervise it, and we have not fully stress-tested robustness to adversarially malformed or poorly-specified runtime policies. Further, the reasoning-quality reward relies on an LLM-as-judge (GPT-OSS-120B) that carries its own stylistic and content biases and adds inference cost during training. Finally, our held-out dynamic-policy test set, though disjoint by construction, is produced by the same synthetic pipeline as training rather than collected from a live deployment. Evaluating AdaGuard against policies drawn from deployment, rather than synthesized ones, is therefore a natural next step.

AI USE STATEMENT

We used generative AI tools in this work to generate the synthetic dynamic-policy training and evaluation data (Section 2.2), to find relevant literature, to assist in writing and debugging the code for our data pipeline and training experiments, and to polish the writing of this paper for readability. We did not use generative AI for other common research activities, such as formulating the core research ideas, methodology, or claims. All AI-assisted outputs were reviewed by the authors, and we verified all cited references for accuracy. We take full responsibility for the final content of this work.

ETHICS STATEMENT

AdaGuard is developed strictly as a defensive guardrail framework to enhance safety and dynamically enforce policy compliance across enterprise applications based on Large Language Models (LLMs). We recognize the dual-use risks associated with emitting explicit reasoning traces, as adversarial actors could potentially analyze these decision justifications to audit model guardrail boundaries or refine jailbreak techniques. Hence, we recommend rigorous evaluations before deployment and regular monitoring during deployment for any undesirable behaviors from models developed based on this work. To ensure ethical data governance, all datasets were constructed from public sources containing no Personally Identifiable Information (PII). Further, all datasets and models used in this work were employed in accordance with their respective licensing constraints.

REPRODUCIBILITY STATEMENT

The training-data construction pipeline is described in Section 2.2, with generation prompts and rubrics in Appendix A.5, dataset composition in Appendix A.4, and the refiner configuration in Appendix A.6. The held-out test set and the human-annotation study validating it are detailed in Appendices A.4 and A.3. Our two-stage recipe (SFT in Section 2.3.1, GRPO in Section 2.3.2) is specified in Section 2.3, with the full reward formulation in Appendix A.10 and all hyperparameters in Appendix A.2. The experimental setup, baselines, and metrics appear in Section 3. We also plan to release the constructed dynamic-policy dataset and associated code recipe upon acceptance.

REFERENCES

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, et al. Constitutional ai: Harmlessness from ai feedback, 2022. URL https://arxiv.org/abs/2212.08073.

Akhiad Bercovich, Itay Levy, Izik Golan, Mohammad Dabbah, Ran El-Yaniv, Omri Puny, Ido Galil, Zach Moshe, Tomer Ronen, Najeeb Nabwani, Ido Shahaf, Oren Tropp, Ehud Karpas, Ran Zilberstein, Jiaqi Zeng, Soumye Singhal, Alexander Bukharin, Yian Zhang, Tugrul Konuk, Gerald Shen, Ameya Sunil Mahabaleshwarkar, Bilal Kartal, Yoshi Suhara, Olivier Delalleau, Zijia Chen, Zhilin Wang, David Mosallanezhad, Adi Renduchintala, Haifeng Qian, Dima Rekesh, Fei Jia, Somshubra Majumdar, Vahid Noroozi, Wasi Uddin Ahmad, Sean Narenthiran, Aleksander Ficek, Mehrzad Samadi, Jocelyn Huang, Siddhartha Jain, Igor Gitman, Ivan Moshkov, Wei Du, Shubham Toshniwal, George Armstrong, Branislav Kisacanin, Matvei Novikov, Daria Gitman, Evelina Bakhturina, Prasoon Varshney, Makesh Narsimhan, Jane Polak Scowcroft, John Kamalu, Dan Su, Kezhi Kong, Markus Kliegl, Rabeeh Karimi Mahabadi, Ying Lin, Sanjeev Satheesh, Jupinder Parmar, Pritam Gundecha, Brandon Norick, Joseph Jennings, Shrimai Prabhumoye, Syeda Nahida Akter, Mostofa Patwary, Abhinav Khattar, Deepak Narayanan, Roger Waleffe, Jimmy Zhang, Bor-Yiing Su, Guyue Huang, Terry Kong, Parth Chadha, Sahil Jain, Christine Harvey, Elad Segal, Jining Huang, Sergey Kashirsky, Robert McQueen, Izzy Putterman, George Lam, Arun Venkatesan, Sherry Wu, Vinh Nguyen, Manoj Kilaru, Andrew Wang, Anna Warno, Abhilash Somasamudramath, Sandip Bhaskar, Maka Dong, Nave Assaf, Shahar Mor, Omer Ullman Argov, Scot Junkin, Oleksandr Romanenko, Pedro Larroy, Monika Katariya, Marco Rovinelli, Viji Balas, Nicholas Edelman, Anahita Bhiwandiwalla, Muthu Subramaniam, Smita Ithape, Karthik Ramamoorthy, Yuting Wu, Suguna Varshini Velury, Omri Almog, Joyjit Daw, Denys Fridman,

Erick Galinkin, Michael Evans, Shaona Ghosh, Katherine Luna, Leon Derczynski, Nikki Pope, Eileen Long, Seth Schneider, Guillermo Siman, Tomasz Grzegorzek, Pablo Ribalta, Monika Katariya, Chris Alexiuk, Joey Conway, Trisha Saar, Ann Guan, Krzysztof Pawelec, Shyamala Prayaga, Oleksii Kuchaiev, Boris Ginsburg, Oluwatobi Olabiyi, Kari Briski, Jonathan Cohen, Bryan Catanzaro, Jonah Alben, Yonatan Geifman, and Eric Chung. Llama-nemotron: Efficient reasoning models, 2025. URL https://arxiv.org/abs/2505.00949.

Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46, 1960. doi: 10.1177/001316446002000104.

Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. Safe RLHF: Safe reinforcement learning from human feedback. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL https://openreview.net/forum?id=TyFrPOKYXw.

Yi Dong, Ronghui Mu, Gaojie Jin, Yi Qi, Jinwei Hu, Xingyu Zhao, Jie Meng, Wenjie Ruan, and Xiaowei Huang. Building guardrails for large language models, 2024. URL https://arxiv.org/abs/2402.01822.

Gongfan Fang, Xinyin Ma, and Xinchao Wang. Thinkless: Llm learns when to think, 2025. URL https://arxiv.org/abs/2505.13379.

Shaona Ghosh, Prasoon Varshney, Makesh Narsimhan Sreedhar, Aishwarya Padmakumar, Traian Rebedea, Jibin Rajan Varghese, and Christopher Parisien. Aegis2.0: A diverse ai safety dataset and risks taxonomy for alignment of llm guardrails, 2025. URL https://arxiv.org/abs/2501.09004.

Google DeepMind. Gemma 4 31b instruction-tuned model card. https://huggingface.co/google/gemma-4-31B-it, 2026.

Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world llm-integrated applications with indirect prompt injection, 2023. URL https://arxiv.org/abs/2302.12173.

K. Gwet and P. Gwet. *Handbook of Inter-Rater Reliability: How to Measure the Level of Agreement Between 2 Or Multiple Raters*. STATAXIS Publishing Company, 2001. ISBN 9780970806208. URL https://books.google.com/books?id=V19NAAAACAAJ.

Daniel Han, Michael Han, and Unsloth team. Unsloth: Faster and memory-efficient llm fine-tuning. https://github.com/unslothai/unsloth, 2023.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. Wildguard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of LLMs. In *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2024. URL https://openreview.net/forum?id=Ich4tv4202.

Laura Hanu and Unitary Team. Detoxify: Open source python library for toxic comment classification. https://github.com/unitaryai/detoxify, 2020.

Monte Hoover, Vatsal Baherwani, Neel Jain, Khalid Saifullah, Joseph Vincent, Chirag Jain, Melissa Kazemi Rad, C. Bayan Bruss, Ashwinee Panda, and Tom Goldstein. Dynaguard: A dynamic guardian model with user-defined policies, 2025. URL https://arxiv.org/abs/2509.02563.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. Llama guard: Llm-based input-output safeguard for human-ai conversations. *arXiv preprint arXiv:2312.06674*, 2023. doi: 10.48550/arxiv.2312.06674.

Liwei Jiang, Kavel Rao, Seungju Han, Allyson Ettinger, Faeze Brahman, Sachin Kumar, Niloofar Mireshghallah, Ximing Lu, Maarten Sap, Yejin Choi, and Nouha Dziri. Wildteaming at scale: From in-the-wild jailbreaks to (adversarially) safer language models. *arXiv preprint arXiv:2406.18510*, 2024. doi: 10.48550/arXiv.2406.18510.

Taeyoun Kim, Fahim Tajwar, Aditi Raghunathan, and Aviral Kumar. Reasoning as an adaptive defense for safety, 2025. URL https://arxiv.org/abs/2507.00971.

Alyssa Lees, Vinh Q. Tran, Yi Tay, Jeffrey Sorensen, Jai Gupta, Donald Metzler, and Lucy Vasserman. A new generation of perspective api: Efficient multilingual character-level transformers. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 3197–3207. ACM, 2022. doi: 10.1145/3534678.3539147.

Shih-Yang Liu, Xin Dong, Ximing Lu, Shizhe Diao, Peter Belcak, Mingjie Liu, Min-Hung Chen, Hongxu Yin, Yu-Chiang Frank Wang, Kwang-Ting Cheng, Yejin Choi, Jan Kautz, and Pavlo Molchanov. Gdpo: Group reward-decoupled normalization policy optimization for multi-reward rl optimization, 2026. URL https://arxiv.org/abs/2601.05242.

Yue Liu, Hongcheng Gao, Shengfang Zhai, Jun Xia, Zhengyu Hu, Tianyi Wu, Zhiwei Xue, Yulin Chen, Kenji Kawaguchi, Jiaheng Zhang, and Bryan Hooi. Guardreasoner: Towards reasoning-based llm safeguards. *ArXiv*, abs/2501.18492, 2025. URL https://api.semanticscholar.org/CorpusID:275993698.

Todor Markov, Chong Zhang, Sandhini Agarwal, Tyna Eloundou, Teddy Lee, Steven Adler, Angela Jiang, and Lilian Weng. A holistic approach to undesired content detection in the real world. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pp. 15009–15018, 2023. doi: 10.48550/arXiv.2208.03274.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal, 2024. URL https://arxiv.org/abs/2402.04249.

James O' Neill, Santhosh Subramanian, Eric Lin, Abishek Satish, and Vaikkunth Mugunthan. Guardformer: Guardrail instruction pretraining for efficient safeguarding. In *Neurips Safe Generative AI Workshop 2024*, 2024. URL https://openreview.net/forum?id=vr31i9pzQk.

OpenAI. gpt-oss-120b & gpt-oss-20b model card, 2025. URL https://arxiv.org/abs/2508.10925.

OpenAI. gpt-oss-safeguard. https://huggingface.co/openai/gpt-oss-safeguard-20b, 2025. Model card. Accessed 2026-09-10.

Victor M. Panaretos and Yoav Zemel. Statistical aspects of wasserstein distances. *Annual Review of Statistics and Its Application*, 6(1):405–431, March 2019. ISSN 2326-831X. doi: 10.1146/annurev-statistics-030718-104938. URL http://dx.doi.org/10.1146/annurev-statistics-030718-104938.

Aldo Pareja, Nikhil Shivakumar Nayak, Hao Wang, Krishnateja Killamsetty, Shivchander Sudalairaj, Wenlong Zhao, Seungwook Han, Abhishek Bhandwaldar, Guangxuan Xu, Kai Xu, Ligong Han, Luke Inglis, and Akash Srivastava. Unveiling the secret recipe: A guide for supervised fine-tuning small llms, 2024. URL https://arxiv.org/abs/2412.13337.

Xiangyu Qi, Ashwinee Panda, Kaifeng Lyu, Xiao Ma, Subhrajit Roy, Ahmad Beirami, Prateek Mittal, and Peter Henderson. Safety alignment should be made more than just a few tokens deep, 2024. URL https://arxiv.org/abs/2406.05946.

Melissa Kazemi Rad, Alberto Purpura, Himanshu Kumar, Emily Chen, and Mohammad Shahed Sorower. Graid: Synthetic data generation with geometric constraints and multi-agentic reflection for harmful content detection, 2025. URL https://arxiv.org/abs/2508.17057.

Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. XSTest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 5377–5399. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.naacl-long.301.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms, 2017. URL https://arxiv.org/abs/1707.06347.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models, 2024. URL https://arxiv.org/abs/2402.03300.

Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, EuroSys '25, pp. 1279–1297. ACM, March 2025. doi: 10.1145/3689031.3696075. URL http://dx.doi.org/10.1145/3689031.3696075.

SingGuard Team. Singguard: A policy-adaptive multimodal llm guardrail with dynamic reasoning, 2026. URL https://arxiv.org/abs/2606.22873.

Gemma Team, Sherif El Abd, Vaibhav Aggarwal, Robin Algayres, Alek Andreev, Olivier Bachem, Ian Ballantyne, Cormac Brick, Victor Cărbune, Michelle Casbon, Mayank Chaturvedi, Aditya Chawla, Victor Cotruta, Alice Coucke, Phil Culliton, Robert Dadashi, Lucas Dixon, Mohamed Elhawaty, Utku Evci, Clément Farabet, Johan Ferret, Filippo Galgani, Sertan Girgin, Jean-Bastien Grill, Maarten Grootendorst, Jiaxian Guo, Cassidy Hardin, Yanzhang He, Steven M. Hernandez, Omri Homburger, Léonard Hussenot, Juyeong Ji, Armand Joulin, Aishwarya Kamath, Parnian Kassraie, Olivier Lacombe, Preethi Lahoti, Gaël Liu, Gus Martins, Luciano Martins, Tatiana Matejovicova, Ramona Merhej, Nikola Momchev, Sneha Mondal, Ryan Mullins, Sindhu Raghuram Panyam, Shreya Pathak, Sarah Perrin, André Susano Pinto, Etienne Pot, Angéline Pouget, Alexandre Ramé, Sabela Ramos, Douglas Reid, David Rim, Morgane Rivière, Karsten Roth, Louis Rouillard, Omar Sanseviero, Pier Giuseppe Sessa, Shane Settle, Danila Sinopalnikov, Sara Smoot, Piotr Stanczyk, Andreas Steiner, Lawrence Stewart, Ilya Tolstikhin, Michael Tschannen, Anton Tsitsulin, Nino Vieillard, Renjie Wu, Pingmei Xu, Haichuan Yang, Edouard Yvinec, Biao Zhang, Li Zhang, Joe Zou, Nicolas Aagnes, Abdelrahman Abdelhamed, Jakub Adamek, Shivani Agrawal, Shubham Agrawal, Ibrahim Alabdulmohsin, Jean Baptiste Alayrac, Uri Alon, Chandramouli Amarnath, Ankesh Anand, Chrysovalantis Anastasiou, Setareh Ariafar, François-Xavier Aubet, Kyriakos Axiotis, Federico Barbero, Joelle Barral, Alexei Bendebury, Urs Bergmann, Stanley Bileschi, Kat Black, Mathieu Blondel, Sebastian Borgeaud, Arthur Bražinskas, Ryan Burnell, Robert Busa-Fekete, Mu Cai, Daniele Calandriello, Glenn Cameron, Charlotte Caucheteux, Rahma Chaabouni, Garima Chadha, Jetha Chan, Blake Jianhang Chen, Jesse Chen, Lin Chen, Xu Chen, Derek Cheng, Tzu hsiang Chien, Nikolai Chinaev, Yi Chou, Zhaohui Chu, Benjamin Coleman, Pooja Consul, Sam Conway-Rahman, Scott Crowell, Dylan Cutler, Vivek Dani, Samira Daruki, Anil Das, Daniel Deutsch, Nishanth Dikkala, Li Ding, Qiuhan Ding, Shenil Dodhia, Konstantin Donhauser, Tulsee Doshi, Anca Dragan, Alex Druinsky, Sahil Dua, Zoltan Egyed, Danielle Eisenbud, Daniel Eppens, Cindy Fan, Bahare Fatemi, Yassir Fathullah, Vlad Feinberg, Milen Ferev, Sebastian Flennerhag, Takumi Fujimoto, João Gabriel Oliveira, Isaac Galatzer-Levy, João Gante, Simon Geisler, Soham Ghosal, Antonious M. Girgis, Tamara von Glehn, Alec Go, Alhaad Gokhale, Alex Grills, Yiming Gu, Mayank Gupta, Pramod Gupta, Guru Guruganesh, Raia Hadsell, Hamza Harkous, Jitendra Harlalka, Demis Hassabis, Anja Hauth, Joe Heyward, Arian Hosseini, Chih-Yang Hsia, I-Hung Hsu, Xiaopeng Huang, Yangsibo Huang, Kevin Hui, Adrian Hutter, Te I, Fotis Iliopoulos, Advait Jain, Ganesh Jawahar, Ziwei Ji, Qilin Jin, Melvin Johnson, Kandarp Joshi, Arun Kandoor, Wang-Cheng Kang, Koray Kavukcuoglu, Mehran Kazemi, Kathleen Kenealy, Amr Khalifa, Phoebe Kirk, Ivan Korotkov, Suraj Kothawade, Vitaly Kovalev, Neel Kovelamudi, Adam Kraft, Ravin Kumar, Vivek Kumar, Harish Kuppam, Justin Lannin, Chen-Yu Lee, Seungji Lee, Dmitry Lepikhin, Alon Levkovitch, Dongdong Li, Qiujia Li, Valentin Liévin, Ethan Lin, Ziqian Lin, Casper Liu, Tianlin Liu, Tianqi Liu, Xin Liu, Ivan Lobov, Mayank Lunayach, Min Ma, Gagan Madan, Andrii Maksai, Eric Malmi, Michal Matuszak, Daniel McDuff, Gaurav Menghani, Maciej Mikuła, Daniil Mirylenka, Karolis Misiunas, Vedant Misra, Andreea Mitran, Kareem Mohamed, Maksim Mukha, Eric Noland, James O'Donnell, Brendan O'Donoghue, Kate Olszewska, Bernett Orlando, Wanqiong Pan, Rina Panigrahy, Unnati Parekh, Nicolas Perez-Nieves, Chunjong Park, Eric Paskie, Liqian Peng, Bryce Petrini, Slav Petrov, Jonas Pfeiffer, Bilal Piot, Martyna Plomecka, Siim Poder, Octavio Ponce, Arijit Pramanik, David Racz, Anish Rajan, Michelle Ramanovich, Anand Rao, Marvin Ritter,

Vitor Rodrigues, Evan Rosen, Mikołaj Rybiński, Noveen Sachdeva, Michaël E. Sander, Rohit Sathyanarayana, Sagar Savla, Samuel Schmidgall, Tal Schuster, George Scrivener, Benoit Seguin, Andrew Sellergren, Aliaksei Severyn, Izhak Shafran, Dhruv Shah, Bobak Shahriari, Yuan Shangguan, Ashish Shenoy, Pradeep Shenoy, Rakesh Shivanna, Pauline Sho, Lucas Spangher, Wojciech Stokowiec, Tim Strother, Yao Su, Yinghao Sun, Mukund Sundararajan, Andrea Tacchetti, Mor Hazan Taege, Pouya Tafti, Jean Tarbouriech, Chetan Tekur, Shantanu Thakoor, Rahul Thapa, Madeleine Traverse, Lenart Treven, Tao Tu, Chien Te Tung, Çağlar Ünlü, Petar Veličković, Malini Pooni Venkat, Sagar Gubbi Venkatesh, Vidya Venkiteswaran, Francesco Visin, Alex Vitvitskyi, Kiran Vodrahalli, Weiyi Wang, Xin Wang, Tris Warkentin, Jan Wassenberg, John Wieting, Cindy Wu, Lechao Xiao, Hao Xu, Yuhui Xu, Fuzhao Xue, Arun Yadav, Jun Yan, Antoine Yang, Lin Yang, Ming-Hsuan Yang, Ziyu Ying, Jae Hyeon Yoo, Morteza Zadimoghaddam, Sajjad Zafar, Fred Zhang, Jiageng Zhang, Jianyi Zhang, Xiaofan Zhang, Chao Zhao, David Zhou, and Chen Zou. Gemma 4 technical report, 2026. URL https://arxiv.org/abs/2607.02770.

Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions, 2023. URL https://arxiv.org/abs/2212.10560.

Yuquan Wang, Mi Zhang, Yining Wang, Geng Hong, Xiaoyu You, and Min Yang. Reasoningguard: Safeguarding large reasoning models with inference-time safety aha moments, 2025. URL https://arxiv.org/abs/2508.04204.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. Jailbroken: How does llm safety training fail?, 2023. URL https://arxiv.org/abs/2307.02483.

Yongliang Wu, Yizhou Zhou, Zhou Ziheng, Yingzhe Peng, Xinyu Ye, Xinting Hu, Wenbo Zhu, Lu Qi, Ming-Hsuan Yang, and Xu Yang. On the generalization of sft: A reinforcement learning perspective with reward rectification, 2026. URL https://arxiv.org/abs/2508.05629.

Tinghao Xie, Xiangyu Qi, Yi Zeng, Yangsibo Huang, Udari Madhushani Sehwag, Kaixuan Huang, Luxi He, Boyi Wei, Dacheng Li, Ying Sheng, Ruoxi Jia, Bo Li, Kai Li, Danqi Chen, Peter Henderson, and Prateek Mittal. SORRY-bench: Systematically evaluating large language model safety refusal. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025. URL https://arxiv.org/abs/2406.14598.

Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, and Daxin Jiang. Wizardlm: Empowering large language models to follow complex instructions, 2023. URL https://arxiv.org/abs/2304.12244.

Richard J. Young. Evaluating the robustness of large language model safety guardrails against adversarial attacks, 2025. URL https://arxiv.org/abs/2511.22047.

Wenjun Zeng, Yuchi Liu, Ryan Mullins, Ludovic Peran, Joe Fernandez, Hamza Harkous, Karthik Narasimhan, Drew Proud, Piyush Kumar, Bhaktipriya Radharapu, Olivia Sturman, and Oscar Wahltinez. Shieldgemma: Generative ai content moderation based on gemma, 2024. URL https://arxiv.org/abs/2407.21772.

Haiquan Zhao, Chenhan Yuan, Fei Huang, Xiaomeng Hu, Yichang Zhang, An Yang, Bowen Yu, Dayiheng Liu, Jingren Zhou, Junyang Lin, Baosong Yang, Chen Cheng, Jialong Tang, Jiandong Jiang, Jianwei Zhang, Jijie Xu, Ming Yan, Minmin Sun, Pei Zhang, Pengjun Xie, Qiaoyu Tang, Qin Zhu, Rong Zhang, Shibin Wu, Shuo Zhang, Tao He, Tianyi Tang, Tingyu Xia, Wei Liao, Weizhou Shen, Wenbiao Yin, Wenmeng Zhou, Wenyuan Yu, Xiaobin Wang, Xiaodong Deng, Xiaodong Xu, Xinyu Zhang, Yang Liu, Yeqiu Li, Yi Zhang, Yong Jiang, Yu Wan, and Yuxin Zhou. Qwen3guard technical report, 2025. URL https://arxiv.org/abs/2510.14276.

Jingnan Zheng, Jingjun Xu, Yanzhen Luo, Chenhang Cui, Gelei Deng, Zhenkai Liang, Xiang Wang, An Zhang, and Tat-Seng Chua. Self-guard: Defending large reasoning models via enhanced self-reflection, 2026. URL https://arxiv.org/abs/2602.00707.

A APPENDIX

A.1 RELATED WORK

LLM guardrails moderate the inputs and/or outputs of generative AI applications to remove harmful content and block adversarial attacks (Dong et al., 2024). Early systems such as the Perspective API (Lees et al., 2022), the OpenAI Moderation API (Markov et al., 2023), and Detoxify (Hanu & Unitary Team, 2020) score text against a closed, predefined taxonomy – a pattern inherited by LLM-based guardrails like Llama Guard (**?**) and WildGuard (Han et al., 2024). Fine-tuned on a static category set, such models adapt poorly to new categories and attacks and emit no reasoning trace, and robustness audits show sharp accuracy collapse out of distribution, indicating that *generalization*, not in-distribution accuracy, is what matters for deployed guardrails (Young, 2025).

Reasoning-centric safeguards. A newer generation shifts from opaque classification toward interpretable, self-reflective moderation, motivated by "superficial safety alignment," where a model flags a prompt as malicious yet drifts into harmful territory over its intermediate reasoning (Qi et al., 2024; Zheng et al., 2026). GuardReasoner (Liu et al., 2025) trains a guard model to reason before issuing a verdict, yielding an explicit rationale and improved out-of-distribution robustness, while ReasoningGuard (Wang et al., 2025) and Self-Guard (Zheng et al., 2026) steer reasoning-phase transitions or latent safety directions at inference time. These harden the *generation model itself* against a fixed notion of harm, whereas ADAGUARD is an external moderator adjudicating an input against runtime-supplied policies.

Dynamic policy enforcement. Because safety is rarely static and is often industry-specific, several guardrails accept free-form policies at runtime: DynaGuard (Hoover et al., 2025) returns a rapid classification plus a CoT justification, gpt-oss-safeguard (OpenAI, 2025) interprets developer policies at inference time without retraining, and Qwen3Guard (Zhao et al., 2025) adds a tri-class severity scheme (Safe, Controversial, Unsafe) with per-request customization. Closest to us, SingGuard (SingGuard Team, 2026) treats the active policy as a runtime input and checks content rule by rule, exposing fast, slow, and hybrid reasoning depths; its hybrid mode is a per-sample early exit gated by a decode-time confidence threshold τ, and its outcome-only RL reward scores verdict and rule correctness but does not reward *whether* to reason.

Efficiency and adaptive compute. To curb the latency of unconditional CoT, Thinkless (Fang et al., 2025) adaptively selects between short- and long-form reasoning via control tokens, TARS (Kim et al., 2025) allocates more test-time reasoning to ambiguous prompts (but adapts the *answering* model rather than moderating against external policies), and GuardFormer (Neill et al., 2024) trains a compact, low-footprint moderation model on synthetic data while still emitting labels and rationales.

While ADAGUARD inherits this runtime-policy interface of gpt-oss-safeguard, DynaGuard, and SingGuard, it differs along two axes. First, its adaptive-reasoning mechanism is a *trained, per-policy* behavior, not a decode-time heuristic: where SingGuard's hybrid mode is a per-sample early exit gated by a fixed confidence threshold, ADAGUARD's `autoreasoning` mode decides *for each policy k within a single response* whether to emit a reasoning trace, conditioned on its own predicted difficulty, so the budget (Eq. 1) is chosen adaptively per input. Second, this allocation is shaped *directly by the reward* during GRPO training (Shao et al., 2024), unlike Thinkless's control tokens and SingGuard's outcome-only reward, which leave the when-to-reason decision unrewarded.

A.2 HYPERPARAMETERS

We used VERL training framework (Sheng et al., 2025) for our GRPO experiments. SFT experiments used one H100 GPU for training, while RL experiments used two. Table 3 gives the best-performing SFT configuration to date (Section 2.3.1): LoRA fine-tuning ($r = 128$, $\alpha = 64$, RS-LoRA) over 4-bit base weights with bf16 compute, learning rate 2×10^{-5} on a cosine schedule, and early stopping on evaluation loss. Table 4 gives the corresponding GRPO settings.

A.3 ANNOTATOR-AGREEMENT METHODOLOGY

We leveraged human annotation of a sample of generated reasoning traces and their final verdicts for an annotator agreement check. Since our synthetic verdict labels are skewed toward the major-

Table 3: SFT hyperparameters for the best-performing configuration identified in the SFT sweep (Section 2.3.1). Values are read directly from the internal training-configuration tracking sheet for that configuration.

Hyperparameter	Value
Early-stopping patience	8 (eval loss)
Per-device train batch size	2
Gradient accumulation steps	2
Weight decay	0.1
Warmup ratio	0.1
Gradient checkpointing	enabled
Max gradient norm (clipping)	0.3
Learning rate	2×10^{-5}
Optimizer	`paged_adamw_32bit`
LR scheduler	cosine
Adam β_1, β_2	0.9, 0.99
Liger kernel	enabled
Precision	bf16
Base-weight quantization	4-bit
LoRA	enabled
LoRA rank r	128
LoRA α	64
RS-LoRA	enabled

ity (compliance) class, we report the chance-corrected agreement statistic best suited to that skew, **Gwet's AC1** (Gwet & Gwet (2001)), which unlike Cohen's/Fleiss' Kappa (Cohen (1960)) does not degenerate toward zero under high imbalance even when raw agreement is high.

An annotator has been instructed to independently re-score a sample of 100 generated reasoning traces (each trace covering a single *Gemma-4-31B*-generated (Section 2.2) reasoning-and-verdict block, evaluated) against the same five-criterion rubric used by the automated GPT-OSS-120B evaluator during the reflective generation-and-verification (Appendix A.5, Stage 2): *Logic*, *Informativeness*, *Policy Structure*, *Policy Boundaries*, and *Final Response Correctness*. Each criterion is scored on the same 1–5 rubric the automated evaluator uses (Appendix A.5), and the annotator's per-criterion pass/fail call (score $\geq$ `success_threshold` $= 4$, matching the automated evaluator's acceptance threshold) is compared against the evaluator's own pass/fail call on the identical trace. Accuracy, F1, and Gwet's AC1 are computed, measuring *evaluator–annotator* agreement (does the automated GPT-OSS-120B evaluator's accept/reject decision match a human reviewer's).

Results. Table 5 reports Accuracy, F1, and Gwet's AC1 per criterion, computed directly from the annotation spreadsheet's recorded scores (no re-derivation or estimation). Agreement is uniformly high: Gwet's AC1 ranges from 0.818 (Informativeness) to 0.915 (Final Response Correctness) on this sample, with an across-criterion mean of 0.862 – comparable in magnitude to the 0.85 Cohen's Kappa (Hoover et al. (2025)) report for their own synthetic-vs-human label agreement, and above the 0.72 Fleiss Kappa they cite for WildGuard's response- refusal task.

Limitations of this measurement. This sample covers a single annotator against the automated evaluator on 82 traces from one generation condition (*Gemma-4-31B* generator / *GPT-OSS-120B* evaluator, low reasoning effort); it is an evaluator-quality check on the generation pipeline (Section 2.2, Appendix A.5), not a full multi-annotator inter-rater-reliability study of the released dataset's ground-truth verdict labels themselves. A companion generation condition (*GPT-OSS-120B*-generated traces evaluated by *Gemma-4-31B*) was scored by the same annotation process over 99 traces, yielding uniformly higher agreement (Gwet's AC1 0.947–1.000 across the same five criteria, mean 0.964); we do not present that number as an independent replication in the main body since it swaps which model is generator vs. evaluator rather than adding a second independent human annotator on the same traces, but it is consistent with the same-order-of-magnitude agreement reported above.

Table 4: GRPO hyperparameters for the `autoreasoning` configuration, which enables the counterfactual reasoning-value reward (CF_Corr). Reward constants (bottom block) are defined in Appendix A.10.

Hyperparameter	Value
Training & rollout	
Algorithm	`gdpo`
Loss mode	`vanilla`
Learning rate	5×10^{-6}
LR scheduler	constant
Warmup steps	16
Train batch size	64
Mini PPO train batch size	64
Weight decay	0.1
Use KL loss	true
KL coefficient	0.01
Entropy coefficient	0.015
Calculate entropy	true
Rollout temperature (train)	0.9
Rollout top-p (train)	1.0
Val. temperature	0.3
Val. top-p	0.9
GRPO group size n (rollouts/prompt)	16
Counterfactual (CF_Corr) settings	
CF_Corr enabled	true
CF_Corr max tokens	4096
CF_Corr temperature	0.3
CF_Corr top-p	0.9
CF_Corr top-k	-1
Reward constants (Appendix A.10)	
$\text{PARSE_PENALTY} = \text{GATE_PENALTY} = -1.5$	
$C_{\text{cor}} = \text{CORRECTNESS_CORRECT} = +1.0$	
$C_{\text{wr}}^{\text{cot}} = -1.0, \quad C_{\text{wr}}^{\text{no}} = -0.5$	
$Q_{\text{end}} = \text{QUALITY_SCORE_END} = 1.5$	
$C_{\text{flip}} = \text{CF_CORR_FLIP_BONUS} = +0.5$	
$C_{\text{both}} = \text{CF_CORR_WRONG_BOTH} = -0.75$	
$C_{\text{broke}} = \text{CF_CORR_BROKE_PENALTY} = -1.25$	
$C_{\text{unnec}} = \text{CF_CORR_UNNECESSARY_COST} = 0.2$	

Table 5: Evaluator-vs-human-annotator agreement on 82 *Gemma-4-31B*-generated reasoning traces, evaluated by GPT-OSS-120B (automated evaluator) against a human annotator's independent scoring, one row per rubric criterion (Appendix A.5, Stage 2). Values computed directly from the recorded per-criterion pass/fail calls; no estimation.

Criterion	Accuracy	F1	Gwet's AC1
Logic	0.878	0.933	0.855
Informativeness	0.854	0.918	0.818
Policy Structure	0.915	0.953	0.898
Policy Boundaries	0.854	0.919	0.822
Final Response Correctness	0.927	0.961	0.915
Mean across criteria	0.885	0.937	0.862

Table 6: Released training-corpus split statistics. Violation ratio is $|\{k : v_k = \text{VIOLATION}\}|/K$ averaged per input (the L1 quantity of Appendix A.6). While the distribution of datapoints with no input-policy pair violations to datapoints with at least one violation is split uniformly across datasets, this ratio measures the ratio of per-input-policy-pair violations. Per-policy difficulty d_k is not present in this export, so target-vs-achieved L1–L4 values await the final curation config (flagged in Appendix A.6). "Unique categories" counts distinct input-category values within that split; the five training/validation splits share 0 categories with the holdout split (Table 7).

Split	# inputs	Mean K	Mean violation ratio	Mean difficulty ratio	Unique categories
SFT train	13,008	5.05	0.164	0.155	112
SFT val	6,038	5.44	0.163	0.137	111
GRPO train	3,500	6.29	0.180	0.327	100
GRPO val	1,952	6.31	0.165	0.339	87
Holdout (dynamic-policy test)	12,291	6.61	0.187	0.307	15
Total (all splits, deduplicated)	75,254	—	—	—	127

A.4 Training-Data Composition

Table 6 gives the released training-corpus split statistics referenced from Section 2.2: set sizes, mean matched-policy count K, achieved per-input violation ratio (the L1 quantity of Appendix A.6), and category coverage. Consistent with the difficulty-stratification goal stated in Section 2.2, the GRPO train/val splits have a substantially larger mean K than SFT train/val; the holdout set's mean K (6.61) falls slightly above both, consistent with it being drawn from held-out categories rather than being curated jointly with either training split. Each input in the corpus carries an input-category field (and, for a subset, a finer sub-category) that is the raw taxonomy label consumed by the dynamic-policy description-synthesis stage (Section 2.2); 137 unique category values appear across the five splits, and their per-split counts are what determines how many dynamic-policy descriptions exist for each category. The data is sourced entirely from open-source data, including `aegis`, `coconot`, `wildguardmix`, `or-bench-toxic`, `toxigen`, `jailbreakv-redteam`, `DAN/Forbidden Q`, `aya-redteaming`, `catharmfulqa`, `ultrasafety`.

In order to create the SFT and GRPO train and validation data splits, we utilize a five-step procedure. The initial set of inputs is comprised of over 367,000 datapoints out of which over 173,000 are safe and 31,000 are difficult (i.e. obfuscated). We have over 10,000 policies generated through our complex policy generation pipelines and 500 from our vanilla policy generation.

Obfuscation To generate complex inputs, we apply a diverse suite of perturbation techniques to a randomly selected subset of approximately 31,000 inputs. These perturbations are organized into two primary categories: structural *obfuscations* and contextual *reframings*. Obfuscation techniques conceal the literal text of the prompt, forcing the model to perform low-level decoding or symbolic translation before addressing the core task. Our static obfuscation methods included *Math Prompt*, which reformulates requests into formal set-theory or logic notation; *Flip-Attack*, which reverses strings while injecting distractors; and *SATA* (Semantic Anagram Task), which masks key terms to necessitate translation-based reasoning. We also applied algorithmic encodings like Base64 (paired with explicit decoding instructions) and Leetspeak, alongside *CodeChameleon*, which embeds the prompt within a mock string-transformation coding task. For the most intensive semantic obfuscation, we deployed *DRA* (Disguise and Reconstruction), a generative technique that buries the core request deep inside a multi-step puzzle. Reframing techniques were utilized to alter the stylistic, structural, or temporal context of the prompt without rendering the core text unreadable. Our comprehensive perturbation strategy is to help ensure the model's underlying reasoning mechanisms are trained to be robust enough to handle highly indirect, complex user intents.

Data Curation Next, we will walk through the process of curating SFT and GRPO datasets.

Step 1 utilizes k-means clustering to select holdout categories (explained in more depth below). The input and policy sets are then filtered out to remove datapoints mapped to these 20 heldout categories (shown in Table 7). No inputs and no policies belonging to the holdout category move forward to

Steps 2-5 because we do not wish to include any holdout data within our training sets in order to avoid leakage.

Step 2 splits inputs between SFT and GRPO. For SFT: we maintain close to a 60/40 easy/obfuscated input split and a 50/50 harmful/safe split. The 50% safe inputs are split 70/30 between safety-adjacent/non-safety adjacent. For GRPO: we maintain close to a 40/60 easy/obfuscated input split and a 50/50 harmful/safe split. The 50% safe inputs are split 70/30 between safety-adjacent/non-safety adjacent.

Step 3 splits policies between SFT and GRPO. For SFT: we maintain close to a 50/50 easy/complex policy split, in which the 50% complex policies are split 50/50 between being conditional/not-conditional. For GRPO: we maintain close to a 30/70 easy/complex policy split, in which the 70% complex policies are split 50/50 between being conditional/not-conditional.

Step 4 splits SFT and GRPO data into SFT train/validation and GRPO train/validation respectively. Data from each category is split into both train and validation to ensure each category's data is present in both. Attempting to utilize cosine similarity to enforce different policies within-category between train and val proved unsuccessful as policies belonging to the same category are similar. Inputs overlap 30% between train and validation sets of both SFT and GRPO; policies overlap 20%.

Step 5 performs the final mapping from input to groups of policies for SFT train, SFT validation, GRPO train, and GRPO validation. Datapoints are categorized into six types of conditions: (1) easy input, all easy policies, all not-conditional policies; (2) easy input, at least 1 complex policy, all not-conditional policies; (3) easy input, at least 1 complex policy, at least 1 conditional policy; (4) obfuscated input, all easy policies, all not-conditional policies; (5) obfuscated input, at least 1 complex policy, all not-conditional policies; (6) obfuscated input, at least 1 complex policy, at least 1 conditional policy. We design the algorithm to map from input to group of policies such that the distribution across these six conditions is even. Namely, we want an even number of datapoints per-condition and an even ratio of violation/compliance. Since the data has not yet passed through the reasoning generation pipeline to make the verdict determination, we assume violation when a policy's category is the same as an input's category and compliance when they differ. We additionally map each input to a group of policies, K, which is higher on average for GRPO than SFT for the purposes of our RL train set being more complex. A normal distribution is applied regarding the number of policies each input is mapped to. SFT mean $K = 10$, GRPO mean $K = 15$, and Holdout mean $K = 12$ with standard deviation being 5 for both.

Initially after running through the aforementioned steps we have approximately 30,000 SFT train, 14,000 SFT val, 7,500 GRPO train, 3,500 GRPO val, and 20,000 holdout datapoints. The average mapped number of policies per input is 10 for SFT (std=5), 15 for GRPO (std=5), and 12 for the heldout dataset (std=5). As seen by the differing values in Table 6, these dataset sizes and ratios change once data passes through the entire pipeline including pruning (Section A.6), which filters policy pairs from the data to achieve correct compliance/violation and difficulty ratios.

Held-out Split Construction The held-out dynamic-policy test set is built from the same label→policy pipeline as the training data (Section 2.2), but starting from a disjoint slice of input *categories* rather than a random sample of inputs. A fixed set of input-category values is reserved *before* dynamic-policy generation and input–policy matching are run, so that no dynamic policy description synthesized for a reserved category is ever seen by the matching step that builds the SFT/GRPO training pool; training and held-out corpora are consequently disjoint at the category level by construction, not by a post-hoc filter applied after matching. The held-out corpus then goes through the same reasoning-trace and difficulty-estimation stages as training data, so each held-out (x, p_k) pair carries a reference verdict v_k and difficulty label d_k exactly like a training example (20,000 inputs, mean $K = 11.99$). After running through pruning, the number of datapoints & matched number of policies changes (Table 6).

Initially we selected the following 20-size subset of input categories: "Bullying & Harassment", "Child Abuse_Neglect", "Criminal Planning/Confessions", "Fraud/Deception_False advertising", "High Risk Gov Decision Making", "Illegal Activity_Drug", "Malware Viruses_Malicious software designed to spread and damage computers", "Malware Viruses_Spyware", "Political Campaigning_Political activism", "Political/Misinformation/Conspiracy", "Privacy Violation", "Sexual", "Unauthorized Advice", "cyberattack", "dangerous or sensitive topics", "deception", "pri-

Table 7: The 15 final input-category values encompassing the holdout set (no exact overlap with SFT/GRPO train or validation split categories), supporting the zero-shot dynamic-policy generalization claim.

Holdout-only input category
Child Sexual Abuse & Exploitation
Criminal Planning & Non-Violent Crime
Disinformation & Misinformation
Drugs & Controlled Substances
Fraud, Deception & Economic Harm
Harassment, Bullying & Toxic Language
Hate Speech & Identity-Based Discrimination
Malware, Hacking & Cyberattacks
Political & Government Decision-Making
Privacy Violations & PII
Self-Harm & Suicide
Sensitive Topics
Sexual Content & Adult Material
Unauthorized & Expert Advice
Violence & Physical Harm

vate_information_individual", "toxic_language_hate_speech", "triggers for offensive language", "unethical". To obtain these we utilize k-means clustering; specifically, our harmful inputs span 130 categories (safe and benign categories were excluded). We embed the category names using *all-MiniLM-L6-v2* and then utilize k-means clustering with $k = 20$ such that each cluster represents a broad family of harm. We then randomly sample one category per cluster, attempting to sample categories in which there are both easy and hard (obfuscated) inputs belonging to each category, when applicable. All inputs and policies belonging to these heldout categories are removed from the set of inputs and policies before splitting into SFT and GRPO train and validation, ensuring zero overlap.

Our holdout set is comprised of open safety inputs from the following sources: `wildguard-test`, `xs-test`, `strongreject`, `aegis-test`, `orbench`, `wildjailbreak`, `realtoxicity`, `anthropic-hh-rlhf`, `toxigen`, `jailbreakbench`, and `decodingtrust`. The datasets contain categories (and sometimes sub-categories) each datapoint falls into, but often these do not coincide with our 20 holdout categories. We utilize policies from our 20 holdout categories in the groups as compliance examples when input categories do not match and violation examples when they do, but the rate of violations is very low without augmenting with policies from input categories. Thus, we utilized the complex policy generation pipeline to synthesize complex policies for each category not mapped to a holdout policy, and then followed the same input-to-policy-group mapping followed by SFT/GRPO train/validation sets to obtain 20,000 datapoints comprised of 12,679 unique inputs, 3,170 unique policies, an average of 12 policies per input, and a violation rate of 17.5%. All unique policies fall into 15 broad categories that have no overlap with categories present in SFT and GRPO train and val. This final set of heldout categories were identified through *claude-5-sonnet*, as the model clustered all policies into 15 broad categories shown in Table 7. The data then runs through the data curation pipeline (Section A.6) after which the holdout set is comprised of 12,291 datapoints.

A.5 Data-Generation Prompts

This appendix reproduces the generation objectives, generator prompts, and evaluator rubrics for the three generation-pipeline stages referenced in Section 2.2: dynamic policy description synthesis (Section 2.2), reference reasoning-trace generation, and verdict-sampling difficulty estimation (both Section 2.2).

A.5.1 DYNAMIC POLICY DESCRIPTION SYNTHESIS

Generation Objection - Dynamic Policy Generation

The goal is to generate various descriptions for each label title provided in Input Label. These labels are related to safety and compliance tagging of textual contents. These textual contents are either user inputs/queries to an AI agent, or an AI agent response to user inputs/queries. The descriptions that are generated define a set of rules that will ultimately be used by another agent to decide whether a user input or AI agent response violates or complies with them. Therefore, these generated descriptions must CAREFULLY take into account Moderation Type." The objective further requires:

- descriptions are based solely on a set of scopes the generator first identifies in `<scopes>`
- if `Moderation Type` is `input`, scopes/descriptions target user-side content, and if `output`, agent-response content
- different descriptions for the same label must cover *different subsets* of the identified scopes
- diversity is achieved by varying the number of scopes used, description length, and semantic/stylistic phrasing
- tone must be imperative, treating each description as a guideline for a downstream guardian agent
- descriptions should be concise.

Below we reproduce the *entire* generator and evaluator prompts.

Generator Instruction - Dynamic Policy Generation

You are a generation assistant. Your task is to generate data label descriptions to achieve the goal outlined in Generation Objective. Carefully follow the steps below:

1. For the data label provided in Input Label, first generate a set of scopes that clearly outline the extent to which the label characterizes different textual contents. These textual contents are either user inputs/queries or AI agent responses to user inputs.
2. Given the scopes you identified in the previous step, synthesize a description that incorporates and reflects all or only a subset of the scopes.
3. A successful label description must be carefully tailored to Moderation Type.
4. The total number of sets of descriptions for Input Label is controlled by New Data Count, i.e. you must repeat step 2 above New Data Count number of times.
5. You must generate New Data Count significantly different descriptions for Input Label.
6. Each description should be a cohesive instruction or rule for a guardian agent for allowed or disallowed contents based on the subset of the scopes you have chosen.

You must follow the output format as outlined in the XML format below.

– `<think>` This tag wraps the internal reasoning and includes:
  – `<steps>`: A concrete attempt to solve the task with logical and incremental steps. This section applies reasoning or domain knowledge, and may include decisions, rule applications, etc.
  – `<scopes>`: Enumerated list of scopes you identified based on your reasoning steps. Scopes must be numbered starting from `1` to the maximum number of scopes identified.

Repeat the following fields New Data Count number of times. Numbers must go up from 1 up to New Data Count.
– `<answer>`: This is the final output, i.e. the description for Input Label given the different subsets of scopes. This description outlines context or actions in a textual input that are or are not allowed. The tone of the descriptions must be imperative.
–`<scopes_used>`: For each description generated in `<answer>`, specify comma-separated numbers corresponding to the subset of the scopes from the enumerated list in `<scopes>` in the think step above that you have used to generate each description.

For example, if New Data Count is 3, the `<answer>` format should repeat three times, following `1.`, `2.`, and `3.`. Then, the entire output looks like the following:

```
<think>
  <steps></steps>
  <scopes>
    1.  Scope 1
```

```
            2.  Scope 2
            3.  Scope 3
            ...
          </scopes>
        </think>
        1.
        <answer></answer>
        <scopes_used>
          2, 3
        </scopes_used>
        2.
        <answer></answer>
        <scopes_used>
          1, 4, 5
        </scopes_used>
```

You must still choose a subset of scopes identified in <think> section and synthesize the label description.

Generation Objective:

New Data Count:

Moderation Type:

Input Label:

Evaluator Instruction - Dynamic Policy Generation

You are an evaluation assistant. Your task is to VERY CAREFULLY evaluate the label description in Generated Description produced by a generation assistant against the provided Optimization Constraints. Carefully follow the instructions below:

1. Go through each constraint in Optimization Constraints one by one.
2. For each constraint, first provide a fairly detailed step-by-step and logical reasoning for the extent to which you think the Generated Description produced by the generation assistant for Input Label satisfies the constraint in thinking mode.
3. For each constraint, use this reasoning to provide an informed score indicating how confident you are that the Generated Description satisfies the constraint. This score should be an integer between 1 and 5, with larger values indicating higher constraint satisfaction.

For each constraint, follow these instructions EXACTLY as provided:
1. Output the title of the constraint exactly as it is provided in Optimization Constraints following **Constraint:** on a new line, for example, **Constraint:** <Optimization Constraint>.
2. For each constraint, output the following sections:
— <think>: This tag wraps the internal reasoning and includes:
— <planning>: A high-level thought process (reflect on the instruction, brainstorm multiple approaches if applicable, consider blockers or alternatives, avoid providing the ultimate verdict).
— <steps>: A concrete attempt to solve the task with logical steps (applies careful reasoning or domain knowledge, follows through on plan, may include decisions, rule applications, etc.).
— <answer>: This is the final output, composed of:
— <score>: The success score for the constraint based on the instruction and the reasoning in <think>.
— <failure>: (Conditional) If and only if the success score in <score> is below Success Threshold, then provide an explanation on why the constraint failed for the Generated Description based on the reasoning in <think>.
— <instruction>: (Conditional) If and only if the success score in <score> is below the Success Threshold, then provide the regeneration instruction.

The output format for each constraint looks like the following. Assuming there are two constraints:

```
**Constraint:** <Optimization Constraint 1>
<think>
```

```
      <planning></planning>
      <steps></steps>
    </think>
    <answer>
      <score></score>
      <failure></failure>
      <instruction></instruction>
    </answer>
    **Constraint:** <Optimization Constraint 2>
    <think>
      <planning></planning>
      <steps></steps>
    </think>
    <answer>
      <score></score>
      <failure></failure>
      <instruction></instruction>
    </answer>
```

Repeat this format for each constraint. All tags must be present exactly once for each optimization constraint if not marked Conditional; Conditional tags appear only if the score is below Success Threshold; all tags must be syntactically valid (no typos, unclosed tags, or mixed nesting).

Optimization Constraints:

Success Threshold:

Moderation Type:

Input Label:

Identified Scopes:

Generated Description:

The three per-constraint evaluator rubric definitions substituted into {`constraints`} above are:

Evaluator Constraints

Scope Relevance: Carefully consider Input Label, Identified Scopes, and Generated Description, and ascertain if Generated Description adequately reflects and covers the list of scopes in Identified Scopes.

Description Tone: Determine if the tone of Generated Description is imperative, and it can be used as a guideline to determine whether a text input is in compliance or violation of Input Label according to Generated Description.

Moderation Type: Determine if Generated Description fully respects Moderation Type. Concretely, if Moderation Type is `input`, Generated Description must only target user inputs/queries to an AI assistant for policy violations, not AI agent responses to user inputs, and vice versa if Moderation Type is `output`.

Each constraint is scored 1–5 by the evaluator; a generation is accepted once every constraint reaches `success_threshold` (by default 4), else it is regenerated (up to `max_eval_recursion` cycles, by default 2) using the evaluator's per-constraint failure explanation and regeneration instruction as feedback.

In an effort to make AdaGuard robust to any type of policy and handle verifying compliance or violation for especially intricate or specialized policies, we utilize three variants of generator instructions to generate highly complex policies. The first method focuses on requesting conditional logic within the generated policy, edge case policies, and provides few-shot examples of simple versus complex. The second method focuses on generating policies with complex intent, severity, and context. The third method produces fusion policies based on two categories rather than one. Instructions for each of these are shown below.

Generator Instruction - Complex Policy Method 1

You are a generation assistant. Your task is to generate data label descriptions to achieve the goal outlined in Generation Objective. Carefully follow the steps below:

1. For the data label provided in Input Label, first generate a set of scopes that clearly outline the extent to which the label characterizes different textual contents. These textual contents are either user inputs/queries or AI agent responses to user inputs.
2. Given the scopes you identified in the previous step, synthesize a description that incorporates and reflects all or only a subset of the scopes.
3. A successful label description must be carefully tailored to Moderation Type.
4. The total number of sets of descriptions for Input Label is controlled by New Data Count, i.e. you must repeat step 2 above New Data Count number of times.
5. You must generate New Data Count SIGNIFICANTLY DIFFERENT descriptions for Input Label.
6. Do not generate separate sentences for each chosen scope in the label descriptions. Each description should be a cohesive instruction or rule for a guardian agent for allowed or disallowed contents based on the subset of the scopes you have chosen.
7. Each description MUST be complex and nuanced. Complexity means:
- The description includes conditional logic, exceptions, or carve-outs. For example: "Disallow X unless the user is explicitly operating in a professional or authorized context such as Y."
- The description distinguishes between borderline or edge cases that might superficially resemble a violation but are not, and those that clearly are.
- The description goes beyond listing obvious violations and instead captures subtle, indirect, or context-dependent manifestations of the label.
- The description uses precise language that would allow a guardian model to make a non-trivial, well-reasoned classification decision rather than a simple keyword match.

EXAMPLES of SIMPLE descriptions to AVOID:
- "Disallow any user input that contains hate speech."
- "Block requests that include instructions for illegal activities."

EXAMPLES of COMPLEX descriptions to GENERATE:
- "Disallow user inputs that use coded language, cultural references, or rhetorical framing to demean individuals based on protected characteristics, including cases where the hateful intent is implicit or plausibly deniable. Permit inputs that critically analyze, report on, or discuss such language in an academic, journalistic, or counter-speech context, provided the framing is clearly analytical rather than endorsing."
- "Disallow user inputs that solicit step-by-step operational guidance for activities that are illegal in most jurisdictions, including cases where the request is framed as hypothetical, fictional, or educational. Permit requests that seek to understand the legal framework around such activities, identify risks for harm prevention, or are explicitly oriented toward lawful professional practice."

Generator Instruction - Complex Policy Generation Method 2

You are a generation assistant. Your task is to generate data label descriptions to achieve the goal outlined in Generation Objective. Carefully follow the steps below:

1. For the data label provided in Input Label, generate a rich and structured set of scopes that characterize the label across multiple dimensions. You must identify scopes along ALL of the following four axes:
- Intent-based scopes: What underlying goals or motivations in the input signal this label? Include both overt and covert intents.
- Severity-based scopes: What range of severity levels does this label cover, from borderline or ambiguous cases to clear-cut violations?
- Context-based scopes: In what situational, professional, or conversational contexts might this label apply differently? What contexts create exceptions or carve-outs?
- Manifestation-based scopes: What are the direct, indirect, coded, or implicit ways this label can surface in text? Include non-obvious or creative circumvention patterns.
2. After identifying scopes along all four axes, synthesize New Data Count descriptions. Each description must:
- Draw from scopes across at least two different axes.
- Produce a structurally and substantively different description from all others — not just paraphrased.
- Cover at least one non-obvious or edge-case scope (e.g., indirect, coded, or context-dependent manifestations).

3. A successful label description must be carefully tailored to Moderation Type.

Generator Instruction - Complex Policy Generation Method 3

You are a generation assistant. Your task is to generate data label descriptions to achieve the goal outlined in Generation Objective. Carefully follow the steps below:

1. You are given two related data labels in Input Labels. First, independently identify scopes for each label that characterize the different textual contents it covers.
2. Next, analyze the relationship between the two labels:
- Where do they overlap? What content could plausibly be classified under either label?
- Where are their boundaries? What content clearly belongs to one and not the other?
- What edge cases exist at the intersection of the two labels?
3. Using this analysis, synthesize New Data Count policy descriptions. Each description must be for one specific label (either the first or the second), but must be informed by the relationship to the other label. Specifically:
- At least one description must explicitly address the boundary between the two labels, carving out content that belongs to the other label.
- At least one description must address edge cases or content that sits at the intersection of both labels.
- All descriptions must be carefully tailored to Moderation Type.
4. You must generate New Data Count SIGNIFICANTLY DIFFERENT descriptions across both labels.

The evaluator agent was also updated to measure across the following constraints.

Evaluator constraint definitions for generated complex policies

Scope Relevance: Carefully consider Input Label, Identified Scopes, and Generated Description, and ascertain if Generated Description adequately reflects and covers the list of scopes in Identified Scopes.

Description Tone: Determine if the tone of Generated Description is imperative, and it can be used as a guideline to determine whether a text input is in compliance or violation of Input Label according to Generated Description.

Complexity: Determine if Generated Description is genuinely complex and nuanced. A complex description must satisfy at least two of the following: (1) it includes conditional logic, exceptions, or explicit carve-outs that distinguish permitted from disallowed content; (2) it addresses non-obvious, indirect, or context-dependent manifestations of the label rather than only the most obvious violations; (3) it uses precise qualifying language that would require non-trivial reasoning to apply, rather than simple keyword matching. A description that lists only obvious violations or uses generic blanket prohibitions without any nuance must receive a low score.

A.5.2 Stage 2: Reference Reasoning-Trace Generation

Generation Objectives - Reasoning Generation

The goal is to generate highly logical and informative reasoning traces and arrive at the most accurate verdict on whether or not Input Data (user input or AI agent responses) is in compliance or violation of each of the policies in Input Policies, requiring

- a single `Input Understanding` block dissecting the input before any per-policy reasoning
- for each policy, in order, a `Policy Understanding` block, an `Input Compliance Understanding` block, and a final `Compliance`/`Violation` verdict, where the verdict is `Violation` if *any* scope of that policy is violated and `Compliance` only if *all* scopes are satisfied
- each policy's reasoning treated in complete isolation from every other policy's reasoning or verdict
- numbered reasoning blocks matching the policy's index exactly

- reasoning concise when the verdict is straightforward and more in-depth only when it aids the decision

Generator Instruction - Reasoning Generation

You are a reasoning assistant. Your task is to achieve the specific goal outlined in Generation Objective. The ultimate goal is to arrive at the most logical conclusion on whether Input Data complies with or violates each of the policy descriptions in Input Policies. Your output must be a structured XML reasoning trace with a final `Compliance` or `Violation` verdict for each policy. Carefully follow the instructions below.

You are given the following as input: Input Data (a user input, an AI agent response, or multi-turn user/agent conversations); an enumerated list of policy descriptions outlining the criteria for user inputs or agent responses to be considered in compliance or violation of each policy.

Consider the following in addition to Generation Objective:
1. Each policy description must be reasoned about in complete isolation. Do not allow the analysis or verdict of one policy to influence the reasoning or verdict of any other policy. Each compliance or violation decision must stand independently.
2. The numbered index of each per-policy reasoning block must correspond exactly to the same-numbered policy in Input Policies. Generate reasoning blocks in the EXACT same order as the policies appear in Input Policies. Mismatched ordering will cause verdict misattribution and is a critical failure.
3. For each policy description, your reasoning must be grounded ONLY in Input Data and that specific policy description; no other policies, external criteria, or default assumptions.
4. All reasonings must follow logical steps at the service of understanding the scopes and nuances of Input Data, each policy description in Input Policies, and their interaction, all helping to arrive at the most logical violation/compliance verdict.
5. Strictly avoid producing introductory phrases anywhere in the response (e.g., "Certainly!", "Let me analyze this...", "Sure, here is..."), or generating tokens that do not enhance the utility of the reasoning in arriving at the final verdict.
6. Follow the output format EXACTLY as it is outlined. Any deviations from the output format will result in a critical failure.
7. Generate a reasoning block for EACH policy description — no more, no fewer.

Follow the XML format EXACTLY as outlined below by including the following sections:
— `<input_understanding>`: This is a step-by-step reasoning, dissecting the different scopes, aspects, nuances, and intents of Input Data. This tag must appear exactly once, before all per-policy reasoning blocks.
— For each policy description in Input Policies, generate the following three blocks in order, numbered to match the policy's index in Input Policies:
— `<policy_understanding>`: Step-by-step reasoning understanding the different scopes and requirements outlined in that specific policy description, considered independently of all other policies.
— `<input_compliance_understanding>`: Step-by-step reasoning, leveraging reasoning in `<input_understanding>` and `<policy_understanding>` for this policy only, focusing on arriving at a resolution on whether or not Input Data complies with or violates this specific policy. Treat this analysis in isolation from all other policies.
— `<answer>`: This is the final compliance or violation verdict for this policy as requested in Generation Objective, which follows all instructions and corresponds clearly to all the preceding reasoning traces for this policy. The verdict is `Violation` if Input Data violates ANY of the scopes outlined in the policy description. The verdict is `Compliance` only if Input Data complies with ALL scopes outlined in the policy description. Only output one of these two tokens in this tag.

All reasoning traces must incorporate a concrete attempt to solve the task with logical steps: apply reasoning or domain knowledge to understand the gist of the scopes covered in each policy description and the context and intent of Input Data; may include decisions, rule applications, etc.; stay focused on the scopes defined in the specific policy being reasoned about and do not consider any other scopes, other policies, or inherent assumptions; wherever multiple steps are required, convert them to a bulleted list, with each bullet on a new line.

Here an example template of the output format. For example, if Input Policies contains two policies, then the output looks like the following:

```
<input_understanding>
</input_understanding>
```

```
1.
<policy_understanding>
</policy_understanding>
<input_compliance_understanding>
</input_compliance_understanding>
<answer>
</answer>
2.
<policy_understanding>
</policy_understanding>
<input_compliance_understanding>
</input_compliance_understanding>
<answer>
</answer>
```

All tags must be present exactly as outlined above and in the exact order demonstrated in the example output format; appear with the XML tags exactly as shown, without any additional tokens or words; be syntactically valid (no typos, unclosed tags, or mixed nesting). If any tag is missing, out of order, duplicated, or lacks meaningful content, the format is invalid.

Generation Objective:

Input Data:

Input Policies:

The five per-constraint evaluator rubric definitions substituted into {`constraints`} above are:

Evaluator Constraints - Reasoning Generation

Logic: Carefully consider the steps inside each of the reasoning traces and determine if any of them have failed to follow a strictly logical path. Additionally, carefully consider whether the final decision in `<answer>` is a logical conclusion following the reasoning steps.

Final Response Correctness: Determine if the final decision in `<answer></answer>` is correct or not. Specifically, the final decision must be `Violation` if Input Data violates ANY of the scopes outlined in the policy description, and `Compliance` only if Input Data complies with ALL scopes outlined in the policy description.

Informativeness: Determine if the different step-by-step reasonings meaningfully contribute to arriving at the most accurate final compliance verdict. Informative reasoning steps must refrain from restating known or redundant information, providing irrelevant digressions that do not contribute to solving the problem, and unnecessary self-doubt or circular troubleshooting that adds no value. Positively, informative reasoning must demonstrate that the policy's key criteria were identified and concretely applied to the specific content of Input Data.

Policy Structure: Verify that a reasoning block comprising `<policy_understanding>`, `<input_compliance_understanding>`, and `<answer>` is present for EVERY policy in Input Policies with no policy silently skipped or merged with another, and that each block's numbered index matches the number of the corresponding policy in Input Policies.

Policy Boundaries: Verify that each policy's reasoning is derived solely from Input Data and that specific policy in isolation, without referencing or being influenced by any other policy's reasoning or verdict. Additionally, verify that the reasoning for each policy considers only the scopes explicitly defined in that policy description, without introducing external criteria, assumptions, or the model's own default policies.

We use Gemma-4-31B as the reasoning generator and GPT-OSS-120B (low reasoning effort) as the evaluator for this stage.

A.5.3 STAGE 3: INPUT/POLICY DIFFICULTY ESTIMATION

Generation Objective - Difficulty Estimation

The goal is to evaluate whether Input Data complies with or violates each policy in the numbered list of Input Policies. For each policy, output exactly one verdict token on its own line, in the same numbered order as the policies appear. Use only these two tokens per policy: Compliance – if Input Data complies with ALL scopes outlined in that policy; Violation – if Input Data violates ANY scope outlined in that policy. Do NOT output anything other than the numbered verdict lines.

Generator Instruction - Difficulty Estimation

You are a compliance evaluation assistant. Your task is to evaluate whether the provided input complies with or violates each policy in a numbered list.

You will be given: (1) Input Data: the text to evaluate. This may be a single text (a user input or an AI agent response), or a multi-turn conversation between a user and an AI agent. (2) Input Policies: a numbered list of policies to evaluate Input Data against. (3) Moderation Target (optional): if provided, specifies which part of Input Data the policies apply to. When Input Data is a multi-turn conversation: if Moderation Target is `user`, evaluate ONLY the user turns of the conversation against each policy (ignore agent turns entirely); if Moderation Target is `agent`, evaluate ONLY the agent turns of the conversation against each policy (ignore user turns entirely); if Moderation Target is not provided, evaluate Input Data as a whole.

For each policy, respond with its number followed by a single verdict token — either `Compliance` or `Violation` — with no explanation, punctuation, or additional text. Output one verdict per line, in the same order as the policies. Do not skip any policy.

Output exactly the following format and nothing else, repeating one line per policy:

```
1. Compliance
2. Violation
...
```

Input Data:

Input Policies:

Generation Objective:

This stage has no LLM-judge evaluator rubric: difficulty is derived directly from *sampling statistics* rather than a scored evaluation. Concretely: each of the three ensemble members (Gemma-4-31B, GPT-OSS-20B low-reasoning-effort, GPT-OSS-120B low-reasoning-effort) independently samples $k = 32$ verdicts per (x, p_k) pair at temperature 0.9 (top-p 0.999); a policy is flagged difficult by a given model when the majority-label agreement rate across that model's 32 samples falls below `min_agreement_rate` ; the released-data invocation sets `min_agreement_rate=0.85` . The final difficulty label is the *union* across the three ensemble members: a pair is HIGH difficulty if *any* ensemble member's majority agreement is below threshold, else LOW.

A.6 DATA CURATION: THE POLICY-DISTRIBUTION REFINER (PIPELINE STAGE 4)

This appendix expands the curation summary of Section 2.2. The four levels are Wasserstein-distance checks against target Gaussians, arranged in a strict hierarchy so that dataset-wide balance is enforced before finer per-category or per-verdict balance is attempted:

- **L1 (per-input violation ratio, requires verdicts).** For each input x, the fraction of its matched policies with $v_k =$ VIOLATION should be distributed as $N(\text{mean}_v, \text{std}_v)$ across the dataset. Enforced jointly with L2 during greedy pruning of individual (x, p_k) pairs; skipped entirely in Stage A.
- **L2 (per-input difficulty ratio, always active).** For each input x, the fraction of its matched policies with $d_k =$ HIGH should be distributed as $N(\text{mean}_d, \text{std}_d)$. This is the only level active

throughout Stage A, and inputs whose every matched policy is LOW-difficulty are removed by a dedicated zero-row reduction pass that targets the resulting structural spike at ratio 0, which pruning alone cannot smooth out.

- **L3 (within-verdict difficulty gap, requires verdicts).** The gap between the high-difficulty rate measured only among violation-labeled pairs and the high-difficulty rate measured only among compliance-labeled pairs must fall within a fixed tolerance of each other, so that difficulty is not systematically confounded with verdict (e.g. violations being trivially easier or harder to call than compliances). The reference point is the L2 target mean, not a fixed 0.5 split.
- **L4 (per-category alignment, active in all modes).** For every policy category, three checks compare the category's local rate against the dataset-wide rate: (i) category difficulty ratio vs. the L2 target mean (active in both stages); (ii) category violation ratio vs. the dataset-wide violation ratio (requires verdicts, Stage B only); and (iii) the within-category version of the L3 verdict/difficulty gap (requires verdicts, Stage B only). This prevents a handful of over-represented categories from dominating the difficulty or violation statistics of the whole set.

Two-stage curation schedule. Because the reasoning/difficulty-generation stage that produces v_k is itself an expensive generation-and-verification pipeline, curation runs in two stages so that verdict generation is only ever run once, on an already-difficulty-balanced pool:



(a) L1: GRPO Violation Ratio

(b) L2: GRPO Difficulty Ratio

(c) L3: Within-Compliance Difficulty

(d) L3: Within-Violation Difficulty

Figure 5: GRPO dataset curation. The refiner successfully flattens extreme left-skewed (zero-inflated) distributions in L1 and L2, pulling the dataset toward the $\mu = 0.30$ target. L3 constraints ensure high-difficulty rates are balanced across both compliance and violation labels.

- **Stage A (difficulty-only).** Before verdicts exist, the refiner sees only (x, p_k, d_k) triples and enforces L2 (per-input difficulty ratio) jointly with zero-row reduction and the difficulty-only slice of L4; L1 and L3, and the verdict-dependent checks within L4, are skipped entirely because they require v_k. The output of this stage is the difficulty-balanced pool that is then passed to the reasoning/verdict-generation stage (Stage 2 above) to obtain v_k for every surviving pair.
- **Stage B (full curation).** Once verdicts are available, the refiner re-runs on the same pool, now with all four levels active in a convergence loop: L1+L2 joint greedy pruning, then zero-row reduction, then L3, then L4, repeated for up to a fixed number of rounds until every active level's Wasserstein distance to its target is within tolerance or a round produces no further change.

Hyperparameter Search and Configuration Selection To determine the optimal parameters for the Policy-Distribution Refiner, we run an extensive hyperparameter search across 16 distinct configurations independently for both the SFT and GRPO datasets. The objective is to find a configuration that optimally smoothes out structural imbalances—specifically, the heavy left-skew (zero-inflation)



(a) Matched Policies per Input



(b) L4: Per-category Difficulty Alignment

Figure 6: Diagnostics for GRPO pruning. The top plot shows how the number of matched policies per input is reduced after pruning in order to achieve desired difficulty and violation ratios, while the L4 bar chart shows individual semantic categories adhering to the global difficulty target.



(a) L1: SFT Violation Ratio

(b) L2: SFT Difficulty Ratio

(c) L3: Within-Compliance Difficulty

(d) L3: Within-Violation Difficulty

Figure 7: SFT dataset curation. The refiner mitigates severe skewness in the raw data, aligning violations ($\mu = 0.30$) and difficulty ($\mu \approx 0.17$) properly within tolerance limits.

where inputs overwhelmingly match with low-difficulty policies or non-violations—without aggressively decimating the dataset size or destroying category diversity.

We experiment with varying target means (μ), standard deviations (σ), and tolerance boundaries for both difficulty and violation ratios. Our configurations ranged from strict baseline bounds to heavily relaxed tolerances and shifted difficulty/violation means.

Ultimately, the configuration below provided the best structural balance across all four pruning levels (L1–L4). By slightly relaxing the target difficulty mean while maintaining strict bounds on violations, this configuration effectively lifted the distributions away from the extreme left-skew while preserving a robust and diverse pool of policies per input.

The chosen parameters are as follows:

- **SFT:** Difficulty $\mu = 0.175$, $\sigma = 0.10$, tolerance$= 0.10$; Violation $\mu = 0.30$, $\sigma = 0.10$, tolerance$= 0.10$.
- **GRPO:** Difficulty $\mu = 0.30$, $\sigma = 0.15$, tolerance$= 0.10$; Violation $\mu = 0.30$, $\sigma = 0.10$, tolerance$= 0.10$.

Note: GRPO inherently targets a higher difficulty distribution compared to SFT to facilitate better reasoning optimization.

Visualizing the Pruning Efficacy (GRPO). Figures 5 and 6 demonstrate the refiner's impact under our aforementioned hyperparameter configuration on the GRPO split. Before pruning (red), the L1 (violation) and L2 (difficulty) distributions exhibit massive spikes near 0%. After pruning (teal), these zero-row spikes are significantly reduced, and the remaining data aligns much more closely with our target Gaussians (Figure 5). Furthermore, as seen in the L3 plots, the pipeline successfully brings within-compliance and within-violation difficulty ratios into the target $\pm 10\%$ tolerance, preventing difficulty from being confounded with verdicts. Figure 6 confirms that local difficulty constraints are met across a wide variety of specific policy categories (L4).

Visualizing the Pruning Efficacy (SFT). Similar positive outcomes were observed on the SFT split. Because SFT requires a slightly lower difficulty baseline to preserve standard instructive behavior, our chosen configuration uses a target mean of $\mu = 0.175$. As shown in Figure 7, the pre-pruning SFT dataset was heavily dominated by 0% violation and 0% high-difficulty inputs.



(a) Matched Policies per Input



(b) L4: Per-category Difficulty Alignment

Figure 8: Diagnostics for SFT pruning. The top plot shows how the number of matched policies per input is reduced after pruning in order to achieve desired difficulty and violation ratios, while the L4 bar chart shows individual semantic categories adhering to the global difficulty target.

The refiner efficiently bounded these metrics, resulting in a robust, balanced subset suitable for supervised fine-tuning.

Additional Pruning: Shifting from SFT to GRPO. Notice that to achieve a higher ratio of difficulty and violations, the GRPO set number of matched policies per input drops significantly. We want a higher ratio of matched policies per input in GRPO compared to SFT and thus, prune the data further by shifting a subset of SFT datapoints into the GRPO sets for train and dev respectively. We specifically sample from the set of datapoints with greater than or equal to 9 policies per input and a difficulty mean greater than or equal to 0.25 to shift from SFT-train into GRPO-train, and similarly for SFT-validation into GRPO-validation. The before (red) and after (green) depict this shift in number of matched policies per input.

A.7 Per-Category F1 Breakdown

Figure 10 shows the relative improvement of SFT and GRPO for Gemma4-E4B model across some top-level safety categories based on evaluations on the dynamic-policy test set. We can observe that overall, the RL stage introduces the most lift in per-category metrics, with 'Malware, Hacking Cyberattack' and 'Disinformation Mininformation' gaining the most improvement boost.



(a) SFT Train # of Matched Inputs

(b) GRPO Train # of Matched Inputs



(c) SFT Dev # of Matched Inputs



(d) GRPO Dev # of Matched Inputs

Figure 9: An additional round of pruning on SFT Train/Dev and GRPO Train/Dev, defined by a shift of difficult datapoints with a high matched number of policies from SFT into GRPO training sets. This was done with the purpose of (1) increasing the matched number of policies in GRPO sets, and (2) enforcing higher difficulty in GRPO sets.



Figure 10: Per-category F1 score breakdown across eight safety taxonomies comparing BASE, SFT, and RL AdaGuard models.

A.8 AdaGuard Prompt

AdaGuard Prompt

You are a guardian model and your job is to check whether the user textual input provided under **Input Data** complies with each of the policies provided under **Policies**.
You must evaluate Input Data against each numbered policy independently and make a determination if Input Data constitutes a violation of any aspect(s) or scope(s) of the respective policy.

Input Data Interpretation:

- If Input Data contains a single utterance, treat it as a single user query or message and evaluate it directly against each policy.
- If Input Data contains a multi-turn conversation, pay attention to all "User" turns of the conversation and consider all of them collectively against each policy when making your determination.

In order to generate your response, you must pay close attention to the reasoning mode provided under **Mode**. The reasoning mode heavily dictates how you curate your response. The following are the three types of reasoning mode:

- reasoning_off: Directly output your final answer without any reasoning. For each policy, output only the verdict token (*Violation* or *Compliance*). No other fields are included.
- reasoning_on: Always generate all reasoning fields for every policy, in the following structure and order:
  - input_understanding: A single top-level field that appears exactly once before all per-policy blocks. Provide step-by-step reasoning that dissects the different scopes, aspects, nuances, and intents of Input Data as a whole.
  - For each numbered policy, generate the following three fields in order:
    - policy_understanding: Step-by-step reasoning understanding the different scopes and requirements outlined in that specific policy description, considered independently of all other policies.
    - input_compliance_understanding: Step-by-step reasoning, leveraging the analysis in input_understanding and policy_understanding for this policy only, focusing on arriving at a resolution on whether or not Input Data complies with or violates this specific policy. Treat this analysis in isolation from all other policies.
    - answer: The final compliance or violation verdict for this policy. The verdict is *Violation* if Input Data violates ANY of the scopes outlined in the policy description. The verdict is *Compliance* only if Input Data complies with ALL scopes outlined in the policy description. Output exactly one of these two tokens.
- autoreasoning: Generate the top-level input_understanding field (same as reasoning_on). Then for each numbered policy, first generate a *difficulty* field:
  - If difficulty is High: also generate policy_understanding and input_compliance_understanding for that policy, followed by answer.
  - If difficulty is Low: output only `answer` for that policy, with no additional reasoning fields.

Output Format: The final answer MUST follow the expected output format shown below, using exactly the verdict tokens shown. In these examples, imagine there are 3 Policies.

For **autoreasoning**, if you determine the first and third policies as Difficult in relation to Input Data, then generate your response in the following way:

```
{
  "input_understanding": "overall understanding of the input
    provided here",
  "1": {
    "difficulty": "High",
    "policy_understanding": "understanding of the policy scope
    provided here",
    "input_compliance_understanding": "understanding of how the
    input relates to the policy provided here",
    "answer": "Violation"
  },
```

```
    "2": {
      "difficulty": "Low",
      "answer": "Violation"
    },
    "3": {
      "difficulty": "High",
      "policy_understanding": "understanding of the policy scope
      provided here",
      "input_compliance_understanding": "understanding of how the
      input relates to the policy provided here",
      "answer": "Compliance"
    }
  }
```

For **reasoning_on**:

```
  {
    "input_understanding": "overall understanding of the input
      provided here",
    "1": {
      "policy_understanding": "understanding of the policy scope
      provided here",
      "input_compliance_understanding": "understanding of how the
      input relates to the policy provided here",
      "answer": "Violation"
    },
    "2": {
      "policy_understanding": "understanding of the policy scope
      provided here",
      "input_compliance_understanding": "understanding of how the
      input relates to the policy provided here",
      "answer": "Violation"
    },
    "3": {
      "policy_understanding": "understanding of the policy scope
      provided here",
      "input_compliance_understanding": "understanding of how the
      input relates to the policy provided here",
      "answer": "Compliance"
    }
  }
```

For **reasoning_off**:

```
  {
    "1": {
      "answer": "Violation"
    },
    "2": {
      "answer": "Violation"
    },
    "3": {
      "answer": "Compliance"
    }
  }
```

content_template:
Input Data:
Policies:
Mode:

A.9 QUALITY RUBRICS

Quality Reward Judge

You are a reward judge agent. Your job is to assess the quality of a guardrail model's chain-of-thought reasoning, which is structured across three distinct components. Each component has a specific analytical purpose and is scored independently.

You will be given:

- **Input Data:** the user message or agent output being evaluated.
- **Policy:** the specific policy being checked.
- **Input Understanding:** the model's analysis of what the input is actually asking or doing.
- **Policy Understanding:** the model's analysis of what this specific policy requires.
- **Input Compliance Understanding:** the model's reasoning about whether the input violates the policy.

Any component may be marked `NONE` if absent — score it 0 and move on.

COMPONENT 1 — Input Understanding

Purpose: Has the model correctly decoded what the input is truly asking or doing? This matters most when the input is obfuscated, indirect, encoded, or embeds its true intent beneath surface framing.

Rubric 1a — Decoding Accuracy (weight 0.50): Does the model arrive at the correct interpretation of the input's true request or intent?

- **0:** Not present (`NONE`).
- **1:** Fundamentally misreads the input — wrong topic, wrong actor, wrong action.
- **2:** Partially correct but misses a material aspect of what is being requested.
- **3:** Correct interpretation reached but through imprecise or underspecified reasoning.
- **4:** Correct and clearly articulated, with minor omissions.
- **5:** Fully accurate — the true intent is identified, any obfuscation is explicitly decoded, and the decoded request is stated precisely enough that it could stand alone as an input.

Rubric 1b — Surface vs. True Intent Distinction (weight 0.50): When there is a gap between what the input literally says and what it is actually asking, does the model recognize and articulate that gap? (For straightforward inputs with no obfuscation, score this 5 automatically.)

- **0:** Not present (`NONE`).
- **1:** Treats the surface framing as the true intent without questioning it.
- **2:** Notes that something seems off but does not resolve it.
- **3:** Identifies the gap but only partially resolves it (e.g., notes encoding but does not decode fully).
- **4:** Correctly identifies and resolves the gap with minor imprecision.
- **5:** Explicitly distinguishes surface framing from true intent and resolves the gap cleanly.

COMPONENT 2 — Policy Understanding

Purpose: Has the model correctly and specifically understood what this policy prohibits, permits, and where its boundaries lie?

Rubric 2a — Scope Accuracy (weight 0.40): Does the model state what the policy actually covers — no more, no less?

- **0:** Not present (`NONE`).
- **1:** Fundamentally wrong about what the policy covers (describes a different policy or inverts it).
- **2:** Correct in general but materially over- or under-states the scope.
- **3:** Mostly accurate scope but omits or mischaracterizes a clause that is relevant to this input.
- **4:** Accurate scope with minor imprecision that does not affect this verdict.

- **5:** Precise statement of the policy's scope, including exceptions where relevant, and correctly identifies which clause(s) are most relevant to the input being evaluated.

Rubric 2b — Exception and Nuance Recognition (weight 0.30): Does the model identify and correctly apply any exceptions, carve-outs, or contextual conditions stated in the policy (e.g., "except for academic context")? (If the policy has no exceptions, score this 5 automatically.)

- **0:** Not present (`NONE`).
- **1:** Ignores an exception that is directly material to this case.
- **2:** Mentions an exception exists but misapplies or mischaracterizes it.
- **3:** Identifies the exception but does not evaluate whether it applies to this input.
- **4:** Correctly evaluates the exception with a minor omission.
- **5:** Correctly identifies all relevant exceptions and evaluates whether each applies.

Rubric 2c — Specificity to This Policy (weight 0.30): Is the policy understanding grounded in the actual text of this policy, or is it a generic paraphrase that could describe many policies?

- **0:** Not present (`NONE`).
- **1:** Generic — could describe any safety policy.
- **2:** Mentions the policy's topic area but no specific clauses or conditions.
- **3:** References the policy's key prohibition but not its specific framing or conditions.
- **4:** Specific and grounded, with minor generality.
- **5:** Directly engages with the particular language and conditions of this policy. A different policy would produce a substantively different analysis.

COMPONENT 3 — Input Compliance Understanding

Purpose: Has the model correctly and rigorously resolved whether the (decoded) input violates the policy, using both the input understanding and policy understanding as premises?

Rubric 3a — Reasoning Chain Integrity (weight 0.40): Does the compliance conclusion follow necessarily from the input and policy analysis, or does it appear to be asserted independently?

- **0:** Not present (`NONE`).
- **1:** Conclusion is disconnected from the preceding reasoning — could be flipped without changing any prior step.
- **2:** Weak connection — reasoning gestures toward the conclusion but does not establish it.
- **3:** Directionally supported but contains a significant gap or skipped step.
- **4:** Solid chain with one minor unstated assumption.
- **5:** Airtight — the verdict is the only conclusion consistent with the stated premises. No gaps, no logic leaps, no hallucinated rules.

Rubric 3b — Deciding Factor Identification (weight 0.35): Does the model identify the specific aspect of the (decoded) input that determines whether the policy is violated, rather than making a general comparison?

- **0:** Not present (`NONE`).
- **1:** Does not identify any deciding factor — just asserts compliance or violation.
- **2:** Identifies the general topic area but not the specific element that triggers or does not trigger the policy.
- **3:** Identifies the deciding factor but does not fully explain why it is decisive.
- **4:** Clearly identifies and explains the deciding factor with minor imprecision.
- **5:** Precisely identifies the deciding factor, explains why it is decisive under this policy, and distinguishes it from non-decisive aspects of the input.

Rubric 3c — Policy Fidelity (weight 0.25): Does the compliance reasoning stay faithful to the actual policy, or does it apply rules that are not in the policy, ignore rules that are, or import assumptions from other policies?

- **0:** Not present (`NONE`).
- **1:** Applies a rule that is not in this policy, or ignores a rule that clearly is.
- **2:** Mostly faithful but makes one material assumption not supported by the policy text.
- **3:** Faithful but applies the policy at the wrong level of specificity (too broad or too narrow).

- **4:** Faithful with a minor unstated assumption that does not affect the verdict.
- **5:** Fully faithful — only rules stated in or clearly implied by the policy are applied.

OUTPUT FORMAT

Return a single JSON object with integer scores (0–5) for each rubric. 0 means the component was absent (NONE). No other text.

```
{
  "input_understanding": {
    "decoding_accuracy": <0-5>,
    "surface_vs_true_intent": <0-5>
  },
  "policy_understanding": {
    "scope_accuracy": <0-5>,
    "exception_nuance": <0-5>,
    "specificity": <0-5>
  },
  "input_compliance_understanding": {
    "reasoning_chain_integrity": <0-5>,
    "deciding_factor": <0-5>,
    "policy_fidelity": <0-5>
  }
}
```

Content Template:

Input Data: "{input}"
Policy: "{policy}"
Input Understanding: "{input_understanding}"
Policy Understanding: "{policy_understanding}"
Input Compliance Understanding: "{input_compliance_understanding}"

A.10 Reward Function Details

This appendix gives the full definition of every GRPO reward term of Eq. 2, the rollout-parsing signals they consume, and the alternative designs that were explored but not adopted (the flat discrete correctness rule, the two log-probability calibration variants, and the additive quality reward). A rollout o is parsed into K per-policy blocks with per-policy verdict $\hat{v}_k \in \{\text{COMPLIANCE}, \text{VIOLATION}, \perp\}$ ($\perp$ = missing or unrecognized), predicted difficulty $\hat{d}_k \in \{\text{HIGH}, \text{LOW}, \perp\}$, and teacher difficulty d_k.

Group Reward-Decoupled (GDPO) advantage normalization. The components of Eq. 2 differ in scale, variance, and firing rate: R_{format} is dominated by rare but large hard-gate penalties, R_{reason} moves only when the reasoning decision changes, and R_{correct} can vary drastically across different examples and throughout training. Collapsing them into one entangled scalar and group-normalizing it, similar to the standard GRPO advantage, makes the advantage a function of whichever component carries the largest within-group variance at that step. We therefore adopt GDPO (Liu et al., 2026), which normalizes each reward stream independently within its own GRPO group before combining them. For reward component s and across the group of G rollouts sharing a prompt,

$$A_i^{(s)} = \frac{r^{(s)}(q,o_i) - \text{mean}\left(\{r^{(s)}(q,o_j)\}_{j=1}^{G}\right)}{\text{std}\left(\{r^{(s)}(q,o_j)\}_{j=1}^{G}\right) + \epsilon_{\text{std}}}, \qquad \widetilde{A}_i = \sum_s w_s A_i^{(s)}, \qquad \hat{A}_i = \frac{\widetilde{A}_i - \mu_B}{\sigma_B + \epsilon_{\text{batch}}} \tag{7}$$

where $r^{(s)}(q,o_i)$ is the raw reward value for objective s on rollout i. The individual normalized advantage dimensions are aggregated using their respective objective weights. To prevent variance collapse and maintain a consistent advantage scale regardless of the number of reward functions, a final batch-level normalization is applied across all samples in the mini-batch B, where μ_B and σ_B denote the empirical mean and standard deviation of the aggregated advantage estimates $\{\widetilde{A}_j\}$ calculated across all tokens/rollouts within the mini-batch B. Because each $A_i^{(s)}$ is a complete, unbiased

Algorithm 1: ADAGUARD training.

Input: SFT set $\mathcal{D}_{\text{SFT}}$, GRPO set $\mathcal{D}_{\text{GRPO}}$, base model π_θ, group size n
Output: Adaptive-reasoning input-moderation guardrail π_θ
`// Stage 1: SFT across the three reasoning modes`
Expand each annotated example into three rows, one per mode $m \in \{$ `reasoning_off`, `reasoning_on`, `autoreasoning` $\}$
Fine-tune π_θ on $\mathcal{D}_{\text{SFT}}$ with the DFT loss
`// Stage 2: single-rollout GRPO`
Initialize the GRPO actor from the SFT checkpoint
foreach *prompt* $(x, P, m) \in \mathcal{D}_{GRPO}$ **do**
  Sample a group of n rollouts $\{o^{(j)}\}_{j=1}^{n} \sim \pi_\theta(\cdot \mid x, P, m)$
  foreach *rollout* $o^{(j)}$ **do**
    Parse into K per-policy blocks; extract $\hat{v}_k, \hat{d}_k, a_k, f_k$
    Sample a `reasoning_off` counterfactual for each block with $\hat{d}_k = \text{HIGH} \wedge a_k$; score $r_{\text{CF}}(k)$ `// Eq. 16`
    Fold the judge's quality q into each judged block: $r_c \leftarrow r_c \cdot \text{mult}(r_c, q, u)$ `// Eq. 6`
    Compute $R^{(j)}_{\text{format}}, R^{(j)}_{\text{correct}}, R^{(j)}_{\text{reason}}$ `// Eq. 2 components`
  end
  foreach *component* $c \in \{format, correct, reason\}$ **do**
    $\hat{A}^{(j)}_c \leftarrow \big(R^{(j)}_c - \text{mean}_j R^{(j)}_c\big) / \big(\text{std}_j R^{(j)}_c + \varepsilon\big)$ `// GDPO: per-component group normalization`
  end
  $\hat{A}^{(j)} \leftarrow \text{whiten}\big(\sum_c w_c \hat{A}^{(j)}_c\big)$ `// Eq. 7`
  Update θ with the GRPO objective using $\{\hat{A}^{(j)}\}$
end

group-relative advantage estimate in its own right, every term casts an equal-variance "vote" regardless of raw magnitude: a batch in which format scores happen to vary more than verdict correctness cannot let formatting overwhelm the correctness signal as an artifact of scale.

The overall loss function optimized by GDPO combines the PPO-style (Schulman et al., 2017) clipped surrogate objective with a token-level KL penalty against a reference model π_{ref}:

$$\mathcal{L}_{\text{GDPO}}(\theta) = -\mathbb{E}_{(q,o_j)\sim\mathcal{D},\{o_j\}_{j=1}^{G}\sim\pi_{\theta_{\text{old}}}} \left[\frac{1}{G} \sum_{j=1}^{G} \frac{1}{|o_j|} \sum_{t=1}^{|o_j|} \left(\min \left(\frac{\pi_\theta(o_j^t \mid q, o_j^{<t})}{\pi_{\theta_{\text{old}}}(o_j^t \mid q, o_j^{<t})} \hat{A}_j, \text{clip} \left(\frac{\pi_\theta(o_j^t \mid q, o_j^{<t})}{\pi_{\theta_{\text{old}}}(o_j^t \mid q, o_j^{<t})}, 1-\epsilon, 1+\epsilon \right) \hat{A}_j \right) - \beta\, \mathcal{D}_{\text{KL}}\big(\pi_\theta \,\|\, \pi_{\text{ref}}\big) \right) \right] \tag{8}$$

CoT-Presence Signals. For the structured JSON schema, the full CoT traces when expected in `reasoning_on` mode (`input_understanding` η, `policy_understanding` η, `input_compliance_understanding` χ_k), yield the following CoT presence indicators

$$\begin{aligned} a_k &= \mathbb{1}[\psi_k \neq \varnothing] \vee \mathbb{1}[\chi_k \neq \varnothing], \\ f_k &= \mathbb{1}[\psi_k \neq \varnothing] \wedge \mathbb{1}[\chi_k \neq \varnothing] \wedge \mathbb{1}[\eta \neq \varnothing], \end{aligned} \tag{9}$$

where a_k fires if the model reasoned *at all* about policy k, while f_k additionally requires the shared input-understanding trace, so that an omitted top-level ι is penalized as partial CoT rather than going unscored.

Format reward. R_{format} owns all schema/formatting signals. Let G be the number of emitted blocks and let the *verdict coverage* be the fraction of the K requested policies with a parseable

verdict,

$$\rho \;=\; \frac{1}{K}\sum_{k=1}^{K} \mathbb{1}[\hat{v}_k \in \{\textsc{Compliance}, \textsc{Violation}\}]\,. \tag{10}$$

A rollout is *hard-gated* to $R_{\text{format}} = \text{PARSE_PENALTY} = -1.5$ if it is unparseable, if $\rho = 0$, if $G \geq 2K$, or if the amount of extra-schema "babble" exceeds $\beta_{\max}$ (default 500 non-whitespace characters). Otherwise R_{format} is a weighted combination of four sub-scores. Content validity applies a step-linear curve to coverage,

$$g_{\text{cv}}(\rho) = \begin{cases} -1.5 + 1.5\,\rho, & 0 < \rho < 0.5 \quad \text{(steep penalty)}, \\ -0.75 + 3\,(\rho - 0.5), & 0.5 \leq \rho < 0.75 \quad \text{(recovery)}, \\ 4\,(\rho - 0.75), & 0.75 \leq \rho \leq 1 \quad \text{(good zone)}, \end{cases} \tag{11}$$

so $g_{\text{cv}} \in [-1.5, +1.0]$. A block-count penalty and a numbering penalty are pure penalties (zero at the correct count/ordering, never rewarded),

$$g_{\text{blk}} = \begin{cases} 0, & G = K, \\ -\min\big((\frac{G-K}{3})^{1.2},\, 1\big), & G > K, \\ -\frac{K-G}{K}, & G < K, \end{cases} \qquad g_{\text{num}} = \begin{cases} 0, & \text{numbering } 1, \ldots, K \text{ exact}, \\ -\big(1 - \frac{n_{\text{correct}}}{K}\big), & \text{otherwise}, \end{cases} \tag{12}$$

where n_{correct} is the count of position-correct block numbers. The babble term rewards a clean response ($\beta \leq \beta_0$, $\beta_0 = 10$ trailing characters) and otherwise penalizes extra-schema characters β,

$$g_{\text{bab}} = \begin{cases} +1, & \beta \leq \beta_0, \\ -\min\big((\frac{\beta-\beta_0}{\beta_{\max}})^{1.1},\, 1.5\big), & \beta_0 < \beta \leq \beta_{\max}, \end{cases} \qquad \tilde{g}_{\text{bab}} = \begin{cases} \rho\, g_{\text{bab}}, & g_{\text{bab}} > 0, \\ g_{\text{bab}}, & g_{\text{bab}} \leq 0, \end{cases} \tag{13}$$

where the *structural multiplier* ρ scales down the positive babble reward when verdict coverage is sparse (but never amplifies the penalty). The format reward is then

$$R_{\text{format}} \;=\; 0.80\, g_{\text{cv}} \;+\; 0.20\, \tilde{g}_{\text{bab}} \;+\; 0.20\, g_{\text{blk}} \;+\; 0.15\, g_{\text{num}}, \tag{14}$$

with a ceiling of $+1.0$ (perfect coverage, no babble, correct count and numbering); the additive penalties can drag it below the -1.5 gate value, but the hard gates catch the worst-formed rollouts first. Difficulty tags are deliberately *not* scored here — they are owned by the reasoning reward.

Correctness reward: the flat discrete fallback. R_{correct} is the sole verdict-bearing term. On the blocks CF-CORR does not cover (predicted-LOW blocks, and any committed-reasoning block whose counterfactual is unavailable) it falls back to the flat discrete rule below, which is also the *alternative* baseline design used when CF-CORR is ablated off entirely. It hard-gates to $\text{GATE_PENALTY} = -1.5$ on an unparseable rollout; otherwise each block earns

$$c_k = \begin{cases} C_{\text{cor}} = +1.0, & \hat{v}_k = v_k \quad \text{(correct)}, \\ C_{\text{wr}}^{\text{cot}} = -1.0, & \hat{v}_k \neq v_k \text{ and } a_k \quad \text{(wrong } \textit{after} \text{ reasoning)}, \\ C_{\text{wr}}^{\text{no}} = -0.5, & \hat{v}_k \neq v_k \text{ and } \neg a_k \quad \text{(wrong, no reasoning)}, \\ 0, & \hat{v}_k = \perp \text{ or block missing}, \end{cases} \qquad R_{\text{correct}} = \frac{1}{K}\sum_{k=1}^{K} c_k. \tag{15}$$

The asymmetry $C_{\text{wr}}^{\text{cot}} < C_{\text{wr}}^{\text{no}}$ penalizes a model more for confidently *rationalizing* an incorrect verdict than for a terse wrong guess. This is where the "did reasoning help?" differential lives: keeping it in the single verdict-bearing reward lets R_{reason} stay purely *decision-only* (Eqs. 18–20), so reasoning behavior and verdict correctness are never double-counted. By default the per-block scores are aggregated by a class-balanced *macro* mean rather than the plain mean of Eq. 15: the mean of the per-block means taken within each ground-truth verdict class, so COMPLIANCE and VIOLATION weigh equally on a class-mixed rollout (removing the majority-class reward hack under significant class skew scenarios) and reduce to Eq. 15 on a single-class rollout.

Counterfactual reasoning-value reward (`CF-CORR`). On `autoreasoning` blocks where the model committed to reasoning ($\hat{d}_k = \text{HIGH}$ and a_k), Eq. 15's flat $C_{\text{cor}}/C_{\text{wr}}^{\text{cot}}$ score can optionally be replaced by a four-way outcome score that grades reasoning against a *counterfactual*: an independent reasoning-off completion of the identical (x, p_k) pair, sampled with the same decoding

parameters as the main rollout. Let $\hat{v}_k^{\text{off}}$ denote the counterfactual's verdict, and define the own/-counterfactual correctness indicators $\text{own}_k = \mathbb{1}[\hat{v}_k = v_k]$, $\text{off}_k = \mathbb{1}[\hat{v}_k^{\text{off}} = v_k]$. The replacement score is

$$c_k^{\text{cf}} = \begin{cases} C_{\text{cor}} + C_{\text{flip}}, & \text{own}_k = 1,\ \text{off}_k = 0 \quad (\textit{flip}\text{: reasoning fixed a wrong no-CoT verdict}), \\ u_k(d_k), & \text{own}_k = 1,\ \text{off}_k = 1 \quad (\textit{unnecessary}\text{: correct with or without reasoning}), \\ C_{\text{both}}, & \text{own}_k = 0,\ \text{off}_k = 0 \quad (\textit{both-wrong}), \\ C_{\text{broke}}, & \text{own}_k = 0,\ \text{off}_k = 1 \quad (\textit{broke}\text{: reasoning wrecked a correct no-CoT verdict}), \end{cases} \tag{16}$$

with $C_{\text{cor}} = +1.0$ (Eq. 15), $C_{\text{flip}} = +0.5$, $C_{\text{both}} = -0.75$, and $C_{\text{broke}} = -1.25$. The unnecessary outcome is conditioned on the *teacher* difficulty label d_k (not the model's own prediction $\hat{d}_k$, which is already pinned to HIGH to reach this branch), giving a floor on genuinely hard pairs and a cap on easy ones from the same term,

$$u_k(d_k) = \begin{cases} C_{\text{cor}}, & d_k = \text{HIGH} \quad \text{(teacher says hard: no discount)}, \\ C_{\text{cor}} - C_{\text{unnec}}, & d_k = \text{LOW} \quad \text{(teacher says easy: reasoning was genuinely gratuitous)}, \end{cases} \tag{17}$$

with $C_{\text{unnec}} = 0.2$. The *flip* outcome is deliberately left unconditioned on d_k: it only fires when the counterfactual was actually wrong, i.e. reasoning was objectively necessary on this instance — a self-verifying fact rather than a proxy needing a floor or cap, and precisely the case a teacher-Low pair that is secretly hard would produce. Eq. 16 replaces Eq. 15's score c_k only for blocks with $\hat{d}_k = \text{HIGH} \wedge a_k$ and an available, parseable counterfactual; predicted-LOW blocks and any block whose counterfactual is unavailable keep the standard score of Eq. 15 unchanged, and R_{correct} is still the mean of K per-block scores (Eq. 15), now with some blocks substituted by Eq. 16. The mechanism is exposed as a boolean flag that defaults to *off* for ablation safety and is *enabled* for every result reported here; when enabled, it is computed entirely from within-rollout information (the rollout's own verdict and its own paired counterfactual sample), consistent with the single-rollout reward design of Section 2.3.2.

Quality multiplier and the unnecessary-reasoning clamp. The reported configuration runs the reasoning-quality judge in *multiplier* mode rather than the additive mode: the judge's raw per-trace score $q \in [0, 5]$ (the component-weighted rubric mean, *before* the additive remap $Q(\cdot)$ of Eq. 21) becomes a coefficient on the block's correctness value rather than a free-standing fifth reward term. The magnitude dial $m(q)$ and its sign-aware, *unnecessary*-conditioned application $\text{mult}(r_c, q, u)$ are both given by Eq. 6 of Section 2.3.2, with $K = 0.5$, so $m(3) = 1.0$ (quality-neutral no-op), $m(5) = 1.5$, and $m(0) = 0.5$; a block with no scored trace takes $m = 1.0$. The block's final value is $r_c \cdot \text{mult}(r_c, q, u)$. The multiplier is applied *once*, *last* in the chain (so it acts on whatever value CF-Corr's Eq. 16 rewrite left behind), and *only* on blocks the judge actually scored — i.e. blocks that emitted a reasoning trace. A correctly-skipped predicted-LOW block emits no trace, so it never enters the judge's index set and never receives any multiplier at all; its value stays at exactly $C_{\text{cor}} = +1.0$. In this mode R_{quality} is *not* added to the reward vector of Eq. 2 and `quality_score` is dropped from GDPO's stream list, since counting it both inside R_{correct} and as its own normalized advantage would double-count it.

Table 8 enumerates every CF-Corr scenario against a good-quality ($q = 5$, $m = 1.5$) and a bad-quality ($q = 0$, $m = 0.5$) trace, using the reward constants $C_{\text{cor}} = 1.0$, $C_{\text{flip}} = 0.5$, $C_{\text{broke}} = -1.25$, $C_{\text{both}} = -0.75$, $C_{\text{unnec}} = 0.2$, $C_{\text{wr}}^{\text{no}} = -0.5$, and $K = 0.5$.

The derivations are direct. Row 1 ($r_c = +1.5$, $u = 0$, so $\text{mult} = m$): $1.5 \times 1.5 = +2.25$ and $1.5 \times 0.5 = +0.75$. Row 2 ($r_c = -1.25$, so $\text{mult} = \max(2 - m, 1)$): $-1.25 \times \max(0.5, 1.0) = -1.25$ and $-1.25 \times \max(1.5, 1.0) = -1.875$. Row 3 likewise: $-0.75 \times 1.0 = -0.75$ and $-0.75 \times 1.5 = -1.125$. Row 4 ($r_c = +1.0$, $u = 1$, so $\text{mult} = \min(m, 1)$): $1.0 \times \min(1.5, 1.0) = +1.0$ and $1.0 \times \min(0.5, 1.0) = +0.5$. Row 5 ($r_c = +0.8$, $u = 1$): $0.8 \times 1.0 = +0.8$ and $0.8 \times 0.5 = +0.4$. Rows 6–7 receive no multiplier.

Design invariant. At *every* quality level, row 4 $\leq$ row 6 (tying at $+1.0$ for good quality, $+0.5 < +1.0$ for bad) and row 5 $<$ row 6 strictly ($+0.8$ and $+0.4$ against $+1.0$). No amount of reasoning quality can make an unnecessary reasoning block outscore a correctly-skipped one: the $\min(m(q), 1.0)$ clamp lets the unnecessary cell only shrink from its already-discounted base, never grow past it.

Table 8: Every CF-Corr scenario (Eq. 16) under the sign-aware, *unnecessary*-aware quality multiplier of Eq. 6, at good quality ($q = 5 \Rightarrow m = 1.5$) and bad quality ($q = 0 \Rightarrow m = 0.5$). Rows 1–3 use the ordinary branches (m on correct, $\max(2 - m, 1)$ on wrong); rows 4–5 are the *unnecessary* cell and use the clamp $\min(m, 1.0)$; rows 6–7 emit no trace, are never judged, and receive no multiplier. The invariant that closes the amplification pathway is visible in the good-quality column: rows 4–5 ($+1.0$, $+0.8$) never exceed the correctly-skipped baseline of row 6 ($+1.0$), whereas the pre-fix unclamped $m(q)$ would have lifted them to $+1.5$ and $+1.2$.

#	Scenario (CF-CORR branch)	Base r_c	Good quality	Bad quality
1	Flip (own correct, off wrong)	$+1.5$	$+2.25$	$+0.75$
2	Broke (own wrong, off correct)	-1.25	-1.25 (clamped)	-1.875
3	Wrong-both (own wrong, off wrong)	-0.75	-0.75 (clamped)	-1.125
4	Unnecessary, teacher HIGH	$+1.0$	$+1.0$ (capped; $+1.5$ pre-fix)	$+0.5$
5	Unnecessary, teacher LOW	$+0.8$	$+0.8$ (capped; $+1.2$ pre-fix)	$+0.4$
6	Predicted-LOW, correct (never judged)	$+1.0$	$+1.0$	$+1.0$
7	Predicted-LOW, wrong (never judged)	-0.5	-0.5	-0.5

Without the clamp, rows 4–5 reach $+1.5$ and $+1.2$, both strictly above row 6's $+1.0$, which would train the model to reason gratuitously in preference to skipping correctly and would invert the intent of C_{unnec} entirely. The wrong-side clamp $\max(2 - m(q), 1.0)$ is the mirror image of the same principle: bad quality makes a wrong verdict's penalty harsher (rows 2–3, bad column), while good quality is prevented from *softening* it, since rewarding a well-written wrong answer is the "eloquent confabulation" failure mode.

Reasoning-decision reward. $R_{\text{reason}} = \frac{1}{K}\sum_k \phi_k$ is a decision-only, mode-conditioned score of whether the CoT behavior matched what the mode requires; missing blocks score $\phi_k = 0$ and an unparseable rollout hard-gates to GATE_PENALTY. For `reasoning_off` any CoT is unexpected,

$$\phi_k^{\text{off}} = \begin{cases} +1, & \neg a_k, \\ -1, & a_k, \end{cases} \tag{18}$$

while `reasoning_on` always expects the full trace, rewarding presence and penalizing partial or absent reasoning,

$$\phi_k^{\text{on}} = \begin{cases} +1, & f_k \text{ (full CoT)}, \\ -0.5, & a_k \wedge \neg f_k \text{ (partial CoT)}, \\ -1, & \neg a_k \text{ (no CoT)}. \end{cases} \tag{19}$$

The adaptive `autoreasoning` mode ties the reasoning decision to the model's *own* predicted difficulty $\hat{d}_k$, using the teacher difficulty d_k only as a floor. This is a decision-only score — verdict correctness is owned by R_{correct}, so it is not double-counted here:

$$\phi_k^{\text{auto}} = \begin{cases} -1.5, & \hat{d}_k = \perp \text{ (malformed difficulty tag)}, \\ +1, & \hat{d}_k = \text{HIGH} \wedge f_k, \\ -0.5, & \hat{d}_k = \text{HIGH} \wedge a_k \wedge \neg f_k, \\ -1, & \hat{d}_k = \text{HIGH} \wedge \neg a_k, \\ -1, & \hat{d}_k = \text{LOW} \wedge a_k \text{ (reasoned despite skipping)}, \\ -1.5, & \hat{d}_k = \text{LOW} \wedge \neg a_k \wedge d_k = \text{HIGH (lazy } \textit{and} \text{ wrong)}, \\ +1, & \hat{d}_k = \text{LOW} \wedge \neg a_k \wedge d_k = \text{LOW}. \end{cases} \tag{20}$$

Eq. 20 is the mechanism that makes the reasoning budget *adaptive*: the model is rewarded for committing to full CoT exactly when it declares a policy HIGH, and for skipping CoT when it declares LOW — but only if the teacher label agrees that the pair is easy.

$$\begin{aligned} &Q(0) = 0, \quad Q(1) = -\tfrac{Q_{\text{end}}}{2} = -0.75, \quad Q(2) = -\tfrac{Q_{\text{end}}}{6} \approx -0.25, \\ &Q(3) = 0, \quad Q(4) = \tfrac{Q_{\text{end}}}{2} = 0.75, \qquad Q(5) = Q_{\text{end}} = 1.5, \end{aligned} \tag{21}$$