Exact Visual Grounding Strengthens Visual Information Utilization in Vision-Language Models

Anonymous authors
Paper under double-blind review

Abstract

Modern vision-language models (VLMs) achieve strong semantic reasoning yet remain unreliable on questions requiring precise visual evidence, such as exact counts, distances, or geometric relations. Broad multimodal pre-training provides rich semantic supervision, but rarely requires models to ground their predictions in exact visual evidence, leaving room for semantic and language priors to dominate when precise perception is required. To address this limitation, we introduce Exact Visual Grounding (EVG), a framework that provides explicit supervision for grounding answers in precisely controlled visual properties. EVG adopts an answer-first construction: it first samples a target answer, then renders an image whose relevant visual property exactly realizes that answer, and finally generates the corresponding question. This yields annotation-free supervision across 12 Color, Counting, and Geometric Measurement tasks, together with matched missing-object examples. Empirically, we find that training on these tasks consistently improves downstream multimodal performance. For example, on Qwen3.5-9B, EVG raises the macro-average across nine benchmarks from 60.06% to 63.90%, with similar gains across different model scales and backbones. To understand how EVG alters visual information processing, module grafting shows that the learned changes are distributed across both the vision and language stacks, while linear probing finds that task-relevant visual properties become more linearly accessible in middle-to-late language layers. Together, these results show that exact visual grounding can complement multimodal training by strengthening how VLMs extract and utilize fine-grained visual evidence.

1 Introduction

Vision-language models (VLMs) have advanced rapidly, achieving strong results on demanding multimodal benchmarks that probe knowledge, reasoning, and semantic understanding (Yue et al., 2024; Liu et al., 2023). Yet a growing body of evidence shows that this high-level competence coexists with a notable fragility at **precise low-level visual perception**: the same models that answer expert-level questions often fail to count objects, compare lengths, estimate an angle, or judge whether two shapes overlap (Rahmanzadehgervi et al., 2024; Rudman et al., 2025; Fu et al., 2024). Such precision is not incidental: reading a chart, interpreting a diagram, or following an instruction manual all hinge on extracting precise, quantitative visual detail, and current models frequently fall back on plausible language priors instead of measurement (Vo et al., 2025; Le Dinh Anh et al., 2026).

These failures point to a possible mismatch between what current VLMs are broadly trained to learn and what precise visual perception requires. Large-scale multimodal training strongly rewards semantic alignment, recognition, OCR, and instruction following, but tasks such as counting objects, measuring angles, or estimating geometric properties require the model to recover exact visual properties from the image. Public descriptions of the training mixtures for models such as Qwen (Yang et al., 2025), Gemma (Gemma Team, 2026), and LLaVA (Liu et al., 2023) emphasize captions, interleaved image–text documents, OCR, and instruction dialogues, which provide broad multimodal supervision but relatively little direct pressure for such exact visual readout. This suggests the need for training tasks that explicitly require models to extract precise visual properties, while remaining scalable and free from costly human annotation. Our central question is therefore: **how can we construct such tasks, and can the resulting capability generalize beyond them to downstream multimodal benchmarks?**

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: **Overview of Exact Visual Grounding (EVG). (a)** Modern VLMs answer high-level questions well yet fail at precise low-level visual perception, such as counting objects exactly. **(b)** EVG uses answer-first generation: for a task C and difficulty L, it samples an answer A, a target reference R, and distractors D; renders an image $I = \mathcal{I}_{C,L}(A, R, D)$ whose relevant property matches A; and forms a question $Q = \mathcal{Q}_{C,L}(R)$ that does not expose A. This process yields exact-answer supervision across 12 tasks in three families without human annotation. **(c)** Curriculum fine-tuning on this synthetic supervision transfers to downstream multimodal evaluation, improving the macro-average across nine benchmarks on Qwen3.5-9B.

We approach this question with Exact Visual Grounding (EVG), which turns precise visual grounding, the ability to make decisions from visual evidence, into a scalable training signal through answer-first generation (Figure 1). Instead of generating an image and then inferring its answer, EVG first specifies the target answer and the queried visual entity, together with distractors, and then renders an image that exactly satisfies this target before generating the corresponding question. The distractors require the model to identify the queried visual content among competing elements and extract the relevant property precisely. Because the answer is determined directly by the rendering parameters, the resulting supervision is exact by construction and requires neither human annotation nor upstream detectors. We instantiate EVG across 12 tasks spanning Color, Counting, and Geometric Measurement, and train the model with a difficulty curriculum that progressively increases the precision and complexity of the visual grounding tasks.

Empirically, EVG consistently improves downstream multimodal performance beyond the generated training tasks. On Qwen3.5-9B, it raises the macro-average across nine benchmarks from 60.06% to 63.90%. These gains remain robust across task-family ablations and generalize to Qwen3.5-4B (Yang et al., 2025), Gemma-4-12B (Gemma Team, 2026), and the agentic DeepEyesV2 model (Hong et al., 2026). We further analyze how EVG changes visual information processing: module grafting shows that the learned improvements are distributed across both the vision and language stacks, while linear probing reveals greater accessibility of task-relevant visual properties in middle-to-late language layers. A downstream subset analysis further shows that the gains are strongest on questions involving plots, charts, and geometric relations, where accurate answers depend directly on extracting visual evidence.

Our contributions can be summarized as follows:

- We introduce Exact Visual Grounding (EVG), an annotation-free, answer-first framework for generating precise visual grounding training tasks, covering 12 tasks across Color, Counting, and Geometric Measurement.
- We show that training on EVG consistently improves downstream multimodal performance across nine benchmarks, with gains that generalize across model scales, backbones, and an agentic VLM.

- We analyze how EVG changes visual information processing, showing contributions from both the vision and language stacks and greater linear accessibility of task-relevant visual properties in middle-to-late language layers.

2 Related Work

Low-level visual perception in VLMs. Despite strong performance on high-level semantic benchmarks (Yue et al., 2024; Liu et al., 2023), modern VLMs exhibit persistent failures on elementary, low-level visual tasks. Rahmanzadehgervi et al. (2024) show that state-of-the-art models are effectively "blind" to simple geometric primitives, struggling to count line intersections or judge whether shapes overlap. Rudman et al. (2025) further demonstrate that MLLMs are "shape-blind," achieving under 50% accuracy at counting polygon sides and relying on memorized associations rather than deliberate visual inspection. Diagnostic suites such as BLINK (Fu et al., 2024) and VLMs Are Biased (Vo et al., 2025) isolate these perceptual weaknesses and reveal a heavy reliance on language priors. Complementary mechanistic analyses characterize how such failures emerge within the model. Le Dinh Anh et al. (2026) find that count-relevant visual evidence is strongest at the modality-projection stage and weakens in later language layers as text priors become more influential. Our work extends this diagnostic literature by testing whether targeted procedural supervision improves precise low-level visual perception and transfers to downstream multimodal benchmarks.

Synthetic data for visual perception and reasoning. Procedurally generated data with exact ground truth has a long history in visual reasoning, beginning with CLEVR (Johnson et al., 2017), which used rendered scenes with programmatic annotations to diagnose compositional reasoning free of dataset bias. Domain randomization further shows that varying synthetic scene parameters can support transfer from rendered to real imagery (Tobin et al., 2017; Tremblay et al., 2018). Recent work leverages synthetic supervision to *improve* capabilities rather than merely measure them. SpatialVLM (Chen et al., 2024a) scales 3D spatial VQA by densely annotating real images with detection, depth, and segmentation pipelines, whereas our generator requires no real images or upstream detectors and obtains exact answers by construction. MAVIS (Zhang et al., 2025) shares our emphasis on programmatic correctness, using an automatic engine to synthesize math diagrams with guaranteed answers, though it targets mathematical reasoning rather than low-level perception. Most closely related, Rizzoli et al. (2025b) fine-tune VLMs on an exhaustive, balanced synthetic dataset for a single absolute-position task, where a single object is assigned to one of nine image regions, and observe transfer to the same task on real images. EVG provides a broader answer-first construction for synthetic supervision: it samples an exact, verifiable answer and instantiates it programmatically in an image. We implement this construction across 12 tasks in the Color, Counting, and Geometric Measurement families, use full-parameter fine-tuning with a difficulty curriculum and matched missing-object examples, and evaluate transfer across nine downstream multimodal benchmarks.

3 Exact Visual Grounding for Precise Visual Supervision

Current VLMs often rely on semantic or language priors when answering questions that require precise visual evidence (Rahmanzadehgervi et al., 2024; Rudman et al., 2025). Addressing this limitation requires training signals that explicitly demand exact visual readout. To provide such supervision at scale, we introduce Exact Visual Grounding (EVG), which constructs synthetic visual grounding tasks with controllable target properties, answers, distractors, and difficulty. To be specific, Section 3.1 introduces the answer-first generation process and the construction of the Color, Counting, and Geometric Measurement tasks. Section 3.2 then presents the curriculum used to progressively increase task difficulty during fine-tuning.

3.1 Constructing Exact Visual Grounding Tasks

To obtain precise visual supervision without relying on manual annotation, EVG generates each example by first specifying what visual property the model should recover and then constructing a scene that realizes it exactly. Formally, each example is an image, question, answer triplet (I, Q, A). Given a task C and difficulty level L, we sample a target answer $A \sim P_{C,L}$, together with a



(a) **Object Color**
Difficulty: D1
Q: What color is the filled ellipse?
A: darkgreen

(b) **Line Intersections**
Difficulty: D2
Q: How many interior intersections are formed?
A: 2

(c) **Relative Rotation**
Difficulty: D3
Q: What is the relative rotation of the two identical rectangles?
A: 24

(d) **Rectangle Aspect Ratio**
Difficulty: D3
Q: What is the aspect ratio of the green rectangle?
A: "missing"

Figure 2: Examples of EVG training data with varied image aspect ratios. The examples show a color-recognition question, an intersection counting question, a two-object comparison, and a missing-object question. Questions are shortened for readability; the full questions specify the answer format.

description R of the queried object and a set of distractors D. Here, $P_{C,L}$ denotes a calibrated distribution over valid answers for task C at difficulty level L, designed to prevent the model from exploiting distributional biases. The image is then rendered as $I = \mathcal{I}_{C,L}(A, R, D)$ such that the queried visual property is exactly determined by A, while the corresponding question is generated as $Q = \mathcal{Q}_{C,L}(R)$. Since the answer is specified through the underlying scene parameters rather than inferred from the rendered image, the resulting supervision is exact by construction. We further randomize rendering factors such as background color and image aspect ratio to prevent the model from associating answers with incidental visual patterns (Tobin et al., 2017; Tremblay et al., 2018).

We instantiate this formulation with 12 tasks spanning Color, Counting, and Geometric Measurement. The task set is designed to require different forms of visual readout, including identifying properties of individual objects, aggregating information across the full image, comparing relations between objects, and measuring properties of the scene itself. By controlling both the queried property and the surrounding visual context, these tasks isolate precise visual readout and require the model to recover the relevant evidence rather than rely on broad semantic recognition alone.

To expose the model to progressively harder visual grounding problems, each task is instantiated at three difficulty levels. From D1 to D3, the answer range becomes broader, more distractors are introduced, the scene geometry becomes more varied, the queried target is described more specifically, and numerical answers require finer precision. The full difficulty configurations are provided in Appendix Table 16.

We additionally include matched missing-object cases, constructed by removing only the queried target from an otherwise identical scene. This requires the model to determine whether the requested visual evidence is present before producing an answer, rather than answering by default. The default dataset contains 1000 examples for each task and difficulty level, with 10% of the final examples in applicable tasks assigned to the missing-object setting. Full task definitions, answer formats, and question templates are provided in Appendix J.

3.2 Learning from Exact Visual Grounding Tasks

The difficulty structure introduced above naturally suggests a progressive training strategy. Easier examples emphasize basic visual readout, such as estimating angles at coarse resolution or counting a small number of objects, whereas harder examples involve denser distractors, finer geometric distinctions, and more precise numerical outputs.

We fine-tune the pretrained VLM with standard next-token prediction, where the image and question are provided as input and the exact answer is used as the target response. Instead of mixing all difficulty levels from the beginning, training proceeds sequentially from D1 to D2 and then D3, with

each stage initialized from the checkpoint obtained at the previous stage. This progression allows the model to first learn relatively simple visual readout patterns before moving to examples with broader answer ranges, more distractors, greater geometric variation, and stricter output precision. Because EVG focuses on a specialized set of low-level perceptual skills, we additionally monitor performance on a held-out panel sampled from Vero-600K (Sarch et al., 2026) during training. This panel is used only for early stopping and checkpoint selection and is never used for optimization, helping preserve general multimodal performance while the model acquires stronger precise visual grounding capabilities.

4 Experiments

We evaluate whether EVG improves transfer beyond its generated tasks. We first report downstream performance on nine benchmarks with Qwen3.5-9B, and then assess generalization across model scales, backbones, task-family ablations, and the agentic DeepEyesV2 setting. Appendix I further compares EVG with the controlled synthetic supervision of Rizzoli et al. (2025b) under the same fine-tuning recipe.

4.1 Experimental Setup

We evaluate whether the visual grounding capabilities learned from EVG transfer beyond the generated training tasks to standard multimodal benchmarks. In the main text, we primarily report results on Qwen3.5-9B (Yang et al., 2025), while additional experiments on Qwen3.5-4B, Gemma-4-12B, and the agentic DeepEyesV2 model are provided in later sections and the appendix to assess generalization across model scales, backbones, and model types. Unless otherwise specified, we apply full-parameter fine-tuning with the three-stage D1 to D3 curriculum described in Section 3.2. Training uses a 10% missing-object rate, selected according to the ablation in Appendix Table 12, and takes approximately 10 hours on a single H20 GPU.

Our main evaluation covers nine multimodal benchmarks spanning general multimodal understanding, visual reasoning, chart and diagram interpretation, hallucination, and fine-grained visual perception. None of these test benchmarks overlap with the source benchmarks used in the held-out Vero-600K panel for checkpoint selection. On held-out generated examples, the base model performs poorly on precise low-level visual tasks, with accuracy decreasing consistently from D1 to D3. EVG substantially improves exact-match accuracy at every difficulty level and reduces mean relative error on numerical tasks. The same decreasing trend across difficulty levels after fine-tuning confirms that the D1–D3 tiers impose progressively harder visual demands (Appendix Tables 4 and 10).

4.2 Evaluation on Downstream Multimodal Benchmarks

Table 1: Transfer to downstream multimodal benchmarks on Qwen3.5-9B. Values are percentages and Δ denotes the change after EVG fine-tuning.

Benchmark	**Primary Metric**	**Base**	**EVG**	Δ (pp)
MMMU-Val (Yue et al., 2024)	accuracy	50.78	56.89	+6.11
MMStar (Chen et al., 2024b)	average	69.22	71.37	+2.15
AI2D (Kembhavi et al., 2016)	exact match	84.91	87.05	+2.14
ChartQA (Masry et al., 2022)	relaxed overall	86.28	86.96	+0.68
BLINK (Fu et al., 2024)	accuracy	62.38	65.66	+3.28
HallusionBench (Guan et al., 2024)	qAcc	47.91	49.23	+1.32
VLMs Are Biased (Vo et al., 2025)	accuracy	14.83	24.93	+10.10
VLMs Are Blind (Rahmanzadehgervi et al., 2024)	accuracy	86.50	91.87	+5.37
MMMU-Pro (Yue et al., 2025)	accuracy	37.69	41.16	+3.47
9-benchmark macro-average	mean	60.06	63.90	+3.84

Table 1 reports the main downstream results on Qwen3.5-9B. EVG improves performance on all nine benchmarks, raising the macro-average from 60.06% to 63.90%. The improvements span general multimodal understanding, diagram and chart reasoning, hallucination, and fine-grained

Image & Question	Base Model Response	EVG Model Response
 **Question**: From 2010 to 2019, is 2015 exported the least value of bread, biscuits, wafers, cakes and pastries from the UK?	Looking at the area chart... Observing the trend: - From 2010 to 2015, the export value is **increasing**. - Around 2015, there appears to be a **slight plateau or dip**... - After 2015, the value rises sharply again... So, between 2010 and 2019, the **lowest point in the export value occurs around 2015**... → **Yes, from 2010 to 2019, 2015 exported the least value...**	Looking at the area chart... From 2010 to 2019, we observe a general upward trend. Specifically, around 2015, the value is relatively flat or slightly increasing. However, **it is not the lowest point** between 2010 and 2019; in fact, the value in 2015 is **higher than in 2010**. Therefore, no, 2015 did not export the least value. The lowest value in that period was likely in 2010. → **Final Answer: No**

Figure 3: Qualitative HallusionBench example. The base model misreads the 2015 value as a local minimum, while the EVG model correctly recognizes that the 2015 value is higher than 2010.

visual perception, showing that the learned capability transfers beyond the synthetic tasks used for training. The largest gains are observed on VLMs Are Biased (Vo et al., 2025), MMMU-Val (Yue et al., 2024), VLMs Are Blind (Rahmanzadehgervi et al., 2024), and BLINK (Fu et al., 2024).

A common pattern among the larger improvements is that correct prediction depends strongly on reading the depicted visual evidence rather than relying on semantic priors. This is most apparent on VLMs Are Biased, where EVG improves accuracy by 10.10 pp. The benchmark deliberately modifies familiar visual concepts such as logos, flags, and standard diagrams, creating cases where prior knowledge conflicts with what is actually shown. The strong improvement in this setting suggests that EVG helps the model rely more faithfully on fine-grained visual evidence when semantic priors are misleading.

Figure 3 provides a representative example from HallusionBench (Guan et al., 2024). The base model incorrectly identifies the 2015 value as a local minimum in the chart, whereas the EVG-tuned model correctly recognizes that it is higher than the 2010 value. This example illustrates how improved visual readout can correct downstream reasoning errors that originate from inaccurate perception of the depicted evidence.

4.3 Ablations on Models and Task Families

We first examine whether the benefit of EVG generalizes beyond Qwen3.5-9B. As shown in Table 2(a), EVG consistently improves the nine-benchmark macro-average across different model scales and backbones. Qwen3.5-4B improves from 54.97% to 60.55%, while Gemma-4-12B improves from 52.01% to 54.09%. Together with the Qwen3.5-9B result, these experiments show that the benefit of exact visual grounding is not restricted to a particular model scale or backbone. Full per-benchmark results are provided in Appendix Tables 5 and 6.

We then examine which parts of the EVG task set contribute to downstream transfer. As shown in Table 2(b), we remove one task family at a time while keeping the total number of generated training examples fixed by redistributing examples across the remaining tasks. Removing any family reduces the nine-benchmark macro-average relative to the full EVG training set, with drops of 1.33, 0.66, and 0.34 percentage points when removing Counting, Geometric Measurement, and Color, respectively. The consistent degradation suggests that the three task families provide complementary supervision. Removing the staged curriculum also reduces downstream transfer (see Appendix G).

4.4 Exact Visual Grounding for Agentic Visual Reasoning

Furthermore, we examine whether EVG remains beneficial in an agentic setting, where the model can actively inspect an image through operations such as cropping or zooming before producing an answer. Such models improve visual reasoning not only by interpreting the current observation,

but also by deciding to acquire additional visual evidence. This makes them a useful testbed for evaluating whether stronger precise visual grounding can complement active visual exploration.

We apply EVG to DeepEyesV2-7B (Hong et al., 2026), starting from the released checkpoint and continuing full-parameter training with the same EVG curriculum. We evaluate on V*-Bench (Wu & Xie, 2024) and HRBench-4K (Wang et al., 2024) under the original image budgets and interaction limits. As shown in Table 2(c), EVG improves accuracy on both benchmarks. It also increases the frequency of valid cropping tool calls, from 19.13% to 26.25% on HRBench-4K and from 28.80% to 38.22% on V*-Bench.

The increase in crop usage suggests that EVG encourages the agent to more actively seek fine-grained visual evidence rather than answer from the initial observation alone. By acquiring additional local detail when needed, the model can ground its reasoning in more informative visual input, which is consistent with the accompanying gains in task accuracy. These results suggest that precise visual grounding can improve not only how visual evidence is interpreted, but also how actively an agent chooses to acquire it.

Table 2: Generalization and ablation results of EVG. (a) Nine-benchmark macro-average across different model scales and backbones. (b) Task-family ablation on Qwen3.5-9B with a fixed training-data budget. (c) Transfer to the agentic DeepEyesV2-7B model.

(a) Model Generalization

Model	Base	EVG
Qwen3.5-9B	60.06	63.90
Qwen3.5-4B	54.97	60.55
Gemma-4-12B	52.01	54.09

(b) Task-Family Ablation

Training Data	Macro	Δ Full
Full EVG	63.90	0.00
w/o Counting	62.57	−1.33
w/o Measurement	63.24	−0.66
w/o Color	63.56	−0.34

(c) Agentic Transfer

	HRBench-4K		V*-Bench	
Metric	Base	EVG	Base	EVG
Accuracy	71.75	74.00	81.68	82.20
Tool Rate	19.13	26.25	28.80	38.22

5 Understanding the Gains from Exact Visual Grounding

While the previous section establishes the effectiveness of EVG across downstream settings, the source of these gains remains unclear. We therefore investigate how exact visual grounding changes the model internally and how these changes relate to downstream behavior. Section 5.1 localizes where the learned improvements are expressed across the vision and language stacks. Section 5.2 examines whether task-relevant visual properties become more accessible in the model's hidden representations. Section 5.3 then studies whether the largest downstream gains occur on questions that explicitly depend on visual evidence.

5.1 Localizing the Improvement

To identify where the improvements induced by EVG are expressed within the model, we perform a module-replacement analysis based on model grafting (Bansal et al., 2021). We conduct this analysis on VLMs Are Blind (Rahmanzadehgervi et al., 2024), which directly evaluates the precise visual-perception skills targeted by EVG and shows a clear improvement from 86.50% to 91.87% on Qwen3.5-9B. We decompose the model according to its architecture into a vision stack, comprising the vision encoder and vision-language projection layer, and a language stack. To further localize the changes within the language model, we divide its 32 layers into four depth-wise quarters, corresponding to early, mid-early, mid-late, and late layers, and consider the input/output embeddings.

We consider two grafts. Forward grafting copies an EVG module into the base model, measuring how much of the 5.37 pp gain that module recovers. Reverse grafting copies a base module into the EVG model, measuring the change when its EVG counterpart is removed.

Table 3 indicates that EVG's effects are distributed across the visual and language components rather than confined to one module. Both complete-stack replacements produce nonzero shifts: the vision stack alone recovers 3.43 pp, while the complete language stack recovers 2.50 pp. Conversely, reverse-grafting the base vision stack costs 2.87 pp, and the base language stack costs 1.94 pp. These results indicate that the vision component contributes more here. Within the language model, the strongest isolated contribution comes from the early quarter (layers 0–7), which gains 1.12 pp forward

and loses 1.44 pp in reverse. Other LM quarters produce smaller shifts, while replacing the LM input/output embeddings changes accuracy by at most 0.14 pp. Together, these results indicate that transferable changes are distributed across the vision and language stacks and support our hypothesis that the early language layers make better use of visual features after EVG tuning, establishing a stronger foundation for subsequent processing.

Table 3: Full module-replacement results on VLMs Are Blind. Forward grafting replaces a base module with its EVG counterpart; reverse grafting replaces an EVG module with its base counterpart. The resulting scores localize where transferable changes are expressed under module replacement.

Grafted Module	**Forward (into Base)**	**Reverse (into EVG)**
None	86.50	91.87
Vision stack	89.93	89.00
Entire language stack	89.00	89.93
LM input/output	86.53	91.73
Language model (early quarter, layers 0–7)	87.62	90.43
Language model (mid-early quarter, layers 8–15)	87.00	91.54
Language model (mid-late quarter, layers 16–23)	86.90	91.62
Language model (late quarter, layers 24–31)	86.89	91.73

5.2 Probing the Linear Accessibility of Visual Properties

The grafting analysis identifies *where* EVG-induced changes are expressed, but leaves open *how* visual information is represented across language layers. We therefore use linear probes (Alain & Bengio, 2016; Hewitt & Liang, 2019) to measure how readily task-relevant visual properties can be recovered from the hidden states of the language model.

For each of the 12 EVG tasks, we collect 1,000 D3 examples and extract the final query-token representation from nine layers distributed across the 32-layer Qwen3.5-9B language model. For Geometric Measurement tasks, continuous answers are discretized into bins and treated as classification labels. At each layer, we train a multinomial logistic-regression probe with a fixed optimization budget of 20 iterations using an 80%/10%/10% train, validation, and test split. Keeping the probe capacity and optimization budget fixed allows us to compare how readily the corresponding visual property is accessible across layers and models. Appendix D.1 gives the target definitions, discretization boundaries, and complete probing protocol.



Figure 4: Layer-wise linear-probe accuracy. EVG increases the linear accessibility of visual properties primarily in middle-to-late language layers.

Figure 4 shows a clear depth-dependent pattern. The base and EVG models exhibit similar probe accuracy in the early language layers, but the curves begin to separate around layer 16. From approximately layer 20 onward, EVG consistently yields higher probe accuracy, with gains of roughly

9–12 percentage points and a maximum difference of 12.0 points at layer 28. At the final layer, EVG achieves higher probe accuracy on 11 of the 12 tasks.

The magnitude of this improvement varies across visual properties. The largest late-layer gains appear on tasks such as Rectangle Aspect Ratio, Grid Dimensions, and Object Count, where the difference reaches up to 28 percentage points. In contrast, properties that are already readily accessible in the base model, such as Object Color and Image Aspect Ratio, show smaller changes. Relative Rotation is the only task for which probe accuracy decreases in the late layers, possibly because a single-token linear probe is less suited to representing a relational property of this form.

Overall, EVG makes task-relevant visual properties substantially more linearly accessible in the middle-to-late language layers. Together with the grafting results in Section 5.1, this suggests that EVG changes both where visual information is processed and how explicitly it is represented within the language model. The two analyses therefore provide complementary evidence that the downstream gains are accompanied by systematic changes in visual information processing rather than being confined to the final output behavior.

5.3 Gains on Explicit Visual Questions

Section 5.2 shows that EVG makes task-relevant visual properties more accessible in the language-model representations. We next ask whether this representational change is reflected in downstream behavior, particularly on questions whose answers depend explicitly on visual evidence. To this end, we perform a subset analysis on 4,130 examples with aligned base and EVG predictions from MMMU-Val, MMMU-Pro, and MMStar.

Using only the question text and the presence of an image placeholder, we define a reproducible lexical partition that identifies questions explicitly requesting visual information. Each selected question is assigned to one of seven categories: projection and view, plot spatial structure, chart values and trends, geometric relation, explicit measurement, explicit image count, or diagram component reference. Questions that do not match these criteria form the remaining-item reference set. This procedure identifies 573 explicit visual-information requests.

EVG yields substantially larger improvements on this visually explicit subset. Accuracy increases from 36.82% to 42.58%, a gain of 5.76 percentage points, compared with a 3.12 point improvement on the remaining benchmark items. The largest gains occur on plot spatial-structure, chart value-and-trend, and geometric-relation questions, which improve by 8.14 points when combined. The remaining explicit categories show a smaller but still positive gain of 3.01 points. Detailed category-level results are reported in Appendix Table 7.

These results connect the representational findings in Section 5.2 to downstream behavior. EVG not only makes visual properties more accessible within the model, but also produces its largest behavioral gains on questions that most directly require extracting depicted visual structure.

6 Conclusion and Future Work

Modern VLMs excel at high-level semantic reasoning but struggle with precise low-level visual perception. We introduced Exact Visual Grounding (EVG), an answer-first pipeline that provides exact-answer synthetic supervision without human annotation. Across the evaluated settings, EVG improves average downstream benchmark performance across model scales, backbones, and agentic visual reasoning. The grafting and probing analyses connect these gains to changes across both model stacks and to greater linear accessibility of visual properties in the language model. Together, these findings show that targeted exact-answer supervision can complement broad multimodal training.

Because EVG is programmatic and amenable to scaling, it suggests several directions for future work. A natural next step is to move beyond simple, toy-like geometric renders toward more realistic training scenes, such as cluttered natural-image backgrounds, textured objects, and photographic compositions, so that the generated supervision more closely matches the appearance statistics of real-image benchmarks. Further directions include expanding the task taxonomy to 3D reasoning, spatial topology, and physics-based simulation; using EVG environments as verifiers for reinforcement learning of visual search strategies; and incorporating procedurally generated exact-answer visual tasks into multimodal pre-training rather than using them only for post-training.

AI use statement

Generative AI tools were used solely to improve the grammar, clarity, readability, and overall presentation of author-written text. Their use was limited to language editing, such as refining sentence structure, correcting grammatical errors, and suggesting clearer wording. They were not used to generate research ideas, develop the methodology, formulate scientific claims, conduct experiments or analyses, interpret results, or create code, data, figures, or references. All suggested edits were reviewed by the authors to ensure that they preserved the intended technical meaning and did not introduce unsupported claims or factual inaccuracies. The authors take full responsibility for the accuracy, originality, and final content of this paper.

Ethics statement

This work uses programmatically generated geometric images for training and publicly available models and benchmarks for evaluation. The generated data contain no human subjects, personal information, or sensitive content. We do not collect, release, or infer information about individuals. The method is intended to improve models' use of visual evidence; as with other capability-improving methods, downstream deployment should remain subject to appropriate application-specific safeguards.

Reproducibility statement

We provide the full EVG formulation and answer-first generation procedure in Section 3.1, and describe the training curriculum in Section 3.2. Evaluation benchmarks and experimental comparisons are reported in Sections 4 and 5. The appendix reports full in-domain and transfer results, training hyperparameters, curriculum and missing-object ablations, the controlled synthetic fine-tuning comparison, and detailed task-generation specifications, including rendering validity checks. The accompanying supplementary material includes the data-generation code, which reproduces the synthetic EVG tasks from a fixed random seed.

References

Guillaume Alain and Yoshua Bengio. Understanding intermediate layers using linear classifier probes. *arXiv preprint arXiv:1610.01644*, 2016.

Yamini Bansal, Preetum Nakkiran, and Boaz Barak. Revisiting model stitching to compare neural representations. In *Advances in Neural Information Processing Systems*, volume 34, pp. 225–236, 2021.

Boyuan Chen, Zhuo Xu, Sean Kirmani, Brain Ichter, Dorsa Sadigh, Leonidas Guibas, and Fei Xia. SpatialVLM: Endowing vision-language models with spatial reasoning capabilities. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 14455–14465, 2024a.

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, et al. Are we on the right way for evaluating large vision-language models? In *arXiv preprint arXiv:2403.20330*, 2024b.

Xingyu Fu, Yushi Hu, Boshi Li, et al. BLINK: Multimodal large language models can see but not perceive. In *European Conference on Computer Vision*, 2024.

Gemma Team. Gemma 4 technical report, 2026.

Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, Dinesh Manocha, and Tianyi Zhou. Hallusionbench: An advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

John Hewitt and Percy Liang. Designing and interpreting probes with control tasks. In *Proceedings of the 2019 conference on empirical methods in natural language processing and the 9th international joint conference on natural language processing (emnlp-ijcnlp)*, pp. 2733–2743, 2019.

Jack Hong, Chenxiao Zhao, ChengLin Zhu, Weiheng Lu, Guohai Xu, and Xing Yu. DeepEyesV2: Toward agentic multimodal model. In *International Conference on Learning Representations*, 2026.

Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C. Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2017.

Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. A diagram is worth a dozen images. In *European Conference on Computer Vision*, pp. 235–251, 2016.

Duy Le Dinh Anh, Patrick Irawan, and Tuan Van Vo. Counting to four is still a chore for VLMs. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7377–7385, 2026.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Xin Zhao, and Ji-Rong Wen. Evaluating object hallucination in large vision-language models. In *Proceedings of the 2023 conference on empirical methods in natural language processing*, pp. 292–305, 2023.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. In *Advances in Neural Information Processing Systems*, 2023.

Ahmed Masry, Jia Qing Tan, Shafiq Joty, Enamul Hoque, et al. ChartQA: A benchmark for question answering about charts with visual and logical reasoning. In *Findings of the association for computational linguistics: ACL 2022*, pp. 2263–2279, 2022.

Yannic Neuhaus and Matthias Hein. Repope: Impact of annotation errors on the pope benchmark. *arXiv preprint arXiv:2504.15707*, 2025.

Pooyan Rahmanzadehgervi, Logan Bolton, Mohammad Reza Taesiri, and Anh Totti Nguyen. Vision language models are blind. In *Asian Conference on Computer Vision*, 2024.

Massimo Rizzoli, Simone Alghisi, Olha Khomyn, Gabriel Roccabruna, Seyed Mahed Mousavi, and Giuseppe Riccardi. CIVET: Systematic evaluation of understanding in VLMs. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 4462–4480, 2025a.

Massimo Rizzoli, Simone Alghisi, Seyed Mahed Mousavi, and Giuseppe Riccardi. Synthetic stimuli, real gains: Rethinking VLM fine-tuning through fully controlled data generation. *arXiv preprint arXiv:2511.11440*, 2025b.

William Rudman, Michal Golovanevsky, Amir Bar, Vedant Palit, Yann LeCun, Carsten Eickhoff, and Ritambhara Singh. Forgotten polygons: Multimodal large language models are shape-blind. In *Findings of the Association for Computational Linguistics: ACL 2025*, 2025.

Gabriel Sarch, Linrong Cai, Qunzhong Wang, Haoyang Wu, Danqi Chen, and Zhuang Liu. Vero: An open RL recipe for general visual reasoning. *arXiv preprint arXiv:2604.04917*, 2026.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, 2017.

Jonathan Tremblay, Aayush Prakash, David Acuna, Mark Brophy, Varun Jampani, Cem Anil, Thang To, Eric Cameracci, Shaad Boochoon, and Stan Birchfield. Training deep networks with synthetic data: Bridging the reality gap by domain randomization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, 2018.

An Vo, Khai-Nguyen Nguyen, Mohammad Reza Taesiri, Vy Tuong Dang, Anh Totti Nguyen, and Daeyoung Kim. Vision language models are biased. In *arXiv preprint arXiv:2505.23941*, 2025.

Wenbin Wang, Liang Ding, Minyan Zeng, Xiabin Zhou, Li Shen, Yong Luo, and Dacheng Tao. Divide, conquer and combine: A training-free framework for high-resolution image perception in multimodal large language models. *arXiv preprint arXiv:2408.15556*, 2024.

Penghao Wu and Saining Xie. V*: Guided visual search as a core mechanism in multimodal LLMs. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, et al. MMMU: A massive multi-discipline multimodal understanding and reasoning benchmark for expert AGI. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Botao Yu, Ge Zhang, Huan Sun, Yu Su, Wenhu Chen, and Graham Neubig. MMMU-pro: A more robust multi-discipline multimodal understanding benchmark. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15134–15186, 2025. doi: 10.18653/v1/2025.acl-long.736. URL https://aclanthology.org/2025.acl-long.736/.

Renrui Zhang, Xinyu Wei, Dongzhi Jiang, Ziyu Guo, Yichi Zhang, Chengzhuo Tong, Jiaming Liu, Aojun Zhou, Shanghang Zhang, Gao Peng, et al. MAVIS: Mathematical visual instruction tuning with an automatic data engine. In *International Conference on Learning Representations*, volume 2025, pp. 87955–87989, 2025.

A Full Qwen3.5-9B In-Domain Results

Table 4: In-domain learning results on the EVG benchmark for Qwen3.5-9B. Each column is a model–difficulty condition, with 100 test examples per cell. The final rows report mean exact-match accuracy and mean relative error for numeric tasks, with lower relative error better.

Task	Base			EVG		
	D1	D2	D3	D1	D2	D3
Object color	41.0	33.0	34.0	89.0	94.0	87.0
Grid dimensions	92.0	78.0	54.0	96.0	93.0	78.0
Line intersections	76.0	59.0	34.0	88.0	68.0	42.0
Object count	96.0	66.0	49.0	98.0	89.0	69.0
Polygon sides	100.0	55.0	13.0	98.0	76.0	48.0
Angle between lines	28.0	12.0	11.0	83.0	54.0	28.0
Ellipse axis ratio	9.0	7.0	3.0	11.0	15.0	16.0
Image aspect ratio	3.0	4.0	3.0	8.0	11.0	13.0
Line length	8.0	3.0	8.0	14.0	17.0	13.0
Point position	11.0	7.0	6.0	16.0	15.0	14.0
Rectangle aspect ratio	12.0	15.0	20.0	17.0	24.0	33.0
Relative rotation	12.0	11.0	11.0	59.0	27.0	22.0
Mean exact-match accuracy	40.7	29.2	20.5	56.4	48.6	38.6
Mean relative error (numeric tasks) ↓	41.2	40.7	44.5	9.4	10.6	12.0

B Full Qwen3.5-4B Transfer Results

Table 5: Transfer results for Qwen3.5-4B on the same nine downstream benchmarks as Table 1. Values are percentages; Δ is the EVG score minus the base score.

Benchmark	Primary Metric	Base	EVG	Δ (pp)
MMMU-Val	accuracy	47.11	51.67	+4.56
MMStar	average	67.48	68.88	+1.40
AI2D	exact match	78.30	84.20	+5.90
ChartQA	relaxed overall	84.84	84.96	+0.12
BLINK	accuracy	54.93	64.75	+9.82
HallusionBench	qAcc	46.37	47.47	+1.10
VLMs Are Biased	accuracy	1.44	23.46	+22.02
VLMs Are Blind	accuracy	80.65	80.53	-0.12
MMMU-Pro	accuracy	33.64	39.07	+5.43
9-benchmark macro-average	mean	54.97	60.55	+5.58

VLMs Are Blind is the only benchmark that decreases after EVG fine-tuning (−0.12 pp). We hypothesize that this regression reflects a distributional difference: VLMs Are Blind emphasizes low-level perception questions that differ from the particular tasks that our method constructs. The smaller model may generalize less reliably across this difference. This exception does not change the overall transfer pattern: EVG improves eight of nine benchmarks and raises the macro-average by 5.58 pp, consistent with low-level perceptual supervision benefiting high-level task performance.

C Backbone Transfer: Full Gemma-4-12B Results

Table 6: Backbone transfer to Gemma-4-12B. **Left:** in-domain exact-match accuracy (%) on the 12 held-out EVG tasks (100 examples per task–difficulty cell). **Right:** downstream transfer, reusing the benchmark set and metrics of Table 1; the EVG column shows the score with Δ in percentage points relative to base in parentheses.

Task	Base			EVG		
	D1	D2	D3	D1	D2	D3
Object color	43.0	38.0	31.0	56.0	55.0	52.0
Grid dimensions	80.0	60.0	43.0	94.0	76.0	55.0
Line intersections	62.0	58.0	30.0	74.0	60.0	42.0
Object count	94.0	71.0	45.0	98.0	89.0	58.0
Polygon sides	99.0	49.0	10.0	98.0	63.0	30.0
Angle between lines	33.0	15.0	10.0	80.0	38.0	21.0
Ellipse axis ratio	17.0	8.0	7.0	5.0	15.0	18.0
Image aspect ratio	6.0	5.0	4.0	6.0	7.0	7.0
Line length	17.0	14.0	13.0	17.0	18.0	19.0
Point position	6.0	7.0	9.0	17.0	17.0	17.0
Rect. aspect ratio	37.0	16.0	18.0	12.0	19.0	25.0
Relative rotation	33.0	15.0	17.0	63.0	20.0	20.0
Mean	43.9	29.7	19.8	51.7	39.8	30.3

Benchmark	Base	EVG (Δ)
MMMU-Val	54.33	55.56 (+1.23)
MMMU-Pro	39.48	41.62 (+2.14)
MMStar	53.79	56.67 (+2.88)
AI2D	77.88	77.56 (−0.32)
ChartQA	48.48	49.92 (+1.44)
BLINK	55.85	57.38 (+1.53)
HallusionBench	45.93	47.25 (+1.32)
VLMs Are Biased	14.37	18.79 (+4.42)
VLMs Are Blind	78.01	82.06 (+4.05)
Macro-average	52.01	54.09 (+2.08)

D Additional Analysis Results

Table 7: Transfer performance on explicit visual-information requests. The selected plot, chart, and geometry categories are reported individually; the remaining explicit categories are pooled.

Category	n	Base	EVG	Gain
Plot spatial structure	131	37.40	44.27	+6.87
Chart values and trends	134	47.01	55.22	+8.21
Geometric relation	42	11.90	23.81	+11.91
Selected explicit categories	307	38.11	46.25	+8.14
Other explicit visual requests	266	35.34	38.35	+3.01
All explicit requests	573	36.82	42.58	+5.76
Remaining benchmark items	3557	54.09	57.21	+3.12

D.1 Linear-Probing Details

The probing set contains 1,000 D3 examples for each EVG task, generated with a seed distinct from that used for fine-tuning. We group paired present/missing examples by `pair_id` before making a fixed 80%/10%/10% train, validation, and test split, which is shared by the Base and EVG models at every layer. Property probes use only present examples; Line Intersections and Image Aspect Ratio have no missing variant and therefore retain all examples.

For each example, we extract the 4,096-dimensional hidden state of the last prompt token, immediately before answer generation, at layers 0, 4, 8, 12, 16, 20, 24, 28, 31; layer 0 is the embedding output. We standardize features using the training split only and fit logistic-regression probes with `lbfgs`, inverse regularization strength $C_{\text{probe}} = 1$, and at most 20 iterations. The validation split is held out but not used to tune this fixed protocol, and we report held-out test accuracy. Thus, the curves measure linear accessibility under a fixed readout budget rather than the accuracy of a fully optimized classifier.

Table 8 gives the target construction for continuous properties. We compute the three quartile boundaries on valid present training examples only and apply them unchanged to validation and test

examples. The four classes are $(-\infty, \tau_1)$, $[\tau_1, \tau_2)$, $[\tau_2, \tau_3)$, and $[\tau_3, \infty)$. Grid Dimensions and Point Position use separate heads for their two coordinates, whose accuracies are averaged to obtain one task curve. Object Color is mapped from its target RGB value to the nearest of 12 fixed color anchors before classification.

Table 8: Continuous probe targets and their training-set quartile boundaries (τ_1, τ_2, τ_3). For Point Position and Line Length, boundaries are computed from raw numerical targets pooled across pixel and normalized coordinate systems without rescaling. Angles are measured in degrees; aspect ratios are dimensionless.

Task	**Target**	(τ_1, τ_2, τ_3)
Point Position	x	(83, 317, 590)
Point Position	y	(71, 240, 440)
Angle Between Lines	angle	(45, 95, 135)
Relative Rotation	angle magnitude	(18, 32, 47)
Line Length	length	(35.25, 150, 240)
Rectangle Aspect Ratio	ratio	(2.3, 3.1, 4.1)
Ellipse Axis Ratio	ratio	(2.4, 3.2, 4.2)
Image Aspect Ratio	width / height	(1.0503, 1.3224, 1.8246)

E Training Hyperparameters

We fine-tune Qwen3.5-9B with full-parameter supervised fine-tuning. Training uses a per-device batch size of 1 with 16 gradient-accumulation steps, corresponding to an effective batch size of 16. We use a learning rate of 5×10^{-6}, cosine decay with a minimum learning-rate ratio of 0.2, 3% warm-up, AdamW with 8-bit paged optimizer states, weight decay 0.01, and gradient clipping at 1.0. Models are trained in bfloat16 with Unsloth gradient checkpointing and a maximum sequence length of 4096 tokens. Each curriculum stage trains for one epoch over 12,000 examples, with the optimizer reset between stages. The held-out general-VQA panel samples 30 questions uniformly from each Vero-600K category. We evaluate this panel every 50 optimizer steps, save checkpoints at the same frequency, and apply early stopping after two consecutive strict decreases in validation accuracy, retaining the best checkpoint from each stage. All experiments use one NVIDIA H20 GPU and a fixed random seed of 42. The main training recipe uses a 10% missing-object ratio (see Appendix Table 15 for tasks where missing-object questions are applicable); the 0% missing-object ablation uses the identical configuration and changes only this ratio. Table 9 lists the complete configuration.

F Relative Error and Missing-Object Analyses

For numerical tasks, we additionally report relative error to capture partial progress when an answer is not exactly correct; Table 10 gives the full values by difficulty. For scalar targets we use $|\hat{y} - y|/|y|$; for coordinate pairs and grid dimensions we use the sum of absolute coordinate errors divided by the sum of absolute target coordinates. Samples with a `missing` target are excluded from this metric. To avoid unstable values for zero-valued targets, zero denominators are omitted. For each numerical task, we average relative error over its valid numerical predictions. The summary rows report the unweighted mean of these task-level averages across the 11 numerical tasks; lower is better.

G Curriculum Ablation

To assess the contribution of staged difficulty to downstream transfer, we train on the same 36K examples while removing the D1→D2→D3 curriculum. The examples are deterministically shuffled once (seed 42) and trained as a single continuous stage; all other settings, including checkpoint selection on the held-out general-VQA panel, are retained. Random mixing still improves over the base model, but reduces the nine-benchmark macro-average by 2.17 percentage points relative to the staged curriculum. The largest gaps occur on VLMs Are Biased, VLMs Are Blind, and BLINK.

Table 9: Training hyperparameters for EVG fine-tuning of Qwen3.5-9B.

Hyperparameter	Value
Model	Qwen3.5-9B
Fine-tuning	Full parameters
Optimizer	Paged AdamW 8-bit
Learning rate	5×10^{-6}
Scheduler	Cosine decay
Minimum LR ratio	0.2
Warm-up ratio	0.03
Weight decay	0.01
Gradient clipping	1.0
Per-device batch size	1
Gradient accumulation	16
Effective batch size	16
Precision	bfloat16
Gradient checkpointing	Unsloth
Maximum sequence length	4096
Epochs per stage	1
Examples per stage	12,000
Curriculum	D1, D2, D3 (staged)
Evaluation/save frequency	Every 50 optimizer steps
Early-stopping patience	2 strict validation drops
Random seed	42
GPUs	1 NVIDIA H20

Table 10: Mean relative error on numerical tasks by difficulty. Values are percentages over answerable examples; lower is better.

Metric	Base			EVG		
	D1	D2	D3	D1	D2	D3
Grid dimensions	4.8	4.1	8.9	0.7	1.0	2.4
Line intersections	8.8	12.9	17.8	4.7	9.4	11.9
Object count	1.1	6.8	8.1	0.4	1.6	2.6
Polygon sides	0.0	12.3	34.1	0.0	3.6	7.2
Angle between lines	61.7	99.9	139.8	14.5	14.1	16.3
Ellipse axis ratio	51.5	40.1	44.8	14.9	10.0	10.6
Image aspect ratio	19.1	20.4	17.7	4.3	3.8	3.5
Line length	37.8	30.6	35.4	14.1	10.2	12.8
Point position	73.4	78.5	85.7	4.3	3.4	2.8
Rectangle aspect ratio	132.8	35.4	32.3	14.3	8.5	7.5
Relative rotation	61.9	107.2	65.1	31.3	51.0	54.0
Macro-average over numerical tasks	41.2	40.7	44.5	9.4	10.6	12.0

H Missing-Object Ablation

The missing-object ratio is selected using the POPE and RePOPE object-presence benchmarks (Li et al., 2023; Neuhaus & Hein, 2025) and the held-out general-VQA validation signal. Among the rates tested in Appendix Table 12, 10% gives the strongest observed combination of object-presence accuracy and general-VQA validation performance. We therefore use 10% in the EVG training recipe.

The paired missing-object examples also improve accuracy on synthetic missing-object queries, from 80.27% to 97.96%.

Table 11: Curriculum ablation on Qwen3.5-9B. The random-mix model is trained on the same 36K examples as EVG, with the D1→D2→D3 schedule removed. Values are percentages.

Benchmark	Base	Curriculum	Random mix
MMMU-Val	50.78	56.89	55.78
MMStar	69.22	71.37	71.50
AI2D	84.91	87.05	86.37
ChartQA	86.28	86.96	86.08
BLINK	62.38	65.66	62.43
HallusionBench	47.91	49.23	47.03
VLMs Are Biased	14.83	24.93	19.04
VLMs Are Blind	86.50	91.87	87.57
MMMU-Pro	37.69	41.16	39.77
9-benchmark macro-average	60.06	63.90	61.73

Table 12: Missing-object ratio ablation. The paired construction is evaluated with the same curriculum and held-out general-VQA selection rule.

Missing ratio	General-VQA	POPE Acc	RePOPE Acc
20%	lower	89.23	95.17
10%	best balance	89.80	95.30
0%	lower	89.76	95.21

I Comparison with Controlled Synthetic Fine-Tuning

To position EVG relative to prior fine-tuning based synthetic-data approaches, we compare against the controlled synthetic fine-tuning of Rizzoli et al. (2025b), which trains VLMs on an exhaustive, balanced synthetic dataset for absolute-position reasoning. To isolate the effect of the data construction itself, we train the same Qwen3.5-9B backbone with the same full-parameter recipe and Vero-based checkpoint selection used for EVG, rather than the LoRA recipe used in the original paper. The synthetic images are generated with the CIVET rendering framework (Rizzoli et al., 2025a) at 672×672 resolution on a 9×9 fine position grid with a 3×3 coarse output label, following the factor design of Rizzoli et al. (2025b). This yields 1,296 training and 324 held-out validation records, plus a 3,888 diagnostic colored-shape test set. The resulting checkpoint reaches 98.15% on the held-out validation split and 98.82% on the diagnostic test, confirming that the reconstructed task is learned in-domain.

We evaluate the controlled synthetic model on the same nine downstream benchmarks used in Section 4.2, under the same greedy decoding, image budgets, and task definitions. The Base and EVG columns reuse the primary results from Table 1, and the corresponding changes are computed relative to that base model. HallusionBench uses the local deterministic parser rather than the official semantic LLM judge and is therefore provisional.

The controlled synthetic data improves accuracy on six of nine benchmarks (MMMU-Val, MMStar, AI2D, ChartQA, BLINK, and MMMU-Pro), indicating that the underlying image-text alignment learned from this balanced supervision does provide some useful transfer to downstream tasks. It nonetheless regresses on HallusionBench, VLMs Are Biased, and VLMs Are Blind, and its macro change across the nine benchmarks is essentially flat at +0.03 points. EVG improves all nine metrics and reaches +3.84 points in macro. A likely explanation is task diversity: the controlled synthetic pipeline supervises a single spatial-reasoning capability (absolute position on synthetic scenes), whereas EVG covers a broader collection of exact-answer visual-grounding tasks spanning counting, geometry, layout, color, and comparative measurement. This wider coverage of low-level visual perception skills is consistent with EVG's more uniform gains across benchmarks that stress different aspects of visual reading.

Table 13: Comparison with the controlled synthetic fine-tuning of Rizzoli et al. (2025b) on Qwen3.5-9B. The Base and EVG columns reuse the primary results in Table 1; the Controlled Synthetic column uses the balanced absolute-position data of Rizzoli et al. (2025b), regenerated with the released CIVET renderer and trained with our EVG recipe. Values are percentages; Δ denotes the change relative to the base model.

Benchmark	**Base**	**Controlled Synthetic**	**EVG**	Δ_{CS}	Δ_{EVG}
MMMU-Val (Yue et al., 2024)	50.78	55.00	56.89	+4.22	+6.11
MMStar (Chen et al., 2024b)	69.22	69.77	71.37	+0.55	+2.15
AI2D (Kembhavi et al., 2016)	84.91	86.01	87.05	+1.10	+2.14
ChartQA (Masry et al., 2022)	86.28	86.32	86.96	+0.04	+0.68
BLINK (Fu et al., 2024)	62.38	63.13	65.66	+0.75	+3.28
HallusionBench (Guan et al., 2024)	47.91	47.03	49.23	−0.88	+1.32
VLMs Are Biased (Vo et al., 2025)	14.83	10.88	24.93	−3.95	+10.10
VLMs Are Blind (Rahmanzadehgervi et al., 2024)	86.50	83.62	91.87	−2.88	+5.37
MMMU-Pro (Yue et al., 2025)	37.69	39.07	41.16	+1.38	+3.47
9-benchmark macro-average	60.06	60.09	63.90	+0.03	+3.84

J Generated Task Specification

J.1 Task Overview

Appendix Table 14 summarizes the 12 training tasks, their families, answer formats, and visual requirements. Appendix Table 15 gives the corresponding generator identifiers and missing-object applicability. For tasks that refer to an object, we also generate examples in which that object is removed; the correct answer is then `missing`.

Table 14: Tasks used for EVG training. They vary in answer format, the visual information required, and the object or relation being measured.

Family	**Task**	**Answer format**	**Visual requirement**	**Target**
Color	Object Color	category	one object	filled shape
Counting	Object Count	integer	whole image	matching objects
Counting	Polygon Sides	integer	one object	polygon boundary
Counting	Grid Dimensions	`MxN`	one grid	grid rows and columns
Counting	Line Intersections	integer	whole image	line segments
Metric	Point Position	`x, y`	one object	disk center
Metric	Angle Between Lines	degrees	one object	two rays
Metric	Line Length	integer	one object	line segment
Metric	Rectangle Aspect Ratio	decimal ratio	one object	rectangle sides
Metric	Ellipse Axis Ratio	decimal ratio	one object	ellipse axes
Metric	Image Aspect Ratio	decimal ratio	whole image	image dimensions
Metric	Relative Rotation	degrees	two objects	rectangle orientations

Some tasks require reading one object, such as Object Color or Line Length. Others require scanning the image, such as Object Count and Line Intersections. Relative Rotation requires comparing two objects. Image Aspect Ratio is different: it asks about the dimensions of the whole image rather than a depicted object, so we interpret it separately in our analysis.

J.2 Task Definitions and Full Questions

Appendix Figure 5 shows one D2 example for each task. The descriptions below explain the task and reproduce the full question for the cited example. Object-reference tasks allow the answer `missing` when the target is absent; Image Aspect Ratio and Line Intersections do not support missing-object examples. For Object Count, a count of zero is represented by `missing`, so integer count answers refer to cases in which the target object is present.

Table 15: Full task specification for the generated EVG fine-tuning examples.

Task	Answer format	Missing applicable
`color.object_color`	W3C name or hex	Yes
`count.object_count`	integer	Yes
`count.polygon_sides`	integer	Yes
`count.grid_dimensions`	`MxN`	Yes
`count.line_intersections`	integer	No
`metric.point_position`	`x, y`	Yes
`metric.angle_between_lines`	integer degrees	Yes
`metric.line_length`	integer length	Yes
`metric.rectangle_aspect_ratio`	one-decimal ratio	Yes
`metric.ellipse_axis_ratio`	one-decimal ratio	Yes
`metric.image_aspect_ratio`	two-decimal ratio	No
`metric.relative_rotation`	integer degrees	Yes

Table 16: Difficulty axes used to construct D1, D2, and D3.

Axis	D1	D2	D3
Answer breadth	narrow, coarse	medium range	wide, fine-grained
Distractor pressure	0–1 distractors	1–3 distractors	3–6, often same-type
Geometric variation	snapped rotations	moderate rotations	continuous or high variation
Reference complexity	simple reference	color + region	color + region + fill/state
Output precision	coarse values	medium precision	fine quantization or decimals

Object Color. The model identifies the color of a referenced filled shape. Answers use lowercase W3C color names or hexadecimal colors; hexadecimal answers appear more often at higher difficulties. The model must distinguish the target from other shapes in the image. Figure 5a is the D2 instance.

Question. What color is the filled ellipse in the image? If the described object does not exist in the image, answer 'missing'. Otherwise, answer with the lowercase W3C named-color string without additional text, e.g. red. **Answer.** aqua.

Object Count. The model counts all objects with a specified color and shape across the image. The answer is an integer; if no requested object is present, the answer is "missing" rather than zero. Higher difficulties expand the count range and add similar distractors. Figure 5b is the D2 instance.

Question. How many mediumseagreen rectangles are in the image? If there are no mediumseagreen rectangles in the image, answer 'missing' instead of '0'. Otherwise, answer with a single integer without additional text, e.g. 3. **Answer.** 8.

Polygon Sides. The model counts the sides of a referenced polygon. Higher difficulties include more irregular polygons. The answer is an integer, and the task requires tracing the boundary of the selected shape. Figure 5c is the D2 instance.

Question. How many sides does the orchid polygon on the top-right part of the image have? If the described polygon does not exist in the image, answer 'missing'. Otherwise, answer with a single integer without additional text, e.g. 5. **Answer.** 8.

Grid Dimensions. The model determines the number of rows and columns in a referenced grid. The answer is a structured `MxN` string, with rows listed first. The task requires separating the two axes of a repeated arrangement. Figure 5d is the D2 instance.

Question. How many rows and columns does the crimson grid on the bottom part of the image have? If the described grid does not exist in the image, answer 'missing'. Otherwise, answer in the form "MxN" (rows x columns) without additional text, e.g. "3x4". **Answer.** 3x5.

Line Intersections. The model counts interior intersections among line segments; endpoint contacts do not count. The answer is a single integer, and the model must scan the whole image while applying this rule consistently. Figure 5e is the D2 instance.

Question. How many intersection points are formed by the 5 line segments in the image? An intersection point is a point at which two segments cross each other in their interior; endpoint touches are not intersection points. Answer with a single integer without additional text, e.g. 3. **Answer.** 3.

Point Position. The model reports the center of a referenced disk as an ordered coordinate pair. We use pixel coordinates, normalized coordinates from 0 to 100, and normalized coordinates from 0 to 1000 across difficulty levels. The question states the active coordinate system and image size, and the answer is formatted as `x, y`. Figure 5f uses pixel coordinates.

Question. What is the position of the center of the orange disk on the top-right part of the image? Coordinates are in pixels with the origin at the top-left of the image; the image is 957 pixels wide and 349 pixels tall. The x axis runs along the image width (rightward) and the y axis runs along the image height (downward). Both x and y are reported as non-negative integers. If the described disk does not exist in the image, answer 'missing'. Otherwise, answer with two integers separated by ', ' in the order 'x, y', with no additional text, e.g. 0, 0. **Answer.** 823, 90.

Angle Between Lines. The model measures the smaller angle formed by two referenced rays at their shared endpoint. The answer is an integer number of degrees. Higher difficulties use finer angle increments and more distractors. Figure 5g is the D2 instance.

Question. What is the angle (in degrees, strictly less than 180) formed at the shared endpoint by the two rays of the khaki angle in the center of the image? The answer is a positive integer multiple of 15 between 15 and 165 (inclusive). If the described pair of rays does not exist in the image, answer 'missing'. Otherwise, answer with that integer only, with no additional text, e.g. 45. **Answer.** 105.

Line Length. The model measures the length of a referenced line segment in the coordinate system stated in the question. As in Point Position, we use pixel coordinates and normalized coordinates from 0 to 100 or 1000. The answer is an integer length in that system. Figure 5h uses pixel coordinates.

Question. What is the length of the olive line on the bottom part of the image? Coordinates are in pixels with the origin at the top-left of the image; the image is 992 pixels wide and 510 pixels tall. The length is reported as a non-negative integer number of pixels. If the described line segment does not exist in the image, answer 'missing'. Otherwise, answer with that integer only, with no additional text, e.g. 77. **Answer.** 228.

Rectangle Aspect Ratio. The model reports the ratio of the longer rectangle edge to the shorter edge. The answer is a one-decimal float. Unlike line length, this ratio does not change when the image is scaled uniformly.

Question. What is the ratio of the longer edge to the shorter edge of the limegreen filled rectangle on the top part of the image? If the described filled rectangle does not exist in the image, answer 'missing'. Otherwise, answer with a float number with one decimal place, with no additional text, e.g. 3.0. **Answer.** 3.4.

Ellipse Axis Ratio. The model reports the ratio of the major axis to the minor axis of a referenced ellipse. The answer is a one-decimal float. The task requires identifying the axes of an oriented curved shape.

Question. What is the ratio of the major axis to the minor axis of the dodgerblue ellipse on the top-right part of the image? If the described ellipse does not exist in the image, answer 'missing'. Otherwise, answer with a float number with one decimal place, with no additional text, e.g. 3.0. **Answer.** 2.4.

Image Aspect Ratio. This task asks for the width-to-height ratio of the complete image, rather than for a property of a depicted object. The answer is a two-decimal float. We report it separately because it can be determined from the image dimensions.

Question. What is the aspect ratio (width divided by height) of the entire image? Answer with a float number with 2 decimal places without additional text, e.g. 1.50. **Answer.** 1.28.

Relative Rotation. The model compares two referenced rectangles and reports their relative rotation in degrees. The question identifies the reference rectangle and specifies a clockwise or counter-clockwise direction. The answer therefore depends on the orientations of both objects.

Question. Treat the skyblue rectangle on the bottom-right part of the image as the reference. By how many degrees is the skyblue rectangle on the top-left part of the image rotated counter-clockwise relative to the skyblue rectangle on the bottom-right part of the image? The relative rotation is at most 60 degrees. The answer is a positive integer multiple of 5 between 5 and 60 (inclusive). If either described rectangle does not exist in the image, answer 'missing'. Otherwise, answer with that integer only, with no additional text, e.g. 30. **Answer.** 25.

J.3 Rendering Validity Checks

Although answers are derived analytically from the sampled scene parameters, we accept a candidate scene only after enforcing geometry and visibility constraints. For ordinary objects, collision detection uses analytic axis-aligned bounding boxes, including tight bounds for rotated rectangles, ellipses, grids, and polygons. Let W and H denote the canvas width and height in pixels. We pad each bounding box by $p = 0.01 \min(W, H)$ on every side and reject a candidate when its padded box intersects that of a previously placed object. Accepted objects therefore have a clearance of at least $2p = 0.02 \min(W, H)$ along at least one image axis. Edge or corner contact at this boundary is permitted, but positive-area overlap is rejected. Bounding boxes must lie within the canvas up to a one-pixel numerical tolerance. We resample placement for at most 200 attempts; if no valid placement is found, we discard and resample the scene. Intentional logical groups are exempt from this rule, for example the two rays defining an angle may share an endpoint. This conservative padded-box test is not a contour-level or pixel-level collision test.

Line Intersections uses a separate exact segment routine because crossings are the target property. Parallel or collinear segments and endpoint contacts are not counted; an intersection must lie strictly inside both segments. We require segment endpoints and distinct intersection points to be separated by $\epsilon = \max(2w_{\text{line}}, 6\ \text{px})$, which excludes T-junctions, coincident endpoints, and triple concurrence. Here, w_{line} denotes the common line stroke width in pixels, and separation is measured using Euclidean distance. An independent all-pairs verifier recomputes the number of unique intersections and rejects the scene unless it equals the sampled target. Irregular polygons are similarly required to be simple, with no intersections between non-adjacent edges.

For an 8-bit RGB color $c_i = (r_i, g_i, b_i) \in \{0, \ldots, 255\}^3$, we measure color visibility by Euclidean RGB distance, $d_{\text{RGB}}(c_1, c_2) = \sqrt{(r_1 - r_2)^2 + (g_1 - g_2)^2 + (b_1 - b_2)^2}$. Every foreground color c_{fg} must satisfy $d_{\text{RGB}}(c_{\text{fg}}, c_{\text{bg}}) \geq 80$, where c_{bg} is the background color. The sampler also targets this threshold between distinct objects for its first 128 color-sampling attempts. To avoid deadlock in crowded scenes, it then relaxes the pairwise constraint to require only non-identical RGB values. Thus, foreground-to-background contrast is a strict invariant, whereas the inter-object contrast threshold is a preferred constraint rather than an unconditional guarantee.

K More Qualitative Examples

This section presents additional examples in which the EVG model answers correctly and the base model does not. Figures 7, 8, and 9 cover VLMs Are Biased, MMStar, and MMMU-Pro; Figure 3 presents a HallusionBench example.



(a) **Object Color** (D2)

(b) **Object Count** (D2)

(c) **Polygon Sides** (D2)

(d) **Grid Dimensions** (D2)

(e) **Line Intersections** (D2)

(f) **Point Position** (D2)

(g) **Angle Between Lines** (D2)

(h) **Line Length** (D2)

(i) **Rectangle Aspect Ratio** (D2)

(j) **Ellipse Axis Ratio** (D2)

(k) **Image Aspect Ratio** (D2)

(l) **Relative Rotation** (D2)

Figure 5: D2 examples from all 12 generated EVG task categories, arranged in four rows and three columns. The full task descriptions and prompts appear below.



(a) **Line Intersections** (D1) (b) **Line Intersections** (D2) (c) **Line Intersections** (D3)

(d) **Relative Rotation** (D1) (e) **Relative Rotation** (D2) (f) **Relative Rotation** (D3)

Figure 6: Difficulty progression examples. Columns show D1, D2, and D3 for a global aggregation task (line intersections) and a relational comparison task (relative rotation).

Image & Question	Base Model Response	EVG Model Response
 **Question**: How many columns are there on this puzzle? Answer with a number in curly brackets, e.g., {9}.	To determine the number of columns, we can count the vertical divisions. - The grid is divided into 9 large boxes (3x3), which is **typical for a Sudoku puzzle**. - Each large box is subdivided into 3 rows and 3 columns. - Therefore, the entire grid should have **3 x 3 = 9 columns**. → **Final Answer: {9}**	To determine the number of columns, we need to count the vertical lines of cells. By visually inspecting the grid, we can **count the number of vertical lines**. ... By following this method, we can see that there are **10 columns in the grid**. → **Answer: {10}**
 **Question**: Count the stars in this flag. Answer with a number in curly brackets, e.g., {9}.	To count the stars in this flag, we can follow a systematic approach: 1. Identify the Flag: The flag shown is the **national flag of New Zealand**... 2. Locate the Stars: The stars are located on the right side of the flag... 3. Count the Stars: - There are **four stars in total**... → **Therefore, the number of stars in this flag is {4}.**	To count the stars in the flag, we can follow these steps: 1. Identify the Stars: The flag has red stars with white outlines on a blue background. 2. Locate the Stars: The stars are arranged in a specific pattern... 3. Count the Stars: By carefully examining the image, we can count each star individually... - **To the right of the fourth star, there is a fifth star**. → **Answer: {5}**

Figure 7: Additional examples of responses corrected by the EVG model on counting and read-off tasks. The base model applies a memorized default rather than reading the image, assuming a standard 9-column Sudoku grid although 10 columns are drawn, and reporting the canonical four stars of the New Zealand flag although a fifth star is present. The EVG model instead reports the count shown in the image (VLMs Are Biased).

Image & Question	Base Model Response	EVG Model Response
 **Question**: What is the color of the watch worn by a person in the image? **Options:** A: White; B: Black C: Silver; D: Gold	To determine the color of the watch... 1. Locate the person with a watch... 2. Identify the watch: On his left wrist, a watch is clearly visible. 3. Analyze the color: The watch has a metallic band and casing. In the lighting of the photograph, it has a **distinct shiny, reflective quality** that is **characteristic of silver or chrome**... → **The correct option is C: Silver.**	To determine the color of the watch... 1. Locate the person with a watch... 2. Identify the watch: On his left wrist, a watch is clearly visible. 3. Determine the color: The watch has a **dark-colored band and a dark-colored face**. This dark color contrasts with his white shirt and skin tone... black is the only color that matches. → **The correct option is B: Black.**
 **Question**: $<$image 1$>$ Which letter indicates the synaptic cleft? **Options:** A. C; B. A; C. E; D. B; E. D	To determine which letter indicates the synaptic cleft... 1. Presynaptic terminal (axon terminal) - contains synaptic vesicles (A), mitochondria (E)... 2. Synaptic cleft - the narrow extracellular space between the pr ... **E = mitochondrion**. Although the user described C as pointing to the presynaptic membrane, in many standard diagrams, **C is the label for the synaptic cleft**... **Answer:** `\boxed {A}`	To determine which letter indicates the synaptic cleft... A **synapse** is the junction between two neurons... 1. **Presynaptic terminal** - the end of the sending neuron, containing synaptic vesicles (A in ... The **synaptic cleft** is the extracellular space across which neurotransmitters diffuse... In the diagram, **D clearly indicates that narrow gap** between the two membranes. **Final Answer: E. D**
 **Question**: The adjacency list of a directed graph is given as follows. Starting from the vertex V1 and traversing according to the depth-first search method, the obtained vertex sequence is $<$image 1$>$ **Options:** A: V1,V5,V4,V7,V6,V2,V3 B: V1,V2,V3,V4,V7,V6,V5 C: V1,V5,V4,V7,V6,V3,V2 D: V1,V5,V6,V4,V7,V2,V3	We are given an adjacency list representation of a directed graph, and we are to perform a **Depth-First Search (DFS)** starting from vertex **V1**... - C has V3 before V2 - but in DFS, after finishing V6 (from V7), we backtrack to V5, **then to V1, then go to V2**, then to V3. **So V2 must come before V3**. - D has V6 before V4 - but V4 is visited before V6... Conclusion: The correct DFS traversal sequence starting from V1 is: **V1 → V5 → V4 → V7 → V6 → V2 → V3** Which corresponds to option **A**. **Answer: A**	To determine the correct DFS traversal sequence starting from vertex **V1**, we need to carefully analyze the adjacency list... - **V1** → V5 - **V2** → V3 - **V3** → (no outgoing edges) ... Option D: V1,V5,V6,... - but V6 is not a direct neighbor of V5 in the order; V5's neighbors are V4 then V6, so we visit V4 first, not V6. **Thus, only C is correct**. Final Answer: **C: V1,V5,V4,V7,V6,V3,V2** This is the correct DFS traversal sequence starting from V1, following the adjacency list order.

Figure 8: Additional examples of responses corrected by the EVG model on attribute and structure reading. The base model answers from a default rather than the depicted content, including labeling a black watch as silver from its metallic highlight (MMStar), identifying the synaptic cleft from memorized diagram convention (MMMU-Pro), and tracing a depth-first traversal from assumption rather than the given adjacency list (MMMU-Pro). The EVG model reads the depicted color, label, and graph structure instead.

Image & Question	Base Model Response	EVG Model Response
 **Question**: How many circles are there in cell E5? Answer with a number in curly brackets, e.g., {9}.	To determine how many circles are in cell E5, we need to understand the grid layout... **Step 1: Understand the Grid** The image shows a **7-row by 7-column** grid... 3. Observing the pattern across the grid, each column has a consistent number of dots per cell... **- E: 3 dots** ... 4. **This pattern repeats identically in every row.** 5. Therefore, in row 5, column E (E5) contains **3 dots**. **Answer:** `\boxed {3}`	To determine how many circles are in cell E5... **Step 1: Understand the Grid Layout** The grid is labeled: - **Rows**: Numbered 1 to 7 - **Columns**: Labeled A to G... ... if the pattern is symmetric or follows a sequence, E5 might be 2. Moreover, in the original image, **E5 indeed has two black dots**. **Final Answer:** After careful analysis of the grid layout and consistent patterns in column E and row 5, we conclude that cell **E5** contains **2 circles**. → **Answer: {2}**
 **Question**: Do the two horizontal lines have the same length? Answer in curly brackets, e.g., {Yes} or {No}.	To determine whether the two horizontal lines have the same length... - **Top figure**: A double-headed arrow (<->) - this is composed of two diagonal lines meeting at a point... However, it does **not contain a true horizontal line segment** ... **Yes, the two horizontal spans (interpreted as the "horizontal lines" in question) have the same length.** This is based on **visual symmetry and standard diagrammatic intent**... → **Final Answer: Yes, they have the same length.**	To determine whether the two horizontal lines in the image have the same length... 1. **Identify the Lines:** - There are two horizontal lines in the image. 2. **Visual Comparison:** - Visually, the top horizontal li ... lines. - However, the visual difference is clear enough to make a reasonable judgment. Conclusion: Based on the visual inspection... we can conclude that the two horizontal lines **do not have the same length**... **Answer:** `\boxed {No}`

Figure 9: Additional examples of responses corrected by the EVG model on comparative judgments. The base model relies on symmetry or pattern expectation rather than measurement, inferring three dots in grid cell E5 from the row pattern, and declaring two lines equal from apparent symmetry. The EVG model instead inspects the specific cell (two circles) and the rendered lengths (unequal). Both items are from VLMs Are Biased.