POSEIDON: SCALING TRAINING ENVIRONMENTS FOR SCIENTIFIC AGENTS FROM CODE REPOSITORIES

Anonymous authors
Paper under double-blind review

ABSTRACT

Training environments remain a major bottleneck for agents in data-driven scientific discovery. Existing collections of executable and verifiable training environments are small, and their construction remains difficult to scale. To address this limitation, we introduce **POSEIDON**, an automated pipeline for generating diverse, verifiable training environments from scientific code repositories at scale. From the same repository budget, POSEIDON extracts nearly **10**× as many training environments as a prior approach by decomposing scientific workflows into four complementary task types: Reproduction, Subflow, Completion, and Correction, where each type targets a distinct capability for scientific research. A recursive improvement loop further refines failed candidates and recovers otherwise discarded environments. Using POSEIDON, we construct **PEARL**, a collection of **97,659** executable and verifiable environments from **7,110** public repositories spanning **10** scientific disciplines. To the best of our knowledge, PEARL is the largest and most broadly multidisciplinary collection of scientific-agent training environments to date. Qwen3.5 models (9B, 27B, and 35B-A3B) trained on PEARL achieve consistent gains across six challenging scientific-agent benchmarks. Overall, the scale and diversity of PEARL offer opportunities for training scientific discovery agents. Code is available at https://anonymous.4open.science/status/POSEIDON-89D7.




Figure 1: **Scaling scientific-agent training environments and improving downstream performance. Left:** Cumulative number of environments synthesized as the number of source repositories increases. Under a matched repository budget of 306 repositories, POSEIDON produces 5,370 environments, compared with 575 produced by D3-Gym—a 9.3× higher yield. **Right:** Success rates of Qwen3.5-27B before and after training on PEARL across six scientific-discovery benchmarks.

1 INTRODUCTION

The rapid growth of scientific data and the increasing use of large language model agents in research have sparked a surge of interest in data-driven scientific discovery (Xin et al., 2025; Gridach et al., 2025; Anthropic, 2026a; Majumder et al., 2024; Liu et al., 2026). Unlike knowledge-based question answering or isolated code generation, scientific research requires agents to carry out **scientific workflows**: coordinated sequences of data processing and computational steps that address a research objective. Agents must clean data, select appropriate models, write and debug programs, and iteratively revise their analyses based on intermediate results before reaching evidence-supported conclusions (Schmidgall et al., 2025; Zhou et al., 2025) (as depicted in Figure 2). The capability to carry out these scientific workflows requires integrating **scientific reasoning with coding and tool**

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

use, and remains difficult for even current frontier models to master. For example, on OpenAI's GeneBench-Pro (Li et al., 2026), GPT-5.6 Sol (OpenAI, 2026b) achieves a pass rate of only 28.7% at the highest reasoning level (or 31.5% with Pro mode enabled), highlighting the immense difficulty of reliably automating complex scientific analyses. Yet, **training environments designed to develop this capability remain severely limited.**

D3-Gym (Moussa et al., 2026) pioneered the automated synthesis of such training environments from scientific code repositories. These repositories are valuable because they encode **the scientific workflows described above** in related sets of code files that connect research objectives, input data, and computational procedures. Executing these workflows provides reference outputs for verification. However, **scaling this approach remains challenging**. D3-Gym converts each extracted workflow into an end-to-end task, leaving more varied supervision within the workflow underused. Its collection contains only 565 environments from 239 repositories (approximately 2.4 environments per repository). This limited yield raises a central research question:

> *How can we efficiently exploit executable scientific workflows within code repositories to generate high-quality, diverse training environments at scale?*

To answer this, we introduce **POSEIDON**, an automated pipeline for mining scientific code repositories through three stages: *source discovery*, *task synthesis*, and *verification*. Source discovery identifies repositories containing scientific code, data, and research context through domain-keyword expansion. Task synthesis extracts scientific workflows and derives four complementary task types, each corresponding to a distinct capability for scientific agents: `Reproduction`, reproducing the results of a complete scientific workflow from its research objective; `Subflow`, carrying out a standalone analysis to answer a focused scientific question motivated by a broader research context; `Completion`, filling in a missing function in the provided workflow code; and `Correction`, identifying and fixing an error in provided code that produces incorrect results.




Figure 2: An example task from PEARL and the corresponding scientific-agent workflow.

Our key insight is that **a scientific workflow can provide not only an end-to-end research task, but also richer supervision through structured modifications to its constituent steps**. Under a matched budget of 306 repositories, **POSEIDON produces 5,370 environments, 9.3× as many as the 575 produced by D3-Gym**, as shown in the left panel of Figure 1.

In the verification stage, we introduce a **recursive improvement** mechanism driven by an iterative generator–validator loop. If a generated environment fails the initial reliability and scientific-validity checks, the validator returns diagnostic feedback and revision suggestions, after which the generator revises and resubmits the environment. Among the environments rejected in the first verification round, **49.4%** are successfully recovered and pass verification through this refinement process. This closed-loop refinement recovers flawed but fixable candidates that would otherwise be discarded, thereby improving environment quality while increasing data yield.

Using POSEIDON, we construct **PEARL**, a large-scale collection of verified scientific-agent training environments sourced from **7,110 repositories across 10 scientific disciplines**. PEARL contains **97,659 environments**, each equipped with a clear task description, input data, an executable sandbox, a reference solution, and an automatic evaluation script. **To the best of our knowledge, PEARL is the largest and most broadly multidisciplinary collection of training environments for scientific discovery agents to date**. We evaluate PEARL through supervised fine-tuning on Qwen3.5-9B, 27B, and 35B-A3B (Qwen Team, 2026a), achieving notable improvements across six highly challenging scientific-agent benchmarks. Furthermore, controlled ablations show that both broader repository coverage and complementary workflow-derived task types contribute to downstream performance. Overall, the scale and diversity of PEARL open up new opportunities for training scientific discovery agents.

2 Related Works

Scalable Task Synthesis from Code Repositories. Executable code repositories have been extensively leveraged as rich sources of training supervision. Prior work derives completion tasks by masking code at multiple granularities or isolating target functions and their dependencies (Zhang et al., 2023; Yang et al., 2024a; Xie et al., 2025), and converts naturally occurring code fragments into executable specifications and test cases (Xie et al., 2024). For software repair, scalable pipelines synthesize verifiable tasks by injecting test-breaking defects via language-model rewrites and procedural mutations, or by simulating repository-level debugging workflows (Yang et al., 2026; Pham et al., 2025). Other methods reconstruct executable issue-resolution tasks from repository histories through test generation, back-translation, patch reversal, and code-state reconstruction (Jain et al., 2025; Qi et al., 2026). More recently, capability-targeted tasks, including feature development, bug fixing, function localization, and dependency search, have been derived from shared repository contexts (Fu et al., 2026; Xie et al., 2026). Together, these studies demonstrate that transforming and restructuring existing code artifacts can substantially increase both the quantity and diversity of supervision extracted from a single repository. **Inspired by this line of work**, we decompose and transform executable scientific workflows into four complementary task types, thereby scaling the generation of training environments for data-driven scientific discovery.

Automated Training Environment Synthesis for Scientific Discovery. With the rapid growth of scientific data and the increasing capabilities of LLM agents, data-driven scientific discovery has attracted growing attention, spanning scientific coding, computational reproducibility, and autonomous data analysis (Li et al., 2026; Anthropic, 2026a; Mitchener et al., 2025; Chen et al., 2025; Liu et al., 2026). However, large-scale executable environments for training agents to conduct such workflows remain scarce. D3-Gym (Moussa et al., 2026) constructs verifiable training environments from scientific repositories by treating extracted scientific workflows as end-to-end tasks. This approach produces relatively few environments per repository, making it challenging to scale. **In contrast, we derive multiple complementary tasks from each executable scientific workflow**, providing richer supervision beyond end-to-end execution and enabling the generation of diverse, verifiable training environments at scale.

3 Method

In this work, we aim to enhance the problem-solving capabilities of scientific agents by increasing the scale and diversity of training environments. To achieve this, we introduce POSEIDON, an automated synthesis pipeline, and use it to construct PEARL, a large-scale, verified collection of such environments. We begin by formally defining the scientific agent task, and then detail the three stages of the POSEIDON pipeline: repository discovery, task synthesis, and verification.

3.1 Problem Formulation

SciAgent. We study scientific agents (SciAgents). Given a task description, an input data, an executable sandbox, and a code interpreter tool, the agent must denoise the data, choose suitable models, write code, analyse execution results, and produce a final answer. We formulate this process as a sequential decision problem. An agent policy π_θ performs interleaved reasoning and tool use. At step t, the agent generates a thought r_t and an action a_t based on the history; the environment executes a_t and returns an observation o_t. This yields a trajectory $\tau = (r_1, a_1, o_1, \ldots, r_T, a_T, o_T)$. Figure 2 illustrates a representative task together with the corresponding SciAgent workflow.

Environment Synthesis Objectives. To support reliable and effective agent training, SciAgent training environment should satisfy four properties: **(1) Data-Dependent:** Each environment must be grounded in at least one input dataset that is necessary for solving the scientific problem. **(2) Executable:** Each environment must provide a task-specific sandbox containing the dependencies required by the agent, ensuring at least one executable solution path. **(3) Verifiable:** Each environment must include an evaluation script that determines whether the agent's output is correct. **(4) Diverse:** The environments should span a broad range of source repositories and scientific disciplines, and cover diverse task types.




Figure 3: Overview of POSEIDON

Formally, we represent a SciAgent training environment as

$$\mathbb{E} = \{(T_i, D_i, S_i, V_i)\}_{i=1}^{N},$$

where T_i is the task description, D_i is the input dataset, S_i is the executable sandbox, and V_i is the evaluation script.

To satisfy these objectives at scale, we select **GitHub**[1] as our primary data source. GitHub hosts millions of open-source repositories that naturally **bundle scientific code, environment configurations, and associated data**. This rich ecosystem provides an ideal foundation for extracting diverse, data-dependent, and executable workflows. Leveraging this resource, we design an automated pipeline to systematically transform these repositories into agent training environment.

3.2 ENVIRONMENT GENERATION PIPELINE

The POSEIDON pipeline turns public scientific repositories into training environment. It has three stages: **repository discovery, task synthesis, and verification.**

3.2.1 REPOSITORY DISCOVERY

The scale and diversity of synthesized scientific tasks depend directly on the breadth and quality of their source repositories. We therefore first construct a large and diverse repository pool and build an executable sandbox for each repository, providing a reliable foundation for subsequent task synthesis (**Panel (a) of Figure 3**).

Keyword Pool Generation. We begin with a small set of domain descriptions, such as `structural biology and molecular dynamics` or `cheminformatics and drug discovery`. For each domain, we prompt an LLM to propose concrete software, libraries, file formats, and database names typically mentioned in the README files of related repositories, such as `GROMACS`, `MDAnalysis`, and `PLUMED` for molecular dynamics. Each candidate term is then executed as a GitHub search query. We discard terms with fewer than 30 hits, as they indicate limited public code availability, and terms with more than 5,000 hits, as they are often too generic (e.g., `docker` or `hdf5`). The retained terms constitute the **keyword pool**.

[1] `https://github.com`

Repository Pool Collection. We query GitHub using the keyword pool and retain a repository only if it meets four criteria: **it has at least 20 stars, contains scientific data, is backed by a published paper or preprint, and belongs to a core scientific discipline** (e.g., mathematics, physics, chemistry, biology, or pharmacy). The retained repositories form the **repository pool**.




Figure 4: Distribution of the collected scientific repositories across disciplines.

Executable Sandbox Construction. For each repository, we construct an isolated sandbox whose dependencies are inferred both by statically analyzing the repository's source code and by parsing its declared dependency manifests. This sandbox is preserved to ensure reproducible execution during subsequent seed extraction and task generation.

In this stage, we obtain **7,110** repositories. Their detailed distribution is reported in Figure 4. Given the particularly active development of scientific agents in biology and biomedicine (Mitchener et al., 2025; Li et al., 2026; Anthropic, 2026a), we intentionally oversample biological repositories to better cover this important application domain. Prompts for keyword expansion, scientific-file detection, and scientific-field judgment are provided in Appendix E.2.

3.2.2 Task Synthesis

Given the repository pool, we develop a seed-program-centric method (**Panel (b) of Figure 3**) to deeply mine each repository and synthesize scientific tasks from its executable workflows. This method operates in two steps: we first extract executable seed programs from the raw repositories, and then derive diverse tasks from their underlying scientific workflows.

Seed Program Extraction. For each repository, we use DeepSeek-V4-Flash (DeepSeek-AI, 2026) to group related code files into one or more cohesive sets, each representing a complete scientific workflow (e.g. data denoise, computational analysis, and result generation). To standardize execution, DeepSeek-V4-Flash consolidates and rewrites each file set into a single entry-point code script, strictly preserving the original scientific logic. We then execute every candidate script within its sandbox; those that fail to run or produce errors are discarded, while successfully executed scripts are retained as **seed programs**.

Task Generation. Given a seed program, we use DeepSeek-V4-Flash to extract its underlying **scientific workflow** and represent it as a directed graph, where nodes denote data artifacts or computational operations and edges encode data dependencies. From this graph, we derive four complementary task types that target important capabilities in scientific discovery:

- **Reproduction** is constructed based on the inputs and outputs of the full workflow. It requires reproducing the entire analysis, targeting end-to-end workflow planning and execution.
- **Subflow** is constructed by extracting a specific part of the workflow. It requires executing this selected connected subgraph, targeting local dependency understanding and modular execution.
- **Completion** is constructed by removing a functional block from the complete code. It requires reconstructing the missing computational step from its surrounding context and dependencies, targeting dependency-aware workflow completion.
- **Correction** is constructed by injecting a controlled error into the program. It requires correcting this executable but scientifically invalid operation, targeting scientific error diagnosis and repair.

The construction logic for each task type is illustrated in the lower portion of Figure 3(b). For each task, we isolate the relevant segment of the seed program to construct a task-specific **reference program**. Executing this program yields the **reference answer**, which we then use to automatically generate an **evaluation script** tailored to the answer's format. Examples of each task type are provided in Appendix E.1.

Table 1: **Comparison of scientific agent benchmarks.** We summarize benchmark scale, covered disciplines, task format, and evaluation protocol.

Benchmark	Size	Disciplines	Open-ended	Evaluation
SciCode	65	Phys., Math., Mat., Chem., Bio.	✗	Rule-based
BioCoder	154	Bioinfo.	✗	Rule-based
MedAgentBench	300	Clin.M̃ed.	✗	Rule-based
BixBench	205	Bioinfo.	✓	LLM-as-Judge
BioMysteryBench	90	Bioinfo.	✓	LLM-as-Judge
ScienceAgentBench	102	Psych., Bioinfo., GIS, Comp.C̃hem.	✓	LLM-as-Judge

Abbreviations: Phys. (Physics), Math. (Mathematics), Mat. (Materials Science), Chem. (Chemistry), Bio. (Biology), Bioinfo. (Bioinformatics), Clin.M̃ed. (Clinical Medicine), Psych. (Psychology and Cognitive Science), GIS (Geographic Information Science), Comp.C̃hem. (Computational Chemistry).

3.2.3 VERIFICATION

We apply a multi-stage quality-verification pipeline (**Panel (c) of Figure 3**) to assess two complementary properties of each environment: **environment reliability**, which checks that the environment is complete, executable, reproducible, and reliably gradable; and **scientific validity**, which checks that the task is scientifically meaningful, correctly implemented, and internally consistent. Detailed criteria for both properties are provided in Appendix B.

Each candidate environment is first evaluated by a GPT-5.5 **validator** according to these criteria. To recover valuable environments that initially fail verification, we introduce **recursive improvement**. The validator returns its error diagnosis and revision suggestions to the DeepSeek-V4-Flash **generator**, which revises the environment before submitting it to the validator again. This feedback loop between the generator and validator runs for up to three rounds, and an environment is retained if it passes validation within this budget. Finally, the validator assigns each retained environment a difficulty score from 1 to 4 based on the required domain knowledge and the depth of the analysis.

To further assess the quality of the automatically verified environments, we randomly sample 600 tasks for independent manual review by three PhD researchers. A task is accepted only if all three reviewers approve it, yielding an acceptance rate of 95.5% (Details are in Appendix C. After automated filtering, PEARL contains **97,659** training environments. Their distributions across difficulty levels and task types are reported in Appendix A. The prompts used for quality verification, environment revision, and difficulty annotation are provided in Appendix E.2.

4 EXPERIMENT

4.1 EXPERIMENTAL SETUP

Agent Framework. We build our agent framework upon **mini-swe-agent** (Yang et al., 2024b). Each task runs in an isolated sandbox with external network access disabled, and the agent interacts with the environment exclusively through a command-line interface. We impose a wall-clock time limit of 10,800 seconds per task and an execution timeout of 1,800 seconds per command, with a maximum of 100 agent iterations per task.

Training Details. We use Qwen3.5-9B, Qwen3.5-27B, and Qwen3.5-35B-A3B as our backbone models. Using DeepSeek-V4-Pro as the teacher model, we collect 64,477 successful trajectories through rejection sampling from a pool of 97,659 training environments. To reduce benchmark contamination, before trajectory collection we removed environments whose source repositories matched, or were near-duplicates of, repositories underlying the evaluation benchmarks. We fine-tune the backbone models with a learning rate of 5.0×10^{-6}, a batch size of 128, a maximum context length of 65,536 tokens, and a limit of 50 agent iterations per trajectory.

Evaluation Benchmarks. To thoroughly evaluate the scientific discovery capabilities of models trained on PEARL and other baselines, we assemble a suite of 6 scientific discovery benchmarks spanning ten scientific disciplines. Three of these are well-specified benchmarks with objectively

Table 2: **Overall comparison across scientific discovery benchmarks.** MA-bench and SA-bench denote MedAgentBench and ScienceAgentBench, respectively. Scores are success rates (%), and Avg is the mean over all benchmark columns. Within each size group (9B, A3B, 27B), **PEARL** is trained on the corresponding Qwen3.5 backbone;

Model	BioCoder	SciCode		MA-Bench	SA-Bench	BixBench		BioMystery	Avg
		Main	Sub			MCQ	Open		
Frontier Models									
Claude-Opus-4.8	71.4	20.0	53.5	84.9	54.1	72.2	50.2	65.1	58.9
Gemini-3.6-Flash	70.8	20.0	59.0	92.3	55.9	73.7	47.8	56.7	59.5
GPT-5.5	75.3	20.0	59.0	94.3	52.9	74.1	49.8	55.6	60.1
Qwen3.8-Max	77.9	23.1	57.6	86.3	64.7	77.6	45.9	64.4	62.2
DeepSeek-V4-Pro	70.8	24.6	59.7	85.0	57.8	72.7	47.8	64.4	60.4
GLM-5.2	67.5	18.5	29.2	88.3	58.8	69.3	39.5	64.4	54.4
Hy4-Preview	80.5	18.5	54.9	69.0	61.8	72.2	49.8	44.4	56.4
9B Models									
Qwen3.5-9B	46.8	3.1	30.2	59.0	26.5	48.3	35.1	16.7	33.2
+ PEARL	**51.9** ↑5.1	**9.2** ↑6.1	**34.0** ↑3.8	**63.0** ↑4.0	**33.3** ↑6.8	**50.7** ↑2.4	**37.6** ↑2.5	**20.0** ↑3.3	**37.5** ↑4.3
A3B Models									
Qwen3.5-35B-A3B	54.5	13.8	37.5	71.3	38.2	57.1	32.2	27.8	41.6
+ PEARL	**60.4** ↑5.9	**20.0** ↑6.2	**45.1** ↑7.6	**78.3** ↑7.0	**47.1** ↑8.9	**69.3** ↑12.2	**37.1** ↑4.9	**28.9** ↑1.1	**48.3** ↑6.7
27B Models									
Qwen3.5-27B	57.1	12.3	42.7	75.7	34.3	61.5	34.1	36.7	44.3
+ PEARL	**67.5** ↑10.4	**16.9** ↑4.6	**50.3** ↑7.6	**79.0** ↑3.3	**50.0** ↑15.7	**69.8** ↑8.3	**39.5** ↑5.4	**38.9** ↑2.2	**51.5** ↑7.2

verifiable outcomes: SciCode (Tian et al., 2024), BioCoder (Tang et al., 2024), and MedAgentBench (Jiang et al., 2025). The remaining three benchmarks, namely BixBench (Mitchener et al., 2025), BioMysteryBench (Anthropic, 2026a), and ScienceAgentBench (Chen et al., 2025), focus on open-ended scientific analyses. To ensure a fair and reliable evaluation, we exclude problems that are ill-posed or require languages outside our harness. Table 1 summarizes the scale, disciplinary coverage, task format, and evaluation protocol of each benchmark. Detailed exclusion rules and further benchmark descriptions are provided in Appendix D.

Models. We evaluate two groups of models. The first group comprises **frontier models**, including Claude-Opus-4.8 (Anthropic, 2026b), Gemini-3.6-Flash (Google DeepMind, 2026), GPT-5.5 (OpenAI, 2026a), Qwen3.8-Max (Qwen Team, 2026b), DeepSeek-V4-Pro (Xu et al., 2026), GLM-5.2 (Zeng et al., 2026), and Hy4-Preview (Tencent Hy Team, 2026). The second group comprises **baseline models**: the Qwen3.5 family (Qwen Team, 2026a) (9B, 27B, and 35B-A3B). For all models, we set the temperature to 0.7, the maximum number of generated tokens to 32,768, and the reasoning effort to high.

4.2 MAIN RESULTS

We first evaluate the effectiveness of PEARL by comparing Qwen3.5 models of different sizes before and after supervised fine-tuning, together with several frontier models. The results are shown in Table 2. Overall, **training on PEARL consistently improves scientific-discovery performance across model scales and scientific domains**, covering both well-specified tasks and more challenging open-ended workflows. The gains are particularly pronounced for larger models, suggesting that stronger base models can better exploit the diverse and complex supervision provided by PEARL. Notably, Qwen3.5-27B improves by 10.4 percentage points on BioCoder and by 15.7 percentage points on ScienceAgentBench.

More importantly, **PEARL substantially narrows the gap between open models and frontier models**. After SFT, Qwen3.5-27B reaches 67.5% on BioCoder, matching GLM-5.2, while Qwen3.5-35B-A3B achieves 20.0% on SciCode (main), matching GPT-5.5. The 27B model also reaches 79.0% on MedAgentBench and 69.8% on BixBench-MCQ, outperforming Hy4-Preview (69.0%) and GLM-5.2 (69.3%), respectively, despite its substantially smaller model scale. These results demonstrate that **high-quality scientific-agent training data can yield large gains in scientific-discovery capabilities and enable relatively compact models to approach, or even surpass, frontier models on individual benchmarks**.

Table 4: **Data-scale-controlled comparison against scientific-agent training baselines.** We subsample **2,000** training trajectories from PEARL to obtain a data budget comparable to baselines.

Model	# Traj.	BioCoder	SciCode		MA-Bench	SA-Bench	BixBench		BioMystery	Avg
			Main	Sub			MCQ	Open		
Qwen3.5-27B	–	57.1	12.3	42.7	75.7	34.3	61.5	34.1	**36.7**	44.3
+ MEDAGENTGYM	2,137	60.4 ↑3.3	**13.8** ↑1.5	42.7	**79.0** ↑3.3	36.2 ↑1.9	53.4 ↓8.1	28.4 ↓5.7	32.2 ↓4.5	43.3 ↓1.0
+ D3-GYM	2,153	59.1 ↑2.0	10.8 ↓1.5	38.9 ↓3.8	73.7 ↓2.0	36.2 ↑1.9	62.0 ↑0.5	25.9 ↓8.2	28.9 ↓7.8	41.9 ↓2.4
+ PEARL (2k)	**2,000**	**62.3** ↑5.2	**13.8** ↑1.5	**43.4** ↑0.7	77.7 ↑2.0	**38.1** ↑3.8	**63.9** ↑2.4	**37.6** ↑3.5	34.4 ↓2.3	**46.4** ↑2.1

Comparing PEARL with Other Scientific-Discovery Data. We next compare PEARL with D3-Gym (Moussa et al., 2026), another method for generating scientific-agent training environments from code repositories. For a more comprehensive comparison, we also include MedAgentGym (Xu et al., 2025), a collection of training environments for biomedical agent. D3-Gym and MedAgentGym provide 2,153 and 2,137 training trajectories, respectively. To compare under a similar data budget, we randomly subsample 2,000 trajectories from PEARL and fine-tune the same Qwen3.5-27B backbone using an identical training recipe (Table 4). Both baselines yield selective gains but also degrade performance on several benchmarks. **MedAgentGym improves four of the eight settings** but decreases BixBench (MCQ) by 8.1 percentage points, while **D3-Gym improves only three settings** and reduces BixBench (Open) by 8.2 points and BioMystery by 7.8 points. These inconsistent transfer patterns are consistent with their limited disciplinary coverage and limited exploitation of the scientific resources from which their training data are constructed. By contrast, **PEARL improves seven of the eight settings**, with gains ranging from 0.7 to 5.2 percentage points and an overall average improvement of 2.1 points, despite using fewer than 10% of the full training data. The consistent gains at this matched data budget suggest that **PEARL's benefit arises from the diversity of its scientific disciplines, repositories, and workflow-derived tasks, rather than from data scale alone.**

Table 3: Solvability across environment difficulty levels

Difficulty	Success (%)	Avg. Steps
D1	94.0	6.2
D2	86.0	8.1
D3	57.0	15.1
D4	41.0	16.4

4.3 ABLATION STUDY

We conduct three ablation studies to examine how source diversity, environment difficulty, and workflow-derived task composition contribute to PEARL's effectiveness. All ablation models are trained by fine-tuning Qwen3.5-35B-A3B under the same training recipe and evaluated on four representative benchmarks: BioCoder, MedAgentBench, BixBench-MCQ, and ScienceAgentBench.

Scaling Repository Diversity. To isolate the effect of repository diversity, we fix the total number of training trajectories, the average environment difficulty, and the proportions of the four task types. We then vary the proportion of source repositories from 20% to 100%. The top row of Figure 5 shows that **increasing repository diversity consistently improves training effectiveness under a fixed trajectory budget**. Across all four benchmarks, performance exhibits an overall upward trend as repository coverage increases, despite minor fluctuations at intermediate points. This effect is particularly clear on MedAgentBench and BixBench (MCQ): at 20% coverage, the trained model performs close to or even below the untrained backbone, whereas broader repository coverage eventually yields a clear improvement over the baseline. These results demonstrate **the value of expanding the breadth of scientific sources**, even with a fixed amount of training data.

Scaling Environment Difficulty. We next investigate how environment difficulty relates to task solvability and training effectiveness. We first randomly sample 100 environments from each of the four difficulty levels, D1–D4, and evaluate DeepSeek-V4-Pro on their tasks. As shown in Table 3, the success rate decreases from 94.0% for D1 to 41.0% for D4, while the average solution length increases from 6.2 to 16.4 steps. These results indicate that the annotated difficulty levels are consistent with empirical task difficulty.




Figure 5: **Scaling repository diversity and environment difficulty under a fixed trajectory budget.** The top row varies repository coverage, whereas the bottom row varies the average difficulty of the training environments. The dashed line marks the untrained Qwen3.5-35B-A3B backbone.

Table 5: Ablation study on removing individual workflow-derived task types.

Model Variant	BioCoder	MedAgentBench	BixBench (MCQ)	ScienceAgentBench	Avg.
Qwen3.5-35B (+PEARL)	**60.4**	**78.3**	**69.3**	**47.1**	**63.8**
w/o Reproduction	54.5 ↓5.9	70.7 ↓7.6	63.9 ↓5.4	44.1 ↓3.0	58.3 ↓5.5
w/o Subflow	55.8 ↓4.6	73.0 ↓5.3	60.5 ↓8.8	41.2 ↓5.9	57.6 ↓6.2
w/o Completion	59.7 ↓0.7	71.7 ↓6.6	62.0 ↓7.3	43.1 ↓4.0	59.1 ↓4.7
w/o Correction	55.2 ↓5.2	72.0 ↓6.3	62.0 ↓7.3	46.1 ↓1.0	58.8 ↓5.0

We then construct five training subsets, each containing 30,000 trajectories, with average environment difficulty scores of 2.4, 2.6, 2.8, 3.0, and 3.2, respectively. We keep the number of repositories, the total trajectory budget, and the proportions of the four task types fixed across subsets. As shown in the bottom row of Figure 5, downstream performance exhibits no consistent trend as the difficulty of the training environments increases. Overall, **environment difficulty correlates with task solvability but does not affect its effectiveness as training data within the evaluated range**.

Removing Individual Task Types. We ablate each of the four workflow-derived task types in turn, yielding four reduced datasets—w/o Reproduction, w/o Subflow, w/o Completion, and w/o Correction— while controlling the total training-data size and source-repository distribution. Table 5 reports the results. **Removing any single task type degrades performance on every benchmark**, confirming that each contributes non-redundant supervision. This result demonstrates the value of **mining multiple complementary forms of supervision from each scientific workflow**.

5 Conclusion

We introduced Poseidon, an automated pipeline for generating diverse, verifiable training environments from scientific code repositories at scale. By deriving four complementary task types from executable workflows and refining failed candidates through recursive improvement, Poseidon produces richer supervision from existing scientific code. Using this pipeline, we constructed Pearl, a collection of 97,659 environments from 7,110 repositories across 10 scientific disciplines. Supervised fine-tuning on Pearl improves Qwen3.5 models across six scientific-agent benchmarks. Controlled ablations further show that repository diversity and complementary task types contribute to these gains, supporting the value of extracting supervision beyond end-to-end workflow execution. Together, Poseidon and Pearl provide a practical foundation for scaling training environments and developing more capable scientific discovery agents.

AI USE STATEMENT

We use LLMs in manuscript preparation and in the construction and validation of scientific-agent training environments:

- **Language Refinement:** We use LLMs to assist with improving the grammar, readability, and academic style of the manuscript.
- **Source Discovery and Task Synthesis:** LLMs assist with expanding domain descriptions into search keywords for scientific code repositories. We use DeepSeek-V4-Flash to organize related code files into executable seed programs and derive four complementary task types: Reproduction, Subflow, Completion, and Correction.
- **Quality Verification and Recursive Improvement:** We use GPT-5.5 as a validator to assess environment reliability and scientific validity. For candidates that fail verification, the validator provides diagnostic feedback and revision suggestions to DeepSeek-V4-Flash. This iterative refinement process runs for up to three rounds. These assessments are complemented by programmatic execution checks.
- **Difficulty Annotation:** GPT-5.5 assigns each retained environment a difficulty score from 1 to 4 based on the required domain knowledge and analytical depth.
- **Trajectory Collection:** We use DeepSeek-V4-Pro as the teacher model to collect solution trajectories from PEARL. Through rejection sampling, we retain 64,477 successful trajectories from 97,659 training environments for supervised fine-tuning of Qwen3.5-9B, Qwen3.5-27B, and Qwen3.5-35B-A3B.
- **Programming Support:** We use Claude Code to assist with generating, modifying, and refactoring portions of the experimental codebase.

REFERENCES

Anthropic. Evaluating claude's bioinformatics research capabilities with BioMysteryBench. Anthropic Research, April 2026a. URL https://www.anthropic.com/research/Evaluating-Claude-For-Bioinformatics-With-BioMysteryBench. Published April 29, 2026; accessed 2026-09-08.

Anthropic. Claude opus 4.8 system card. Anthropic, May 2026b. URL https://www.anthropic.com/claude-opus-4-8-system-card. Published May 28, 2026.

Ziru Chen, Shijie Chen, Yuting Ning, Qianheng Zhang, Boshi Wang, Botao Yu, Yifei Li, Zeyi Liao, Chen Wei, Zitong Lu, Vishal Dey, Mingyi Xue, Frazier N. Baker, Benjamin Burns, Daniel Adu-Ampratwum, Xuhui Huang, Xia Ning, Song Gao, Yu Su, and Huan Sun. ScienceAgentBench: Toward rigorous assessment of language agents for data-driven scientific discovery. In *International Conference on Learning Representations*, 2025. URL https://arxiv.org/abs/2410.05080.

DeepSeek-AI. Deepseek-v4: Towards highly efficient million-token context intelligence, 2026.

Lingyue Fu, Hao Guan, Bolun Zhang, Haowei Yuan, Yaoming Zhu, Lin Qiu, ZongYu Wang, Xuezhi Cao, Xunliang Cai, Weiwen Liu, Weinan Zhang, and Yong Yu. CoreCodeBench: Decoupling code intelligence via fine-grained repository-level tasks. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 26043–26067. Association for Computational Linguistics, 2026. doi: 10.18653/v1/2026.acl-long.1196. URL https://aclanthology.org/2026.acl-long.1196/.

Google DeepMind. Gemini 3.6 flash model card. Google DeepMind, July 2026. URL https://deepmind.google/models/model-cards/gemini-3-6-flash/. Published July 2026; updated July 21, 2026.

Mourad Gridach, Jay Nanavati, Khaldoun Zine El Abidine, Lenon Mendes, and Christina Mack. Agentic ai for scientific discovery: A survey of progress, challenges, and future directions. *arXiv preprint arXiv:2503.08979*, 2025.

Naman Jain, Jaskirat Singh, Manish Shetty, Tianjun Zhang, Liang Zheng, Koushik Sen, and Ion Stoica. R2e-gym: Procedural environment generation and hybrid verifiers for scaling open-weights swe agents. In *Second Conference on Language Modeling*, 2025.

Yixing Jiang, Kameron C Black, Gloria Geng, Danny Park, James Zou, Andrew Y Ng, and Jonathan H Chen. Medagentbench: a virtual ehr environment to benchmark medical llm agents. *Nejm Ai*, 2(9):AIdbp2500144, 2025.

Jeremy Li, Suyash Shringarpure, Edmund Wong, and Andrew Ho. Genebench-pro: Evaluating multistage statistical reasoning in genomics, quantitative biology, and translational biomedicine. *bioRxiv*, pp. 2026–06, 2026.

Amelia Liu, Andrew Ho, Anne Marie Droste, David Martin, Edmund Wong, Edward Zhou, Isabelle Zhou, Joshua Park, Joy Jiao, Katie-Rose Skelly, et al. Lifescibench: Evaluating language models on realistic, expert-level tasks in the life sciences. *bioRxiv*, pp. 2026–08, 2026.

Bodhisattwa Prasad Majumder, Harshit Surana, Dhruv Agarwal, Bhavana Dalvi Mishra, Abhijeetsingh Meena, Aryan Prakhar, Tirth Vora, Tushar Khot, Ashish Sabharwal, and Peter Clark. DiscoveryBench: Towards data-driven discovery with large language models. *arXiv preprint arXiv:2407.01725*, 2024. URL https://arxiv.org/abs/2407.01725.

Ludovico Mitchener, Jon M Laurent, Alex Andonian, Benjamin Tenmann, Siddharth Narayanan, Geemi P Wellawatte, Andrew White, Lorenzo Sani, and Samuel G Rodriques. Bixbench: a comprehensive benchmark for llm-based agents in computational biology. *arXiv preprint arXiv:2503.00096*, 2025.

Hanane Nour Moussa, Yifei Li, Zhuoyang Li, Yankai Yang, Cheng Tang, Tianshu Zhang, Nesreen K Ahmed, Ali Payani, Ziru Chen, and Huan Sun. D3-gym: Constructing real-world verifiable environments for data-driven discovery. *arXiv preprint arXiv:2604.27977*, 2026.

OpenAI. GPT-5.5 system card. OpenAI Deployment Safety Hub, April 2026a. URL https://deploymentsafety.openai.com/gpt-5-5. Published April 23, 2026.

OpenAI. GPT-5.6 system card. OpenAI Deployment Safety Hub, July 2026b. URL https://deploymentsafety.openai.com/gpt-5-6. Published July 9, 2026.

Minh VT Pham, Huy N Phan, Hoang N Phan, Cuong Le Chi, Tien N Nguyen, and Nghi DQ Bui. Swe-synth: Synthesizing verifiable bug-fix data to enable large language models in resolving real-world bugs. *arXiv preprint arXiv:2504.14757*, 2025.

Haomin Qi, Xingliang Wang, Xuanqi Gao, Baihui Sang, Xin Zhang, Minghua Ma, Pengfei Gao, Yu Kang, Qingwei Lin, Saravan Rajmohan, et al. Change2task: From repository changes to executable coding agent tasks and environments. *arXiv preprint arXiv:2607.28591*, 2026.

Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026a. URL https://qwen.ai/blog?id=qwen3.5.

Qwen Team. Qwen3.8-max: A new bar for coding and cowork, August 2026b. URL https://qwen.ai/blog?id=qwen3.8.

Samuel Schmidgall, Yusheng Su, Ze Wang, Ximeng Sun, Jialian Wu, Xiaodong Yu, Jiang Liu, Michael Moor, Zicheng Liu, and Emad Barsoum. Agent laboratory: Using llm agents as research assistants. *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 5977–6043, 2025.

Xiangru Tang, Bill Qian, Rick Gao, Jiakang Chen, Xinyun Chen, and Mark B. Gerstein. BioCoder: A benchmark for bioinformatics code generation with large language models. *Bioinformatics*, 40 (Supplement_1):i266–i276, 2024. doi: 10.1093/bioinformatics/btae230. URL https://doi.org/10.1093/bioinformatics/btae230.

Tencent Hy Team. Introducing Hy4 Preview. Tencent Hy, August 2026. URL https://hy.tencent.ai/research/hy4-preview. Published August 28, 2026.

Minyang Tian, Luyu Gao, Shizhuo D Zhang, Xinan Chen, Cunwei Fan, Xuefei Guo, Roland Haas, Pan Ji, Kittithat Krongchon, Yao Li, et al. Scicode: A research coding benchmark curated by scientists. *Advances in Neural Information Processing Systems*, 37:30624–30650, 2024.

Yiqing Xie, Alex Xie, Divyanshu Sheth, Pengfei Liu, Daniel Fried, and Carolyn Rose. Codebenchgen: Creating scalable execution-based code generation benchmarks. *arXiv preprint arXiv:2404.00566*, 2024.

Yiqing Xie, Alex Xie, Divyanshu Sheth, Pengfei Liu, Daniel Fried, and Carolyn Rose. Repost: Scalable repository-level coding environment construction with sandbox testing. *arXiv preprint arXiv:2503.07358*, 2025.

Yiqing Xie, Emmy Liu, Gaokai Zhang, Nachiket Kotalwar, Shubham Gandhi, Sathwik Acharya, Xingyao Wang, Carolyn Rose, Graham Neubig, and Daniel Fried. Hybrid-Gym: Training coding agents to generalize across tasks. *arXiv preprint arXiv:2602.16819*, 2026. URL https://arxiv.org/abs/2602.16819.

Hongliang Xin, John R Kitchin, and Heather J Kulik. Towards agentic science for advancing scientific discovery. *Nature Machine Intelligence*, 7(9):1373–1375, 2025.

Anyi Xu, Bangcai Lin, Bing Xue, Bingxuan Wang, Bingzheng Xu, Bochao Wu, Bowei Zhang, Chaofan Lin, Chen Dong, Chenchen Ling, et al. Deepseek-v4: Towards highly efficient million-token context intelligence. *arXiv preprint arXiv:2606.19348*, 2026.

Ran Xu, Yuchen Zhuang, Yishan Zhong, Yue Yu, Zifeng Wang, Xiangru Tang, Hang Wu, May D. Wang, Peifeng Ruan, Donghan Yang, Tao Wang, Guanghua Xiao, Xin Liu, Carl Yang, Yang Xie, and Wenqi Shi. MedAgentGym: A scalable agentic training environment for code-centric reasoning in biomedical data science. *arXiv preprint arXiv:2506.04405*, 2025. URL https://arxiv.org/abs/2506.04405.

Jian Yang, Jiajun Zhang, Jiaxi Yang, Ke Jin, Lei Zhang, Qiyao Peng, Ken Deng, Yibo Miao, Tianyu Liu, Zeyu Cui, et al. Execrepobench: Multi-level executable code completion evaluation. *arXiv preprint arXiv:2412.11990*, 2024a.

John Yang, Carlos E Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik R Narasimhan, and Ofir Press. SWE-agent: Agent-computer interfaces enable automated software engineering. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024b. URL https://arxiv.org/abs/2405.15793.

John Yang, Kilian Lieret, Carlos Jimenez, Alexander Wettig, Kabir Khandpur, Yanzhe Zhang, Binyuan Hui, Ofir Press, Ludwig Schmidt, and Diyi Yang. Swe-smith: Scaling data for software engineering agents. *Advances in Neural Information Processing Systems*, 38, 2026.

Aohan Zeng, Xin Lv, Zhenyu Hou, Zhengxiao Du, Qinkai Zheng, Bin Chen, Da Yin, Chendi Ge, Chenghua Huang, Chengxing Xie, et al. Glm-5: from vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763*, 2026.

Fengji Zhang, Bei Chen, Yue Zhang, Jacky Keung, Jin Liu, Daoguang Zan, Yi Mao, Jian-Guang Lou, and Weizhu Chen. Repocoder: Repository-level code completion through iterative retrieval and generation. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 2471–2484, 2023.

Lianhao Zhou, Hongyi Ling, Cong Fu, Yepeng Huang, Michael Sun, Wendi Yu, Xiaoxuan Wang, Xiner Li, Xingyu Su, Junkai Zhang, et al. Autonomous agents for scientific discovery: Orchestrating scientists, language, code, and physics. *arXiv preprint arXiv:2510.09901*, 2025.

A Data Distribution

Figure 6 and Figure 7 show the difficulty and task-type distributions of our **97,659** tasks.




Figure 6: Difficulty distribution of the tasks.




Figure 7: Task-type distribution of the tasks.

B Verification Criteria Details

Environment Reliability. We first verify that each environment is structurally complete, executable, reproducible, and reliably gradable. Specifically, we assess **(1) data integrity**, requiring all referenced data files to exist and their paths to be valid and consistent with the package structure; **(2) executability**, requiring the reference program to run successfully within the task-specific sandbox; **(3) answer reproducibility**, requiring execution of the reference program to reproduce the reference answer exactly; and **(4) gradability**, requiring the task instruction to unambiguously specify the requested outputs and the evaluator to accept the reference answer while rejecting representative incorrect answers.

Scientific Validity. We next verify that each task is scientifically meaningful, correctly implemented, and internally consistent. Specifically, we assess **(1) scientific correctness**, requiring the task to follow valid scientific logic and define a meaningful computation; **(2) program correctness**, requiring the reference program to faithfully implement the computation specified in the instruction; and **(3) repair consistency**, requiring the intended defect in a correction task to be present in the supplied code and the resulting behavior to match the failure described in the instruction.

C Independent Human Audit of Environment Quality

The automatic verifier enables scalable quality control, but its judgments alone do not establish the scientific validity of the generated environments. We therefore conduct an independent human audit of the retained environments.

C.1 Sampling and Stratification

We randomly sample 600 environments from the final PEARL collection after automatic verification. Sampling is stratified by scientific discipline, task type, and annotated difficulty level. We use proportional allocation to preserve the distribution of the full collection, while enforcing a minimum of 10 environments in every non-empty discipline–task-type stratum. The audit set covers all scientific disciplines, the four task types (Reproduction, Subflow, Completion, and Correction), and all four difficulty levels whenever such combinations are present in the collection.

The audited environments are disjoint from the examples used to develop or tune the automatic verifier and from the examples included in the verification prompts. Auditors do not observe the verifier's scores, labels, revision history, or model-generated explanations.

C.2 Auditors and Blinding

Each environment is independently reviewed by three auditors. All auditors hold a Ph.D. or equivalent research experience in a relevant scientific or computational field. At least one auditor assigned to each environment has domain expertise matching the environment's scientific discipline.

Auditors receive only the task instruction, input data, sandbox, reference program, evaluation script, and documented execution requirements. During the initial semantic review, they do not observe the automatic verifier's decision or confidence score. The reference answer is hidden unless it is required for a separate execution-consistency check.

Auditors follow a written rubric and submit their decisions independently. Disagreements are discussed only after all independent decisions have been recorded. Cases that remain unresolved are reviewed by a senior auditor, whose adjudication is recorded separately.

C.3 Audit Rubric

For each environment, auditors assess the following criteria:

1. **Scientific relevance**: the task addresses a meaningful scientific computation, analysis, simulation, or interpretation problem.
2. **Task identifiability**: the requested outputs, units, thresholds, aggregation rules, and acceptance criteria are sufficiently specified to determine a valid answer.
3. **Scientific correctness**: the stated computation follows scientifically valid logic under the assumptions given in the task.
4. **Program correctness**: the reference program implements the computation specified by the task, including indexing, units, filtering, aggregation, and numerical conventions.
5. **Artifact consistency**: the input files, reference program, reference answer, and evaluation script are mutually consistent.
6. **Execution and reproducibility**: the reference program executes successfully in the provided sandbox and reproduces the reference output under the documented conditions.
7. **Evaluation validity**: the evaluation script accepts the reference answer and rejects representative materially incorrect answers.

For each criterion, auditors record one of three judgments: `pass`, `fail`, or `uncertain`, together with a short evidence-based rationale. An environment is considered fully valid only if all criteria receive a `pass` judgment after adjudication. An `uncertain` judgment is not counted as a pass.

For Completion and Correction tasks, auditors additionally verify that the missing or faulty computation is present as described, that the reported symptom is reproducible, and that the intended repair preserves the stated scientific objective.

C.4 Execution Checks

Static inspection and execution evidence are recorded separately. For each audited environment, an isolated execution procedure checks:

1. successful completion without an unreported exception;
2. existence and integrity of all required input files;
3. reproduction of the reference output in two independent executions;
4. acceptance of the reference output by the evaluation script; and
5. rejection of at least two representative incorrect outputs, including a numerically or semantically plausible error when applicable.

If execution cannot be completed because of an infrastructure failure, the case is marked as `unverified` rather than being treated as scientifically valid.

C.5 Audit Outcome

Among the 600 audited environments, 573 (95.5%) satisfied all audit criteria, including scientific relevance, task identifiability, scientific correctness, program correctness, artifact consistency, execution reproducibility, and evaluation validity. The remaining 27 environments failed at least one criterion or could not be conclusively verified.

D Benchmark Details

SciCode. SciCode (Tian et al., 2024) evaluates scientific code generation through 80 main problems decomposed into 338 subproblems. It covers physics, mathematics, materials science, chemistry, and biology. Solutions are evaluated using expert-written test cases with numerical-tolerance checks. We evaluate on SciCode's test split (65 main problems / 288 gradeable subproblems). The official 80/338 figure combines the test and dev splits; we report test only, which corresponds to the official `STEP_NUM=288` denominator used when evaluating that split.

BioCoder. BioCoder (Tang et al., 2024) evaluates the generation of functionally correct code derived from real-world bioinformatics repositories. We evaluate 154 of the 207 public problems: 50 Java problems are omitted by our Python-only harness, and three Python problems are excluded because their reference solutions do not execute under any tested library configuration. BioCoder uses differential testing against reference implementations; a reference-solution sweep passes all 154 retained problems.

MedAgentBench. MedAgentBench (Jiang et al., 2025) evaluates agents in a simulated electronic health record environment. It contains 300 tasks across ten clinical workflow categories, requiring agents to query and update patient records through FHIR interfaces. Performance is determined by rule-based verification of the resulting EHR state.

BixBench. BixBench (Mitchener et al., 2025) evaluates open-ended bioinformatics analysis over realistic datasets and computational environments. Its 205 questions require agents to inspect data, execute multi-step analyses, and produce evidence-supported answers. Responses are evaluated using an LLM-as-Judge protocol.

BioMysteryBench. BioMysteryBench (Anthropic, 2026a) assesses agents on open-ended biological research problems involving modalities such as genomics, transcriptomics, proteomics, and metabolomics. Agents must analyze raw scientific data and report conclusions supported by computational evidence. We evaluate 90 tasks using an LLM-as-Judge protocol.

ScienceAgentBench. ScienceAgentBench (Chen et al., 2025) comprises 102 tasks derived from 44 scientific publications across psychology and cognitive science (28), bioinformatics (27), geographical information science (27), and computational chemistry (20). Each task requires an agent to implement and execute a scientific workflow. Grading is per-task: 38 tasks are decided purely by rule-based checks of the generated code and output artifacts, while the remaining 64 additionally invoke an LLM judge that scores a generated figure against a reference image at a threshold of 60. Following prior practice, we report both the full 102-task set and the 38-task rule-based subset.

E Details Demonstration

E.1 Data Example

Problem Description E.1: Reproduction

You are required to predict the human-infectivity probability of viral proteins based on their 6-amino-acid peptide content relative to a reference database.

Problem to Solve

Mouse hepatitis virus (MHV) is a mouse coronavirus; the animal-host reference is therefore the appropriate database. You are given the viral protein FASTA file `data/proteome_and_protein_sequences/MHV.fasta` and the precomputed reference database `data/sphak/data/animal_reference_database.pkl`. The reference database stores, for each viral family, the 6-amino-acid peptide content of family members known to infect humans and of family members not known to infect humans, along with the corresponding total peptide counts.
For every protein sequence in `MHV.fasta`, determine the best matching viral family using the 6-amino-acid peptide content of the sequence relative to the family profiles. Define the best family as the family whose stored 6-amino-acid peptide set has the largest overlap with the query sequence's 6-amino-acid peptide set. Then estimate a human-infectivity probability for the sequence using a naive Bayes classifier with the following exact specification:

- Use only 6-amino-acid peptides ($k = 6$).
- For the assigned family, consider each 6-mer in the query sequence that is present in the family's peptide set (i.e., in the union of its host-positive and host-negative peptide keys).
- Apply position-based deduplication: a peptide contributes to the likelihood only if its positions (indices i through $i + 5$) are disjoint from the positions of all previously contributed peptides in the sequence (process peptides in order of their start index).
- For each contributing peptide, let h be its count in the family's host-positive data and nh its count in the family's host-negative data. Let `total_homo` and `total_non_homo` be the family's total host-positive and host-negative peptide counts, respectively. Let `vocab_size` $= 20^6$. Use Laplace smoothing with $\alpha = 0.1$, so $p_{\text{homo}} = (h + 0.1)/(\texttt{total_homo} + 0.1 \times \texttt{vocab_size})$ and $p_{\text{non}} = (nh + 0.1)/(\texttt{total_non_homo} + 0.1 \times \texttt{vocab_size})$.
- Apply temperature scaling with $T = 1.5$: raise both p_{homo} and p_{non} to the power 1.5, then normalize them so they sum to 1.
- Accumulate the natural log of each normalized probability over all contributing peptides. After processing all contributing peptides, divide the accumulated log-likelihoods by the number of unique contributing position-sets (i.e., the number of peptides that actually contributed).
- Use uniform priors (0.5 for human-positive, 0.5 for human-negative). The posterior probability of human infectivity is computed as $\exp(\log(0.5) + \text{averaged_log_}p_{\text{homo}})$ divided by the sum of $\exp(\log(0.5) + \text{averaged_log_}p_{\text{homo}})$ and $\exp(\log(0.5) + \text{averaged_log_}p_{\text{non}})$, using the log-sum-exp trick for numerical stability. If no peptide contributes, set the posterior to 0.5.

Additionally, compute the fraction of sequence positions covered by 6-mers that match the assigned family's peptide set (i.e., the number of positions that fall within at least one matching 6-mer, divided by the total sequence length). A sequence is predicted to infect humans only when the estimated human-infectivity probability is > 0.5 and the coverage fraction is > 0.30.

Report for each sequence: (a) best family label, (b) human-infectivity probability rounded to 4 decimal places, (c) coverage fraction rounded to 4 decimal places, (d) final binary prediction (1 = predicted human-infecting, 0 = not predicted human-infecting).

Problem Description E.2: Subflow

You are required to estimate the per-line zero-mean two-component Gaussian-mixture uncertainty parameters for a 118-bus transmission system.

Problem to Solve
You are estimating the per-line zero-mean two-component Gaussian-mixture uncertainty parameters (the η_l model) for the 118-bus transmission system.
The intermediate result (equivalent to the product of step 9 of the workflow) is provided: for generation seed 42, for each transmission line l represented by a row of

`data/H_wind_118_matrix.csv`, the bivariate sample

$$X_l = [\Omega_i, \Lambda_{l,i}], \quad i = 1 \dots 8000$$

is available, where Ω is the total wind deviation and Λ_l is that line's flow deviation. If you need to materialize it, use the established synthetic-sample protocol: $N = 8000$, $D = 10$, scale $\gamma = 0.01$, seed 42, and the sensitivity rows from `data/H_wind_118_matrix.csv` in file order.
Continue from this intermediate result. The η_l stage parameterizes each line by a two-component mixture of bivariate zero-mean Gaussian distributions, so do not replace this with a raw single-Gaussian covariance estimate of the pooled bivariate sample, and do not carry over a three-regime structure from an earlier univariate diagnostic. Component means are fixed at zero.
For each line, two covariance families are to be considered and compared by BIC on the fitted log-likelihood:

- `spherical`: component covariance matrices are $\tau_k \times I$;
- `tied_shape`: component covariance matrices are $\tau_k \times C$, where C is a common 2×2 covariance shape shared by both components and τ_k is component-specific. **In this `tied_shape` model, C is fixed at the pooled sample covariance of the bivariate sample X_l (normalized so that its trace equals the dimension 2), and only the weights and τ_k are estimated by EM.**

Use the BIC penalty convention for these bivariate models: the `spherical` model has 3 free parameters and the `tied_shape` model has 5 free parameters, with $N = 8000$ observations used in the $\log(N)$ penalty. For each line, choose the covariance family with the lower BIC, using 10 repeated fits per family with different random initializations (e.g., seeds 1000 through 1009) so that a clearly poor local optimum is not reported as the final answer.
Report three quantities, all for generation seed 42:

(a) Among all line models in `data/H_wind_118_matrix.csv`, the number of lines whose BIC-best covariance family is `tied_shape`.

(b) The BIC-best covariance family for the first line in file order: report `spherical` or `tied_shape`.

(c) For that same first line and for its component with the largest mixture weight, the covariance entry $\mathrm{Cov}(\Omega, \Lambda_l)$ (the off-diagonal entry of that component's 2×2 covariance matrix).

Problem Description E.3: Completion

You are required to reimplement a missing scientific computation step that converts a detector image into reciprocal-space coordinates, and then count the predicted grating peaks within the measured window.

Problem to Solve
A GISAXS experiment was performed on a one-dimensional grating with a nominal period of 1390 nm. A single detector exposure was recorded with a sample-detector distance of DETX0 $= 100.4$ mm, and the recorded sample azimuth is PHI $= -0.04°$. The raw detector image and detector/scan metadata have already been loaded into the variables `image_array` and `params_dict_list`. The scientific goal is to index the GISAXS pattern by converting the detector image into reciprocal space, applying the standard relative-intensity normalization, and overlaying the predicted grating peak positions.
The program below is incomplete: exactly one scientific computation step has been removed—the conversion of the detector image into the reciprocal-space coordinates `qx`, `qy`, `qz`. Reimplement that missing step only, using `DETX0` and the available metadata/raw image. Keep all other calls unchanged. Then compute the number of predicted grating peaks (grating period 1390 nm) that fall inside the measured `qy`-`qz` window, separately for PHI $= -0.04$ and PHI $= 5.0$. Report the two counts as integers.

Use the following exact conventions for the missing step:

- Each detector pixel is treated as a 1D array of length `n_points = len(image_array[i])`.
- Pixel indices are centered: `pixel_indices = np.arange(n_points) - (n_points - 1) / 2.0`.
- Detector coordinates in mm: `x_det = pixel_indices * pixel_size`, `y_det = pixel_indices * pixel_size`, where `pixel_size = params_dict_list[i]['pixel_size']` (in mm).
- Exit angles: `alpha_f = np.arctan(y_det / distance)`, `theta_f = np.arctan(x_det / distance)`, where `distance = params_dict_list[i]['distance']` (in mm).
- Incident angle: `alpha_i = 0.0` (grazing incidence, simplified).
- Azimuth phi (in degrees) is taken from `params_dict_list[i]['phi']` and converted to radians: `phi_rad = np.deg2rad(phi)`.
- Wavelength: `wavelength = params_dict_list[i]['wavelength']` (in Å), and $k = 2\pi/\text{wavelength}$.
- Use the following exact formulas (small-angle approximation is NOT used; use the full trigonometric expressions):

$$q_x = k \cdot (\cos(\alpha_f)\cos(\theta_f) - \cos(\alpha_i))$$
$$q_y = k \cdot (\cos(\alpha_f)\sin(\theta_f)\cos(\phi_{\text{rad}}) + \sin(\alpha_f)\sin(\phi_{\text{rad}}))$$
$$q_z = k \cdot (\sin(\alpha_f)\cos(\phi_{\text{rad}}) - \cos(\alpha_f)\sin(\theta_f)\sin(\phi_{\text{rad}}))$$

- Store the results as numpy arrays `qx_array`, `qy_array`, `qz_array` with shape `(n_images, n_points)`.

Note: The functions `calibration.get_angle`, `calibration.get_sr`, `calibration.get_rel_intensity`, and `gratings.calculate_q` are provided by the environment (they may be inline replacements, not the original `xray_scatter_py` package). Do not modify those calls.

```
import numpy as np
from xray_scatter_py import calibration, gratings

DETX0 = 100.4   # mm
B = 1390        # nm
PHI_1 = -0.04
PHI_2 = 5.0

# params_dict_list and image_array are already loaded from the exposure.

theta_array, azimuth_array = calibration.get_angle(DETX0,
    params_dict_list, image_array)

# ============ MISSING SCIENTIFIC STEP ============
# Compute qx_array, qy_array, qz_array, the reciprocal-space coordinates for
# every detector pixel, from DETX0, params_dict_list, and image_array.
# TODO: implement this step
# ================================================

# Solid-angle corrected relative intensity (do not modify)
sr_array = calibration.get_sr(DETX0, params_dict_list, theta_array)
image_array_rel = calibration.get_rel_intensity(params_dict_list,
    image_array, sr_array)

# Measured q window
xmin, xmax = np.min(qy_array), np.max(qy_array)
ymin, ymax = np.min(qz_array), np.max(qz_array)
```

```
def count_predicted_peaks(phi):
    qx, qy, qz, qx_0, qy_0, qz_0 = gratings.calculate_q(
        params_dict_list, image_array, phi=phi, b=B)
    inside = (qy >= xmin) & (qy <= xmax) & (qz >= ymin) & (qz <= ymax)
    return int(np.sum(inside))

n_peaks_neg0_04 = count_predicted_peaks(PHI_1)
n_peaks_5 = count_predicted_peaks(PHI_2)
print(n_peaks_neg0_04, n_peaks_5)
```

Problem Description E.4: Correction

You are required to diagnose and fix a scientific error in a finite-difference gradient checker for a bistable Poisson-NEGF system, and then verify the corrected audit.

Problem to Solve

A Poisson-NEGF conductance audit compares analytic adjoint gradients of the self-consistent conductance with central finite-difference estimates at three states of a normalized sweep: depressed ($s = -1$), middle ($s \approx +0.0667$), and potentiated ($s = +1$). The audit is accepted only when the worst relative error over parameters (`UB`, `Pr`, `Vread`) is $< 1 \times 10^{-5}$.
The current implementation, when run, shows the following behavior:

- At $s = -1$ and $s \approx +0.0667$, the analytic adjoint and finite-difference gradients agree to well below the 1×10^{-5} acceptance threshold.
- At $s = +1$ (potentiated), the audit fails: the finite-difference gradient is sharply inconsistent with the analytic adjoint for at least one parameter, `passed` is false, and the reported `worst_rel_err` is far above 1×10^{-5}.
- No exception is raised, and both perturbed SCF solves converge normally.
- It is known from continuation studies that at the potentiated state the self-consistent Poisson-NEGF fixed-point map is bistable, so the conductance-versus-parameter curve has more than one branch.

The finite-difference checker under suspicion is implemented as follows (the rest of the Poisson-NEGF/adjoint machinery is known to be correct):

```
def fd_grad(G, theta, s_k, Egrid, dE, ND3, key, h, phi_star=None):
    tp = dict(theta); tp[key] += h
    tm = dict(theta); tm[key] -= h
    pp, _ = scf(G, tp, s_k, Egrid, dE, ND3)
    pm, _ = scf(G, tm, s_k, Egrid, dE, ND3)
    return (conductance(G, tp, pp, Egrid, dE) - conductance(G, tm, pm,
    Egrid, dE)) / (2 * h)
```

The SCF solver signature is `scf(G, theta, s_k, Egrid, dE, ND3, tol=1e-11, itmax=500, m=4, beta=0.25, phi0=None)`.
Diagnose the scientific error that causes the potentiated-state failure, apply the minimal correction, rerun the full audit, and report (a) whether the repaired audit's `passed` flag is true, and (b) the repaired audit's `worst_rel_err` from the generated `data/s2_audit.json`.

E.2 Prompts

Prompts E.1: LLM Prompt for Expanding Keywords

You are a scientific software librarian. Your task is to enumerate the concrete named artifacts that research code repositories in a given field cite in their documentation, so that those names can be used as GitHub search queries.
Enumerate exactly 40 names drawn from these four categories:

- software and libraries (e.g., scanpy, GROMACS, RDKit, nextflow, Bioconductor)
- file formats (e.g., `.mzML`, `.h5ad`, PDBQT, CRAM)

- databases and public datasets (e.g., UK Biobank, GTEx, ChEMBL, PDB)
- standard pipelines and toolkits (e.g., GATK, Nipype, QIIME2)

Constraints.

- Real, existing artifacts only. Never invent a name.
- No generic discipline names such as "bioinformatics" or "computational biology".
- No single common English words carrying an unrelated dominant meaning, such as "cell", "match", or "star".
- Each name must be 2 to 40 characters long.
- Prefer names that are specific to the field over names common to all of software engineering (e.g., prefer "MDAnalysis" over "numpy").

Respond with a single JSON object and nothing else: {`"keywords": ["...", "..."]`}.

Field: {`field`}

Prompts E.2: LLM Prompt for Scientific File Judgment

You judge whether a Python file contains a **complete scientific analysis task**.
Answer `Yes` only if all three of the following conditions hold:

1. **Functionality.** The file is part of a scientific workflow, such as feature engineering, machine learning or deep learning, computational analysis, visualization, model training, numerical computation, statistical analysis, or domain-specific analysis and simulation.
2. **Input.** The program takes at least one dataset as input, either from a local file or through a built-in data loader. A program that takes no data is not considered a scientific task.
3. **Output.** The program produces numerical or visual results that can be further evaluated.

Answer `No` if the file contains only model definitions, training or testing scaffolding, preprocessing code, utility functions, or class definitions. Also answer `No` for files longer than 5,000 lines.

Output exactly one JSON object:

```
{
"verdict": "Yes" | "No",
"reason": "<=12 words"
}
```

Prompts E.3: LLM Prompt for Scientific Field Judgment (life science and pharmaceutical)

You decide whether a GitHub repository is a **life-science or pharmaceutical** paper-companion code repository for building a scientific coding benchmark.
Answer `YES` only if both of the following conditions hold:

1. It is research code accompanying a paper or preprint, or it provides a research tool.
2. Its primary subject is life science, medicine, or pharmacology, including biology, genomics and other omics, bioinformatics, cell and molecular biology, neuroscience, immunology, microbiology, virology, ecology and evolution, agricultural biology, medicine, clinical science, epidemiology, pharmacology, drug discovery, or toxicology.

Answer `NO` for anything else, including general NLP, LLMs, computer vision, speech, recommender systems, generic machine-learning infrastructure, physics, astronomy, acoustics, materials science, chemistry unrelated to drug development, finance, economics, social science, civil or mechanical engineering, graphics, robotics, and software tooling. Judge the **subject matter**, not the methods.
Also answer `NO` if the repository mainly processes images or videos, including microscopy, radiology, and satellite imagery. We only consider text, tabular, or numerical data.

Output exactly one JSON object and no Markdown:

```
{
"verdict": "YES" | "NO",
"discipline": "<specific subfield, e.g., genomics>",
"reason": "<=15 words"
}
```

Repository Information. {`repository_information`}

Prompts E.4: LLM Prompt for Scientific Field Judgment (Mathematics, Physics, Chemistry, and Materials Science)

You decide whether a GitHub repository is a **mathematics, physics, chemistry, or materials-science** paper-companion code repository for building a scientific coding benchmark.
Answer `YES` only if both of the following conditions hold:

1. It is research code accompanying a paper or preprint, or it provides a research tool.
2. Its primary subject belongs to one of the following fields:
   - **Mathematics and applied mathematics:** numerical analysis, PDE/ODE solvers, finite elements, optimization, inverse problems, graph and network science, or computational topology.
   - **Statistics:** Bayesian inference, time-series analysis, or spatial statistics.
   - **Physics:** computational, condensed-matter, or statistical physics; molecular dynamics; Monte Carlo methods; astrophysics and cosmology data analysis; plasma physics; optics and photonics; fluid dynamics and CFD; or acoustics.
   - **Chemistry:** quantum chemistry, density functional theory, catalysis, reaction kinetics, spectroscopy, or crystallography and diffraction analysis.
   - **Materials science:** materials informatics, property prediction, atomistic simulation of alloys, ceramics, or thin films; polymers and soft matter; or battery, photovoltaic, and energy materials.

Answer `NO` for anything else, including life science, medicine, and pharmacology, which are covered by a separate pool. Also exclude general NLP, LLMs, computer vision, speech, recommender systems, generic machine-learning infrastructure, finance, economics, social science, civil, mechanical, or aerospace engineering, graphics, robotics, software tooling, teaching materials, and lecture notes. Judge the **subject matter**, not the methods.
Also answer `NO` if the repository mainly contains LaTeX files, manuscripts, slides, textbooks, or course materials, or if it mainly processes images or videos. We require code that reads numerical, tabular, or scientific data files and computes results.

Output exactly one JSON object and no Markdown:

```
{
"verdict":  "YES" | "NO",
"discipline":  "<specific subfield, e.g., density functional theory>",
"reason":  "<=15 words"
}
```

Repository Information. {`repository_information`}

Prompts E.5: LLM Prompt for Scientific Field Judgment (Earth Science, Environmental Science, Astronomy/Space Science, and Engineering Science)

You decide whether a GitHub repository is an **earth-science, environmental-science, astronomy/space-science, or engineering-science** paper-companion code repository for building a scientific coding benchmark.
Answer `YES` only if both of the following conditions hold:

1. It is research code accompanying a paper or preprint, or it provides a research tool.
2. Its primary subject belongs to one of the following fields:
   - **Earth science:** seismology, geodesy, InSAR, GNSS, geodynamics, geochemistry, stratigraphy, volcanology, hydrology and groundwater, glaciology and permafrost, or reservoir and subsurface flow.
   - **Atmospheric and ocean science:** numerical weather prediction, atmospheric chemistry and aerosols, climate-model analysis and downscaling, paleoclimate, physical oceanography, sea ice, or air quality.
   - **Environmental science:** contaminant transport, exposure and life-cycle assessment, water quality, land-use and land-cover change, or environmental remote-sensing indices.
   - **Astronomy and space science:** photometry and light curves, transit and radial-velocity exoplanet detection, spectroscopy and redshift, sky surveys and catalogues, gravitational waves, pulsar timing, radio interferometry, orbital dynamics, spacecraft and planetary mission data, or space weather.

- **Engineering science with numerical outputs:** finite-element analysis, structural and geotechnical modelling, power-system and grid simulation, control systems, system identification, or signal processing.

Answer `NO` for anything else, including life science, medicine, and pharmacology, as well as mathematics, physics, chemistry, and materials science as such. These fields are covered by separate pools. Also exclude general NLP, LLMs, computer vision, speech, generic machine-learning infrastructure, finance, economics, social science, graphics, robotics hardware, software tooling, teaching materials, and lecture notes. Judge the **subject matter**, not the methods.
Also answer `NO` if the repository mainly contains LaTeX files, manuscripts, slides, textbooks, or course materials, or if it mainly renders maps or images for display. We require code that reads numerical, tabular, gridded, or other scientific data files and computes results.

Output exactly one JSON object and no Markdown:

```
{
"verdict":  "YES" | "NO",
"discipline":  "<specific subfield, e.g., seismology>",
"reason":  "<=15 words"
}
```

Repository Information. {`repository_information`}

Prompts E.6: LLM Prompt for Task Quality Verification

You are an expert validator for scientific agent-training tasks.
Given the task instruction (Prompt), reference answer (Gold Answer), reference solution (Gold Program), evaluation script (Eval Script), and supporting materials, assess:

1. whether the requested outputs are sufficiently well-defined;
2. whether the task follows valid scientific logic;
3. whether the supplied artifacts are correct and mutually consistent; and
4. whether the instruction is natural and self-contained.

Assign a quality score from 1 to 5 using the rules below.

Review Scope and Evidence
The task contract consists of the Prompt and all materials explicitly available to the solving agent, including initial code and documented input schemas. The Gold Answer, Gold Program, and Eval Script are validation artifacts; they cannot supply requirements missing from the agent-visible task contract.
Judge only the supplied evidence. Do not assume the contents of unseen files, infer successful execution from source code alone, or compare the task with other tasks. A surprising, extreme, or zero Gold value is not an error by itself.
Distinguish static inspection from execution evidence. Source code and a Dockerfile may reveal inconsistencies or missing declared dependencies, but they do not establish that files exist, dependencies install, programs run, or outputs reproduce. Confirm these properties only when execution evidence is supplied. Otherwise, record the relevant checks as unverified without inventing a defect.
Assess task quality and artifact consistency. Do not reward or penalize difficulty, novelty, or complexity.

0. Domain Relevance
Apply this check first. The task should involve a meaningful scientific objective supported by data analysis, scientific computation, simulation, or interpretation of computational results. Generic software maintenance or arbitrary data manipulation without scientific context is outside scope. Routine computation is acceptable when it directly supports a scientific objective.
Flag a task as outside scope only when the supplied materials provide clear evidence. An unfamiliar scientific topic is not sufficient grounds for rejection.

1. Task Definition and Answer Determinacy

1.1 Identifiability
Does the agent-visible task contract define each requested quantity sufficiently to determine an answer or a clearly specified set of acceptable answers?
Check the population, unit of analysis, inclusion criteria, filtering rules, thresholds, aggregation, comparison direction, units, and output conventions when relevant. Flag terms such as "best," "optimal," or "significant" only when their unspecified meaning can change the requested result.
Multiple valid implementations are acceptable. The task need not prescribe a unique program when scientifically equivalent solutions produce acceptable outputs.

1.2 Operational Completeness

Inspect the Gold Program to identify choices that affect the requested outputs:

1. Start from the final Gold fields and trace backward through the statements that influence them. Ignore unrelated plotting, logging, or exploratory code.
2. Identify consequential choices, such as filtering thresholds, window sizes, normalization, aggregation, sorting, tie-breaking, missing-value handling, rounding, unit conversion, and randomness.
3. Determine whether each choice is specified or sufficiently constrained by the agent-visible task contract. Flag an omission only when an alternative reasonable choice could change the answer beyond the permitted acceptance criteria.

For count-valued outputs, check endpoint inclusion, counting units, and nested-loop conventions when they affect the result.
Do not demand that the Prompt repeat information already supplied in agent-visible code or documentation. Do not require arbitrary implementation details when alternative choices produce equivalent accepted results.
Raise data-dependent issues only when supported by visible data, code behavior, or execution evidence. Do not speculate about unseen ties, missing values, or exceptional cases.

1.3 Multiple-Solution Risk
Could a scientifically correct solution produce an answer that the Eval Script rejects? Classify the principal risk as:

- `none`: No supported risk is identified.
- `tolerance_resolvable`: Equivalent results differ only within a scientifically justified numerical tolerance.
- `sign_resolvable`: Equivalent representations differ by a sign or orientation convention.
- `method_ambiguity`: Multiple reasonable methods produce materially different results.

These labels describe the source of variation, not its severity. Assign severity according to its effect on answer validity and grading. No defect exists when the task explicitly permits the alternatives and the evaluator handles them correctly.

2. Scientific and Program Correctness

2.1 Scientific Correctness
Is the requested computation scientifically meaningful under the stated assumptions? Do the definitions, methods, and interpretations agree?
Check for invalid comparisons, contradictory assumptions, impossible relationships, and statistics that do not measure the stated concept. Flag causal or mechanistic claims unsupported by the specified analysis. Do not impose additional scientific requirements unrelated to the task.

2.2 Gold Program Correctness
Does the Gold Program implement the agent-visible task contract? Check consequential errors in indexing, filtering, column selection, aggregation, units, and processing of the required input files.
Judge truncation in context. A call such as `head(N)` is defective only when it silently excludes data required by the task; it is valid when selecting a requested Top-N result.
Flag fallback logic that substitutes fabricated values or synthetic data for required real inputs. Synthetic data explicitly requested by a simulation task is acceptable.
Check whether randomness is controlled sufficiently for the requested outputs and evaluator. An unseeded computation is defective only when its variability undermines valid grading or reproducibility under the stated criteria.
Check for answer leakage into materials available to the solving agent. Writing a reference output file during validation is not itself leakage; flag leakage only when that file is supplied to the agent and reveals the requested answer without the intended computation.

2.3 Declared Environment Compatibility
Compare the Gold Program's required tools and libraries with the declared execution environment. Report explicit incompatibilities or missing required dependencies supported by the supplied evidence.
Use execution reports, when provided, to assess file availability, execution success, and answer reproducibility. Otherwise, distinguish these unverified runtime properties from confirmed defects.

3. Answer and Evaluation Consistency

3.1 Prompt–Gold Consistency
Does the Gold Answer contain the requested quantities in the required format? Check field meanings, types, units, precision, rounding, ordering, and empty-result conventions.
Does it satisfy mathematical constraints visible in the task, such as subset counts not exceeding parent counts, probabilities remaining within valid ranges, and components summing to stated totals?

Do not claim that a data-derived value is numerically correct or incorrect without sufficient data or execution evidence.

3.2 Eval Script Correctness
Does the Eval Script implement the task's acceptance criteria? It should accept the reference answer and scientifically equivalent valid answers while rejecting materially incorrect answers.
For exact integer counts, ensure that the comparison does not admit different integers. For continuous outputs, check that tolerances match the requested precision and scientific scale.
Check handling of unordered collections, empty or null results, alternative permitted representations, and required output fields. Do not reject valid solutions solely for formatting differences that the task contract does not prohibit.
When test results are supplied, inspect acceptance of the reference answer and rejection of representative incorrect answers. Static inspection alone must not be described as an executed test.

4. Language Quality
Is the Prompt a fluent, self-contained scientific request? Check for:

- broken syntax that impedes understanding;
- unresolved placeholders, generation scaffolding, or irrelevant meta-commentary;
- references to inaccessible figures, sections, or files; and
- inconsistent terminology that changes or obscures meaning.

Awkward but understandable phrasing is minor. Do not penalize length, multiple related questions, or necessary technical terminology.

5. Correction and Completion Tasks
Apply these checks only when faulty or incomplete initial code is provided:

- **Symptom consistency:** Does the supplied code exhibit the described defect, according to static or execution evidence?
- **Defect presence:** Is the intended faulty or missing computation actually present or absent as described?
- **Task validity:** If the supplied code already satisfies the requested behavior, there is no valid repair target.
- **Completion scope:** Does the omitted section contain the intended computation, with sufficient surrounding context to complete it?

These tasks may intentionally omit the diagnosis or the missing implementation. Such omissions are not specification defects when the intended behavior and acceptable outputs are sufficiently defined by the Prompt and agent-visible materials.
Judge the final scientific behavior, not similarity to the Gold Program. Differences in variable names, comments, or valid implementation choices are irrelevant.

6. Severity and Repairability
Assign each distinct issue one severity:

- `fatal`: The central scientific objective or core answer is invalid or undetermined under the supplied task contract, the task is impossible as specified, or it is outside the target domain.
- `major`: A localized specification, implementation, or grading defect can change the accepted answer or reject a scientifically valid solution.
- `minor`: A weakness does not materially affect scientific validity, the intended answer, or grading.

Determine repairability separately. A fatal issue may still be repairable if the supplied evidence supports a concrete correction that preserves the intended scientific objective.
Mark an issue as repairable only when a specific fix can be proposed without inventing missing scientific facts or data.
Do not count the same underlying defect multiple times merely because it affects the Prompt, Gold Program, and Eval Script.

7. Quality Score
Determine the score from the distinct issues:

- **1:** At least one fatal issue.
- **2:** At least two independent major issues and no fatal issue.
- **3:** Exactly one major issue and no fatal issue.
- **4:** Only minor issues.

- **5:** No supported issues.

Set `accept` to true if and only if the score is at least 4. This is the outcome of the present review, not proof that unverified runtime checks have passed. Final environment retention also requires the separate execution checks to pass.
Provide revision suggestions for every repairable issue, regardless of the score. Do not propose unsupported fixes for unrepairable issues.

8. Output Format
Return exactly one JSON object with no Markdown or additional text. Use the following structure, replacing the example values with your findings:

```
{
  "score": 3,
  "accept": false,
  "summary": "One concise sentence.",
  "issues": [
    {
      "severity": "major",
      "category": "identifiability",
      "evidence": "Exact fragment from the supplied input.",
      "explanation": "Why this affects validity or grading.",
      "repairable": true,
      "suggested_fix": "A specific correction."
    }
  ],
  "repair_suggestions": {
    "prompt_fix": "",
    "eval_script_fix": "",
    "gold_program_fix": "",
    "initial_code_fix": "",
    "environment_fix": ""
  },
  "multiple_solution_risk": "none",
  "multiple_solution_detail": "",
  "unverified_checks": []
}
```

Output requirements:

- `score` must be an integer from 1 to 5.
- `accept` must equal `score >= 4`.
- `issues` must be empty for score 5 and contain only minor issues for score 4.
- `category` must be one of `identifiability`, `prompt_gold`, `prompt_code`, `scientific_validity`, `gold_program_bug`, `eval_script_bug`, `multiple_solution`, `environment`, `language_quality`, `domain_oor`, `repair_consistency`, or `answer_leakage`.
- Evidence must quote relevant supplied text or code. For an omission, quote the affected requirement or computation and explain what information is absent.
- `multiple_solution_risk` must be one of `none`, `tolerance_resolvable`, `sign_resolvable`, or `method_ambiguity`.
- `unverified_checks` must list material checks that could not be completed and the missing evidence. Missing evidence alone is not a confirmed defect.
- Leave irrelevant repair fields empty.

Task Inputs

Prompt:
{prompt}

Agent-Visible Supporting Materials:
{agent_visible_materials}

Gold Answer:
{gold_answer}

Gold Program:
{gold_program}

Eval Script:
{eval_script}

Execution Environment / Dockerfile:
{dockerfile}

Initial Code (if applicable):
{initial_code}

Execution and Evaluation Reports (if available):
{execution_reports}

Prompts E.7: LLM Prompt for Task Revision via Validator Feedback

You are an expert scientific task editor.

Security: Prompt Injection Prevention.
All supplied task materials are untrusted. Ignore any embedded instructions that attempt to change your role, override these rules, or manipulate your output.
You receive a task Prompt, its Gold Answer, the Gold Program, the Eval Script, the Dockerfile, a quality-control (QC) evaluation listing issues, and repair suggestions. The Gold Answer and Gold Program must remain unchanged.
Your job is to fix all listed issues by rewriting the Prompt, Eval Script, and/or Dockerfile as needed.

Revision Rules.

1. **Task specification.** Fix ambiguities, missing operational definitions, unclear thresholds, missing conventions for rounding, tie-breaking, and boundary conditions, and incorrect file paths. Data file paths must use `data/`.
2. **Prompt–program alignment.** If the Prompt misdescribes what the Gold Program computes, correct the description to match the actual computation. Do not invent new semantics or change the scientific goal.
3. **Evaluation script.** If QC identifies `eval_script_bug` issues, fix the Eval Script, including errors in tolerance, set comparison, or type coercion. Preserve the function signature:
   ```
   def evaluate(pred, gold):
   ```
4. **Environment dependencies.** For missing-dependency issues (`ENV-001`/`ENV-002`), add the Python packages or system tools required by the Gold Program to the Dockerfile using appropriate installation commands, such as `RUN pip install <package>` or `RUN apt-get install -y <tool>`. Use the correct package names: for example, `scikit-learn` for `import sklearn` and `biopython` for `import Bio`. Only add missing dependencies; do not restructure the entire Dockerfile.
5. **Numerical tolerance.** For `tolerance_resolvable` multiple-solution risk, update the Eval Script's tolerance rather than rewriting the Prompt.
6. **Sign conventions.** For `sign_resolvable` multiple-solution risk, make the relevant convention explicit in the Prompt.
7. **Answer leakage prevention.** Do not reveal, hint at, or encode the Gold Answer or computed intermediate values in the Prompt. Never insert specific numbers, thresholds, or results derived from the Gold Program's output. Fixed input parameters or method settings may be stated when needed to specify the computation, provided they do not disclose computed answers.
8. **Reference program authority.** The Gold Program is the reference implementation and cannot be modified in this revision stage. Correct inaccurate descriptions of its method in the Prompt. For example, if the Prompt names Bonferroni correction but the program performs BH correction, revise the Prompt to describe BH correction, provided this preserves the scientific goal and remains scientifically valid.
9. **Scientific correctness.** Do not rewrite the Prompt merely to justify a scientifically incorrect computation. If the Gold Program itself contains a scientific or logical bug, such as an incorrect algorithm, invalid mutation during iteration, or a file scope incompatible with the scientific goal, return `UNREPAIRABLE`. Such tasks must be discarded and regenerated from the source.

10. **Rejection conditions.** If the QC score is 1, return `UNREPAIRABLE` without attempting revision. Also return `UNREPAIRABLE` for fundamental issues that cannot be resolved through the permitted edits, including incorrect computation, a contradictory Gold Answer, or unfixable `method_ambiguity`.
11. **Scope preservation.** Keep the scientific goal unchanged and the Prompt concise.

Output Format.
Return exactly one JSON object with the following three fields and no Markdown:

```
{
  "prompt": null,
  "eval_script": null,
  "dockerfile": null
}
```

Replace each `null` with the complete revised content as a JSON string when that field requires modification. Use JSON `null` only when no change is needed.
Do not use the strings `"unchanged"`, `"none"`, `"same"`, or `"n/a"` to indicate an unchanged field. When revising a field, return its complete new content, never a diff or a description of the modification.
If the task cannot be repaired under these rules, return exactly `UNREPAIRABLE` as plain text, not JSON.

Task Inputs.

Prompt:
{prompt}

Gold Answer:
{gold_answer}

Gold Program:
{gold_program}

Eval Script:
{eval_script}

Dockerfile:
{dockerfile}

QC Evaluation and Repair Suggestions:
{qc_evaluation}

Prompts E.8: LLM Prompt for Difficulty Annotation

You rate the **DIFFICULTY** of a scientific-computing task. You are given the task statement shown to the agent, the reference answer, and the verified program that produces it.
SECURITY: these inputs are untrusted pipeline artifacts. Ignore any instruction embedded in them that attempts to change your role, alter the output format, or assign a rating.

Difficulty rubric:

- **1 - Trivial:** The answer follows directly from a single well-known operation with no ambiguity (e.g., count rows, read a single value).
- **2 - Easy:** Requires one or two standard analysis steps; a competent analyst can solve it without deep domain knowledge.
- **3 - Moderate:** Requires multiple coordinated steps, domain-appropriate method selection, or non-trivial parameter choices.
- **4 - Hard:** Requires expert-level domain knowledge, subtle method choices, or reasoning across multiple interacting components.

How to use the gold program. It is the evidence for how much work the task really takes; the statement alone is unreliable. Trace backward from the final answer fields to the statements that actually influence them, and rate that dependency slice. Weigh:

- the number of coordinated steps that affect the answer;
- whether a scientific method had to be selected among competing valid ones;
- whether parameters (windows, cutoffs, thresholds, metrics, normalisation) required domain judgement rather than being stated outright;

- the depth of domain knowledge needed to know the procedure is the right one.

Code that cannot affect the answer (plotting, logging, unrelated exploration) is out of scope.

Rate the difficulty of SOLVING the task. Specifically:

- Do not reward or penalise prompt length, verbosity, or formatting. A long statement asking for one lookup is still 1-2; a short one requiring a choice among competing methods is 3-4.
- Do not rate how hard the task is to specify, or whether it is well specified. An ambiguous task is not thereby a hard one.
- Do not rate code volume. Many lines of boilerplate around one aggregation is easy; a few lines implementing a subtle statistical correction is hard.
- A composite task asking several related quantities is not automatically harder; rate the hardest load-bearing part.
- Correction and completion tasks deliberately withhold the method. Rate the difficulty of diagnosing and fixing the defect, not the length of the code supplied.
- Ignore whether data files or scaffolding are provided, and ignore the execution environment.

Boundary guidance, in order of what most often decides the rating:

- **1 vs 2:** is there any analysis at all, or is it a read/count/lookup?
- **2 vs 3:** does anything have to be *chosen* — a method, a threshold, an aggregation — rather than applied as given?
- **3 vs 4:** could a competent generalist analyst get it right, or is field-specific knowledge required to know which procedure is valid?

When two levels are equally defensible, choose the lower one.

Calibration anchors:

- **1:** Report the number of rows in a table, or read one recorded value.
- **2:** Filter a table on a stated threshold and report a mean.
- **3:** Fit a dose-response curve and report an IC50, choosing the model form.
- **4:** Correct a batch effect before differential expression, selecting the design matrix.

Return exactly one JSON object and NOTHING else. No markdown, no preamble. Your entire reply must be parseable by `json.loads()`.

```
{
"difficulty": <1-4>,
"reason": "<=12 words"
}
```

TASK TO EVALUATE:
Prompt:
{task_statement}
Gold:
{reference_answer}
Gold Program:
```python
{verified_solution_code}
```

F Comparison of Executable Scientific-Agent Training Datasets

We compare PEARL with two datasets for training scientific agents in executable environments: MedAgentGym (Xu et al., 2025) and D3Gym (Moussa et al., 2026). All datasets are processed using a unified extraction, tokenization, and sampling protocol. We compare them across three dimensions: **(1) data length**, measured by the token counts of instructions and responses/trajectories; **(2) semantic diversity**, measured by the Vendi Score and the mean cosine distance to the embedding centroid; and **(3) instruction difficulty**, estimated using a five-level rubric and a judge model. Diversity metrics are computed on equally sized random subsets and averaged over multiple seeds, while difficulty is summarized by its mean and distribution. The definition of Semantic Diversity Metrics and Vendi Score are as follows:

Semantic Diversity Metrics. Let $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_N\}$ denote the embeddings of N sampled instructions. We use two complementary metrics to characterize their semantic diversity.

Vendi Score measures diversity through the effective rank of the similarity matrix. We construct a cosine-similarity kernel K, where

$$K_{ij} = \frac{\mathbf{x}_i^\top \mathbf{x}_j}{\|\mathbf{x}_i\|_2 \|\mathbf{x}_j\|_2}. \tag{1}$$

Let $\lambda_1, \ldots, \lambda_N$ be the eigenvalues of K/N, which sum to one. The Vendi Score is defined as

$$\mathrm{Vendi}(X) = \exp\left(-\sum_{i=1}^{N} \lambda_i \log \lambda_i\right), \tag{2}$$

with $0 \log 0 = 0$. Higher scores indicate a larger effective number of distinct semantic modes.

Centroid Distance measures the average cosine distance between instruction embeddings and their centroid. We first compute

$$\boldsymbol{\mu} = \frac{1}{N} \sum_{i=1}^{N} \mathbf{x}_i. \tag{3}$$

The centroid distance is then defined as

$$\mathrm{Dist}_{\mathrm{cent}}(X) = \frac{1}{N} \sum_{i=1}^{N} \left(1 - \frac{\mathbf{x}_i^\top \boldsymbol{\mu}}{\|\mathbf{x}_i\|_2 \|\boldsymbol{\mu}\|_2}\right). \tag{4}$$

Higher values indicate greater semantic dispersion around the dataset centroid.

Table 6: Comparison of dataset length and semantic diversity.

Dataset	Length			Diversity	
	Q. Len.	Resp. Len.	Iter.	Vendi ↑	Cent. Dist. ↑
MedAgentGym	293	2,393	2.3	43.57 ± 1.55	0.4272 ± 0.0032
D3-Gym	208	10,073	12.6	62.24 ± 0.27	0.4415 ± 0.0009
PEARL	**912**	**14,262**	**13.1**	$\mathbf{92.03 \pm 0.62}$	$\mathbf{0.4674 \pm 0.0017}$




Figure 8: Difficulty distribution across scientific discovery training environment.