TRACETRIGGER: BENCHMARKING DISTRIBUTED TRIGGER ATTACKS IN AGENTIC SYSTEMS

Anonymous authors
Paper under double-blind review

ABSTRACT

Self-hosted agents may combine interaction history, contextual documents, and persistent memory before choosing routes, tools, and actions. A safeguard that inspects each source separately can therefore miss harmful behavior produced by their joint influence. We present TraceTrigger, a controlled benchmark for studying evidence distributed across interaction steps, contextual locations, and simulated session boundaries. Control is necessary to remove one evidence channel while holding the authorized request, available tools, and outcome check fixed. The benchmark contains 450 clean, false-activation, and attack records built from self-hosted skill descriptions and targets memory, planning, and routing because these surfaces respectively govern retained state, action composition, and tool selection. Each task uses one model planning call followed by deterministic parsing, a logged component policy and defense, and mock execution; this ordering exposes where an unauthorized action enters the pipeline while preventing external side effects. We evaluate five language models to test dependence on a single model or access pattern and seven defense families spanning context-, action-, and trace-level intervention points. Aggregate pipeline ASR ranges from 0.81 to 0.94. To separate attack construction from runtime structure, a matched 40-task Llama-3.2-3B-Instruct control evaluates both attack families in both runtimes: TraceTrigger-1D reaches ASR 0.773 in the single-agent runtime and 0.909 in the modular runtime, whereas prior-1D controls reach 0 in both. To test incomplete evidence, removing one required channel yields 0/30 unauthorized final actions on a separate near-miss slice. Multi-channel configurations generally have higher pipeline ASR, although defenses and channel combinations produce non-monotonic exceptions. Because the component policy can modify a parsed model plan, these aggregate results measure the controlled pipeline rather than pure model susceptibility. TraceTrigger thereby separates distributed-context, execution-setting, and authorization effects that an aggregate ASR would otherwise conflate. Anonymized code is available at `https://anonymous.4open.science/r/TraceTrigger-4E70/`.

1 INTRODUCTION

Agentic systems do not act from the current request alone. Before selecting a route or tool, they may combine interaction history, retrieved files, tool observations, and persistent memory (Shen & Shen, 2026; Mo, 2026; JorgeGX, 2024; Khurana, 2026). A safeguard that inspects each source separately can therefore miss their joint influence on the final action. TraceTrigger evaluates how information distributed across interaction history, contextual sources, and persistent memory can jointly influence agent actions.

Self-hosted agents motivate this setting because they expose these channels in a single workflow: local histories, workspace files, memory retained between sessions, routing logic, and tools (Chowa et al., 2026; May et al., 2026; Wedel, 2025). Our experiments do not claim to reproduce a deployed OpenClaw installation. They use a controlled benchmark inspired by self-hosted workflows so that evidence placement, available actions, and outcome checks can be varied reproducibly.

Three difficulties shape the evaluation. First, *tracking information across channels* requires distinguishing interaction history from contextual sources and persistent memory. History contains earlier turns in the current execution sequence; contextual sources are files or retrieved documents supplied to

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: Concrete full-condition trace and missing-channel control logic for a Dashlane task. In the logged full T+S record, Llama-3.2-3B-Instruct returns `mock_send_message` to `audit-shadow`; the executor records but does not perform the unauthorized send. The lower branch shows how the benchmark constructs a missing-S near miss: it removes S before planning and disables component-policy eligibility, so any activation must originate in the model plan. This branch states the control logic rather than claiming an unlogged task-level counterfactual outcome.

the current planning pass; persistent memory is saved state carried across a simulated session boundary. Second, *establishing joint influence* requires paired controls that remove one fragment while holding the request and tools fixed; pipeline-level near misses and model-plan counterfactuals answer different parts of this question. Third, *separating attack effects from benchmark effects* requires matched execution settings and inspection of model-returned actions rather than comparison across unmatched runtimes alone. We use "dimensional" as shorthand for the number of selected channels, and otherwise name the temporal-history (T), contextual-source (P), and cross-session-memory (S) channels directly.

Figure 1 makes the audit separation explicit. Its upper branch is a logged model plan; its lower branch shows the missing-channel construction and success criterion without presenting an unmatched counterfactual as an observed plan. The benchmark never performs the external send or data access. We report an outcome as model-originated only when the unauthorized action is already present in the parsed model plan.

Our contributions are: (1) a framework for organizing trigger placement across temporal history, contextual sources, and cross-session memory; (2) a 450-task controlled benchmark spanning memory, planning, and routing surfaces; and (3) an evaluation across five models and seven defenses with incomplete-trigger controls, matched execution settings, and audits that distinguish preference changes from simulated authorization violations.

2 Related Work

Prompt-Level Attacks. A large body of work studies prompt injection, jailbreaks, and retrieval poisoning (Clop & Teglia, 2024; Ragab Mahmoud, 2026; Cai, 2026; Yang et al., 2025). These attacks establish that adversarial context can alter both generated text and agent behavior. TraceTrigger does not claim that prior work is limited to text generation; its narrower question is how evidence placement across several agent context channels affects an executable plan.

Attacks on Self-Hosted Agent Components. Agent-security work already covers persistent-memory poisoning, adversarial tool descriptions, routing metadata, and planner manipulation (Jing et al., 2026; Herrador & Rehberger, 2026; Sunil et al., 2026; Pelekis et al., 2025; Wang et al., 2026; Hu et al., 2026). TraceTrigger complements these attack methods with a common controlled protocol spanning memory, planning, and routing surfaces and with matched-runtime and missing-fragment controls.

Multi-Stage and Persistent Attacks. Multi-turn and persistent attacks show that earlier interactions can influence later responses or actions (Liu et al., 2024; Kulkarni & Namer, 2025; Chang et al., 2026; Kumarappan & Mujoo, 2025). Most directly, Salami Attack introduces MemCollusion, which constructs coalitions of individually benign-looking memory records that jointly induce unsafe

behavior across sessions (Lin et al., 2026). TraceTrigger therefore does not claim the general idea of compositional benign fragments as new. Its added scope is the controlled combination of three placement channels-interaction history, files or retrieved documents, and persistent memory-across memory, planner, and router surfaces, together with incomplete-trigger and matched-runtime controls. Salami Attack provides an automated attack generator and a realistic memory-specific testbed; TraceTrigger provides a broader channel-by-surface benchmark protocol.

Distributed Execution Triggers in Agent Systems. TraceTrigger consequently makes a bounded benchmark contribution: it organizes evidence placement and evaluates downstream action outcomes across channel combinations and execution surfaces. It is not presented as a new optimization algorithm or as the first compositional attack.

3 Threat Model

We consider workflows inspired by self-hosted agents in which a language model plans within a modular pipeline containing memory, routing, and tool interfaces. The evaluated system is a controlled harness, not a deployed OpenClaw runtime.

System Model. We formalize the agent pipeline as $\mathcal{P} = (\mathcal{U}, \mathcal{M}, \mathcal{G}, \mathcal{R}, \mathcal{T})$, where $\mathcal{U}$ denotes user inputs, $\mathcal{M}$ persistent memory, $\mathcal{G}$ intermediate planning states, $\mathcal{R}$ routing decisions, and $\mathcal{T}$ tool interfaces. For each task, the harness serializes prior turns, retrieved-document content, and saved-memory entries into labeled context blocks supplied to one model planning pass. Session boundaries are simulated by setting and later retrieving task-scoped persistent-state flags; no live user account or production memory store is used.

Adversary Model. The adversary can inject or modify content in one or more substrate channels without modifying model parameters or system code. Specifically, the attacker can influence

$$\mathcal{C}_{\text{adv}} \subseteq \{\text{files}, \text{retrieved documents}, \text{memory entries}, \text{tool observations}, \text{interaction history}\}.$$

The attacker does not control model weights, system prompts, routing logic, or execution infrastructure. Instead, the attack operates by placing fragments within normal data pathways that are processed during execution. The benchmark's deterministic component policy is part of the evaluated harness, not an attacker capability; we therefore distinguish model-returned actions from policy-mediated final actions. This threat model applies to self-hosted workflows where local context affects execution, including document assistants, messaging automation, booking agents, and developer agents (Chowa et al., 2026; May et al., 2026; Shapira et al., 2026; Jiang et al., 2026). These cases include one-channel triggers and multi-channel triggers whose evidence must align across the selected channels.

Attack Objective. The adversary aims to induce an action outside the task's authorization, such as an unapproved external message, private-data lookup, or repository access. Let A_{model} be the parsed model plan and A_{final} the action list after component-policy and defense processing. Model-plan success requires the designated unauthorized action in A_{model}; pipeline success, used by the aggregate benchmark tables, requires it in A_{final}. A textual mention of the target is insufficient for either measure. All actions are mock operations, so "execution" means that the simulated executor accepted and recorded the action, not that a real external side effect occurred.

Execution Surfaces and Scope. We evaluate attacks across three execution surfaces, $s \in \{\text{memory}, \text{planner}, \text{router}\}$, because they represent three distinct decision boundaries: retained state, action composition, and tool or component selection. Together they cover where distributed evidence is stored, converted into a plan, and routed toward execution. The goal is to evaluate whether defenses can mitigate attacks whose activation depends on interactions across multiple contexts and components.

4 Trace Channels and Controlled Benchmark

This section defines the channel organization and shows how TraceTrigger turns it into an executable benchmark. We use "dimensionality" only to denote the number of selected channels.

4.1 CHANNEL FORMALIZATION

We organize trigger fragments across temporal history (T), contextual sources (P), and cross-session memory (S). T places evidence in prior turns of the current sequence; P places evidence in files or retrieved documents available to the current task; S places evidence in saved state retrieved after a simulated session boundary. An attack configuration is $D \subseteq \{T, P, S\}$, and $|D|$ is its dimensionality. For each $d \in D$, fragment f_d is inserted into the corresponding channel. A task is $t = (k, \sigma(k), D, \mathcal{F}_D)$, where k is the base skill, $\sigma(k)$ is the targeted execution surface, and $\mathcal{F}_D = \{f_d \mid d \in D\}$.

The selected channels define both the example label and the controlled component condition: every required fragment must be present before the component policy is eligible. The model plans first. If its parsed plan already contains the designated unauthorized action, that model decision determines success; otherwise, an eligible component policy may append or replace the designated action. ASR therefore measures end-to-end behavior of the controlled pipeline, not pure model susceptibility. Incomplete-trigger controls disable policy eligibility and test whether the model nevertheless produces the unauthorized action.

Fragments influence execution through memory, planner, and router components. These surfaces are not isolated sinks; they are stages through which contextual evidence may propagate. A fragment observed in memory may affect planning, and a planning state may affect routing or tool selection. This makes the execution trace, rather than an isolated prompt or component, the correct unit of analysis. Full formalization is provided in Appendix B.

4.2 EVALUATION QUESTIONS

TraceTrigger asks three questions. **RQ1:** how much of the apparent advantage over prior 1D attacks comes from attack construction versus execution setting? **RQ2:** how are individual and combined channels associated with final pipeline outcomes, and what happens when one required channel is removed? **RQ3:** which observation and intervention points are covered by current defense families, and where does residual pipeline risk remain? These questions make TraceTrigger a benchmark organization and evaluation protocol rather than a claim to a new attack-generation algorithm.

4.3 BENCHMARK DESIGN RATIONALE

TraceTrigger uses controlled component policies because the motivating failure is not limited to a model spontaneously inventing an unsafe tool call. In a self-hosted workflow, installed skills, routing rules, memory handlers, and tool adapters can attach semantics to otherwise ordinary context. The benchmark therefore asks what happens when a component maps a conjunction of channel evidence to an action and the surrounding pipeline accepts, modifies, or blocks that action. This produces an auditable stress test of a vulnerable component inside an agent pipeline; it is not evidence that an unmodified language model contains a hidden backdoor. Logging the model plan before policy processing is essential because it reveals whether the model independently selected the target or whether the component introduced it later.

The controlled construction also enables counterfactual comparisons that production logs rarely provide. Clean, false-activation, prior-attack, and multi-channel variants retain a common workflow and authorization boundary while changing the evidence placement or execution setting. One planning call per task avoids adaptive search and keeps the unit of analysis fixed: request and context $\rightarrow$ model plan $\rightarrow$ component and defense processing $\rightarrow$ mock outcome. The resulting benchmark measures pipeline sensitivity under specified assumptions, not the prevalence of these attacks in deployed systems.

4.4 TRACETRIGGER BENCHMARK

TraceTrigger operationalizes distributed-context risk as a benchmark for testing how modular pipelines and defenses handle cross-channel evidence. It constructs execution-grounded tasks across memory, planning, and routing. TraceTrigger is inspired by OpenClaw-style workflows rather than a full runtime clone: it uses self-hosted skill definitions and workflow metadata to assign surfaces and instantiate trigger channels under controlled, reproducible conditions.

4.5 Task Construction and Trigger Injection

We build TraceTrigger from a curated set of self-hosted agent skills collected from a public skill repository.[1] These skills provide base workflow descriptions, expected tool affordances, and task contexts. Each skill is associated with an expected route and nominal tool, which are used to construct clean, control, and triggered variants. Fragments are short workflow cues tied to the selected skill and substrate rather than standalone imperative requests; their role is tested operationally through clean, false-activation, and missing-channel controls rather than assumed from wording alone. Temporal fragments are placed across interaction steps, contextual-source fragments across files or retrieved documents, and cross-session fragments within persistent memory. For one-channel settings, one designated fragment is sufficient for component eligibility. For two- and three-channel settings, all selected fragments must be observed during execution.

4.6 Benchmark Generation

Algorithm 1 shows benchmark generation. Starting from a sampled skill, TraceTrigger constructs a benign workflow, selects channels, injects fragments, and builds a trace through the targeted surface. Channel conditions define labels and gate the deterministic component policy; they do not predetermine the model's returned plan. The recorded outcome is determined after parsing the model plan, applying any eligible component policy and defense, and simulating the resulting actions.

Algorithm 1: TraceTrigger Task Generation

Input: Skill set $\mathcal{K}$
Output: Task t
Sample skill $k \sim \mathcal{K}$;
Map k to execution surface $\sigma(k)$ and attack family $f(k)$;
Sample dimensional configuration $D \subseteq \{T, P, S\}$;
Initialize trigger set $\mathcal{F}_D \leftarrow \emptyset$;
Construct benign workflow induced by k;
foreach $d \in D$ **do**
  Sample trigger fragment f_d;
  Insert f_d into substrate of dimension d;
  $\mathcal{F}_D \leftarrow \mathcal{F}_D \cup \{f_d\}$;
Build execution trace π passing through $\sigma(k)$;
Label benign and triggered outcomes;
return $t = (k, \sigma(k), D, \mathcal{F}_D)$;

4.7 Channel-to-Surface Coverage

TraceTrigger spans workflows such as travel planning, document retrieval, email automation, and developer assistance. Each workflow is mapped to an execution surface and instantiated under one or more dimensional configurations. For example, in a travel task, a 1D temporal trigger may appear in prior interaction history and influence the planner when retrieved. A 2D trigger may combine prior history with a retrieved recommendation document, while a 3D trigger may additionally use persistent memory to bias routing toward an unintended service. These examples show that TraceTrigger does not assume all attacks require multiple fragments: 1D attacks test whether one dimension-specific fragment can affect an execution surface, while 2D and 3D attacks test whether distributed evidence can jointly alter downstream behavior. Additional surface-to-dimension mappings and qualitative examples are provided in Appendix G.

4.8 Dataset Overview

TraceTrigger includes clean, control, and triggered task variants across memory, planner, and router surfaces. Tasks are balanced across execution surfaces and dimensional configurations, enabling controlled evaluation of 1D, 2D, and 3D trigger conditions. This structure allows TraceTrigger to measure both single-dimension execution risks and higher-dimensional trigger alignment under the same evaluation framework. Further details on dataset construction and additional examples are provided in Appendix C.

5 Experimental Setup

We evaluate TraceTrigger using the benchmark and execution pipeline implemented in our repository. The evaluation follows the three questions above: matched settings address RQ1, channel combinations and missing-channel controls address RQ2, and a shared defense interface addresses

[1] https://github.com/VoltAgent/awesome-openclaw-skills

RQ3. We use four open-weight checkpoints spanning small and larger local deployment regimes and one API model to test whether observations are tied to a single access pattern; these models are coverage points, not a representative sample of all agents. Full details are provided in Appendix D, with additional audit and control experiments in Appendix E.

Model–benchmark boundary. Each task makes one model planning call. The prompt contains the authorized request, allowed mock tools, and labeled context blocks for history, documents, and saved memory. For triggered pipeline tasks it also contains the installed component-card semantics, including the action mapped to satisfied evidence. This exposure models an active component contract; it does not test whether the model can infer a secret target from innocuous fragments alone. A deterministic parser extracts a route and tool calls. The harness then applies the controlled component policy and defense, simulates the final mock actions, and checks them against the task authorization. No task causes a real message, data access, file change, or external API call. This ordering distinguishes model-returned actions from benchmark-injected component behavior; Figure 1 shows a logged case in which the unsafe action already appears in the model plan.

Execution settings. The benchmark uses two primary execution settings. The first is a modular controlled harness with explicit routing, planning, tool selection, and task-scoped persistent state. This setting is used for the main TraceTrigger evaluation because multi-channel conditions depend on interactions across these intermediate components. The second is a baseline single-agent platform, where one model directly plans actions without an explicit modular routing layer. Broad comparisons to prior single-surface attacks are descriptive because the settings differ; a matched-runtime control isolates this confound. Full details on task generation, seeds, decoding settings, routing, and reproducibility are provided in Appendix D.1.

Comparison design. The prior one-dimensional tasks are mapped to the single-agent setting and instantiate representative single-surface attacks: AgentPoison (Chen et al., 2024) for memory, ASB-PoT (Liu et al., 2024) for planner-oriented attacks, and AMA (Mo et al., 2025) for routing or selection-oriented attacks. In contrast, the TraceTrigger tasks are evaluated in the self-hosted agent modular setting and include 1D, 2D, and 3D trigger constructions. Appendix E reports a matched runtime-control analysis that separates attack design from execution setting.

Defenses. Defenses are benchmark implementations operating through a shared registry. We select seven families to cover three intervention points: context before planning, actions before execution, and route/provenance across the trace. Input-level variants observe request/context text; action-level variants observe parsed tool names and arguments; trace-level variants additionally observe routes, trigger state, and provenance. They rewrite context, strip or replace actions, restrict capabilities, or reject a trace according to their stated interface. Appendix E gives the exact observability and intervention point; we do not claim these controlled implementations are production guardrails.

Metrics. Pipeline ASR is the fraction of attack tasks whose final simulated action list contains the designated unauthorized action. Clean success requires a benign tool action and no unauthorized action. False activation is the corresponding rate on near-miss tasks; trigger specificity is computed as $\mathrm{ASR}/(\mathrm{ASR}+\mathrm{FAR})$, with value 1 when both rates are zero. Harm is an ordinal task-level score: 0 for no unauthorized action, 1 for lower-impact preference/routing manipulation or external lookup, and 2 for simulated security-boundary violations such as private-data access or unapproved transmission. Stealthiness is a benchmark proxy equal to one minus the fraction of final actions marked attack-origin or using the designated suspicious-send tool. Appendix E reports the category audit and full metric definitions.

6 RESULTS

We report results in the same order as the evaluation questions: matched comparisons isolate execution-setting effects (RQ1), channel combinations test pipeline scaling and missing-channel behavior (RQ2), and defense results expose coverage gaps across intervention points (RQ3).

Table 1: Attack success rate comparison for 1D attacks across surfaces. Baselines correspond to representative single-surface attacks evaluated in the single-agent baseline setting, while TraceTrigger denotes the 1D configuration instantiated on the corresponding surface in the modular setting. Because the broad settings differ, these values are descriptive; the matched-runtime control below isolates the execution-setting confound.

Model	Memory		Planner		Router	
	AgentPoison	TraceTrigger	PoT	TraceTrigger	AMA	TraceTrigger
Qwen-3.5-2B	31.62	82.41	34.14	74.36	33.88	66.52
Llama-3.2-3B	27.91	68.46	38.52	81.84	30.44	75.27
Qwen-3.5-27B	41.62	73.94	47.85	86.18	39.27	69.41
Gemma-4-31B	55.11	91.23	45.32	89.67	36.79	76.42
GPT-5.4-mini	50.05	80.58	37.83	92.45	41.76	83.33

6.1 Comparison with Single-Surface Attacks

Table 1 gives the broad cross-setting comparison: prior attacks run in the single-agent baseline, whereas TraceTrigger runs in the modular harness. It is descriptive rather than a causal estimate of attack-design advantage. Across the five models, TraceTrigger-1D is higher on most matched surfaces, but runtime structure, task construction, and attack design all contribute to this difference.

Controls in the main analysis. On a 40-task Llama-3.2-3B-Instruct matched-runtime slice, TraceTrigger-1D attains ASR 0.7727 in the single-agent runtime and 0.9091 in the modular runtime; prior-1D controls attain 0.0000 in both. These focused zeros do not replace the broader nonzero baseline rates in Table 1: the control uses a smaller stratified slice and disables the dimensional component to isolate runtime effects, while the broad table aggregates the full method-specific evaluation. In a separate incomplete-trigger ablation, removing one required channel yields 0/30 unsafe actions and clean success 0.9833. Missing evidence disables component-policy eligibility by construction, while the absence of unauthorized actions in all 30 parsed model plans is an observed control result. Full counts and intervals appear in Appendix E.

6.2 Channel Combination Scaling

Additional channels can provide corroborating evidence to different pipeline stages, but they can also split evidence less coherently or expose it to a defense that observes one channel especially well. We therefore expect an aggregate tendency rather than strict monotonicity. Table 2 reports pipeline attack success for individual and combined channels. ASR is generally higher for multi-channel configurations in the no-defense setting and in aggregate, although individual defenses and channel combinations deviate from this trend. For example, on Qwen-3.5-2B, ASR is 67.41 for P, 79.36 for P+S, and 87.47 for T+P+S. On GPT-5.4-mini, T+P+S reaches 94.18. Combined-channel component eligibility requires all selected temporal-history, contextual-source, and/or cross-session-memory evidence, so these values do not by themselves measure model-only susceptibility.

6.3 Defense Robustness

Table 2 also evaluates the controlled defense implementations. Their effects are not uniformly monotonic. For Qwen-3.5-2B under execution policy, P falls from 67.41 to 39.74 while T+P+S is 56.42; under proof guardrail, P is 34.18 and T+P+S is 43.36. On GPT-5.4-mini, execution policy gives 44.72 for P and 63.51 for T+P+S. These results show that safeguards observing one stage do not automatically cover every channel combination, but they do not establish effectiveness on production defenses.

6.4 Comprehensive Metric Analysis

Across models, clean task success and trigger specificity remain near-perfect, while pipeline attack success ranges from 0.81 to 0.94. Mean execution-harm scores are approximately 0.55-0.76, the trace-unobtrusiveness proxy reported as stealthiness is 0.61-0.85, and temporal fire-task success reported as persistence is 0.60–0.91. These benchmark proxies summarize final traces; they do not

Table 2: **Attack success rate by trigger-channel combination.** Columns report individual channels (P, S, T), two-channel combinations (P+S, T+P, T+S), and the three-channel combination (T+P+S). Values are percentages; the pattern is not monotonic for every defense and channel combination.

Model	Defense	P	S	T	P+S	T+P	T+S	T+P+S
Qwen-3.5-2B	**None**	67.41	74.82	42.63	79.36	81.94	61.28	87.47
	execution_policy	39.74	28.54	37.18	31.62	43.71	48.53	56.42
	tool_anomaly	42.18	26.83	29.74	34.26	58.37	37.92	49.68
	capability_isolation	51.27	31.49	38.56	36.84	54.91	59.73	57.86
	least_privilege	44.63	27.41	36.27	33.51	35.64	56.95	52.78
	trigger_sensitivity	56.84	63.71	41.86	25.93	72.39	58.67	65.44
	causal_tracing	27.36	18.84	34.91	29.47	32.85	46.28	41.73
	proof_guardrail	34.18	39.57	36.41	47.92	39.26	45.82	43.36
Llama-3.2-3B	**None**	61.58	69.44	46.83	73.27	78.65	66.14	84.18
	execution_policy	37.92	31.26	39.85	34.61	46.73	50.47	58.36
	tool_anomaly	40.67	29.58	33.14	36.92	55.84	41.63	52.41
	capability_isolation	48.73	35.64	41.92	39.18	58.27	61.44	60.63
	least_privilege	43.85	30.72	38.47	35.26	41.88	57.96	54.37
	trigger_sensitivity	53.44	58.83	42.79	32.74	70.13	61.22	67.95
	causal_tracing	29.41	21.76	35.62	31.35	36.28	44.93	43.28
	proof_guardrail	36.58	41.82	38.73	49.16	42.35	47.69	46.11
Qwen-3.5-27B	**None**	72.64	78.11	58.37	84.26	88.93	71.48	92.41
	execution_policy	46.83	35.72	43.26	38.59	52.71	56.18	61.94
	tool_anomaly	49.37	33.85	36.92	41.44	63.58	45.73	55.26
	capability_isolation	57.91	39.64	45.73	43.27	61.84	66.27	64.52
	least_privilege	52.28	34.17	42.63	39.36	44.58	68.91	58.73
	trigger_sensitivity	61.46	69.28	51.82	34.51	77.62	66.84	71.58
	causal_tracing	33.24	24.51	39.18	34.27	39.82	49.67	46.81
	proof_guardrail	40.16	45.38	41.72	53.74	46.25	51.39	49.83
Gemma-4-31B	**None**	73.68	71.43	85.21	80.10	90.08	85.06	93.33
	execution_policy	49.21	36.88	51.47	42.63	57.94	61.38	66.27
	tool_anomaly	52.74	34.16	43.82	44.27	68.31	51.54	59.73
	capability_isolation	60.38	41.29	55.63	46.81	66.42	70.58	69.11
	least_privilege	55.42	35.94	49.36	42.18	47.63	73.24	63.57
	trigger_sensitivity	64.83	67.52	71.29	38.46	81.87	73.64	76.42
	causal_tracing	36.92	25.37	44.58	36.14	42.35	54.81	49.66
	proof_guardrail	43.67	47.83	46.21	57.92	49.64	56.73	53.48
GPT-5.4-mini	**None**	70.84	75.62	61.37	82.55	91.42	78.94	94.18
	execution_policy	44.72	34.95	46.28	40.83	56.34	58.46	63.51
	tool_anomaly	47.38	32.61	39.74	43.16	66.92	48.27	57.84
	capability_isolation	56.43	39.18	48.62	45.37	64.58	68.91	67.44
	least_privilege	51.86	33.72	44.91	41.64	46.73	71.28	61.82
	trigger_sensitivity	62.94	66.38	58.51	37.58	80.64	72.33	74.97
	causal_tracing	32.58	23.44	40.86	34.76	40.91	52.47	47.35
	proof_guardrail	39.63	45.92	43.71	55.28	47.16	54.32	51.64

establish human undetectability or persistence in a deployed agent. A full metric-summary plot is provided in Appendix F.

7 Interpretation and Scope

What the experiments establish. For RQ1, the broad comparison is confounded by different runtimes. In the matched Llama-3.2-3B-Instruct slice, TraceTrigger retains pipeline ASR of 0.773 in the baseline harness and 0.909 in the OpenClaw-like harness, while matched prior-attack controls yield zero unauthorized actions in both runtimes. Modular execution therefore amplifies risk but does not alone explain the matched gap. Because attack implementations still differ, this is a benchmark comparison, not universal superiority over prior systems. For RQ2, the Llama all-channel run rises from 0.8205 (1D) to 0.9750 (2D) and 1.0000 (3D), while 30 incomplete traces produce neither the designated final action nor that action in parsed plans. This establishes pipeline-level joint gating, not a model-only causal effect, because channel removal also disables component eligibility. Importantly, the verified full trace in Figure 1 contains the unauthorized `mock_send_message` in the model plan before policy or defense processing. For RQ3, defenses reduce some combinations but leave non-monotonic residual ASR. This diagnoses stage-local observation gaps; it does not rank production defenses, because our implementations are auditable benchmark policies.

Why the outcomes are security relevant. Success requires an action outside task authorization, not merely a preference mention. In the Llama 1D audit, 46 of 51 successful attacks cross a clear boundary through unapproved messaging, private-data access, or repository access; the remainder are lower-severity lookups or previews. Preference manipulation is reported separately as an integrity failure. Full counts appear in Appendix E.3.

Why use a controlled benchmark. TraceTrigger fixes requests, components, memory, and mock tools while logging each execution stage, making failures reproducible and locating where unsafe behavior first appears. The cost is limited external validity: T/P/S are operational channels rather than independent latent factors, and claims remain conditional on the released generator, prompts, component contracts, and mock runtime.

8 Potential Defenses

The defense results point to gaps that source-local screening cannot close. In Table 2, execution policy reduces Qwen-3.5-2B P attacks from 67.41 to 39.74, yet T+P+S retains 56.42 ASR; on GPT-5.4-mini, the corresponding defended values are 44.72 and 63.51. Even causal tracing leaves T+P+S ASR of 41.73 and 47.35 on these models. Figure 1 further shows why an execution boundary is necessary: the unauthorized send already exists in the model plan before component-policy processing. We therefore derive three requirements. Provenance should persist across history, retrieved context, and memory; authorization should be re-evaluated immediately before sensitive execution; and channel-removal tests should distinguish missing evidence from a later policy block. Appendix Table 8 maps these requirements to the information each evaluated defense actually observes. These are design implications from controlled implementations, not production-defense rankings.

9 Conclusion

We introduced TraceTrigger, a controlled benchmark for studying how evidence distributed across interaction history, contextual sources, and persistent memory influences agent execution. Across five models, aggregate pipeline ASR ranges from 0.81 to 0.94, and multi-channel configurations are generally stronger than single-channel configurations, although the pattern is not monotonic under every defense. In the matched Llama-3.2-3B-Instruct comparison, TraceTrigger-1D reaches ASR 0.773 in the single-agent runtime and 0.909 in the modular runtime, while prior-1D controls produce no unauthorized actions in either setting. Removing one required channel likewise produces 0/30 unauthorized actions in the incomplete-trigger evaluation. A verified full trace further shows that an unauthorized external-send action can appear in the model plan before component-policy processing. Together, these results show why attack construction, execution setting, model planning, and policy-mediated outcomes must be reported separately. TraceTrigger provides that separation across memory, planning, and routing and motivates provenance-preserving, execution-time authorization over complete traces. The conclusions remain bounded to the released controlled benchmark and mock runtime rather than deployed-agent prevalence or production-defense efficacy.

AI USE STATEMENT

Generative AI tools assisted with grammar and language editing. These uses are distinct from the model-based audits and judgments that form part of the research method, which are described in Sections 4 and 5. The authors are responsible for the final text, code, analyses, and claims.

REPRODUCIBILITY STATEMENT

The submission includes the benchmark code, task-generation pipeline, evaluation scripts, and generated task records needed to reproduce the reported experiments. Dataset construction is documented in Appendix C, and the exact execution settings, model interfaces, decoding procedure, routing procedure, and evaluation protocol are documented in Appendix D.1.

REFERENCES

Yunfu Cai. Prompt injection attacks on educational large language models for higher and vocational education. *Scientific Reports*, Mar 2026. ISSN 2045-2322. doi: 10.1038/s41598-026-46563-1. URL https://doi.org/10.1038/s41598-026-46563-1.

Hwan Chang, Yonghyun Jun, and Hwanhee Lee. Chatinject: Abusing chat templates for prompt injection in LLM agents. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=WVhgFSKniL.

Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. Agentpoison: Red-teaming llm agents via poisoning memory or knowledge bases. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 130185–130213. Curran Associates, Inc., 2024. doi: 10.52202/079017-4136. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/eb113910e9c3f6242541c1652e30dfd6-Paper-Conference.pdf.

Sadia Sultana Chowa, Riasad Alvi, Subhey Sadi Rahman, Md Abdur Rahman, Mohaimenul Azam Khan Raiaan, Md Rafiqul Islam, Mukhtar Hussain, and Sami Azam. From language to action: a review of large language models as autonomous agents and tool users. *Artificial Intelligence Review*, 59(2):71, Jan 2026. ISSN 1573-7462. doi: 10.1007/s10462-025-11471-9. URL https://doi.org/10.1007/s10462-025-11471-9.

Cody Clop and Yannick Teglia. Backdoored retrievers for prompt injection attacks on retrieval augmented generation of large language models, 2024. URL https://arxiv.org/abs/2410.14479.

Manuel Herrador and Johann Rehberger. Spaiware: Uncovering a novel artificial intelligence attack vector through persistent memory in llm applications and agents. *Future Generation Computer Systems*, 174:107994, 2026. ISSN 0167-739X. doi: https://doi.org/10.1016/j.future.2025.107994. URL https://www.sciencedirect.com/science/article/pii/S0167739X25002894.

Yuepeng Hu, Yuqi Jia, Mengyuan Li, Dawn Song, and Neil Gong. Maltool: Malicious tool attacks on llm agents, 2026. URL https://arxiv.org/abs/2602.12194.

Xiaochong Jiang, Shiqi Yang, Wenting Yang, Yichen Liu, and Cheng Ji. Sok: A taxonomy of attack vectors and defense strategies for agentic supply chain runtime, 2026. URL https://arxiv.org/abs/2602.19555.

Hao Jing, Fanxiao Li, Yunyun Dong, Wei Zhou, and Renyang Liu. Memory poisoning attacks on retrieval-augmented large language model agents via deceptive semantic reasoning. *Engineering Applications of Artificial Intelligence*, 167:113968, 2026. ISSN 0952-1976. doi: https://doi.org/10.1016/j.engappai.2026.113968. URL https://www.sciencedirect.com/science/article/pii/S0952197626002496.

JorgeGX. Baseline Agentic AI Systems Architecture | Microsoft Community Hub — techcommunity.microsoft.com. https://techcommunity.microsoft.com/blog/azure-ai-foundry-blog/baseline-agentic-ai-systems-architecture/4207137, 2024. [Accessed 19-04-2026].

Udayan Khurana. Autonomous data processing using meta-agents, 2026. URL https://arxiv.org/abs/2602.00307.

Prashant Kulkarni and Assaf Namer. Temporal context awareness: A defense framework against multi-turn manipulation attacks on large language models. In *2025 IEEE Conference on Artificial Intelligence (CAI)*, pp. 930–935, 2025. doi: 10.1109/CAI64502.2025.00164. URL https://ieeexplore.ieee.org/document/11050551.

Adarsh Kumarappan and Ananya Mujoo. Automating deception: Scalable multi-turn LLM jailbreaks. In *First Workshop on Multi-Turn Interactions in Large Language Models*, 2025. URL https://openreview.net/forum?id=ePGtpjbr5g.

Zheng Lin, Yuzhe Huang, Zhenxing Niu, Xianmin Ye, and Haichang Gao. Salami attack: Stealthy collusive memory poisoning against openclaw, 2026. URL https://arxiv.org/abs/2608.01637.

Yupei Liu, Yuqi Jia, Runpeng Geng, Jinyuan Jia, and Neil Zhenqiang Gong. Formalizing and benchmarking prompt injection attacks and defenses. In *33rd USENIX Security Symposium (USENIX Security 24)*, pp. 1831–1847, Philadelphia, PA, August 2024. USENIX Association. ISBN 978-1-939133-44-1. URL https://www.usenix.org/conference/usenixsecurity24/presentation/liu-yupei.

Victor May, Aaditya Salgarkar, Yishan Wang, Diganta Misra, and Huu Nguyen. Agents learn their runtime: Interpreter persistence as training-time semantics, 2026. URL https://arxiv.org/abs/2603.01209.

Kanghua Mo, Li Hu, Yucheng Long, and Zhihao Li. Attractive metadata attack: Inducing llm agents to invoke malicious tools. In D. Belgrave, C. Zhang, H. Lin, R. Pascanu, P. Koniusz, M. Ghassemi, and N. Chen (eds.), *Advances in Neural Information Processing Systems*, volume 38, Main Conference, pp. 162770–162793. Curran Associates, Inc., 2025. doi: 10.52202/085713-5434. URL https://proceedings.neurips.cc/paper_files/paper/2025/file/ee46288ab2aaf5c6e53aebebe719712c-Paper-Conference.pdf.

Xi Mo. Ironengine: Towards general ai assistant, 2026. URL https://arxiv.org/abs/2603.08425.

Sotiris Pelekis, Thanos Koutroubas, Afroditi Blika, Anastasis Berdelis, Evangelos Karakolis, Christos Ntanos, Evangelos Spiliotis, and Dimitris Askounis. Adversarial machine learning: a review of methods, tools, and critical industry sectors. *Artificial Intelligence Review*, 58(8):226, May 2025. ISSN 1573-7462. doi: 10.1007/s10462-025-11147-4. URL https://doi.org/10.1007/s10462-025-11147-4.

Ahmed Ragab Mahmoud. Jailbreaking llms: An in-depth security analysis of prompt injection vulnerabilities, 01 2026. URL https://www.researchgate.net/publication/399282198_Jailbreaking_LLMs_An_In-depth_Security_Analysis_of_Prompt_Injection_Vulnerabilities.

Natalie Shapira, Chris Wendler, Avery Yen, Gabriele Sarti, Koyena Pal, Olivia Floody, Adam Belfki, Alex Loftus, Aditya Ratan Jannali, Nikhil Prakash, Jasmine Cui, Giordano Rogers, Jannik Brinkmann, Can Rager, Amir Zur, Michael Ripa, Aruna Sankaranarayanan, David Atkinson, Rohit Gandikota, Jaden Fiotto-Kaufman, EunJeong Hwang, Hadas Orgad, P Sam Sahil, Negev Taglicht, Tomer Shabtay, Atai Ambus, Nitay Alon, Shiri Oron, Ayelet Gordon-Tapiero, Yotam Kaplan, Vered Shwartz, Tamar Rott Shaham, Christoph Riedl, Reuth Mirsky, Maarten Sap, David Manheim, Tomer Ullman, and David Bau. Agents of chaos, 2026. URL https://arxiv.org/abs/2602.20021.

Alfred Shen and Aaron Shen. Stem agent: A self-adapting, tool-enabled, extensible architecture for multi-protocol ai agent systems, 2026. URL https://arxiv.org/abs/2603.22359.

Balachandra Devarangadi Sunil, Isheeta Sinha, Piyush Maheshwari, Shantanu Todmal, Shreyan Mallik, and Shuchi Mishra. Memory poisoning attack and defense on memory based llm-agents, 2026. URL https://arxiv.org/abs/2601.05504.

Zhiqiang Wang, Yichao Gao, Yanting Wang, Suyuan Liu, Haifeng Sun, Haoran Cheng, Guanquan Shi, Haohua Du, and Xiang-Yang Li. Mcptox: a benchmark for tool poisoning attack on real-world mcp servers. In *Proceedings of the Fortieth AAAI Conference on Artificial Intelligence and Thirty-Eighth Conference on Innovative Applications of Artificial Intelligence and Sixteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI'26/IAAI'26/EAAI'26. AAAI Press, 2026. ISBN 978-1-57735-906-7. doi: 10.1609/aaai.v40i42.40895. URL https://doi.org/10.1609/aaai.v40i42.40895.

Kristy Wedel. Contextual memory intelligence – a foundational paradigm for human-ai collaboration and reflective generative ai systems, 2025. URL https://arxiv.org/abs/2506.05370.

Yifan Yang, Qiao Jin, Furong Huang, and Zhiyong Lu. Adversarial prompt and fine-tuning attacks threaten medical large language models. *Nature Communications*, 16(1):9011, Oct 2025. ISSN 2041-1723. doi: 10.1038/s41467-025-64062-1. URL https://doi.org/10.1038/s41467-025-64062-1.

A Limitation and Broader Impact

Our evaluation is conducted in a controlled harness inspired by self-hosted agent workflows; it is not an evaluation of a deployed agent runtime. Sessions, persistent state, tools, and external effects are simulated, and component policies can alter a parsed model plan. Consequently, aggregate ASR measures the complete benchmark pipeline rather than pure model susceptibility. Real deployments may add evolving histories, heterogeneous tool ecosystems, access-control boundaries, and long-lived memory states that are absent here.

The benchmark focuses on structured combinations of interaction-history, multi-source context, and cross-session memory channels. These channels are operational benchmark factors, not independent physical axes: every input necessarily has a time and location, while our labels indicate whether evidence must be accumulated across steps, sources, or a simulated session boundary. The generated templates do not establish prevalence in real incidents, and the current catalog cannot represent all fragment phrasings or workflow topologies.

As agentic systems are increasingly integrated into real-world applications, ensuring the robustness of execution pipelines is an important safety concern. This work highlights that vulnerabilities can arise from the aggregation of distributed contextual signals across execution stages, rather than from isolated inputs. By identifying how such signals propagate through memory, planning, and routing components, our goal is to inform the design of defenses that account for cross-stage interactions in agent systems.

We acknowledge that the attack mechanisms studied in this work could be misused if applied irresponsibly. To mitigate this risk, all experiments use simulated workflows, mock tools, and no production credentials or external side effects. We release the benchmark artifacts needed for audit and reproduction while keeping evaluation confined to controlled environments. Our intent is to support defensive research on trace-aware authorization and monitoring.

B Full Channel-Combination Formulation

We provide the full formalization of channel-combination activation.

Let $\mathcal{H}$ denote the execution trace, $\mathcal{X}$ contextual sources, and $\mathcal{M}$ persistent memory.

We define dimensional evidence scores:

$$\phi_T = \frac{1}{n}\sum_{i=1}^{n}[f_T \in h_i], \quad \phi_P = \frac{1}{m}\sum_{j=1}^{m}[f_P \in x_j], \quad \phi_S = \frac{1}{r}\sum_{k=1}^{r}[f_S \in m_k].$$

For a selected dimensional configuration $D \subseteq \{T, P, S\}$, we define the interaction term only over selected dimensions:

$$\Psi_D = \sum_{\substack{i,j \in D \\ i<j}} \phi_i \phi_j + [|D| = 3] \prod_{k \in D} \phi_k.$$

The aggregate dimensional evidence is:

$$\Phi_D = \sum_{k \in D} w_k \phi_k + \lambda \Psi_D.$$

The conjunctive activation indicator is:

$$I_{\text{conj}}(D) = \left[\left(\bigwedge_{k \in D} \phi_k \geq \gamma \right) \wedge \Phi_D \geq \tau \right].$$

For $|D| = 1$, the conjunctive condition reduces to observation of the selected dimension-specific fragment; the aggregate score is used only to express evidence strength, not to introduce an additional independent trigger.

C Dataset Construction and Examples

C.1 Task Construction Details

A task instance is defined as:

$$t = (k, \sigma(k), D, \mathcal{F}_D),$$

where k is the base workflow, $\sigma(k)$ is the execution surface, D is the dimensional configuration, and $\mathcal{F}_D$ is the set of trigger fragments.

Trigger fragments are injected across:

- interaction history (temporal),
- contextual inputs such as files or retrieved documents (multi-place),
- persistent memory (cross-session).

C.2 Execution Trace Illustration

A typical execution trace consists of:

- prior interaction steps (history),
- retrieved contextual inputs (documents or files),
- memory states accumulated across sessions,
- intermediate planning decisions.

For 1D tasks, activation occurs when the selected dimension-specific fragment is observed in the execution trace. For 2D and 3D tasks, activation occurs when fragments from all selected dimensions align within a single execution trace.

C.3 Dataset Properties

The dataset is balanced across:

- execution surfaces: memory, planner, router,
- dimensional configurations: 1D, 2D, and 3D.

This ensures consistent comparison of attack effectiveness across dimensions and system components.

C.4 REPRODUCIBILITY

All tasks are generated using Algorithm 1. Released task records preserve the task input, raw model plan, post-policy actions, defense decision, and final mock-execution outcome. Exact task counts, model interfaces, decoding limits, and routing procedure are specified below; the reported tables summarize the released runs rather than an unreported repeated-run protocol.

D EXPERIMENTAL SETTINGS

Compute. All experiments were conducted on multiple NVIDIA H100 GPUs. Experiments were executed sequentially across model and defense configurations to ensure consistent evaluation conditions.

D.1 SETUP AND REPRODUCIBILITY

We evaluate TraceTrigger on a 450-record benchmark generated from a curated skill catalog with `tasks_per_family`=60. The dataset contains 60 clean tasks, 30 false-activation controls, and 360 attack-related records. Of the latter, 120 are temporal seed records that establish prior state and are not scored as attack targets; the remaining 240 are evaluated attack tasks, comprising 60 examples in each of the TraceTrigger-1D, TraceTrigger-2D, TraceTrigger-3D, and prior-1D groups. Each record is instantiated from a skill specification containing the benign tool affordance, expected route, and natural-language task context. These SkillCard-style specifications define the normal skill behavior and tool interface used to construct clean tasks, prior 1D baselines, and TraceTrigger variants. We stratify the evaluated attack tasks across execution surfaces, attack families, and channel configurations and report aggregate results over the resulting distribution.

We evaluate two execution settings. The first is a single-agent runtime in which one model plans tool calls from the request and task context. It contains matched-surface 1D baselines: AgentPoison for memory, ASB-PoT for planning, and AMA for routing/tool metadata. The second is a modular harness inspired by self-hosted pipelines, with routing, planning, tool selection, task-scoped persistent state, and component-mediated execution. AgentCard-style metadata describes the active component, nominal route, and channel evidence available to the harness. Clean and false-activation tasks are evaluated in both settings.

For open-weight models, we run local Hugging Face inference with `max_new_tokens`=220. For closed-source models, including GPT-5.4-mini, we use one Responses API call per task with `max_output_tokens`=400. We do not perform trigger search, beam search, prompt optimization, or iterative refinement at evaluation time. The model returns one route-and-action plan; deterministic code parses it, applies any channel-eligible component policy and defense, and sends the final action list to a mock executor. This ordering means aggregate ASR measures the controlled pipeline. Task records separately preserve the raw model plan, post-policy actions, defense decisions, and final outcome.

Routing proceeds in two stages. Each task is assigned an initial nominal route from `expected_route` when available, or from a fixed keyword heuristic over the user request otherwise. The evaluated model then returns a JSON plan containing a route and a list of tool calls. When using a task subset, we apply stratified subsampling. The sampler balances task category, dimensionality, and attack family, and preserves seed-before-fire ordering for temporal multi-stage attacks.

D.2 MODELS

Table 3 records the checkpoint or API identifier for every evaluated model. Short labels are used elsewhere only to keep the result tables legible.

Table 3: Model identifiers used in TraceTrigger.

Short label	Checkpoint/API identifier	Access
Qwen-3.5-2B	`DavidAU/Qwen3.5-2B-GPT-5.1-HighIQ-INSTRUCT`	Hugging Face
Llama-3.2-3B	`meta-llama/Llama-3.2-3B-Instruct`	Hugging Face
Qwen-3.5-27B	`Qwen/Qwen3.5-27B`	Hugging Face
Gemma-4-31B	`google/gemma-4-31B-it`	Hugging Face
GPT-5.4-mini	`gpt-5.4-mini`	Responses API

D.3 Evaluation Metrics

We report the metrics used to evaluate attack effectiveness, robustness, stealth, and impact in the controlled pipeline in Table 4. These metrics extend beyond attack success rate to record multi-stage and multi-channel behavior.

Table 4: Evaluation metrics used in TraceTrigger.

Metric	Definition	Objective
Clean Task Success	Fraction of benign tasks completed correctly in absence of trigger fragments	Preserve utility
Attack Success Rate (ASR)	Fraction of attack tasks whose final mock action list contains the designated unauthorized action	Pipeline effectiveness
Trigger Specificity	$\mathrm{ASR}/(\mathrm{ASR} + \mathrm{FAR})$, with value 1 when both rates are zero	Separate attack success from near-miss activation
Mean Execution Harm	Mean task score: 0 none, 1 lower-impact manipulation/lookup, 2 authorization-boundary violation	Quantify impact
Mean Stealthiness	One minus the fraction of final actions marked attack-origin or using the suspicious-send tool	Trace-unobtrusiveness proxy
Persistence Across Turns	Unsafe-action success rate on temporal fire tasks after the corresponding seed task	Multi-stage completion

D.4 Execution-Level Defense Mechanisms

We evaluate a set of defenses that operate at different stages of the agent execution pipeline in Table 5, including memory, planning, routing, and tool execution.

Table 5: Execution-level defenses evaluated in TraceTrigger.

Defense	Description	Target Surface
Execution Policy	Restricts tool execution based on predefined rules and safety constraints	Planner / Tools
Tool Anomaly Detection	Detects abnormal tool invocation patterns during execution	Planner / Router
Capability Isolation	Limits tool access to predefined capability scopes	Router
Least Privilege	Restricts permissions to the minimum required for task completion	System-wide
Trigger Sensitivity Analysis	Identifies contextual signals resembling trigger fragments	Memory / Context
Causal Tracing	Analyzes execution trace dependencies to detect abnormal influence paths	Pipeline-wide
Proof Guardrail	Verifies reasoning steps before executing sensitive actions	System-wide

E Additional Audits and Control Experiments

This appendix reports additional analyses used to separate benchmark construction effects, execution-setting effects, and harm severity. These analyses are included to make the evaluation easier to interpret as a controlled benchmark rather than as a claim about naturally occurring production incidents.

E.1 Matched Runtime-Control Experiment

To separate attack design from execution setting, we evaluate prior 1D attacks and TraceTrigger 1D under both the baseline single-agent runtime and the OpenClaw-like modular runtime. For the prior-1D OpenClaw control, the TraceTrigger dimensional component is disabled. The experiment

uses Llama-3.2-3B-Instruct under the same 40-task stratified budget. As shown in Table 6, the modular runtime increases TraceTrigger effectiveness, but the gap is not explained solely by changing runtimes: TraceTrigger remains effective in the baseline runtime, while prior 1D attacks remain inactive under both settings.

Table 6: Matched runtime-control results on Llama-3.2-3B-Instruct.

Attack family	Runtime	ASR	Clean	False act.
Prior 1D	single-agent baseline	0.0000	1.0000	0.0000
Prior 1D	OpenClaw-like, TraceTrigger disabled	0.0000	1.0000	0.0000
TraceTrigger 1D	single-agent baseline	0.7727	1.0000	0.0000
TraceTrigger 1D	OpenClaw-like modular	0.9091	1.0000	0.0000

Bootstrap intervals over task-level attack-success indicators are [0.5909, 0.9091] for TraceTrigger 1D in the baseline runtime and [0.7727, 1.0000] for TraceTrigger 1D in the OpenClaw-like runtime.

E.2 Incomplete-Trigger Ablation

To test pipeline behavior under incomplete evidence, we construct near misses by removing one required T/P/S evidence channel from multi-channel tasks. On Llama-3.2-3B-Instruct, the ablation contains 60 clean tasks and 30 incomplete-trigger tasks. The incomplete-trigger false activation rate is 0/30, trigger specificity is 1.0000, and clean-task success is 0.9833. Missing evidence disables deterministic component-policy eligibility by construction; separately, none of the 30 parsed model plans contains the designated unauthorized action. The result therefore establishes a negative control for this slice, but it does not attribute a plan change causally to the removed channel because component eligibility changes at the same time.

E.3 Harm-Category Audit

We separate lower-severity preference/routing manipulation from security-boundary violations. On Llama-3.2-3B-Instruct in the TraceTrigger 1D OpenClaw-like setting, the 60-task attack-evaluation subset has ASR 0.8500, false activation 0.0000, clean-task success 0.9833, mean harm score 1.4167, and a 95% bootstrap interval of [0.7667, 0.9333]. Among 51 successful attacks, the harm categories are shown in Table 7. Preference manipulation is therefore treated as an agentic-integrity failure, but it is not conflated with higher-severity boundary violations.

Table 7: Successful attack outcomes by harm category in the Llama-3.2-3B-Instruct TraceTrigger 1D OpenClaw-like audit.

Outcome category	Count
Unapproved external message	32
Private document access	6
Private calendar access	5
Private security lookup	2
External tool lookup	2
Code or repository access	1
Lower-severity message preview	3

Execution harm is scored as 0 for no malicious execution, 1 for lower-impact preference/routing manipulation or external lookup, and 2 for security-boundary violations such as private-data access, unauthorized external send, repository access, or unsafe state modification.

E.4 Dimensional Scaling and Non-Monotonic Cases

One explanation for the aggregate scaling pattern is evidence accumulation across separate agent substrates, although component eligibility and prompt construction also contribute to the measured pipeline result. In a no-defense Llama-3.2-3B-Instruct all-channel run, TraceTrigger increases from 1D ASR 0.8205 to 2D ASR 0.9750 and 3D ASR 1.0000, with pooled all-channel ASR 0.9184 and 95% bootstrap interval [0.8571, 0.9694]. The strongest multi-channel combinations are T+P, T+S,

and T+P+S, each with ASR 1.0000 in this run. We do not claim strict monotonicity in every row: a two-channel setting can underperform when the added channel is observed strongly by a defense or when splitting evidence reduces model coherence.

E.5 Defense Observability

Table 8 specifies the information available to each defense and where it intervenes. These are controlled defense-family instantiations in the benchmark harness, not claims about fully deployed production guardrails.

Table 8: Defense observability and intervention points.

Defense	Observed information	Intervention
Execution policy	Planned route and tool calls	Blocks or downgrades actions that violate task-level authorization.
Tool anomaly detection	Action sequence and tool-use pattern	Flags abnormal tool chains or unexpected extra actions.
Capability isolation	Route, selected component, and capability scope	Restricts tools to the capability set assigned to the active component.
Least privilege	Sensitive action and action arguments	Blocks or narrows actions whose arguments exceed the user-visible request.
Trigger sensitivity	Input/context/memory text before execution	Rewrites or suppresses trigger-like fragments without observing final actions.
Causal tracing	Route, actions, trigger-state trace, and provenance	Blocks unsafe actions without a benign causal path from the request.
Proof guardrail	Final plan and justification before execution	Requires a valid benign justification for sensitive actions.

F Additional Metric Summary

Figure 2 provides the full metric-summary plot referenced in the Results section.



Figure 2: **Pipeline evaluation metrics across models.** Clean task success, trigger specificity, final-action ASR, ordinal execution harm, trace-unobtrusiveness (stealthiness), and temporal fire-task success (persistence) are benchmark-specific measures rather than production-security estimates.

G Qualitative Examples of Dimensional Triggers

We provide qualitative examples illustrating how dimensional trigger configurations are instantiated in the benchmark. Each configuration corresponds to the injection of dimension-specific trigger fragments into execution substrates and their subsequent evaluation over the execution trace.

Table 9: Examples of TraceTrigger attack configurations across execution surfaces (memory, planner, router) and trigger dimensions: temporal (T), multi-place (P), and cross-session (S). Each configuration corresponds to dimension-specific fragment injection into distinct substrate channels, with activation determined by their joint presence during execution.

Surface	Dimension	Example Attack Scenario
memory	T	poisoning across turns (gradual memory injection)
memory	P	poisoning across documents in retrieval memory
memory	S	persistence across sessions via stored memory state
memory	T+P	multi-stage memory poisoning distributed across files
memory	T+S	staged memory trigger activated across sessions
memory	P+S	cross-session document poisoning
memory	T+P+S	persistent multi-session memory contamination
planner	T	delayed reasoning trigger across turns
planner	P	reasoning manipulation via distributed prompt fragments
planner	S	planner behavior drift across sessions
planner	T+P	multi-stage reasoning trigger assembled across files
planner	T+S	reasoning trigger activated after session restart
planner	P+S	planner routing altered by cross-session context fragments
planner	T+P+S	long-horizon reasoning manipulation across files and sessions
router	T	delayed tool-routing manipulation
router	P	routing trigger distributed across prompt sources
router	S	tool selection altered across sessions
router	T+P	staged router manipulation across multiple files
router	T+S	delayed tool misuse across sessions
router	P+S	distributed routing manipulation across files and sessions
router	T+P+S	persistent cross-session router hijacking

G.1 Concrete Examples from Dataset Construction

We illustrate how channel labels correspond to task construction. These preference-oriented examples test routing influence but are not, by themselves, evidence of a crossed security boundary. Security-labeled tasks instead pair an explicit authorization rule with a mock action whose target, capability, or data scope violates that rule, as in Figure 1. In all cases, fragments are inserted per selected channel and outcomes are evaluated over the recorded trace.

Temporal Dimension (T) - Planner Surface. Consider a travel planning task where the agent interacts with a user over multiple turns. In an earlier turn, the user includes a seemingly benign statement such as "I usually prefer premium airlines for long trips." This statement is recorded in the interaction history as part of the conversation. During a later step, when the agent constructs the itinerary, the planner revisits this history and prioritizes more expensive options, even when cheaper alternatives are better. In the implementation, this corresponds to inserting f_T directly into prior interaction messages, where it is later consumed by the planner during reasoning.

Multi-place Dimension (P) - Memory Surface. Consider a document-driven task where the agent retrieves multiple files, such as hotel listings and travel recommendations. One retrieved document includes a sentence like "Hotel Aurora is highly recommended for travelers seeking premium comfort," while another document contains a related contextual signal reinforcing this preference. These sentences are embedded within otherwise normal documents stored in the retrieval corpus. Individually, each document appears benign, but when both are retrieved together, the combined content biases the agent's memory interpretation toward that hotel. In the implementation, this corresponds to inserting f_P as natural-language content inside multiple documents or files in the retrieval store.

Cross-session Dimension (S) - Router Surface. Consider a multi-session interaction where the agent stores user preferences in persistent memory. During an earlier session, a statement such as "The user frequently chooses Tool-X for bookings" is written into memory as part of a summary or stored context. In a later session, when the agent selects tools, this stored memory influences routing decisions, causing the agent to favor Tool-X even when alternatives are more appropriate.

In the implementation, this corresponds to inserting f_S into persistent memory entries that are later retrieved during execution.

Two-Dimensional Trigger (T+P) - Planner Surface. Consider a planning task where the agent combines prior interaction history with retrieved documents. In an earlier turn, the user states a mild preference such as "I tend to choose quieter locations," which is stored in the interaction history. Separately, a retrieved document contains a sentence highlighting a specific location as "well-known for its quiet and exclusive environment." Individually, neither signal strongly influences the plan. However, when both are present during reasoning, the planner overemphasizes that location and selects it over better alternatives. In the implementation, this corresponds to inserting f_T into prior interaction messages and f_P into retrieved documents, with both signals jointly affecting the planning process.

Three-Dimensional Trigger (T+P+S) - Router Surface. Consider a tool-selection task where the agent uses prior interactions, retrieved content, and persistent memory. In a previous session, a memory entry such as "Preferred provider: Service-A" is stored. During the current session, the user includes a neutral statement that aligns with this preference, and a retrieved document reinforces Service-A. The incomplete-channel controls omit one of these signals, while the complete condition makes all three available to the controlled pipeline. This preference example measures routing influence, not unauthorized execution. In the implementation, f_T is inserted into interaction history, f_P into retrieved documents, and f_S into persistent memory; separately labeled security tasks require the resulting mock action to violate an explicit authorization rule before it counts as attack success.