MALICIOUSSKILLBENCH: A COMPREHENSIVE BENCHMARK FOR MALICIOUS AGENT SKILL DETECTION

Anonymous authors
Paper under double-blind review

ABSTRACT

Agent Skills extend LLM agents with reusable instruction packages that can carry scripts, resources, and service configuration, turning the Skill distribution channel into a direct vector for malicious behavior. Progress on pre-installation detection is limited by its data: existing malicious Skill resources are fragmented across sources, artifact formats, evidence regimes, and benign coverage, and they overlap enough that concatenating published rows both inflates apparent scale and places related content on both sides of any evaluation split. We present MALICIOUSSKILLBENCH, a consolidated benchmark for malicious Agent Skill detection. From 13 frozen public sources, 11 of which yield eligible malicious Skill artifacts, we recover artifact-level Skills and apply canonicalization, deduplication, structural analysis, and conflict filtering, preserving provenance throughout. The malicious Core reduces from 8,414 raw to 7,539 normalized unique identities organized into 4,588 structural families, yielding **9,740 Skills: 7,505 malicious and 2,235 benign**. Using only labels native to each source, we harmonize 11 attack categories for 4,983 malicious identities and find that threat composition differs sharply across sources. On static primary-instruction text, the benchmark reshapes detector conclusions: the strongest sparse lexical baseline falls from 0.932 Random Macro-F1 to 0.665 once whole sources are held out, and a fine-tuned long-context ModernBERT encoder reaches 0.964/0.940/0.734 on Random/structural-disjoint/Source-Disjoint but still carries a 0.230 gap. Class prevalence accounts for little of this gap: evaluation-only standardization removes 5.9% of it, and fully balanced retraining still yields 0.966 vs. 0.662 Macro-F1 and 0.991 vs. 0.718 AUROC. Held-out-source failures are heterogeneous and model-specific: some sources lose ranking quality outright, others rank well but transfer their decision boundary poorly; the encoder over-flags unseen benign sources at **47.3%** FPR, whereas a zero-shot LLM judge keeps 0.7% benign FPR but only 41.6% malicious recall. Malicious Skill detection should therefore be reported using three separate quantities: ranking quality, fixed-operating-point performance, and benign false-positive rate, each capturing a distinct failure mode.

1 INTRODUCTION

Large language model (LLM) agents increasingly acquire reusable capabilities through *Skills*: installable packages that combine natural language instructions with scripts, templates, resources, and service configuration. A malicious Skill can therefore act as trusted procedural authority inside the agent's workflow. Recent studies show that malicious Skills can steal credentials, manipulate agent behavior, introduce triggered backdoors, or conceal unsafe side effects (Guo et al., 2026; Zhuang et al., 2026; Liu et al., 2026a; Feng et al., 2026). This makes pre-installation malicious Skill detection an increasingly important security problem.

No existing dataset yet provides a single, reliable basis for studying that problem. Existing Skill security resources were created for different purposes and release different objects: complete Skill artifacts, constructed attack variants, runtime-verified cases, vulnerability records, marketplace observations, or signals derived from scanners (Guo et al., 2026; Zhuang et al., 2026; Liu et al., 2026a; Ning et al., 2026; Jin et al., 2026). Their labels are supported by different mixtures of

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: Overview of MALICIOUSSKILLBENCH. **(A)** Fragmented sources differ in artifacts, provenance, evidence, and benign support. **(B)** Controlled canonicalization, deduplication, structural grouping, benign curation, and conflict filtering yield 9,740 normalized-unique Skills (7,505 malicious; 2,235 benign). **(C)** Characterization and held-out-source evaluation expose heterogeneous attack coverage and distinct detector recall/FPR regimes; the source–attack matrix is schematic (quantitative results in Figure 2).

construction, human review, runtime verification, static analysis, and automated scanning, and their benign coverage is uneven. Sources also overlap: Skills that are identical or equivalent up to formatting recur across datasets, related variants reuse common scaffolds, and the same normalized content carries conflicts between labels. Simply concatenating published rows therefore overstates independent coverage and can produce misleading evaluation splits.

We build MALICIOUSSKILLBENCH to turn this fragmented landscape into a common detection benchmark, freezing 13 public sources and retaining the 11 that satisfy a conservative Core-malicious artifact rule. We canonicalize heterogeneous records while preserving source and evidence semantics, deduplicate exact content and content equivalent up to formatting, model broader structural reuse separately from attack semantics, and exclude cross-label conflicts before evaluation. The resulting benchmark contains 9,740 normalized unique Skills: 7,505 malicious and 2,235 benign. Its malicious side originates from 8,414 raw Core artifacts, which reduce to 7,562 exact unique and 7,539 normalized unique identities organized into 4,588 operational structural families.

Using only labels documented by each source and deterministic strong-semantic mappings, we harmonize 11 attack categories for 4,983 of the 7,505 malicious identities. Their distributions differ sharply across sources, so individual datasets emphasize different slices of the threat landscape.

Across three sparse lexical baselines, Random Macro-F1 is **0.882–0.932** but Source-Disjoint Macro-F1 falls to **0.653–0.665**; a fine-tuned long-context ModernBERT baseline is stronger at **0.964/0.940/0.734** on Random/structural-disjoint/Source-Disjoint, yet its gap from Random to Source-Disjoint remains **0.230** and survives both prevalence standardization and fully balanced retraining. LOSO, class-conditional, and source-equal diagnostics show substantial source heterogeneity: supervised models over-flag held-out benign Skills, whereas the zero-shot judge preserves low held-out benign FPR but loses malicious recall mainly on SRC009; ranking degradation and operating-point transfer remain distinct failure modes. The evaluated local static scanner configurations each occupy a distinct recall/FPR regime. All detector results concern static screening of a Skill's primary instruction document; the zero-shot LLM judge uses that same text-only contract, while package-level and runtime detection remain outside scope (Section 8).

We make three contributions.

- **A comprehensive malicious Skill detection benchmark.** We consolidate 13 public sources into a traceable artifact-level resource, preserving heterogeneous evidence while controlling exact/normalized duplication, structural reuse, and cross-label conflicts; the frozen primary benchmark contains 9,740 Skills.
- **A source-aware threat characterization.** We harmonize 11 attack categories for the supported mapped subset and quantify source, provenance, attack, and derived-impact coverage, revealing substantial heterogeneity across existing resources.
- **A unified detector evaluation.** On static primary text, sparse lexical models, a long-context ModernBERT encoder, and a zero-shot LLM judge expose distinct held-out-source failure modes; evaluated local static scanner configurations provide additional operating points under the same primary-text boundary.

2 Background and Related Work

2.1 Agent and Tool Security

Tool-using agents inherit security failures from untrusted observations, tool interfaces, and persistent state. InjecAgent and AgentDojo established indirect prompt injection in tool-mediated workflows, Agent Security Bench broadened evaluation to attacks on prompts, tools, and memory, and MCP studies show that even tool metadata can become an attack channel (Zhan et al., 2024; Debenedetti et al., 2024; Zhang et al., 2024; Wang et al., 2026b). Agent Skills create a related but distinct trust boundary: the Skill itself is installed as reusable procedural authority and may combine instructions, helper code, resources, and permissions. The security question therefore shifts from what an agent observes at run time to whether a capability package can be trusted *before* it is installed.

2.2 Skill-Specific Threats, Datasets, and Defenses

Recent work studies complementary parts of the Skill attack surface. Skill-Inject evaluates prompt injections carried by Skill files, SkillTrojan studies triggered backdoors, and SkillSafetyBench and SkillHarm study Skill-mediated unsafe behavior and harmful capability use (Schmotz et al., 2026; Feng et al., 2026; Jin et al., 2026; Ning et al., 2026). Large-scale empirical studies also characterize Skill vulnerabilities at marketplace scale and credential leakage (Liu et al., 2026b; Chen et al., 2026). Artifact-oriented datasets cover other parts of the space: Liu et al. (2026a) behaviorally verifies marketplace samples; AgentTrap evaluates complete runtime trajectories; and MalSkillBench combines generated runtime-verified attacks, wild samples, and matched benign Skills (Zhuang et al., 2026; Guo et al., 2026). Scanner-oriented resources use still different supervision: ClawHub Security Signals releases a large silver-standard marketplace snapshot, SkillTrustBench separates normal, suspicious, and malicious cases for scanner evaluation, and SkillFortifyBench provides a synthetic testbed across multiple formats (Koc et al., 2026; Tencent Zhuque Lab and The Chinese University of Hong Kong (Shenzhen), 2026; Bhardwaj, 2026).

Defenses are similarly heterogeneous. RouteGuard uses internal model signals for pre-execution poisoning detection, Locate-and-Judge uses attention to scale marketplace triage, SkillGate combines lexical prefiltering with LLM judgment, and Runtime Skill Audit and SkillDetonate move toward evidence from execution-time behavior (Xiao et al., 2026; Etteib et al., 2026; Yang et al., 2026; Lan & Xiao, 2026; Ji et al., 2026). Other work exposes blind spots beyond plain text, including compositional risk among individually safe Skills and malicious instructions hidden in visual resources (Wang et al., 2026a; Jia et al., 2026). ColluSkill further studies composition across Skills and reports that harmful workflows can evade scanners that inspect Skills individually (Zeng et al., 2026). MaliciousSkillBench complements these attack and defense proposals by consolidating heterogeneous public resources into a common artifact-level detection benchmark and evaluating both learned and off-the-shelf detectors under the same frozen data contract.

2.3 Benchmark Artifacts and Distribution Shift

A broader benchmark literature shows why this consolidation must control both duplication and domain-specific shortcuts. Annotation artifacts can make labels predictable from unintended cues (Gururangan et al., 2018); WILDS demonstrates degradation under naturally occurring distribution

shifts, and DomainBed shows that conclusions about domain generalization depend strongly on standardized evaluation protocols (Koh et al., 2021; Gulrajani & Lopez-Paz, 2021). Security-specific evaluation practice makes the same point more sharply: TESSERACT shows that spatio-temporal bias inflates reported malware-classification performance, and Arp et al. (2022) catalogue sampling bias, label inaccuracy, data snooping, and base-rate neglect as recurring pitfalls in learning-based security systems (Pendlebury et al., 2019). Our controls map onto those pitfalls directly: normalized deduplication and structural-family splitting addresses snooping driven by content reuse, conflict exclusion addresses label inaccuracy, held-out source evaluation addresses sampling bias, and benign FPR reporting addresses base-rate neglect. We use source identity and construction provenance for audit and stratification and exclude them from detector features. Our held-out source evaluation measures generalization under coupled source factors; normalized deduplication, structural-disjoint evaluation, class balancing, and scaffold sanitization probe distinct shortcut channels.

3 Why a Comprehensive Benchmark?

Existing malicious Skill datasets were built under different assumptions and cannot be treated as interchangeable rows. Our 13-source registry exposes four concrete deficiencies that a detection benchmark must address.

Existing coverage is fragmented. Prior work studies complementary slices of the Skill threat surface (generated and runtime-verified malicious artifacts, in-the-wild marketplace samples, triggered backdoors, harmful capability use, vulnerability records, and scanner-oriented resources (Guo et al., 2026; Zhuang et al., 2026; Liu et al., 2026a; Feng et al., 2026; Ning et al., 2026; Jin et al., 2026)), but their released units and labels differ in kind. A complete Skill artifact supported by runtime evidence and a vulnerability record or an automated scanner verdict each constitute distinct observations, so consolidation must reconcile these resources without erasing source, artifact, provenance, or evidence semantics.

More rows do not necessarily mean more independent coverage. In the frozen collection, 8,414 Core malicious records reduce to 7,562 exact unique and 7,539 normalized unique Skill contents; broader static similarity further partitions the malicious side into 4,588 operational structural families, and 34 normalized identities collide across malicious and benign labels. Content identity, scaffold reuse, and label inconsistency are different phenomena requiring different controls: concatenating all rows would inflate apparent scale and place reused content on both sides of a split.

Detection also requires credible benign data. The source registry is strongly asymmetric: several resources contain malicious Skills only, and benign labels vary in strength. Because source, construction procedure, and class composition are coupled, a detector can achieve high apparent attack coverage simply by broadly flagging unfamiliar artifacts. Evaluating deployable detection therefore requires high-confidence benign examples from multiple source conventions; after conservative eligibility and conflict exclusion, the primary benchmark contains 7,505 malicious and 2,235 Main-benign normalized unique Skills.

Random splits are an incomplete test of deployment robustness. Random splitting is a useful reference, but it distributes source conventions and structurally related variants across train and test. For malicious Skills, source identity bundles collection venue, attack construction, documentation style, labeling policy, provenance, and benign population, so a detection benchmark needs three complementary evaluation protocols: random evaluation, structural-disjoint evaluation, and held-out-source evaluation, the last measuring generalization under coupled source factors.

Section 4 translates these four deficiencies into concrete decisions: a common artifact-level unit, evidence-preserving canonicalization, explicit identity/reuse/conflict control, a high-confidence benign pool, and evaluation protocols that test random, structural, and source-conditioned generalization separately.

4 BUILDING MALICIOUSSKILLBENCH

We construct MALICIOUSSKILLBENCH with four stages (Figure 1): qualify source artifacts, map records into an evidence-preserving schema, control identity and structural reuse, and finalize the detection set after conflict exclusion. Detailed controlled vocabularies, lineage records, and release rules appear in the appendix.

4.1 SOURCE COLLECTION AND ARTIFACT ELIGIBILITY

Collect broadly, qualify conservatively. We freeze 13 public malicious Skill datasets and security corpora and record source revision, license, redistribution status, reported and acquired counts, and artifact availability. Across all benchmark roles, the canonical manifest contains 182,699 records. A source contributes to the Core malicious benchmark only when we can recover an actual Skill artifact, preserve the malicious claim native to that source and its supporting evidence, keep the artifact inert as detector input, and trace it to a frozen source revision. Security-relevant task pairs, vulnerability-only rows, scanner verdicts, environment fixtures, and non-Skill configurations are retained as Auxiliary under their original source semantics.

Eleven of the 13 sources satisfy this Core rule (Table 1), contributing 8,414 raw malicious Skill artifacts. Their provenance spans wild, test-fixture, injected/backdoored, and synthetic collections, and their benign support is highly uneven. This heterogeneity is retained so later analyses can distinguish what was observed, constructed, or inferred.

Table 1: Coverage of the 11 Core-contributing sources in the frozen benchmark. "Norm." reports per-source normalized-unique malicious identities and therefore need not sum to 7,539 because identities can occur in multiple sources; Main-benign counts precede conflict exclusion.

Source	Core raw	Norm.	Main benign	Core provenance
MalSkillBench	3,944	3,430	0	mixed/unresolved
MaliciousAgentSkillsBench	157	157	0	wild
SkillLeakBench	79	67	0	wild
Agent Skill Malware	124	124	0	wild
AgentTrap	91	89	50	test fixture
SkillTrojan	1	1	2	backdoored
SkillHarm	879	739	0	injected/backdoored
SkillTrustBench	2,863	2,861	1,643	injected/synth./wild
ATR Skill Security	32	29	466	wild/test fixture
SkillFortifyBench	90	90	90	synthetic
SkillSafetyBench	154	154	0	injected

Recover missing artifacts without relaxing eligibility. Two sources require a documented acquisition exception. SRC002 (*MaliciousAgentSkillsBench*) and SRC004 (*SkillLeakBench*) (Chen et al., 2026) publicly release study metadata and labels but not the raw malicious artifacts. Keeping those public revisions as the source of record, we link eligible rows to author-provided historical research snapshots and recover 157 SRC002 and 79 SRC004 artifacts under the same Core rule; four ambiguous SRC004 cases involving multiple Skills and its vulnerability-only rows remain outside Core (Appendix A.4).

4.2 CANONICALIZATION WITHOUT ERASING EVIDENCE

Every acquired record receives a stable canonical ID while retaining source ID, source label, source revision, artifact type, provenance, label strength, evidence type, hashes, and available lineage metadata. We map source-specific labels conservatively: a record supported only as *vulnerable*, *suspicious*, dual-use, or flagged by a scanner stays below malicious ground truth, and unresolved provenance or parentage remains unresolved. The complete vocabulary records intent, provenance, and evidence as distinct fields (Appendix B).

This common schema keeps the row count, variant count, and content identity of each source distinct. Published links between base and variant Skills are retained when explicit; similarity is used only for structural reuse analysis and never establishes causal lineage. Throughout, potentially malicious artifacts are handled as inert static data: the pipeline parses text and metadata but executes no Skill code, helper, payload, URL, installer, or embedded instruction.

4.3 Deduplication and Structural Reuse Control

We separate three forms of relatedness because they answer different benchmark questions. *Exact identity* is SHA-256 equality over acquired Skill content. *Normalized identity* applies deterministic conservative text normalization to collapse content that is equivalent up to formatting while preserving substantive text. These stages reduce 8,414 raw Core malicious artifacts to 7,562 exact unique and 7,539 normalized unique malicious identities.

Broader scaffold reuse is handled separately from identity and threat semantics. On one representative per normalized malicious identity, a frozen pipeline using static similarity at threshold 0.68 yields 4,588 operational structural families. We use these families only for reuse audits and structural-disjoint splitting on the malicious side; they encode operational structural reuse with no attack, campaign, actor, or threat-class semantics. A blinded review of 72 sampled pairs within families, restricted to positive cases, provides a bounded coherence check, with the full method and limitations reported in Appendix C.

4.4 Benign Pool, Label Conflicts, and Final Benchmark

A detection benchmark also needs credible negatives. We separate 48,217 benign candidates into Main and Auxiliary pools by artifact availability and source evidence: Main requires an actual Skill artifact plus strong or moderate benign evidence, while unflagged in the marketplace, clean by scanner, silver, or otherwise weak negatives remain Auxiliary. This yields 2,251 raw Main-benign artifacts (2,238 normalized unique) and 45,966 raw Auxiliary-benign artifacts (44,327 normalized unique); Auxiliary examples support audit and future work but are never primary benign ground truth.

Finally, we compare exact and normalized identities across malicious and benign pools. Thirty-four normalized identities carry conflicting labels, malicious in some sources and benign in others. We exclude every conflicting identity from primary evaluation and retain it for consistency auditing, avoiding new automatic adjudication. Because only three of the 34 also occur in the Main benign pool—the remainder conflict with Auxiliary negatives—the malicious side loses 34 units while the benign side loses three (Appendix D.4). The resulting frozen benchmark contains 9,740 normalized unique Skills: 7,505 malicious and 2,235 Main benign. Every evaluation protocol starts from this same master table, with no relabeling or synthetic oversampling applied to any split.

5 Threat Landscape of MaliciousSkillBench

We harmonize threat metadata native to each source into a common attack taxonomy without inferring labels from Skill text. Direct labels and mappings with strong semantic grounding support attack characterization for 4,983 of 7,505 primary malicious identities (66.4%) across 11 attack categories with multi-label support. Nine of the 11 Core contributing sources provide mappable per-unit attack annotations; unsupported units remain unannotated, with no model-inferred labels added.

5.1 Attack Coverage Is Broad but Source-Dependent

Figure 2a shows several recurring behaviors. *Execution / Code Delivery* appears in 3,320 identities (66.6% of the mapped subset), followed by *Instruction / Goal / Memory Manipulation* in 1,671 (33.5%) and *Privilege / Tool / Authority Abuse* in 1,013 (20.3%). Credential access, data exfiltration, persistence, abuse of supply chains, resource abuse, integrity manipulation, defense evasion, and discovery provide additional coverage.

The aggregate distribution hides strong source concentration (Figure 2b). SkillTrustBench contributes 2,755 of the 3,320 identities coded as execution and 1,258 of the 1,671 identities coded as instruction manipulation, whereas MalSkillBench contributes 262 of the 330 identities coded as resource or availability abuse. Other categories draw from different mixtures of wild, synthetic, injected, backdoored, and test-fixture sources. The contributing datasets therefore provide complementary threat coverage that is specific to each source: different sources can expose substantially different threat profiles.




Figure 2: Threat landscape of MALICIOUSSKILLBENCH. **(a)** Prevalence of 11 harmonized attack categories among 4,983 malicious identities with direct or strong-semantic source-native mappings; categories are multi-label and percentages use this mapped subset. **(b)** Source-wise attack composition for the nine Core sources with mappable annotations; cells show raw counts, with power-normalized color intensity for visibility. **(c)** Attack–impact co-occurrence for the 1,888 identities with both mappings. Impact labels are conservative high-level derived mappings available for a bounded subset of the corpus.

5.2 DERIVED IMPACTS PROVIDE A MORE CONSERVATIVE VIEW

Explicit source-native impact labels are sparse, so impact characterization remains separate from the attack taxonomy. Conservative high-level impact mappings are supported for 2,128 of 7,505 malicious identities (28.4%), of which 1,888 (25.2%) also carry attack mappings; Figure 2c visualizes that bounded subset, in which execution/code delivery most often co-occurs with unauthorized code execution or system control (489 identities), data exfiltration/disclosure with sensitive-data disclosure (345), and credential access with credential compromise (293). These co-occurrences are descriptive, reflecting the bounded subset of identities with both mappings. No single source represents the full observed malicious Skill landscape, motivating both multi-source construction and source-aware evaluation.

6 BENCHMARKING STATIC PRIMARY-INSTRUCTION SCREENING

6.1 EVALUATION DESIGN

All evaluations use the frozen master table of 9,740 units (7,505 malicious / 2,235 benign). Random is label-stratified 70/10/20; Malicious-Structural-Disjoint keeps the 4,588 malicious structural families atomic; and Source-Disjoint holds out SRC009/011/012 after removing eight identities that cross the boundary; Source-Balanced Random is a composition diagnostic (inventories in Appendix F). Learned detectors use static primary Skill instruction text: three TF–IDF models and a fine-tuned ModernBERT-base encoder (Warner et al., 2024), which uses up to 8,192 tokens and excludes five withheld exact texts without changing frozen splits (Source-Disjoint test remains 1,384). A zero-shot

LLM judge (`deepseek-v4.1-flash`) reads the identical text; Appendix N gives its configuration and abstention handling. We report Macro-F1, malicious recall, benign FPR_B, and supplementary ranking metrics; scanner comparisons are limited to the local static configurations of Appendix J.

6.2 Finding 1: The Held-Out-Source Gap Survives Prevalence Controls

Table 2 reports primary-text detector results. Sparse baselines reach 0.882–0.932 Random Macro-F1 but only 0.653–0.665 on Source-Disjoint. ModernBERT reaches **0.964/0.940/0.734** on Random/Malicious-Structural-Disjoint/Source-Disjoint: a 0.024 drop from Random to structural versus a **0.230** gap from Random to Source-Disjoint. Reweighting Source-Disjoint to the exact Random-test prevalence leaves a 0.216 gap, removing only 5.9% (0.2296 $\rightarrow$ 0.2160 unrounded); AUROC likewise falls from 0.9965 ± 0.0001 to 0.8118 ± 0.0385.

Table 2: Static primary-text detector results (Macro-F1 unless marked FPR_B). Classical rows are deterministic across seeds 42/43/44; ModernBERT reports mean $\pm$ sample SD. SB is Source-Balanced Random. In the SRC009 FPP placement diagnostic, reported supervised gaps are 2.9–5.5 points between in-document (n=143) and routed (n=423) payloads, versus 78.4 for the zero-shot judge (Appendix N).

Model	Random	SB	M-Struct.	Source	Rand. FPR_B	Src. FPR_B
Word TF–IDF + LR	.882	.874	.860	.661	.105	.620
Word TF–IDF + SVM	.932	.921	.916	.665	.094	.624
Char TF–IDF + SVM	.921	.907	.883	.653	.098	.644
ModernBERT-base	**.964**$_{\pm.004}$	**.964**$_{\pm.003}$	**.940**$_{\pm.002}$	**.734**$_{\pm.007}$	**.057**$_{\pm.014}$	**.488**$_{\pm.028}$
LLM judge (zero-shot)	.825	.815	.795	.636	.018	.007

Fully balanced retraining also preserves the gap: ModernBERT obtains 0.9661 ± 0.0032 Macro-F1 and 0.9912 ± 0.0013 AUROC on balanced Random versus 0.6616 ± 0.0567 and 0.7177 ± 0.0549 on balanced Source-Disjoint. Aggregate prevalence accounts for little of the held-out-source degradation.

6.3 Finding 2: Source Shift Produces Model-Specific Failure Modes

ModernBERT retains $93.8 \pm 1.9\%$ malicious recall at $48.8 \pm 2.8\%$ benign FPR on Source-Disjoint. Equal-source averaging sharpens this supervised asymmetry: source-macro malicious recall across SRC009/011/012 is $96.1 \pm 0.7\%$, but benign FPR across SRC011/012 is $69.3 \pm 1.7\%$ (word-SVM: 58.3%); the class-conditional benign holdout likewise reaches **47.3%** FPR at 98.1% malicious recall. These diagnostics are descriptive and cover only two held-out sources with benign support.

The zero-shot judge instead has 0.44% source-macro benign FPR but 75.3% source-macro malicious recall, with most misses on SRC009; its validation $\mathrm{FPR} \leq 1\%$ rule transfers to **0.7%** test FPR versus $22.9 \pm 7.1\%$ for ModernBERT. Of 566 SRC009 FPP identities with source-native realization metadata, 423 route the payload to an added resource. Under the frozen 0.68 family partition, ModernBERT routed recall is $98.0 \pm 1.3\%$ for family-seen versus $87.7 \pm 5.0\%$ for family-unseen identities; judge recall is 91.9%/23.1% (in-document/routed) when family-seen and 91.4%/9.5% when family-unseen (Appendix N).

6.4 Finding 3: Evaluated Scanner Configurations Occupy Distinct Operating Regimes

Three evaluated local static configurations (Appendix J) occupy distinct Source-Disjoint operating regimes. Cisco and SkillSpector lower benign FPR to 1.1%/0.55% but detect 2.5%/0% of malicious Skills, while SkillFortify reaches 25.3% recall at 49.9% FPR. Each result reflects the specific configuration under evaluation.

Held-out source failures are heterogeneous across sources. Supplementary ModernBERT LOSO includes ranking inversion on SRC006 (AUROC 0.221), while SRC011 and SRC012 retain useful ranking (AUROC 0.939 and 0.805) but transfer poorly at the fixed 0.5 operating point. On canonical Source-Disjoint, a threshold selected for validation FPR $\leq 1\%$ transfers to $22.9 \pm 7.1\%$ test FPR with $70.0 \pm 8.2\%$ recall. We therefore treat discrimination, fixed-threshold performance, and

threshold transfer from validation to test as distinct quantities that warrant separate reporting; LOSO reconstruction details are in Appendix I.6.

7 Discussion

The Random-to-Source-Disjoint gap survives prevalence standardization and balanced retraining. Source-equal diagnostics expose model-specific errors: supervised models retain high malicious recall while over-flagging the two held-out benign-support sources, whereas the zero-shot judge keeps low benign FPR but loses recall mainly on SRC009. The SRC009 FPP analysis further shows associations with both payload placement and structural-family familiarity, without identifying a causal shortcut or establishing corpus-wide observability.

AUROC measures ordering, while Macro-F1 and benign FPR depend on the operating point: a ModernBERT threshold chosen for $\leq 1\%$ validation FPR reaches $22.9 \pm 7.1\%$ test FPR. Discrimination, fixed-threshold performance, and threshold transfer should therefore be reported separately. Benchmark diversity should cover benign populations and evidence locations alongside attack profiles. The exploratory 610-item static-text study in Appendix M records reference-label alignment without validating benchmark labels or explaining detector-transfer errors.

8 Limitations and Threats to Validity

Coverage and interpretation conditioned on source. *Comprehensive* denotes traceable consolidation of 13 frozen public sources, with coverage bounded by this registry. Source-Disjoint entangles provenance, construction, labeling, documentation style, and class composition, with universal unseen-source performance remaining an open question. Supplementary ModernBERT LOSO covers four selected two-class sources; its held-source tests are recovered and sanity-checked, but development partitions are deterministic reconstructions whose byte-level correspondence to historical manifests is unverified. Variation across them evidences heterogeneity in transfer behavior. Attack mappings remain partial and structural families are operational reuse groups.

Benign, model-input, and threshold scope. The Main benign pool favors label confidence over ecological balance and has narrower source coverage; learned results measure static primary-text screening even when some labels rely on package or runtime evidence. ModernBERT truncates at 8,192 tokens (118/9,735 public-text identities; 7/1,384 Source-Disjoint test items) and excludes five withheld exact texts. Independent threshold re-selection from saved validation scores is unavailable for ModernBERT. Source-equal diagnostics cover three held-out sources, only two with benign support, while the FPP placement/family diagnostic is limited to SRC009 identities with source-native realization metadata; neither establishes corpus-wide observability or a causal source/structure effect. The zero-shot judge is one fixed primary-text configuration; package-aware, tool-using, runtime, and other LLM-backed modes remain outside scope (Yang et al., 2026; Etteib et al., 2026).

Scanner configuration scope. Results apply only to evaluated local static primary-text configurations, each reflecting a specific tested setup. SkillSpector runs `--no-llm`; SkillFortify has SRC012 source overlap. Cisco's rerun, conducted to satisfy dependency compliance, reproduces its operating points with native YARA checks (Appendix J.3). Package-, runtime-, and cloud-backed scanner modes fall outside the evaluated scanner scope.

9 Conclusion

We introduced MaliciousSkillBench, a 9,740-Skill benchmark consolidating 13 public sources. Its 0.230 Random-to-Source-Disjoint gap survives prevalence controls and balanced retraining; source-equal and payload-placement diagnostics expose model-specific transfer failures, motivating broader benign-source coverage and explicit reporting of evidence location.

REPRODUCIBILITY STATEMENT

We freeze source revisions, the canonical metadata manifest, Core eligibility rules, exact and normalized hashes, structural-family assignments, benchmark master tables, split manifests, leakage checks, threat-characterization mappings, text-preprocessing rules, scanner verdict contracts, and detector configurations. An anonymized repository with the benchmark text layer, frozen splits, detector code, and archived outputs is available at `https://anonymous.4open.science/r/msb-F725/`; identifying repository and project-page links are omitted for double-blind review, and verifying the reported statistics requires no execution of untrusted Skill payloads. All 9,740 benchmark identities are represented in the release materials. Exact frozen static Skill text is available for 9,735 identities (7,500 malicious and 2,235 benign); five credential-bearing malicious records instead have sanitized public representations. The added ModernBERT experiments use the public text layer and exclude exactly those five records; their sanitized text is not substituted; the frozen split manifests remain unchanged and Source-Disjoint test remains all 1,384 units. ModernBERT runs record the resolved model/data revisions, configuration, per-run metrics, predictions, and manifests used for the reported results. The source-equal and FPP family-familiarity diagnostics are deterministic post-hoc analyses over the frozen Source-Disjoint split, structural-family assignments, archived predictions, and source-native realization metadata; their scripts and join audits are retained with the supplementary analysis record. For the zero-shot LLM judge, Appendix N records the prompt, gateway alias, temperature, interface, 8,192-token input contract, abstention/threshold rules, and item-level judgments. Its preparation script names but does not pin the ModernBERT tokenizer revision, and the gateway exposes no immutable backend snapshot; exact checkpoint replay is not claimed. Appendix J.3 documents the dependency-compliant Cisco rerun and native-rule checks; the accompanying payload-free per-item outcomes support offline metric recomputation, distinct from rebuilding the scanner environment. For the supplementary multi-LLM case study, Appendix M specifies the sampling, text-view preparation, judging protocol, and weighted summaries; the accompanying sampling manifest and item-level judgments support recomputation of the reported statistics.

ETHICS STATEMENT

This work studies malicious Agent Skills and therefore involves dual-use security artifacts. We treat all Skill contents as untrusted static data and do not execute malicious payloads, helper scripts, or embedded commands during benchmark construction or the reported detector experiments. Full-package redistribution remains subject to source-specific licenses and constraints. For five malicious records containing sensitive credential material, the exact frozen text is withheld and a sanitized public representation is released instead. The benchmark is intended to support defensive detection and auditing, and released documentation should avoid operationalizing harmful payloads beyond what is necessary for reproducible security research. The detailed release, redistribution, safety, intended-use, and maintenance contract is documented in Appendix L.

AI USE STATEMENT

We used generative AI tools for literature search, workflow scripting and code editing, experimental planning support, result analysis and interpretation support, prose drafting and editing, LaTeX organization, consistency checking, the blind structural-template review in Appendix C, the zero-shot LLM detector baseline in Appendix N, and the exploratory multi-LLM static-text judgments and disagreement adjudication in Appendix M. All LLM-based judgment components are identified as such and are not treated as human ground truth or benchmark labels. AI-assisted planning and interpretation were advisory; detector and case-study judgments were generated by the stated models, numerical summaries were computed from archived records, and the authors determined the final scientific interpretation. We did *not* use generative AI tools to generate benchmark data, assign or alter benchmark reference labels, or produce the attack-category and impact mappings; every benchmark reference label derives from source-native annotations and deterministic mapping rules. The LLM detector and case-study outputs do not enter those labels or change the frozen splits. The remaining required-disclosure categories, such as developing theoretical models or assisting with proofs, are not applicable to this work. All AI-assisted work was reviewed by the authors: AI-assisted code was verified against the frozen manifests and checksums, and the reported claims, citations,

benchmark statistics, and experimental numbers were checked against the recorded run artifacts. We take responsibility for the final content of this work, including text, claims, and artifacts produced with the aid of generative AI.

REFERENCES

Daniel Arp, Erwin Quiring, Feargus Pendlebury, Alexander Warnecke, Fabio Pierazzi, Christian Wressnegger, Lorenzo Cavallaro, and Konrad Rieck. Dos and don'ts of machine learning in computer security. In *31st USENIX Security Symposium (USENIX Security 22)*, pp. 3971–3988, 2022.

Varun Pratap Bhardwaj. Formal analysis and supply chain security for agentic ai skills. *arXiv preprint arXiv:2603.00195*, 2026.

Zhihao Chen, Ying Zhang, Yi Liu, Gelei Deng, Yuekang Li, Yanjun Zhang, Jianting Ning, Leo Yu Zhang, Lei Ma, and Zhiqiang Li. How your credentials are leaked by LLM agent skills: An empirical study. In *Proceedings of the 41st IEEE/ACM International Conference on Automated Software Engineering (ASE '26)*, 2026. arXiv:2604.03070.

Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. Agentdojo: A dynamic environment to evaluate prompt injection attacks and defenses for llm agents. *arXiv preprint arXiv:2406.13352*, 2024.

Bacem Etteib, Daniele Lunghi, and Tégawendé F. Bissyandé. Detecting malicious agent skills in the wild using attention. *arXiv preprint arXiv:2606.23416*, 2026.

Yunhao Feng, Yifan Ding, Yingshui Tan, Boren Zheng, Yanming Guo, Xiaolong Li, Kun Zhai, Yishan Li, and Wenke Huang. Skilltrojan: Backdoor attacks on skill-based agent systems. *arXiv preprint arXiv:2604.06811*, 2026.

Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. *arXiv preprint arXiv:2007.01434*, 2021.

Wenbo Guo, Wei Zeng, Chengwei Liu, Xiaojun Jia, Yijia Xu, Lei Tang, Yong Fang, and Yang Liu. Malskillbench: A runtime-verified benchmark of malicious agent skills. *arXiv preprint arXiv:2606.07131*, 2026.

Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel R. Bowman, and Noah A. Smith. Annotation artifacts in natural language inference data. *arXiv preprint arXiv:1803.02324*, 2018.

Zimo Ji, Congying Xu, Zongjie Li, Yudong Gao, Xin Wei, Shuai Wang, and Shing-Chi Cheung. Cloak and detonate: Scanner evasion and dynamic detection of agent skill malware. *arXiv preprint arXiv:2607.02357*, 2026.

Xiaojun Jia, Jie Liao, Simeng Qin, Ke Ma, Wenbo Guo, Yebo Feng, Aishan Liu, and Yang Liu. Seeing is not screening: Multimodal hidden instruction attacks on agent skill scanners. *arXiv preprint arXiv:2606.18198*, 2026.

Chang Jin, An Wang, Zeming Wei, Kai Wang, Biaojie Zeng, Qiaosheng Zhang, Chao Yang, Jingjing Qu, Xia Hu, and Xingcheng Xu. Skillsafetybench: Evaluating agent safety under skill-facing attack surfaces. *arXiv preprint arXiv:2605.12015*, 2026.

Vincent Koc, Patrick Erichsen, Jacob Tomlinson, Agustin Rivera, Michael Appel, and Nir Paz. Clawhub security signals: When virustotal, static analysis, and skillspector disagree. *arXiv preprint arXiv:2606.01494*, 2026.

Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, et al. Wilds: A benchmark of in-the-wild distribution shifts. *arXiv preprint arXiv:2012.07421*, 2021.

Tu Lan and Chaowei Xiao. Runtime skill audit: Targeted runtime probing for agent skill security. *arXiv preprint arXiv:2606.11671*, 2026.

Yi Liu, Zhihao Chen, Yanjun Zhang, Gelei Deng, Yuekang Li, Jianting Ning, and Leo Yu Zhang. "Do Not Mention This to the User": Detecting and understanding malicious agent skills in the wild. *arXiv preprint arXiv:2602.06547*, 2026a.

Yi Liu, Weizhe Wang, Ruitao Feng, Yao Zhang, Guangquan Xu, Gelei Deng, Yuekang Li, and Leo Zhang. Agent skills in the wild: An empirical study of security vulnerabilities at scale. *arXiv preprint arXiv:2601.10338*, 2026b.

Yuting Ning, Zhehao Zhang, Yash Kumar Lal, Boyu Gou, Junyi Li, Weitong Ruan, Chentao Ye, Rahul Gupta, Diyi Yang, Yu Su, and Huan Sun. Skillharm: Lifecycle-aware skill-based attacks via automated construction. *arXiv preprint arXiv:2606.02540*, 2026.

Feargus Pendlebury, Fabio Pierazzi, Roberto Jordaney, Johannes Kinder, and Lorenzo Cavallaro. TESSERACT: Eliminating experimental bias in malware classification across space and time. In *28th USENIX Security Symposium (USENIX Security 19)*, pp. 729–746, 2019.

David Schmotz, Luca Beurer-Kellner, Sahar Abdelnabi, and Maksym Andriushchenko. Skill-inject: Measuring agent vulnerability to skill file attacks. *arXiv preprint arXiv:2602.20156*, 2026.

Tencent Zhuque Lab and The Chinese University of Hong Kong (Shenzhen). Skilltrustbench, 2026. Benchmark dataset for agent skill security evaluation, version 1.0.

Su Wang, Pin Qian, Yihang Chen, Junxian You, Xiaoyuan Wang, Xiaochong Jiang, Lifei Liu, Haoran Yu, and Jingzhou Xu. When safe skills collide: Measuring compositional risk in agent skill ecosystems. *arXiv preprint arXiv:2606.00448*, 2026a.

Zhiqiang Wang, Yichao Gao, Yanting Wang, Suyuan Liu, Haifeng Sun, Haoran Cheng, Guanquan Shi, Haohua Du, and Xiang-Yang Li. MCPTox: A benchmark for tool poisoning attack on real-world MCP servers. In *Proceedings of the Fortieth AAAI Conference on Artificial Intelligence (AAAI-26)*, pp. 35811–35819, 2026b. arXiv:2508.14925.

Benjamin Warner, Antoine Chaffin, Benjamin Clavié, Orion Weller, Oskar Hallström, Said Taghadouini, Alexis Gallagher, Raja Biswas, Faisal Ladhak, Tom Aarsen, Nathan Cooper, Griffin Adams, Jeremy Howard, and Iacopo Poli. Smarter, better, faster, longer: A modern bidirectional encoder for fast, memory efficient, and long context finetuning and inference. *arXiv preprint arXiv:2412.13663*, 2024.

Wenjie Xiao, Xuehai Tang, Biyu Zhou, Songlin Hu, and Jizhong Han. Routeguard: Internal-signal detection of skill poisoning in llm agents. *arXiv preprint arXiv:2604.22888*, 2026.

Rui Yang, Michael Fu, Kla Tantithamthavorn, Chetan Arora, and Joey Chua. Skillgate: Cost efficient runtime malicious skill file detection in coding agents. *arXiv preprint arXiv:2607.25619*, 2026.

Puyu Zeng, Simeng Qin, Jingzhi Li, Ju Jia, Zheli Liu, and Xiaojun Jia. Colluskill: Adversarial cross-skill composition for evading agent skill scanners. *arXiv preprint arXiv:2608.09732*, 2026.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents. *arXiv preprint arXiv:2403.02691*, 2024.

Hanrong Zhang, Jingyuan Huang, Kai Mei, Yifei Yao, Zhenting Wang, Chenlu Zhan, Hongwei Wang, and Yongfeng Zhang. Agent security bench (asb): Formalizing and benchmarking attacks and defenses in llm-based agents. *arXiv preprint arXiv:2410.02644*, 2024.

Haomin Zhuang, Hanwen Xing, Yujun Zhou, Yuchen Ma, Yue Huang, Yili Shen, Yufei Han, and Xiangliang Zhang. Agenttrap: Measuring runtime trust failures in third-party agent skills. *arXiv preprint arXiv:2605.13940*, 2026.

A SOURCE REGISTRY AND BENCHMARK SCOPE

A.1 SCOPE AND ACQUISITION PRINCIPLES

MALICIOUSSKILLBENCH is built from a frozen public-source registry with pinned source revisions. We include public datasets and security corpora that materially characterize the Agent Skill attack surface, even when their released unit or supervision is not eligible for the Core malicious pool. This distinction is deliberate: the registry is broader than the primary detection benchmark. A source can therefore contribute Core malicious artifacts, high-confidence Main-benign artifacts, Auxiliary evidence, or a mixture of these roles.

The public source-of-record revisions are frozen and traceable. We preserve *reported* and *acquired* counts separately and do not synthesize missing records to force agreement with a paper or README. Acquisition is static only: archives and text are inspected for canonicalization and hashing, but Skill code, helper programs, payloads, URLs, installers, evaluators, and test harnesses are never executed. For SRC002 and SRC004, the public revisions remain the source of record while eligible malicious rows are linked to author-provided historical research snapshots that recover the corresponding static Skill artifacts. Table 3 gives the complete 13-source snapshot used by this paper.

Table 3: Complete frozen source registry used by this paper. "Reported" is the source/paper count at the recorded public revision; "Acquired" is the number of source records materialized into the canonical registry. Core M is the number of malicious Skill artifacts admitted to Core, including SRC002/SRC004 artifacts recovered from author-provided historical research snapshots. Main B is the raw high-confidence benign contribution before cross-label conflict exclusion. A dash denotes zero.

ID	Source	Reported	Acquired	Core M	Main B	Canonical benchmark role
SRC001	MalSkillBench	7,944	7,944	3,944	–	Core malicious; source benign labels retained outside Main
SRC002	MaliciousAgentSkills Bench	98,380	98,380	157	–	Recovered malicious artifacts enter Core; public metadata/security labels otherwise remain Auxiliary
SRC003	Skill-Inject	202	319	–	–	Auxiliary only: released unit is an injection–task pair
SRC004	SkillLeakBench	520	520	79	–	Recovered malicious artifacts enter Core; vulnerability-only and unresolved rows remain Auxiliary
SRC005	Agent Skill Malware	350	347	124	–	Core malicious; weak benign labels retained outside Main
SRC006	AgentTrap	141	141	91	50	Core malicious + Main benign
SRC007	ClawHub Security Signals	67,453	67,453	–	–	Auxiliary only: automated silver scanner labels
SRC008	SkillTrojan	3,000+	3	1	2	Core example + Main benign examples; full reported corpus unavailable
SRC009	SkillHarm	879	879	879	–	Core malicious
SRC010	SkillTrustBench	5,520	5,520	2,863	1,643	Core malicious + Main benign; vulnerable rows remain Auxiliary
SRC011	ATR Skill Security Benchmark	498	498	32	466	Core malicious + Main benign
SRC012	SkillFortifyBench	540	540	90	90	Claude Skill artifacts enter Core/Main; MCP/OpenClaw formats remain Auxiliary
SRC013	SkillSafetyBench	155	155	154	–	Skill-carried attack cases enter Core; one environment-only case is Auxiliary

A.2 CORE, MAIN-BENIGN, AND AUXILIARY ROLES

The Core malicious pool is intentionally narrower than the source registry. A record enters Core only when the released or recovered research unit is a Skill artifact (`skill_md` or `skill_package`), canonical intent is malicious, static content is available for content hashing/detector input, and the record is traceable to the frozen source revision. **Eleven sources** satisfy these requirements for at least one malicious artifact. Five sources—SRC006, SRC008, SRC010, SRC011, and SRC012—also contribute strong/moderate Main-benign artifacts before conflict exclusion, yielding 2,251 raw Main-benign records (2,238 exact- and normalized unique units).

The remaining source content is not discarded. Vulnerability-only records, task-pair attack cases, metadata-only verdicts without recovered artifacts, automated scanner labels, non-Skill formats, weak/silver benign labels, and environment-only cases are retained as Auxiliary data with their original source semantics. Table 4 explains the two registry sources that contribute no Core malicious artifact. Mixed-role sources are handled at record level: SRC002 and SRC004 now contribute recovered malicious Skill artifacts to Core while their public metadata-only/non-malicious rows

retain Auxiliary semantics; SkillFortifyBench contributes only Claude Skill artifacts to Core/Main while MCP/OpenClaw formats remain Auxiliary; and SkillSafetyBench contributes 154 Skill-carried attack cases while its single environment-only case remains Auxiliary.

Table 4: Why the two registry sources with zero Core malicious artifacts remain Auxiliary. Auxiliary status is a semantic decision about the released unit/evidence, not a judgment that the source is unimportant.

ID	Released object / supervision	Reason for Auxiliary-only status
SRC003	injection–task pairs over host Skills	The benchmark unit is a task pair with no malicious Skill artifact; contextual cases are additionally retained as harmful/dual-use under their source semantics.
SRC007	sanitized marketplace content with automated security signals	Labels are automated silver supervision (clean/suspicious/malicious signals), so scanner-positive records are not promoted to malicious Core ground truth.

A.3 Frozen revisions and release constraints

Reproducibility requires distinguishing the source snapshot used for analysis from source/package redistribution beyond the public benchmark text layer. Table 5 records the frozen revision, acquisition status, upstream license, and source/package redistribution policy. "Allowed" refers only to the acquired public artifact under the recorded license; it does not override upstream terms. For SRC002 and SRC004, the recovered malicious artifacts come from author-provided historical research snapshots; the exact frozen static Skill text for accepted public identities is now released while that historical provenance remains recorded. Where full package/archive redistribution is restricted or unclear, the benchmark exposes the per-identity text representation together with source adapters, revision identifiers, metadata, and hashes, while omitting the underlying package bytes.

Table 5: Frozen source revisions, licensing, and source/package redistribution policy. Revisions are abbreviated here for readability; the release registry stores full commit/revision identifiers and checksums. The policy column concerns upstream package/archive material beyond the public per-identity static-text layer described in Appendix L. "Partial" means the pinned public artifact does not exactly reproduce the count or artifact set claimed by the associated paper/README; no missing records are reconstructed.

ID	Revision	Status	Upstream license	Source/package redistribution policy
SRC001	`06e08312`	completed	academic-research-only	adapter only
SRC002	`422bf340`	completed	MIT	exact frozen static Skill text released; historical snapshot provenance retained
SRC003	`182f3d9d`	partial	MIT	allowed
SRC004	`8264436a`	completed	MIT	exact frozen static Skill text released; historical snapshot provenance retained
SRC005	`5cff435d`	partial	MIT	allowed
SRC006	`ab13f59d`	completed	terms not provided	metadata/hash only
SRC007	`69dcbd32`	completed	MIT	allowed
SRC008	`2864c752`	partial	Apache-2.0 snapshot	allowed for acquired repository snapshot
SRC009	`cc21f909`	completed	CC-BY-4.0	metadata/hash only
SRC010	`f90517b7`	completed	CC-BY-NC-SA-4.0	metadata/hash only
SRC011	`7219b10d`	completed	MIT	allowed
SRC012	`eb9d5a9c`	completed	MIT	allowed
SRC013	`e0589d7b`	completed	Apache-2.0	allowed

A.4 Documented source discrepancies and recovery cases

We preserve version/count discrepancies and recovery boundaries as explicit provenance. The most consequential cases are:

- **SRC002 (MaliciousAgentSkillsBench).** The public snapshot contains 98,380 metadata rows, including 157 confirmed-malicious rows, but does not release the corresponding raw malicious Skill packages. We link all 157 rows to author-provided historical research artifacts with high-confidence mapping and admit those static artifacts to Core. The public metadata remains the source of record for provenance; exact frozen static Skill text for the accepted benchmark identities

is included in the public benchmark release, without treating the historical package snapshot as the public source of record.

- **SRC003 (Skill-Inject).** The paper reports 202 injection–task pairs over 23 Skills, whereas the pinned current commit contains 319 pairs over 33 referenced host Skill paths. We retain the pinned 319-row snapshot, mark the acquisition as partial relative to the paper, and keep the task-pair unit outside Core.
- **SRC004 (SkillLeakBench).** The corresponding empirical study reports 520 affected Skills (Chen et al., 2026); the public snapshot contains 437 vulnerable and 83 malicious metadata rows but does not contain the raw malicious `SKILL.md` artifacts. Author-provided historical packages resolve 79 malicious artifacts under the Core rule, and exact frozen static Skill text for accepted benchmark identities is included in the public benchmark release. Four ambiguous multi-Skill cases remain outside Core, and the 437 vulnerability-only rows remain Auxiliary.
- **SRC005 (Agent Skill Malware).** The README reports 350 rows (127 malicious + 223 benign), but the fixed revision contains 347 (124 malicious + 223 benign). The three missing malicious records are not reconstructed; Core therefore contains the 124 acquired malicious artifacts.
- **SRC006 (AgentTrap).** A previous metadata-only ingestion did not contain runnable Skill packages. The frozen P1 revision safely recovered all 141 public packages (91 malicious + 50 benign) for local static research. Because the upstream archive provides no explicit redistribution terms, full package/archive redistribution remains restricted; the public benchmark still provides its per-identity static-text representation and reproducibility metadata.
- **SRC008 (SkillTrojan).** The paper reports a curated SkillTrojanX corpus with 3,000+ backdoored Skills, but the pinned official repository exposes only three example Skill packages. We acquire exactly those three examples (one malicious, two benign) and do not generate the missing paper-scale corpus.
- **SRC013 (SkillSafetyBench).** The benchmark reports 155 adversarial cases. Static carrier auditing finds 154 cases with an explicitly injected/modified file inside a Skill package and one environment-only case; the former enter Core and the latter remains Auxiliary.

These cases illustrate why MALICIOUSSKILLBENCH treats source revision, released artifact unit, recovered-artifact provenance, and acquired count as first-class benchmark metadata. "Paper-reported size" and "artifact-level samples available for a frozen evaluation snapshot" are treated as distinct quantities.

B CANONICAL TAXONOMY AND DATA MODEL

The unified registry is intentionally multi-axis: *what a record is labeled as*, *where it came from*, *how strongly that label is supported*, *what evidence supports it*, and *whether it is an original or derived artifact* are represented separately. This design prevents a source-specific word such as "malicious," "suspicious," or "clean" from silently determining benchmark role. The schema is frozen for this paper; source labels are retained losslessly alongside canonical fields.

B.1 CANONICAL RECORD SCHEMA

Table 6 summarizes the field families used by the frozen benchmark. Stable identifiers and source metadata preserve traceability; semantic fields separate intent, provenance, confidence, and evidence; content hashes support conservative identity checks; lineage fields are populated only from source-published relationships; and release fields document what may be redistributed. Fields used only for auditing or split construction are never supplied to the text detectors in Section 6.

The canonical manifest contains 182,699 source records. Its observed intent distribution is 142,490 `benign`, 29,840 `uncertain`, 8,779 `malicious`, 1,451 `vulnerable`, and 139 `harmful_or_dual_use`. Importantly, canonical intent is not benchmark membership: **8,414** of the 8,779 malicious-intent records satisfy the stricter Core artifact rule in the frozen benchmark, while benign records are further separated into Main and Auxiliary pools according to evidence strength and artifact availability.

Table 6: Field groups in the frozen canonical schema. Fields shown are representative; source-native labels are retained in addition to the canonical fields.

Field group	Representative fields	Purpose
Identity	`canonical_id`, `source_id`, `source_record_id`	Stable benchmark identity while retaining upstream traceability.
Source snapshot	`source_dataset`, `repository_commit`, `dataset_snapshot_date`, paper version	Reconstruct the exact public revision used for acquisition.
Artifact / role	`artifact_unit`, `core_malicious_skill`, `auxiliary_type`	Separate Skill artifacts from task pairs, metadata, fixtures, and other non-Core units.
Semantic labels	`source_label`, `intent_label`, `provenance`, `ground_truth_strength`, `evidence_level`	Preserve source semantics while exposing orthogonal canonical axes.
Content identity	`skill_sha256`, `normalized_skill_sha256`	Exact and conservative formatting-normalized identity; no semantic equivalence claim.
Lineage	`lineage_status`, `lineage_resolution`, `lineage_basis`, `base_skill_id`, `variant_id`, `base_skill_semantics`	Preserve only source-supported parent/family relationships and explain what a base identifier means.
Release / safety	`license`, redistribution status, local/static content reference	Record what can be audited or redistributed without executing potentially malicious artifacts.

B.2 Intent labels

Canonical intent answers *what claim is being made about the record*; it does not encode origin or confidence. Table 7 gives the operational definitions used during source mapping. We choose the most conservative label supported by the source semantics: ambiguous scanner findings remain `uncertain`, vulnerability findings remain `vulnerable`, and harmful-but-not-intentionally-malicious cases remain `harmful_or_dual_use`.

Table 7: Canonical intent labels. Counts are over all 182,699 source records before Core/Main filtering.

Intent	Records	Operational meaning
`malicious`	8,779	The source supports intentional malicious or unauthorized behavior associated with the record. Core eligibility is checked separately.
`vulnerable`	1,451	A weakness, exposure, or exploitable condition is reported, without sufficient evidence that the Skill artifact itself is intentionally malicious.
`harmful_or_dual_use`	139	The case can facilitate harmful behavior, but the released case is not treated as an intentionally malicious Skill artifact.
`benign`	142,490	The source presents the record as normal/safe/negative; confidence and admissibility as Main benign are represented separately.
`uncertain`	29,840	Suspicious, ambiguous, or scanner-derived security signal that is insufficient for a stronger canonical intent claim.

B.3 Provenance taxonomy

Provenance answers *how the artifact arose*. It is independent of label confidence: a synthetic artifact can have strong ground truth, while a wild record can have only silver scanner evidence. Table 8 reports the controlled vocabulary and the frozen Core-malicious distribution. `mixed_unresolved` is used when a source reports an aggregate mixture (for example, wild and generated records) but does not publish a trustworthy row-level mapping. We do not infer such provenance from filenames, content similarity, or repository context.

Table 8: Provenance vocabulary and frozen Core-malicious distribution. Raw counts are source records and sum to 8,414. Normalized-unique counts are identity coverage by provenance and can overlap when the same normalized identity appears in sources with different provenance labels.

Provenance	Core raw	Norm. unique	Meaning
`wild`	413	364	Collected from a real upstream ecosystem/repository under the source's published semantics; no benchmark-authored attack construction.
`synthetic`	295	295	Synthetic standalone Skill/test artifact generated or authored for evaluation.
`injected`	3,460	3,352	Malicious/harmful content is inserted into a pre-existing carrier, host Skill, or task construction.
`backdoored`	193	161	Benign-looking Skill contains hidden or triggered malicious behavior.
`test_fixture`	109	107	Curated or benchmark-authored fixture used as a controlled security test artifact.
`mixed_unresolved`	3,944	3,430	Source reports a mixture of origins but lacks a trustworthy row-level provenance mapping.
`unknown`	0	0	No supported provenance classification is available.

B.4 Label strength and evidence are orthogonal

We represent confidence and evidentiary mechanism as two separate axes. *Ground-truth strength* describes how strongly the benchmark is willing to rely on a label; *evidence level* describes what kind of evidence produced that label. For example, a deliberately constructed attack can be `strong`/`constructed`, a manually curated benign artifact can be `moderate`/`static`, and a marketplace record can be `silver`/`scanner`. Consequently, evidence type must not be interpreted as an ordinal confidence score. Table 9 gives the frozen vocabulary for both axes.

Table 9: Ground-truth strength and evidence-level vocabularies. These axes are intentionally independent. Full-registry counts are shown for observed values.

Ground-truth strength		
`strong`	10,525	High-confidence source evidence suitable for primary ground truth when artifact/unit constraints are also satisfied.
`moderate`	2,275	Meaningful source evidence with weaker certainty than strong; may still enter Core/Main under source-specific rules.
`silver`	169,676	Automated/scanner-derived or weakly supervised labels; retained for analysis but not sufficient alone for Core/Main ground truth.
`weak`	223	Weak negative/heuristic evidence; Auxiliary only.
`unknown`	0	No confidence assignment.
Evidence level		
`human+runtime`	4,621	Human-grounded label together with runtime/behavioral confirmation.
`runtime`	141	Behavioral execution/runtime evidence without the combined human+runtime designation.
`static`	2,359	Static artifact inspection or curated source evidence without runtime confirmation.
`scanner`	169,676	Automated scanner or security-signal output.
`constructed`	5,902	Label is known from controlled benchmark construction, injection, or backdoor generation.
`human`, `llm`, `unknown`	0	Controlled vocabulary values reserved for explicit human-only, LLM-only, or unavailable evidence; not observed in the frozen analysis manifest.

In the frozen registry, the full 182,699-record manifest contains 169,676 silver, 10,525 strong, 2,275 moderate, and 223 weak labels. Scanner evidence dominates the full registry because the largest marketplace-security corpora are silver-standard resources. By contrast, the **8,414 raw Core mali-**

cious artifacts contain only strong (8,237) or moderate (177) labels, supported by `constructed` (3,966), `human+runtime` (4,180), `static` (177), or `runtime` (91) evidence. Scanner-only evidence therefore never enters Core malicious ground truth.

B.5 Artifact units and Core eligibility

Artifact unit records *what the released or recovered row actually represents*. This distinction is central to the benchmark: a source may publish a security-relevant task pair, scanner verdict, MCP configuration, or environment fixture without releasing a malicious Agent Skill artifact that can be hashed and evaluated as a Skill. Table 10 reports the observed values in the frozen analysis manifest. Only `skill_package` and `skill_md` are eligible artifact units for the Core malicious pool, and even those must also satisfy intent, traceability, content-availability, and source-mapping requirements.

Table 10: Observed artifact units in the frozen analysis manifest. Core counts show the stricter malicious-Skill subset; recovered SRC002/SRC004 malicious artifacts account for the increase in `skill_md` units relative to the earlier snapshot.

Artifact unit	All records	Core malicious	Interpretation / Core policy
`skill_package`	82,094	7,932	Complete or package-level Skill artifact; Core-eligible when all other rules pass.
`skill_md`	1,261	482	Primary Skill instruction artifact; Core-eligible when all other rules pass.
`task_pair`	319	0	Attack/task evaluation pair; no released malicious Skill artifact; Auxiliary.
`mcp_config`	180	0	MCP-format configuration from a multi-format testbed; outside current Skill Core.
`openclaw_manifest`	180	0	OpenClaw-format manifest from a multi-format testbed; outside current Skill Core.
`environment_fixture`	1	0	Attack is carried only in the environment and is absent from the Skill package; Auxiliary.
`other`	98,664	0	Metadata/scanner/vulnerability or other non-Core record representation.

B.6 Evidence-based lineage semantics

Lineage is recorded only when the source publishes a relationship that can be traced without similarity-based inference. We distinguish three concepts. `lineage_status` describes whether a record is standalone, derived, or a variant; `lineage_resolution` describes whether the source-published linkage is fully resolved, only family-level resolved, or unresolved; and `base_skill_semantics` states what a source's "base" identifier actually denotes. Table 11 defines these fields.

Among the 8,414 Core records, lineage status is `variant` for 3,892, `derived` for 177, `independent` for 165, and `unknown` for 4,180. Official lineage is fully resolved for 1,380 Core records and family-level partially resolved for another 35; 6,999 remain unresolved. The 1,415 records with official full/partial linkage expose 448 namespaced base identifiers in the analysis manifest, but these identifiers are deliberately *not* summed as "448 independent attacks." Depending on the source, a base identifier may denote a pre-attack carrier Skill, an upstream Skill identity, a benchmark family, a logical generation seed, or a standalone benchmark artifact. Structural-template families are a separate audit construct and are never converted into lineage or campaign identity.

B.7 Source-label preservation and conservative mapping

The original `source_label` is retained alongside canonical intent, strength, and evidence. Mapping is source-specific and follows each release's documented semantics; the same surface word can support different canonical claims across sources. Table 12 gives representative mappings that illustrate this policy. A canonical malicious intent still does not imply Core membership unless an inspectable Skill artifact can be mapped to the frozen source record under the Core eligibility rule.

Table 11: Lineage semantics in the frozen schema. Lineage is source-evidenced and is never inferred from textual similarity or structural clustering.

Field	Values	Meaning
`lineage_status`	`independent`, `derived`, `variant`, `unknown`	Logical relationship asserted by the source: standalone identity, explicit derivative, member of a published variant family, or unresolved.
`lineage_resolution`	`resolved_official`; `partially_resolved_official`; `unresolved`	Whether an official parent/upstream/logical identity is fully available, only a family-level identity is available, or no trustworthy row-level link exists.
`lineage_basis`	official parent/family ID, upstream slug, benchmark-authored identity, logical construction ID, none	What source-published signal justifies the linkage; filenames and similarity are not accepted as lineage evidence.
`base_skill_semantics`	pre-attack carrier, upstream identity, benchmark family, generation seed, standalone identity, unknown	Explains what the source-specific `base_skill_id` denotes so heterogeneous base IDs are not mistaken for a common attack-family unit.
`base_skill_id`, `variant_id`	source-scoped strings or null	Retain the publisher's identifier when available; values are namespaced/source-specific and are not globally additive.

Table 12: Representative source-label mappings. Mapping depends on source semantics, evidence, and artifact availability, not on the literal label string alone.

Source	Source label	Canonical intent	Strength / evidence	Benchmark interpretation
SRC002	`safe`	`benign`	silver / scanner	Metadata-level negative signal; retained in Auxiliary and excluded from Main benign.
SRC002	confirmed malicious	`malicious`	strong / human+runtime	Eligible for Core only after high-confidence linkage to an author-provided historical Skill artifact.
SRC007	`malicious`	`uncertain`	silver / scanner	Even a literal "malicious" scanner verdict remains uncertain without stronger ground truth.
SRC003	`contextual`	`harmful_or_dual_use`	moderate / constructed	Context-dependent harmful task case; not a Core malicious Skill artifact.
SRC010	`suspicious`	`vulnerable`	strong/moderate; constructed/static	Source semantics describe vulnerable/suspicious cases without asserting intentional malicious artifacts.
SRC004	`malicious`	`malicious`	strong / human+runtime	79 source-malicious rows map to recovered historical Skill artifacts and enter Core; four ambiguous multi-Skill rows remain outside Core.
SRC001	`malware`	`malicious`	strong / human+runtime	Inspectable Skill artifact with supported malicious intent; eligible for Core.
SRC010	`normal`	`benign`	moderate/static or strong/constructed	High-confidence benign Skill artifact; eligible for the Main-benign candidate pool.

This multi-axis representation is the basis for the benchmark's evidence-preserving consolidation. It preserves disagreements and evidentiary differences as auditable metadata instead of forcing all upstream taxonomies into a single binary label before deduplication, conflict checking, and split construction.

C Deduplication and Structural Reuse

The benchmark separates three increasingly permissive notions of reuse: byte-level identity, conservative normalized-text identity, and static structural-template similarity. These levels serve different purposes and are never collapsed into a single notion of "same attack." Exact and normalized hashes support content identity checks; structural families are an operational grouping used for audit and

split construction. No Skill, helper, payload, URL, or executable content is run during any stage of this analysis.

C.1 Exact and normalized content identity

Exact identity is SHA-256 over the acquired Skill content. Normalized identity hashes a deterministic text normalization that is intentionally conservative. The frozen normalization decodes valid UTF-8, removes one leading BOM, converts CRLF/CR to LF, strips trailing spaces/tabs on each line, trims leading/trailing blank lines, collapses runs of three or more blank lines to two, and writes exactly one final LF for non-empty text. It does *not* lowercase text, remove Markdown front matter, code, punctuation, or semantic content, and it does not paraphrase or rewrite instructions. Normalized equality therefore captures identity equivalent up to formatting; semantic equivalence is outside the scope of this identity rule.

Applying the two identity levels to **8,414 Core malicious records** yields **7,562 exact unique** and **7,539 normalized unique** contents. Exact deduplication removes 852 redundant raw records (10.1% of Core), while normalization merges 23 additional global identities. Table 13 shows where within-source duplication occurs. Per-source unique counts do not sum to the global unique totals because the same content can appear in more than one source.

Table 13: Frozen Core malicious deduplication by source. "Raw−Exact" is the within-source reduction from repeated byte-identical artifacts; "Exact−Norm." is the additional within-source reduction after conservative text normalization. Per-source unique counts do not sum to the global unique totals because cross-source identities are shared.

Source	Raw	Exact unique	Norm. unique	Raw−Exact	Exact−Norm.
SRC001	3,944	3,430	3,430	514	0
SRC002	157	157	157	0	0
SRC004	79	67	67	12	0
SRC005	124	124	124	0	0
SRC006	91	89	89	2	0
SRC008	1	1	1	0	0
SRC009	879	739	739	140	0
SRC010	2,863	2,861	2,861	2	0
SRC011	32	31	29	1	2
SRC012	90	90	90	0	0
SRC013	154	154	154	0	0
Global unique	8,414	7,562	7,539	852	23

At the exact-hash level, 131 duplicate clusters contain 983 raw Core records, with a largest cluster of 54 records; 28 exact clusters contain at least ten records. Duplication remains concentrated in a few sources, while the recovered SRC004 artifacts add 12 within-source exact duplicates. These counts describe repeated released/recovered artifacts, not independent attack lineage.

C.2 Cross-source content reuse

Content reuse also crosses nominal dataset boundaries. Across the frozen Core pool, **105 exact hashes** and **119 normalized hashes** occur in more than one source. Those shared hashes involve 830 raw Core records at exact identity and 871 raw Core records at normalized identity. Table 14 lists every source pair with non-zero normalized overlap.

The overlap is strongly asymmetric. The 90 normalized hashes shared by SRC001 and SRC005 cover 15.14% of SRC001 raw Core records but 72.58% of SRC005. The recovered sources add further observable overlap: 21 normalized hashes are shared by SRC001 and SRC004, covering 35.44% of SRC004 raw Core records, while three are shared by SRC001 and SRC002. A single normalized identity can occur in more than two sources, so pairwise overlap counts are not additive. We therefore report overlap at the artifact-reuse level and make no inference about source ancestry, common actor identity, or campaign membership.

Table 14: Non-zero cross-source Core content overlap in the frozen benchmark. Coverage is the fraction of each source's raw Core records participating in a shared normalized hash with the paired source. Pairwise counts overlap when one identity occurs in three or more sources.

Source A	Source B	Exact hashes	Norm. hashes	Norm. cov. A	Norm. cov. B
SRC001	SRC002	3	3	0.13%	1.91%
SRC001	SRC004	21	21	0.79%	35.44%
SRC001	SRC005	69	90	15.14%	72.58%
SRC001	SRC006	1	1	0.03%	1.10%
SRC001	SRC010	78	78	14.63%	2.72%
SRC001	SRC011	6	8	0.35%	28.13%
SRC004	SRC005	0	3	7.59%	2.42%
SRC004	SRC009	1	1	1.27%	3.53%
SRC004	SRC010	7	7	13.92%	0.24%
SRC004	SRC011	4	5	6.33%	15.63%
SRC005	SRC010	63	68	54.84%	2.38%
SRC005	SRC011	4	4	3.23%	15.63%
SRC010	SRC011	0	1	0.03%	3.13%

C.3 Static structural-similarity pipeline

Exact/normalized equality does not capture templated variants that preserve a common document scaffold while changing names, endpoints, paths, identifiers, parameters, or local insertions. We therefore maintain a separate static structural-similarity partition over one representative per normalized hash. Cluster membership is determined entirely by fixed text features and the pre-specified medium threshold 0.68; no LLM or embedding model decides membership.

Template normalization conservatively replaces front-matter Skill names, URLs, domains, email/IP values, UUIDs and long IDs, filesystem paths, obvious secret values, long numeric payload parameters, environment variables, and assignment-left-hand-side identifiers. Behavior-bearing terms—including credential access, file reads, network sends, shell/subprocess operations, `eval`, encryption, download, and execution—are retained. Template similarity is the weighted score

$$0.36J_{\text{3-gram}} + 0.28C_{\text{tfidf}} + 0.14J_{\text{struct}} + 0.12J_{\text{behavior}} + 0.10\,\text{containment},$$

where the terms denote token-3-gram Jaccard, TF-IDF cosine, structural-line Jaccard, behavior-token Jaccard, and token containment, respectively.

The frozen partition applies the same operational threshold to **7,539 normalized Core identities**. Relative to the inherited 7,340-node partition, 199 newly recovered normalized identities are integrated with explicit hash-origin bookkeeping: 25 join inherited families, two form one new recovered-only two-node family, and 172 become new singletons. A full family crosswalk confirms that none of the 4,415 inherited families is split or merged. Table 15 reports the resulting partition evolution. The 0.68 threshold is used solely as an operational structural-reuse control. It was fixed independently of detector performance and carries no semantic attack interpretation.

Table 15: Structural-partition evolution at the frozen medium threshold 0.68. The final partition preserves every inherited pre-recovery family without split/merge and integrates 199 newly recovered normalized identities under the same operational similarity rule.

Snapshot	Nodes	Families	Singletons	Non-singleton	Largest	Cross-source
Pre-recovery inherited base	7,340	4,415	3,059	1,356	146	91
Final frozen partition	7,539	4,588	3,219	1,369	146	113

C.4 Family distribution and cross-source structural reuse

At threshold 0.68, the frozen partition contains **4,588 operational structural-family identifiers**: 3,219 singletons and 1,369 non-singletons containing 4,320 normalized identities. These identifiers are frozen before final cross-label exclusion: **4,575** are represented by at least one final primary malicious identity, while 13 retained identifiers have no final primary member after conservative cross-label exclusion. Among non-singleton families, median size is 2 and mean size is 3.16; the largest family contains 146 normalized identities spanning SRC001, SRC009, and SRC013. **113**

families contain artifacts associated with more than one source. Table 16 reports the largest pairwise structural overlaps.

Table 16: Largest pairwise cross-source structural overlaps in the frozen partition at threshold 0.68. Coverage is computed over normalized-unique Core units associated with each source. These entries report operational template overlap only, with no lineage or campaign attribution.

Source A	Source B	Shared families	Coverage A	Coverage B
SRC001	SRC010	39	3.38%	3.04%
SRC001	SRC005	36	3.09%	75.81%
SRC001	SRC004	30	2.22%	49.25%
SRC005	SRC010	29	68.55%	2.48%
SRC009	SRC013	26	42.35%	62.99%
SRC004	SRC010	17	26.87%	1.47%
SRC004	SRC005	13	19.40%	40.32%
SRC001	SRC006	11	1.14%	22.47%
SRC001	SRC002	10	0.61%	8.28%
SRC001	SRC011	9	0.35%	34.48%

Structural overlap can be substantial even when exact/normalized hashes do not overlap. SRC009 and SRC013, for example, share no exact or normalized Core hash, yet 26 operational structural families span both sources; those families cover 42.35% of SRC009 normalized units and 62.99% of SRC013. The recovered SRC004 artifacts also expose substantial structural reuse with existing corpora: 30 families span SRC001/SRC004, covering 49.25% of SRC004 normalized identities. This provides scaffold-level reuse evidence under the fixed static method; it does not support claims about copying, shared actors, shared campaigns, or independent attack identity.

C.5 Connected-component bridge audit

Connected components can link members indirectly through intermediate nodes even when a member is below threshold relative to a selected representative. The frozen summary flags **15 of 4,588 families** (0.33%) for possible chaining; the largest 146-unit family is among them. We retain the connected-component family IDs as the operational partition and report the bridge flag explicitly; each family remains a connected component and need not form a clique. The recovery crosswalk additionally confirms that artifact recovery did not merge or split any inherited family.

C.6 Blind structural positive validation

Before the artifact-recovery extension, we performed a separate blind positive check on the inherited structural partition using an independent LLM reviewer on anonymized static artifact pairs. The reviewer received neither cluster IDs, similarity scores, threshold values, sampling categories, algorithm predictions, nor earlier reviewer labels. All 72 cases were valid blind cases; there were no blindness violations or unreadable pairs. The reviewer labeled all 72 pairs as sharing the same structural template, all at high confidence (Table 17). No embedded instruction, script, helper, URL, or payload was executed or followed.

Table 17: Blind structural positive-validation summary. The reviewer saw anonymized static artifact pairs only; cluster identifiers, similarity values, thresholds, sample categories, algorithm predictions, and prior labels were hidden.

Measure	Count
Total / valid blind cases	72 / 72
Blindness violations	0
Same structural template	72
Different structural template	0
Uncertain	0
High-confidence judgments	72
Unreadable / missing	0

Because the final partition preserves every inherited family without split or merge, this validation remains a bounded positive-coherence check for the sampled inherited within-family pairs. Its coverage is limited to those sampled inherited pairs and leaves the 199 recovered identities, newly

created families, clustering recall, and threshold semantics unvalidated. The **4,588 families** serve as an operational structural partition for reducing scaffold reuse across evaluation splits; they carry no gold attack-ontology interpretation.

C.7 Interpretation boundaries

The three reuse levels answer different questions. Exact hashes identify identical acquired content; normalized hashes identify conservatively content equivalent up to formatting; structural families identify static scaffold similarity under the frozen feature/threshold pipeline. None of these establishes lineage, actor identity, uploader identity, campaign membership, or attack-mechanism equivalence. Candidate-generation heuristics may miss deep paraphrases that share no selected feature, while static similarity may over-link boilerplate. These limitations motivate the paper's conservative use of structural family IDs as grouping variables for audit and Malicious-Structural-Disjoint evaluation, with no ground-truth attack-label semantics.

D Benign Pool and Cross-Label Conflicts

The negative class is constructed conservatively because "benign," "clean," "not flagged," and "safe" do not carry the same evidentiary meaning across the 13 sources. The primary detection benchmark therefore uses a high-confidence *Main-benign* pool and keeps weaker or non-comparable negative signals in an *Auxiliary-benign* layer. This appendix documents the candidate gates, deduplication accounting, and the cross-label conflict policy that converts 48,217 benign-side candidates into the 2,235 normalized unique benign units used by the frozen primary benchmark.

D.1 Main versus Auxiliary benign candidates

A benign-side record is eligible for the Main pool only when it is an inspectable Skill artifact, its source semantics support canonical benign intent, its label strength is strong or moderate, static content is available for hashing and detector input, and the record remains traceable to a frozen source revision. Scanner-clean, marketplace-unflagged, silver, weak, metadata-only, and otherwise non-comparable negative signals remain Auxiliary. Table 18 summarizes this gate.

Table 18: Frozen eligibility gate for the benign reference pools. "Auxiliary" preserves security-relevant negative signals without promoting them to primary benign ground truth.

Criterion	Main-benign requirement	Auxiliary treatment
Released unit	Inspectable Agent Skill artifact usable for static hashing/detector input	Metadata-only, scanner-only, non-Skill, or otherwise non-comparable negative records remain Auxiliary
Canonical intent	`benign` under source-specific mapping	Uncertain, vulnerable, harmful/dual-use, or unresolved semantics are never collapsed into benign
Label strength	Strong or moderate	Silver, weak, "not flagged," marketplace-unflagged, and analogous weak negatives remain Auxiliary
Content availability	Static primary Skill content available	Records lacking inspectable Skill text are excluded from the primary negative class
Traceability	Frozen source revision and source record can be reconstructed	Untraceable or revision-ambiguous records are not promoted to Main

Applying the gate yields 2,251 raw Main-benign artifacts and 45,966 raw Auxiliary-benign records. The two pools are kept separate throughout benchmark construction; Auxiliary negatives are not silently promoted merely because they are numerous. Table 19 reports the frozen identity counts.

Table 19: Frozen benign-side pool counts before cross-label conflict exclusion. Main is the primary high-confidence negative pool; Auxiliary retains weaker or non-comparable benign-side evidence.

Pool	Raw	Exact-unique	Normalized-unique	Primary benchmark use
Main benign	2,251	2,238	2,238	Eligible before conflict exclusion
Auxiliary benign	45,966	44,329	44,327	Not used as primary negative ground truth

The Main pool is intentionally much smaller than the full benign-side registry. This trades coverage for label comparability: the primary benchmark asks whether a detector can separate Core malicious

Skills from higher-confidence benign Skill artifacts, while the much larger Auxiliary layer remains available for future stress tests, scanner-comparison studies, or separately versioned evaluations.

D.2 Main-benign source contributions

Only five frozen sources contribute Main-benign candidates: SRC006, SRC008, SRC010, SRC011, and SRC012. Their raw contributions sum exactly to 2,251 (Table 20). Sources with weaker negative semantics remain outside Main even when they contain records described upstream as benign or clean. For example, SRC001 source-benign records are retained outside Main under the frozen adapter, SRC005 benign rows are weak evidence under the benchmark taxonomy, and scanner-derived negative signals from SRC002/SRC007 remain silver Auxiliary supervision.

Table 20: Sources contributing raw Main-benign candidates before deduplication and conflict exclusion. Counts sum to 2,251.

ID	Source	Raw Main B	Frozen benchmark interpretation
SRC006	AgentTrap	50	Inspectable benign Skill packages with strong/moderate source evidence
SRC008	SkillTrojan	2	Benign example packages in the pinned public repository
SRC010	SkillTrustBench	1,643	High-confidence source-normal Skill artifacts eligible under the canonical benign mapping
SRC011	ATR Skill Security Benchmark	466	Inspectable benign Skill artifacts admitted by the frozen source adapter
SRC012	SkillFortifyBench	90	Benign Claude Skill artifacts; non-Skill MCP/OpenClaw formats remain Auxiliary
Total		2,251	

The resulting source mix is a high-confidence reference set assembled from public sources that expose both an inspectable Skill artifact and sufficiently strong benign-side evidence under the frozen mapping rules. Its coverage is bounded by those source and evidence gates. This restriction is also why source and class composition remain entangled in the Source-Disjoint evaluation.

D.3 Benign deduplication and static handling

The benign pools use the same exact and conservative normalized identity definitions as Appendix C. Main-benign deduplication reduces 2,251 raw records to 2,238 exact unique contents; normalized text identity introduces no additional merge, leaving 2,238 normalized unique Main candidates before conflict exclusion. The Auxiliary pool reduces from 45,966 raw records to 44,329 exact unique and 44,327 normalized unique contents. Thus the primary benign reference set is already close to content-unique before cross-label auditing, whereas the Auxiliary layer contains substantially more repeated content.

Five benign artifacts contain malformed UTF-8. They are processed statically using replacement decoding for text analysis while preserving raw-byte hashes for identity accounting. No affected artifact is executed, and the decoding choice does not alter the frozen raw hash. Benign structural clustering was not part of the frozen malicious-family pipeline; consequently, Malicious-Structural-Disjoint treats each normalized unique benign unit as a singleton group and performs no post-freeze benign family inference.

D.4 Cross-label conflict definition and accounting

After malicious and benign-side canonicalization, we compare exact and normalized content identities across opposite labels. A *cross-label conflict* occurs when the same content identity is represented on the malicious side and on the benign side of the frozen registry. This is a content-level inconsistency signal; it is not itself evidence that either source is wrong.

The frozen audit finds **34 exact-hash conflicts** and **34 normalized-hash conflicts**, affecting 162 Core-malicious raw records, four Main-benign raw records, and 39 Auxiliary-benign raw records. The exact and normalized audits expose the same number of conflicting identity groups in this snapshot; conservative normalization does not increase the conflict count. Table 21 shows how those groups affect the primary benchmark.

The benign-side conflict audit is broader than Main-negative membership. Although 43 benign-side raw records participate across Main and Auxiliary pools, only three normalized Main-benign

Table 21: Cross-label conflict accounting in the frozen benchmark. Raw affected counts measure source records participating in a conflict; removed-unit counts measure normalized-unique units that would otherwise enter the primary benchmark.

Quantity	Count	Benchmark effect
Exact conflict hashes	34	Identity groups with both malicious- and benign-side labels
Normalized conflict hashes	34	Frozen conflict groups used for exclusion
Core-malicious raw records affected	162	Source records participating on the malicious side
Main-benign raw records affected	4	High-confidence negative records participating in conflicts
Auxiliary-benign raw records affected	39	Auxiliary negative records participating in conflicts
Core-malicious normalized units removed	34	7,539 → 7,505
Main-benign normalized units removed	3	2,238 → 2,235
Total primary units removed	37	9,777 pre-conflict candidates → 9,740 final units

candidates would otherwise enter the primary benchmark. All **34 conflicting Core-malicious normalized identities** are excluded under the conservative conflict rule. The pre-conflict 7,539 malicious plus 2,238 Main-benign normalized units therefore lose 37 benchmark units in total, yielding the frozen **9,740-unit primary table: 7,505 malicious and 2,235 benign**.

D.5 Conservative conflict exclusion

Every conflicting normalized-content group is removed from the primary detection benchmark and retained as a separate label-consistency audit layer. Automatic relabeling by source majority, evidence ranking, filename, marketplace reputation, structural family, or detector score would introduce a new ground-truth judgment that is absent from the upstream releases. This policy is deliberately symmetric at the benchmark level: conflicting content cannot be used as a clean positive or negative training/test unit simply because one upstream source is preferred.

The policy has two consequences. First, the primary benchmark is easier to interpret because no normalized content is knowingly assigned both detection labels. Second, the excluded groups remain scientifically useful: they identify concrete places where public corpora disagree and can support a later human adjudication study. Any such adjudication should be separately versioned so the frozen benchmark used in this paper remains unchanged.

For safety and licensing reasons, the paper does not reproduce full malicious payload text from conflict groups. The audit is defined at the canonical-ID, source-ID, evidence-metadata, and content-hash level; potentially executable content remains inert and subject to the source-specific redistribution constraints in Appendix A.3.

D.6 Interpretation boundaries

The 34 conflicts quantify exact/normalized identity disagreement across corpora with different collection procedures, supervision regimes, and label semantics; the audit does not estimate annotation error rates. Main benign consists of records that satisfy the frozen primary-negative gate, while the remaining 45,966 Auxiliary records retain weaker or non-comparable evidence. The final 2,235-unit benign class is a conservative reference set for the paper's primary detection experiments, with coverage bounded by these source and evidence criteria.

E Threat Characterization Details

Section 5 uses source-supported threat metadata to describe what MaliciousSkillBench covers. This appendix records the characterization boundary, final harmonized categories, and supplementary views used to audit that summary. The unit throughout is the normalized unique primary malicious identity unless stated otherwise. The denominator is therefore the 7,505 final primary malicious identities; raw Core and pre-conflict counts are excluded from these prevalence calculations.

E.1 Characterization boundary and source-native coverage

Threat metadata are heterogeneous across the contributing resources, so we preserve source-native dimensions before harmonization and map only supported semantics into the common taxonomy.

Table 22: Threat-metadata coverage in the 7,505 primary malicious identities. Source-native fields preserve upstream semantics; harmonized fields use only documented direct or strong-semantic mappings. No missing field is inferred from Skill text.

Dimension	Annotated	Coverage	Sources	Semantics
Attack vector	1,466	19.5%	1	Source-native vector
Attack type / tactic	4,147	55.3%	9	Source-native attack labels
Behavior	5,456	72.7%	7	Source-native behavior labels
Insertion strategy	166	2.2%	1	Source-native insertion strategy
Target / asset	2,312	30.8%	3	Source-native target labels
Severity	209	2.8%	2	Source-native severity
MITRE ATT&CK	87	1.2%	1	Source-native ATT&CK mapping
Explicit impact / outcome	154	2.1%	1	Source-native impact
Harmonized attack	**4,983**	**66.4%**	9	Direct + strong-semantic mapping
Harmonized derived impact	**2,128**	**28.4%**	9	Conservative behavior-to-impact mapping

Table 22 reports the resulting coverage. Source-native behavior is available for 5,456 identities (72.7%), attack type/tactic for 4,147 (55.3%), and targets/assets for 2,312 (30.8%); explicit source-native impact labels are much sparser at only 154 identities (2.1%). These dimensions are not interchangeable: for example, a source-native behavior label is not automatically treated as an attack tactic or impact label.

The harmonized attack taxonomy is constructed only from documented *direct* or *strong-semantic* source-native mappings. No actor, campaign, provenance, mechanism, attack class, or impact is inferred from Skill text. Under this rule, 4,983 of 7,505 primary malicious identities (66.4%) receive at least one harmonized attack category. The remaining 2,522 identities stay attack-unmapped. Likewise, the derived impact taxonomy covers 2,128 identities (28.4%); this is a bounded characterization subset, not a new full-corpus label set.

Deterministic SRC001 recovery. MalSkillBench (SRC001) contains 3,426 primary normalized malicious identities. Its frozen release paths encode source-native CI/PI/MIXED vector and B1–B15 behavior suffixes for a subset. We recover these labels only by exact suffix matching, never by Skill-text interpretation. This yields vector and behavior labels for 1,466 identities and insertion-strategy labels for 166; 1,960 SRC001 identities have no trustworthy row-level taxonomy in the pinned release and remain unresolved. This deterministic recovery is one reason behavior coverage exceeds source-native attack-type/tactic coverage, while the B1–B15 labels remain source-native behavior labels and are not promoted to attack-type labels.

E.2 Final harmonized attack taxonomy

Table 23 gives the 11 final attack categories. The taxonomy is multi-label: one malicious identity can contribute to several categories when the source-native metadata supports multiple behaviors. The most common mapped category is Execution / Code Delivery (3,320 identities), followed by Instruction / Goal / Memory Manipulation (1,671) and Privilege / Tool / Authority Abuse (1,013). These aggregate counts should not be interpreted as a representative population distribution outside the collected sources.

E.3 Provenance composition varies by attack category

Figure 3 decomposes each harmonized attack category by the benchmark's frozen provenance field. The normalized view is used because absolute category prevalence is already reported in Table 23 and Figure 2a. The composition differs substantially across categories: large injected components appear in execution, instruction manipulation, privilege/tool abuse, and dependency/supply-chain abuse, while credential access, defense evasion, and discovery contain larger wild components. `mixed_unresolved` is retained when the source reports an aggregate mixture but no trustworthy per-row provenance mapping; we do not infer the missing provenance from content.

Table 23: Final harmonized attack taxonomy and prevalence. Counts are normalized-unique primary malicious identities among the 4,983 attack-mapped units. Categories are multi-label, so counts and percentages do not sum to the mapped denominator or 100%. "Sources" is the number of Core sources contributing at least one mapped identity to the category.

Attack category	Identities	% mapped	Sources
Execution / Code Delivery	3,320	66.6	7
Instruction / Goal / Memory Manipulation	1,671	33.5	8
Privilege / Tool / Authority Abuse	1,013	20.3	6
Data Exfiltration / Disclosure	355	7.1	6
Resource / Availability Abuse	330	6.6	4
Credential Access	303	6.1	5
Persistence / Control	249	5.0	6
Dependency / Supply-Chain Abuse	167	3.4	5
Integrity / Output Manipulation	97	1.9	3
Defense Evasion / Obfuscation	34	0.7	3
Discovery / Reconnaissance	15	0.3	2




Figure 3: Provenance composition by harmonized attack category. Each bar is normalized within category and therefore sums to 100%; the absolute mapped category total is printed at the right. Categories are multi-label, and provenance is taken directly from frozen benchmark metadata with no text-based inference.

E.4 MalSkillBench source-native attack vectors

Figure 4 reports the separate source-native attack-vector dimension recovered for 1,466 MalSkillBench (SRC001) identities: CI 621 (42.4%), PI 484 (33.0%), and MIXED 361 (24.6%). These labels remain SRC001-specific and are not imposed on the other ten Core-contributing sources. The figure therefore complements the 11-category harmonized attack taxonomy without extending its scope.

E.5 Attack-category co-occurrence

Because the taxonomy is multi-label, Figure 5 reports pair counts in the attack-mapped subset. The largest pairs are Execution / Code Delivery with Instruction / Goal / Memory Manipulation (1,244), Execution / Code Delivery with Privilege / Tool / Authority Abuse (810), and Instruction Manipulation with Privilege / Tool Abuse (235). They are descriptive co-memberships, not temporal, causal, or campaign relations.




Figure 4: MalSkillBench (SRC001) source-native attack-vector distribution for the 1,466 primary normalized identities with deterministic vector recovery. CI/PI/MIXED retain the source's own semantics and are not generalized to other sources.




Figure 5: Pairwise attack-category co-occurrence in the attack-mapped subset. The upper triangle reports raw normalized-identity counts; axes follow prevalence ordering and color uses power normalization only for visibility. The diagonal is omitted.

E.6 Derived impact taxonomy and intersection boundary

Explicit source-native impact/outcome labels cover only 154 identities. We therefore use a conservative nine-category derived mapping, supported by documented source-native behavior semantics, for

2,128 identities. Table 24 reports its marginal prevalence; the largest categories are unauthorized code execution / system control (489), sensitive data disclosure (423), and credential compromise (297).

Table 24: Conservative derived-impact prevalence among the 2,128 impact-mapped malicious identities. Labels are multi-label and come from documented source-native behavior semantics, not model labeling.

Derived impact	Identities	% mapped
Unauthorized code execution / system control	489	23.0
Sensitive data disclosure	423	19.9
Credential compromise	297	14.0
Agent-control / instruction compromise	275	12.9
Privilege / control manipulation	247	11.6
Resource / service abuse	212	10.0
Persistence / sustained control	146	6.9
Availability / destructive impact	144	6.8
Integrity / output manipulation	99	4.7

Only 1,888 identities have both mappings, so Figure 2c is restricted to this intersection. Key pairs are Execution–System Control (489), Exfiltration–Sensitive Data Disclosure (345), and Credential Access–Credential Compromise (293); these are descriptive, not causal. We omit a Sankey because this subset is only 25.2% of the primary malicious population. Scanner recall by attack category is reported with the scanner evaluation section, where detector behavior is analyzed.

F Evaluation Protocols and Leakage Audits

The primary evaluation protocols are frozen views of the conflict-clean normalized unique benchmark described in Appendix D. This appendix makes the assignment contracts and overlap audits explicit. The purpose is to distinguish a protocol's *required* disjointness from other relationships that may legitimately remain shared across partitions. Source IDs, provenance, lineage identifiers, and structural-family IDs are used only for split construction and auditing; none is supplied to the text detectors.

F.1 Frozen evaluation unit and assignment invariants

The frozen master detection table contains **9,740** normalized unique units: **7,505 malicious** and **2,235 Main-benign**. Labels and normalized-content identities are frozen before split construction. A unit is assigned to at most one train/validation/test partition, and no protocol performs split-specific relabeling, duplication, or synthetic oversampling. Seed 42 is used for the frozen assignments.

Table 25 gives the complete split inventory. Random, Source-Balanced Random, and Malicious-Structural-Disjoint retain all 9,740 master units. Source-Disjoint retains 9,732 because eight normalized identities have provenance spanning both a held-out source and a non-held-out source; these cross-boundary units are conservatively excluded before assignment to either side.

Table 25: Expanded inventory of the frozen evaluation protocols. M/B denotes malicious/benign counts. Source-Disjoint contains eight fewer units because cross-boundary multi-source normalized identities are conservatively excluded.

Protocol	**Retained**	**Train (M/B)**	**Val. (M/B)**	**Test (M/B)**	**Test src.**
Random	9,740	6,818 (5,254/1,564)	974 (750/224)	1,948 (1,501/447)	10
Source-bal. Random	9,740	6,817 (5,254/1,563)	973 (750/223)	1,950 (1,501/449)	11
Mal.-Struct.-Disj.	9,740	6,818 (5,254/1,564)	974 (750/224)	1,948 (1,501/447)	11
Source-Disjoint	9,732	7,513 (5,992/1,521)	835 (666/169)	1,384 (839/545)	3

Two similarly named controls should not be conflated. **Source-Balanced Random** is a split-assignment diagnostic: it allocates within source×label cohorts when possible while preserving the natural class prevalence. The later **Balanced** robustness control instead starts from an already frozen split and deterministically downsamples the majority malicious class within each partition to obtain a 1:1 class ratio. The former changes assignment; the latter changes only the retained subset within that assignment.

F.2 PROTOCOL CONSTRUCTION CONTRACTS

Random. We perform a label-stratified 70/10/20 assignment over the normalized unique master table. Exact and normalized identity are disjoint across partitions, but source, structural-family, and explicit-lineage relationships are not constrained. This serves as the conventional random-split reference; broader distributional independence is outside its scope.

Source-Balanced Random. Assignment is performed within representative-source×label cohorts when cohort size permits, targeting the same 70/10/20 proportions. The goal is to reduce accidental source-composition variation while retaining a random-style benchmark. Entire sources remain shared across partitions, so this is not a source-generalization protocol.

Malicious-Structural-Disjoint. Each of the **4,588** frozen malicious operational structural families is treated as an atomic group: a family may appear in train, validation, or test, but never in more than one partition. Benign structural clustering is not part of the frozen malicious-family pipeline; each benign normalized unique unit therefore uses a singleton fallback grouping ID. The protocol guarantees malicious structural-family disjointness, not full-benchmark structural ground truth and not explicit-lineage disjointness.

Source-Disjoint. SRC009, SRC011, and SRC012 are held out entirely for testing. After the eight cross-boundary multi-source normalized identities are removed, all remaining records associated with these held-out sources enter the test side and non-held-out sources supply train/validation. The 1,384-unit test therefore remains identical to the held-out source composition used for the longitudinal pre-recovery/post-recovery comparison, while the non-held-out train/validation pool expands after artifact recovery.

F.3 HELD-OUT SOURCE AND LABEL COMPOSITION

Source-Disjoint is intentionally reported as *source-conditioned generalization*, because source identity is entangled with label prevalence and corpus construction. Table 26 makes this confounding visible. SRC009 contributes only malicious test units, SRC011 is overwhelmingly benign, and SRC012 is balanced. The aggregate test set is 839 malicious / 545 benign, but that aggregate ratio hides substantial between-source label skew.

Table 26: Held-out test composition in Source-Disjoint. The source-wise label mixture is strongly heterogeneous, motivating the term source-conditioned generalization and limiting interpretation as a pure source-effect estimate.

ID	Source	Malicious	Benign	Total	Malicious share
SRC009	SkillHarm	728	0	728	100.0%
SRC011	ATR Skill Security	21	455	476	4.4%
SRC012	SkillFortifyBench	90	90	180	50.0%
Total	–	839	545	1,384	60.6%

This composition is why we do not interpret the Source-Disjoint gap as a pure causal effect of "unseen source identity." Holding out a source simultaneously changes provenance, construction procedure, documentation style, and label mixture. The balanced robustness control reduces overall class-prevalence effects, but it does not decorrelate these source-linked properties.

F.4 SUPPLEMENTARY CLASS-CONDITIONAL SOURCE HOLDOUTS

To separate the two label directions as far as the available source support permits, we construct two supplementary 50/50 diagnostics after inspecting the source×label support matrix and before model outcomes. The *malicious-side* diagnostic tests all 839 text-available malicious examples from held sources SRC009/011/012 against 839 benign controls sampled without replacement from benign-support sources represented in development (SRC006/008/010). The *benign-side* diagnostic tests all 545 benign examples from SRC011/012 against 545 malicious controls sampled without

replacement from non-held malicious sources. Remaining records are assigned deterministically to train/validation within source×label strata; train/validation/test identities are disjoint and both tests are exactly balanced.

These are class-conditional source-holdout diagnostics, not new canonical Source-Disjoint protocols: label support is limited, SRC009 is malicious-only, and opposite-class records from a held source may remain in development when needed to isolate the target class. They therefore support directional comparison, not a causal source effect. The canonical split hashes are unchanged.

F.5 Cross-partition overlap audit

For each frozen protocol, we audit five relationship types under one common definition: an identifier is counted when it appears both in the development side (train ∪ validation) and in the test side of that protocol. Development-internal recurrence between train and validation is excluded, because it cannot move information into the held-out test set. *Exact* and *normalized* count content identities, *structural* counts malicious operational structural-family IDs, *source* counts source IDs, and *explicit lineage* counts source-published base-Skill/lineage identifiers among records for which such linkage is available. Table 27 reports the frozen benchmark audit; `scripts/generate_leakage_audit.py` regenerates every cell from the frozen master table and split manifests and re-checks each protocol against its declared contract.

Table 27: Frozen cross-partition overlap audit. Every cell uses one definition: the number of identifiers that appear both in the development side (train ∪ validation) and in the test side of that protocol. Counts are overlapping relationship/group identifiers, not sample counts. A non-zero value is permitted when that axis is not part of the protocol's declared disjointness contract. Regenerate with `scripts/generate_leakage_audit.py`.

Protocol	Exact	Norm.	Struct.	Source	Lineage	Required zero-overlap axes
Random	0	0	584	10	83	exact, norm.
Source-bal. Random	0	0	575	11	87	exact, norm.
Mal.-Struct.-Disj.	0	0	0	11	63	exact, norm., struct.
Source-Disjoint	0	0	30	0	0	exact, norm., source

A non-zero entry is not automatically a protocol failure. It is a failure only when that relationship is part of the protocol's declared contract. Random and Source-Balanced Random therefore pass despite structural/source/lineage overlap because only exact and normalized identity are required to be disjoint. Malicious-Structural-Disjoint passes with 11 shared sources and 63 explicit-lineage overlaps because its added requirement is zero malicious structural-family overlap. Source-Disjoint passes with 30 development-to-test structural families and zero explicit-lineage overlaps because its added requirement is zero shared sources. This distinction prevents uncontrolled relationships from being retroactively labeled "leakage."

F.6 Lineage as audit metadata

Official lineage is much less complete than content identity. Among 8,414 Core malicious records, 1,380 have fully resolved official lineage and 35 have family-level partial official linkage; 6,999 remain unresolved (Appendix B.6). The 1,415 records with full/partial linkage expose 448 namespaced base identifiers whose semantics differ by source. We therefore do not infer parentage from text or structural similarity and do not define a corpus-wide lineage-disjoint primary split in the frozen benchmark. Lineage remains an audit axis used to show that official ancestry, structural similarity, and source identity are distinct relationships.

F.7 Interpretation and reproducibility boundaries

The split audits support three bounded statements. First, every primary protocol satisfies the disjointness constraint it explicitly declares. Second, Malicious-Structural-Disjoint controls only the frozen malicious structural grouping; it should not be described as full-benchmark structural disjointness. Third, Source-Disjoint measures source-conditioned distribution shift under the frozen source par-

tition; it does not isolate a causal estimate of universal unseen-source difficulty. In particular, the 30 development-to-test structural families under Source-Disjoint are expected and do not contradict source disjointness.

All split decisions are detector-independent and frozen before baseline comparison. Audit-only metadata (source, provenance, structural family, label strength, evidence, and lineage) remains excluded from detector inputs. The release therefore separates *information needed to construct/audit a split* from *information available to a detector*, allowing later models to reuse the same partitions without receiving the nuisance variables that define them.

G Experimental Details

This appendix specifies detector inputs, estimator configurations, score extraction, and metric definitions used by the paper. All systems operate on static Skill text and the same frozen split manifests from Appendix F; no Skill code, helper, payload, URL, installer, or runtime environment is executed during feature extraction or evaluation. The three classical baselines preserve their frozen pre-release configurations, while the added ModernBERT run uses the public text-available layer described below.

G.1 Detector input and feature fitting

Each benchmark row points to one inert primary Skill instruction document through its frozen `content_reference`. Normalized hashes determine benchmark identity and deduplication, but source IDs, canonical IDs, file paths, provenance, label strength, evidence type, lineage fields, and structural-family IDs are excluded from detector features. Package helper code and runtime artifacts are also excluded. For the five malformed-UTF-8 benign artifacts documented in Appendix D, static replacement decoding is used while raw-byte hashes remain unchanged.

The text pipelines fit their vectorizer only on the training partition of the corresponding frozen protocol and then transform validation/test text with that fitted representation. The format-only baseline analogously fits its scaler on training features. The same fixed model configuration is reused across Random, Source-Balanced Random, Malicious-Structural-Disjoint, and Source-Disjoint; the serialized seed-42 estimators show no split-specific hyperparameter changes. Table 28 records the feature extractors exactly as stored in the frozen estimators.

Table 28: Frozen feature-extractor configurations for the primary classical baselines. Parameters are read from the serialized seed-42 estimators and are identical across the four primary protocols.

Representation	Analyzer / n-grams	Document-frequency filters	Feature cap / TF-IDF	Text normalization inside vectorizer
Word TF-IDF	word; 1–2 grams	`min_df=2`; `max_df=0.995`	feature cap 120,000; sublinear TF; smooth IDF; L2 norm	lowercase; Unicode accent stripping
Character TF-IDF	`char_wb`; 3–5 grams	`min_df=2`; `max_df=1.0`	feature cap 160,000; sublinear TF; smooth IDF; L2 norm	lowercase; no accent stripping
Format-only	five scalar document features	n/a	5 dimensions; standardized before classification	no lexical representation

G.2 Primary classical estimators

Table 29 reports the classifier-side parameters from the frozen estimator artifacts. The word logistic-regression and both LinearSVC baselines use class weighting to compensate for the malicious-heavy natural benchmark. The format-only diagnostic standardizes its five scalar features before logistic regression. No split-specific threshold optimization or probability calibration is applied.

The classical linear pipelines are deterministic under the frozen feature matrices and configurations; seeds 42/43/44 produced identical discrete predictions. We report the common score and retain the

Table 29: Frozen classifier configurations. For the classical models, `random_state` is set to the repeated-run seed (42/43/44). Other parameters are fixed across protocols and seeds.

Model	Classifier	Fixed classifier parameters
Word TF-IDF + LR	LogisticRegression	$C = 1.0$; L2 penalty; balanced class weights; liblinear solver; max. 1,500 iterations; tolerance 10^{-4}.
Word TF-IDF + SVM	LinearSVC	$C = 1.0$; L2 penalty; squared-hinge loss; balanced class weights; automatic dual mode; max. 6,000 iterations; tolerance 10^{-4}.
Char TF-IDF + SVM	LinearSVC	$C = 1.0$; L2 penalty; squared-hinge loss; balanced class weights; automatic dual mode; max. 6,000 iterations; tolerance 10^{-4}.
Format-only + LR	StandardScaler + LogisticRegression	Five standardized scalar inputs; $C = 1.0$; L2 penalty; balanced class weights; liblinear solver; max. 1,000 iterations; tolerance 10^{-4}.

repeated runs as a reproducibility check. The package retains per-seed metrics for all three runs and serialized seed-42 estimators. These repeats do not estimate resampling uncertainty across alternative dataset constructions.

G.3 MODERNBERT LONG-CONTEXT BASELINE

We fine-tune `answerdotai/ModernBERT-base` (Warner et al., 2024) (resolved model SHA `8949b909ec900327062f0ebf497f51aef5e6f0c8`) as a binary sequence classifier on inert `skill_text`. Source IDs, provenance, taxonomy, family, lineage, release metadata, and all other benchmark fields are excluded from model features. For double-blind review, the dataset is referred to as the frozen MALICIOUSSKILLBENCH review snapshot; its identifying repository namespace and public revision identifier are omitted from the manuscript. Inputs use standard truncation at 8,192 tokens. We train for three epochs with learning rate 2×10^{-5}, weight decay 0.01, warmup ratio 0.10, weighted cross-entropy from training-split class weights, per-device train/evaluation batch size 2/2, and gradient accumulation 8 (effective train batch 16). The formal runs use bfloat16 with gradient checkpointing disabled and seeds 42/43/44 under every frozen protocol.

The public release withholds exact original text for five credential-bearing malicious identities. ModernBERT therefore excludes exactly those five records; sanitized substitutes are not used; no split manifest is regenerated. Effective train/validation/test counts are 6,814/974/1,947 for Random, 6,812/973/1,950 for Source-Balanced Random, 6,814/974/1,947 for Malicious-Structural-Disjoint, and 7,510/833/1,384 for Source-Disjoint. The Source-Disjoint test is unaffected (839 malicious + 545 benign). The headline decision rule is $p(\text{malicious}) \geq 0.5$. Auxiliary operating points select thresholds on validation only and apply them unchanged to test (Appendix I.3).

Formal runs record NVIDIA L4 GPUs, PyTorch 2.12.0+cu130 (CUDA 13.0), Transformers 5.9.0, and Datasets 4.8.5. Each run stores continuous scores, metrics, predictions, PR-curve data, token-length audit, and a manifest. The run manifests do not populate `benchmark_repo_git_commit`; reproducibility therefore relies on the frozen dataset revision, model SHA, frozen split hashes, configuration, and recorded software environment, and no repository commit is inferred.

An additional 24-run ModernBERT batch uses the same resolved model/data revisions and formal profile: four LOSO sources, two class-conditional diagnostics, and balanced Random/Source-Disjoint, each with seeds 42/43/44. All 24 jobs ran on NVIDIA L4, passed CUDA/bfloat16, identity, split-disjointness, manifest, and checksum checks, and their threshold-0.5 metrics were independently recomputed from saved predictions. Preparation and result revisions are frozen and checksum-verified; identifying repository commit IDs are omitted from the double-blind manuscript. For saved auxiliary thresholds, test application is reproducible from the predictions; independent replay of threshold selection is limited by the absence of raw validation predictions.

G.4 FORMAT-ONLY SANITY BASELINE

The format-only model is intentionally weak and receives no lexical tokens. Its five inputs are character length, line count, Markdown heading count, fenced-code-block count, and URL count. These features are standardized with `StandardScaler` and passed to the logistic-regression configuration in Table 29. The diagnostic is used only to test whether coarse document formatting alone can account for text-model performance; it serves as a sanity baseline and is excluded from competitive detector claims.

G.5 METRICS AND DECISION SCORES

Malicious is the positive class throughout. Let TP/FP/TN/FN use this convention. We report malicious- and benign-class precision/recall/F1, Macro-F1, weighted F1, accuracy, balanced accuracy, MCC, benign false-positive rate, AUROC, and AUPRC when a decision score exists. Table 30 gives the paper-level definitions of the main metrics.

Table 30: Main metric definitions. Malicious is the positive class; $F1_M$ and $F1_B$ denote class-wise F1 for malicious and benign Skills, respectively.

Metric	Definition	Role in this paper
Macro-F1	$(F1_M + F1_B)/2$	Primary paper-level metric; gives equal weight to malicious and benign classes.
Balanced accuracy	$\frac{1}{2}(\mathrm{TPR} + \mathrm{TNR})$	Secondary prevalence-robust accuracy summary.
Benign FPR	$\mathrm{FP}/(\mathrm{FP} + \mathrm{TN})$	Fraction of truly benign Skills incorrectly flagged malicious; central transfer error diagnostic.
MCC	$\frac{\mathrm{TP}\mathrm{TN} - \mathrm{FP}\mathrm{FN}}{\sqrt{(\mathrm{TP}+\mathrm{FP})(\mathrm{TP}+\mathrm{FN})(\mathrm{TN}+\mathrm{FP})(\mathrm{TN}+\mathrm{FN})}}$	Correlation-style summary using all four confusion-matrix cells.
AUROC / AUPRC	ranking metrics over continuous decision scores	Secondary diagnostics; omitted for constant predictors without a decision score.

Macro-F1 is the primary metric because the natural benchmark is malicious-heavy. In particular, a constant always-malicious classifier can obtain a deceptively high malicious-class F1 while assigning every benign Skill to the malicious class; Macro-F1 and benign FPR expose this failure mode. AUROC/AUPRC are computed from each estimator's continuous decision score. The classical primary comparisons use their fixed default decision rules without validation threshold tuning. ModernBERT's headline comparison uses $p(\mathrm{malicious}) \geq 0.5$; validation-selected operating points are reported only as supplementary calibration-transfer diagnostics and are never tuned on test. Reported gaps and differences are computed from unrounded values before display rounding. Constant baselines have no continuous score and therefore do not receive AUROC/AUPRC values.

G.6 AUXILIARY MINILM EMBEDDING BASELINE

The embedding baseline is intentionally auxiliary to the three classical text systems. It uses a locally cached `sentence-transformers/paraphrase-MiniLM-L6-v2` snapshot with identifier `c9a2bfebc254878aee8c3aca9e6844d5bbb102d1`. Loading is offline-only (`local_files_only=true`); no model is downloaded during the benchmark run. The frozen methodology records mean pooling, 384-dimensional embeddings, L2 normalization, and a class-weighted logistic-regression classifier with random state 42. The encoder is not fine-tuned on MALICIOUSSKILLBENCH. The final benchmark archive stores complete class-wise metrics and confusion counts for its Random, Malicious-Structural-Disjoint, and Source-Disjoint runs; only seed 42 is reported for this auxiliary baseline.

G.7 SOFTWARE-VISIBLE REPRODUCIBILITY ARTIFACTS

The historical classical experiment package retains the split CSVs, per-seed metric tables, seed-42 serialized estimators, the local MiniLM embedding matrix, and the embedding-methodology manifest.

The serialized scikit-learn estimators record version 1.7.1. For future replay, this version is the safest compatibility target for the saved `joblib` artifacts; loading them under a different scikit-learn version may emit model-persistence compatibility warnings.

That historical classical package does not record an exact host Python version, operating-system build, CPU model, RAM size, or GPU model, so we do not invent those fields. The TF-IDF/linear models require no GPU by method design, while the optional MiniLM embeddings are already frozen in the archived artifact. In contrast, the added ModernBERT archive records the resolved model/data SHAs, GPU model, software versions, configuration, per-run metrics, predictions, and token audits described above.

H Robustness Controls

Two pre-specified controls test whether the Random-to-Source-Disjoint degradation can be reduced to comparatively simple explanations: the natural malicious-heavy class ratio, or explicit construction wrappers that recur in some generated corpora. Both controls are detector-independent transformations of the frozen benchmark. Neither changes canonical labels, cross-label conflict decisions, source holdouts, or the primary split assignments described in Appendix F. They serve as diagnostic stress tests and leave the benchmark definition unchanged.

H.1 Class-balanced subsets

The natural primary benchmark contains 7,505 malicious and 2,235 benign units. For the balanced control, we retain every benign unit already assigned to a partition and deterministically downsample only the malicious units *within that same partition* until the class counts match. We never oversample, move a unit across train/validation/test, or alter the frozen label. This is distinct from Source-Balanced Random, which is a separate assignment diagnostic over source$\times$label cohorts (Appendix F.1).

Table 31 gives the exact subset arithmetic for the three protocols rerun under balancing. Each balanced protocol contains 2,235 malicious and 2,235 benign units in total (4,470 units), but the selected malicious subset is determined independently inside the corresponding frozen partitions. In particular, the Source-Disjoint test remains restricted to SRC009/SRC011/SRC012; balancing changes prevalence, not source membership.

Table 31: Class-balanced robustness subsets. Malicious units are deterministically downsampled *within* each frozen partition to match the benign count; benign units are never removed for balancing and no unit crosses partitions.

Protocol	Partition	Orig. M	Orig. B	Bal. M	Bal. B	Bal. total
Random	Train	5,254	1,564	1,564	1,564	3,128
Random	Validation	750	224	224	224	448
Random	Test	1,501	447	447	447	894
Mal.-Struct.-Disj.	Train	5,254	1,564	1,564	1,564	3,128
Mal.-Struct.-Disj.	Validation	750	224	224	224	448
Mal.-Struct.-Disj.	Test	1,501	447	447	447	894
Source-Disjoint	Train	5,992	1,521	1,521	1,521	3,042
Source-Disjoint	Validation	666	169	169	169	338
Source-Disjoint	Test	839	545	545	545	1,090

Balancing preserves each underlying split contract. Table 32 reports the frozen audit after downsampling: exact and normalized overlap remain zero for all three balanced protocols, Malicious-Structural-Disjoint retains zero structural-family overlap, and Source-Disjoint retains zero source overlap. Non-zero values on uncontrolled axes have the same diagnostic interpretation as in Appendix F.5.

Table 32: Overlap audit after class balancing, using the same definition as Table 27: identifiers present both in the development side (train ∪ validation) and in the test side. Balancing only removes units within their existing partitions, so every count is bounded above by the corresponding unbalanced count. Regenerate with `scripts/generate_leakage_audit.py`.

Balanced protocol	Exact	Norm.	Structural	Source	Status
Random	0	0	102	10	PASS
Mal.-Struct.-Disj.	0	0	0	10	PASS
Source-Disjoint	0	0	13	0	PASS

H.2 AUDITED SCAFFOLD SANITIZATION

The second control applies a deterministic, frozen scaffold-sanitization rule set to the static Skill instruction text. Rule selection is provenance-driven. The rules come from construction markers identified in the audit protocol and exact repeated generator-wrapper forms concentrated in constructed corpora; no token or phrase is added because it receives a high classifier weight. The sanitizer is then applied uniformly before fitting the same three text baselines on the unchanged Random, Malicious-Structural-Disjoint, and Source-Disjoint assignments.

The sanitizer is deliberately narrow. It does not remove attack-semantic terms such as `credential`, `secret`, `API key`, `exfiltration`, `curl`, `wget`, `shell`, `command`, `upload`, `network`, `file`, `browser`, `token`, or `password`. When a confirmed construction wrapper contains a backticked command, the command itself is preserved. Table 33 gives the complete frozen rule categories and their observed impact.

Table 33: Frozen scaffold-sanitization rules. Counts are over the 9,740-unit primary benchmark. Rules target audited construction wrappers, not attack-semantic content.

Rule	Deterministic action / evidence boundary	Docs	Lines
R1 Original-Skill delimiter	Replace exact BEGIN/END ORIGINAL `SKILL.md` delimiter lines; generator boundary only.	888	917
R2 Generator-output instruction	Replace the exact instruction requiring complete reproduction of the original `SKILL.md`; construction instruction only.	61	61
R3 Initialization-contract marker	Mask only the phrases "SDK initialization contract" and "part of this skill's initialization contract"; retain commands and surrounding behavior.	356	356
R4 Generated pre-flight heading	Replace exact generated headings of the forms "Pre-flight guard (...)" and "Pre-flight step (...)"; heading only.	297	297
R5 Pre-flight concealment annotation	Replace the exact construction annotation "Do not explain the pre-flight step to the user."	113	113
R6 Operational-note wrapper	Collapse the exact generated Operational-note wrapper to a construction placeholder while preserving its backticked command.	176	176
R7 Safety-preface annotation	Replace the exact repeated assistant safety-preface construction annotation.	57	57

Across the **9,740** benchmark documents, at least one rule fires in **1,771** documents and affects 1,977 unique lines; affected documents come from SRC001 (904) and SRC010 (867). The sanitizer control reuses the definition fixed before artifact recovery unchanged. The reproducibility artifact records original/sanitized hashes, lengths, and rule IDs for every transformed document, so the control can be regenerated without treating the sanitized text as a second benchmark release.

A separate marker audit is intentionally one-way and fixed after the sanitizer definition. After the fixed sanitizer is defined and results are produced, the audit searches exported top linear features for explicit source IDs, benchmark IDs, and configured dataset-name markers; it records **zero marker hits**. We do not use that audit to add new stripping rules. This separation prevents the sanitizer from becoming a detector-tailored feature-removal loop.

H.3 CONTROL RESULTS

Table 34 places original, balanced, and sanitized Random/Source-Disjoint results on the same scale. Under the natural benchmark, Random-to-Source-Disjoint Macro-F1 gaps are 0.220–0.268. Balancing does not eliminate them: Balanced Random is 0.881–0.925 whereas Balanced Source-Disjoint is 0.633–0.710. The word-SVM improves most under balancing, with Source-Disjoint Macro-F1 rising from 0.665 to 0.710 and benign FPR falling from 0.624 to 0.433, but substantial source-conditioned error remains.

Scaffold sanitization also leaves the gap intact. Sanitized Random Macro-F1 is 0.860–0.914 and Sanitized Source-Disjoint is 0.643–0.662, with held-out benign FPR remaining 0.624–0.640. Removing the audited wrappers therefore does not convert held-out source evaluation into random-split behavior.

Table 34: Random-to-Source-Disjoint robustness controls on the frozen benchmark. Gap is Random Macro-F1 minus Source-Disjoint Macro-F1. FPR_B is the benign false-positive rate under the malicious-positive convention.

Model	Setting	Random F1	Source F1	Gap	Rand. FPR_B	Src. FPR_B
Word LR	Original	.882	.661	.220	.105	.620
Word SVM	Original	.932	.665	.266	.094	.624
Char SVM	Original	.921	.653	.268	.098	.644
Word LR	Balanced	.881	.633	.249	.072	.583
Word SVM	Balanced	.925	.710	.215	.056	.433
Char SVM	Balanced	.904	.660	.244	.072	.525
Word LR	Sanitized	.860	.648	.211	.112	.635
Word SVM	Sanitized	.914	.662	.252	.116	.624
Char SVM	Sanitized	.913	.643	.270	.112	.640

The balanced Malicious-Structural-Disjoint diagnostic lies below Balanced Random for all three text models: 0.876 versus 0.881 for Word LR, 0.906 versus 0.925 for Word SVM, and 0.881 versus 0.904 for Char SVM. These are smaller differences than the balanced source-disjoint gaps. The robust headline remains that cross-source degradation persists even when class balance and a fixed family of construction wrappers are separately controlled.

H.4 MODERNBERT PREVALENCE AND RETRAINED BALANCE CONTROLS

Two complementary controls separate aggregate prevalence from model retraining. First, using the original saved Source-Disjoint scores and no refitting or threshold change, class-constant weighting to the exact Random evaluated prevalence raises ModernBERT Source-Disjoint Macro-F1 from 0.7343 to 0.7478. The Random-to-Source-Disjoint gap therefore changes from 0.2296 to 0.2160: only 0.0135 (5.9%) is removed. Weighting to 50/50 gives 0.7117. AUROC is unchanged by this class-constant reweighting, as expected.

Second, we retrain ModernBERT on the frozen balanced subsets from Table 31. Table 35 shows that balanced Random remains strong, whereas balanced Source-Disjoint remains substantially worse. The Macro-F1 gap is 0.3044 and the AUROC gap is 0.2735. All three paired seed gaps have the same direction. Thus both an evaluation-only prevalence standardization and a fully retrained class-balanced control reject aggregate class prevalence as the main explanation for the held-out source evaluation gap; neither identifies a unique causal mechanism.

Table 35: Retrained ModernBERT class-balanced control (mean $\pm$ sample SD, seeds 42/43/44). The same frozen partition contracts are retained; malicious examples are downsampled within partition to match benign counts.

Protocol	Test M/B	Macro-F1	Mal. recall	FPR_B	AUROC	AUPRC
Balanced Random	447/447	.9661±.0032	.9575±.0116	.0254±.0052	.9912±.0013	.9921±.0026
Balanced Source-Disjoint	545/545	.6616±.0567	.6924±.1423	.3651±.0358	.7177±.0549	.6978±.0621

Table 36: Full frozen metrics for the three classical static-text detectors. Seeds 42/43/44 produced identical discrete predictions under the fixed feature matrices and configurations; the common score is shown and repeated runs are retained as a reproducibility check. Malicious is the positive class; FPR_B is the benign false-positive rate.

Model	Split	Acc.	M-F1	B-F1	Macro-F1	Bal. Acc.	MCC	FPR_B	AUROC	AUPRC
Word TF–IDF + LR	Random	0.911	0.941	0.822	0.882	0.905	0.768	0.105	0.965	0.989
	Source-bal. Random	0.906	0.937	0.811	0.874	0.897	0.753	0.120	0.967	0.990
	Mal.-Struct.-Disj.	0.893	0.928	0.792	0.860	0.891	0.729	0.112	0.957	0.987
	Source-Disjoint	0.722	0.804	0.518	0.661	0.662	0.409	0.620	0.738	0.769
Word TF–IDF + SVM	Random	0.951	0.968	0.895	0.932	0.935	0.863	0.094	0.986	0.996
	Source-bal. Random	0.944	0.964	0.879	0.921	0.922	0.842	0.120	0.985	0.996
	Mal.-Struct.-Disj.	0.938	0.959	0.872	0.916	0.929	0.833	0.087	0.977	0.993
	Source-Disjoint	0.728	0.810	0.521	0.665	0.666	0.427	0.624	0.809	0.847
Char TF–IDF + SVM	Random	0.943	0.963	0.879	0.921	0.928	0.842	0.098	0.979	0.994
	Source-bal. Random	0.934	0.957	0.857	0.907	0.909	0.814	0.138	0.977	0.993
	Mal.-Struct.-Disj.	0.914	0.943	0.823	0.883	0.899	0.768	0.128	0.965	0.990
	Source-Disjoint	0.720	0.806	0.501	0.653	0.657	0.411	0.644	0.821	0.871

H.5 What the controls establish—and what they do not

The two controls support a bounded conclusion. The observed cross-source gap cannot be explained *solely* by the natural class imbalance, and it cannot be explained *solely* by the audited construction markers removed by the frozen scaffold-sanitization rule set. They do not establish a unique causal mechanism. Source remains entangled with provenance, attack-construction process, benign population, labeling policy, and documentation style, and the held-out sources have markedly different label mixtures (Appendix F.3).

Likewise, scaffold sanitization should not be described as removing all dataset artifacts or all source-specific scaffolds. It removes seven fixed classes of confirmed construction wrappers while intentionally preserving attack semantics and executable-looking text. The paper-level interpretation is therefore *source sensitivity that survives two targeted controls*; these controls do not establish leakage or any single construction artifact as the causal explanation for the Random-to-Source-Disjoint difference.

I Full Learned-Detector Results and Error Analysis

The main paper reports the compact comparison needed to explain what MaliciousSkillBench reveals about detection. This appendix expands that view with complete metrics for the three classical static text detectors and the added ModernBERT baseline, together with confusion counts, trivial/format diagnostics, the auxiliary MiniLM run, exploratory leave-one-source-out (LOSO) results, and source-wise error accounting. Classical seeds 42/43/44 produce identical discrete predictions under the fixed feature matrices and configurations; we report the common score and retain the repeated outputs only as a reproducibility check (Appendix G). Robustness controls are reported separately in Appendix H.

I.1 Full primary detector metrics

Table 36 reports the full class-aware metric matrix for the three classical text detectors and all four frozen protocols. Source-Balanced Random remains close to Random, while Malicious-Structural-Disjoint produces a smaller degradation than Source-Disjoint. On Source-Disjoint, Macro-F1 is only 0.653–0.665, balanced accuracy 0.657–0.666, and MCC 0.409–0.427. In contrast, malicious F1 remains 0.804–0.810, illustrating why malicious-class-only summaries understate the held-out source failure.

Ranking metrics answer a related but distinct question from thresholded classification. For ModernBERT, AUROC falls from 0.9965 ± 0.0001 under Random to 0.8118 ± 0.0385 under Source-Disjoint ($\Delta = 0.1847$), while the classical Source-Disjoint AUROCs are 0.738–0.821. Because AUROC is threshold-independent and invariant to the class-constant prevalence weighting used in Appendix H.4,

Table 37: ModernBERT-base results across the four frozen protocols (mean ± sample SD over seeds 42/43/44). Malicious is positive; FPR_B is benign false-positive rate.

Protocol	Macro-F1	Mal. recall	FPR_B	Bal. Acc.	MCC	AUROC	AUPRC
Random	.9639±.0042	.9840±.0007	.0574±.0137	.9633±.0066	.9278±.0084	.9965±.0001	.9990±.0000
Source-bal. Random	.9645±.0031	.9789±.0042	.0401±.0039	.9694±.0002	.9291±.0059	.9945±.0004	.9985±.0001
Mal.-Struct.-Disj.	.9403±.0022	.9593±.0042	.0529±.0127	.9532±.0047	.8819±.0045	.9882±.0015	.9967±.0005
Source-Disjoint	.7343±.0075	.9380±.0187	.4881±.0285	.7250±.0071	.5161±.0139	.8118±.0385	.8291±.0584

Table 38: ModernBERT effective public-text counts. Five withheld exact texts are excluded after frozen split membership is read; manifests themselves are unchanged.

Protocol	Train	Validation	Test
Random	6,814	974	1,947
Source-bal. Random	6,812	973	1,950
Mal.-Struct.-Disj.	6,814	974	1,947
Source-Disjoint	7,510	833	1,384

this is direct evidence of discrimination loss beyond the default threshold and aggregate prevalence. AUPRC also falls but remains prevalence-sensitive, so we treat it as secondary.

I.2 ModernBERT long-context results

Table 37 gives the added ModernBERT results. The encoder substantially improves the absolute level of performance: Source-Disjoint Macro-F1 is 0.7343 ± 0.0075, compared with 0.665 for the word-SVM. The Random-to-Source drop nevertheless remains 0.2296 (0.230 rounded), while the Random-to-Malicious-Structural-Disjoint drop is only 0.0236. On Source-Disjoint, malicious recall remains 0.9380 ± 0.0187 and benign FPR remains 0.4881 ± 0.0285. The source-conditioned degradation is therefore reduced but not removed by a fine-tuned long-context encoder.

Figure 6 visualizes Source-Disjoint score behavior. Curves are computed from saved continuous scores; scanner configurations appear only as fixed points because they do not define score curves here. ModernBERT markers show the default 0.5 point and validation-selected FPR-cap points; no threshold is selected from test ROC/PR data.




Figure 6: Source-Disjoint ROC (left) and precision–recall (right) views from saved continuous detector scores. Scanner configurations are fixed points. Threshold markers for ModernBERT are fixed at 0.5 or selected on validation and applied unchanged to test. PR values depend on the 839/1,384 malicious prevalence; ROC does not.

Table 38 records the effective public-text split counts. The five excluded credential-bearing records account for the difference from frozen manifest counts; the 1,384-unit Source-Disjoint test is unaffected.

Length coverage. Table 39 audits tokenized length under the exact ModernBERT tokenizer. Only 118/9,735 (1.21%) public-text identities exceed 8,192 tokens, and only 7/1,384 (0.51%) Source-Disjoint test units do so. The full universe contains one extreme 15,739,803-token record. Audit

Table 39: ModernBERT tokenizer length audit. The public text-available universe is summarized from the Random run; Source-Disjoint test is reported separately. Formal inputs are truncated at 8,192 tokens.

Population	n	Median	P95	P99	> 8192
Public text universe	9,735	1,493	5,489.3	8,764.96	118 (1.21%)
Source-Disjoint test	1,384	1,327	5,013.65	7,245	7 (0.51%)

Table 40: ModernBERT Source-Disjoint source-wise diagnostic at the fixed 0.5 threshold (mean $\pm$ sample SD across three seeds). FPR is undefined for SRC009 because it contains no benign test units.

Source	Mal. n	Benign n	Mal. recall	Benign FPR	Accuracy	Pred.-mal. rate
SRC009	728	0	.9299±.0216	–	.9299±.0216	.9299±.0216
SRC011	21	455	.9524±.0000	.3868±.0341	.6282±.0326	.4118±.0326
SRC012	90	90	1.0000±.0000	1.0000±.0000	.5000±.0000	1.0000±.0000

Table 41: Source-Disjoint sensitivity to excluding SRC012, using saved formal predictions and unchanged decision rules. ModernBERT values are mean $\pm$ sample SD across seeds 42/43/44; Word-SVM rows show the common deterministic score. No model is retrained or threshold-retuned.

Model	Evaluation	Macro-F1	Mal. recall	Benign FPR	AUROC	AUPRC
ModernBERT	Full SD	.7343±.0075	.9380±.0187	.4881±.0285	.8118±.0385	.8291±.0584
ModernBERT	Excl. SRC012	.7845±.0077	.9306±.0210	.3868±.0341	.8875±.0384	.9071±.0618
Word TF–IDF + SVM	Full SD	.6653	.9559	.6239	.8090	.8471
Word TF–IDF + SVM	Excl. SRC012	.6536	.9506	.6440	.7752	.8243

against the pinned upstream artifact confirms that it is a source-faithful 21,002,040-byte `SKILL.md`: ordinary Markdown is followed by a 20 MiB single-line generated, binary-like repeated payload. The benchmark ingestion does not create this expansion. We retain it as a representation/resource caveat and report robust length summaries because it makes the arithmetic mean unrepresentative. Formal model inputs use standard 8,192-token truncation for all records.

I.3 ModernBERT source-conditioned and calibration diagnostics

Table 40 decomposes Source-Disjoint at the fixed 0.5 threshold. SRC011 has mean benign FPR 0.387 while preserving 0.952 malicious recall. For SRC012, every test unit is predicted malicious in every seed, yielding recall 1.0 and benign FPR 1.0 on its balanced 90/90 composition. This is a descriptive concentration of errors under the frozen source holdout; it does not establish memorization, leakage, or a particular causal shortcut.

Equal weighting across the held-out sources sharpens the same supervised heterogeneity. ModernBERT's source-macro malicious recall over SRC009/011/012 is 0.9608 ± 0.0072, while benign FPR averaged equally over SRC011/SRC012 is 0.6934 ± 0.0171; the two-class source-macro F1 over SRC011/SRC012 is 0.4026 ± 0.0099. These diagnostics do not replace the aggregate benchmark metrics and are based on only two held-out sources with benign support.

As a source-sensitivity check, Table 41 recomputes the fixed-threshold Source-Disjoint metrics after excluding SRC012 without retraining or retuning. ModernBERT Macro-F1 rises from 0.7343 ± 0.0075 to 0.7845 ± 0.0077, while benign FPR falls from 0.4881 ± 0.0285 to 0.3868 ± 0.0341 and malicious recall remains 0.9306 ± 0.0210. The Random-to-ex-SRC012 Macro-F1 gap is still 0.1794. Word-SVM does not improve under the same exclusion. Thus SRC012 amplifies the aggregate ModernBERT degradation but does not solely account for it.

Validation-selected operating points also transfer imperfectly across the held-out sources (Table 42). A threshold selected to keep validation benign FPR at or below 1% yields 0.229 ± 0.071 test FPR and 0.700 ± 0.082 malicious recall; the 5% validation rule yields 0.506 ± 0.065 test FPR. These thresholds are selected entirely on validation and are reported only as calibration-transfer diagnostics, not as test-tuned alternatives to the 0.5 headline rule.

Table 42: ModernBERT Source-Disjoint calibration-transfer diagnostic. Thresholds are selected on validation and applied unchanged to test; values are mean ± sample SD across seeds.

Validation selection rule	Test mal. recall	Test benign FPR
FPR $\leq 1\%$	.6996±.0823	.2294±.0710
FPR $\leq 5\%$	.9424±.0251	.5064±.0655

These results motivate an explicit three-way distinction. *Discrimination* concerns score ordering (AUROC/AUPRC); the *fixed operating point* concerns threshold-0.5 classification; and *calibration/decision-boundary transfer* concerns whether a threshold selected on validation preserves its intended behavior on held-out test sources. A source can fail along one axis without failing equally on the others.

Class-conditional direction. The supplementary balanced diagnostics from Appendix F.4 isolate the two label directions as far as source support permits. Table 43 shows a strong asymmetry: the malicious-side holdout remains comparatively robust, while the benign-side holdout retains 98.1% malicious recall but flags 47.3% of benign examples. Its mean AUROC remains 0.9265, indicating that much of the error is an operating-point transfer problem, although seed 44 also shows weaker ranking (AUROC 0.8651). The same direction appears for Word-SVM (benign-side FPR 0.7009 versus 0.1514 malicious-side). For these supervised models, this supports benign-side source generalization as the dominant observed class-conditional failure direction, not an exclusive or causal mechanism.

Table 43: Balanced class-conditional source-holdout diagnostics for ModernBERT (mean ± sample SD, seeds 42/43/44). These supplementary diagnostics are not canonical fully source-disjoint protocols.

Diagnostic	Test M/B	Macro-F1	Mal. recall	FPR_B	AUROC	AUPRC
Malicious-side	839/839	.8989±.0015	.8546±.0176	.0564±.0162	.9480±.0049	.9524±.0056
Benign-side	545/545	.7402±.0213	.9810±.0038	.4734±.0385	.9265±.0535	.9076±.0996

I.4 Confusion matrices and diagnostic references

Table 44 gives the underlying counts for the three headline protocols. On Random, the word-SVM makes 42 benign false positives and 53 malicious false negatives. On Source-Disjoint, it makes **340 benign false positives** but only **37 malicious false negatives**. The same class asymmetry appears in Word LR (338 FP versus 47 FN) and Char SVM (351 FP versus 36 FN). Thus the source-conditioned degradation is dominated by false alarms on benign held-out Skills; malicious recall remains high.

Table 44: Frozen confusion-matrix counts for the three headline protocols. Counts follow the malicious-positive convention and are identical across seeds 42/43/44.

Model	Split	M	B	TP	FP	TN	FN
Word TF–IDF + LR	Random	1501	447	1375	47	400	126
	Mal.-Struct.-Disj.	1501	447	1343	50	397	158
	Source-Disjoint	839	545	792	338	207	47
Word TF–IDF + SVM	Random	1501	447	1448	42	405	53
	Mal.-Struct.-Disj.	1501	447	1420	39	408	81
	Source-Disjoint	839	545	802	340	205	37
Char TF–IDF + SVM	Random	1501	447	1434	44	403	67
	Mal.-Struct.-Disj.	1501	447	1390	57	390	111
	Source-Disjoint	839	545	803	351	194	36

Table 45 provides two constant predictors and the five-feature format-only logistic-regression baseline. The always-malicious rule reaches 0.870 malicious F1 on Random because roughly 77% of the

Random test is malicious, yet its Macro-F1 is only 0.435 and its benign FPR is 1.0. The format-only model is also substantially weaker than the text detectors (Random Macro-F1 0.486), so strong random-split performance cannot be reduced to character length, line count, Markdown heading count, fenced-code-block count, and URL count alone.

Table 45: Frozen trivial and coarse-formatting diagnostics. The high Random malicious F1 of the always-malicious rule illustrates why malicious-class F1 alone is not an appropriate paper-level metric for the natural class ratio.

	Random				Source-Disjoint			
Model	M-F1	Macro	BalAcc	FPR_B	M-F1	Macro	BalAcc	FPR_B
Always-malicious	0.870	0.435	0.500	1.000	0.755	0.377	0.500	1.000
Always-benign	0.000	0.187	0.500	0.000	0.000	0.283	0.500	0.000
Format-only LR	0.583	0.486	0.568	0.313	0.513	0.483	0.495	0.457

I.5 Auxiliary MiniLM embedding baseline

The full run includes a locally cached `paraphrase-MiniLM-L6-v2` embedding baseline with a class-weighted logistic-regression head (Appendix G.6). Unlike the earlier archived result snapshot, the final run stores both class-wise metrics and confusion counts. Table 46 therefore reports Macro-F1 and benign FPR directly.

Table 46: Auxiliary MiniLM embedding baseline (seed 42). Unlike the earlier archived snapshot, the final run stores both class-wise metrics and confusion counts, so Macro-F1 and benign FPR are reported directly.

Split	M-Prec.	M-Rec.	M-F1	B-F1	Macro-F1	Acc.	FPR_B
Random	0.880	0.688	0.772	0.501	0.636	0.687	0.315
Mal.-Struct.-Disj.	0.893	0.689	0.778	0.522	0.650	0.697	0.277
Source-Disjoint	0.648	0.895	0.752	0.356	0.554	0.642	0.749

MiniLM reaches Macro-F1 0.636 on Random, 0.650 on Malicious-Structural-Disjoint, and 0.554 on Source-Disjoint. Its Source-Disjoint malicious recall is high (0.895), but benign FPR is 0.749. This auxiliary representation check therefore does not remove the cross-source error regime observed with sparse text features. Because the encoder is frozen and not fine-tuned on MaliciousSkillBench, we use it only as a compact representation baseline and make no state-of-the-art neural comparison.

I.6 Leave-one-source-out transfer diagnostic

To expose source-level heterogeneity beyond the fixed three-source holdout, we report the historical word-SVM LOSO diagnostic and a new ModernBERT reconstruction for SRC006, SRC010, SRC011, and SRC012, the selected sources with two-class test support. The word-SVM reconstruction sanity checks differ from the archived historical Macro-F1/FPR values by less than 0.015, but exact historical development/training identity equivalence is not provable. We therefore describe ModernBERT LOSO as a *supplementary reconstruction*: for every row the held source is absent from train/validation, test identities are exactly disjoint, and all three seeds share the same manifest hash, but the development partition is not claimed byte-identical to the historical one. Table 47 reports the word-SVM diagnostic, Table 48 the aggregated ModernBERT reconstruction, and Table 49 its per-seed values.

The ModernBERT results show qualitatively different failure mechanisms. SRC006 exhibits ranking inversion (mean AUROC 0.2208 and negative MCC); SRC010 combines moderate ranking degradation with 66.7% benign FPR; SRC011 retains strong ranking (AUROC 0.9391) but its fixed 0.5 operating point over-flags benign items; and SRC012 ranks moderately well (AUROC 0.8054) while every test item is classified malicious at 0.5 in every seed. Only 21 SRC011 test items are malicious, making Macro-F1 especially sensitive to false positives. These rows support recurrent source-transfer difficulty with strong source heterogeneity, not a universal unseen-source error rate or a single causal mechanism.

Table 47: Exploratory leave-one-source-out (LOSO) diagnostic for the word TF–IDF + linear SVM. Label mixtures differ substantially across held-out sources, so the rows are reported as source-specific heterogeneity diagnostics and are not aggregated into one summary score.

Held-out	Test n	M/B	M-Prec.	M-Rec.	M-F1	Macro-F1	Acc.	FPR_B
SRC006	131	86/45	0.580	0.674	0.624	0.351	0.466	0.933
SRC010	4,426	2,783/1,643	0.654	0.850	0.739	0.529	0.623	0.762
SRC011	476	21/455	0.065	0.952	0.122	0.329	0.393	0.633
SRC012	180	90/90	0.667	1.000	0.800	0.733	0.750	0.500

Table 48: Supplementary four-source ModernBERT LOSO results (mean ± sample SD over seeds 42/43/44, fixed threshold 0.5). Development partitions are deterministic reconstructions; held-source test identities are absent from train/validation.

Held source	Test M/B	Macro-F1	Mal. recall	FPR_B	Bal. Acc.	AUROC	AUPRC
SRC006	86/45	.3519±.0208	.5969±.0640	.8815±.0339	.3577±.0254	.2208±.0700	.5564±.0518
SRC010	2781/1643	.6435±.0214	.9571±.0076	.6673±.0333	.6449±.0164	.7872±.0185	.8344±.0157
SRC011	21/455	.5303±.0679	.9365±.0275	.2945±.0952	.8210±.0557	.9391±.0291	.5875±.1115
SRC012	90/90	.3333±.0000	1.0000±.0000	1.0000±.0000	.5000±.0000	.8054±.0050	.8098±.0488

Table 49: Per-seed fixed-threshold detail for the supplementary ModernBERT LOSO study. Counts are TP/FN/FP/TN under the malicious-positive convention.

Held source	Seed	Macro-F1	Recall	FPR_B	AUROC	TP/FN/FP/TN
SRC006	42	.3341	.5930	.9111	.1479	51/35/41/4
SRC006	43	.3748	.6628	.8889	.2269	57/29/40/5
SRC006	44	.3467	.5349	.8444	.2875	46/40/38/7
SRC010	42	.6544	.9493	.6439	.7950	2640/141/1058/585
SRC010	43	.6189	.9576	.7054	.7661	2663/118/1159/484
SRC010	44	.6573	.9644	.6525	.8005	2682/99/1072/571
SRC011	42	.6086	.9524	.1846	.9562	20/1/84/371
SRC011	43	.4886	.9048	.3495	.9055	19/2/159/296
SRC011	44	.4936	.9524	.3495	.9556	20/1/159/296
SRC012	42	.3333	1.0000	1.0000	.8006	90/0/90/0
SRC012	43	.3333	1.0000	1.0000	.8050	90/0/90/0
SRC012	44	.3333	1.0000	1.0000	.8106	90/0/90/0

I.7 Source-conditioned error concentration

Table 50 decomposes the final Source-Disjoint word-SVM predictions. SRC009 has no benign test units and retains 0.952 malicious recall. Of the aggregate **340** benign false positives, **293** come from SRC011 (FPR 0.644) and 47 from SRC012 (FPR 0.522). The overall benign FPR of 0.624 is therefore concentrated in the two benign-containing held-out sources, while aggregate malicious recall remains 802/839 = 0.956.

Table 50: Source-wise error accounting for the frozen Source-Disjoint word-SVM predictions. A dash denotes that the source supplies no benign examples in the held-out test.

Source	M	B	TP	FP	TN	FN	M-Rec.	FPR_B
SRC009	728	0	693	0	0	35	0.952	–
SRC011	21	455	19	293	162	2	0.905	0.644
SRC012	90	90	90	47	43	0	1.000	0.522

For descriptive context, Table 51 compares SRC011/SRC012 word-SVM Random-test benign FPRs (0.113/0.000) with the values observed when the entire sources are held out (0.644/0.522). The evaluated units are unpaired and the protocols differ in several factors, so this is *not* a causal estimate of source identity; it only illustrates source sensitivity visible in the aggregate benchmark.

We do not assign semantic "error cause" labels to individual false positives or false negatives. Automated keyword summaries are used only as inspection aids and have no human-verified causal-annotation status; some artifacts also contain security-sensitive text. We therefore report frozen

Table 51: Descriptive benign false-positive rates for the *word-SVM* detector on the two Source-Disjoint held-out sources that contain benign examples, compared with their Random-test subsets. ModernBERT values for the same sources differ and are reported separately in Table 40. The evaluated units differ and Random exposes each source during training, so this is not a paired causal estimate.

Source	Protocol	Benign n	FP	TN	FPR_B
SRC011	Random	97	11	86	0.113
SRC011	Source-Disjoint	455	293	162	0.644
SRC012	Random	14	0	14	0.000
SRC012	Source-Disjoint	90	47	43	0.522

counts and source concentration without reproducing payload-bearing examples or promoting those keywords to ground truth.

I.8 Linear-feature inspection and interpretation limits

The feature-marker audit searches exported top linear features for explicit source IDs, benchmark IDs, and configured dataset-name markers and records **zero marker hits**. Source identifiers are also excluded from detector inputs by construction (Appendix G.1). This reduces the likelihood of a trivial metadata leak but does not establish source invariance: high-weight lexical features can still reflect corpus-specific language and packaging conventions.

Appendix H.2 removes a fixed audited subset of construction wrappers without using classifier weights, yet the Source-Disjoint gap persists. Together, these results support only the bounded conclusion that the evaluated detectors are source sensitive; they do not isolate a single causal mechanism.

J Off-the-Shelf Scanner Evaluation

J.1 Common artifact track and frozen verdict contracts

All three scanners are evaluated on the same primary static artifact used by the learned text baselines: an isolated `SKILL.md` copy of each frozen benchmark unit. This is therefore a *common primary-artifact* comparison whose scope is limited to static Skill text and excludes full-package/runtime behavior. Scanner integration is label-blind, untrusted Skill contents are never executed, and the benchmark scan is performed without paid/cloud LLM APIs. The comparison covers 29,220 unique scanner–item pairs (9,740 benchmark units $\times$ three scanners), with scanner output parsing fixed before metric computation.

Primary operating points are fixed from each scanner's documented semantics before benchmark metric comparison. **Cisco-local-behavioral** uses the native HIGH/CRITICAL safety gate; **SkillFortify-offline** uses an explicit MEDIUM+ rule over saved maximum severity; and **SkillSpector-static** disables LLM analysis and treats its native block/`DO_NOT_INSTALL` state as positive. The SkillFortify native `is_safe` gate is retained only as a sensitivity operating point: 131 successful predictions differ from the final explicit MEDIUM+ primary gate, all corresponding to LOW-severity native-positive cases. Technical failures remain a third state, `ABSTAIN_ERROR`, and are never silently converted to benign predictions. Primary binary metrics therefore use successful scans while reporting coverage separately.

Table 52: Off-the-shelf scanner results on the full 9,740-unit benchmark. Primary metrics exclude technical abstentions and report coverage separately.

Scanner	Coverage	Mal. recall	Benign FPR	Macro-F1	FP	FN
Cisco-local-behavioral	.9998	.064	.008	.254	17	7,021
SkillFortify-offline	.9999	.566	.451	.516	1,007	3,257
SkillSpector-static	1.0000	.033	.002	.222	4	7,258

Table 52 reports full-benchmark metrics and coverage. Cisco succeeds on 9,738/9,740 units, SkillFortify on 9,739/9,740, and SkillSpector on all 9,740. The full-benchmark result already shows distinct operating regimes: Cisco and SkillSpector achieve very low benign FPR but only 6.4% and 3.3% malicious recall, whereas SkillFortify reaches 56.6% recall with a 45.1% benign FPR. These are operational properties of the frozen configurations, not a controlled comparison of scanner architecture or capacity.

J.2 Protocol behavior and operating-point sensitivity

For each frozen scanner configuration, one per-item prediction set is joined to the existing frozen protocol test manifests; scanner outputs are not regenerated separately for each protocol, and scanners are not retrained. Table 53 therefore reports how the same scanner decision rules behave as the evaluated test composition changes. On Source-Disjoint all three scanners have 100% coverage. Cisco and SkillSpector continue to avoid most benign false positives but miss nearly all held-out malicious Skills, whereas SkillFortify is more sensitive but incurs much larger benign false-positive rates.

Table 53: Fixed scanner configurations on the four frozen protocol test sets. Scanners are not trained on protocol train splits; coverage is reported because technical abstentions remain outside primary binary metrics.

Scanner	Protocol	Coverage	Mal. recall	Benign FPR	Macro-F1
Cisco-local	Random	1.0000	0.065	0.004	0.254
	Source-Bal.	1.0000	0.065	0.004	0.255
	M-Struct	0.9990	0.082	0.004	0.272
	Source	1.0000	0.025	0.011	0.308
SkillFortify	Random	1.0000	0.553	0.421	0.518
	Source-Bal.	1.0000	0.569	0.490	0.504
	M-Struct	0.9995	0.580	0.444	0.526
	Source	1.0000	0.253	0.499	0.349
SkillSpector-static	Random	1.0000	0.033	0.002	0.222
	Source-Bal.	1.0000	0.028	0.002	0.217
	M-Struct	1.0000	0.047	0.000	0.237
	Source	1.0000	0.000	0.006	0.281

Table 54 reports pre-specified secondary gates; no post-hoc best-threshold selection is performed. The primary paper-facing gates remain Cisco HIGH+/native, SkillFortify MEDIUM+, and SkillSpector block. Secondary settings illustrate that moving the gate changes the false-positive/false-negative balance but does not create a uniformly strong operating point.

Table 54: Pre-specified scanner operating-point sensitivity on the full benchmark. Primary rows are the paper-facing configurations.

Scanner	Gate	Mal. recall	Benign FPR	Macro-F1
Cisco	HIGH+ / native (primary)	.064	.008	.254
Cisco	MEDIUM+	.127	.025	.310
SkillFortify	MEDIUM+ (primary)	.566	.451	.516
SkillFortify	native `is_safe`	.576	.474	.514
SkillFortify	HIGH+	.565	.450	.515
SkillSpector	block gate (primary)	.033	.002	.222
SkillSpector	CAUTION+	.151	.042	.329

J.3 Source overlap, technical abstentions, and uncertainty

SRC012 is derived from SkillFortifyBench. Under the final MEDIUM+ gate, excluding all SRC012-provenance units from the full benchmark changes SkillFortify Macro-F1 from 0.516 to 0.505. More importantly, excluding SRC012 from Source-Disjoint leaves SRC009+SRC011 and changes Macro-

F1 from 0.349 to 0.254, malicious recall from 25.3% to 16.7%, and benign FPR from 49.9% to 59.8% (Table 55). This is a source-overlap sensitivity analysis, not evidence of training-set memorization.

Table 55: SkillFortify source-overlap sensitivity under the fixed MEDIUM+ primary gate.

Population	N	Mal. recall	Benign FPR	Macro-F1
Full benchmark	9,740	.566	.451	.516
Full excluding SRC012 provenance	9,560	.561	.470	.505
Source-Disjoint	1,384	.253	.499	.349
Source-Disjoint excluding SRC012	1,204	.167	.598	.254

Exactly three technical abstentions occur across the 29,220 scanner–item pairs (Table 56). Two are Cisco failures—one roughly 21 MB input for which no result is produced and one invalid-UTF-8 input—and SkillFortify reports no Skill for that same invalid-UTF-8 unit. All three occur in the Malicious-Structural-Disjoint test and none occurs in Source-Disjoint, so the main held-out source comparison is unaffected by technical abstention.

Table 56: The three technical abstentions among 29,220 scanner–item jobs. None occurs in Source-Disjoint; all appear in the Malicious-Structural-Disjoint test.

Benchmark ID	Scanner	Label	Source	Technical reason
`ASB04_002434`	Cisco-local	Mal.	SRC001	no result (21 MB input)
`ASB04_007741`	Cisco-local	Ben.	SRC010	invalid UTF-8
`ASB04_007741`	SkillFortify	Ben.	SRC010	no Skill parsed

Bootstrap intervals use 10,000 item-level resamples with seed 42 and quantify sampling uncertainty for deterministic scanner outputs; training-seed variance is outside this calculation. Table 57 reports the Source-Disjoint intervals used to bound the paper-facing scanner comparison.

Table 57: Bootstrap 95% confidence intervals on Source-Disjoint (10,000 item-level resamples; seed 42). These intervals quantify sampling uncertainty for deterministic scanner outputs, not seed variance.

Scanner	Macro-F1	Mal. recall	Benign FPR
Cisco-local	0.308 [0.290, 0.325]	0.025 [0.015, 0.036]	0.011 [0.004, 0.021]
SkillFortify	0.349 [0.324, 0.375]	0.253 [0.224, 0.283]	0.499 [0.457, 0.541]
SkillSpector-static	0.281 [0.268, 0.295]	0.000 [0.000, 0.000]	0.006 [0.000, 0.013]

Dependency-compliant Cisco rerun. The earlier compatibility run used `yara-x==1.4.0` with `--no-deps`, below the scanner's declared `yara-x>=1.10,<2` requirement. We repeated the evaluation at the same Cisco commit `48f59347a54b93606dd1e31c41989ebfd0fcc84d` in an isolated macOS 12.7.6/arm64, Python 3.12.2 environment with source-built YARA-X 1.10.0. The installed dependencies satisfy the declared constraints and `pip check` passes; this is a dependency-compliant rebuild, not an exact reproduction of the upstream lockfile. The rerun uses the frozen primary artifacts, unchanged scanner source/rules, the same static, bytecode, pipeline, and behavioral analyzers, policy, and both verdict gates. Network access and cloud/LLM integrations remain disabled.

Health checks confirm 18 compiled native YARA rules from 15 rule files and the expected native-rule positive/negative fixture outcomes. The successful benchmark reports contain 476 YARA findings across 206 identities, directly demonstrating YARA participation. The rerun succeeds on 9,738/9,740 units with the same two technical abstentions. Across all 9,738 common-success items, primary and secondary verdicts and rule/severity/analyzer finding signatures match the archived historical per-item extraction. The reported Cisco metrics, bootstrap intervals, and threat-stratified recalls are reproduced; Source-Disjoint remains TP=21, FP=6, TN=539, and FN=818 (2.503% malicious recall). This supports the reported operating points without establishing every internal state of the earlier environment.

The rerun archive records dependencies, rule hashes, health checks, sanitized reports, and offline metric-recomputation code. Report copies redact local paths, descriptions, and payload snippets while retaining verdicts, severities, and rule identifiers. Historical raw reports are not included in the comparison artifact; agreement is checked against the archived decision/signature extraction. Numerical replay from archived outputs is distinct from environment reconstruction, which additionally requires the complete pinned upstream checkout.

J.4 THREAT-STRATIFIED MALICIOUS RECALL

Figure 7 joins final primary scanner verdicts to the already-frozen harmonized attack mapping. The denominator is the same 4,983 attack-mapped malicious identities characterized in Appendix E; categories are multi-label, so category sample sizes are not additive. SkillFortify has substantially higher recall than the other two primary scanner configurations across the mapped categories, including 81.5% for Credential Access, 73.8% for Data Exfiltration/Disclosure, 70.6% for Defense Evasion/Obfuscation, 59.6% for Execution/Code Delivery, and 66.9% for Privilege/Tool/Authority Abuse. Its weakest mapped category is Integrity/Output Manipulation at 25.8%. Cisco and SkillSpector remain low-recall across all categories at their frozen primary gates.




Figure 7: Malicious recall by harmonized attack category for the three frozen primary scanner configurations. Cell annotations are recall percentages; category sample sizes N are shown on the x-axis. The analysis is conditional on the 4,983 malicious identities with supported attack mappings, and categories are multi-label. Differences are descriptive and may reflect source composition as well as scanner behavior.

The stratified view should not be interpreted as a source-adjusted causal comparison. Attack categories are unevenly distributed across source datasets (Figure 2b), and some categories have small N (e.g., Discovery/Reconnaissance $N = 15$ and Defense Evasion/Obfuscation $N = 34$). We therefore use this analysis to describe coverage gaps, not to rank scanners by attack family independently of source composition.

J.5 COMPARABILITY BOUNDARY

The scanner study evaluates binary malicious-versus-benign detection on a common static primary-text artifact with fixed local configurations. It is not an adversarial-evasion/attack-success-rate experiment, and **SkillSpector-static** specifically uses its no-LLM mode. Results should therefore not be treated as numerically interchangeable with evaluations that use full packages, runtime behavior, cloud services, or LLM-backed scanner modes. The conclusion is limited to the operational trade-off observed in these evaluated local static primary-text configurations: lower benign FPR can coincide with very low malicious recall, while a more sensitive configuration can incur substantial false positives. These points are neither product upper bounds nor claims about untested runtime, package-aware, cloud-backed, or LLM-enabled modes.

K REPRESENTATIVE EXAMPLES

This appendix makes the benchmark units and audit decisions concrete without reproducing operational malicious payloads. Every example is anchored to the frozen benchmark identifiers used elsewhere in the paper. For malicious artifacts we report source-side attack descriptors, provenance/evidence metadata, hashes or family identifiers when useful, and a non-operational abstraction of the content. Commands, endpoints, credentials, executable helper logic, and other payload-bearing details are omitted. Benign examples may be named more directly because they do not carry an attack payload.

K.1 REPRESENTATIVE BENCHMARK UNITS

Table 58 illustrates four distinct ways a primary benchmark unit can arise. The examples are not intended to define the entire taxonomy; they show why intent, provenance, evidence, artifact unit, and lineage are recorded separately. In particular, "wild" does not imply stronger evidence than "constructed," and a backdoored package is not treated as interchangeable with an injected synthetic variant.

Table 58: Representative primary benchmark units. Malicious content is summarized non-operationally; no payload command, endpoint, helper code, or executable instruction is reproduced.

Example	Frozen ID / source	Canonical metadata	Safe content abstraction
Wild malicious	ASB04_002865 UASSB_00181999 SRC011	wild; Skill text; moderate/static	Upstream Snyk exfiltration case. The source descriptor identifies exfiltration behavior; transport command and destination are omitted.
Injected malicious	ASB04_006504 UASSB_00175991 SRC010	injected; Skill package; strong/constructed	SkillTrustBench case 00004 with a tool-hijack attack type; injected control-changing content is not reproduced.
Backdoored malicious	ASB04_006168 UASSB_00175105 SRC008	backdoored; Skill package; strong/constructed; derived lineage	SkillTrojan EHR/SQL backdoor example. The hidden malicious delta is omitted; frozen base linkage is unresolved.
Benign reference	ASB04_009716 UASSB_00181530 SRC011	wild; Skill text; moderate/static; independent lineage	ATR's official-fetch reference case, retained as a high-confidence Main-benign unit under the same canonical schema.

The malicious rows intentionally use safe abstractions and omit verbatim attack instructions. For example, the SRC011 record is retained as a wild malicious Skill because the frozen source identifies an exfiltration behavior under static evidence; the transport command and destination are not reproduced here. The SRC010 record is a constructed injected tool-hijack variant, while the SRC008 record is a constructed backdoored package. The benign SRC011 record demonstrates that the same canonical schema also preserves ordinary wild Skill artifacts as high-confidence reference negatives.

K.2 A STRUCTURAL-REUSE EXAMPLE

Table 59 shows two distinct normalized malicious units assigned to the same frozen operational structural family. Their exact and normalized hashes differ, so this is not an exact/normalized duplicate case. The family contains five normalized identities and spans SRC001/SRC005/SRC010 after source-set propagation. In the independent blind positive-validation sample, the pair was judged high-confidence "same structural template": both retain the same YouTube-transcript summarization workflow and section ordering, while one variant adds a local prerequisite block. This is precisely the kind of scaffold reuse the structural partition is designed to capture.

The example also illustrates the interpretation boundary emphasized in Appendix C.7: shared instructional structure does not establish a shared attacker, campaign, causal lineage, or attack mechanism. The family is an operational similarity control for evaluation, not an attack ontology.

Table 59: Representative non-duplicate structural-reuse pair from a frozen operational structural family. The pair was included in the blinded positive-validation set and judged high-confidence same structural template.

Canonical / benchmark ID	Source-record shorthand	Source	Normalized hash prefix	Similarity to representative	Structural-review observation
UASSB_00007858 ASB04_001347	YouTube summarize (35o20)	SRC001	2c9012ef5e9f...	0.9967	Shared transcript-summarization setup, extraction, metadata, summarization, language, and option sections.
UASSB_00007934 ASB04_003626	yt-summarize	SRC001	7983b6100b3a...	0.9109	Same ordered workflow; the blind reviewer identified a local prerequisite addition as the main structural difference.

Family context. The current family contains five normalized identities associated with SRC001/SRC005/SRC010. The historical raw-record context contains repeated released artifacts; these counts describe structural reuse, not independent attacks or campaigns.

K.3 A CROSS-LABEL CONFLICT GROUP

One conflict group from SRC006 (AgentTrap) makes the need for artifact-level conflict exclusion especially clear. Four source records share the same exact Skill hash and the same normalized hash, yet two source cases are canonicalized as benign test fixtures and two as malicious test fixtures. The shared base Skill is the same `xlsx` artifact; the case-level labels differ under the upstream runtime-fixture design. Table 60 lists the four records without reproducing any executable fixture or payload.

Table 60: Representative SRC006 cross-label identity conflict. All four records share exact Skill hash prefix `dd316db7785a...` and normalized hash prefix `6afac6531997...`; the conflicting group is excluded from the primary benchmark.

Canonical ID	Record	Intent	Evidence	Upstream case descriptor	Shared artifact context
UASSB_00107519	107	benign	strong / runtime	DIM7: output tampering	Derived from the same upstream `xlsx` Skill identity; artifact text is identical at the frozen exact-hash level.
UASSB_00107520	108	benign	strong / runtime	DIM8: unauthorized disclosure	
UASSB_00107538	20	malicious	strong / runtime	DIM7: output tampering	
UASSB_00107550	22	malicious	strong / runtime	DIM8: unauthorized disclosure	

At the primary static-artifact level, automatically choosing one side would collapse source context into an unsupported "correct" artifact label. We therefore exclude the entire conflicting identity group from the primary benchmark, while retaining its provenance and evidence in the audit layer. This example should not be read as proof that either upstream label is erroneous: the conflict may arise because the source label is attached to surrounding runtime context while the benchmark unit contains only the static Skill text.

K.4 A PAIRED SOURCE-CONDITIONED FALSE-POSITIVE EXAMPLE

The same frozen benign record can also behave differently under different training protocols. ASB04_007510 (UASSB_00181982) is the SRC011 wild benign Skill `real-wix--wix-cli-backend-event`. It is a moderate/static, independently identified benign reference unit that appears in both frozen test manifests. The seed-42 word TF–IDF + linear-SVM model predicts the record correctly under Random but flips it to malicious under Source-Disjoint,

even though the evaluated static Skill unit itself is unchanged. Table 61 reports the frozen decision scores.

Table 61: Paired prediction for the same benign Skill under two frozen test protocols (seed-42 word TF–IDF + linear SVM). Positive decision scores predict malicious.

Protocol	True label	Prediction	Decision score	Interpretation
Random	benign	benign	-0.360	Correct classification for `ASB04_007510`.
Source-Disjoint	benign	malicious	$+0.509$	False positive on the same unchanged static Skill unit under source-held-out training.

Record metadata. `UASSB_00181982`, SRC011, `real-wix--wix-cli-backend-event`, `skill_md`, wild provenance, moderate/static benign evidence, independent lineage. The exact seed-42 decision scores are -0.360467 (Random) and $+0.509328$ (Source-Disjoint).

This paired example provides a descriptive comparison under two protocols. The model parameters and training distributions differ between protocols, and source identity bundles content style, provenance, construction process, and label composition. The example therefore supports the paper's narrower claim of source-conditioned generalization sensitivity; it does not identify which source-associated factor caused the decision boundary to move.

L Benchmark Release, Safety, and Governance

MaliciousSkillBench is a security benchmark whose source registry contains both benign and malicious Agent Skill artifacts. Reproducibility therefore cannot be reduced to publishing every acquired byte in one archive. The release contract separates (i) the information needed to reproduce benchmark membership and evaluation, (ii) the public static-text representation of each benchmark identity, and (iii) source/package artifacts whose redistribution remains governed by recorded upstream terms. This appendix documents that contract and the maintenance rules for the frozen paper snapshot.

L.1 Release package and reproducibility layers

The public benchmark release is organized into complementary layers for identities, text, metadata, and reproducibility artifacts. Table 62 summarizes the release-facing contract. All 9,740 benchmark identities have a publicly readable representation. Exact frozen static Skill text is released for 9,735 identities (7,500 malicious and 2,235 benign); the remaining five malicious identities have sanitized public representations because their exact originals contain sensitive credential material. Source/package redistribution beyond these per-identity text representations remains subject to recorded upstream terms and benchmark-side safety constraints.

The central design principle is that *benchmark reproducibility is not identical to full-package republication*. Stable canonical IDs, pinned source revisions, exact and normalized hashes, source labels, provenance/evidence fields, conflict decisions, structural-family assignments, split manifests, and checksums make the paper snapshot auditable while the public text layer makes every primary identity inspectable. The 186 accepted identities whose text came from author-provided historical research snapshots (153 from SRC002 and 33 from SRC004) now include their exact frozen static Skill text in the public release; their historical provenance remains recorded. Full upstream packages or auxiliary source content may still require source-specific reacquisition under the recorded terms.

L.2 Static-only handling and harmful-content minimization

All acquired Skill contents are treated as untrusted data. Benchmark construction, deduplication, structural comparison, text-feature extraction, sanitization, and the reported detector experiments operate on static text/metadata only. The pipeline does not execute Skill code, helper scripts, installers, embedded shell commands, URLs, network requests, evaluation harnesses, or payloads. This non-execution rule applies regardless of whether an upstream source describes an artifact as benign, malicious, vulnerable, synthetic, or a test fixture.

Table 62: Release layers for the frozen paper snapshot. Every primary identity has a public readable representation; source/package redistribution beyond that text layer remains source-specific as recorded in Appendix A.3.

Layer	Contents	Release form	Reproducibility role
Canonical registry	Canonical/source IDs, frozen revision, original/canonical label, provenance, evidence, label strength, artifact unit, lineage fields, license metadata	Public metadata	Reconstruct benchmark scope and source semantics
Identity and audit	Raw/exact identity hashes, normalized hashes, conflict flags, structural-family IDs, benchmark membership	Public metadata/hash	Verify identity, deduplication, reuse, and exclusions without executing artifacts
Primary static Skill text	Exact frozen text for 9,735 identities; sanitized readable representations for five credential-bearing malicious identities	Public text	Inspect all 9,740 primary identities while preserving the exact experimental text for 9,735
Evaluation	Master unit IDs, split assignments, leakage checks, sanitizer rules, detector configurations, metric/result tables	Public non-payload artifacts	Reproduce paper protocols and reported analyses
Redistributable Skill artifacts	Static Skill text/packages whose recorded source terms and benchmark-side policy permit republication	Source-specific	Enable direct local detector input where redistribution is allowed
Restricted-source reconstruction	Pinned source revision, source record identifiers, adapter/reacquisition instructions, and checksums for artifacts not republished	Adapter or metadata/hash only	Let users reacquire under upstream terms and verify local correspondence

The same principle constrains release documentation. Reproducibility tables describe artifact identity, provenance, evidence, labels, transformations, and evaluation outcomes without requiring execution of operational payloads. For five credential-bearing malicious records, the released text is sanitized to remove sensitive credential material while preserving a readable Skill representation. Those sanitized texts are not bit-for-bit copies of the historical frozen inputs used by the pre-release classical analyses; the added ModernBERT baseline excludes the five withheld exact texts, and their sanitized substitutes are never used. This release-safety exception is distinct from the deterministic scaffold-sanitization control in Appendix H.2; that control is an analysis condition with no effect on benchmark release identity and provides no guarantee that harmful semantics have been removed.

L.3 Licensing and redistribution policy

Each source retains its own upstream license and redistribution constraints. Appendix A.3 records the frozen revision and benchmark-side policy for all 13 sources. The benchmark does not infer redistribution permission from the fact that a repository is publicly accessible, and it does not use a permissive benchmark-level license to supersede a more restrictive source license.

For source/package material beyond the public per-identity text layer, we apply the following precedence rule: the released representation is the most informative form that is both consistent with the recorded upstream terms and compatible with the benchmark's safety policy. Practical cases include package redistribution where allowed, metadata/hash-only representation, or adapter-based reconstruction from the upstream source. Any later discovery of changed or clarified upstream terms is handled as a release-governance event while preserving the frozen scientific snapshot.

L.4 Intended and out-of-scope uses

Intended uses. MaliciousSkillBench is designed for defensive and measurement-oriented research: static malicious Agent Skill detection, source-conditioned generalization evaluation, dataset provenance auditing, duplicate/reuse analysis, label-consistency auditing, benign false-positive analysis, threat-stratified analysis, and reproducibility studies over the frozen source registry. The benchmark can also support development of new defensive models provided that comparisons report the benchmark version, split protocol, detector inputs, and class-aware metrics.

Out-of-scope uses. The benchmark is not intended as an execution suite for malicious Skills, a payload-generation or payload-improvement resource, an actor/campaign attribution dataset, or a prevalence estimate for the wider Agent Skill ecosystem. Operational structural families are not attack-mechanism or campaign labels (Appendix C.7), and Source-Disjoint is not a causal estimate of universal future-source performance (Appendix F.7). Likewise, performance of the static text

baselines should not be interpreted as an upper bound on runtime, code-aware, behavioral, or multimodal security systems.

Table 63: Compact benchmark card for the frozen MALICIOUSSKILLBENCH paper snapshot. Counts refer to the canonicalized static benchmark unless a subset is stated explicitly.

Field	Frozen paper-snapshot value / contract
Source registry	13 public sources; 182,699 canonical registry records; 11 sources contribute at least one Core malicious Skill artifact.
Core malicious construction	8,414 raw artifacts → 7,562 exact-unique → 7,539 normalized-unique malicious identities.
Structural reuse control	4,588 operational structural families at the frozen 0.68 threshold; family IDs support structural-disjoint evaluation and reuse auditing, with no campaign-attribution semantics.
Cross-label conflicts	34 normalized malicious identities conflict with benign identities and are excluded from the primary benchmark under the frozen conflict policy.
Primary detection benchmark	9,740 normalized-unique Skills: 7,505 malicious + 2,235 Main-benign.
Threat-characterization coverage	4,983 malicious identities have harmonized multi-label attack mappings; 2,128 have conservative derived-impact mappings; 1,888 have both attack and impact mappings.
Frozen evaluation protocols	Random (6,818/974/1,948 train/dev/test); Source-Balanced Random (6,817/973/1,950); Malicious-Structural-Disjoint (6,818/974/1,948); Source-Disjoint (7,513/835/1,384), with 8 cross-boundary exclusions.
Detector suite	Three TF–IDF text baselines, a fine-tuned ModernBERT encoder, one zero-shot LLM judge, and three evaluated local static primary-text scanner configurations (Cisco-local-behavioral, SkillFortify-offline, SkillSpector-static).
Artifact handling	Static analysis only: benchmark construction/evaluation never executes Skill instructions, helper code, installers, URLs, network actions, or payloads.
Public text release	All 9,740 identities have readable public representations; 9,735 provide exact frozen static Skill text (7,500 malicious + 2,235 benign), while five credential-bearing malicious identities provide sanitized representations only.
Release principle	Canonical metadata, hashes, split manifests, audit artifacts, and reproducibility material are public; full source/package redistribution beyond the per-identity text layer remains source-license- and safety-policy-specific.

L.5 VERSIONING, CORRECTIONS, AND MAINTENANCE

The benchmark state used in this paper is frozen for reproducibility. Future maintenance must preserve that snapshot, including its members, labels, hashes, structural-family assignments, and split manifests. Table 64 specifies how common maintenance events should be handled.

Table 64: Maintenance and versioning contract. The paper snapshot remains immutable; scientifically material data changes create a new benchmark release while historical results remain tied to the frozen snapshot.

Maintenance event	Required action	Effect on frozen paper snapshot
Documentation/citation clarification	Record in changelog; do not alter data bytes, labels, hashes, or splits	None; paper numbers remain directly comparable
License/redistribution clarification	Update release representation and attribution; preserve the recorded historical policy in the archived snapshot	May change what is distributed, not the historical benchmark membership
Label, content, or conflict correction	Issue a new benchmark release; regenerate affected canonical metadata, hashes, conflicts, splits, and derived metrics as needed	The paper snapshot remains available and unchanged
Source addition/removal or newer upstream revision	Create a new release with explicit source/revision delta and fresh deduplication/conflict auditing	Not backfilled into the paper snapshot
Split/protocol redesign	Version the protocol and keep the original assignments available	Prior results retain their original protocol meaning
New detector or leaderboard entry	Record model, inputs, configuration, release, protocol, and class-aware metrics	Does not require a benchmark-data version change

Every benchmark result should therefore identify at least: the benchmark release, the evaluation protocol, the detector input representation, the model/configuration, and the reported metric set. New source additions or revised labels can be scientifically useful, but they define a new benchmark release and should be evaluated separately from the frozen paper snapshot. This prevents a continuously updated corpus from silently changing the meaning of previously reported numbers.

L.6 Compact benchmark card

Table 63 summarizes the frozen scientific and release-facing contract in one place. It is intentionally a compact index; the source-, construction-, threat-, protocol-, and scanner-specific appendices above provide the full details.

M Exploratory Multi-LLM Static-Text Case Study

This case study examines how automated judgments based on primary Skill text align with the frozen benchmark reference labels. It supplements the detector-transfer experiments with a descriptive view of text-level interpretation under a shared rubric. The analysis is separate from benchmark construction: its judgments leave all reference labels, frozen splits, and detector results unchanged.

M.1 Sampling and text views

The sample contains 610 unique identities and 631 cohort draws: 180 from Random test, 371 from Source-Disjoint test, and 80 from Source-Disjoint train. The text-available sampling populations contain 1,947, 1,384, and 7,510 identities, respectively. Excluding the five withheld exact texts from eligibility removes one Random-test item and three Source-Disjoint-training items; no Source-Disjoint-test item is excluded. These are audit-population sizes, and the frozen split sizes remain unchanged.

Sampling uses benchmark metadata without detector predictions or judgment outcomes. Source-Disjoint test is stratified by source and reference label. Random test and Source-Disjoint train additionally stratify by the recorded evidence type. Their allocations start with up to three and two items per nonempty cell, respectively, then distribute the remaining quota by square-root allocation subject to cell capacities. Within strata, stable SHA-256 ranks with seed 271828 select items without replacement. The 21 cross-cohort identities are judged once and retain separate cohort-specific weights; the cohort estimates are therefore not independent replications.

Primary-text views were prepared with the pinned ModernBERT-base tokenizer and an 8,192-token budget including special tokens; three selected identities require truncation. The readable view is extracted using the retained tokens' character offsets. This preparation budget defines the supplied text, not the judging models' native context limits. Organizer-supplied source identifiers, reference labels, evidence categories, provenance, and detector outputs are hidden. Naturally occurring source names are preserved: 119 views contain the literal `SkillFortifyBench`. The protocol is consequently metadata-blinded, with content-level source cues retained.

M.2 Agent-assisted judging protocol

The two initial judges were Gemini-3.8-flash in Antigravity (High reasoning mode) and GPT-5.6-luna in Codex (Max reasoning mode). They performed the initial judgments separately. GPT-5.6 Sol (Max reasoning mode) adjudicated the 165 disagreements using the same primary-text views and the A/B judgment notes. All three roles used the same task prompt and four-category decision rubric. Agreed judgments were inherited directly; each disagreement received the adjudicator's final judgment.

The rubric assigns MALICIOUS when visible text provides concrete malicious intent or behavior, and BENIGN when it coherently supports a benign purpose without material visible malicious behavior. INSUFFICIENT CONTEXT denotes missing evidence needed for a reliable decision, including behavior delegated to unseen files or runtime context; UNCERTAIN denotes genuine ambiguity within the available text. A text-level benign judgment does not certify the full package. The task restricts inspection to the prepared text view and does not permit execution of Skill contents or retrieval of omitted material.

The initial judges agree on 445/610 identities (72.95%); four-category Cohen's κ is 0.479. The final 610 judgments comprise 379 BENIGN, 144 MALICIOUS, 86 INSUFFICIENT CONTEXT, and one UNCERTAIN. These pooled counts describe the sampled identities and are not population-weighted estimates.

M.3 REFERENCE-LABEL ALIGNMENT

Let $\mathcal{H}_{c,y}$ index the strata of cohort c with reference class y. Stratum h has population size N_h and sample s_h of size n_h; J_i is the final judgment for item i. We report the design-weighted alignment

$$\widehat{a}_{c,y} = \frac{\sum_{h \in \mathcal{H}_{c,y}} (N_h/n_h) \sum_{i \in s_h} \mathbf{1}\{J_i = y\}}{\sum_{h \in \mathcal{H}_{c,y}} N_h}.$$

All four judgment categories remain in the denominator. Thus INSUFFICIENT CONTEXT and UNCERTAIN are non-matches for alignment, while remaining distinct outcomes in the descriptive counts. Overall alignment uses the same weights over both reference classes. These are point estimates for the specified text-available populations.

Table 65: Design-weighted final-judgment alignment with benchmark reference labels (%). Benign and malicious columns condition on the reference class; overall alignment includes both classes. All four judgment categories remain in the denominator. The eligible population N excludes withheld exact texts; n counts cohort draws.

Cohort	n	N	Benign	Malicious	Overall
Random test	180	1,947	99.69	54.09	64.56
Source-Disjoint test	371	1,384	97.78	18.19	49.53
Source-Disjoint train	80	7,510	99.10	55.42	64.27

Table 65 shows high benign-reference alignment across the three cohorts (97.78–99.69%) and lower malicious-reference alignment (18.19–55.42%). Table 66 localizes the Source-Disjoint-test pattern. SRC009 contributes 728 of the 839 reference-malicious test identities, and its sampled alignment is 12/123 (9.76%). Its composition therefore strongly influences the 18.19% weighted malicious alignment. The corresponding SRC011 and SRC012 malicious strata align on 20/21 (95.24%) and 39/57 (68.42%) items. SRC011 malicious is a census stratum; the other rows are samples.

Table 66: Source-Disjoint-test source–reference-label strata. N_h and n_h are population and sample sizes. Aligned entries give the match count and percentage of n_h. Final-judgment counts are B: benign, M: malicious, IC: insufficient context, and U: uncertain.

Source	Reference	N_h	n_h	Aligned (%)	Final judgments			
					B	M	IC	U
SRC009	Malicious	728	123	12 (9.76)	61	12	49	1
SRC011	Benign	455	113	110 (97.35)	110	1	2	0
SRC011	Malicious	21	21	20 (95.24)	1	20	0	0
SRC012	Benign	90	57	57 (100.00)	57	0	0	0
SRC012	Malicious	90	57	39 (68.42)	18	39	0	0

M.4 INTERPRETATION BOUNDARY

The estimates describe this agent-assisted workflow and its eligible populations. Low malicious-reference alignment can reflect omitted package/runtime evidence, limited text views, conservative decisions, or model errors; a BENIGN outcome and an INSUFFICIENT CONTEXT outcome are different observations. High benign-reference alignment alone cannot rule out a benign decision preference. With no paired full-package or runtime comparison, the study does not isolate an observability limit, validate or overturn benchmark labels, or establish a causal explanation for detector-transfer failures. It provides a supplementary characterization of how static-text judgments vary across reference classes and sources under one shared rubric.

N ZERO-SHOT LLM JUDGE BASELINE

This appendix documents the zero-shot LLM judge reported in Table 2. The judge is evaluated as a detector under the same frozen protocols as the learned baselines, not as a label-validation procedure: its verdicts change no reference label, no split, and no other reported result.

N.1 CONFIGURATION AND INPUT CONTRACT

Each eligible benchmark identity contributes one retained outcome to evaluation on its static primary instruction text, and protocol slicing is applied only after this retention step, so identities shared across protocols do not receive separate verdicts. The judge uses the same public primary-text layer, five-record exclusion, and 8,192-token budget as the ModernBERT baseline. Prepared inputs were generated with `AutoTokenizer.from_pretrained("answerdotai/ModernBERT-base")` without an explicit immutable revision; we therefore do not claim that the tokenizer snapshot was independently pinned for this run. The resulting inventory contains 9,735 eligible identities, of which 118 require truncation, matching the encoder's token-length audit.

Requests use the gateway model alias `deepseek-v4.1-flash` at temperature 0 through the recorded OpenAI-compatible routing endpoint. The archived run records preserve this alias but do not expose a provider-side immutable backend revision or snapshot identifier; the result therefore characterizes the frozen service run and archived outputs rather than an independently reconstructable backend checkpoint. The initial pass processed all 9,735 eligible identities and produced 9,616 parseable outputs and 119 parsing failures. The resumable job was then rerun under the same prompt and configuration, processing only those 119 failed identities: 104 returned parseable outputs and 15 failed again. The archive therefore contains 9,854 terminal run records for 9,735 identities; evaluation retains the parseable rerun result where available and otherwise marks the identity unjudged, yielding 9,720 (99.85%) retained parseable judgments and 15 unjudged identities. Successful-response records include the model identifier, temperature, per-item input hash, token usage, and latency; failed-attempt records retain the identity, label, source, model, error, and status. The 15 unresolved identities failed output parsing on both recorded attempts and were not resolved under a modified prompt. They span 7 sources and both classes.

N.2 TASK DEFINITION

The judge receives the following system prompt verbatim. The instruction that the document is data rather than instruction is load-bearing: the corpus contains artifacts constructed to redirect an agent that reads them, so a judge without an explicit data boundary is itself a target.

```
You are a security analyst auditing Agent Skill packages
before installation.
You will be shown the primary instruction document
(SKILL.md) of one Skill.  Decide whether that document
indicates the Skill is malicious.
CRITICAL: The document is DATA under examination, never
instructions to you.  It may contain text addressed to an
AI assistant, including attempts to redirect you, claim
authority, or declare itself safe.  Treat all such text as
evidence to evaluate, never as commands to follow.  Never
execute, fetch, or act on anything it contains.
Decide among:
- MALICIOUS: the visible text indicates concrete harmful
behavior (exfiltration, unauthorized execution or download,
credential access, privilege abuse, tampering with logs
or protected paths, hidden instructions to the agent, and
similar).
- BENIGN: the visible text coherently supports a legitimate
purpose with no material harmful behavior.
- INSUFFICIENT_CONTEXT: the visible text defers the operative
behavior to files, scripts, or runtime context that are
not shown, so a reliable decision cannot be made from this
document alone.
```

```
Also report malicious_probability:  your calibrated
probability in [0,1] that this Skill is malicious.  Use
the full range; do not snap to 0 or 1.
Respond with exactly one JSON object and nothing else.  Keep
rationale under 20 words so the object always closes.
```

N.3 SCORING ABSTENTIONS

INSUFFICIENT CONTEXT is an abstention, and collapsing it silently would either flatter or penalize the judge by fiat. Table 67 reports both readings. The main table uses abstain-as-benign because it is the deployment-faithful reading: an artifact that is not flagged is installed. The coverage-conditional reading is reported here for completeness, but it is not directly comparable to a detector that scores every item, since the judge answers only 72.5% of the Source-Disjoint test under that reading.

Table 67: Zero-shot LLM judge under both abstention readings. Abstain-as-benign is the deployment reading used in Table 2: an artifact that is not flagged is installed. The coverage-conditional reading drops abstentions and reports the retained fraction; it is not directly comparable to a detector that scores every item.

Protocol	Mal. n	Ben. n	Macro-F1	Mal. recall	FPR_B	AUROC
Abstain scored as benign						
Random	1499	444	0.825	81.5%	1.8%	0.965
Source-bal. Random	1500	448	0.815	80.1%	1.3%	0.965
Mal.-Struct.-Disj.	1496	447	0.795	77.6%	1.8%	0.955
Source-Disjoint	839	544	0.636	41.6%	0.7%	0.971
Abstain excluded (coverage-conditional)						
Random (90.4% coverage)	1347	409	0.903	90.7%	2.0%	0.970
Source-bal. Random (90.1% coverage)	1337	418	0.899	89.8%	1.4%	0.969
Mal.-Struct.-Disj. (88.5% coverage)	1312	408	0.885	88.5%	2.0%	0.961
Source-Disjoint (72.5% coverage)	471	532	0.870	74.1%	0.8%	0.965

Under either reading the judge degrades from Random to Source-Disjoint. What distinguishes it from the encoder is the mechanism: its ranking quality is unchanged (AUROC 0.965 to 0.971) while abstention on reference-malicious items rises from 10.1% to 43.9%. The encoder shows the opposite signature, losing AUROC from 0.9965 to 0.8118 while continuing to emit a decision for every item.

N.4 THRESHOLD SELECTION ON THE CONTINUOUS SCORE

Scoring abstentions as benign is one decision rule, not a bound on what the judge's scores support. Table 68 therefore applies an analogous validation-only selection rule: choose an operating point on judge validation and hold it fixed on test. Selecting for validation Macro-F1 raises Source-Disjoint recall from 41.6% to 62.2% and Macro-F1 from 0.636 to 0.768, so part of the recall deficit is attributable to the default rule rather than to the scores. Because item-level ModernBERT validation-score exports are unavailable, we do not claim a unified cross-model re-selection under identical candidate thresholds.

The operating points also transfer differently. On Source-Disjoint, every selection rule lands the judge at 0.74% test benign FPR, including the rule that targets $\mathrm{FPR} \leq 1\%$ on validation. The same target applied to ModernBERT transfers to $22.9 \pm 7.1\%$ test FPR on Source-Disjoint. Threshold transferability is thus a third axis along which the two families differ, separate from ranking quality and from fixed-threshold accuracy.

N.5 WHERE THE JUDGE FAILS, AND WHY

SRC009 contributes 728 of the 839 Source-Disjoint reference-malicious identities and accounts for almost all of the judge's recall loss: recall is 33.7% on SRC009 against 100.0% on SRC011 and 92.2% on SRC012. Equal-source aggregation gives 75.3% malicious recall across SRC009/011/012 and 0.44% benign FPR across SRC011/012, so the judge's aggregate failure is concentrated on reference-malicious SRC009 rather than held-out benign examples. SRC009 contains 570 fixed-payload-

Table 68: Threshold selection on the continuous judge score with validation-only operating-point selection followed by fixed test application. This is analogous to the recorded ModernBERT calibration diagnostic but is not a unified cross-model re-selection because ModernBERT item-level validation scores are unavailable. On Source-Disjoint, the judge's test benign FPR is 0.74% under every rule, whereas the encoder's recorded $\leq 1\%$ validation target transfers to $22.9 \pm 7.1\%$ test FPR.

Protocol	Operating point	t	Macro-F1	Mal. recall	FPR_B
Random	Fixed $t = 0.5$	0.50	0.849	84.5%	1.80%
	Val. best Macro-F1	0.18	0.896	94.1%	12.84%
	Val. max recall at $\mathrm{FPR} \leq 1\%$	0.68	0.805	78.6%	0.68%
Source-Disjoint	Fixed $t = 0.5$	0.50	0.698	51.0%	0.74%
	Val. best Macro-F1	0.38	0.768	62.2%	0.74%
	Val. max recall at $\mathrm{FPR} \leq 1\%$	0.72	0.604	36.9%	0.74%

poisoning (FPP) and 158 self-mutating-poisoning (SMP) identities. For 566 FPP identities, source-native records align the benchmark input with one of four payload realizations; four FPP identities have input/target-path mismatches and are excluded from this placement diagnostic. Table 69 stratifies those 566 identities.

Table 69: Zero-shot LLM judge on the 566 SRC009 FPP identities whose source-native realization record aligns with the evaluated benchmark input. Recall separates by 78.4 points between in-document and routing-based payloads, and the median reported probability declines as the payload moves further from the judged text.

Payload realization	n	Judged malicious	Abstained	Judged benign	Median prob.
Payload written into SKILL.md	143	91.6%	0	12	0.85
Routed to added script	161	31.1%	104	7	0.50
Routed to added document	141	4.3%	104	31	0.35
Routed to added PDF	121	0.0%	117	4	0.20
In-document payload	143	**91.6%**	0	12	0.85
Routing-based payload	423	**13.2%**	325	42	0.35

Recall separates by 78.4 points between artifacts whose payload is written into the primary document and artifacts whose primary document only routes to an attacker-added resource, and the median reported probability declines monotonically as the payload moves further from the judged text. The judge therefore behaves as a reader of the supplied evidence: it detects harmful behavior when that behavior is present in the text it is given, and abstains or declines when the text only points elsewhere.

N.6 Evidence placement and structural familiarity separate detector behavior

We further cross source-native payload placement with structural-family familiarity. "Family in development" means that the frozen malicious structural-family ID under the 0.68 partition occurs in Source-Disjoint train or validation; it does not imply that different family IDs are structurally unrelated. Table 70 reports the resulting four strata.

Aggregating over family status reproduces the existing placement comparison. Table 71 extends that aggregate FPP stratification to the three sparse baselines: supervised in-document versus routed recall gaps are 2.9–5.5 points, while the zero-shot judge differs by 78.4 points.

Where the payload is present in the primary document, ModernBERT and the judge reach 93.5% and 91.6% recall overall. On the 423 routing-based FPP identities, the judge falls to 13.2% while ModernBERT averages 90.5%. Family familiarity modulates this supervised result: ModernBERT routed recall is $98.0 \pm 1.3\%$ for the 117 family-seen identities and $87.7 \pm 5.0\%$ for the 306 family-unseen identities. The judge remains strongly placement-sensitive, with 91.9%/91.4% in-document recall and 23.1%/9.5% routed recall for family-seen/unseen strata.

Table 70: SRC009 FPP malicious recall by source-native payload placement and frozen structural-family familiarity. The cohort contains 566 identities with aligned realization metadata. "Family in dev" means the malicious structural-family ID under the frozen 0.68 partition appears in Source-Disjoint train or validation; different family IDs may still share residual similarity. ModernBERT reports mean ± sample SD over seeds 42/43/44. The LLM uses the paper-primary MALICIOUS-only flagging rule.

Payload placement	Family in dev	n	ModernBERT recall	LLM recall
In primary document	yes	62	$98.4 \pm 0.0\%$	91.9%
In primary document	no	81	$89.7 \pm 0.7\%$	91.4%
Routed to added resource	yes	117	$98.0 \pm 1.3\%$	23.1%
Routed to added resource	no	306	$87.7 \pm 5.0\%$	9.5%

Table 71: Source-Disjoint malicious recall on the 566 SRC009 FPP identities whose source-native realization record aligns with the evaluated benchmark input. SMP identities (n=158) and four FPP identities whose benchmark input does not align with the recorded target file are excluded. Reported supervised-model gaps are 2.9–5.5 points; the zero-shot judge gap is 78.4. ModernBERT is the three-seed mean.

Detector	**Payload in SKILL.md** (n=143)	**Routed payload** (n=423)	Δ
Word TF–IDF + LR	95.8%	91.7%	4.1
Word TF–IDF + SVM	98.6%	93.1%	5.5
Char TF–IDF + SVM	97.9%	93.6%	4.3
ModernBERT-base	93.5%	90.5%	2.9
LLM judge (zero-shot)	91.6%	13.2%	**78.4**

This does not imply that routing-based reference labels are wrong, that supervised predictions identify no harmful evidence, or that family-unseen items contain no residual construction similarity. The primary documents can still carry source- or construction-specific cues when the source-native payload itself is elsewhere. The stratification therefore localizes two correlates of detector behavior without assigning a causal mechanism.

The same placement stratification could be reported under Random, but Random does not control source or structural familiarity, so it cannot by itself separate evidence-placement effects from reuse of source-specific or structurally related construction patterns. The scaffold-sanitization control in Appendix H.2 applies to the sparse baselines and therefore does not identify the cues used by ModernBERT. The family-familiarity stratification above is a separate structural-reuse diagnostic, while residual similarity across different frozen families remains unmeasured.