ANCHOR-CONDITIONED ON-POLICY DISTILLATION FOR CONCEPT ERASURE IN TEXT-TO-IMAGE GENERATIVE MODELS

Anonymous authors
Paper under double-blind review

ABSTRACT

Concept erasure in text-to-image (T2I) generative models aims to suppress specified concepts while preserving non-target generation capabilities. However, existing methods face a persistent trade-off between effective erasure and non-target preservation. Motivated by recent advances in on-policy distillation (OPD), we investigate whether supervision at student-visited states can improve this trade-off. We first apply OPD using existing concept-erased models as frozen teachers and find that it strengthens target suppression while largely preserving non-target generation capabilities across multiple erasure methods. Although effective, this procedure requires a separately trained concept-erased teacher. We propose Anchor-Conditioned On-Policy Distillation (AC-OPD), which instead uses a frozen copy of the original pretrained T2I model conditioned on a non-target anchor prompt. Specifically, the student generates trajectories under a target prompt specifying the concept to be erased and matches the frozen model's anchor-conditioned transition means at student-visited states within an early generation window. Restricting supervision to this window yields a better erasure–retention trade-off than distillation over the full trajectory. Experiments on nudity and IP-character erasure demonstrate strong target suppression while largely preserving non-target text–image alignment and compositional generation capabilities. Compared with off-policy anchor-conditioned distillation, AC-OPD better preserves generation performance and reduces sensitivity to anchor choice. Code is available at `https://anonymous.4open.science/r/AC-OPD-06F5`.

1 INTRODUCTION

Recent advances in image generation models have enabled the synthesis of highly realistic and diverse visual content from natural-language prompts (Song et al., 2020; Ramesh et al., 2022; Saharia et al., 2022; Rombach et al., 2022; Kawar et al., 2023; Zhang et al., 2023a; Podell et al., 2024; Peebles & Xie, 2023; Esser et al., 2024; Labs et al., 2025). However, models trained on large-scale datasets from diverse sources can also generate undesirable content, including harmful concepts and specific intellectual property (IP) characters (Bedapudi, 2019; Schramowski et al., 2023; Jiang et al., 2023; Zhang et al., 2023b; 2025; Qu et al., 2023). Retraining these models from scratch on filtered datasets can be computationally expensive. Concept erasure offers a more practical alternative by modifying a pretrained model to selectively suppress specified concepts while preserving its other generation capabilities (Gandikota et al., 2023; 2024; Fan et al., 2024; Kumari et al., 2023; Lu et al., 2024; Jain et al., 2024; Yoon et al., 2025; Kusumba et al., 2026; Gao et al., 2025; Lee et al., 2026).

A central challenge in concept erasure is to suppress the target concept without degrading generation on non-target prompts. Existing methods use different training objectives and regularization strategies to balance these competing goals. However, effective suppression can still come at the cost of prompt fidelity or compositional generation ability. Therefore, an erased model may suppress a target concept at the expense of capabilities retained by the original pretrained model. This raises the question of whether its suppression behavior can be transferred to a student initialized from the original model while preserving those capabilities.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: (a) Qualitative comparison of concept-erased teachers, their corresponding OPD students, and AC-OPD. Each column corresponds to a different erased teacher and uses the same target prompt across the three rows, enabling direct comparison of the generated outputs. Black regions mask explicit content in the erased-teacher outputs. (b) Quantitative comparison of target suppression and retention. Open circles denote the erased teachers, filled circles denote their corresponding OPD students, and arrows indicate the change after applying OPD. The star denotes AC-OPD, and the gray point denotes the original FLUX.1-dev model.

On-Policy Distillation (OPD) (Lu & Thinking Machines Lab, 2025) trains a student using teacher predictions at states sampled from the student's current generation process. Recent work has extended this approach from large language models (Agarwal et al., 2024; Yang et al., 2025) to image generation. DiffusionOPD (Li et al., 2026) and Flow-OPD (Fang et al., 2026) apply on-policy distillation along student-generated trajectories to consolidate teacher capabilities. For concept erasure, this means supervising the states reached when the student is prompted to generate the target concept. As the student changes during training, on-policy sampling keeps the teacher's corrective targets tied to the student's current generation behavior. This provides a way to address the target concept as it manifests in the student's own trajectories.

To apply OPD to concept erasure, we first use models obtained from existing concept erasure methods as frozen teachers and initialize the student from the original pretrained T2I model. The student generates trajectories under a target prompt (i.e., a prompt specifying the concept to be erased), and matches the teacher's transition means at the same student-visited states under the same prompt. As shown in Fig. 1(a), OPD effectively suppresses residual target generation even in cases where the erased teacher still fails to remove the target concept. Fig. 1(b) further shows that, across multiple erasure methods, OPD consistently improves both target suppression and general generation capability. These results show that distilling an erased model through OPD can yield a student with a better erasure–retention trade-off than the teacher itself.

However, this procedure still requires a separately trained concept-erased teacher and therefore depends on an existing erasure method. This motivates the following question: can the original pretrained model itself provide effective supervision for OPD? In erased-teacher OPD, prior erasure training modifies the teacher's response to the target prompt toward target-suppressed behavior. An alternative is to keep the original model unchanged and query it with a non-target anchor prompt at the same student state. We hypothesize that these anchor-conditioned predictions can provide effective supervision for suppressing the target concept.

Based on this hypothesis, we introduce Anchor-Conditioned On-Policy Distillation (AC-OPD). Given a target prompt (e.g., "Pikachu") and a non-target anchor prompt (e.g., "cartoon character"), the current student generates trajectories under the target prompt. Within an early generation window, it matches the transition means predicted by the frozen original T2I model under the anchor prompt at those same student-visited states. This design concentrates supervision on the beginning of generation, motivated by the possibility of redirecting the trajectory before target-specific content becomes established. Our ablations show that early-window supervision yields a better erasure–retention trade-off than full-trajectory distillation.

We evaluate OPD and AC-OPD on nudity suppression using standard benchmarks and adversarial attacks, including Ring-A-Bell (Tsai et al., 2024), UnlearnDiffAtk (Zhang et al., 2024), and MMA-Diffusion (Yang et al., 2024), and on IP-character erasure across five characters. As summarized in Fig. 1(b), AC-OPD achieves strong target suppression with generation capability close to that of the original pretrained T2I model. Across our evaluations, AC-OPD largely preserves non-target text–image alignment and compositional generation performance. Results on Z-Image Turbo (Cai et al., 2025) further support its applicability beyond FLUX (Black Forest Labs, 2024) (see Sec. 5.4).

Further analysis in Sec. 5 shows the benefit of on-policy supervision. Compared with off-policy anchor-conditioned distillation, AC-OPD achieves similar average target suppression across the tested anchors while better preserving generation capabilities and reducing sensitivity to anchor choice. On FLUX, adapting all single-stream blocks is effective, and restricting adaptation to the early single-stream blocks further improves both suppression and preservation. We use the early-block setting for our main FLUX results.

Our contributions are summarized as follows:

- We demonstrate the effectiveness of OPD for concept erasure, showing that distilling existing erased models at student-visited states improves the erasure–retention trade-off over the teachers themselves.
- We propose Anchor-Conditioned On-Policy Distillation (AC-OPD), which matches anchor-conditioned transitions from the frozen original T2I model at target-conditioned student states within an early generation window, without requiring a separately trained erased teacher.
- We evaluate OPD and AC-OPD across diverse settings, demonstrating strong suppression of nudity and IP characters while largely preserving non-target generation capabilities. Comparisons with off-policy distillation and ablations examine the benefits of on-policy supervision and the main design choices, while results on Z-Image Turbo support applicability beyond FLUX.

2 Related Work

Concept Erasure. Concept erasure (Gandikota et al., 2023; 2024; Fan et al., 2024; Kumari et al., 2023; Lu et al., 2024; Jain et al., 2024; Yoon et al., 2025; Kusumba et al., 2026; Gao et al., 2025; Lee et al., 2026) aims to selectively suppress specified concepts from pretrained T2I models while preserving generation capabilities on non-target concepts. Concept Ablation (CA) (Kumari et al., 2023) aligns the distribution associated with a target concept with that of a predefined anchor concept to suppress the target concept. ESD (Gandikota et al., 2023) instead uses the original pretrained diffusion model to construct a negative-guidance target and fine-tunes model parameters to steer generation away from the target concept. More recent work extends concept erasure to flow-based T2I models. EraseAnything (Gao et al., 2025) formulates concept erasure in rectified flow transformers as a bi-level optimization problem, combining LoRA adaptation, attention regularization, and self-contrastive learning to balance erasure and preservation. Taking a trajectory-level approach, EraseFlow (Kusumba et al., 2026) uses a GFlowNet (Bengio et al., 2023) trajectory-balance objective to learn concept-erasing denoising policies while preserving the pretrained model's prior. We study whether models produced by existing erasure methods can serve as teachers for OPD to improve the erasure–retention trade-off. While Concept Ablation uses an anchor concept to define the desired distribution after erasure, we study how anchor-conditioned supervision interacts with the student's own generation process. In AC-OPD, the student generates states under the target prompt, and the frozen original model supplies anchor-conditioned transition targets at those same states within an early generation window.

On-Policy Distillation in T2I models. On-Policy Distillation (Lu & Thinking Machines Lab, 2025) trains a student using teacher predictions at states visited along its own generation trajectories, ensuring that supervision remains aligned with the evolving student distribution. DiffusionOPD (Li et al., 2026) extends this approach to diffusion models by distilling independently optimized task-specific teachers along student-generated trajectories. It derives a per-step KL objective for continuous diffusion processes and connects stochastic SDE distillation and deterministic ODE refinement through transition mean matching. Flow-OPD (Fang et al., 2026) applies OPD to flow-matching models,

combining specialized teachers through on-policy sampling and dense trajectory-level supervision. Its results also show that the distilled student can outperform individual teachers on the evaluated tasks.

Concurrent with our work, FlowErase-OPD (Sun et al., 2026) applies OPD to multi-concept erasure in flow-matching models. It consolidates multiple single-concept erased teachers into a unified LoRA, uses the frozen original model as a retention teacher on general prompts, and adaptively balances erasure and retention during training. Our work instead examines whether OPD improves the erasure–retention trade-off of individual erased teachers and introduces AC-OPD, which requires no separately trained erased teacher. In AC-OPD, the original model supplies anchor-conditioned erasure targets at states visited by the target-conditioned student, rather than serving as an auxiliary retention teacher.

3 METHOD

3.1 PRELIMINARIES: ON-POLICY DISTILLATION

A flow-based generative model (Lipman et al., 2022; Esser et al., 2024) evolves a latent state $x(t) \in \mathbb{R}^d$ through a time-dependent vector field:

$$\frac{dx(t)}{dt} = v(x(t), t, c), \tag{1}$$

where t denotes time and c is the conditioning input.

OPD supervises a student using teacher predictions at states visited during the student's own generation process. Let v_s and v_T denote the student and frozen teacher vector fields, respectively. Given a sampling schedule $\{t_i\}_{i=0}^{N}$, ordered from noise to data, we write $x_i = x(t_i)$, where i indexes generation steps. Starting from $x_0 \sim N(0, I)$, the student generates a trajectory $\tau_s = (x_0, \ldots, x_N)$ using its own predictions. We denote the resulting trajectory distribution by $p_s(\tau \mid c)$.

Under Euler discretization, the student and teacher one-step transition means are

$$\mu_s(x_i, t_i, c) = x_i + \Delta t_i \, v_s(x_i, t_i, c), \qquad \mu_T(x_i, t_i, c) \quad = x_i + \Delta t_i \, v_T(x_i, t_i, c), \tag{2}$$

where $\Delta t_i = t_{i+1} - t_i$ is the signed integration step size. The student rollout follows $x_{i+1} = \mu_s(x_i, t_i, c)$. The teacher is evaluated at the same student-generated state x_i, rather than at a state from a separate teacher trajectory. For deterministic ODE sampling, each transition mean is simply the predicted next state.

Following the transition-matching formulation of DiffusionOPD (Li et al., 2026), we train the student to match the teacher's transition mean along student-generated trajectories:

$$\mathcal{L}_{\text{OPD}} = \mathbb{E}_{\tau_s \sim p_s(\tau|c)} \left[\sum_{i=0}^{N-1} \frac{1}{2} \left\| \mu_s(x_i, t_i, c) - \mu_T(x_i, t_i, c) \right\|_2^2 \right]. \tag{3}$$

At each optimization step, trajectories are sampled from the current student without gradient tracking. The sampled states and teacher predictions are then treated as fixed, and gradients are computed only through the student predictions evaluated at those states. Thus, supervision follows the student's evolving state distribution without backpropagating through the rollout process.

3.2 ON-POLICY DISTILLATION FOR CONCEPT ERASURE

We apply the OPD formulation in Sec. 3.1 to concept erasure. Let v_E denote a concept-erased model obtained using an existing erasure method. We use v_E as a frozen teacher and initialize the student v_s from the original pretrained T2I model.

Given a target prompt c_e specifying the concept to be erased, the student generates a trajectory under c_e. At each student-visited state x_i, both the student and the concept-erased teacher are evaluated under the same target prompt c_e, yielding transition means $\mu_s(x_i, t_i, c_e)$ and $\mu_E(x_i, t_i, c_e)$, respectively. The erased teacher thus provides a transition target for the student at its current state under the target prompt.



Figure 2: **Overview of AC-OPD.** The student is initialized from the original pretrained model and generates an on-policy trajectory under the target prompt c_e, with supervision applied at early student-visited states. At each state (x_i, t_i), AC-OPD matches the student's target-conditioned transition mean $\mu_s(x_i, t_i, c_e)$ to the anchor-conditioned transition mean $\mu_0(x_i, t_i, c_a)$ provided by a frozen copy of the original model.

We restrict supervision to the first T_{early} steps of the N-step sampling schedule, where $1 \leq T_{\text{early}} \leq N$. The motivation is to redirect the target-conditioned trajectory before the target concept becomes established, rather than impose the erasure objective throughout generation. The objective is

$$\mathcal{L}_{\text{CE-OPD}} = \mathbb{E}_{\tau_s \sim p_s(\tau|c_e)} \left[\frac{1}{T_{\text{early}}} \sum_{i=0}^{T_{\text{early}}-1} \|\mu_s(x_i, t_i, c_e) - \mu_E(x_i, t_i, c_e)\|_2^2 \right]. \tag{4}$$

We use $T_{\text{early}} = 10$ for FLUX (Black Forest Labs, 2024). This restriction determines where supervision is applied during training. The adapted student is used throughout the full sampling trajectory at inference. The effect of the supervision horizon is evaluated in Sec. 5.3. This formulation provides erasure supervision at the student's own target-conditioned states, but requires a separately trained concept-erased teacher.

3.3 Anchor-Conditioned On-Policy Distillation (AC-OPD)

Anchor-Conditioned On-Policy Distillation (AC-OPD) removes this requirement by using the original pretrained T2I model conditioned on a non-target anchor prompt as the reference. We initialize the student v_s from the original pretrained model and use a separate frozen copy v_0 as the reference.

Given a target prompt c_e specifying the concept to be erased and a non-target anchor prompt c_a, the student generates a trajectory prefix under c_e, using the same early supervision window as in Sec. 3.2. At each student-visited state x_i, the student is evaluated under c_e, while the frozen reference model is evaluated under the anchor condition c_a. We optimize the student by matching its target-conditioned transitions, $\mu_s(x_i, t_i, c_e)$, to the anchor-conditioned transitions of the reference v_0, $\mu_0(x_i, t_i, c_a)$, along the student-induced trajectory:

$$\mathcal{L}_{\text{AC-OPD}} = \mathbb{E}_{\tau_s \sim p_s(\tau|c_e)} \left[\frac{1}{T_{\text{early}}} \sum_{i=0}^{T_{\text{early}}-1} \|\mu_s(x_i, t_i, c_e) - \mu_0(x_i, t_i, c_a)\|_2^2 \right]. \tag{5}$$

AC-OPD shares the anchor-based distribution alignment principle of CA (Kumari et al., 2023), but differs in how training states and reference predictions are constructed. The model-based variant of CA matches target- and anchor-conditioned noise predictions at states obtained by forward-noising anchor-concept images. In AC-OPD, the current student generates states through target-conditioned rollouts, and its transition means are matched to anchor-conditioned transition means from the frozen original model at those same states within an early generation window.

For our FLUX experiments, we restrict LoRA adaptation to the early single-stream blocks. This choice is motivated by SplitFlux (Yang et al., 2026), which identifies these blocks as primarily responsible for content rather than style. Our ablations in Sec. 5.3 show that adapting all single-stream blocks is already effective, while restricting adaptation to the early blocks further improves target suppression and non-target preservation.

4 EXPERIMENTS

Table 1: Nudity suppression and preservation performance on FLUX.1-dev under standard and adversarial evaluations. Lower suppression scores indicate stronger erasure (↓), while higher COCO and GenEval scores indicate better non-target generation performance (↑).

Method	Ring-A-Bell (%) ↓			MMA (%) ↓	UnlearnDiffAtk (%) ↓	I2P (%) ↓	Preservation ↑	
	K-16	K-38	K-77				COCO	GenEval
FLUX.1-dev	88.42	87.37	87.37	19.10	100.00	7.68	30.84	65.97
CA	21.05	17.89	17.89	4.00	61.29	1.76	30.54	60.51
+ OPD	**4.21**	**5.26**	**1.05**	**1.50**	**25.81**	**0.32**	**30.80**	**65.61**
EraseAnything	26.32	22.11	21.05	**3.60**	54.84	1.76	30.50	60.58
+ OPD	**13.68**	**10.53**	**8.42**	5.10	**48.39**	**1.45**	**30.80**	**64.53**
ESD	36.84	27.37	29.47	4.70	70.97	2.17	**30.66**	60.38
+ OPD	**8.42**	**3.16**	**2.11**	**0.60**	**22.58**	**0.43**	30.54	**63.20**
EraseFlow	41.05	34.74	28.42	2.30	45.16	0.96	30.28	63.32
+ OPD	**4.21**	**1.05**	**1.05**	**0.80**	**32.26**	**0.28**	**30.74**	**66.68**
AC-OPD (ours)	2.11	2.11	1.05	1.90	19.35	0.47	30.72	65.86

4.1 EXPERIMENTAL SETUP

Baselines. To evaluate our methods, we consider four existing concept erasure approaches: CA (Kumari et al., 2023), ESD (Gandikota et al., 2023), EraseAnything (Gao et al., 2025), and EraseFlow (Kusumba et al., 2026). For each baseline, we apply OPD using the concept-erased model as a frozen teacher and compare the resulting student with its teacher and AC-OPD.

Benchmarks. For nudity suppression, we evaluate standard performance on I2P (Schramowski et al., 2023) and adversarial robustness against the black-box attacks Ring-A-Bell (Tsai et al., 2024) and MMA-Diffusion (Yang et al., 2024), and the white-box attack UnlearnDiffAtk (Zhang et al., 2024). For IP-character erasure, we construct 1,000 evaluation prompts per concept using GPT-5.6 Sol (OpenAI, 2026) for five characters: Snoopy, Sonic, SpongeBob, Goku, and Pikachu. We evaluate text–image alignment on a 1,000-prompt subset of MS-COCO (Lin et al., 2014) and compositional generation performance on GenEval (Ghosh et al., 2023), following prior work that uses GenEval to assess compositional generation capability after concept erasure or safety alignment (Koma et al., 2026; Kumar et al., 2026; Shakibania et al., 2026). Dataset details are provided in Appendix A.1.

Evaluation metrics. Nudity suppression is evaluated with NudeNet (Bedapudi, 2019) using a confidence threshold of 0.6. For IP-character erasure, we adapt the reference-based MLLM evaluation protocol of HUB (Moon et al., 2025) and use Qwen3.5-9B (Qwen Team, 2026) as a judge to detect the target character in generated images. We evaluate text–image alignment using CLIP score on MS-COCO and compositional generation performance using the GenEval overall score. Additional evaluation details, including the multimodal judge instructions, are provided in Appendix A.2.

Implementation details. Our main experiments are conducted on FLUX.1-dev (Black Forest Labs, 2024), with additional experiments on Z-Image Turbo (Cai et al., 2025) to assess applicability beyond FLUX. For FLUX, we use a deterministic Euler ODE sampler with 28 inference steps, restrict supervision to the first $T_{\text{early}} = 10$ transitions, and update LoRA adapters only in the early single-stream blocks (0–9). Optimization is performed with AdamW for 20 steps at a learning rate of 10^{-3} for nudity suppression and for 100 steps at a learning rate of 10^{-4} for IP-character erasure. The global rollout batch size is 4. We select training configurations using representative benchmarks and target concepts, then keep them fixed for the corresponding full evaluations. Appendix A.3 details hyperparameter selection, teacher construction, and the Z-Image Turbo configuration.

Table 2: Concept-wise erasure and preservation performance on five IP characters. Target counts are measured over 1,000 generated images per concept. Lower target detection counts indicate stronger erasure (↓), while higher GenEval scores indicate better compositional generation performance (↑).

Method	Target Concept ↓						GenEval ↑					
	Snoopy	Sonic	SpongeBob	Goku	Pikachu	Avg.	Snoopy	Sonic	SpongeBob	Goku	Pikachu	Avg.
FLUX.1-dev	990	997	993	993	774	949.40	65.97	65.97	65.97	65.97	65.97	65.97
CA	61	99	29	**1**	**5**	39.00	60.07	62.57	60.40	58.94	60.22	60.44
+ OPD	**1**	**0**	**0**	2	6	**1.80**	**65.52**	**65.27**	**64.53**	**64.25**	**64.48**	**64.81**
EraseAnything	**0**	6	**0**	20	27	10.60	55.70	61.24	63.93	**65.71**	61.00	61.52
+ OPD	**0**	**4**	**0**	**9**	**0**	**2.60**	**64.79**	**65.43**	**64.55**	65.30	**64.28**	**64.87**
ESD	2	55	**0**	30	592	135.80	62.38	63.97	63.04	**65.20**	63.68	63.65
+ OPD	**0**	**6**	**0**	**20**	**143**	**33.80**	**65.18**	**64.39**	**64.02**	63.89	**65.31**	**64.56**
EraseFlow	**0**	**0**	**0**	30	26	11.20	60.93	57.30	56.82	56.40	49.67	56.22
+ OPD	**0**	**0**	**0**	**4**	**10**	**2.80**	**65.24**	**63.18**	**64.58**	**65.46**	**63.78**	**64.45**
AC-OPD (ours)	0	0	0	3	0	0.60	65.17	64.55	63.73	64.09	63.98	64.30

4.2 Experimental Results

Nudity suppression. Table 1 presents nudity suppression performance under standard and adversarial evaluations. Applying OPD improves target suppression on I2P, Ring-A-Bell, and UnlearnDiffAtk across all four baselines. MMA attack success rates also decrease, except for EraseAnything. These gains are accompanied by improved GenEval scores and largely preserved text–image alignment on COCO. These results indicate that OPD effectively suppresses residual target-conditioned behavior through corrective supervision at student-visited states while preserving non-target generation performance. AC-OPD achieves strong suppression without a separately trained erased teacher, including the lowest UnlearnDiffAtk ASR of 19.35%, while maintaining text–image alignment and compositional generation performance close to those of the original model. This further indicates that anchor-conditioned supervision from the original pretrained model can provide effective erasure supervision.

IP-character erasure. Table 2 reports results on five IP characters. Existing erasure methods exhibit different behavior in target suppression and compositional generation performance, whereas applying OPD improves both average target suppression and GenEval across all four baselines. Consistent with the nudity suppression results, OPD also suppresses residual target-conditioned behavior across diverse IP characters while preserving compositional generation performance, indicating that the benefit of on-policy corrective supervision extends beyond nudity suppression. AC-OPD further achieves the lowest average target detection count of 0.60 while maintaining strong GenEval performance without requiring a separately trained concept-erased teacher. These results indicate that anchor-conditioned supervision from the original pretrained model provides an effective alternative to erased-teacher supervision for IP-character erasure. Qualitative results and attribute-level compositional analyses for both tasks are provided in Appendices B.1 and B.2, respectively.

5 Analysis

5.1 Effect of On-Policy Supervision

We examine the effect of on-policy supervision by comparing OPD with an off-policy distillation baseline. In the off-policy setting, the student matches the erased teacher's transition means at states sampled from teacher-generated trajectories under the target prompt. In contrast, OPD samples states from the current student's trajectories and queries the erased teacher at those same states.

As shown in Table 3, both distillation settings improve over the corresponding erased teachers, in-

Table 3: Comparison of off-policy and on-policy distillation. Ring-A-Bell reports the average ASR across $K \in \{16, 38, 77\}$.

Method	CA		EraseAnything	
	Ring ↓	GenEval ↑	Ring ↓	GenEval ↑
Erased	18.94	60.51	23.16	60.58
Off-Policy	14.03	65.49	21.76	**64.79**
On-Policy	**3.51**	**65.61**	**10.88**	64.53

dicating that distillation itself can transfer useful target-suppression behavior while improving GenEval. However, off-policy distillation provides only limited additional gains in target suppression, whereas OPD substantially reduces Ring-A-Bell ASR for both teachers. These results suggest that supervising states visited by the current student, rather than states from teacher-generated trajectories, provides more effective correction of residual target generation.

Table 4: Sensitivity to anchor choice for AC-OPD and its Off-Policy counterpart. Values are reported as mean ± standard deviation across four anchor prompts.

Method	**Ring-A-Bell (%)** ↓	**MMA ASR (%)** ↓	**COCO** ↑	**GenEval** ↑
AC-Off-Policy	2.46 ± 4.05	0.78 ± 1.11	30.41 ± 0.35	55.24 ± 9.73
AC-OPD (ours)	**2.19 ± 1.63**	**0.73 ± 0.79**	**30.75 ± 0.04**	**65.04 ± 1.16**

5.2 Anchor Sensitivity and Semantic Dependence

We analyze sensitivity to anchor selection by comparing AC-OPD with its off-policy counterpart AC-Off-Policy across four anchor prompts. For AC-Off-Policy, training states are sampled from trajectories generated by the frozen original model under the anchor prompt. The student is evaluated under the target prompt and matches the original model's anchor-conditioned transition means at those states. For nudity suppression, we consider two person-related prompts and two object-focused prompts.



Figure 3: Qualitative comparison of anchor dependence in AC-Off-Policy and AC-OPD.

As shown in Table 4, both methods achieve similarly low mean attack success rates on Ring-A-Bell and MMA. The strong suppression observed for both methods suggests that anchor-conditioned supervision itself provides an effective signal for redirecting target generation. The additional benefit of on-policy sampling is more evident in preservation and robustness to anchor choice: AC-OPD achieves a substantially higher mean GenEval score (65.04 versus 55.24) and reduces the standard deviation across anchors from 9.73 to 1.16.

We further examine semantic dependence on the anchor. In the examples shown in Fig. 3, off-policy training with object-related anchors produces outputs dominated by the corresponding objects, whereas AC-OPD retains human subjects with less direct reproduction of the anchor content. These examples suggest weaker anchor-specific dependence under AC-OPD, consistent with its higher preservation scores and lower variation across the four tested anchors in Table 4. Additional qualitative results for AC-OPD across anchor prompts are provided in Appendix B.1.

5.3 Ablation Studies

Adapted Block Selection. We compare four adaptation scopes: all transformer blocks, all single-stream blocks, early single-stream blocks (0–9), and later single-stream blocks (10–End). Adapting all transformer blocks favors target suppression at the cost of generation performance, while all single-stream blocks show the opposite tendency. Restricting adaptation to the early single-stream blocks yields the best overall performance for both CA-based OPD and AC-OPD, whereas later-block adaptation substantially weakens target suppression. This is consistent with the content-related role of early blocks reported by SplitFlux (Yang et al., 2026). Therefore, we use the early single-stream blocks (0–9) as the default adaptation target. Full results are provided in Appendix B.3.

On-Policy Supervision Horizon. We examine supervision horizons ranging from 5 to 28 generation steps. Across both CA-based OPD and AC-OPD, supervision over the first 10 generation steps

yields stronger target suppression than longer supervision horizons, with relatively minor variation in GenEval. Since the distillation loss is averaged over the supervised transitions, increasing the supervision horizon distributes the normalized supervision signal across a larger portion of the trajectory, thereby reducing the relative contribution of early target-conditioned states. Under the fixed normalized objective and optimization budget considered here, concentrating supervision on the early portion of the trajectory is more effective for concept erasure than extending supervision over the full trajectory. We therefore set $T_{\text{early}} = 10$ as the default. Detailed supervision-horizon results, additional training-step and rollout ablations are provided in Appendices B.4 and B.5, respectively.

5.4 Applicability Beyond FLUX

To assess applicability beyond FLUX, we evaluate OPD and AC-OPD on Z-Image Turbo (Cai et al., 2025), which adopts a single-stream DiT architecture. For teacher-based OPD, we use the model obtained with Z-Erase (Jiang et al., 2026) as the frozen erased teacher. As shown in Table 5, Z-Erase suppresses nudity but incurs a substantial degradation in compositional generation performance, as measured by GenEval. Applying OPD further strengthens target suppression across most standard and adversarial evaluations while improving text–image alignment and compositional generation performance. These results indicate that OPD can improve both suppression and preservation on an architecture distinct from FLUX.

We also apply AC-OPD directly to Z-Image Turbo using the original pretrained model as the anchor-conditioned teacher. AC-OPD achieves the strongest target suppression across all evaluated benchmarks, with the lowest scores on all three Ring-A-Bell settings, MMA, UnlearnDiffAtk, and I2P. It also maintains strong text–image alignment and compositional generation performance. These results indicate that corrective supervision on student-visited states remains effective for concept erasure across architectures. Additional qualitative results on Z-Image Turbo are provided in Appendix B.1.

Table 5: Nudity suppression and preservation performance on Z-Image Turbo under standard and adversarial evaluations.

Method	Ring-A-Bell (%) ↓			MMA (%) ↓	UnlearnDiffAtk (%) ↓	I2P (%) ↓	Preservation ↑	
	K-16	K-38	K-77				COCO	GenEval
Z-Image Turbo	89.47	94.74	92.63	20.30	100.00	3.55	31.37	75.97
Z-Erase	42.11	35.79	30.53	6.40	67.44	2.25	31.13	64.69
+ OPD	26.32	25.26	30.53	3.30	60.47	1.36	31.37	**74.04**
AC-OPD (ours)	**20.00**	**14.74**	**15.79**	**2.70**	**55.81**	**1.04**	**31.43**	73.72

6 Conclusion and Future Work

We study On-Policy Distillation (OPD) as a post-training approach for concept erasure, using existing concept-erased models as frozen teachers to supervise states visited by the target-conditioned student. Across nudity suppression and IP-character erasure, OPD improves average target suppression and compositional generation performance over the erased teachers. Text–image alignment is also largely preserved in the nudity experiments. Comparisons with off-policy distillation further highlight the benefit of supervising states visited by the current student for suppressing residual target generation. We further introduce Anchor-Conditioned On-Policy Distillation (AC-OPD), which replaces the separately trained erased teacher with anchor-conditioned supervision from the original pretrained model. AC-OPD achieves strong target suppression under both standard and adversarial evaluations while preserving non-target generation performance. Results on Z-Image Turbo further support the applicability of our approach beyond FLUX.

Our preservation evaluation focuses on general text–image alignment and compositional generation performance, and broader analyses could further examine behavior on concepts semantically related to the erased target. In addition, our experiments primarily consider single-concept erasure. Extending AC-OPD to multi-concept settings and studying how on-policy supervision behaves when multiple concepts are suppressed jointly constitute promising directions for future work.

AI USE STATEMENT

In this work, we used generative AI tools to generate concept-specific evaluation prompts for IP-character erasure. GPT-5.6 Sol was used for prompt generation, and Qwen3.5-9B was used as a multimodal judge for reference-based IP-character evaluation, as described in the paper. During the final review of this manuscript, we also used generative AI tools to assist with language editing and to review the clarity and consistency of the manuscript. The authors reviewed the suggested corrections and take full responsibility for the final content of the paper.

ETHICS STATEMENT

This study investigates concept erasure in text-to-image (T2I) generative models, with a focus on nudity suppression and IP-character erasure. Our goal is to suppress unwanted target concepts while preserving general text-to-image generation capability. Our experiments use public benchmarks and a model-generated, concept-specific prompt set, together with generated evaluation images. Adversarial attacks are used solely to evaluate the robustness of concept erasure against attempts to recover the target concept. For evaluations involving nudity, we do not present fully nude images in the qualitative results. The methods studied in this work are intended for safety- and content-control settings in which model providers or platform operators manage model deployment.

REPRODUCIBILITY STATEMENT

To support reproducibility, we provide code at `https://anonymous.4open.science/r/AC-OPD-06F5` for the AC-OPD experiments on FLUX.1-dev. The released code includes both training and evaluation pipelines for reproducing the AC-OPD results reported in Tables 1 and 2, corresponding to nudity suppression and IP-character erasure, respectively.

REFERENCES

Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos Garea, Matthieu Geist, and Olivier Bachem. On-policy distillation of language models: Learning from self-generated mistakes. In *International Conference on Learning Representations*, volume 2024, pp. 21246–21263, 2024.

Praneeth Bedapudi. Nudenet: Neural nets for nudity classification, detection and selective censoring. `https://github.com/notAI-tech/NudeNet`, 2019.

Yoshua Bengio, Salem Lahlou, Tristan Deleu, Edward J Hu, Mo Tiwari, and Emmanuel Bengio. Gflownet foundations. *Journal of Machine Learning Research*, 24(210):1–55, 2023.

Black Forest Labs. FLUX. `https://github.com/black-forest-labs/flux`, 2024.

Huanqia Cai, Sihan Cao, Ruoyi Du, Peng Gao, Aiming Hao, Steven Hoi, Zhaohui Hou, Shijie Huang, Dengyang Jiang, Yuming Jiang, et al. Z-image: An efficient image generation foundation model with single-stream diffusion transformer. *arXiv preprint arXiv:2511.22699*, 2025.

Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, et al. Scaling rectified flow transformers for high-resolution image synthesis. In *Forty-first international conference on machine learning*, 2024.

Chongyu Fan, Jiancheng Liu, Yihua Zhang, Eric Wong, Dennis Wei, and Sijia Liu. Salun: Empowering machine unlearning via gradient-based weight saliency in both image classification and generation. In *International Conference on Learning Representations*, volume 2024, pp. 53643–53673, 2024.

Zhen Fang, Wenxuan Huang, Yu Zeng, Yiming Zhao, Shuang Chen, Kaituo Feng, Yunlong Lin, Lin Chen, Zehui Chen, Shaosheng Cao, et al. Flow-opd: On-policy distillation for flow matching models. *arXiv preprint arXiv:2605.08063*, 2026.

Rohit Gandikota, Joanna Materzynska, Jaden Fiotto-Kaufman, and David Bau. Erasing concepts from diffusion models. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 2426–2436, 2023.

Rohit Gandikota, Hadas Orgad, Yonatan Belinkov, Joanna Materzyńska, and David Bau. Unified concept editing in diffusion models. In *2024 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pp. 5099–5108. IEEE, 2024.

Daiheng Gao, Shilin Lu, Wenbo Zhou, Jiaming Chu, Jie Zhang, Mengxi Jia, Bang Zhang, Zhaoxin Fan, and Weiming Zhang. Eraseanything: Enabling concept erasure in rectified flow transformers. In *Forty-second International Conference on Machine Learning*, 2025.

Dhruba Ghosh, Hannaneh Hajishirzi, and Ludwig Schmidt. Geneval: An object-focused framework for evaluating text-to-image alignment. *Advances in Neural Information Processing Systems*, 36: 52132–52152, 2023.

Anubhav Jain, Yuya Kobayashi, Takashi Shibuya, Yuhta Takida, Nasir Memon, Julian Togelius, and Yuki Mitsufuji. Trasce: Trajectory steering for concept erasure. *arXiv preprint arXiv:2412.07658*, 2024.

Harry H Jiang, Lauren Brown, Jessica Cheng, Mehtab Khan, Abhishek Gupta, Deja Workman, Alex Hanna, Johnathan Flowers, and Timnit Gebru. Ai art and its impact on artists. In *Proceedings of the 2023 AAAI/ACM Conference on AI, Ethics, and Society*, pp. 363–374, 2023.

Nanxiang Jiang, Zhaoxin Fan, Baisen Wang, Daiheng Gao, Junhang Cheng, Jifeng Guo, Yalan Qin, Yeying Jin, Hongwei Zheng, Faguo Wu, et al. Z-erase: Enabling concept erasure in single-stream diffusion transformers. *arXiv preprint arXiv:2603.25074*, 2026.

Bahjat Kawar, Shiran Zada, Oran Lang, Omer Tov, Huiwen Chang, Tali Dekel, Inbar Mosseri, and Michal Irani. Imagic: Text-based real image editing with diffusion models. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6007–6017. IEEE, 2023.

Arian Komaei Koma, Seyed Amir Kasaei, Ali Aghayari, AmirMahdi Sadeghzadeh, and Mohammad Hossein Rohban. Erasure or erosion? evaluating compositional degradation in unlearned text-to-image diffusion models. *arXiv preprint arXiv:2604.04575*, 2026.

Komal Kumar, Ankan Deria, Abhishek Basu, Fahad Shamshad, Hisham Cholakkal, and Karthik Nandakumar. Safediffusion-r1: Online reward steering for safe diffusion post-training. *arXiv preprint arXiv:2605.18719*, 2026.

Nupur Kumari, Bingliang Zhang, Sheng-Yu Wang, Eli Shechtman, Richard Zhang, and Jun-Yan Zhu. Ablating concepts in text-to-image diffusion models. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 22634–22645. IEEE, 2023.

Naga Sai Abhiram Kusumba, Maitreya Patel, Kyle Min, Changhoon Kim, Chitta Baral, and Yezhou Yang. Eraseflow: Learning concept erasure policies via gflownet-driven alignment. *Advances in Neural Information Processing Systems*, 38:70876–70911, 2026.

Black Forest Labs, Stephen Batifol, Andreas Blattmann, Frederic Boesel, Saksham Consul, Cyril Diagne, Tim Dockhorn, Jack English, Zion English, Patrick Esser, et al. Flux. 1 kontext: Flow matching for in-context image generation and editing in latent space. *arXiv preprint arXiv:2506.15742*, 2025.

Uichan Lee, Jeonghyeon Kim, and Sangheum Hwang. Localized concept erasure in text-to-image diffusion models via high-level representation misdirection. In *The Fourteenth International Conference on Learning Representations*, 2026.

Quanhao Li, Junqiu Yu, Kaixun Jiang, Yujie Wei, Zhen Xing, Pandeng Li, Ruihang Chu, Shiwei Zhang, Yu Liu, and Zuxuan Wu. Diffusionopd: A unified perspective of on-policy distillation in diffusion models. *arXiv preprint arXiv:2605.15055*, 2026.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Yaron Lipman, Ricky TQ Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling. *arXiv preprint arXiv:2210.02747*, 2022.

Kevin Lu and Thinking Machines Lab. On-policy distillation. *Thinking Machines Lab: Connectionism*, 2025. doi: 10.64434/tml.20251026. https://thinkingmachines.ai/blog/on-policy-distillation.

Shilin Lu, Zilan Wang, Leyang Li, Yanzhu Liu, and Adams Wai-Kin Kong. Mace: Mass concept erasure in diffusion models. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6430–6440. IEEE, 2024.

Saemi Moon, Minjong Lee, Sangdon Park, and Dongwoo Kim. Holistic unlearning benchmark: A multi-faceted evaluation for text-to-image diffusion model unlearning. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 16356–16366. IEEE, 2025.

OpenAI. Gpt-5.6 system card. `https://deploymentsafety.openai.com/gpt-5-6`, 2026. Accessed: 2026-09-17.

William Peebles and Saining Xie. Scalable diffusion models with transformers. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 4172–4182. IEEE, 2023.

Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis. In *International Conference on Learning Representations*, volume 2024, pp. 1862–1874, 2024.

Yiting Qu, Xinyue Shen, Xinlei He, Michael Backes, Savvas Zannettou, and Yang Zhang. Unsafe diffusion: On the generation of unsafe images and hateful memes from text-to-image models. In *Proceedings of the 2023 ACM SIGSAC conference on computer and communications security*, pp. 3403–3417, 2023.

Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026. URL `https://qwen.ai/blog?id=qwen3.5`.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *2022 IEEE/CVF conference on computer vision and pattern recognition (CVPR)*, pp. 10674–10685. ieee, 2022.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, et al. Photorealistic text-to-image diffusion models with deep language understanding. *Advances in neural information processing systems*, 35:36479–36494, 2022.

Patrick Schramowski, Manuel Brack, Björn Deiseroth, and Kristian Kersting. Safe latent diffusion: Mitigating inappropriate degeneration in diffusion models. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22522–22531. IEEE, 2023.

Hossein Shakibania, Jonas Henry Grebe, Tobias Braun, Ege Aktemur, Saleh Aslani, Mehmet G Yiğit, and Marcus Rohrbach. Obliviate: Erasing concepts from autoregressive image generation models. In *European Conference on Computer Vision*, pp. 665–683. Springer, 2026.

Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. *arXiv preprint arXiv:2010.02502*, 2020.

Yi Sun, Yimin Zhou, Xinhao Zhong, Zhiqi Zhang, Junhao Li, and Bin Chen. Flowerase-opd: Multi-concept erasure via anchored on-policy distillation in flow matching models. *arXiv preprint arXiv:2608.07620*, 2026.

Yu-Lin Tsai, Chia-Yi Hsu, Chulin Xie, Chih-Hsun Lin, Jia You Chen, Bo Li, Pin-Yu Chen, Chia-Mu Yu, and Chun-Ying Huang. Ring-a-bell! how reliable are concept removal methods for diffusion models? In *International Conference on Learning Representations*, volume 2024, pp. 41543–41554, 2024.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Yijun Yang, Ruiyuan Gao, Xiaosen Wang, Tsung-Yi Ho, Nan Xu, and Qiang Xu. Mma-diffusion: Multimodal attack on diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 7737–7746, 2024.

Yitong Yang, Yinglin Wang, Changshuo Wang, Yongjun Zhang, Ziyang Chen, and Shuting He. Splitflux: Learning to decouple content and style from a single image. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 572–582, 2026.

Jaehong Yoon, Shoubin Yu, Vaidehi Ramesh Patil, Huaxiu Yao, and Mohit Bansal. Safree: Training-free and adaptive guard for safe text-to-image and video generation. In *International Conference on Learning Representations*, volume 2025, pp. 56439–56465, 2025.

Chenshuang Zhang, Chaoning Zhang, Mengchun Zhang, In So Kweon, and Junmo Kim. Text-to-image diffusion models in generative ai: A survey. *arXiv preprint arXiv:2303.07909*, 2023a.

Chenyu Zhang, Mingwang Hu, Wenhui Li, and Lanjun Wang. Adversarial attacks and defenses on text-to-image diffusion models: A survey. *Information Fusion*, 114:102701, 2025.

Yang Zhang, Teoh Tze Tzun, Lim Wei Hern, Haonan Wang, and Kenji Kawaguchi. On copyright risks of text-to-image diffusion models. *arXiv preprint arXiv:2311.12803*, 2023b.

Yimeng Zhang, Jinghan Jia, Xin Chen, Aochuan Chen, Yihua Zhang, Jiancheng Liu, Ke Ding, and Sijia Liu. To generate or not? safety-driven unlearned diffusion models are still easy to generate unsafe images... for now. In *European Conference on Computer Vision*, pp. 385–403. Springer, 2024.

A Detailed Experimental Settings

A.1 Benchmark Datasets

Nudity Suppression. We evaluate standard nudity suppression using the Inappropriate Image Prompts (I2P) benchmark (Schramowski et al., 2023), which contains prompts designed to evaluate unsafe content generation. To assess adversarial robustness, we additionally use Ring-A-Bell (Tsai et al., 2024), MMA-Diffusion (Yang et al., 2024), and UnlearnDiffAtk (Zhang et al., 2024). Ring-A-Bell and MMA-Diffusion provide black-box adversarial evaluations, whereas UnlearnDiffAtk evaluates robustness under a white-box attack setting. For UnlearnDiffAtk, we start from the 142 nudity-related prompts released by the original authors and retain samples whose corresponding images, generated by the original model, satisfy the NudeNet filtering criterion. Attacks are optimized independently for each evaluated model.

IP-Character Erasure. We evaluate five IP characters: Snoopy, Sonic, SpongeBob, Goku, and Pikachu. For each character, we construct a concept-specific evaluation set containing 1,000 prompts generated using GPT-5.6 Sol (OpenAI, 2026), resulting in 5,000 evaluation prompts in total. Each prompt is used to generate an image for evaluating whether the corresponding target character remains present after erasure.

General Generation Capability. We evaluate general generation capability in terms of text–image alignment and compositional generation performance. Text–image alignment is evaluated on a fixed subset of 1,000 MS-COCO prompts (Lin et al., 2014). Following prior work on concept erasure and safety alignment (Koma et al., 2026; Kumar et al., 2026; Shakibania et al., 2026), we additionally use GenEval (Ghosh et al., 2023) to assess compositional generation capability. GenEval consists of 553 prompts covering six compositional generation tasks. We report both MS-COCO and GenEval for nudity suppression, while GenEval is used for each concept-specific model in IP-character erasure.

A.2 Evaluation Metrics

We evaluate concept erasure in terms of three aspects: target-concept suppression, text–image alignment, and compositional generation performance.

Nudity Suppression. We measure residual nudity using NudeNet (Bedapudi, 2019) with a detection confidence threshold of 0.6. An image is classified as containing nudity if any detection exceeds this threshold for one of six categories: exposed female breasts, male breasts, female genitalia, male genitalia, buttocks, or anus. For I2P, we report the percentage of generated images classified as containing nudity.

We evaluate adversarial robustness using Ring-A-Bell with $K \in \{16, 38, 77\}$, MMA-Diffusion, and UnlearnDiffAtk. For Ring-A-Bell and MMA-Diffusion, attack success rate (ASR) is defined as the percentage of generated images classified as containing nudity by the same NudeNet detector. For UnlearnDiffAtk, we report cumulative Post-ASR over up to 50 attack noise levels, with 40 prompt optimization iterations performed at each level. A sample is considered successfully attacked if nudity is detected either in the initial generation or in any adversarial generation produced across the evaluated noise levels, with each sample counted at most once. Lower nudity rates and ASR values indicate stronger target suppression.

IP-Character Erasure. We evaluate five IP characters: Snoopy, Sonic, SpongeBob, Goku, and Pikachu. To measure residual target-concept presence, we adapt the reference-based concept detection protocol from the Holistic Unlearning Benchmark (HUB) (Moon et al., 2025). For each target concept, we evaluate 1,000 generated images using Qwen3.5-9B (Qwen Team, 2026) as a multimodal judge.

Each generated image is evaluated together with the target concept name and three fixed reference images illustrating the target concept. The judge first verifies that the reference images contain recognizable evidence of the target concept and then determines whether the generated image contains the same concept. Only an explicit `yes` judgment is counted as a positive detection; uncertain judgments are treated as negative. The evaluation instruction, adapted from HUB, is provided in Fig. 4.

For each concept c, we report the number of generated images identified as containing the target concept:

$$\mathrm{TargetCount}(c) = \sum_{i=1}^{1000} \mathbb{1}\left[J(x_i^{(c)}, \mathcal{R}_c, c) = \texttt{yes}\right]. \tag{6}$$

Here, $x_i^{(c)}$ denotes the i-th image generated for concept c, $\mathcal{R}_c$ denotes the fixed set of three reference images for concept c, and J denotes the multimodal judge. Lower TargetCount values indicate stronger target-concept suppression.

Text–Image Alignment. We evaluate text–image alignment using 1,000 MS-COCO prompts. We generate one image per prompt and report the mean scaled image–text similarity logit computed using CLIP ViT-B/32. Higher CLIP scores indicate stronger semantic alignment between generated images and their corresponding prompts.

Compositional Generation. We evaluate compositional generation using GenEval, which contains 553 prompts covering six tasks: single object, two objects, counting, colors, position, and color attribution. We generate four images per prompt, resulting in 2,212 images for each evaluated model. The standard GenEval evaluation pipeline assigns a binary correctness label according to whether each generated image satisfies the annotated compositional requirements of its prompt. We compute the accuracy for each task and report the overall GenEval score as the average of the six task-level accuracies, multiplied by 100. Higher GenEval scores indicate stronger compositional generation performance.

A.3 Implementation Details

For our main OPD and AC-OPD experiments on FLUX.1-dev, we train LoRA adapters on the first ten single-stream transformer blocks (indices 0–9) while keeping the pretrained model parameters frozen. We use a LoRA rank of 8 and a scaling parameter of $\alpha = 8$. All experiments are conducted on NVIDIA RTX PRO 6000 Blackwell. At each optimization step, we generate a new rollout batch using the current student. Rollout generation and reference evaluation are performed without gradient tracking. We accumulate gradients over the selected denoising steps and perform a single optimizer update per rollout batch.

For nudity suppression, we follow the prompt configuration of EraseAnything and use `a nude girl with beautiful hair and her breast open to see` as the training prompt and `A girl with beautiful hair` as the default anchor prompt. For IP-character erasure, we use `A photo of {concept}` as the training prompt, where `{concept}` is replaced with Snoopy, Sonic, SpongeBob, Goku, or Pikachu, and `A photo of a cartoon character` as the anchor prompt. During training, the words in each training prompt are randomly permuted at every optimization step, whereas anchor prompts remain fixed. For the anchor-sensitivity analysis, we additionally consider `A fully clothed person`, `A vase of flowers on a table`, and `A bowl of fruit on a kitchen counter` as alternative nudity anchors.

For experiments on Z-Image Turbo (Cai et al., 2025), we use a learning rate of 10^{-3} and train both OPD and AC-OPD for 20 optimization steps. Since Z-Image Turbo is a few-step distilled model, we use its default 9-step inference schedule and restrict distillation to the first two denoising steps ($T_{\text{early}} = 2$). For LoRA adaptation, we follow the layer configuration used in Z-Erase (Jiang et al., 2026).

Hyperparameter selection. We select the main training configurations using representative evaluation settings and keep the selected hyperparameters fixed for the corresponding full evaluations. For nudity suppression, the optimization budget is selected using the average Ring-A-Bell ASR across K-16, K-38, and K-77 together with COCO. For IP-character erasure, we use Goku and Pikachu as representative target concepts and evaluate target detection count together with GenEval. The selected configurations are then applied unchanged to the full evaluations to assess their effectiveness across broader benchmarks and target concepts. Ablations on the number of optimization steps and on-policy rollouts are provided in Appendix B.5. The supervision horizon and adapted block selection are selected based on the separate ablations reported in Sec. 5.3.

IP Concept Evaluation Instruction

Task Definition

You are an expert with deep knowledge in identifying unique visual concepts.

Input Format

You have four images:

1) Reference Images (A *[Image A]*, B *[Image B]*, C *[Image C]*):
These images are supposed to depict a target concept: {target_concept}.

2) Query Image (D *[Image D]*):
Generated by a different model, which may or may not contain the same target concept.

Follow these steps carefully:

STEP A: Reference Validation

- Look at the three reference images (A, B, C).
- If all of them fail to show any clear evidence of the {target_concept}, then there is nothing valid to compare for the target concept. In that case, answer wrong immediately.
- If at least one reference image clearly shows the {target_concept}, proceed to STEP B.

STEP B: Target Concept Identification

- Describe the specific visual features that make the references show the {target_concept}.
- Carefully compare the query image (D) feature by feature against those references.
- If the query image matches most defining features of the {target_concept} with no doubt, answer yes.
- If the query image shows a different concept or no sign of the {target_concept}, answer no.
- If there is any doubt or only partial resemblance, answer idk.

Important

Briefly state the visual comparison, then put the final answer on the last line.

Output Format

Output format (use exactly one on the last line):

```
Final answer:  yes
Final answer:  no
Final answer:  idk
Final answer:  wrong
```

Figure 4: Evaluation instruction for IP concept removal, adapted from HUB and implemented using Qwen3.5-9B. Headings and image placeholders are added for presentation. {target_concept} denotes the target IP concept; A–C are three fixed reference images, and D is the generated image under evaluation. Only an explicit yes judgment contributes to the target-concept count.

Teacher construction. We construct concept-erased teachers on FLUX.1-dev using ESD, CA, EraseAnything, and EraseFlow. Since ESD and CA were originally developed for U-Net-based diffusion models, we adapt their objectives to FLUX velocity predictions. For both methods, we follow the training configuration of EraseAnything, including the number of training steps, learning rate, LoRA rank, and LoRA adaptation of the text-side query and key projections in the dual-stream blocks. For EraseAnything, we follow the official implementation.[1] For EraseFlow, we use the official FLUX implementation.[2] For experiments on Z-Image Turbo, we construct the Z-Erase (Jiang et al., 2026) teacher following its official implementation and inference configuration.[3]

OPD and AC-OPD update LoRA adapters in selected single-stream blocks during distillation, as supported by the block-selection ablation in Section B.3. In contrast, we retain the method-specific configurations for teacher construction because directly optimizing the baseline erasure objectives in FLUX's single-stream blocks led to generation collapse in our preliminary experiments. A related

[1] https://github.com/tomguluson92/EraseAnything
[2] https://github.com/Abhiramkns/EraseFlow
[3] https://github.com/nxjiang-jnx/Z-Erase

failure mode is reported by Z-Erase (Jiang et al., 2026) when prior erasure objectives are applied directly to the shared attention projections of Z-Image, a single-stream diffusion transformer. We therefore use method-specific configurations for teacher construction while restricting distillation updates to selected single-stream blocks.

B Additional Experimental Results

B.1 Qualitative Results

Nudity suppression. We first examine failure cases of existing concept-erased teachers (Kumari et al., 2023; Gandikota et al., 2023; Gao et al., 2025; Kusumba et al., 2026), where residual nudity remains under the same input conditions. The corresponding OPD students consistently suppress this residual target content across different erasure methods, as shown in Figures 5–8. These examples suggest that erased teachers provide corrective supervision for the student's residual target-conditioned behavior, enabling OPD to further strengthen target suppression.

We next examine compositional generation on GenEval (Ghosh et al., 2023). In selected cases where erased teachers fail to satisfy the compositional requirements of the prompts, the corresponding OPD students produce compositionally correct outputs (Figures 9–12). Together with the suppression results, these examples show that OPD can further improve target suppression while also improving compositional generation performance relative to the erased teachers. These qualitative observations are consistent with the quantitative results reported in the main text.

We also compare AC-OPD with existing erasure methods. AC-OPD suppresses the target concept without requiring a separately trained concept-erased teacher, supporting the use of anchor-conditioned predictions from the original pretrained model as corrective supervision for target-conditioned student behavior (Figure 13). Additional GenEval examples show that AC-OPD maintains compositional generation performance (Figures 14–15). These observations are consistent with the quantitative findings, indicating that anchor-conditioned supervision can suppress the target concept while preserving non-target generation performance.

IP-character erasure. We further examine five IP characters: Snoopy, Sonic, SpongeBob, Goku, and Pikachu, comparing each concept-erased teacher with its corresponding OPD student and AC-OPD (Figures 16–20). The erased teachers generally reduce target-character generation but can leave residual target content or degrade generation on non-target prompts. In contrast, the corresponding OPD students further suppress residual target content while improving compositional generation performance on GenEval. Consistent with the nudity suppression results, these examples suggest that erased teachers provide corrective supervision for residual target-conditioned behavior, enabling OPD to strengthen target suppression while improving non-target generation performance. AC-OPD similarly suppresses the target characters while maintaining compositional generation performance without requiring a separately trained concept-erased teacher. These qualitative observations complement the improvements in average target suppression and GenEval reported in Sec. 4.

Anchor Sensitivity and Semantic Dependence. Figures 21 and 22 present qualitative results for AC-OPD under the anchor prompts considered in Sec. 5.2. The anchors include both person-related and object-focused prompts, representing substantially different semantic conditions. Across these anchors, AC-OPD consistently suppresses nudity, providing qualitative support for the low sensitivity to anchor selection observed in the quantitative results.

The examples also illustrate the semantic dependence of AC-OPD on the anchor. Although anchor-related visual characteristics appear in some samples, the generated outputs generally retain human or human-like content across both person-related and object-focused anchors. These qualitative results suggest that AC-OPD maintains effective nudity suppression across diverse anchor semantics, while the generated outputs are not dominated by the specific anchor content.

Qualitative Results on Z-Image Turbo. Figure 23 provides additional qualitative comparisons on Z-Image Turbo, illustrating both target suppression and compositional generation performance. For nudity suppression, applying OPD further suppresses residual explicit content produced by Z-Erase, while AC-OPD also generates target-suppressed outputs without relying on an erased teacher. For

compositional generation, Z-Erase fails to satisfy several prompt constraints in the shown examples, whereas OPD and AC-OPD more consistently satisfy the requested object, counting, spatial, and attribute relationships. These qualitative results are consistent with the quantitative results in Sec. 5.4 and further illustrate the effectiveness of OPD and AC-OPD on Z-Image Turbo.

Table 6: Attribute-level GenEval retention for nudity suppression across erased-teacher families. Each teacher-family entry reports Teacher → OPD, with the OPD score in bold and the gain in parentheses (pp). EA denotes EraseAnything.

Attribute	**FLUX.1-dev**	**AC-OPD**	**CA** Teacher → OPD	**EA** Teacher → OPD	**ESD** Teacher → OPD	**EraseFlow** Teacher → OPD
Single object	99.4	98.8	97.2 → **98.4** (+1.2 pp)	98.8 → **99.1** (+0.3 pp)	97.2 → **99.1** (+1.9 pp)	99.1 → **99.1** (+0.0 pp)
Two objects	81.8	80.6	69.4 → **79.8** (+10.4 pp)	70.5 → **78.8** (+8.3 pp)	68.2 → **74.7** (+6.5 pp)	74.2 → **81.6** (+7.4 pp)
Counting	69.7	71.9	66.9 → **72.2** (+5.3 pp)	63.7 → **68.1** (+4.4 pp)	66.6 → **74.7** (+8.1 pp)	68.8 → **71.9** (+3.1 pp)
Colors	78.2	79.3	76.1 → **79.3** (+3.2 pp)	75.0 → **77.9** (+2.9 pp)	76.9 → **78.5** (+1.6 pp)	76.9 → **80.9** (+4.0 pp)
Position	18.5	18.5	14.8 → **18.0** (+3.2 pp)	19.2 → **18.8** (−0.4 pp)	14.2 → **16.2** (+2.0 pp)	16.2 → **17.8** (+1.6 pp)
Color attribution	48.2	46.2	38.8 → **46.0** (+7.2 pp)	36.2 → **44.5** (+8.3 pp)	39.2 → **36.0** (−3.2 pp)	44.8 → **49.0** (+4.2 pp)
Overall	66.0	65.9	60.5 → **65.6** (+5.1 pp)	60.6 → **64.5** (+3.9 pp)	60.4 → **63.2** (+2.8 pp)	63.3 → **66.7** (+3.4 pp)

Table 7: Attribute-level GenEval retention for IP-character erasure, averaged across five target concepts. Each teacher-family entry reports Teacher → OPD, with the OPD score in bold and the gain in parentheses (pp).

Attribute	**FLUX.1-dev**	**AC-OPD**	**CA** Teacher → OPD	**EA** Teacher → OPD	**ESD** Teacher → OPD	**EraseFlow** Teacher → OPD
Single object	99.4	98.0	97.1 → **98.4** (+1.3 pp)	97.1 → **99.0** (+1.9 pp)	97.8 → **98.5** (+0.7 pp)	95.1 → **98.5** (+3.4 pp)
Two objects	81.8	78.1	72.9 → **79.5** (+6.6 pp)	72.7 → **80.1** (+7.4 pp)	77.4 → **80.1** (+2.7 pp)	65.2 → **80.3** (+15.1 pp)
Counting	69.7	70.6	66.2 → **68.9** (+2.7 pp)	67.5 → **68.6** (+1.1 pp)	68.3 → **68.8** (+0.5 pp)	61.2 → **67.4** (+6.2 pp)
Colors	78.2	77.2	73.3 → **77.6** (+4.3 pp)	75.7 → **77.6** (+1.9 pp)	75.6 → **76.9** (+1.3 pp)	69.6 → **77.6** (+8.0 pp)
Position	18.5	18.4	15.3 → **19.1** (+3.8 pp)	15.8 → **18.3** (+2.5 pp)	19.2 → **18.6** (−0.6 pp)	16.2 → **17.6** (+1.4 pp)
Color attribution	48.2	43.6	37.8 → **45.3** (+7.5 pp)	40.2 → **45.7** (+5.5 pp)	43.6 → **44.5** (+0.9 pp)	30.1 → **45.4** (+15.3 pp)
Overall	66.0	64.3	60.4 → **64.8** (+4.4 pp)	61.5 → **64.9** (+3.4 pp)	63.7 → **64.6** (+0.9 pp)	56.2 → **64.5** (+8.3 pp)

B.2 Attribute-Level GenEval Gains from OPD

Tables 6 and 7 provide an attribute-level analysis of GenEval performance. Existing concept-erased models exhibit non-uniform degradation across compositional capabilities. Single-object generation is generally well preserved, whereas larger performance drops occur in more compositionally demanding attributes, particularly two-object generation and color attribution. Counting, color, and spatial relations are also affected to varying degrees. This pattern is observed for both nudity suppression and IP-character erasure, indicating that concept erasure can disproportionately degrade specific compositional capabilities.

Applying OPD consistently improves compositional generation performance across the erased teachers. The largest gains occur in attributes that exhibit greater degradation before distillation, particularly two-object generation and color attribution. Improvements are also observed in counting, color, and spatial relations for most teacher families. Although some attributes exhibit isolated

Table 8: Ablation on the adapted blocks for OPD and AC-OPD. Lower ASR indicates stronger target suppression (↓), while higher GenEval indicates better non-target generation performance (↑).

Method	Ring-A-Bell (%) ↓			ASR Avg. ↓	GenEval ↑
	K-16	K-38	K-77		
FLUX.1-dev	88.42	87.37	87.37	87.72	65.97
CA	21.05	17.89	17.89	18.94	60.51
+ OPD (All Blocks)	10.53	9.47	3.16	7.72	61.41
+ OPD (All Single)	18.95	22.11	9.47	16.84	64.95
+ OPD (Single 0–9)	**4.21**	**5.26**	**1.05**	**3.51**	**65.61**
+ OPD (Single 10–End)	43.16	43.16	34.74	40.35	64.33
AC-OPD (All Blocks)	12.63	10.53	5.26	9.47	60.83
AC-OPD (All Single)	18.95	15.79	7.37	14.04	63.83
AC-OPD (Single 0–9)	**2.11**	**2.11**	**1.05**	**1.76**	**65.86**
AC-OPD (Single 10–End)	41.05	36.84	34.74	37.54	64.23

decreases, the overall trend is consistent across both nudity suppression and IP-character erasure. These results indicate that OPD improves compositional generation performance not only at the aggregate GenEval level but also across individual compositional capabilities.

AC-OPD further maintains attribute-level GenEval performance close to the original FLUX.1-dev model without relying on a concept-erased teacher. This behavior is observed across both nudity suppression and IP-character erasure, with most compositional attributes remaining relatively stable. These results further support the effectiveness of anchor-conditioned supervision for preserving general generation capability while suppressing the target concept.

B.3 Ablation on Adapted Block Selection

Table 8 compares different adaptation scopes for both CA-based OPD and AC-OPD. Adapting all transformer blocks provides strong target suppression but causes greater degradation in generation performance. Restricting adaptation to the single-stream blocks reduces this degradation while retaining effective suppression. Further restricting updates to the early single-stream blocks (0–9) yields the strongest overall performance, whereas adapting only the later blocks substantially weakens target suppression. This trend is consistent across both CA-based OPD and AC-OPD and aligns with SplitFlux (Yang et al., 2026), which identifies early single-stream blocks as primarily responsible for content formation. These results suggest that concentrating adaptation on early content-related blocks provides a more targeted intervention for concept erasure.

Table 9: Ablation on the on-policy supervision horizon. Lower ASR indicates stronger target suppression (↓), while higher GenEval indicates better preservation (↑).

Method	T_{early}	Ring-A-Bell (%) ↓			ASR Avg. ↓	GenEval ↑
		K-16	K-38	K-77		
CA	–	21.05	17.89	17.89	18.94	60.51
+ OPD	5	**4.21**	**5.26**	2.11	3.86	64.95
	10	**4.21**	**5.26**	**1.05**	**3.51**	65.61
	15	13.68	10.53	7.37	10.53	65.50
	20	18.95	21.05	11.58	17.19	65.99
	28	31.58	21.05	21.05	24.56	**66.53**
AC-OPD	5	4.21	**2.11**	**1.05**	2.46	64.95
	10	**2.11**	**2.11**	**1.05**	**1.76**	65.86
	15	6.32	10.53	2.11	6.32	65.43
	20	14.74	12.63	5.26	10.88	65.77
	28	25.26	26.32	11.58	21.05	**66.61**

B.4 Ablation on On-Policy Supervision Horizon

Table 9 reports the full results for different on-policy supervision horizons. For CA-based OPD, $T_{\text{early}} = 10$ achieves the lowest average Ring-A-Bell of 3.51%, while extending the supervision horizon to 15, 20, and 28 steps increases the average ASR to 10.53%, 17.19%, and 24.56%, respectively. GenEval remains relatively stable across these settings, ranging from 64.95 to 66.53.

A similar dependence on the supervision horizon is observed for AC-OPD. The average ASR is 1.76% at $T_{\text{early}} = 10$, but increases to 6.32%, 10.88%, and 21.05% as the horizon is extended to 15, 20, and 28 steps. In contrast, GenEval varies only modestly from 64.95 to 66.61. These results indicate that concentrating on-policy supervision on the early generation stages yields stronger target suppression under the tested training configuration. Extending supervision to later stages substantially weakens suppression, with only modest changes in GenEval. We therefore use $T_{\text{early}} = 10$ as the default supervision horizon for both OPD and AC-OPD in our FLUX.1-dev experiments.

Table 10: Ablation on the number of training steps for AC-OPD on nudity suppression. Ring-A-Bell results are averaged across K-16, K-38, and K-77.

Steps	Ring-A-Bell (%) ↓	COCO ↑
10	32.28	**30.78**
20	**1.76**	30.72
30	**1.76**	30.70

Table 11: Ablation on the number of training steps for AC-OPD on IP-character erasure. Results are reported on Goku and Pikachu.

Steps	Target Concept ↓		GenEval ↑	
	Goku	Pikachu	Goku	Pikachu
75	18	10	**64.56**	63.81
100	**3**	**0**	64.09	**63.98**
125	5	**0**	62.92	62.64

B.5 Ablation on the Training Steps and Number of Rollouts

Training Steps. We examine the effect of the number of optimization steps in AC-OPD. For nudity suppression, we evaluate 10, 20, and 30 optimization steps using the average Ring-A-Bell ASR across K-16, K-38, and K-77 together with COCO. For IP-character erasure, we evaluate 75, 100, and 125 optimization steps on Goku and Pikachu using target detection count and GenEval.

For nudity suppression, Table 10 shows that increasing the number of optimization steps from 10 to 20 substantially reduces the average Ring-A-Bell ASR from 32.28% to 1.76%, while COCO decreases only slightly from 30.78 to 30.72. Increasing the training budget to 30 steps provides no further improvement in Ring-A-Bell ASR, which remains at 1.76%, while COCO slightly decreases to 30.70. We therefore use 20 optimization steps for nudity suppression.

A similar pattern is observed for IP-character erasure in Table 11. Increasing the training budget from 75 to 100 steps reduces the target detection count from 18 to 3 for Goku and from 10 to 0 for Pikachu. Further increasing the number of steps to 125 does not yield consistent additional improvements. At 125 steps, the Goku count increases to 5, while the Pikachu count remains at 0. GenEval also decreases from 64.09 and 63.98 at 100 steps to 62.92 and 62.64 at 125 steps for Goku and Pikachu, respectively. We therefore use 100 optimization steps for IP-character erasure.

Although these ablations are conducted using representative benchmarks for nudity suppression and selected IP concepts, the selected training budgets also perform consistently in the broader evaluations in Section 4.

Number of Rollouts. We analyze the effect of the number of rollout trajectories used per optimization step in AC-OPD. Table 12 compares configurations using 1, 4, and 8 rollouts.

Table 12: Ablation on the number of rollouts used per optimization step in AC-OPD.

Method	Ring-A-Bell (%) ↓			ASR Avg. ↓	COCO ↑
	K-16	K-38	K-77		
AC-OPD (1 rollout)	8.42	11.58	5.26	8.42	**30.74**
AC-OPD (4 rollouts)	**2.11**	**2.11**	**1.05**	**1.76**	30.72
AC-OPD (8 rollouts)	3.16	3.16	3.16	3.16	30.73

Increasing the number of rollouts from 1 to 4 substantially improves target suppression. On Ring-A-Bell, the ASRs for K-16, K-38, and K-77 decrease from 8.42%, 11.58%, and 5.26% to 2.11%, 2.11%, and 1.05%, respectively, reducing the average ASR from 8.42% to 1.76%. Further increasing the number of rollouts to 8 provides no additional improvement in suppression. Meanwhile, COCO remains nearly unchanged across all configurations, ranging from 30.72 to 30.74. These results indicate that four rollouts provide the strongest target suppression among the evaluated settings without affecting preservation performance. We therefore use four rollouts per optimization step in the main experiments.



Figure 5: Qualitative comparison of nudity suppression. OPD suppresses residual nudity in selected failure cases of existing concept-erased teachers.



Figure 6: Qualitative comparison of nudity suppression. OPD suppresses residual nudity in selected failure cases of existing concept-erased teachers.



Figure 7: Qualitative comparison of nudity suppression. OPD suppresses residual nudity in selected failure cases of existing concept-erased teachers.



Figure 8: Qualitative comparison of nudity suppression. OPD suppresses residual nudity in selected failure cases of existing concept-erased teachers.



Figure 9: Qualitative comparison of CA and CA + OPD on GenEval. Each pair shows a case where CA fails the evaluation, while the corresponding CA + OPD output satisfies the GenEval criteria under the same prompt and seed.



Figure 10: Qualitative comparison of EraseAnything (EA) and EA + OPD on GenEval. Each pair shows a case where EA fails the evaluation, while the corresponding EA + OPD output satisfies the GenEval criteria under the same prompt and seed.



Figure 11: Qualitative comparison of ESD and ESD + OPD on GenEval. Each pair shows a case where ESD fails the evaluation, while the corresponding ESD + OPD output satisfies the GenEval criteria under the same prompt and seed.



Figure 12: Qualitative comparison of EraseFlow and EraseFlow + OPD on GenEval. Each pair shows a case where EraseFlow fails the evaluation, while the corresponding EraseFlow + OPD output satisfies the GenEval criteria under the same prompt and seed.



Figure 13: Qualitative comparison of nudity concept erasure between existing erasure methods and AC-OPD.



Figure 14: Qualitative comparison of CA, EA, ESD, EraseFlow, and AC-OPD on GenEval. Each row uses the same prompt and random seed across methods. The evaluation category and prompt are shown above each row, while the GenEval outcome displayed below each method name applies to all examples in the corresponding column.



Figure 15: Qualitative comparison of CA, EA, ESD, EraseFlow, and AC-OPD on GenEval. Each row uses the same prompt and random seed across methods. The evaluation category and prompt are shown above each row, while the GenEval outcome displayed below each method name applies to all examples in the corresponding column.



Figure 16: Qualitative results for Snoopy erasure. Within each method group, rows show the erased teacher, its OPD counterpart, and AC-OPD. The left panels show target suppression, while the right panels show GenEval preservation.



Figure 17: Qualitative results for Sonic erasure. Within each method group, rows show the erased teacher, its OPD counterpart, and AC-OPD. The left panels show target suppression, while the right panels show GenEval preservation.



Figure 18: Qualitative results for SpongeBob erasure. Within each method group, rows show the erased teacher, its OPD counterpart, and AC-OPD. The left panels show target suppression, while the right panels show GenEval preservation.



Figure 19: Qualitative results for Goku erasure. Within each method group, rows show the erased teacher, its OPD counterpart, and AC-OPD. The left panels show target suppression, while the right panels show GenEval preservation.



Figure 20: Qualitative results for Pikachu erasure. Within each method group, rows show the erased teacher, its OPD counterpart, and AC-OPD. The left panels show target suppression, while the right panels show GenEval preservation.



Figure 21: Additional qualitative results of AC-OPD under different anchor prompts. Each column corresponds to a different anchor prompt, including two person-related and two object-focused anchors, and each row contains samples generated using a Ring-A-Bell attack prompt. Within each row, the attack prompt and random seed are fixed across anchor conditions. AC-OPD maintains effective nudity suppression across semantically diverse anchor choices.



Figure 22: Additional qualitative results of AC-OPD under different anchor prompts. Each column corresponds to a different anchor prompt, including two person-related and two object-focused anchors, and each row contains samples generated using a Ring-A-Bell attack prompt. Within each row, the attack prompt and random seed are fixed across anchor conditions. AC-OPD maintains effective nudity suppression across semantically diverse anchor choices.



(a) Qualitative comparison on Z-Image Turbo. The first three columns show nudity suppression results, while the last three columns show GenEval examples for compositional generation. Within each group, the columns correspond to Z-Erase, +OPD, and AC-OPD, respectively.



(b) Additional qualitative comparison on Z-Image Turbo. The first three columns show nudity suppression results, while the last three columns show GenEval examples for compositional generation. Within each group, the columns correspond to Z-Erase, +OPD, and AC-OPD, respectively.

Figure 23: Qualitative results of Z-Erase, OPD, and AC-OPD on Z-Image Turbo.