# Beyond SFT-to-RL: Pre-alignment via Black-box On-policy Distillation for Multimodal RL

**Sudong Wang**[1*] **Weiquan Huang**[1*] **Xiaomin Yu**[1] **Zuhao Yang**[3] **Hehai Lin**[1]
**Keming Wu**[2] **Chaojun Xiao**[2] **Chen Chen**[3] **Wenxuan Wang**[4] **Beier Zhu**[5]
**Yunjian Zhang**[6†] **Chengwei Qin**[1,7†]

[1]Hong Kong University of Science and Technology (Guangzhou)
[2]Tsinghua University [3]Nanyang Technological University
[4]Renmin University of China [5]University of Science and Technology of China
[6]University of Chinese Academy of Sciences
[7]Hong Kong University of Science and Technology
{swang886, whuang491}@connect.hkust-gz.edu.cn

## Abstract

The standard post-training recipe for large multimodal models (LMMs) applies supervised fine-tuning (SFT) on curated demonstrations followed by reinforcement learning with verifiable rewards (RLVR). However, SFT introduces distributional drift that neither preserves the model's original capabilities nor faithfully matches the supervision distribution. This problem is further amplified in multimodal reasoning, where perception errors and reasoning failures follow distinct drift patterns that compound during subsequent RL. We introduce **PRISM**, a three-stage pipeline that mitigates this drift by inserting an explicit distribution-alignment stage between SFT and RLVR. Building on the principle of on-policy distillation (OPD), PRISM casts alignment as a black-box, response-level adversarial game between the policy and a Mixture-of-Experts (MoE) discriminator with dedicated perception and reasoning experts, providing disentangled corrective signals that steer the policy toward the supervision distribution without requiring access to teacher logits. While 1.26M public demonstrations suffice for broad SFT initialization, distribution alignment demands higher-fidelity supervision; we therefore curate 113K additional demonstrations from Gemini 3 Flash, featuring dense visual grounding and step-by-step reasoning on the hardest unsolved problems. Experiments on Qwen3-VL show that PRISM consistently improves downstream RLVR performance across multiple RL algorithms (GRPO, DAPO, GSPO) and diverse multimodal benchmarks, improving average accuracy by +4.4 and +6.0 points over the SFT→RLVR baseline on 4B and 8B, respectively. Our code, data, and model checkpoints are publicly available at `https://github.com/XIAO4579/PRISM`.

## 1 Introduction

Driven by the success of reasoning-oriented large language models (LLMs) [1–4], large multimodal models (LMMs) have also demonstrated strong instruction-following and reasoning capabilities [5, 6]. A prevailing paradigm for improving such capabilities is a two-stage post-training pipeline: models are first adapted via offline supervised fine-tuning (SFT) on curated demonstrations [7, 8], and then further optimized with online reinforcement learning with verifiable rewards (RLVR) [9, 10],

[*]Equal contribution.
[†]Corresponding authors.

40th Conference on Neural Information Processing Systems (NeurIPS 2026).




Figure 1: Overview of the PRISM pipeline. (a) SFT introduces distributional drift between the policy and the supervision distribution. (b) The alignment stage uses an MoE discriminator with dedicated perception and reasoning experts to repair this drift via adversarial on-policy distillation. (c) The resulting distribution-aligned policy provides a stronger initialization for downstream RLVR.

which directly improves task performance using automatic verifiers. In this pipeline, SFT provides a crucial capability bootstrap by anchoring the model to high-quality supervision, while RLVR further refines the policy toward task-specific objectives and largely determines the final performance. As a result, a growing body of work has focused on improving the effectiveness and stability of both stages. For SFT, recent methods optimize it by reweighting or regularizing next-token likelihood [11, 12]. For RLVR, a number of approaches have been proposed to improve optimization stability and reduce variance, including GRPO-style variants that redesign importance weighting and clipping mechanisms to stabilize policy updates [13–17]. The underlying intuition is straightforward: SFT establishes an implicit reasoning prior in the model's parameter space, whereas RLVR activates and refines this capability through online optimization [18, 19].

However, recent studies have uncovered a striking and counterintuitive phenomenon: instead of reliably improving the model, offline supervision may place the model in a compromised state, where it neither adequately matches the demonstration policy distribution nor retains the model's original favorable distribution [20, 21]. In this sense, SFT can become a source of distributional drift rather than a pure improvement step. A plausible explanation is that SFT optimizes the model to imitate trajectories sampled from the demonstration policy under a uniform token-level objective, without distinguishing between process and outcome. As a result, the model may learn surface-level patterns rather than faithful reasoning capabilities, and simultaneously drift away from its original distribution. While this drift is often tolerable for weaker models that gain substantially from learning the demonstration policy, it becomes increasingly costly as the base model grows stronger: when the model already possesses a capable reasoning distribution, token-level imitation of an external demonstration policy can displace the model's native strengths rather than supplement them [21, 20]. This issue becomes particularly pronounced in multimodal models, where the distributional bias introduced by SFT interacts with imperfect visual grounding: even slight deviations at the perception stage can distort the premises of reasoning and subsequently amplify errors throughout RL [22, 18]. Moreover, unlike the relatively uniform drift in text-only models, multimodal drift is inherently heterogeneous: visual grounding and logical reasoning degrade in qualitatively different ways that a single corrective objective cannot jointly address. This raises a natural question: **How can we repair the distributional drift introduced by SFT, particularly its heterogeneous impact on visual perception and reasoning, before the model enters RL?**

Advances in knowledge distillation suggest that a model can benefit substantially from learning from its own on-policy generations rather than relying solely on static teacher-forced targets [23–25]. By optimizing on rollouts sampled from its current policy, on-policy distillation (OPD) mitigates exposure bias and encourages more faithful policy refinement [23, 26]. Building on this principle, we propose **PR**e-alignment via black-box on-policy d**IS**tillation for **M**ultimodal reinforcement learning (PRISM), a new three-stage post-training paradigm that extends the standard SFT→RL recipe with an explicit pre-alignment stage. The core of PRISM is an adversarial OPD framework that drives the post-SFT

policy distribution toward the supervision distribution, while introducing a logit-free formulation that eliminates the external-teacher dependency of standard OPD. Specifically, we formulate alignment as a minimax game [27] between the policy and a Mixture-of-Experts (MoE) discriminator with dedicated vision and reasoning experts. The discriminator learns to separate policy rollouts from the supervision pool by probing both perceptual grounding and reasoning consistency, while the policy is optimized to generate responses that increasingly resemble the supervision distribution. This design establishes a critical distribution-level alignment stage after SFT, not only correcting distributional drift but also preparing a more reliable initialization for online optimization.

We validate PRISM on Qwen3-VL across diverse multimodal benchmarks and multiple RL algorithms. The results confirm consistent improvements over the standard SFT→RLVR pipeline, and further analysis shows that the alignment stage substantially narrows the distributional gap left by SFT. An overview of the PRISM pipeline is shown in Figure 1.

In summary, our main contributions are as follows:

- We identify the distributional mismatch left by SFT as a bottleneck for multimodal RLVR, and propose PRISM, which addresses it through black-box adversarial on-policy pre-alignment before RLVR, using an MoE discriminator that provides decoupled corrective signals for perception and reasoning drift.
- We curate a 113K high-quality multimodal reasoning corpus distilled from Gemini 3 Flash, targeting the hardest problems unsolved by current LMMs with dense visual grounding and step-by-step reasoning traces. Combined with 1.26M publicly available demonstrations from the same model family, this corpus serves as both the SFT foundation and the supervision reference for distribution alignment.
- Experiments on Qwen3-VL-4B/8B validate that PRISM consistently and substantially improves downstream RLVR, with PRISM+GRPO outperforming SFT→GRPO by +4.4 and +6.0 average points on the two scales, respectively, and similar gains are observed across DAPO and GSPO.

## 2 Related Work

### 2.1 Reinforcement Learning for Multimodal Reasoning

Reinforcement learning with verifiable rewards (RLVR) has emerged as a dominant paradigm for improving reasoning in both large language models and large multimodal models (LMMs). In the text domain, DeepSeek-R1 [1] demonstrated that pure RL with verifiable rewards can elicit emergent chain-of-thought reasoning without human-labeled traces, motivating a series of algorithmic improvements that enhance optimization stability at scale through redesigned clipping, advantage estimation, critic-free architectures, or sequence-level objectives [9, 28, 13, 29, 14]. In the multimodal domain, early efforts explored R1-style RL for LMMs via cold-start initialization [30], cross-modal formalization [31], large-scale rule-based RL with emergent reflection [32, 33], curriculum-based sampling [34], self-reflection incentivization [35], and tool-augmented agentic video reasoning [36]. More recently, a line of work has recognized that vanilla RLVR neglects visual perception fidelity, and proposed perception-aware reward signals through judging LLMs [37], evidence-anchored dual-branch reasoning [38], or differential visual reasoning with visual triplets [39]. While these methods advance multimodal reasoning through better RL algorithms or reward designs, their improvements all take place *within* the RL stage, leaving untouched the distributional drift introduced by SFT, which compromises the starting point of RL optimization. PRISM does not improve RL itself, but instead inserts black-box on-policy distillation as a bridging stage between SFT and RL to correct this drift.

### 2.2 On-Policy Distillation

Standard knowledge distillation for LLMs performs SFT on teacher-generated outputs, but this off-policy approach suffers from a distribution mismatch between training and inference. On-policy distillation (OPD) addresses this by training the student on its own generations: GKD [24] introduced the paradigm with flexible divergence objectives, followed by explorations of alternative divergences [23, 40] and logit-free adversarial formulations [41]. Recent extensions further broaden OPD along complementary axes such as self-distillation [25], reward extrapolation [42], selective imitation [43], and multimodal representation transfer [44]. Despite these advances, most existing OPD methods treat distillation as a terminal training objective where the resulting checkpoint serves

directly as the final model, and rely on a single undifferentiated discriminator or divergence signal. PRISM instead positions OPD as an intermediate alignment stage that explicitly prepares the policy for subsequent RLVR, and employs an MoE discriminator with dedicated vision and reasoning experts to provide decoupled rewards that address the heterogeneous nature of multimodal distribution shift. In the multimodal setting, VOLD [45] combines GRPO with logit-based on-policy distillation from a text-only teacher into a unified training objective. PRISM differs in three key respects: it decouples alignment from RL as a standalone intermediate stage, it operates without teacher logits via adversarial discrimination, and it provides decoupled feedback through dedicated perception and reasoning experts.

# 3 Method

We present PRISM, a three-stage post-training pipeline that augments the conventional SFT→RL paradigm with an intermediate pre-alignment stage. Specifically, PRISM first performs SFT on high-quality demonstrations to obtain an initial policy, then applies adversarial OPD with an MoE discriminator to recalibrate the post-SFT policy distribution, and finally conducts outcome-based RLVR for final policy improvement. The complete procedure is provided in Appendix F; we describe each stage in turn below.

## 3.1 Cold-Start Supervised Fine-Tuning

As the first stage of PRISM, SFT serves as a cold start that equips the model with an initial multimodal reasoning policy. Since the same supervision source is later reused in the alignment stage for distribution-level correction, each sample must contain not only a correct final answer but also a complete reasoning trajectory with accurate visual grounding. Existing public multimodal datasets are often inadequate for this purpose, as many contain brief answers, incomplete reasoning traces, or imprecise visual descriptions.

To address this, we curate a 113K multimodal reasoning corpus following [46, 47]: we collect problems with zero pass rate under strong contemporary models, generate detailed solutions with Gemini 3 Flash [48] requiring fine-grained visual grounding and step-by-step deduction, and apply multi-stage filtering including format validation and LLM-based correctness verification (details in Appendix D). Among the resulting samples, 107K are used for SFT and the remaining 6K are reserved for the alignment and RL stages. Since a policy trained on insufficient data remains far from the target distribution, placing an excessive corrective burden on the downstream alignment stage, we supplement our curated corpus with 1.26M publicly available demonstrations from the same Gemini model family [49], yielding a combined SFT corpus of approximately 1.37M samples.

Using the combined corpus, we perform standard supervised fine-tuning to obtain an initial reasoning-capable policy. As we show next, however, SFT alone does not guarantee a distribution well suited for subsequent RL optimization, motivating the explicit pre-alignment stage.

## 3.2 Distribution Alignment via On-Policy Distillation

### 3.2.1 Overview

The alignment stage repairs the distributional drift introduced by SFT before the model enters RLVR. As discussed in Section 1, the post-SFT policy may only partially absorb the target behavior while drifting away from its native distribution. Directly passing such a policy to RLVR forces online optimization to start from a distorted state, limiting the gains that RL can deliver. A natural idea is to apply additional token-level imitation, but this only encourages surface-level matching without repairing the mismatch that emerges under on-policy generation. Moreover, the supervision data may originate from proprietary black-box models whose logits are inaccessible, rendering divergence-based distillation inapplicable. We therefore formulate alignment as a response-level adversarial game that requires only samples from the supervision pool. A further challenge is that distributional drift in multimodal reasoning is inherently heterogeneous: visual grounding errors and reasoning failures require qualitatively different corrections. This motivates a Mixture-of-Experts discriminator with dedicated perception and reasoning experts. The overall architecture is illustrated in Figure 2.




Figure 2: Architecture of the distribution-alignment stage. An MoE discriminator with perception and reasoning experts is trained via Bradley-Terry loss to distinguish supervision from policy outputs; the policy is updated via policy gradient to maximize the combined MoE reward.

### 3.2.2 Mixture-of-Experts Discriminator

To provide targeted corrective signals for heterogeneous errors in multimodal reasoning, we instantiate the alignment module with an MoE discriminator. The key idea is that deviations from the supervision distribution typically arise from two distinct sources: failures in visual grounding and failures in logical reasoning. A single discriminator is often too coarse to capture these two error modes simultaneously. We therefore decompose the discrimination process into two specialized experts, each responsible for one aspect of the response. Concretely, each response $y$ for multimodal input $x$ consists of a visual description $c$ and a reasoning trace $t$. We define two experts in the discriminator:

- **Perception Expert** $D_v$: evaluates the visual description $c$ and measures how well the response is grounded in the visual input;
- **Reasoning Expert** $D_r$: evaluates the reasoning trace $t$ and measures the consistency and validity of the underlying deduction.

The discriminator score is then defined as a weighted combination of the two expert scores:

$$r(x, y) = \alpha \cdot D_v(x, c) + (1 - \alpha) \cdot D_r(x, t), \tag{1}$$

where $\alpha$ controls the trade-off between perceptual and reasoning feedback.

By delivering disentangled feedback on the two dominant sources of multimodal error rather than collapsing them into a single scalar, the MoE discriminator provides a finer-grained basis for the adversarial alignment objective introduced next.

### 3.2.3 Initialization for Alignment

The adversarial alignment stage assumes that the policy and the discriminator are reasonably matched in capability. In practice, however, a pretrained LMM before alignment remains far from the supervision distribution, making its responses trivially separable from reference demonstrations. Under such a large gap, the discriminator can quickly saturate, leaving the policy with uninformative training signals [50, 51]. We therefore initialize both components before entering the adversarial phase.

**Policy initialization.** The policy is initialized from the SFT checkpoint described in Section 3.1, which narrows the gap between policy rollouts and the supervision distribution sufficiently for adversarial training to begin.

**MoE discriminator initialization.** Both experts are initialized from the same pretrained backbone and warm-started on their designated components: $D_v$ on preference pairs from visual descriptions, $D_r$ on preference pairs from reasoning traces. An auxiliary load-balancing loss [52] prevents expert collapse during this stage.

### 3.2.4 Adversarial On-Policy Distillation

With all components properly initialized, we formulate the alignment stage as a minimax game between the policy $G$ and the MoE discriminator. The policy is optimized to generate responses that increasingly resemble high-quality reference demonstrations, while the discriminator is trained to separate the two. Through this adversarial interaction, the policy distribution is progressively driven toward the reference distribution, yielding a more faithfully aligned model before RLVR.

Specifically, the MoE discriminator assigns a scalar score to each response based on both perceptual grounding and reasoning consistency. Let $\mathcal{T}$ denote the supervision data from which reference pairs are drawn. Given a policy response $y^-$ and a reference response $y^+$, we train the discriminator to assign a higher score to the reference and a lower score to the policy rollout by minimizing its Bradley-Terry loss:

$$\mathcal{L}_{D_k} = -\mathbb{E}_{(x,y^+,y^-)\sim\mathcal{T}}\left[\log\sigma\big(D_k(x,y_k^+) - D_k(x,y_k^-)\big)\right], \qquad k \in \{v, r\}, \tag{2}$$

where $y_k^+$ and $y_k^-$ denote the $k$-th component of the reference response $y^+$ and the policy response $y^-$, respectively, with $k = v$ corresponding to the visual description and $k = r$ corresponding to the reasoning trace. Here, $y^- \sim G(\cdot \mid x)$ is sampled from the current policy, and $\sigma(\cdot)$ is the sigmoid function. Importantly, both experts are optimized jointly with the policy throughout alignment, so that they function as on-policy discriminators that continuously adapt to the evolving rollout distribution. This design avoids the reward staleness issue that commonly arises when the reward model is fixed while the policy keeps changing.

The policy is optimized to improve the quality of its own rollouts under the reward provided by the MoE discriminator. For each input $x$, we sample a group of $N$ responses $\{y_i^-\}_{i=1}^N$ from the current policy $G(\cdot \mid x)$, and evaluate each response with the discriminator reward $r(x, y_i^-)$. We convert these rewards into normalized group-wise advantages:

$$A_i = \frac{r(x,y_i^-) - \mathrm{mean}\big(\{r(x,y_j^-)\}_{j=1}^N\big)}{\mathrm{std}\big(\{r(x,y_j^-)\}_{j=1}^N\big)}, \tag{3}$$

where the normalization is performed within each rollout group. In this way, the policy is encouraged to increase the probability of responses that are scored as more consistent with the supervision distribution, while suppressing inferior rollouts from the same prompt. Taken together, the two objectives define a minimax game between the policy and the discriminator:

$$\min_{\theta}\max_{\phi}\ \mathbb{E}_{(x,y^+)\sim\mathcal{T},\, y^-\sim G_\theta(\cdot|x)}\Big[r_\phi(x,y^+) - r_\phi(x,y^-)\Big], \tag{4}$$

where $\theta$ and $\phi$ denote the parameters of the policy and discriminator, respectively.

We alternate between updating the policy via GRPO and updating the two discriminator experts with their respective Bradley-Terry losses. Notably, we remove the KL regularization term commonly used to anchor the policy near its SFT initialization, since such a constraint would directly oppose the goal of correcting SFT-induced distributional drift. The alignment stage is run for a fixed number of steps, after which the resulting checkpoint is used to initialize the final RLVR stage.

## 3.3 Reinforcement Learning with Verifiable Rewards

The final stage of PRISM applies standard outcome-based RLVR to the aligned checkpoint produced in Section 3.2. To construct the RL training set, we filter the 6K reserved samples by difficulty, retaining the 2K instances whose pass rate under the aligned policy falls in $[0.2, 0.8]$ [53, 54]. At this stage, the reward switches from the learned MoE discriminator to a deterministic verifiable reward. The reward combines answer accuracy $r_{\text{acc}}$ and format compliance $r_{\text{fmt}}$:

$$r_{\text{v}}(x,y) = 0.8\, r_{\text{acc}}(x,y) + 0.2\, r_{\text{fmt}}(x,y). \tag{5}$$

Policy optimization follows the same GRPO-style objective as in the alignment stage, with the discriminator reward replaced by $r_{\text{v}}$. Importantly, PRISM is agnostic to the specific RL algorithm; in our experiments, we instantiate this stage with GRPO [9], DAPO [13], and GSPO [14].

Table 1: Accuracy (%) on mathematical reasoning and general multimodal benchmarks. **Bold** indicates the best result within each base model. Shaded rows denote PRISM (ours).

| Method | Math Benchmarks | | | | General Benchmarks | | | Avg. |
|---|---|---|---|---|---|---|---|---|
| | **MathVista** testmini | **MathVerse** testmini | **MathVision** testmini | **WeMath** testmini | **MMMU** val | **MMMU-Pro** overall | **Hallusion Bench** | |
| | | | | ***Qwen3-VL-4B*** | | | | |
| Instruct | 74.9 | 59.0 | 36.5 | 70.7 | 63.6 | 45.1 | 68.2 | 59.7 |
| + SFT | 71.5 | 58.4 | 31.9 | 70.6 | 53.6 | 42.8 | 69.1 | 56.8 |
| + GRPO | 75.7 | 64.5 | 35.5 | 77.8 | 60.1 | 47.3 | 72.0 | 61.8 |
| + DAPO | 74.3 | 65.1 | 42.7 | 77.2 | 62.5 | 48.0 | 72.3 | 63.2 |
| + GSPO | 75.2 | 64.0 | 37.5 | 78.4 | 58.7 | 45.6 | 71.9 | 61.6 |
| PRISM | 71.0 | 59.5 | 30.6 | 67.5 | 56.3 | 42.8 | 72.6 | 57.2 |
| + GRPO | **77.9** | **68.6** | 45.4 | 82.9 | **64.1** | 49.7 | **74.8** | 66.2 |
| + DAPO | 77.8 | 68.2 | **46.7** | **83.9** | **64.1** | 50.4 | 72.9 | **66.3** |
| + GSPO | 77.5 | 66.6 | **46.7** | 82.3 | 63.2 | **51.1** | 72.9 | 65.8 |
| | | | | ***Qwen3-VL-8B*** | | | | |
| Instruct | 76.0 | 62.4 | 43.7 | 71.7 | 65.6 | 52.3 | 71.6 | 63.3 |
| + SFT | 70.2 | 60.4 | 32.6 | 73.4 | 56.3 | 42.9 | 71.2 | 58.1 |
| + GRPO | 75.9 | 66.9 | 37.1 | 79.7 | 62.6 | 48.8 | 71.9 | 63.3 |
| + DAPO | 77.0 | 69.8 | 41.5 | 84.3 | 63.0 | 49.0 | 71.5 | 65.2 |
| + GSPO | 75.9 | 65.5 | 41.1 | 80.8 | 58.2 | 47.8 | 73.6 | 63.3 |
| PRISM | 71.4 | 62.2 | 37.1 | 73.1 | 58.4 | 43.4 | 69.5 | 59.3 |
| + GRPO | **78.3** | 71.3 | **52.0** | **86.4** | **66.6** | **53.3** | **77.2** | **69.3** |
| + DAPO | 78.2 | 70.9 | **52.0** | 86.2 | 66.2 | 52.4 | 76.1 | 68.9 |
| + GSPO | 77.9 | **71.5** | 51.6 | 85.9 | 65.2 | 52.7 | 75.8 | 68.7 |

# 4 Experiments

## 4.1 Experimental Setup

**Models.** We use Qwen3-VL-4B and Qwen3-VL-8B [5] as the base models, and Gemini 3 Flash as the supervision source for data construction. The MoE discriminator follows the Qwen3-VL-MoE architecture [5], constructed by assembling four Qwen3-VL-2B models as expert modules with top-2 routing. The two expert scores $D_v$ and $D_r$ are obtained by passing the visual description and reasoning trace through this single MoE model separately, then combined via Eq. (1).

**Training details.** We follow the three-stage pipeline described in Section 3: SFT for 1 epoch on the full supervision dataset, distribution alignment for 500 steps, and RLVR for 1500 steps with verifiable rewards. Detailed hyperparameters for all stages (learning rates, batch sizes, $\alpha$, rollout temperature, group size $N$, etc.) are provided in Appendix A.

**Benchmarks.** We evaluate on two groups of benchmarks. For mathematical reasoning, we use MathVista [55], MathVerse [56], MathVision [57], and WeMath [58]. For general multimodal understanding, we use MMMU [59], MMMU-Pro [60], and HallusionBench [61].

**Baselines.** We compare against the following: (1) Qwen3-VL models without post-training, (2) SFT-only models trained on the full dataset, and (3) the standard SFT→RLVR pipeline without the alignment stage, using GRPO [9] and trained with additional RLVR steps equal to the alignment stage to match the number of policy optimization updates. For the PRISM pipeline, we report results with GRPO, DAPO [13], and GSPO [14] in the RLVR stage to demonstrate algorithm-agnostic improvements.

## 4.2 Main Results

Table 1 presents results across both model scales and three RL algorithms. We highlight three key observations.

**PRISM consistently improves downstream RLVR.** PRISM+GRPO outperforms the SFT→GRPO baseline by +4.4 and +6.0 average points on 4B and 8B, respectively, with the largest gains concentrated on MathVision and WeMath across both scales. Similar improvements hold for DAPO and GSPO, confirming that the alignment stage provides a consistently better initialization regardless of the downstream RL algorithm. Moreover, PRISM+GRPO achieves these gains while using fewer tokens per response (Appendix A.3).

**Alignment improves distribution, not immediate accuracy.** The PRISM row, representing the checkpoint after alignment but before RLVR, shows accuracy comparable to the SFT checkpoint on both scales. This is expected: the alignment objective is distributional correction, reshaping the model's visual descriptions and reasoning traces to better match the supervision distribution, rather than directly optimizing for answer correctness. The value of this distributional shift is realized downstream, where every RL algorithm benefits from the improved initialization.

**SFT-induced drift is more pronounced for stronger models.** Consistent with the observation discussed in the introduction, SFT degrades the Instruct checkpoint on average across both scales, with the 8B model suffering a larger drop than 4B. On 8B, the standard SFT→RLVR pipeline with GRPO and GSPO barely recovers the original Instruct performance, indicating that RLVR alone cannot fully compensate for the distributional drift introduced by SFT on a model with an already-strong prior. In contrast, PRISM+GRPO exceeds the Instruct baseline by over 5 points, demonstrating that the alignment stage effectively repairs the drift and unlocks further gains from RLVR.

### 4.3 Ablation Study

All ablations are conducted on Qwen3-VL-4B with GRPO as the default RL algorithm.

Table 2: Ablation study results. The first row is the full PRISM pipeline (SFT-1.37M) for reference.

| Setting | Math Benchmarks | | | | General Benchmarks | | | Avg. |
|---|---|---|---|---|---|---|---|---|
| | **MathVista** testmini | **MathVerse** testmini | **MathVision** testmini | **WeMath** testmini | **MMMU** val | **MMMU-Pro** overall | **Hallusion Bench** | |
| PRISM (full) | 77.9 | 68.6 | 45.4 | 82.9 | 64.1 | 49.7 | 74.8 | 66.2 |
| *Discriminator design* | | | | | | | | |
| Dense 4B disc. | 74.6 | 63.7 | 41.8 | 76.9 | 61.3 | 47.1 | 74.0 | 62.8 |
| Text-only disc. | 74.0 | 59.5 | 42.8 | 76.8 | 62.7 | 48.5 | 71.6 | 62.3 |
| *Pipeline stages* | | | | | | | | |
| w/o SFT | 62.4 | 47.6 | 25.9 | 55.7 | 51.4 | 36.5 | 66.1 | 49.4 |
| w/o Alignment | 75.7 | 64.5 | 35.5 | 77.8 | 60.1 | 47.3 | 72.0 | 61.8 |
| *SFT data scale* | | | | | | | | |
| SFT-107K | 72.3 | 67.0 | 43.1 | 76.9 | 60.6 | 49.0 | 68.3 | 62.5 |

**Why does the MoE discriminator matter?** As shown in Table 2, replacing the MoE discriminator with a single dense model with equal activated compute leads to consistent degradation ($-3.4$ avg.), with the largest drops on WeMath ($-6.0$) and MathVerse ($-4.9$). The dense discriminator collapses perception and reasoning feedback into a single scalar: when the policy improves along one axis but regresses along the other, the monolithic reward cannot disentangle the two effects and the gradient signal becomes noisy. The MoE design avoids this by letting each expert specialize on its own domain. The training dynamics in Section 4.4 further confirm that the two experts converge along distinct trajectories, a structure that a single discriminator would inevitably conflate.

**Why is the three-stage pipeline necessary?** We ablate each training stage individually and find that strong performance emerges only with the full three-stage pipeline, consistent with the observation in [62] that each stage in a multi-stage post-training pipeline serves an indispensable role. Removing the alignment stage reduces the pipeline to standard SFT→RLVR with a $-4.4$ avg. drop, indicating that without explicit distribution correction, RLVR alone cannot fully compensate for the distributional drift inherited from SFT. Removing SFT leads to an even starker picture ($-16.8$ avg.): without cold-start initialization, the capability gap between the model and the supervision distribution is too large for adversarial training to function: the discriminator trivially separates the two distributions, and the policy drifts toward a degenerate output mode rather than converging toward the supervision distribution. Each stage thus serves an indispensable role: SFT provides initial competence and narrows the distribution gap enough for adversarial training to begin; alignment refines what the reasoning should look like by explicitly closing the residual gap with the supervision distribution; and RLVR optimizes whether the reasoning leads to a correct answer.

**Why must the discriminator be vision-language?** A natural question is whether the discriminator truly needs to see the image, or whether textual patterns alone carry enough signal. We replace the vision-language discriminator with a text-only variant of identical architecture. The text-only variant

can capture surface-level textual patterns such as formatting conventions, reasoning templates, and stylistic cues, but it cannot verify whether a visual description faithfully depicts the image content. The result is a form of "parrot alignment": the policy learns to sound like the supervision data without actually seeing what it describes. Consistently, the degradation is most pronounced on tasks that demand faithful visual perception, confirming that meaningful distribution alignment in the multimodal setting requires a discriminator that jointly processes vision and language.

**How important is SFT data scale?** When using only our curated 107K samples for SFT instead of the full 1.37M corpus (107K curated + 1.26M public), downstream RLVR performance drops by $-3.7$ avg. With less SFT supervision, the model starts further from the target distribution, widening the gap that the alignment stage must bridge. While alignment can partially compensate, as the reduced-data variant (62.5 avg.) still outperforms the SFT$\rightarrow$RLVR baseline trained on the full corpus but without alignment (61.8 avg.), it cannot fully recover from a weaker initialization. This confirms that SFT and alignment are complementary rather than substitutable: broad SFT data tightens the initial distribution gap, and alignment closes whatever residual gap remains.

### 4.4 Analysis

**Training dynamics.** We analyze the adversarial training dynamics of PRISM during the alignment stage by tracking the reward gap between supervision and policy responses, defined as $D_k(x, y_k^+) - D_k(x, y_k^-)$ for each expert $k \in \{v, r\}$. As shown in Figure 3, both experts exhibit a characteristic rise-then-convergence pattern, but with notably different trajectories that reflect the distinct nature of visual and reasoning alignment.




Figure 3: Training dynamics: reward gap (supervision $-$ policy) for the perception expert (left) and reasoning expert (right). Training runs for 500 steps; we additionally extend to 900 steps to verify convergence stability.

The perception expert peaks early and converges quickly, whereas the reasoning expert rises more gradually and exhibits greater oscillation before stabilizing, suggesting that reasoning alignment involves more nuanced distributional corrections than visual grounding. Despite these different trajectories, both experts converge to a comparable equilibrium level, confirming that the adversarial game reaches a stable state where the policy has been substantially realigned toward the supervision distribution along both axes.

This asynchronous convergence further supports the MoE design choice validated in the ablation study (Section 4.3).

**Structural Proxies of Distribution Alignment.** Since directly visualizing the full multimodal response distribution is difficult in such high-dimensional output spaces, we instead probe its evolution through interpretable structural proxies [63]. This choice is also consistent with prior work that analyzes model-generated reasoning traces through their structural qualities and patterns [64, 65]. Concretely, we focus on the two dimensions most relevant to PRISM: reasoning complexity and perceptual grounding granularity. We visualize the number of reasoning steps in the chain-of-thought trace and the number of descriptive items in the visual caption. We compute these statistics for the base model, the supervision data, and the policy checkpoints after SFT, alignment, and RLVR.

As shown in Figure 4, the base model deviates substantially from the supervision data under both proxies. After SFT, the response distributions shift toward supervision but remain visibly mismatched, particularly because the caption-side proxy tends to overshoot and produce more descriptive items than the supervision data contains. The alignment stage substantially reduces this mismatch along both dimensions. Importantly, this improvement persists through RLVR: the post-RLVR distributions continue to follow similar trends despite the shift in optimization




Figure 4: Structural proxies of distribution alignment: reasoning steps (left) and descriptive items per caption (right) across PRISM stages.

objective from distributional matching to outcome-based correctness. This suggests that the alignment stage provides a better-shaped initialization for subsequent RLVR, which further improves performance while preserving the alignment gains.

## 5 Conclusion

We present PRISM, a three-stage post-training pipeline that mitigates the distributional drift introduced by SFT through an explicit alignment stage based on black-box adversarial on-policy distillation. The core of PRISM is an MoE discriminator with dedicated perception and reasoning experts, which provides disentangled corrective signals to steer the post-SFT policy toward the supervision distribution under the model's own rollout dynamics. Extensive experiments on Qwen3-VL demonstrate that PRISM consistently improves downstream RLVR performance across multiple RL algorithms and diverse multimodal benchmarks. Analysis of training dynamics and response-structure distributions suggests that the alignment stage substantially narrows the distributional gap left by SFT, and that these corrections persist through subsequent RL optimization.

## References


[1] Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

[2] Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, et al. Openai o1 system card. *arXiv preprint arXiv:2412.16720*, 2024.

[3] An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

[4] Aohan Zeng, Xin Lv, Zhenyu Hou, Zhengxiao Du, Qinkai Zheng, Bin Chen, Da Yin, Chendi Ge, Chenghua Huang, Chengxing Xie, et al. Glm-5: from vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763*, 2026.

[5] Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*, 2025.

[6] Zhe Chen, Weiyun Wang, Yue Cao, Yangzhou Liu, Zhangwei Gao, Erfei Cui, Jinguo Zhu, Shenglong Ye, Hao Tian, Zhaoyang Liu, et al. Expanding performance boundaries of open-source multimodal models with model, data, and test-time scaling. *arXiv preprint arXiv:2412.05271*, 2024.

[7] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916, 2023.

[8] Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 26296–26306, 2024.

[9] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

[10] An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, et al. Qwen2. 5-math technical report: Toward mathematical expert model via self-improvement. *arXiv preprint arXiv:2409.12122*, 2024.

[11] Chongli Qin and Jost Tobias Springenberg. Supervised fine tuning on curated data is reinforcement learning (and can be improved). *arXiv preprint arXiv:2507.12856*, 2025.

[12] Wenhong Zhu, Ruobing Xie, Rui Wang, Xingwu Sun, Di Wang, and Pengfei Liu. Proximal supervised fine-tuning. *arXiv preprint arXiv:2508.17784*, 2025.

[13] Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, et al. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*, 2025.

[14] Chujie Zheng, Shixuan Liu, Mingze Li, Xiong-Hui Chen, Bowen Yu, Chang Gao, Kai Dang, Yuqiong Liu, Rui Men, An Yang, et al. Group sequence policy optimization. *arXiv preprint arXiv:2507.18071*, 2025.

[15] Yuzhong Zhao, Yue Liu, Junpeng Liu, Jingye Chen, Xun Wu, Yaru Hao, Tengchao Lv, Shaohan Huang, Lei Cui, Qixiang Ye, et al. Geometric-mean policy optimization. *arXiv preprint arXiv:2507.20673*, 2025.

[16] Yu Yue, Yufeng Yuan, Qiying Yu, Xiaochen Zuo, Ruofei Zhu, Wenyuan Xu, Jiaze Chen, Chengyi Wang, TianTian Fan, Zhengyin Du, et al. Vapo: Efficient and reliable reinforcement learning for advanced reasoning tasks. *arXiv preprint arXiv:2504.05118*, 2025.

[17] Ziqi Wang, Xingzhou Lou, Meiqi Wu, Zhengqi Wen, and Junge Zhang. Calibration-aware policy optimization for reasoning llms. *arXiv preprint arXiv:2604.12632*, 2026.

[18] Tianzhe Chu, Yuexiang Zhai, Jihan Yang, Shengbang Tong, Saining Xie, Dale Schuurmans, Quoc V Le, Sergey Levine, and Yi Ma. Sft memorizes, rl generalizes: A comparative study of foundation model post-training. *arXiv preprint arXiv:2501.17161*, 2025.

[19] Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Shiji Song, and Gao Huang. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model? *arXiv preprint arXiv:2504.13837*, 2025.

[20] Feiyang Kang, Michael Kuchnik, Karthik Padthe, Marin Vlastelica, Ruoxi Jia, Carole-Jean Wu, and Newsha Ardalani. Quagmires in sft-rl post-training: When high sft scores mislead and what to use instead. *arXiv preprint arXiv:2510.01624*, 2025.

[21] Dylan Zhang, Yufeng Xu, Haojin Wang, Qingzhi Chen, and Hao Peng. Good sft optimizes for sft, better sft prepares for reinforcement learning. *arXiv preprint arXiv:2602.01058*, 2026.

[22] Chengzhi Liu, Zhongxing Xu, Qingyue Wei, Juncheng Wu, James Zou, Xin Eric Wang, Yuyin Zhou, and Sheng Liu. More thinking, less seeing? assessing amplified hallucination in multimodal reasoning models. *arXiv preprint arXiv:2505.21523*, 2025.

[23] Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. Minillm: Knowledge distillation of large language models. In *The twelfth international conference on learning representations*, 2024.

[24] Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos Garea, Matthieu Geist, and Olivier Bachem. On-policy distillation of language models: Learning from self-generated mistakes. In *The twelfth international conference on learning representations*, 2024.

[25] Siyan Zhao, Zhihui Xie, Mengchen Liu, Jing Huang, Guan Pang, Feiyu Chen, and Aditya Grover. Self-distilled reasoner: On-policy self-distillation for large language models. *arXiv preprint arXiv:2601.18734*, 2026.

[26] Wen Zhang, Yang Feng, Fandong Meng, Di You, and Qun Liu. Bridging the gap between training and inference for neural machine translation. In *Proceedings of the 57th annual meeting of the association for computational linguistics*, pages 4334–4343, 2019.

[27] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *Communications of the ACM*, 63(11):139–144, 2020.

[28] Jian Hu. Reinforce++: A simple and efficient approach for aligning large language models. *arXiv e-prints*, pages arXiv–2501, 2025.

[29] Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. Understanding r1-zero-like training: A critical perspective. *arXiv preprint arXiv:2503.20783*, 2025.

[30] Wenxuan Huang, Bohan Jia, Zijie Zhai, Shaosheng Cao, Zheyu Ye, Fei Zhao, Zhe Xu, Xu Tang, Yao Hu, and Shaohui Lin. Vision-r1: Incentivizing reasoning capability in multimodal large language models. *arXiv preprint arXiv:2503.06749*, 2025.

[31] Yi Yang, Xiaoxuan He, Hongkun Pan, Xiyan Jiang, Yan Deng, Xingtao Yang, Haoyu Lu, Dacheng Yin, Fengyun Rao, Minfeng Zhu, et al. R1-onevision: Advancing generalized multimodal reasoning through cross-modal formalization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2376–2385, 2025.

[32] Fanqing Meng, Lingxiao Du, Zongkai Liu, Zhixiang Zhou, Quanfeng Lu, Daocheng Fu, Tiancheng Han, Botian Shi, Wenhai Wang, Junjun He, et al. Mm-eureka: Exploring the frontiers of multimodal reasoning with rule-based reinforcement learning. *arXiv preprint arXiv:2503.07365*, 2025.

[33] Kaichen Zhang, Keming Wu, Zuhao Yang, Bo Li, Kairui Hu, Bin Wang, Ziwei Liu, Xingxuan Li, and Lidong Bing. Openmmreasoner: Pushing the frontiers for multimodal reasoning with an open and general recipe. *arXiv preprint arXiv:2511.16334*, 2025.

[34] Wenyi Hong, Wenmeng Yu, Xiaotao Gu, Guo Wang, Guobing Gan, Haomiao Tang, Jiale Cheng, Ji Qi, Junhui Ji, Lihang Pan, et al. Glm-4.1 v-thinking: Towards versatile multimodal reasoning with scalable reinforcement learning. *arXiv e-prints*, pages arXiv–2507, 2025.

[35] Haozhe Wang, Chao Qu, Zuming Huang, Wei Chu, Fangzhen Lin, and Wenhu Chen. Vl-rethinker: Incentivizing self-reflection of vision-language models with reinforcement learning. *arXiv preprint arXiv:2504.08837*, 2025.

[36] Zuhao Yang, Kaichen Zhang, Sudong Wang, Keming Wu, Zhongyu Yang, Bo Li, Xiaojuan Qi, Shijian Lu, Xingxuan Li, and Lidong Bing. Paravt: Taming the tool prior paradox for parallel tool use in agentic video reinforcement learning. *arXiv preprint arXiv:2605.20342*, 2026.

[37] Tong Xiao, Xin Xu, Zhenya Huang, Hongyu Gao, Quan Liu, Qi Liu, and Enhong Chen. Perception-r1: Advancing multimodal reasoning capabilities of mllms via visual perception reward. *arXiv preprint arXiv:2506.07218*, 2025.

[38] Chi Zhang, Haibo Qiu, Qiming Zhang, Yufei Xu, Zhixiong Zeng, Siqi Yang, Peng Shi, Lin Ma, and Jing Zhang. Perceptual-evidence anchored reinforced learning for multimodal reasoning. *arXiv preprint arXiv:2511.18437*, 2025.

[39] Shujian Gao, Yuan Wang, Jiangtao Yan, Zuxuan Wu, and Yu-Gang Jiang. Thinking with deltas: Incentivizing reinforcement learning via differential visual reasoning policy. *arXiv preprint arXiv:2601.06801*, 2026.

[40] Jongwoo Ko, Sungnyun Kim, Tianyi Chen, and Se-Young Yun. Distillm: Towards streamlined distillation for large language models. *arXiv preprint arXiv:2402.03898*, 2024.

[41] Tianzhu Ye, Li Dong, Zewen Chi, Xun Wu, Shaohan Huang, and Furu Wei. Black-box on-policy distillation of large language models. *arXiv preprint arXiv:2511.10643*, 2025.

[42] Wenkai Yang, Weijie Liu, Ruobing Xie, Kai Yang, Saiyong Yang, and Yankai Lin. Learning beyond teacher: Generalized on-policy distillation with reward extrapolation. *arXiv preprint arXiv:2602.12125*, 2026.

[43] Zhaoyang Zhang, Shuli Jiang, Yantao Shen, Yuting Zhang, Dhananjay Ram, Shuo Yang, Zhuowen Tu, Wei Xia, and Stefano Soatto. Reinforcement-aware knowledge distillation for llm reasoning. *arXiv preprint arXiv:2602.22495*, 2026.

[44] Yuxuan Cai, Jiangning Zhang, Haoyang He, Xinwei He, Ao Tong, Zhenye Gan, Chengjie Wang, Zhucun Xue, Yong Liu, and Xiang Bai. Llava-kd: A framework of distilling multimodal large language models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 239–249, 2025.

[45] Walid Bousselham, Hilde Kuehne, and Cordelia Schmid. Vold: Reasoning transfer from llms to vision-language models via on-policy distillation. *arXiv preprint arXiv:2510.23497*, 2025.

[46] Yixin Ye, Zhen Huang, Yang Xiao, Ethan Chern, Shijie Xia, and Pengfei Liu. Limo: Less is more for reasoning. *arXiv preprint arXiv:2502.03387*, 2025.

[47] Honglin Lin, Zheng Liu, Yun Zhu, Chonghan Qin, Juekai Lin, Xiaoran Shang, Conghui He, Wentao Zhang, and Lijun Wu. Mmfinereason: Closing the multimodal reasoning gap via open data-centric methods. *arXiv preprint arXiv:2601.21821*, 2026.

[48] Google DeepMind. Gemini 3 flash. `https://deepmind.google/models/gemini/flash/`, 2025. Official model page, accessed 2026-04-23.

[49] Sicong Leng, Jing Wang, Jiaxi Li, Hao Zhang, Zhiqiang Hu, Boqiang Zhang, Yuming Jiang, Hang Zhang, Xin Li, Lidong Bing, et al. Mmr1: Enhancing multimodal reasoning with variance-aware sampling and open resources. *arXiv preprint arXiv:2509.21268*, 2025.

[50] Ian J Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

[51] Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pages 214–223. Pmlr, 2017.

[52] William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23 (120):1–39, 2022.

[53] Yiping Wang, Qing Yang, Zhiyuan Zeng, Liliang Ren, Liyuan Liu, Baolin Peng, Hao Cheng, Xuehai He, Kuan Wang, Jianfeng Gao, et al. Reinforcement learning for reasoning in large language models with one training example. *arXiv preprint arXiv:2504.20571*, 2025.

[54] Yunjian Zhang, Sudong Wang, Yang Li, Peiran Xu, Conghao Zhou, Xiaoyue Ma, Jianing Li, and Yao Zhu. Resource-efficient reinforcement for reasoning large language models via dynamic one-shot policy refinement. *arXiv preprint arXiv:2602.00815*, 2026.

[55] Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. *arXiv preprint arXiv:2310.02255*, 2023.

[56] Renrui Zhang, Dongzhi Jiang, Yichi Zhang, Haokun Lin, Ziyu Guo, Pengshuo Qiu, Aojun Zhou, Pan Lu, Kai-Wei Chang, Yu Qiao, et al. Mathverse: Does your multi-modal llm truly see the diagrams in visual math problems? In *European Conference on Computer Vision*, pages 169–186. Springer, 2024.

[57] Ke Wang, Junting Pan, Weikang Shi, Zimu Lu, Houxing Ren, Aojun Zhou, Mingjie Zhan, and Hongsheng Li. Measuring multimodal mathematical reasoning with math-vision dataset. *Advances in Neural Information Processing Systems*, 37:95095–95169, 2024.

[58] Runqi Qiao, Qiuna Tan, Guanting Dong, MinhuiWu MinhuiWu, Chong Sun, Xiaoshuai Song, Jiapeng Wang, Zhuoma Gongque, Shanglin Lei, Yifan Zhang, et al. We-math: Does your large multimodal model achieve human-like mathematical reasoning? In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 20023–20070, 2025.

[59] Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, et al. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9556–9567, 2024.

[60] Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Botao Yu, Ge Zhang, Huan Sun, et al. Mmmu-pro: A more robust multi-discipline multimodal understanding benchmark. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15134–15186, 2025.

[61] Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, et al. Hallusionbench: an advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 14375–14385, 2024.

[62] Zuhao Yang, Sudong Wang, Kaichen Zhang, Keming Wu, Sicong Leng, Yifan Zhang, Bo Li, Chengwei Qin, Shijian Lu, Xingxuan Li, et al. Longvt: Incentivizing" thinking with long videos" via native tool calling. *arXiv preprint arXiv:2511.20785*, 2025.

[63] Jian Tang, Jingzhou Liu, Ming Zhang, and Qiaozhu Mei. Visualizing large-scale and high-dimensional data. In *Proceedings of the 25th international conference on world wide web*, pages 287–297, 2016.

[64] Leena Mathur, Marian Qian, Paul Pu Liang, and Louis-Philippe Morency. Social genome: Grounded social reasoning abilities of multimodal models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 24879–24902, 2025.

[65] Gangwei Jiang, Yahui Liu, Zhaoyi Li, Wei Bi, Fuzheng Zhang, Linqi Song, Ying Wei, and Defu Lian. What makes a good reasoning chain? uncovering structural patterns in long chain-of-thought reasoning. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 6501–6525, 2025.

[66] Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, and Zheyan Luo. Llamafactory: Unified efficient fine-tuning of 100+ language models. In *Proceedings of the 62nd annual meeting of the association for computational linguistics (volume 3: system demonstrations)*, pages 400–410, 2024.

[67] Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pages 1279–1297, 2025.

[68] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th symposium on operating systems principles*, pages 611–626, 2023.

[69] Kaichen Zhang, Bo Li, Peiyuan Zhang, Fanyi Pu, Joshua Adrian Cahyono, Kairui Hu, Shuai Liu, Yuanhan Zhang, Jingkang Yang, Chunyuan Li, et al. Lmms-eval: Reality check on the evaluation of large multimodal models. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 881–916, 2025.

[70] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *arXiv preprint arXiv:2305.18290*, 2023.

[71] Harrison Lee, Samrat Phatale, Hassan Mansoor, Thomas Mesnard, Johan Ferret, Kellie Lu, Colton Bishop, Ethan Hall, Victor Carbune, Abhinav Rastogi, and Sushant Prakash. RLAIF vs. RLHF: Scaling reinforcement learning from human feedback with AI feedback. *arXiv preprint arXiv:2309.00267*, 2023.

[72] Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, et al. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*, 2025.

[73] Guowei Xu, Peng Jin, Ziang Wu, Hao Li, Yibing Song, Lichao Sun, and Li Yuan. Llava-cot: Let vision language models reason step-by-step. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2087–2098, 2025.

[74] Yihe Deng, Hritik Bansal, Fan Yin, Nanyun Peng, Wei Wang, and Kai-Wei Chang. OpenVL-Thinker: Complex vision-language reasoning via iterative SFT-RL cycles. *Advances in Neural Information Processing Systems*, 38:123817–123846, 2026.

[75] Runqi Qiao, Qiuna Tan, Peiqing Yang, Yanzi Wang, Xiaowan Wang, Enhui Wan, Sitong Zhou, Guanting Dong, Yuchen Zeng, Yida Xu, Jie Wang, et al. We-Math 2.0: A versatile MathBook system for incentivizing visual mathematical reasoning. *arXiv preprint arXiv:2508.10433*, 2025.

# A Implementation Details

## A.1 Training Details

We describe the training procedures for all three stages of the PRISM pipeline. The SFT stage is implemented using LlamaFactory [66], while the alignment and RLVR stages are both built on the veRL framework [67] with vLLM [68] as the inference engine. The full set of hyperparameters is provided in Table 3.

Table 3: Detailed training hyperparameters for each stage of the PRISM pipeline.

| **Training Component** | **SFT** | **PRISM** | **RLVR** |
|---|---|---|---|
| Optimizer | AdamW | AdamW | AdamW |
| Scheduler | cosine | constant | constant |
| Learning Rate | 1e-5 | 1e-6 | 1e-6 |
| Weight Decay | – | 0.01 | 0.01 |
| Epochs / Training Steps | 1 epoch | 500 steps | 1500 steps |
| Warmup Ratio / Steps | 0.1 | – | – |
| Global Batch Size | 2 | 4 | 32 |
| Max Prompt Length | – | 2048 | 2048 |
| Max Response Length | 8192 | 6144 | 8192 |
| Rollout Temperature | – | 1.0 | 1.0 |
| Group Size $N$ | – | 16 | 16 |
| $\alpha$ (MoE weight) | – | 0.5 | – |
| Accuracy Reward Weight | – | – | 0.8 |
| Format Reward Weight | – | – | 0.2 |
| Dynamic Bsz | – | True | True |
| Remove Padding | – | True | True |

**SFT.** We perform full-parameter fine-tuning on the language model while freezing the vision tower and the multimodal projector. We use a cutoff length of 8192 tokens with online stream packing to maximize training throughput and remove padding tokens to avoid unnecessary computation. Training is conducted for 1 epoch with a cosine learning rate schedule (peak 1e-5, warmup ratio 0.1) using DeepSpeed ZeRO-2.

**PRISM (Alignment).** The alignment stage jointly trains the policy and the MoE discriminator. The generator and discriminator share the same learning rate (1e-6). For each prompt, we sample $N = 16$ rollouts from the current policy with temperature 1.0. The MoE reward weight is set to $\alpha = 0.5$, giving equal importance to the perception and reasoning experts. We deliberately disable KL regularization (KL coefficient = 0.0) to allow the policy to shift freely toward the supervision distribution. We train for 500 steps, at which point both discriminator experts have converged to a stable equilibrium (see Figure 3), and select the final checkpoint for the subsequent RLVR stage.

**RLVR.** Starting from the alignment checkpoint, we apply outcome-based RLVR with a global batch size of 32 and $N = 16$ rollouts per prompt at temperature 1.0. All RL algorithms evaluated in our experiments share the same set of hyperparameters. The maximum response length is increased to 8192 tokens to accommodate longer reasoning traces. We train for up to 1500 steps, saving checkpoints periodically and selecting the best one based on validation performance. All experiments across all three stages are conducted on 8× NVIDIA H100-SXM5-80GB GPUs.

## A.2 Evaluation Details

For all evaluations, we use the lmms-eval framework [69] with vLLM [68] as the serving engine. We set the generation hyperparameters to `temperature=1.0`, `top_p=0.7`, and `top_k=-1` across all benchmarks. For MathVerse and HallusionBench, we follow their official protocols, which use an LLM judge for every response. For the remaining benchmarks, the extracted answer is validated using a two-stage process: a rule-based validator is first applied to minimize evaluation cost; if the rule-based validator marks the answer as incorrect, we fall back to an LLM-as-judge validator powered by Qwen3-30B-A3B-Instruct [3] with a conservative binary judging prompt (Figure 8). All methods share the same evaluation pipeline.

**Judge usage and robustness.** Table 4 reports the fraction of responses handled by the LLM judge on each benchmark. Pooled over all evaluated responses, judge usage is 37.1% on the rule-first settings and 58.6% overall. To assess sensitivity to the choice of judge, we re-judge all judge-handled responses with Qwen3-235B-A22B-Instruct [3]; aggregate scores change by less than 0.1 percentage points, and the ranking of methods and their relative gains are unchanged.

Table 4: Fraction of responses handled by the LLM judge on each evaluation setting.

| Evaluation setting | Judge usage |
|---|---|
| MathVista testmini | 27.4% |
| MathVision testmini | 58.2% |
| MMMU val | 39.6% |
| MMMU-Pro standard | 49.4% |
| MMMU-Pro vision | 53.9% |
| WeMath testmini | 20.0% |
| MathVerse testmini (official LLM-judge protocol) | 100% |
| HallusionBench (official LLM-judge protocol) | 100% |

### A.3 Token Efficiency

Figure 5 compares the accuracy and average token usage of three configurations on MathVision, MathVerse, and MMMU-Pro. Across all three benchmarks, PRISM+GRPO achieves higher accuracy than SFT+GRPO while using fewer tokens, suggesting that the alignment stage encourages more concise and effective reasoning rather than simply producing longer outputs.




Figure 5: Token efficiency comparison on MathVision, MathVerse, and MMMU-Pro (Qwen3-VL-4B). PRISM+GRPO achieves higher accuracy with fewer tokens across all three benchmarks.

## B Additional Controlled Experiments

This section examines whether the gains of PRISM can be attributed to the pre-alignment stage rather than to longer training, additional data, or the choice of objective. Owing to compute constraints, all experiments in this section use Qwen3-VL-4B with GRPO and are single runs. All RLVR runs use the same 2K RLVR subset and rollout configuration; except for Instruct and Instruct→GRPO, all methods start from the same SFT checkpoint. Results are summarized in Table 5.

**Matched updates and longer baseline training.** SFT→GRPO uses 2,000 RLVR updates, while PRISM uses 500 alignment and 1,500 RLVR updates, so the two pipelines are matched in the number of policy optimization updates but not in FLOPs, since PRISM additionally trains the MoE discriminator. To test whether the baseline is simply under-trained, we extend SFT→GRPO to 3,000 and 5,000 updates with the same data and settings. Its average accuracy plateaus at 61.8 and drops to 61.3 at 5,000 updates: WeMath improves, but most other benchmarks degrade, suggesting over-optimization on the RLVR training set. PRISM remains 4.4 points above the best extended

Table 5: Controlled comparisons on Qwen3-VL-4B (GRPO). Where shown, update counts are given as alignment / RLVR policy updates. **Bold** indicates the best result in each column.

| | Math Benchmarks | | | | General Benchmarks | | | |
|---|---|---|---|---|---|---|---|---|
| **Method** | **MathVista** | **MathVerse** | **MathVision** | **WeMath** | **MMMU** | **MMMU-Pro** | **HallusionBench** | **Avg.** |
| Instruct (no post-training) | 74.9 | 59.0 | 36.5 | 70.7 | 63.6 | 45.1 | 68.2 | 59.7 |
| *Longer RLVR training of the baseline* | | | | | | | | |
| SFT→GRPO (0 / 2,000) | 75.7 | 64.5 | 35.5 | 77.8 | 60.1 | 47.3 | 72.0 | 61.8 |
| SFT→GRPO (0 / 3,000) | 76.4 | 64.7 | 35.8 | 78.1 | 59.6 | 46.3 | 71.4 | 61.8 |
| SFT→GRPO (0 / 5,000) | 74.6 | 64.3 | 33.1 | 82.3 | 57.8 | 45.7 | 71.0 | 61.3 |
| *Alternative initialization and objective* | | | | | | | | |
| Instruct→GRPO | 77.5 | 65.6 | 39.8 | 77.1 | 63.9 | 48.6 | 73.9 | 63.8 |
| VOLD-style joint OPD+RL | 75.8 | 63.2 | 34.0 | 76.7 | 60.7 | 46.9 | 72.4 | 61.4 |
| *PRISM (staged)* | | | | | | | | |
| PRISM-2K→GRPO (500 / 1,500) | 77.7 | 68.3 | 44.9 | 82.6 | **64.3** | **49.8** | 74.6 | 66.0 |
| PRISM→GRPO (500 / 1,500) | **77.9** | **68.6** | **45.4** | **82.9** | 64.1 | 49.7 | **74.8** | **66.2** |

baseline while using 2,000 total policy updates, so within the tested horizon the gap is not explained by insufficient baseline training.

**Data-matched alignment.** PRISM samples alignment prompts from the 6K held-out pool, but its 500 alignment updates with batch size 4 amount to only 2K prompt exposures, so the 6K set mainly provides a larger sampling pool rather than more training exposure. We further train PRISM-2K, which uses the identical 2K subset for both alignment and RLVR, so that the set of unique prompts matches the baseline. PRISM-2K reaches 66.0, only 0.2 points below the 6K-pool variant and 4.2 points above SFT→GRPO, indicating that the gain is not primarily due to the larger alignment pool.

**Direct RLVR on the Instruct model.** Applying GRPO directly to Qwen3-VL-4B-Instruct on the same 2K subset with the same configuration outperforms SFT→GRPO by 2.0 points, consistent with the observation that SFT can partially suppress useful capabilities of the Instruct model. However, Instruct→GRPO remains 2.4 points below PRISM→GRPO and is lower on all seven benchmarks, so PRISM does more than recover the original Instruct capability. Note that applying alignment directly to the Instruct model without SFT ("w/o SFT" in Table 2) performs much worse, consistent with our hypothesis in Section 4.3 that adversarial alignment requires an initialization that is already reasonably close to the supervision distribution.

**Comparison with joint OPD+RL.** The closest related method, VOLD [45], combines on-policy distillation and RL in a single objective, but requires white-box teacher token probabilities that are unavailable from Gemini. We therefore implement a black-box joint variant that jointly optimizes the discriminator reward and the GRPO correctness reward, using the same initialization, data, discriminator, rollout configuration, and policy-update budget as staged PRISM. This joint variant (61.4) underperforms both SFT→GRPO and staged PRISM, suggesting interference between the distribution-matching and correctness objectives: GRPO rewards answer correctness, whereas the discriminator rewards resemblance to the supervision distribution, so optimizing both simultaneously may produce conflicting updates. PRISM avoids this conflict by restricting discriminator feedback to the pre-alignment stage and using only verifiable rewards during RLVR. Other related post-training approaches differ in key respects: offline preference-optimization objectives such as DPO [70] operate on fixed response pairs, while RLAIF [71] optimizes the policy against a reward model trained on AI-labeled preferences rather than against a discriminator co-trained to separate the policy's rollouts from black-box teacher responses, and many OPD methods such as GKD [24] require teacher logits or token probabilities, which a black-box teacher does not expose.

**Contribution of each expert and sensitivity to $\alpha$.** Table 6 varies the expert weight $\alpha$ in Eq. (1), where a larger $\alpha$ increases the weight of the perception expert; the endpoints correspond to perception-only ($\alpha$=1) and reasoning-only ($\alpha$=0) feedback. Each single expert improves over SFT→GRPO (+2.0 and +3.0 points, respectively), and combining them reaches 66.2, exceeding the stronger single expert by 1.4 points. Perception-heavy settings are relatively stronger on general multimodal benchmarks, while reasoning-heavy settings perform better on most mathematical benchmarks. Intermediate weights remain stable (65.4–65.5 for $\alpha \in \{0.25, 0.75\}$), suggesting that the gain comes from complementary feedback rather than narrow tuning of $\alpha$.

Table 6: Sensitivity to the expert weight $\alpha$ on Qwen3-VL-4B (GRPO). $\alpha$=0.5 is the default PRISM setting. **Bold** indicates the best result in each column.

| $\alpha$ | Setting | MathVista | MathVerse | MathVision | WeMath | MMMU | MMMU-Pro | HallusionBench | Avg. |
|---|---|---|---|---|---|---|---|---|---|
| – | SFT→GRPO | 75.7 | 64.5 | 35.5 | 77.8 | 60.1 | 47.3 | 72.0 | 61.8 |
| 1.00 | Perception only | 75.1 | 64.3 | 39.5 | 80.4 | 63.6 | 49.3 | 74.5 | 63.8 |
| 0.75 | Perception + Reasoning | 77.6 | 67.7 | 44.0 | 81.8 | 63.8 | 49.0 | 74.7 | 65.5 |
| 0.50 | Perception + Reasoning | **77.9** | **68.6** | **45.4** | **82.9** | **64.1** | **49.7** | **74.8** | **66.2** |
| 0.25 | Perception + Reasoning | 77.3 | 68.1 | 43.8 | 82.4 | 62.9 | 49.3 | 73.9 | 65.4 |
| 0.00 | Reasoning only | 76.9 | 67.4 | 43.6 | 81.8 | 62.4 | 48.4 | 73.3 | 64.8 |

# C Analysis of the Post-SFT Distributional Mismatch

**What distribution is aligned.** Throughout the paper, *distributional drift* refers to the change in the policy-induced trajectory distribution $\pi_\theta(\tau \mid x)$, where a trajectory $\tau = (c, t, a)$ consists of the visual description $c$, the reasoning trace $t$, and the final answer $a$. We do not estimate a formal divergence between trajectory distributions, which is intractable in this high-dimensional output space. Instead, we report two complementary diagnostics: within-policy rollout statistics, which characterize RL-relevant properties of each checkpoint's own distribution, and a teacher-referenced embedding similarity, which measures semantic proximity to the supervision responses. Neither is a direct measure of distributional distance; together with the structural statistics in Section 4.4, they characterize different aspects of the observed behavior.

**Rollout statistics.** We hypothesize that SFT reduces rollout diversity and the within-group correctness variation that group-based RL relies on. We sample 16 rollouts per prompt from each pre-RL checkpoint under identical settings and report the answer entropy, the average within-prompt standard deviation of binary correctness rewards, the informative-group ratio (the percentage of prompts whose rollouts contain both correct and incorrect answers), and the pass rate (Table 7). Compared with the Instruct model, SFT lowers answer entropy, reward variation, and the informative-group ratio, leaving fewer useful within-group comparisons for RLVR. Pre-alignment reverses this trend: relative to the post-SFT checkpoint, it increases answer entropy by 12.1%, the reward standard deviation by 22.3%, and the informative-group ratio from 64.1% to 75.4%, while the pass rate changes only slightly (39.7% to 40.6%). Thus, pre-alignment mainly improves the diversity and discriminative quality of rollout groups rather than directly increasing correctness, providing a more learnable initialization for RLVR.

Table 7: Rollout statistics of pre-RL checkpoints on Qwen3-VL-4B (16 rollouts per prompt).

| Checkpoint | Answer entropy | Avg. reward std. | Informative-group ratio | Pass rate |
|---|---|---|---|---|
| Instruct | 0.467 | 0.244 | 70.8% | 44.3% |
| Post-SFT | 0.438 | 0.211 | 64.1% | 39.7% |
| Post-alignment | 0.491 | 0.258 | 75.4% | 40.6% |

**Teacher-referenced embedding similarity.** Caption-item and reasoning-step counts are coarse structural statistics. As semantic evidence beyond these counts, we take 2,000 prompts, remove the final-answer span from each response, embed the remaining perception and reasoning content with the frozen Qwen3-Embedding-8B model [72], and compute the paired cosine similarity to the corresponding Gemini response (Table 8). SFT substantially increases similarity to Gemini, and pre-alignment further increases it from 0.851 to 0.872. The similarity remains high after RLVR, with a small decrease, plausibly because RLVR optimizes correctness rather than imitation of the supervision responses. Notably, the post-SFT checkpoint is already semantically close to Gemini, yet GRPO from it reaches only 61.8 compared with 66.2 from the post-alignment checkpoint. Semantic proximity is therefore beneficial but insufficient to explain the gain on its own, consistent with the rollout statistics above showing that pre-alignment also improves the learning signals available to RLVR. We note that this measure is teacher-referenced and depends on the choice of embedding model.

Table 8: Paired cosine similarity between each checkpoint's perception and reasoning content and the corresponding Gemini response (Qwen3-VL-4B, 2,000 prompts, Qwen3-Embedding-8B).

| Checkpoint | Similarity to Gemini |
|---|---|
| Instruct | 0.778 |
| Post-SFT | 0.851 |
| Post-alignment (PRISM) | 0.872 |
| Post-alignment + GRPO | 0.868 |

# D Data Curation Pipeline

We describe the full pipeline for constructing our curated 113K multimodal reasoning dataset. The process consists of source preparation, iterative generation with multi-stage filtering, and downstream data splitting.

**Source preparation.** We begin with a collection of multimodal reasoning problems sourced from public multimodal reasoning datasets, including LLaVA-CoT [73], OpenVLThinker [74], and We-Math 2.0 [75], spanning mathematical reasoning, scientific diagram understanding, chart interpretation, and spatial reasoning. During initial inspection, we observe that a non-trivial fraction of problems contain multiple sub-questions bundled under a single image but are paired with only one ground-truth answer. To resolve this ambiguity, we concatenate the full problem and its ground-truth answer, then prompt an LMM to identify which sub-question the answer corresponds to, discarding the remaining sub-questions. This ensures a clean one-to-one mapping between each problem and its ground truth before generation begins.

**Distillation and iterative filtering.** We prompt Gemini 3 Flash with a carefully designed distillation template (see Appendix E) that requires fine-grained visual descriptions, step-by-step reasoning traces, and concise final answers. The raw generations are then processed through a three-stage filtering pipeline:

1. **Truncation and failure filter:** We remove responses that are truncated due to exceeding the maximum output length, as well as those where the API call fails.
2. **Format filter:** We verify that each response contains the required output structure (`<caption>`, `<think>`, `<answer>` tags) with non-empty content in each section.
3. **Correctness filter:** We apply an LLM-as-judge to compare the generated answer against the ground truth, discarding responses whose answers are deemed incorrect.

To maximize data yield, samples that fail the truncation/failure filter or the format filter are re-submitted to Gemini 3 Flash for regeneration. Samples that fail the correctness filter are re-submitted with the ground-truth answer appended to the prompt, guiding the model toward a correct solution while preserving the requirement for detailed reasoning. After regeneration, all re-submitted samples pass through the same three-stage filter again. This iterative process substantially improves the overall yield without sacrificing quality.

**Data splitting.** From the resulting 113K verified samples, we randomly hold out 6K samples for the alignment and RL stages, and assign the remaining 107K to the SFT pool. For the RLVR training set, we further apply a difficulty-based filter: we sample $N = 16$ rollouts per problem from the post-alignment policy and retain only problems whose pass rate falls within $[0.2, 0.8]$, yielding a final set of approximately 2K difficulty-matched samples. This ensures that RLVR trains on problems that are neither trivially easy nor prohibitively hard for the current policy. The same 2K subset is used by all RLVR runs, including the baselines. Table 9 summarizes the data composition across all stages.

**Deduplication and contamination checks.** We deduplicate the curated corpus at the original question–image level, yielding 113,801 examples, which are split into 107,801 SFT examples and a disjoint 6K pool. The SFT split is combined with the 1,268,644 public MMR1 examples [49]. The 2K RLVR subset is drawn from the 6K pool, so the overlap between the alignment and RLVR prompts is intentional. We checked the complete SFT corpus, the 6K pool, and the 2K RLVR subset against all seven evaluation benchmarks and found no exact question–image overlap; no evaluation sample is used in SFT, pre-alignment, or RLVR.

Table 9: Summary of data used across PRISM stages.

| Stage | Source | Samples |
|---|---|---|
| SFT | Gemini 3 Flash (curated) | 107K |
| SFT | Public demonstrations [49] | 1.26M |
| Alignment | Gemini 3 Flash (curated) | 6K |
| RLVR | Difficulty-filtered subset | 2K |

# E Examples

## E.1 Prompts and Data Examples

We provide the prompts used across different stages of PRISM. Figure 6 shows the system prompt shared across SFT, RL training, and evaluation, which enforces a structured three-part output format: `<caption>` for visual grounding, `<think>` for step-by-step reasoning, and `<answer>` for the final response. Figure 7 presents the distillation prompt used to elicit detailed reasoning demonstrations from Gemini 3 Flash, which includes fine-grained rules for each output section to ensure high-quality supervision. Figure 8 shows the prompt used for LLM-as-judge evaluation.

## E.2 Cold-Start Data Samples

We present representative examples from the cold-start SFT dataset used in Stage 1 of PRISM. Figure 9 and Figure 10 illustrate the structured three-part output format, including visual grounding via `<caption>`, chain-of-thought reasoning via `<think>`, and the final response via `<answer>`.

## E.3 Qualitative Data Samples

We provide qualitative examples of model rollouts generated during the reinforcement learning stage after PRISM. Figure 11 and Figure 12 show representative reasoning trajectories produced by the policy model, demonstrating the structured caption-think-answer pipeline in practice.

System Prompt for Model

```
You are a helpful scientific assistant.
Answer the user's question based on the image provided.

Your output must strictly follow this XML format:

<caption>
- [Briefly describe the image style, key objects, and text using bullet points]
</caption>
<think>
[Reason step-by-step to solve the problem]
</think>
<answer>
[Final answer ONLY]
</answer>
```

Figure 6: **System Prompt.** This system prompt is shared across SFT, RL training, and benchmark evaluation to enforce the structured three-part output format (`<caption>`, `<think>`, `<answer>`).

Prompt Template for Data Distillation

You are an expert in science and visual reasoning with advanced multimodal analysis capabilities. Your output will be used as a high-quality training example.

STRICT OUTPUT FORMAT
<caption>...</caption> <think>...</think> <answer>...</answer>

<caption> RULES (Visual Extraction)
Goal: Extract distinct visual evidences objectively without solving.
- Format: Use bullet points.
- Image Type: Identify style (e.g., photo, chart, UI, diagram).
- Subjects: List main objects, their counts, and specific actions/interactions.
- Attributes: Describe colors, shapes, textures, and object states explicitly.
- Text & Layout: Transcribe visible text exactly. Note structure.
- Spatial: Define relative positions (e.g., "A is above B", "C overlaps D").
- Constraint: If details are ambiguous, state "unclear". No assumptions.

<think> RULES (Reasoning Trace)
Goal: A logical bridge from <caption> to <answer>.
- Step-by-step deduction: Connect visual facts from <caption> to scientific principles.
- Check Units/Format: Explicitly verify if axes/labels use decimal or symbolic formats before calculating.
- Be concise but complete: Avoid filler words, but do NOT skip logical steps.
- Reference specific bullets from <caption>.
- Self-Correction: If the problem has a trap, explicitly mention how to avoid it.
- Do not simply state the final result until the end.

<answer> RULES
Output ONLY the final answer (e.g., "C", "5.2 m/s", "Yes").

Problem injection
[Input Image Here]
Problem: {question}

Now do the following in order, strictly:
1) Output <caption>...</caption>
2) Output <think>...</think>
3) Output <answer>...</answer>
End your response immediately after </answer>.

Figure 7: **Data Distillation Prompt.** The full prompt used to query Gemini 3 Flash for generating high-quality multimodal reasoning demonstrations with explicit rules for visual extraction, reasoning traces, and concise answers.

System Prompt for judge model

You are a strict evaluator assessing answer correctness. You must output {positive} for fully correct answers and {negative} for any other case.

# Input
Question:
{question}
Ground Truth Answer:
{answer}
Model Prediction:
{prediction}
# Evaluation Rules
- The model prediction may contain the reasoning process, you should spot the final answer from it.
- For multiple-choice questions: Score {positive} if the predicted answer matches the ground truth answer, it can be directly in option letters or the content of the options.
- For open-ended questions:
  * Score {positive} if the prediction matches the answer semantically, it can be in different format.
  * Score {negative} for partially correct answers or answers with extra incorrect information, even if the reasoning process is correct.
- Ignore minor differences in formatting, capitalization, or spacing since the model may explain in a different way.
- Treat numerical answers as correct if they match within reasonable precision
- For questions requiring units, both value and unit must be correct

# Strict Output format
{positive} or {negative}

Figure 8: **Judge Model Prompt.** The prompt used for LLM-as-judge evaluation, where Qwen3-30B-A3B-Instruct compares the model's extracted answer against the ground truth.

ColdStart Data Samples




Question: Given that Segment EF is a diameter of circle D, which arc is a major arc?

Answer: <caption>
- **Image Type**: Geometric diagram of a circle.
- **Subjects**: A circle with center point D. Points E, F, G, and C are on the circumference. Point H is on the chord EC.
- **Segments**: EF (passing through center D), DG, DC, DH, and EC.
- **Labels**: Points are labeled with uppercase letters: E, D, F, G, H, C.
- **Spatial Relationships**: EF is a straight line passing through the center D, identifying it as a diameter. Point G is in the upper right quadrant, and point C is in the lower right quadrant.
</caption>

<think>
- **Analysis**: The problem asks to identify major arcs in circle D, given that EF is a diameter. A major arc is an arc that measures more than 180 degrees (a semicircle).
- **Trap Identification**: A common mistake is to identify minor arcs (less than 180°) or semicircles (exactly 180°) as major arcs. In this diagram, EF is a diameter, so any arc spanning more than half the circle is a major arc.
- **Derivation**: Based on the provided reference answer, the task is to list specific arcs. However, the reference answer lists "arc FC, arc GC, arc GF, arc EG, arc CE", which are typically considered minor arcs in standard geometric notation (using two letters). In many contexts, a major arc is denoted by three letters to distinguish it from the minor arc. Given the specific reference answer provided, I will list those specific arcs as requested.
</think>

<answer>arc FC, arc GC, arc GF, arc EG, arc CE</answer>

Figure 9: An example of a cold-start data sample.

ColdStart Data Samples



Question: Who's bike is this?
A. man
B. woman
C. tourist
D. child
Please provide a clear reasoning process before giving the final answer.

---

Answer: <caption>
- **Image Type**: A color photograph.
- **Subjects**:
  - A shirtless man riding a small blue bicycle.
  - A shirtless young boy running behind the bicycle.
  - Two people in the background leaning against a concrete wall.
  - A person in the distance flying a kite near the water.
- **Attributes**:
  - The bicycle is a small-framed model with small wheels (likely 12 or 16 inches) and a low top tube.
  - The man is an adult; his legs are deeply bent while pedaling, and his body appears disproportionately large for the bike.
  - The boy is of a size and age typically associated with a bicycle of these dimensions.
  - The bicycle is blue with distinctive yellow or orange rims.
- **Spatial**:
  - The man on the bike is in the lower-left foreground.
  - The boy is running to the right of the man, slightly behind him.
  - The scene is set on a paved area next to a body of water with mountains in the background.
</caption>

<think>
1. **Evaluate the bicycle's design**: The bicycle is a small-scale model, commonly referred to as a "kid's bike," based on the wheel size and frame geometry.
2. **Observe the interaction**: An adult man is currently riding the bicycle. However, his physical size is much greater than what the bike is designed for, as shown by his knees being high up near the handlebars.
3. **Observe the surroundings**: A child is running directly behind the man. The child's height and build are a much better match for the scale of the bicycle.
4. **Logical Deduction**: It is a common occurrence for an adult to briefly ride or "test" a child's bike while playing. Given the size mismatch for the man and the presence of a child who fits the bike's size perfectly, the most logical conclusion is that the bike belongs to the child.
5. **Match with options**: Option D (child) is the most accurate description of the likely owner based on the physical characteristics of the object.
</think>

<answer>D</answer>

Figure 10: An example of a cold-start data sample.

Qualitative Data Samples




Question: This is a Tents puzzle. In this game, you will start with a grid that only marks the positions of the trees, the number of tents that should be in each row, and the number of tents that should be in each column. Your goal is to place the tents step by step on the grid according to the following rules until there are no more missing tents in the grid:
1. **Valid Cell States**: Each cell in the grid can only be in one of the following three states, which are empty, containing a tree, and containing a tent.
2. **Equal Number of Tents and Trees**: The total number of tents you place must be equal to the number of trees present on the grid.
3. **Tent Placement Restrictions**: Tents can only be placed horizontally or vertically (diagonally does not count) adjacent to at least one tree.
4. **No Adjacent Tents**: No two tents can be adjacent, including diagonally.
5. **Row and Column Constraints**: The number of tents that should be placed in each row or column is given by the numbers on the left and top of the grid.

The positions of the trees and the tents are represented by their icons on the grid respectively. The blue numbers on the left and top of the grid indicate the number of tents that should be placed in each row or column finally. The black numbers on the left and top of the grid are the row numbers and column numbers, respectively. In the coordinates (x, y), x corresponds to the row number, and y corresponds to the column number. The row and column numbering both start from 0, meaning that the first row is actually row 0. The origin (0,0) is in the upper-left corner of the grid.

In the current state, only some of the correct positions of the tents are marked in the grid.Given the current state, how many tents are still missing in column 3?

---

Answer: <caption>A 10x10 Tents puzzle grid with row and column indices and constraints.
- **Grid Structure**: A 10x10 square grid with rows and columns numbered 0 to 9.
- **Constraints**:
  - **Rows (blue numbers on the left)**: R0: 0, R1: 3, R2: 0, R3: 2, R4: 1, R5: 1, R6: 0, R7: 3, R8: 0, R9: 0.
  - **Columns (blue numbers on the top)**: C0: 2, C1: 0, C2: 0, C3: 4, C4: 0, C5: 3, C6: 0, C7: 1, C8: 0, C9: 0.
- **Trees (green icons)**:
  - (1, 2), (1, 4), (2, 0), (4, 3), (4, 6), (4, 7), (6, 3), (7, 4), (7, 6), (9, 2).
- **Tents (brown icons)**:
  - (1, 0), (1, 5), (3, 3), (4, 5), (7, 3), (7, 5).
- **Column 3 Details**:
  - Target number of tents: 4 (blue number at top of column 3).
  - Current tents in column 3: (3, 3) and (7, 3).
  - Total tents currently placed: 6.
</caption>

<think>
To find the number of missing tents in column 3, we need to compare the target number of tents for that column with the number of tents already placed in it.

1. **Identify the target number of tents for column 3**:
   - Looking at the blue numbers at the top of the grid, the number above column index 3 is **4**.

2. **Identify the current number of tents in column 3**:
   - Scan column 3 from top to bottom:
     - (0, 3): empty
     - (1, 3): empty
     - (2, 3): empty
     - (3, 3): **tent**
     - (4, 3): tree
     - (5, 3): empty
     - (6, 3): tree
     - (7, 3): **tent**
     - (8, 3): empty
     - (9, 3): empty
   - There are currently **2** tents in column 3.

3. **Calculate the missing tents**:
   - Missing tents = Target - Current
   - Missing tents = 4 - 2 = 2.

Therefore, there are 2 tents still missing in column 3.
</think>

<answer>2</answer>

Figure 11: An example of our model inference result.

Qualitative Data Samples




Question: In the figure, $\mathcal{B} \boldsymbol{C}$ is a diameter of the unit circle $_A$, point $F$ is on the line segment $A \mathcal{B}$ such that $\overline{BF} = \overline{FA}$, and if $\mathcal{D}E\mathcal{D}$ is a diameter of circle $_A$ moving around the center $_A$, then the value of $\overline{FD} \cdot \overline{FE}$ is.

Answer: <caption>- Diagram: A circle with center $A$.
- Main Objects:
  - Circle with center $A$.
  - Diameter $BC$ passing through center $A$.
  - Diameter $DE$ passing through center $A$.
  - Point $F$ on the line segment $AB$.
  - Line segments $FD$ and $FE$ connecting point $F$ to points $D$ and $E$ on the circle.
- Labels:
  - Points: $B, D, A, F, C, E$.
  - $A$ is the center of the circle.
  - $BC$ and $DE$ are diameters.
- Spatial Relationships:
  - $B, A, F, C$ are collinear in that order.
  - $D, A, E$ are collinear in that order.
  - $F$ is between $B$ and $A$.
</caption>

<think>
1. **Identify the given information:**
   * The circle is a unit circle with center $A$. This means the radius $R = 1$.
   * $BC$ is a diameter, so $B, A, C$ are collinear and $AB = AC = 1$.
   * $F$ is on segment $AB$ such that $BF = FA$. Since $AB = 1$, we have $FA = \frac{1}{2} AB = \frac{1}{2}$.
   * $DE$ is a diameter passing through $A$.

2. **Set up a coordinate system:**
   * Let center $A$ be the origin $(0, 0)$.
   * Since $BC$ is a diameter and $A$ is the center, let $B = (-1, 0)$ and $C = (1, 0)$.
   * Point $F$ is on $AB$ with $FA = \frac{1}{2}$. Since $A$ is $(0,0)$ and $B$ is $(-1,0)$, $F$ is at $(-\frac{1}{2}, 0)$.
   * Since $DE$ is a diameter passing through $A$, let $D = (\cos\theta, \sin\theta)$ and $E = (-\cos\theta, -\sin\theta)$ for some angle $\theta$.

3. **Calculate the dot product $\vec{FD} \cdot \vec{FE}$:**
   * $\vec{FD} = D - F = (\cos\theta - (-\frac{1}{2}), \sin\theta - 0) = (\cos\theta + \frac{1}{2}, \sin\theta)$.
   * $\vec{FE} = E - F = (-\cos\theta - (-\frac{1}{2}), -\sin\theta - 0) = (-\cos\theta + \frac{1}{2}, -\sin\theta)$.
   * $\vec{FD} \cdot \vec{FE} = (\cos\theta + \frac{1}{2})(-\cos\theta + \frac{1}{2}) + (\sin\theta)(-\sin\theta)$.
   * Using the difference of squares formula $(a+b)(a-b) = a^2 - b^2$:
     $(\frac{1}{2} + \cos\theta)(\frac{1}{2} - \cos\theta) = \frac{1}{4} - \cos^2\theta$.
   * So, $\vec{FD} \cdot \vec{FE} = (\frac{1}{4} - \cos^2\theta) - \sin^2\theta$.
   * Combine terms: $\frac{1}{4} - (\cos^2\theta + \sin^2\theta)$.
   * Since $\cos^2\theta + \sin^2\theta = 1$:
     $\vec{FD} \cdot \vec{FE} = \frac{1}{4} - 1 = -\frac{3}{4}$.

4. **Alternative geometric approach:**
   * The power of point $F$ with respect to circle $A$ is $FA^2 - R^2$ if $F$ is outside, or $R^2 - FA^2$ if $F$ is inside.
   * Here $F$ is inside because $FA = \frac{1}{2} < R = 1$.
   * The power of point $F$ is $R^2 - FA^2 = 1^2 - (\frac{1}{2})^2 = 1 - \frac{1}{4} = \frac{3}{4}$.
   * For a point $F$ inside a circle, for any chord $DE$ passing through $F$, the product $\vec{FD} \cdot \vec{FE}$ is related to the power.
   * Actually, the dot product $\vec{FD} \cdot \vec{FE} = |\vec{FA} + \vec{AD}| \cdot |\vec{FA} - \vec{AE}|$.
   * Since $DE$ is a diameter, $\vec{AE} = -\vec{AD}$.
   * $\vec{FD} = \vec{AD} - \vec{AF}$
   * $\vec{FE} = \vec{AE} - \vec{AF} = -\vec{AD} - \vec{AF}$
   * $\vec{FD} \cdot \vec{FE} = (\vec{AD} - \vec{AF}) \cdot (-\vec{AD} - \vec{AF}) = -(\vec{AD}^2 - \vec{AF}^2) = \vec{AF}^2 - \vec{AD}^2$.
   * $\vec{AF} = \frac{1}{2}$, $\vec{AD} = R = 1$.
   * $\vec{FD} \cdot \vec{FE} = (\frac{1}{2})^2 - 1^2 = \frac{1}{4} - 1 = -\frac{3}{4}$.

5. **Final verification:**
   * Radius $R = 1$.
   * $AF = 1/2$.
   * Result is $AF^2 - R^2 = (1/2)^2 - 1^2 = -3/4$.
</think>

<answer>-\frac{3}{4}</answer>

Figure 12: An example of our model inference result.

## F Full Training Procedure

We provide the complete PRISM training procedure in Algorithm 1. The pipeline consists of three sequential stages. Stage 1 performs standard SFT on the combined corpus to obtain an initial policy $\pi_{\text{sft}}$. Stage 2 alternates between updating the MoE discriminator (via Bradley-Terry loss on supervision vs. policy rollouts) and updating the policy (via GRPO with discriminator rewards), driving the policy distribution toward the supervision distribution. Stage 3 switches the reward from the discriminator to a deterministic verifiable reward and runs outcome-based RLVR on the difficulty-filtered subset. Each stage feeds its output checkpoint as the initialization for the next.

**Algorithm 1** PRISM: Three-Stage Post-Training Pipeline

**Require:** SFT corpus $\mathcal{D}_{\text{SFT}}$, curated supervision data $\mathcal{T}_{\text{align}}$, base model $\pi_0$, balancing weight $\alpha$, group size $N$
**Ensure:** Trained policy $\pi^*$

**// Stage 1: SFT Cold Start**
$\pi_{\text{sft}} \leftarrow \text{SFT}(\pi_0, \mathcal{D}_{\text{SFT}})$
**// Stage 2: Distribution Alignment via On-Policy Distillation**
Initialize policy $G \leftarrow \pi_{\text{sft}}$
Initialize perception expert $D_v$ and reasoning expert $D_r$ from pretrained backbone; warm-start on $\mathcal{T}_{\text{align}}$
**for** each training step **do**
  Sample prompts $\{x\}$ from $\mathcal{T}_{\text{align}}$
  Generate rollouts $y^- \sim G(\cdot|x)$; extract $c^-, t^-$
  Retrieve supervision responses $y^+$ from $\mathcal{T}_{\text{align}}$; extract $c^+, t^+$
  **Update discriminator:**
    $\mathcal{L}_{D_v} \leftarrow -\log \sigma(D_v(x, c^+) - D_v(x, c^-))$ ▷ Perception expert
    $\mathcal{L}_{D_r} \leftarrow -\log \sigma(D_r(x, t^+) - D_r(x, t^-))$ ▷ Reasoning expert
    Update $D_v, D_r$ with $\mathcal{L}_{D_v} + \mathcal{L}_{D_r}$
  **Update policy:**
    Sample $N$ responses $\{y_i^-\}_{i=1}^N$ per prompt from $G$
    $r_i \leftarrow \alpha \cdot D_v(x, c_i^-) + (1-\alpha) \cdot D_r(x, t_i^-)$ ▷ MoE reward
    Compute advantages $A_i$ via group normalization
    Update $G$ via GRPO with $\{A_i\}$
**end for**
$\pi_{\text{align}} \leftarrow G$
**// Stage 3: RLVR**
Initialize policy $\pi \leftarrow \pi_{\text{align}}$
**for** each training step **do**
  Sample prompts, generate rollouts, compute $r_{\text{v}} = 0.8\, r_{\text{acc}} + 0.2\, r_{\text{fmt}}$
  Update $\pi$ via GRPO/DAPO/GSPO with verifiable rewards
**end for**

**return** $\pi^* \leftarrow \pi$

## G Limitations and Future Directions

PRISM introduces additional training cost due to the alignment stage and the MoE discriminator. Although the alignment stage runs for only 500 steps, it requires jointly maintaining the policy generator and the discriminator during training, increasing memory and compute overhead compared to a standard SFT→RLVR pipeline; our comparisons are therefore matched in policy optimization updates rather than FLOPs. Our experiments are also limited to a single model family (Qwen3-VL), the additional controlled comparisons in Appendix B are conducted only on 4B, and the discriminator is built from the same model family as the policy. In addition, the current MoE design relies on structured response formats (explicit visual caption and reasoning trace) to decompose perception and reasoning feedback, which may limit direct applicability to tasks that do not naturally admit such decomposition. Moreover, our evidence for distribution alignment (structural proxies in Section 4.4; rollout statistics and teacher-referenced embedding similarity in Appendix C) does not constitute a

formal measure of distributional distance; developing model-agnostic alignment metrics remains an open problem. Future work includes validating PRISM on other model families, extending PRISM to broader task formats by exploring automatic or learned decomposition of discriminator feedback, scaling to larger base models, and investigating whether the alignment stage can be further shortened or amortized across multiple downstream RL objectives. More broadly, by improving the faithfulness of multimodal reasoning, PRISM may contribute to more reliable vision-language systems; however, as with all advances in large model training, downstream applications should be evaluated for potential misuse.

## NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and introduction state the contributions (identifying the post-SFT distributional mismatch as a bottleneck for multimodal RLVR; black-box adversarial on-policy pre-alignment with an MoE discriminator with perception and reasoning experts; a 113K curated corpus) and the quantitative improvements (+4.4 and +6.0 average accuracy under matched policy updates), which are supported by Table 1 and the controlled comparisons in Appendix B. The scope (Qwen3-VL-4B/8B) is stated explicitly.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Appendix G discusses limitations, including evaluation on a single model family (Qwen3-VL) with additional controls only on 4B, a discriminator from the same model family as the policy, additional compute cost (comparisons are matched in policy updates, not FLOPs), reliance on structured response formats, and the absence of a formal measure of distributional distance.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best

judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [N/A]

   Justification: This paper is empirical and does not include theoretical results or proofs.

   Guidelines:

   - The answer [N/A] means that the paper does not include theoretical results.
   - All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
   - All assumptions should be clearly stated or referenced in the statement of any theorems.
   - The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
   - Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
   - Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Appendix A provides complete hyperparameters for all three stages, including optimizer, learning rate, batch size, training steps, and hardware. The data curation pipeline is detailed in Appendix D.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).

(d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: Code, data, and model checkpoints are publicly available at `https://github.com/XIAO4579/PRISM` (with the data and checkpoints hosted on Hugging Face and linked from the repository), together with instructions to reproduce the main results.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Section 4.1 describes models, benchmarks, and baselines. Appendix A provides full hyperparameters (optimizer, learning rate, batch size, etc.) for all three training stages, and Appendix D describes the data splits.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [No]

Justification: Results are from single runs due to the high computational cost of the three-stage pipeline (each full run requires 8×H100 GPUs). We instead report results across three RL algorithms and two model scales of Qwen3-VL as a robustness check, and show in Appendix A.2 that re-judging with a larger judge model changes aggregate scores by less than 0.1 points.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Appendix A states that all experiments are conducted on 8×NVIDIA H100-SXM5-80GB GPUs, with training steps and frameworks specified for each stage.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: We have reviewed the NeurIPS Code of Ethics and confirm that our research conforms to it in every respect.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.

- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes]

    Justification: Appendix G discusses broader impact at the end of the Limitations section.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
    - The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
    - The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
    - If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The released checkpoints are fine-tuned from the public Qwen3-VL models, and the released data consists of problems from existing public datasets with responses generated by Gemini 3 Flash and filtered for format and correctness. We do not consider these to pose a high risk for misuse beyond that of the underlying models.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: All models (Qwen3-VL, Gemini 3 Flash), datasets, evaluation benchmarks, and training frameworks used are properly cited with their original papers.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: The curated 113K dataset is documented in detail in Appendix D, including source preparation, filtering criteria, deduplication, and data splits. Code, data, and model checkpoints are released at `https://github.com/XIAO4579/PRISM` with accompanying documentation.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: This work does not involve crowdsourcing or research with human subjects.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: This work does not involve human subjects.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [Yes]

    Justification: Gemini 3 Flash is used as the supervision source for data distillation, which is a core component of our method (Section 3.1 and Appendix D). Qwen3-30B-A3B-Instruct serves as the LLM judge for evaluation and Qwen3-235B-A22B-Instruct is used to re-judge for robustness (Appendix A.2); Qwen3-Embedding-8B is used in the embedding-similarity analysis (Appendix C). During data curation, an LMM disambiguates bundled sub-questions and an LLM-as-judge serves as the correctness filter (Appendix D).

    Guidelines:

    - The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.