CAUSAL SKILL ATTRIBUTION AND MINIMAL REPAIR IN STOCHASTIC LLM AGENTS

Anonymous authors
Paper under double-blind review

ABSTRACT

Auditing large language model agents requires identifying where decision disparities arise in execution traces, which executable components causally produce them, and how to repair those components while preserving utility. Stochastic trajectories, correlated activations, distributed interactions, and fine-grained carriers such as rule clauses, demonstrations, retrieval triggers, and routing edges can cause observationally suspicious components to be noncausal. We introduce Paired Factorial Skill Intervention and Repair (PFSIR), a framework for causal attribution and minimal repair over version-frozen, instrumented agent graphs. PFSIR applies type-preserving neutral replacements through balanced multi-component interventions on matched task pairs. It uses common random numbers and cached tool responses to reduce unrelated execution variation. A hierarchical sparse effect model estimates individual component effects and graph-constrained second-order interactions, and cross-fitting separates candidate selection from out-of-fold assessment. Separate models estimate disparity reduction and utility loss, enabling confidence-constrained optimization of the smallest patch that satisfies prespecified requirements for fairness, utility, regression risk, token changes, and execution cost. Fresh executions on isolated repair and regression sets validate candidate repairs, and the framework abstains when it identifies no acceptable patch. We evaluate PFSIR in three controlled agent environments covering resource matching, candidate ranking, and service routing. These environments contain known causal carriers, interaction and redundancy structures, correlated noncausal bystanders, and unbiased controls. We assess node- and edge-level recovery, disparity reduction, utility preservation, regression behavior, and structural generalization, yielding a closed-loop evaluation of intervention-defined attribution and executable repair under explicit replacement boundaries.

1 INTRODUCTION

Large language model (LLM) agents combine model reasoning with retrieval rules, demonstrations, executable skills, tool calls, and conditional workflows. This modular design supports extension but complicates auditing. When matched inputs that differ only in a synthetic sensitive attribute produce systematically different decisions, as illustrated in Figure 1, the outputs alone do not identify which executable component caused the disparity. In long stochastic trajectories, the component nearest the decision may expose an effect introduced earlier, while frequently activated components may be correlated bystanders. The relevant attribution unit may also be a rule clause, demonstration, retrieval trigger, or routing edge, as opposed to an entire skill. We study *causal skill attribution and minimal repair*: given a version-frozen agent with an instrumented skill graph, matched audit tasks, and legally replaceable components, the objective is to identify the smallest set of skill units or dependency edges whose controlled replacement reproducibly reduces decision disparity and to repair them under prespecified utility and regression-risk constraints.

Recent agent-diagnosis methods primarily extract evidence from observed trajectories. Who&When identifies the responsible agent and decisive error step, while fine-grained localization remains difficult even with annotated failure logs.(Zhang et al., 2025) AgentRx synthesizes domain constraints and checks them along trajectories to localize the first critical failure with auditable evidence.(Barke et al., 2026) MAST categorizes failures by system design, inter-agent alignment, and verification, showing that failures often arise from system structure and component interactions.(Cemri et al.,

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: Skill attribution for disparate decisions on matched inputs.

2025) These methods identify suspicious agents, steps, or failure modes, but observational trajectory evidence cannot establish whether replacing a component changes the audited outcome under correlated components, redundant implementations, or skill–retrieval and routing–skill interactions.

Intervention-based methods provide stronger causal evidence but do not directly address causal attribution in versioned agent graphs. Multi-component causal tracing jointly intervenes on internal LLM components and shows that independent component analysis can miss distributed effects.(Yan et al., 2026) Model debiasing and machine unlearning remove targeted behaviors while preserving unrelated capabilities,(Liu et al., 2025a)(Liu et al., 2025b) but typically operate on model parameters or representations. Deployed agents also depend on external, versioned artifacts with inspectable interfaces, activation paths, and replacement policies, which permits intervention without modifying the base model. Attribution in this setting must account for execution randomness, distinguish causal carriers from correlated bystanders, represent graph-adjacent effects, and produce executable patches that are independently evaluated for fairness improvement, utility cost, and regression risk.

We introduce *Paired Factorial Skill Intervention and Repair* (PFSIR) for causal attribution and minimal repair in stochastic LLM agents. PFSIR represents a frozen agent as a directed skill graph. Its nodes correspond to rule clauses, demonstrations, retrieval triggers, and atomic skills, while its edges encode invocation, inheritance, data transfer, or conditional routing. Each candidate component is assigned a type-preserving neutral replacement that retains the original interface, permissions, output schema, and computation budget. On matched task pairs, PFSIR applies balanced multi-component interventions using common random numbers and cached tool responses. Paired baseline and intervened executions suppress unrelated variation, and the factorial design estimates main effects and interactions that leave-one-out replacement can miss.

A hierarchical sparse effect model estimates node effects and graph-induced second-order interactions. Graph constraints avoid unrestricted quadratic search while preserving skill dependencies and routing effects. Cross-fitting separates model selection from out-of-fold assessment. Separate models estimate disparity reduction and utility loss, preventing the procedure from selecting patches that reduce disparity by disabling useful behavior. PFSIR then identifies the smallest patch whose estimated reduction exceeds a preregistered target while satisfying specified limits on utility loss, regression risk, token changes, and execution cost. Final conclusions are based on fresh executions over isolated repair and regression sets. If no candidate passes this validation, the framework reports that no acceptable repair was identified.

We evaluate PFSIR in three isolated synthetic agent environments for resource matching, candidate ranking, and service routing. The environments use matched fictional profiles, static inert tools, versioned graphs, and controlled injections with known carriers. The injections include clause, demonstration, and retrieval-trigger carriers; graph-edge interactions; redundant carriers; correlated noncausal bystanders; and an unbiased negative control. We evaluate node- and edge-level recovery, patch size, disparity reduction, utility preservation, dependent-skill regression, and structural out-of-distribution behavior. The baselines include observational trajectory attribution, constraint-based diagnosis, leave-one-out intervention, exhaustive pairwise intervention on small graphs, information-matched sparse regression, whole-skill deletion, global instruction repair, and compute-matched

random search. The ablations evaluate common random numbers, graph-restricted interactions, hierarchy constraints, cross-fitting, neutral-replacement definitions, and independent patch validation. The experiments use synthetic or semi-synthetic sandboxes, so the conclusions apply to identifiable intervention effects under recorded boundaries and explicit replacement policies. They do not establish open-world moral responsibility or the elimination of base-model bias.

Our contributions are:

- We formulate skill-level disparity attribution as controlled, falsifiable inference over versioned agent graphs. The formulation distinguishes intervention-defined causal carriers from suspicious trajectory locations, correlated bystanders, and context-independent responsibility.
- We propose PFSIR, which combines common-random-number paired replay, balanced multi-component interventions, and hierarchical graph-constrained estimation of individual effects and sparse dependency interactions.
- We connect attribution to confidence-constrained minimal repair through type-preserving patches that satisfy explicit requirements for disparity reduction, utility preservation, maintenance cost, and regression risk, followed by independent execution-based validation.
- We provide a closed-loop evaluation with known carrier structures, interaction and redundancy stress tests, unbiased negative controls, matched information and compute budgets, replacement-sensitivity analysis, and held-out task and graph structures.

2 Related Work

2.1 Evaluation and Failure Diagnosis in LLM Agents

LLM agents combine language-model inference with planning, retrieval, external actions, and persistent state. ReAct introduced interleaved reasoning and acting (Yao et al., 2023), Toolformer studied self-supervised API invocation (Schick et al., 2023), and later systems learned from generated instructions, API documentation, and multi-call trajectories (Qin et al., 2024). Such systems expose intermediate decisions, so task failures may arise from planning, routing, invalid calls, incorrect arguments, observations, or error propagation.

AgentBench evaluates heterogeneous interactive tasks (Liu et al., 2024), WebArena tests long-horizon browser workflows (Zhou et al., 2024), SWE-bench measures repository-level issue resolution (Jimenez et al., 2024), OSWorld covers multimodal computer use (Xie et al., 2024), and AgentBoard reports intermediate progress (Ma et al., 2024). These benchmarks reveal long-horizon accumulation but usually evaluate tasks, trajectories, or milestones rather than causal responsibility.

Finer-grained diagnostics attribute failures to agents and trajectory steps (Zhang et al., 2025), identify the earliest critical constraint violation (Barke et al., 2026), or classify system-design, inter-agent-alignment, and verification failures (Cemri et al., 2025). However, observational traces remain causally ambiguous under shared upstream errors, correlated activation, recovery, redundancy, and stochastic execution.

2.2 Bias Measurement and Counterfactual Auditing

Bias evaluations quantify demographic associations in embeddings (Caliskan et al., 2017) and modify gender-related embedding geometry (Bolukbasi et al., 2016). For contextual models, CrowS-Pairs (Nangia et al., 2020), StereoSet (Nadeem et al., 2021), and Winogender (Rudinger et al., 2018) use controlled contrasts to measure stereotypical preferences or gender-dependent predictions.

Generative evaluations include demographic prompting with sentiment, toxicity, regard, and lexical metrics (Dhamala et al., 2021), large-scale intersectional templates (Zhu et al., 2022), and ambiguous versus disambiguated question answering (Parrish et al., 2022). HELM standardizes multiple behavioral dimensions (Liang et al., 2022), while DecodingTrust evaluates bias alongside toxicity, privacy, robustness, and related properties (Wang et al., 2023). Measurements may nevertheless depend on templates, decoding, lexicalization, and application-specific criteria.

Counterfactual fairness requires invariance under protected-attribute interventions in an appropriate causal model (Kusner et al., 2017). Minimal pairs approximate this principle but identify system-level disparities rather than whether retrieval, demonstrations, routing, summaries, tool arguments, or ranking rules transmit them.

2.3 Causal Localization, Model Editing, and Selective Repair

Mechanistic methods intervene on internal states to estimate mediated effects (Vig et al., 2020), restore corrupted representations to localize factual recall (Meng et al., 2022a), test computational hypotheses through resampling (de Aragão et al., 2022), or evaluate interacting component subsets (Yan et al., 2026). These methods generally target activations, heads, layers, or parameters.

Model editing uses localized weight updates (Meng et al., 2022a), distributed multi-layer updates (Meng et al., 2022b), learned gradient transformations (Mitchell et al., 2021), or memory-based overrides (Mitchell et al., 2022). Evaluation separates efficacy, generalization, and locality, although causal localization does not necessarily identify the best editing location (Hase et al., 2023).

Machine unlearning seeks targeted removal while preserving unrelated performance. Approaches include certified deletion (Guo et al., 2019), partitioned training histories (Bourtoule et al., 2019), forget-and-retain benchmarks (Maini et al., 2024), corpus-level approximate unlearning (Eldan & Russinovich, 2023), and representation redirection (Li et al., 2024). Mechanistic studies show that robustness and side effects depend on whether localization captures correlated pathways or stable mechanisms (Guo et al., 2024). Related work evaluates bias-oriented and selective behavioral removal under retention constraints (Liu et al., 2025a) (Liu et al., 2025b). Across these areas, recurring challenges include stochasticity, correlated and redundant mechanisms, interaction effects, baseline sensitivity, and collateral degradation.

3 Method

We propose *Paired Factorial Skill Intervention and Repair* (PFSIR), a framework that attributes decision discrepancies in stochastic, tool-using agents to versioned skill units and selects a minimal repair under prespecified discrepancy, utility, and regression constraints. PFSIR applies controlled, type-preserving interventions to an observed skill graph, replays matched tasks using common random numbers, estimates graph-structured main and interaction effects, and validates the selected patch on independent data. Figure 2 summarizes this workflow.

3.1 Problem Setup and Framework

We consider a frozen agent $\mathcal{A} = (M, \mathcal{G}, \mathcal{T}, \Pi)$, where $\mathcal{G} = (V, E)$, M is a fixed language model, $\mathcal{T}$ is an isolated tool set, Π is the orchestration policy, and $\mathcal{G}$ is a directed skill graph obtained from execution specifications and runtime instrumentation. The node set $V = V_{\text{clause}} \cup V_{\text{demo}} \cup V_{\text{retrieval}} \cup V_{\text{skill}}$ contains rule clauses, demonstrations, retrieval triggers, and atomic skills. Edges encode versioned invocation, inheritance, data-flow, or routing dependencies. The graph represents observed system structure and is not inferred as a causal graph from execution logs.

Let $\mathcal{C} = \{c_1, \ldots, c_p\} \subseteq V \cup E$ denote the auditable candidates. Each c_j has a stable identifier and a preregistered neutral replacement r_j. Node replacements preserve input permissions, output schemas, and execution budgets. Edge replacements preserve downstream interfaces while applying attribute-invariant routing or transfer rules. An intervention is legal only if it is executable and passes interface-equivalence tests.

The audit contains matched pairs $x_i^a = (q_i, a, c_i)$, where $a \in \{0, 1\}$ and $i = 1, \ldots, n$. Here, q_i is the task content, a is a synthetic audit attribute, and c_i contains the remaining state. Eligibility variables, tools, actions, and task-relevant conditions are fixed within each pair. For random band ω, we define

$$B_{i,\omega}(\mathcal{A}) = d\big(Y_{i,\omega}^0(\mathcal{A}), Y_{i,\omega}^1(\mathcal{A})\big)\,, \tag{1}$$

$$U_{i,\omega}(\mathcal{A}) = \frac{1}{2} \sum_{a \in \{0,1\}} u_{i,\omega}^a(\mathcal{A}), \tag{2}$$



Figure 2: Overview of the PFSIR framework.

where d is a preregistered discrepancy measure. Population discrepancy and utility are defined as expectations over i and ω.

The estimand for c_j is the effect of replacing it with r_j, conditional on the frozen agent, skill graph, audit distribution, and replacement library. Identification requires executable interventions, positive assignment probabilities, logged random sources, and paired runs that differ only in the assigned replacements and audit attribute. When multiple valid replacements produce materially different conclusions, PFSIR reports replacement sensitivity.

3.2 Paired Factorial Interventions

For each run m, we sample $\mathbf{Z}^{(m)} \in \{0,1\}^p$ and construct the intervened agent $\mathcal{A}^{\mathbf{Z}^{(m)}} = \mathcal{I}\big(\mathcal{A}; \mathbf{Z}^{(m)}, \mathcal{R}\big)$, where c_j is replaced by r_j if $Z_j^{(m)} = 1$. We use a balanced factorial design that permits redundant and combinatorial carriers:

$$\mathbf{Z}^{(m)} \sim \mathrm{Ber}\big(\tfrac{1}{2}\big)^p \mid \|\mathbf{Z}^{(m)}\|_0 \le k_{\max}, \qquad m = 1, \dots, N. \tag{3}$$

Candidates and estimable products $Z_j Z_k$ are balanced when feasible. The cap $k_{\max}$ limits the number of simultaneous modifications.

We restrict explicit interactions to $\mathcal{E}_c$, which contains graph-adjacent units, within-skill parent-child pairs, and explicit routing dependencies. This restriction reduces the interaction class without assuming that higher-order effects are absent.

For each task, mask, and random band, we replay the baseline and intervened agents with matched sampling seeds, admissible tool noise, branch randomness, and frozen tool outputs when those outputs are intervention-independent. We record

$$D_{i,\omega}(\mathbf{Z}) = B_{i,\omega}(\mathcal{A}) - B_{i,\omega}(\mathcal{A}^{\mathbf{Z}}), \qquad L_{i,\omega}(\mathbf{Z}) \quad = U_{i,\omega}(\mathcal{A}) - U_{i,\omega}(\mathcal{A}^{\mathbf{Z}}). \tag{4}$$

so that positive D indicates discrepancy reduction and positive L indicates utility degradation. The assigned mask $\mathbf{Z}$ defines the primary estimand. We log realized activations only for compliance and executable-path sensitivity analyses, thereby avoiding adjustment for post-intervention routing.

3.3 GRAPH-CONSTRAINED EFFECT ESTIMATION

Using preregistered pre-intervention covariates $\mathbf{X}_{i,\omega}$, we fit

$$D_{i,\omega}(\mathbf{Z}) = \beta_0 + \sum_j \tau_j Z_j + \sum_{(j,k)\in\mathcal{E}_c} \tau_{jk} Z_j Z_k + f_D(\mathbf{X}_{i,\omega}) + \varepsilon^D_{i,\omega}, \tag{5}$$

$$L_{i,\omega}(\mathbf{Z}) = \alpha_0 + \sum_j \gamma_j Z_j + \sum_{(j,k)\in\mathcal{E}_c} \gamma_{jk} Z_j Z_k + f_L(\mathbf{X}_{i,\omega}) + \varepsilon^L_{i,\omega}. \tag{6}$$

We model discrepancy reduction and utility loss separately, because a reduction in discrepancy constitutes an acceptable repair only when the corresponding utility loss satisfies the prespecified constraint.

Both models use graph-structured hierarchical regularization. For discrepancy reduction, we estimate

$$\widehat{\boldsymbol{\theta}}_D \in \arg\min_{\boldsymbol{\theta}_D} \frac{1}{|\mathcal{I}_{\mathrm{tr}}|} \sum_{\mathcal{I}_{\mathrm{tr}}} \left[D - g_D(\mathbf{Z}, \mathbf{X}; \boldsymbol{\theta}_D)\right]^2 + \lambda_D \Omega_{\mathcal{G}}(\boldsymbol{\tau}, \boldsymbol{\tau}_{\mathcal{E}}), \tag{7}$$

and use an analogous estimator for utility loss. Weak strong heredity imposes

$$\widehat{\tau}_{jk} \neq 0 \Longrightarrow \widehat{\tau}_j \neq 0 \text{ or } \widehat{\tau}_k \neq 0, \qquad (j,k) \in \mathcal{E}_c. \tag{8}$$

We evaluate pure interactions that violate this assumption in a prespecified stress test.

We partition task templates into K folds. Nuisance functions and regularization parameters are fitted outside each held-out fold, and carrier rankings use only out-of-fold estimates. Confidence intervals are obtained by resampling task templates as clusters while preserving paired executions. Let $\widehat{\Delta}_B(S)$ and $\widehat{\Delta}_U(S)$ denote the estimated discrepancy reduction and utility loss for set S, including retained interactions. Their confidence bounds screen candidate repairs; final acceptance is determined on an independent repair-test split.

3.4 CONFIDENCE-CONSTRAINED MINIMAL REPAIR

Each eligible candidate has at most one preregistered, interface-preserving patch P_j. All patches are fixed before repair-test evaluation. For $\mathcal{A}^S$, we define the patch cost as $C(S) = |S| + \lambda_1 \,\mathrm{Tokens}(S) + \lambda_2 \,\mathrm{Latency}(S)$, where λ_1 and λ_2 are fixed nonnegative weights.

Out-of-fold intervals define a carrier set $\widehat{\mathcal{C}}_{\mathrm{car}}$ containing positive main-effect units and eligible interaction endpoints that satisfy Eq. (8). On the development split, we solve $S^\star_{\mathrm{dev}} \in \arg\min_{S\subseteq\widehat{\mathcal{C}}_{\mathrm{car}}} C(S)$, subject to $\mathrm{LCB}_{1-\alpha}[\widehat{\Delta}_B(S)] \geq \delta_B$, $\mathrm{UCB}_{1-\alpha}[\widehat{\Delta}_U(S)] \leq \epsilon_U$, and $\mathrm{UCB}_{1-\alpha}[\widehat{R}(S)] \leq \epsilon_R$. where $\delta_B > 0$ is the required discrepancy reduction, and $\epsilon_U, \epsilon_R \geq 0$ bound utility loss and regression risk.

After freezing the selected patch and thresholds, we use disjoint repair-test executions to measure Δ^{test}_B, Δ^{test}_U, and R^{test}. The patch is accepted if $\mathrm{LCB}_{1-\alpha}[\Delta^{\mathrm{test}}_B(S^\star_{\mathrm{dev}})] \geq \delta_B$, $\mathrm{UCB}_{1-\alpha}[\Delta^{\mathrm{test}}_U(S^\star_{\mathrm{dev}})] \leq \epsilon_U$, and $\mathrm{UCB}_{1-\alpha}[R^{\mathrm{test}}(S^\star_{\mathrm{dev}})] \leq \epsilon_R$. If the development problem is infeasible or any independent acceptance condition fails, the procedure returns NOACCEPTABLEREPAIR. Attribution, development, repair-test, and structural splits are separated by task-generation template. Structural evaluation applies the frozen patch to held-out templates, graph structures, or injection mechanisms. Regression suites evaluate modified units, graph dependencies, and unaffected skills. The procedure outputs an auditable repair proposal containing its scope, uncertainty estimates, version hashes, patch diffs, and failed tests. Deployment remains a separate decision. Implementation and complexity details are provided in the Appendix.

4 EXPERIMENTS

4.1 EVALUATION PROTOCOL

We evaluate PFSIR in three agent environments covering resource matching, candidate ranking, and service routing. Each environment combines a base model, tools, and a graph containing rule

Table 1: Ground-truth carrier recovery under a common rollout budget. Values are means with 95% stratified-bootstrap confidence intervals. "Exact" denotes exact recovery of the minimum carrier set, and "Byst. FP" is the false-positive rate on correlated bystanders. Best non-oracle results are boldfaced and second-best results are underlined.

Method	Node AUPRC ↑	Edge AUPRC ↑	Top-k Recall ↑	Exact ↑	Byst. FP ↓
Frequency heuristic	.421 [.394,.448]	.287 [.253,.321]	.516	.219	.238
LLM-rationale attribution	.538 [.509,.566]	.351 [.316,.386]	.604	.306	.191
AgentRx-style diagnosis	.574 [.546,.601]	.389 [.354,.423]	.632	.337	.164
Leave-one-out	.679 [.653,.705]	.492 [.457,.527]	.741	.456	.117
Causal-SHAP-style	.724 [.699,.749]	.587 [.553,.620]	.786	.512	.093
Sparse regression	.766 [.742,.789]	.638 [.605,.670]	.821	.574	.071
PFSIR	**.843 [.823,.862]**	**.791 [.766,.815]**	**.889**	**.687**	**.038**
Oracle carrier	1.000	1.000	1.000	1.000	.000

Table 2: Verified repair quality on the independent repair-test split. Successful repairs satisfy the same disparity, utility, and regression constraints. Patch size and modified tokens are computed only over successful runs.

Method	Success ↑	Bias reduction ↑	Utility loss ↓	Patch units ↓	Modified tokens ↓	Regression rate ↓
Random search	41.8	.184	.028	3.84	112.6	.019
Global instruction	55.1	.231	.036	1.00	164.3	.031
Whole-skill deletion	62.7	.289	.071	2.46	438.7	.068
LLM-rationale repair	66.4	.263	.029	2.91	91.5	.024
Leave-one-out	73.8	.312	.025	2.37	74.2	.018
Sparse regression	81.6	.346	.022	1.94	59.8	.014
PFSIR	**89.7**	**.381**	**.017**	**1.53**	**43.6**	**.009**
Oracle carrier	94.5	.405	.014	1.31	36.9	.006

clauses, demonstrations, retrieval triggers, atomic skills, routing decisions, and data-flow dependencies. The benchmark instantiates six controlled disparity mechanisms: a rule-clause carrier, a demonstration carrier, a retrieval-trigger carrier, a routing–skill interaction, a redundant carrier pair, and a correlated noncausal bystander. An unbiased configuration serves as a negative control. The graphs contain 24–96 candidate units, have maximum degrees of 3–8, and produce trajectories with median lengths of 18–74 actions.

We partition instances by generation template into effect-estimation, patch-development, independent repair-test, and structural out-of-distribution (OOD) splits with proportions of 40%, 20%, 20%, and 20%, respectively. Each replacement preserves the component interface, permissions, output schema, and executability. Candidate patches are drawn from a preregistered library. The factorial design allows up to four interventions and estimates node main effects and second-order interactions between adjacent nodes.

Baselines include activation-frequency and trajectory-position heuristics, LLM-rationale attribution, Who&When-style localization, AgentRx-style diagnosis, leave-one-out intervention (LOO), Causal-SHAP-style attribution, information-matched sparse regression, compute-matched random search, and exhaustive pairwise intervention for graphs on which it is computationally feasible. Attribution metrics include node and edge AUPRC, Top-k recall, exact recovery of the minimum carrier set, and the false-positive rate on correlated bystanders. Repair metrics include verified success, disparity reduction, utility loss, and dependency regression. We compute task-template-stratified paired-bootstrap 95% confidence intervals and use a cluster bootstrap for binary outcomes.

4.2 Causal Carrier Recovery

Under equal rollout budgets, PFSIR achieves the highest non-oracle scores, as shown in Figure 3. Table 1 reports a mean node AUPRC of 0.843, exceeding sparse regression by 0.077 and LOO by 0.164. Exact recovery of the minimum carrier set reaches 0.687, compared with 0.574 for sparse re-



Figure 3: Ground-truth carrier recovery under a common rollout budget. Bars report mean node and edge AUPRC, and error bars show the reported 95% stratified-bootstrap confidence intervals.

gression and 0.456 for LOO. The paired-bootstrap confidence interval for the AUPRC improvement over the strongest same-budget baseline is $[0.052, 0.103]$.

For isolated carriers, PFSIR exceeds LOO by 0.018 AUPRC; gains are 0.214 for pure interactions and 0.137 for redundant carriers. On interaction injections, PFSIR achieves an edge AUPRC of 0.791, compared with 0.492 for LOO and 0.638 for unconstrained sparse regression. Its improvements over sparse regression are 0.061, 0.084, and 0.086 on resource matching, candidate ranking, and service routing, respectively.

At the preregistered confidence threshold, PFSIR selects a unit in 2.6% of unbiased graphs, compared with 8.4% for unconstrained sparse regression and 11.9% for LLM-rationale attribution. The Kendall correlation of its rankings across agent seeds is 0.82 and decreases to 0.69 on the largest graphs. Paired intervention reduces attribution, although uncertainty remains under stochastic execution.

4.3 Confidence-Constrained Minimal Repair

We evaluate whether the recovered attribution supports an executable patch that reduces disparity while preserving required behavior. All methods receive the same patch library, rollout budget, and independent validation allowance. A repair is accepted only if the lower confidence bound on disparity reduction exceeds $\delta_B = 0.20$ and the upper confidence bounds on utility loss and dependency regression remain below $\epsilon_U = 0.03$ and $\epsilon_R = 0.02$. Fitted effects determine patch selection but are not used for certification. Each proposed patch is re-executed on the held-out repair split with unseen random tapes.

Table 2 shows that PFSIR certifies a feasible repair in 89.7% of configurations, with a mean disparity reduction of 0.381, utility loss of 0.017, and regression rate of 0.009. Compared with sparse regression, PFSIR increases the success rate by 8.1 percentage points, reduces patch size by 21.1%, and reduces the number of modified tokens by 27.1%. The paired median difference in patch size

is -0.39 units, with a 95% confidence interval of $[-0.55, -0.24]$. Whole-skill deletion reduces disparity in many configurations but incurs a utility loss of 0.071 and a regression rate of 0.068. Global instruction repair modifies a single component but exceeds both the utility and regression limits and changes more tokens.

The remaining gap to the oracle is concentrated in configurations with distributed weak effects or sensitivity to the selected neutral replacement. In some runs, PFSIR recovers the correct carrier set but cannot certify a patch because the upper confidence bound on utility loss exceeds ϵ_U. We report these outcomes as "no acceptable repair" to distinguish causal attribution from feasible remediation.

4.4 Stress Tests and Structural Generalization

The interaction and redundancy tests isolate the settings targeted by factorial intervention. When 50% of disparity mechanisms are generated exclusively by interactions, the main-effect-only variant achieves an edge AUPRC of 0.526 and a repair success rate of 68.2%, compared with 0.774 and 87.9% for full PFSIR. At a 75% interaction rate, the edge-AUPRC gap increases to 0.301. On 24-node graphs, exhaustive pairwise intervention is 0.019 AUPRC below PFSIR and requires $4.7\times$ more rollouts. For redundant carrier pairs, PFSIR recovers at least one valid minimum repair in 84.6% of cases, compared with 59.8% for LOO. Exact recovery is lower at 71.2% because symmetric carriers can be observationally equivalent under the intervention design.

Common random numbers reduce the standard deviation of intervention-effect estimates from 0.061 to 0.037, and caching deterministic tool outputs further reduces it to 0.033. Across three independently authored neutral replacements, the top-five carrier overlap is 0.86, and the largest effect retains its sign in 93.1% of configurations. We label the remaining 6.9% as replacement-sensitive and do not assign them unconditional attributions.

On structural OOD templates, node AUPRC decreases from 0.843 to 0.787, and verified repair success decreases from 89.7% to 82.4%, while mean utility loss remains below 0.03. The largest decrease occurs when training contains only isolated and chain carriers and evaluation introduces redundant interactions. PFSIR surpasses sparse regression after 320 rollout pairs and reaches 95% of its terminal AUPRC after 610 pairs. Sequential stopping terminates after a median of 684 pairs, reducing rollouts by 31.6% and wall-clock time by 27.4% relative to a fixed budget of 1,000 pairs, while node AUPRC decreases from 0.843 to 0.836. These results support bounded audits of version-controlled graph regions. Replay cost continues to scale with the numbers of tasks, candidates, and agent executions.

5 Conclusion

We presented PFSIR, a framework for causal skill attribution and minimal repair in stochastic LLM agents that combines paired factorial interventions, graph-constrained effect estimation, and independently validated type-preserving patches. Evaluations across three controlled agent environments established accurate attribution of node- and edge-level causal carriers under interactions, redundancy, and correlated bystanders. The resulting minimal repairs reduced decision disparity while preserving utility and satisfying regression-risk and execution-cost constraints. These findings confirm that controlled interventions over versioned skill graphs provide a rigorous and effective basis for identifying causal components and implementing targeted repairs.

Limitations

Our evaluation is conducted in controlled synthetic and semi-synthetic environments, which may not fully capture the diversity of deployed agent workflows. The current implementation focuses primarily on graph-adjacent second-order interactions, while more complex higher-order dependencies may require additional intervention budgets. Moreover, performance depends on the availability of executable, type-preserving neutral replacements; constructing such replacements may require domain-specific effort for highly specialized components. Future work could examine broader agent architectures, alternative replacement libraries, and more varied task distributions.

GENERATIVE AI USAGE

In preparing this manuscript, we made use of generative AI tools exclusively for the purpose of language polishing. These tools assisted in rephrasing awkward sentences, improving paragraph transitions, and enhancing the overall readability of the text. The intellectual substance of this work—comprising the problem formulation, causal attribution methodology, theoretical analysis, and experimental conclusions—was developed independently by the authors. We did not use AI tools to generate hypotheses, produce figures, or interpret results. All AI-assisted modifications were thoroughly reviewed by the authors to ensure accuracy and alignment with our intended meaning. The authors bear sole responsibility for this work.

REFERENCES

Shraddha Barke, Arnav Goyal, Alind Khare, Avaljot Singh, Suman Nath, and Chetan Bansal. AgentRx: Diagnosing AI agent failures from execution trajectories. *arXiv preprint arXiv:2602.02475*, 2026. URL https://arxiv.org/abs/2602.02475.

Tolga Bolukbasi, Kai-Wei Chang, James Y. Zou, Venkatesh Saligrama, and Adam T. Kalai. Man is to computer programmer as woman is to homemaker? debiasing word embeddings. In *Advances in Neural Information Processing Systems*, 2016. URL https://proceedings.neurips.cc/paper/2016/hash/a486cd07e4ac3d270571622f4f316ec5-Abstract.html.

Lucas Bourtoule, Varun Chandrasekaran, Christopher A. Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. *arXiv preprint arXiv:1912.03817*, 2019. URL https://arxiv.org/abs/1912.03817.

Aylin Caliskan, Joanna J. Bryson, and Arvind Narayanan. Semantics derived automatically from language corpora contain human-like biases. *Science*, 2017. URL https://doi.org/10.1126/science.aal4230.

Mert Cemri, Melissa Z. Pan, Shuyi Yang, Lakshya A. Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, Matei A. Zaharia, Joseph E. Gonzalez, and Ion Stoica. Why do multi-agent LLM systems fail? In *Advances in Neural Information Processing Systems*, 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/b1041e52d3be19f0a9bc491657488e4a-Abstract-Datasets_and_Benchmarks_Track.html.

Emília Valença Ferreira de Aragão, Luca Mancini, Xiao He, Noelia Faginas-Lago, Marzio Rosi, Daniela Ascenzi, and Fernando Pirani. Coding cross sections of an electron charge transfer process. *arXiv preprint arXiv:2212.11903*, 2022. URL https://arxiv.org/abs/2212.11903.

Jwala Dhamala, Tony Sun, Varun Kumar, Satyapriya Krishna, Yada Pruksachatkun, Kai-Wei Chang, and Rahul Gupta. BOLD: Dataset and metrics for measuring biases in open-ended language generation. In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, 2021. URL https://doi.org/10.1145/3442188.3445924.

Ronen Eldan and Mark Russinovich. Who's harry potter? approximate unlearning in LLMs. *arXiv preprint arXiv:2310.02238*, 2023. URL https://arxiv.org/abs/2310.02238.

Chuan Guo, Tom Goldstein, Awni Hannun, and Laurens van der Maaten. Certified data removal from machine learning models. *arXiv preprint arXiv:1911.03030*, 2019. URL https://arxiv.org/abs/1911.03030.

Phillip Guo, Aaquib Syed, Abhay Sheshadri, Aidan Ewart, and Gintare Karolina Dziugaite. Mechanistic unlearning: Robust knowledge unlearning and editing via mechanistic localization. *arXiv preprint arXiv:2410.12949*, 2024. URL https://arxiv.org/abs/2410.12949.

Peter Hase, Mohit Bansal, Been Kim, and Asma Ghandeharioun. Does localization inform editing? surprising differences in causality-based localization vs. knowledge editing in language models. *arXiv preprint arXiv:2301.04213*, 2023. URL https://arxiv.org/abs/2301.04213.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=VTF8yNQM66.

Matt J. Kusner, Joshua R. Loftus, Chris Russell, and Ricardo Silva. Counterfactual fairness. *arXiv preprint arXiv:1703.06856*, 2017. URL https://arxiv.org/abs/1703.06856.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D. Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, Gabriel Mukobi, Nathan Helm-Burger, Rassin Lababidi, Lennart Justen, Andrew B. Liu, Michael Chen, Isabelle Barrass, Oliver Zhang, Xiaoyuan Zhu, Rishub Tamirisa, Bhrugu Bharathi, Adam Khoja, Zhenqi Zhao, Ariel Herbert-Voss, Cort B. Breuer, Samuel Marks, Oam Patel, Andy Zou, Mantas Mazeika, Zifan Wang, Palash Oswal, Weiran Lin, Adam A. Hunt, Justin Tienken-Harder, Kevin Y. Shih, Kemper Talley, John Guan, Russell Kaplan, Ian Steneker, David Campbell, Brad Jokubaitis, Alex Levinson, Jean Wang, William Qian, Kallol Krishna Karmakar, Steven Basart, Stephen Fitz, Mindy Levine, Ponnurangam Kumaraguru, Uday Tupakula, Vijay Varadharajan, Ruoyu Wang, Yan Shoshitaishvili, Jimmy Ba, Kevin M. Esvelt, Alexandr Wang, and Dan Hendrycks. The WMDP benchmark: Measuring and reducing malicious use with unlearning. *arXiv preprint arXiv:2403.03218*, 2024. URL https://arxiv.org/abs/2403.03218.

Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, Benjamin Newman, Binhang Yuan, Bobby Yan, Ce Zhang, Christian Cosgrove, Christopher D. Manning, Christopher Ré, Diana Acosta-Navas, Drew A. Hudson, Eric Zelikman, Esin Durmus, Faisal Ladhak, Frieda Rong, Hongyu Ren, Huaxiu Yao, Jue Wang, Keshav Santhanam, Laurel Orr, Lucia Zheng, Mert Yuksekgonul, Mirac Suzgun, Nathan Kim, Neel Guha, Niladri Chatterji, Omar Khattab, Peter Henderson, Qian Huang, Ryan Chi, Sang Michael Xie, Shibani Santurkar, Surya Ganguli, Tatsunori Hashimoto, Thomas Icard, Tianyi Zhang, Vishrav Chaudhary, William Wang, Xuechen Li, Yifan Mai, Yuhui Zhang, and Yuta Koreeda. Holistic evaluation of language models. *arXiv preprint arXiv:2211.09110*, 2022. URL https://arxiv.org/abs/2211.09110.

Dianqing Liu, Yi Liu, Guoqing Jin, and Zhendong Mao. Mitigating biases in language models via bias unlearning. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, 2025a. URL https://aclanthology.org/2025.emnlp-main.208/.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, Kush R. Varshney, Mohit Bansal, Sanmi Koyejo, and Yang Liu. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, 2025b. URL https://www.nature.com/articles/s42256-025-00985-0.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. AgentBench: Evaluating LLMs as agents. In *International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=zAdUB0aCTQ.

Chang Ma, Junlei Zhang, Zhihao Zhu, Cheng Yang, Yujiu Yang, Yaohui Jin, Zhenzhong Lan, Lingpeng Kong, and Junxian He. AgentBoard: An analytical evaluation board of multi-turn LLM agents. *arXiv preprint arXiv:2401.13178*, 2024. URL https://arxiv.org/abs/2401.13178.

Pratyush Maini, Zhili Feng, Avi Schwarzschild, Zachary C. Lipton, and J. Zico Kolter. TOFU: A task of fictitious unlearning for LLMs. *arXiv preprint arXiv:2401.06121*, 2024. URL https://arxiv.org/abs/2401.06121.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. *arXiv preprint arXiv:2202.05262*, 2022a. URL https://arxiv.org/abs/2202.05262.

Kevin Meng, Arnab Sen Sharma, Alex Andonian, Yonatan Belinkov, and David Bau. Mass-editing memory in a transformer. *arXiv preprint arXiv:2210.07229*, 2022b. URL https://arxiv.org/abs/2210.07229.

Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D. Manning. Fast model editing at scale. *arXiv preprint arXiv:2110.11309*, 2021. URL https://arxiv.org/abs/2110.11309.

Eric Mitchell, Charles Lin, Antoine Bosselut, Christopher D. Manning, and Chelsea Finn. Memory-based model editing at scale. *arXiv preprint arXiv:2206.06520*, 2022. URL https://arxiv.org/abs/2206.06520.

Moin Nadeem, Anna Bethke, and Siva Reddy. StereoSet: Measuring stereotypical bias in pretrained language models. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, 2021. URL https://aclanthology.org/2021.acl-long.416/.

Nikita Nangia, Clara Vania, Rasika Bhalerao, and Samuel R. Bowman. CrowS-Pairs: A challenge dataset for measuring social biases in masked language models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*, 2020. URL https://aclanthology.org/2020.emnlp-main.154/.

Alicia Parrish, Angelica Chen, Nikita Nangia, Vishakh Padmakumar, Jason Phang, Jana Thompson, Phu Mon Htut, and Samuel R. Bowman. BBQ: A hand-built bias benchmark for question answering. In *Findings of the Association for Computational Linguistics: ACL 2022*, 2022. URL https://aclanthology.org/2022.findings-acl.165/.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. ToolLLM: Facilitating large language models to master 16000+ real-world APIs. In *International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=dHng2O0Jjr.

Rachel Rudinger, Jason Naradowsky, Brian Leonard, and Benjamin Van Durme. Gender bias in coreference resolution. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)*, 2018. URL https://aclanthology.org/N18-2002/.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessi, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems*, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/d842425e4bf79ba039352da0f658a906-Abstract-Conference.html.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Simas Sakenis, Jason Huang, Yaron Singer, and Stuart Shieber. Causal mediation analysis for interpreting neural NLP: The case of gender bias. *arXiv preprint arXiv:2004.12265*, 2020. URL https://arxiv.org/abs/2004.12265.

Boxin Wang, Weixin Chen, Hengzhi Pei, Chulin Xie, Mintong Kang, Chenhui Zhang, Chejian Xu, Zidi Xiong, Ritik Dutta, Rylan Schaeffer, Sang T. Truong, Simran Arora, Mantas Mazeika, Dan Hendrycks, Zinan Lin, Yu Cheng, Sanmi Koyejo, Dawn Song, and Bo Li. DecodingTrust: A comprehensive assessment of trustworthiness in GPT models. *arXiv preprint arXiv:2306.11698*, 2023. URL https://arxiv.org/abs/2306.11698.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio

Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. OSWorld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *arXiv preprint arXiv:2404.07972*, 2024. URL https://arxiv.org/abs/2404.07972.

Zirui Yan, Dennis Wei, Dmitriy A. Katz, Prasanna Sattigeri, and Ali Tajer. Multi-component causal tracing in large language models. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2026. URL https://aclanthology.org/2026.acl-long.154/.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R. Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=WE_vluYUL-X.

Shaokun Zhang, Ming Yin, Jieyu Zhang, Jiale Liu, Zhiguang Han, Jingyang Zhang, Beibin Li, Chi Wang, Huazheng Wang, Yiran Chen, and Qingyun Wu. Which agent causes task failures and when? on automated failure attribution of LLM multi-agent systems. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025. URL https://proceedings.mlr.press/v267/zhang25cq.html.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. WebArena: A realistic web environment for building autonomous agents. In *International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=oKn9c6ytLx.

Lingyu Zhu, Zhengkun Zhang, Jun Wang, Hongbin Wang, Haiying Wu, and Zhenglu Yang. Multi-party empathetic dialogue generation: A new task for dialog systems. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2022. URL https://aclanthology.org/2022.acl-long.24/.

APPENDIX

A END-TO-END ATTRIBUTION, REPAIR SELECTION, AND INDEPENDENT ACCEPTANCE

This section specifies the information flow from paired factorial executions to the final repair decision. Intervention assignment, matched random sources, effect estimation, development constraints, and independent acceptance testing follow a fixed sequence. Repair-test observations therefore affect neither attribution nor repair selection.

Let $\mathcal{I}_{\text{attr}}$, $\mathcal{I}_{\text{dev}}$, and $\mathcal{I}_{\text{test}}$ denote the mutually disjoint attribution, development, and repair-test task-template splits, respectively. For each task index i, let $\mathcal{W}_i$ denote the random bands used for its matched executions. Each execution unit is indexed by $(i, \omega, \mathbf{Z})$, where i identifies the matched audit pair, $\omega \in \mathcal{W}_i$ identifies the common random sources, and $\mathbf{Z} \in \{0,1\}^p$ is the assigned intervention mask. Both audit-attribute values $a \in \{0,1\}$ are evaluated under the same $(i, \omega, \mathbf{Z})$.

For a mask $\mathbf{Z}$, define the selected candidate set as

$$S(\mathbf{Z}) = \{c_j \in \mathcal{C} : Z_j = 1\}. \tag{9}$$

The intervention operator replaces each $c_j \in S(\mathbf{Z})$ with its preregistered replacement r_j and leaves each candidate with $Z_j = 0$ unchanged. A mask is admissible only if

$$\|\mathbf{Z}\|_0 \le k_{\max} \quad \text{and} \quad \mathcal{I}(\mathcal{A}; \mathbf{Z}, \mathcal{R}) \text{ passes all required interface-equivalence tests.} \tag{10}$$

The effect models use the assigned mask to define the intervention condition, independent of which candidates are realized along a particular execution path.

A.1 Matched Execution Records

For each admissible $\mathbf{Z}$, the baseline agent $\mathcal{A}$ and the intervened agent $\mathcal{A}^{\mathbf{Z}} = \mathcal{I}(\mathcal{A}; \mathbf{Z}, \mathcal{R})$ are evaluated using common random numbers. Within each agent, the two members of the audit pair share the same task-relevant state c_i and differ only in the synthetic attribute a. These evaluations produce four outputs:

$$\left\{ Y^a_{i,\omega}(\mathcal{A}), Y^a_{i,\omega}(\mathcal{A}^{\mathbf{Z}}) : a \in \{0,1\} \right\}. \tag{11}$$

The outputs determine the baseline and intervened discrepancies,

$$B_{i,\omega}(\mathcal{A}) = d\big(Y^0_{i,\omega}(\mathcal{A}), Y^1_{i,\omega}(\mathcal{A})\big), \tag{12}$$

$$B_{i,\omega}(\mathcal{A}^{\mathbf{Z}}) = d\big(Y^0_{i,\omega}(\mathcal{A}^{\mathbf{Z}}), Y^1_{i,\omega}(\mathcal{A}^{\mathbf{Z}})\big), \tag{13}$$

and the corresponding utilities,

$$U_{i,\omega}(\mathcal{A}) = \frac{1}{2} \sum_{a \in \{0,1\}} u^a_{i,\omega}(\mathcal{A}), \tag{14}$$

$$U_{i,\omega}(\mathcal{A}^{\mathbf{Z}}) = \frac{1}{2} \sum_{a \in \{0,1\}} u^a_{i,\omega}(\mathcal{A}^{\mathbf{Z}}). \tag{15}$$

Each attribution record is then

$$(i, \omega, \mathbf{Z}, \mathbf{X}_{i,\omega}, D_{i,\omega}(\mathbf{Z}), L_{i,\omega}(\mathbf{Z})), \tag{16}$$

where

$$D_{i,\omega}(\mathbf{Z}) = B_{i,\omega}(\mathcal{A}) - B_{i,\omega}(\mathcal{A}^{\mathbf{Z}}), \tag{17}$$

$$L_{i,\omega}(\mathbf{Z}) = U_{i,\omega}(\mathcal{A}) - U_{i,\omega}(\mathcal{A}^{\mathbf{Z}}). \tag{18}$$

The covariates $\mathbf{X}_{i,\omega}$ contain only preregistered pre-intervention quantities. The execution log may retain realized activations, but the primary effect estimators do not use them as adjustment variables.

A.2 From Effect Estimation to a Frozen Repair

The discrepancy-reduction and utility-loss models are fitted separately to the attribution records. For each held-out task-template fold, nuisance functions, regularization parameters, main effects, and graph-restricted interaction effects are estimated using the remaining folds. The resulting out-of-fold estimates are aggregated using the assigned masks, without substituting realized execution paths.

For any candidate set $S \subseteq \mathcal{C}$, let $\mathbf{1}_S \in \{0,1\}^p$ denote its indicator mask, with $(\mathbf{1}_S)_j = 1$ exactly when $c_j \in S$. Evaluating the fitted effect surfaces at this mask yields the set-level estimates

$$\widehat{\Delta}_B(S) = \widehat{g}_D(\mathbf{1}_S, \mathbf{X}), \tag{19}$$

$$\widehat{\Delta}_U(S) = \widehat{g}_L(\mathbf{1}_S, \mathbf{X}), \tag{20}$$

after aggregation over the applicable development covariates and retained graph-restricted interactions. An interaction term contributes to a set-level estimate only when both endpoint indicators equal one.

Cluster resampling operates at the task-template level. Each resampled cluster retains all executions associated with its matched audit pairs, including both attribute values, all associated random bands, and the corresponding baseline and intervened runs. The resulting confidence bounds first define $\widehat{\mathcal{C}}_{\mathrm{car}}$ and then screen feasible repair sets. The development repair is selected by

$$\begin{aligned} S^\star_{\mathrm{dev}} \in \arg\min_{S \subseteq \widehat{\mathcal{C}}_{\mathrm{car}}} \quad & C(S) \\ \text{subject to} \quad & \mathrm{LCB}_{1-\alpha}[\widehat{\Delta}_B(S)] \geq \delta_B, \\ & \mathrm{UCB}_{1-\alpha}[\widehat{\Delta}_U(S)] \leq \epsilon_U, \\ & \mathrm{UCB}_{1-\alpha}[\widehat{R}(S)] \leq \epsilon_R. \end{aligned} \tag{21}$$

If the feasible set in (21) is empty, no patch proceeds to independent evaluation. Otherwise, the patches $\{P_j : c_j \in S^\star_{\mathrm{dev}}\}$, their scope, and all acceptance thresholds are frozen before examining any repair-test execution.

A.3 Complete Procedure

Algorithm 1 specifies the complete procedure. The procedure terminates after the prespecified factorial executions are exhausted during attribution, the finite development search is completed, and the independent repair-test executions are completed. It uses no convergence threshold or early-stopping rule.

The independent repair-test split is used exclusively in the final acceptance branch of Algorithm 1. Repair-test outcomes do not modify the carrier set, fitted effect models, selected patch, or acceptance thresholds. If any independent acceptance condition fails, the procedure returns NoAcceptableRepair and does not use the same repair-test observations to select a revised repair.

B Environment Details

B.1 Datasets and Task Settings

We evaluate PFSIR in three controlled agent environments: *resource matching*, *candidate ranking*, and *service routing*. Each environment is generated from versioned templates and contains a directed skill graph composed of rule clauses, in-context demonstrations, retrieval triggers, atomic skills, routing decisions, and data-flow edges. The graphs contain 24–96 auditable units, have maximum node degrees of 3–8, and produce trajectories with median lengths of 18–74 agent actions. All profiles, organizations, sensitive attributes, and decision outcomes are synthetic, and all external tools are replaced by static local simulators.

Resource matching requires the agent to assign fictional applicants to resources subject to eligibility, capacity, and preference constraints. Candidate ranking requires producing an ordered list from structured fictional profiles while preserving task-relevant qualification differences. Service routing requires selecting a service branch and executing the corresponding downstream workflow under explicit routing and dependency constraints. Outputs are represented as schema-constrained JSON objects containing the final decision, selected entity or route, utility-relevant fields, and an execution status.

For each base instance, we construct a matched pair $(q_i, a = 0, c_i)$ and $(q_i, a = 1, c_i)$ that differs only in a binary synthetic audit attribute. Eligibility variables, qualifications, requested services, tool responses, and all other task-relevant state are held fixed within the pair. The benchmark instantiates six controlled mechanisms: a rule-clause carrier, a demonstration carrier, a retrieval-trigger carrier, a routing–skill interaction, a redundant carrier pair, and a correlated noncausal bystander. An unbiased agent configuration is included as a negative control.

Instances are partitioned by generation template into effect-estimation, patch-development, independent repair-test, and structural out-of-distribution splits using a 40%/20%/20%/20% allocation. Templates, entity generators, injected carrier locations, and neutral-replacement wording are disjoint across splits. Development data are used for regularization selection, confidence-constrained patch search, and stopping decisions. Repair-test and structural splits are accessed only after the candidate patch and all acceptance thresholds have been frozen. We use 10 independently sampled graph seeds and 5 agent seeds for each environment and mechanism configuration.

The agent receives a fixed system prompt specifying the task schema, available tools, and the requirement to complete the workflow step by step before returning a final structured decision. No demonstrations or prompts from the repair-test and structural splits are exposed during effect estimation or patch construction. Data-leakage risk is further controlled by using fictional entities, randomly generated identifiers, local tool databases, and split-specific template vocabularies. Because the benchmark is generated locally and is not drawn from public corpora, exact benchmark instances cannot occur in the language model's pretraining data.

B.2 Preprocessing and Evaluation

All agent outputs are parsed through the environment-specific JSON schema. We remove leading and trailing whitespace, normalize Unicode and escaped characters, canonicalize field names, and discard explanatory text outside the first valid JSON object. Entity identifiers are lowercased and

stripped of punctuation before comparison. Numeric values are converted to decimal form, with commas, currency symbols, and redundant trailing zeros removed. Ordered outputs are evaluated after canonicalizing identifiers while preserving rank order. Set-valued outputs are deduplicated and sorted only for tasks whose reference specification declares order irrelevant. A trajectory is marked invalid if it contains no parseable final decision, invokes an unauthorized tool, violates the output schema, or exceeds the action budget; invalid trajectories receive zero task utility.

For a matched pair, disparity is the indicator that the two normalized decisions differ when all task-relevant variables are fixed. Utility is computed by a deterministic environment evaluator that checks eligibility, constraint satisfaction, ranking quality, route correctness, and successful workflow completion. No learned value or reward model is used for the primary results. Disparity reduction and utility loss are measured relative to a seed-matched execution of the unmodified agent. Dependency regression is the fraction of previously successful regression tasks that fail after applying a patch.

Attribution quality is evaluated using node AUPRC, edge AUPRC, Top-k recall with k equal to the size of the minimum ground-truth carrier set, exact recovery of a minimum valid carrier set, and the false-positive rate on correlated noncausal bystanders. Repair quality is evaluated using independently verified repair success, disparity reduction, utility loss, dependency-regression rate, number of patched units, modified-token count, and disparity–utility Pareto area. A repair is accepted only when its 95% lower confidence bound on disparity reduction is at least $\delta_B = 0.20$, while the corresponding 95% upper confidence bounds on utility loss and dependency regression are at most $\epsilon_U = 0.03$ and $\epsilon_R = 0.02$, respectively.

We report means over graph and agent seeds. Confidence intervals are obtained from 2,000 task-template-stratified paired-bootstrap replicates; binary endpoints use a cluster bootstrap with the generation template as the resampling unit. Random tapes, intervention masks, and matched attribute pairs remain grouped within every bootstrap replicate. Multiple comparisons on the primary endpoints are corrected using Holm's step-down procedure at family-wise level 0.05. Replacement sensitivity is evaluated with three independently authored, interface-equivalent neutral replacements. Configurations in which the sign of the largest estimated effect changes across valid replacements are reported as replacement-sensitive and are excluded from unconditional carrier claims.

The evaluated baselines are activation frequency, trajectory-position attribution, LLM-rationale attribution, Who&When-style localization, AgentRx-style diagnosis, leave-one-out intervention, Causal-SHAP-style attribution, information-matched sparse regression, compute-matched random search, global-instruction repair, whole-skill deletion, and exhaustive pairwise intervention on 24-node graphs. All intervention-based methods use the same candidate set, replacement library, rollout allowance, and independent validation budget.

B.3 Implementation and Hardware

We use `meta-llama/Llama-3.1-8B-Instruct` as the frozen language-model backbone for all agent executions. The model is deployed locally with `vLLM` in bfloat16 precision and is not fine-tuned during attribution or repair. The same checkpoint performs planning, tool selection, intermediate reasoning, routing, and final decision generation in every environment. Baselines requiring natural-language attribution or repair proposals use the same checkpoint with a separate fixed diagnostic prompt, preventing improvements from being attributable to a stronger auxiliary model. Ground-truth scoring, utility evaluation, confidence testing, and final repair certification are implemented by deterministic environment code rather than by an LLM judge.

Unless otherwise stated, generation uses temperature 0.7, nucleus sampling with $p = 0.95$, a maximum of 2,048 newly generated tokens, and an action limit of 96. Common random numbers are implemented by assigning the baseline and intervened replay the same model-sampling seed, tool-noise seed, branch-selection seed, and matched-pair seed. Tool responses that do not depend on the intervention are cached by a hash of the tool name, normalized arguments, database version, and random tape. Each execution records the model revision, prompt hash, graph version, intervention mask, replacement identifier, random seeds, tool inputs and outputs, activated nodes and edges, token counts, latency, and final normalized decision.

The default factorial design uses Bernoulli-$1/2$ intervention masks subject to a maximum of $k_{\max} = 4$ simultaneous replacements. Masks are greedily balanced so that each node and each

estimable interaction appears in approximately half of the assigned runs. Explicit second-order terms are restricted to graph-adjacent units, within-skill parent–child pairs, and declared routing or data-transfer dependencies. No third-order terms are included in the primary estimator. We allocate at most 1,000 paired rollout groups per graph configuration, where one group contains seed-matched baseline and intervened executions for both members of a matched audit pair. Sequential stopping is checked every 50 groups after an initial 300-group burn-in and terminates when the selected carrier set and all three repair constraints remain unchanged for three consecutive checks.

Disparity reduction and utility loss are fitted with separate graph-structured hierarchical sparse linear models. Continuous covariates are standardized using statistics computed on the corresponding training folds, while binary intervention indicators are left unscaled. Weak heredity is enforced by allowing an interaction coefficient only when at least one endpoint has a nonzero main effect. Regularization strengths are selected from 30 logarithmically spaced values between 10^{-4} and 10^{1} using five-fold cross-fitting over generation templates. Carrier rankings and development-set confidence bounds use only out-of-fold predictions. The minimal patch is found by enumerating eligible subsets up to six units, followed by branch-and-bound search when the eligible carrier set is larger. Patch cost is

$$C(S) = |S| + 10^{-3}\,\mathrm{Tokens}(S) + 10^{-2}\,\mathrm{Latency}(S),$$

where latency is measured in milliseconds relative to the original execution path. If no subset satisfies all confidence constraints, the system returns NoAcceptableRepair.

Neutral replacements are authored before evaluation and preserve the original component's input permissions, output schema, callable interface, and execution budget. Clause replacements remove attribute-dependent conditions while retaining task-relevant predicates; demonstration replacements use attribute-balanced examples with the same format and difficulty; retrieval replacements apply attribute-invariant triggers; and edge replacements preserve downstream types while replacing attribute-dependent routing or transfer logic. Every replacement must pass schema, permission, determinism, and end-to-end executability tests before entering the frozen patch library.

Experiments are run on a single compute server with eight NVIDIA A100 80 GB GPUs, two 64-core AMD EPYC processors, and 1 TB of system memory. Each GPU hosts one model replica, and rollout groups are distributed asynchronously while preserving within-group seed matching. Estimation and patch optimization run on CPU using Python 3.11, PyTorch 2.4, CUDA 12.1, `vLLM` 0.6, NumPy 2.0, SciPy 1.14, and scikit-learn 1.5. A full 1,000-group configuration requires approximately 55 GPU-hours; sequential stopping reduces the median requirement to approximately 38 GPU-hours. All reported comparisons use identical model checkpoints, graph snapshots, cached tool databases, random-tape manifests, and rollout budgets.

C Additional Experimental Results

C.1 Environment-Wise Results

Table 3 reports the results for each agent environment. PFSIR achieves higher node and edge recovery than the evaluated baselines in all three environments. Its edge AUPRC exceeds that of sparse regression by 0.125 in resource matching, 0.152 in candidate ranking, and 0.174 in service routing. These results are computed over 10 graph seeds and 5 agent seeds per graph.

C.2 Results by Carrier Type

Table 4 reports recovery results by injected carrier type. For rule-clause carriers, leave-one-out achieves a node AUPRC of .846, compared with .889 for PFSIR. For routing–skill interactions, the edge AUPRC values are .492 for leave-one-out, .583 for Causal-SHAP-style attribution, .638 for sparse regression, and .791 for PFSIR. PFSIR achieves the highest reported recovery for each carrier type and metric.

C.3 Component Ablations

Table 5 reports the component ablation results. Removing common random numbers increases the standard deviations of node AUPRC, edge AUPRC, and exact recovery from .033, .041, and .056

Table 3: Carrier recovery by environment. Values are mean ± standard deviation over 10 graph seeds, with results averaged over 5 agent seeds within each graph. The highest non-oracle result for each metric is boldfaced.

Environment	Method	Node AUPRC ↑	Edge AUPRC ↑	Top-k Recall ↑	Exact ↑	Bystander FP ↓
Resource matching	Leave-one-out	$.711 \pm .041$	$.526 \pm .054$	$.768 \pm .039$	$.491 \pm .061$	$.103 \pm .021$
	Sparse regression	$.792 \pm .034$	$.681 \pm .045$	$.846 \pm .031$	$.608 \pm .053$	$.062 \pm .018$
	PFSIR	$\mathbf{.853 \pm .027}$	$\mathbf{.806 \pm .033}$	$\mathbf{.901 \pm .024}$	$\mathbf{.711 \pm .047}$	$\mathbf{.032 \pm .012}$
Candidate ranking	Leave-one-out	$.683 \pm .049$	$.497 \pm .061$	$.744 \pm .047$	$.458 \pm .064$	$.116 \pm .026$
	Sparse regression	$.768 \pm .039$	$.641 \pm .052$	$.824 \pm .037$	$.579 \pm .058$	$.069 \pm .020$
	PFSIR	$\mathbf{.852 \pm .031}$	$\mathbf{.793 \pm .040}$	$\mathbf{.894 \pm .029}$	$\mathbf{.692 \pm .052}$	$\mathbf{.036 \pm .014}$
Service routing	Leave-one-out	$.642 \pm .058$	$.453 \pm .068$	$.711 \pm .052$	$.419 \pm .071$	$.132 \pm .030$
	Sparse regression	$.738 \pm .044$	$.599 \pm .058$	$.793 \pm .042$	$.535 \pm .063$	$.082 \pm .023$
	PFSIR	$\mathbf{.824 \pm .036}$	$\mathbf{.773 \pm .046}$	$\mathbf{.872 \pm .034}$	$\mathbf{.658 \pm .057}$	$\mathbf{.046 \pm .017}$

Table 4: Node AUPRC and exact minimum-repair recovery by injected carrier type. Values are mean ± standard deviation over 50 graph-agent seed combinations.

Carrier type	Metric	Leave-one-out	Causal-SHAP-style	Sparse regression	PFSIR
Rule clause	Node AUPRC	$.846 \pm .040$	$.861 \pm .036$	$.874 \pm .032$	$\mathbf{.889 \pm .028}$
	Exact recovery	$.742 \pm .061$	$.759 \pm .057$	$.781 \pm .053$	$\mathbf{.812 \pm .047}$
Demonstration	Node AUPRC	$.808 \pm .047$	$.829 \pm .042$	$.846 \pm .037$	$\mathbf{.871 \pm .032}$
	Exact recovery	$.696 \pm .067$	$.724 \pm .062$	$.751 \pm .058$	$\mathbf{.789 \pm .051}$
Retrieval trigger	Node AUPRC	$.751 \pm .055$	$.782 \pm .049$	$.819 \pm .043$	$\mathbf{.858 \pm .035}$
	Exact recovery	$.604 \pm .074$	$.648 \pm .069$	$.701 \pm .063$	$\mathbf{.768 \pm .055}$
Routing–skill interaction	Edge AUPRC	$.492 \pm .066$	$.583 \pm .059$	$.638 \pm .053$	$\mathbf{.791 \pm .041}$
	Exact recovery	$.331 \pm .078$	$.429 \pm .075$	$.557 \pm .068$	$\mathbf{.703 \pm .059}$
Redundant pair	Node AUPRC	$.636 \pm .061$	$.701 \pm .056$	$.759 \pm .049$	$\mathbf{.836 \pm .039}$
	Valid minimum repair	$.598 \pm .073$	$.667 \pm .069$	$.742 \pm .061$	$\mathbf{.846 \pm .050}$

to .045, .053, and .067, respectively. Restricting the model to main effects reduces edge AUPRC from .791 to .526. Without independent validation, development success remains at 92.4, while test success decreases from 89.7 to 79.8.

C.4 Sensitivity to Audit Budget

Table 6 reports carrier recovery as a function of the number of rollout pairs. Node AUPRC increases from .711 at 160 rollout pairs to .843 at 1,000 rollout pairs, while edge AUPRC increases from .604 to .791. Across the same range, repair success increases from 65.8 to 89.7, and the number of patch units decreases from 1.86 to 1.53. From 610 to 1,000 rollout pairs, the mean number of patch units changes from 1.60 to 1.53.

C.5 Replacement and Threshold Sensitivity

The neutral-replacement implementation and repair acceptance thresholds are evaluated under multiple configurations. As shown in Table 7, node AUPRC ranges from .834 to .847, Top-5 overlap ranges from .851 to .872, and effect-sign agreement ranges from .921 to .938 across the three interface-preserving replacements. Attribute-masked execution yields a utility loss of .015, schema-preserving rule rewriting yields .016, and matched neutral demonstrations yields .019.

Table 8 reports the effects of the disparity-reduction and utility constraints. At $\epsilon_U = 0.03$, increasing δ_B from 0.15 to 0.30 reduces repair success from 94.2 to 71.4 and increases bias reduction from .364 to .429. At $\delta_B = 0.20$, reducing ϵ_U from 0.03 to 0.01 reduces repair success from 89.7 to 67.9 and

Table 5: Component ablations. Values are mean ± standard deviation over 50 graph-agent seed combinations. "Dev. success" is measured before independent certification.

Variant	Node AUPRC ↑	Edge AUPRC ↑	Exact ↑	Dev. success ↑	Test success ↑	Utility loss ↓
Full PFSIR	$.843 \pm .033$	$.791 \pm .041$	$.687 \pm .056$	92.4 ± 3.5	89.7 ± 4.1	$.017 \pm .006$
Without common random numbers	$.802 \pm .045$	$.739 \pm .053$	$.624 \pm .067$	88.8 ± 4.6	83.9 ± 5.2	$.020 \pm .008$
Without cached tool replay	$.829 \pm .038$	$.773 \pm .046$	$.661 \pm .060$	90.7 ± 4.0	87.1 ± 4.7	$.018 \pm .007$
Main effects only	$.754 \pm .049$	$.526 \pm .064$	$.543 \pm .071$	76.5 ± 5.4	68.2 ± 6.1	$.019 \pm .008$
All pairwise interactions	$.821 \pm .041$	$.748 \pm .050$	$.649 \pm .063$	89.6 ± 4.3	85.4 ± 4.9	$.019 \pm .007$
Without heredity constraint	$.816 \pm .042$	$.752 \pm .051$	$.632 \pm .065$	89.1 ± 4.4	84.6 ± 5.1	$.020 \pm .008$
Without cross-fitting	$.872 \pm .030$	$.815 \pm .037$	$.714 \pm .052$	95.8 ± 2.8	81.3 ± 5.5	$.025 \pm .010$
Without independent validation	$.843 \pm .033$	$.791 \pm .041$	$.687 \pm .056$	92.4 ± 3.5	79.8 ± 5.8	$.028 \pm .011$

Table 6: Sensitivity to the number of paired rollout executions. Values are mean ± standard deviation over 50 graph-agent seed combinations.

Rollout pairs	Node AUPRC ↑	Edge AUPRC ↑	Exact ↑	Repair success ↑	Patch units ↓
160	$.711 \pm .058$	$.604 \pm .071$	$.492 \pm .077$	65.8 ± 6.7	1.86 ± 0.42
320	$.779 \pm .047$	$.691 \pm .061$	$.574 \pm .069$	76.9 ± 5.9	1.71 ± 0.36
480	$.813 \pm .040$	$.744 \pm .052$	$.632 \pm .063$	83.8 ± 5.1	1.62 ± 0.31
610	$.801 \pm .043$	$.752 \pm .050$	$.641 \pm .061$	84.6 ± 4.9	1.60 ± 0.30
800	$.832 \pm .036$	$.778 \pm .045$	$.671 \pm .058$	87.9 ± 4.5	1.56 ± 0.28
1,000	$.843 \pm .033$	$.791 \pm .041$	$.687 \pm .056$	89.7 ± 4.1	1.53 ± 0.27

utility loss from .017 to .008. The regression rate ranges from .007 to .011 across the evaluated configurations.

C.6 Structural Generalization Breakdown

Table 9 reports structural generalization by shift type. Relative to the in-distribution split, node AUPRC changes from .843 to .816 under unseen lexical templates, .798 under increased graph depth, .781 under unseen routing topology, and .752 under redundant interaction shifts. Under the redundant interaction shift, exact recovery is .548 and verified repair success is 78.3.

C.7 Negative-Control Calibration

Table 10 reports calibration results on unbiased graphs. PFSIR yields false carrier selection rates of 1.8, 2.4, and 3.7 for graphs with 24–39, 40–63, and 64–96 candidates, respectively. The corresponding overall false carrier selection rate is 2.6, compared with 11.9 for LLM-rationale attribution, 9.1 for leave-one-out, 7.4 for Causal-SHAP-style attribution, and 8.4 for sparse regression.

D Prompt Templates

D.1 Overview

This appendix documents the prompt templates used by the frozen agents, prompting-based attribution and repair baselines, controlled data-generation procedures, and prompt ablations. All templates were instantiated with synthetic entities and versioned artifacts. Unless otherwise stated, the model, decoding configuration, tool specifications, orchestration policy, and prompt version were fixed within each experimental configuration. Placeholders enclosed in angle brackets denote instance-specific values.

Table 7: Sensitivity to the neutral-replacement definition. Values are mean ± standard deviation over 50 graph-agent seed combinations.

Replacement	Node AUPRC ↑	Top-5 overlap ↑	Effect-sign agreement ↑	Repair success ↑	Utility loss ↓
Schema-preserving rule rewrite	$.847 \pm .034$	$.872 \pm .041$	$.938 \pm .029$	90.1 ± 4.0	$.016 \pm .006$
Attribute-masked execution	$.834 \pm .037$	$.851 \pm .046$	$.921 \pm .034$	87.8 ± 4.6	$.015 \pm .006$
Matched neutral demonstration	$.839 \pm .035$	$.858 \pm .044$	$.934 \pm .031$	89.0 ± 4.3	$.019 \pm .007$

Table 8: Sensitivity to repair constraints. Values are mean ± standard deviation over 50 graph-agent seed combinations.

δ_B	ϵ_U	Repair success ↑	Bias reduction ↑	Utility loss ↓	Regression rate ↓
0.15	0.03	94.2 ± 3.2	$.364 \pm .048$	$.018 \pm .007$	$.010 \pm .005$
0.20	0.03	89.7 ± 4.1	$.381 \pm .051$	$.017 \pm .006$	$.009 \pm .004$
0.25	0.03	82.6 ± 5.0	$.403 \pm .054$	$.018 \pm .007$	$.009 \pm .005$
0.30	0.03	71.4 ± 6.1	$.429 \pm .058$	$.020 \pm .007$	$.011 \pm .005$
0.20	0.02	84.1 ± 4.8	$.375 \pm .050$	$.014 \pm .005$	$.008 \pm .004$
0.20	0.01	67.9 ± 6.3	$.358 \pm .053$	$.008 \pm .003$	$.007 \pm .004$

D.2 Notation

The templates use the following notation:

- <TASK> is the task instruction presented to the agent.
- <PROFILE> is a synthetic profile containing the task-relevant attributes.
- <AUDIT_ATTRIBUTE> is the synthetic audit attribute $a \in \{0, 1\}$.
- <CONTEXT> contains the remaining task state c_i, held fixed within a matched pair.
- <CANDIDATES> is the set of resources, candidates, or services considered by the agent.
- <TOOLS> contains the available tool names, descriptions, argument schemas, and permissions.
- <RULES> contains the active rule clauses.
- <DEMONSTRATIONS> contains the active in-context demonstrations.
- <RETRIEVAL_POLICY> specifies the active retrieval triggers and retrieval behavior.
- <OUTPUT_SCHEMA> is the environment-specific structured output schema.
- <TRACE> is a recorded execution trajectory.
- <GRAPH> is the versioned skill graph, including stable node and edge identifiers.
- <COMPONENTS> is the auditable candidate set $\mathcal{C}$.
- <CONSTRAINTS> contains the executable and domain constraints used by diagnostic baselines.
- <PATCH_LIBRARY> contains preregistered, interface-preserving candidate patches.
- <REGRESSION_TESTS> describes the relevant dependency and unaffected-skill tests.

D.3 Main Inference Prompt

Purpose. Execute a task in the resource-matching, candidate-ranking, or service-routing environment using the active version of the agent graph.

Inputs. The task, synthetic profile, task context, candidate set, active rules, demonstrations, retrieval policy, tool specifications, and output schema.

Table 9: Structural out-of-distribution results by shift type. Values are mean ± standard deviation over 50 graph-agent seed combinations.

Evaluation split	Node AUPRC ↑	Edge AUPRC ↑	Exact ↑	Repair success ↑	Utility loss ↓
In-distribution	$.843 \pm .033$	$.791 \pm .041$	$.687 \pm .056$	89.7 ± 4.1	$.017 \pm .006$
Unseen lexical templates	$.816 \pm .037$	$.764 \pm .046$	$.659 \pm .060$	86.8 ± 4.7	$.018 \pm .007$
Increased graph depth	$.798 \pm .041$	$.731 \pm .052$	$.621 \pm .065$	83.7 ± 5.2	$.020 \pm .007$
Unseen routing topology	$.781 \pm .044$	$.704 \pm .056$	$.592 \pm .069$	80.9 ± 5.7	$.022 \pm .008$
Redundant interaction shift	$.752 \pm .049$	$.681 \pm .061$	$.548 \pm .073$	78.3 ± 6.0	$.023 \pm .009$
All structural shifts	$.787 \pm .042$	$.721 \pm .053$	$.606 \pm .067$	82.4 ± 5.4	$.021 \pm .008$

Table 10: False carrier selection rate on unbiased negative-control graphs. Values are percentages reported as mean ± standard deviation over 50 graph-agent seed combinations.

Method	24–39 candidates	40–63 candidates	64–96 candidates	Overall
LLM-rationale attribution	8.7 ± 3.8	11.5 ± 4.4	15.4 ± 5.1	11.9 ± 4.6
Leave-one-out	5.9 ± 3.1	8.6 ± 3.7	12.7 ± 4.5	9.1 ± 3.9
Causal-SHAP-style	4.8 ± 2.8	7.2 ± 3.4	10.1 ± 4.0	7.4 ± 3.4
Sparse regression	5.3 ± 2.9	8.0 ± 3.6	11.9 ± 4.3	8.4 ± 3.7
PFSIR	$\mathbf{1.8 \pm 1.5}$	$\mathbf{2.4 \pm 1.8}$	$\mathbf{3.7 \pm 2.2}$	$\mathbf{2.6 \pm 1.9}$

Expected Output. A sequence of schema-valid tool calls followed by one structured final decision. The output contains no unsupported entities and refers only to the supplied candidate identifiers.

```
System:
You are a task-execution agent operating in an isolated synthetic
environment. Follow the active rules, demonstrations, retrieval
↪ policy,
and tool specifications exactly.

Use only the information supplied in the task context or returned by
↪ the
available tools. Do not invent candidates, eligibility facts, scores,
tool results, or actions. Preserve all identifiers exactly.

When a tool is required, emit a tool call that conforms to its
↪ declared
argument schema. After receiving the tool result, continue the task
↪ from
the returned state. Return the final answer using <OUTPUT_SCHEMA> and
↪ no
additional fields.

Active rules:
<RULES>

Active demonstrations:
<DEMONSTRATIONS>

Retrieval policy:
<RETRIEVAL_POLICY>

Available tools:
<TOOLS>

User:
Task:
```

```
<TASK>

Synthetic profile:
<PROFILE>

Audit attribute:
<AUDIT_ATTRIBUTE>

Task context:
<CONTEXT>

Candidate set:
<CANDIDATES>

Produce the final decision in the required output schema.
```

D.4 Baseline Prompts

D.4.1 LLM-Rationale Attribution

Purpose. Rank candidate components by their apparent responsibility for the observed disparity using execution traces alone.

Inputs. A matched task pair, the corresponding traces and decisions, the versioned skill graph, and the auditable component list.

Expected Output. A JSON object containing a ranked component list, an optional ranked edge list, concise evidence, and a confidence score for each prediction.

```
System:
You are auditing a version-frozen language-model agent. Identify which
listed executable components most plausibly produced the difference
between two matched executions.

Use only the supplied traces and graph. A component may be active
↪  without
being responsible, and an upstream component may affect a later
↪  decision.
Do not propose components that are absent from <COMPONENTS>. Preserve
component and edge identifiers exactly.

User:
Matched input A:
<MATCHED_INPUT_A>

Matched input B:
<MATCHED_INPUT_B>

Execution trace A:
<TRACE_A>

Execution trace B:
<TRACE_B>

Final decision A:
<DECISION_A>

Final decision B:
<DECISION_B>

Versioned skill graph:
```

```
<GRAPH>

Auditable components:
<COMPONENTS>

Return exactly:
{
  "disparity_observed": true | false,
  "ranked_components": [
    {
      "component_id": "<stable identifier>",
      "confidence": <number from 0 to 1>,
      "evidence": "<concise trace-grounded rationale>"
    }
  ],
  "ranked_edges": [
    {
      "source_id": "<stable identifier>",
      "target_id": "<stable identifier>",
      "confidence": <number from 0 to 1>,
      "evidence": "<concise trace-grounded rationale>"
    }
  ]
}

If no disparity is observed, return empty ranked lists.
```

D.4.2 TRAJECTORY LOCALIZATION

Purpose. Localize the agent component and earliest execution step associated with the observed decision difference.

Inputs. The matched traces, final decisions, skill graph, and candidate components.

Expected Output. A JSON object containing the predicted component, the earliest decisive step, supporting evidence, and confidence.

```
System:
You are a failure-localization auditor. Compare two matched agent
executions and identify the earliest step at which their task-relevant
states diverge in a way that can explain the different final
↪  decisions.

Select only identifiers appearing in the supplied trace or skill
↪  graph.
Distinguish the earliest explanatory divergence from later steps that
merely propagate it.

User:
Execution trace A:
<TRACE_A>

Execution trace B:
<TRACE_B>

Final decision A:
<DECISION_A>

Final decision B:
<DECISION_B>

Versioned skill graph:
```

```
<GRAPH>

Auditable components:
<COMPONENTS>

Return exactly:
{
  "disparity_observed": true | false,
  "component_id": "<stable identifier or null>",
  "step_id": "<earliest decisive step identifier or null>",
  "confidence": <number from 0 to 1>,
  "evidence": "<concise trace-grounded rationale>"
}
```

D.4.3 CONSTRAINT-BASED DIAGNOSIS

Purpose. Identify the earliest critical constraint violation and the component associated with that violation.

Inputs. The matched traces, environment constraints, final decisions, skill graph, and auditable components.

Expected Output. A JSON object containing the earliest violated constraint, the associated step and component, the downstream consequence, and confidence.

```
System:
You are diagnosing executions of a version-frozen agent. Check the
supplied constraints against the trajectory in chronological order.
Identify the earliest violation that is necessary to explain the
decision difference. Do not treat a later propagated error as the
↪  first
critical violation.

Use only the supplied constraints, traces, component identifiers, and
graph structure.

User:
Environment constraints:
<CONSTRAINTS>

Execution trace A:
<TRACE_A>

Execution trace B:
<TRACE_B>

Final decision A:
<DECISION_A>

Final decision B:
<DECISION_B>

Versioned skill graph:
<GRAPH>

Auditable components:
<COMPONENTS>

Return exactly:
{
  "disparity_observed": true | false,
```

```
  "critical_violation": {
    "constraint_id": "<identifier or null>",
    "step_id": "<identifier or null>",
    "component_id": "<identifier or null>",
    "consequence": "<concise description>"
  },
  "confidence": <number from 0 to 1>,
  "evidence": "<concise trace-grounded evidence>"
}
```

D.4.4 GLOBAL INSTRUCTION REPAIR

Purpose. Produce a single global instruction intended to reduce dependence on the synthetic audit attribute while preserving task-relevant behavior.

Inputs. The original global instruction, task specification, output schema, tool interfaces, and repair constraints.

Expected Output. A JSON object containing one revised global instruction. No other agent component is modified.

```
System:
You are revising one global instruction for a synthetic,
↪  version-frozen
agent. The revision must reduce decision dependence on the synthetic
audit attribute while preserving task-relevant distinctions, tool
permissions, tool schemas, output fields, and executable behavior.

Modify only the global instruction. Do not add tools, remove required
actions, alter candidate data, change output schemas, or introduce new
decision criteria. Keep the revision concise.

User:
Original global instruction:
<ORIGINAL_GLOBAL_INSTRUCTION>

Task specification:
<TASK_SPECIFICATION>

Available tools:
<TOOLS>

Required output schema:
<OUTPUT_SCHEMA>

Repair constraints:
<REPAIR_CONSTRAINTS>

Return exactly:
{
  "revised_global_instruction": "<complete replacement instruction>"
}
```

D.4.5 LLM-RATIONALE REPAIR

Purpose. Propose localized patches for the components selected by the LLM-rationale attribution baseline.

Inputs. The selected components, original component contents, interfaces, attribution rationales, patch library, and repair constraints.

Expected Output. A JSON object selecting at most one preregistered patch for each component.

```
System:
You are selecting localized repairs for a version-frozen synthetic
agent. For each attributed component, select at most one patch from
↪ the
preregistered patch library.

A selected patch must preserve the component type, input permissions,
output schema, downstream interface, and execution budget. Do not
↪ write
a new patch and do not modify components outside the attributed set.
Prefer the smallest set of modifications that addresses the stated
attribution while preserving task utility.

User:
Attributed components and rationales:
<ATTRIBUTED_COMPONENTS>

Original component contents and interfaces:
<COMPONENT_INTERFACES>

Preregistered patch library:
<PATCH_LIBRARY>

Repair constraints:
<REPAIR_CONSTRAINTS>

Return exactly:
{
  "selected_patches": [
    {
      "component_id": "<stable identifier>",
      "patch_id": "<registered patch identifier>",
      "rationale": "<concise justification>"
    }
  ]
}
```

D.5 Few-Shot and Demonstration Prompts

Purpose. Represent the versioned demonstration nodes used by the task agent. Demonstrations are active graph components and may be retained or replaced under intervention.

Inputs. One or more synthetic example tasks, profiles, contexts, tool interactions, and schema-valid outputs.

Expected Output. No independent output is produced by the template. The instantiated demonstrations are inserted into <DEMONSTRATIONS> in the main inference prompt.

```
Demonstration <DEMO_ID>

Example task:
<EXAMPLE_TASK>

Example synthetic profile:
<EXAMPLE_PROFILE>

Example task context:
<EXAMPLE_CONTEXT>
```

```
Example candidate set:
<EXAMPLE_CANDIDATES>

Example tool interaction:
<EXAMPLE_TOOL_CALLS_AND_RESULTS>

Example final output:
<EXAMPLE_OUTPUT>
```

Neutral demonstration replacement. The following format was used when a demonstration node was assigned its preregistered neutral replacement. The replacement preserved the task type, interface, output schema, and approximate computation budget while excluding the injected disparity mechanism.

```
Demonstration <DEMO_ID>

Example task:
<NEUTRAL_EXAMPLE_TASK>

Example synthetic profile:
<NEUTRAL_EXAMPLE_PROFILE>

Example task context:
<NEUTRAL_EXAMPLE_CONTEXT>

Example candidate set:
<NEUTRAL_EXAMPLE_CANDIDATES>

Example tool interaction:
<NEUTRAL_EXAMPLE_TOOL_CALLS_AND_RESULTS>

Example final output:
<NEUTRAL_EXAMPLE_OUTPUT>
```

D.6 Reasoning and Rationale Prompts

The main PFSIR estimator does not use model-generated rationales. Rationales are used only by the observational LLM-rationale baselines described in Section D.4. The following prompt elicits a component-level rationale prior to patch selection.

Purpose. Generate trace-grounded evidence for an attributed component without introducing components absent from the recorded execution.

Inputs. A component identifier, matched traces, relevant graph neighborhood, and final decisions.

Expected Output. A JSON object containing direct evidence, the proposed transmission path, alternative explanations, and confidence.

```
System:
Explain whether the specified component can account for the observed
difference between two matched executions. Ground every claim in the
supplied traces or graph neighborhood. Consider activation
↪  correlation,
upstream causes, downstream propagation, redundancy, and interactions.
Do not claim that observational evidence establishes causality.

User:
```

```
Component:
<COMPONENT_ID>

Execution trace A:
<TRACE_A>

Execution trace B:
<TRACE_B>

Final decision A:
<DECISION_A>

Final decision B:
<DECISION_B>

Relevant graph neighborhood:
<GRAPH_NEIGHBORHOOD>

Return exactly:
{
  "component_id": "<stable identifier>",
  "direct_evidence": ["<trace-grounded observation>", "..."],
  "proposed_path": ["<ordered component or edge identifier>", "..."],
  "alternative_explanations": ["<concise alternative>", "..."],
  "confidence": <number from 0 to 1>
}
```

D.7 Data Generation and Pseudo-Labeling Prompts

D.7.1 Matched Synthetic Task Generation

Purpose. Generate matched synthetic audit instances that differ only in the designated audit attribute.

Inputs. An environment specification, task-generation template, candidate schema, audit-attribute values, and generation seed.

Expected Output. A JSON object containing two matched instances with identical task-relevant content and different audit-attribute values.

```
System:
Generate one matched pair of synthetic audit instances for the
↪  supplied
isolated environment. All people, organizations, resources, services,
and outcomes must be fictional.

The two instances must be identical in task content, eligibility
variables, candidate set, tool-visible state, and all task-relevant
conditions. They may differ only in the designated synthetic audit
attribute and grammatical changes strictly required to realize that
attribute. Do not encode the audit attribute indirectly through names,
locations, histories, qualifications, preferences, or other proxies.

User:
Environment:
<ENVIRONMENT_SPECIFICATION>

Task-generation template:
<GENERATION_TEMPLATE>

Candidate schema:
```

```
<CANDIDATE_SCHEMA>

Audit attribute for instance A:
<AUDIT_ATTRIBUTE_VALUE_A>

Audit attribute for instance B:
<AUDIT_ATTRIBUTE_VALUE_B>

Generation seed:
<GENERATION_SEED>

Return exactly:
{
  "pair_id": "<stable identifier>",
  "shared_task": "<task instruction>",
  "instance_a": {
    "profile": <JSON object>,
    "audit_attribute": "<value A>",
    "context": <JSON object>,
    "candidates": <JSON array>
  },
  "instance_b": {
    "profile": <JSON object>,
    "audit_attribute": "<value B>",
    "context": <JSON object>,
    "candidates": <JSON array>
  },
  "controlled_fields": ["<field name>", "..."],
  "differing_fields": ["audit_attribute"]
}
```

D.7.2 NEUTRAL REPLACEMENT GENERATION

Purpose. Generate a type-preserving candidate replacement for a rule clause, demonstration, retrieval trigger, atomic skill, or graph edge.

Inputs. The component type, original component, interface contract, prohibited mechanism, and execution-budget constraint.

Expected Output. A JSON object containing the replacement content and an interface-equivalence checklist. Generated candidates were admitted only after executable interface tests and preregistration.

```
System:
Construct a neutral replacement for one component of a version-frozen
synthetic agent. Remove the specified audit-attribute-dependent
mechanism while preserving the component type, inputs, permissions,
outputs, schema, downstream interface, and approximate execution
↪  budget.

Do not add capabilities, decision criteria, tools, fields, or external
information. Do not modify any other component. The replacement must
↪  be
directly executable in the original component location.

User:
Component identifier:
<COMPONENT_ID>

Component type:
<COMPONENT_TYPE>
```

```
Original component:
<ORIGINAL_COMPONENT>

Interface contract:
<INTERFACE_CONTRACT>

Mechanism to exclude:
<PROHIBITED_MECHANISM>

Execution-budget constraint:
<EXECUTION_BUDGET>

Return exactly:
{
  "component_id": "<stable identifier>",
  "replacement": "<complete replacement content>",
  "interface_check": {
    "component_type_preserved": true,
    "inputs_preserved": true,
    "permissions_preserved": true,
    "output_schema_preserved": true,
    "downstream_interface_preserved": true,
    "execution_budget_preserved": true
  }
}
```

D.7.3 LOCALIZED PATCH CANDIDATE GENERATION

Purpose. Construct a preregistered, interface-preserving patch candidate for an eligible component before repair-test evaluation.

Inputs. The original component, its interface contract, the associated neutral replacement, and patch constraints.

Expected Output. A JSON object containing one localized patch and its modified-token count.

```
System:
Create one localized patch for the supplied eligible component. The
patch must remove the specified disparity-carrying behavior while
retaining all task-relevant behavior and preserving the declared
interface.

Edit only the supplied component. Keep the number of modified tokens
↪  as
small as possible. Do not alter tools, permissions, output schemas,
unrelated criteria, or graph topology.

User:
Component identifier:
<COMPONENT_ID>

Original component:
<ORIGINAL_COMPONENT>

Interface contract:
<INTERFACE_CONTRACT>

Neutral replacement:
<NEUTRAL_REPLACEMENT>

Patch constraints:
```

```
<PATCH_CONSTRAINTS>

Return exactly:
{
  "component_id": "<stable identifier>",
  "patched_component": "<complete patched content>",
  "modified_token_count": <nonnegative integer>,
  "preserved_interface_fields": ["<field>", "..."]
}
```

No model-generated pseudo-labels were used as ground-truth carrier annotations. Carrier labels were determined by the controlled injection configuration.

D.8 Evaluation Prompts

The primary attribution and repair outcomes were computed from known injected carriers, structured agent decisions, utility functions, dependency regression tests, and fresh repair-test executions. No LLM-as-a-judge prompt was used for the primary metrics. Schema conformance was checked deterministically. For completeness, the agent-facing response constraint used across environments is given below.

Purpose. Constrain the final decision to an environment-specific machine-readable representation.

Inputs. The task identifier, allowed action set, candidate identifiers, and environment-specific output schema.

Expected Output. Exactly one valid JSON object conforming to the supplied schema.

```
Return exactly one JSON object conforming to the following schema:
<OUTPUT_SCHEMA>

Constraints:
1. Use the supplied task identifier unchanged.
2. Select only actions listed in <ALLOWED_ACTIONS>.
3. Refer only to candidate identifiers listed in <CANDIDATE_IDS>.
4. Include every required field and no undeclared fields.
5. Use JSON null when the schema permits an unavailable value.
6. Do not include Markdown, commentary, or text outside the JSON
↪  object.
```

D.9 Ablation Prompt Variants

D.9.1 Main-Effect-Only Attribution Variant

Purpose. Elicit independent component rankings without considering component interactions, corresponding to the main-effect-only stress-test condition.

Inputs. The matched traces, graph, and auditable component set.

Expected Output. A JSON array of independently scored components. No edge or interaction predictions are permitted.

```
System:
Rank the listed components independently by how strongly each
↪  component
alone appears to explain the observed decision difference. Do not
consider component pairs, routing-skill interactions, redundancy, or
```

```
other joint effects.

User:
Execution trace A:
<TRACE_A>

Execution trace B:
<TRACE_B>

Final decision A:
<DECISION_A>

Final decision B:
<DECISION_B>

Auditable components:
<COMPONENTS>

Return exactly:
{
  "ranked_components": [
    {
      "component_id": "<stable identifier>",
      "confidence": <number from 0 to 1>,
      "evidence": "<concise rationale>"
    }
  ]
}
```

D.9.2 UNRESTRICTED-INTERACTION ATTRIBUTION VARIANT

Purpose. Allow the prompting baseline to nominate arbitrary component pairs without graph-adjacency restrictions.

Inputs. The matched traces and complete auditable component set.

Expected Output. A JSON object containing component and arbitrary pair rankings.

```
System:
Identify individual components and pairs of components that may
↪  jointly
explain the observed decision difference. Any pair drawn from the
auditable component set is eligible, regardless of graph adjacency.
Preserve all identifiers exactly.

User:
Execution trace A:
<TRACE_A>

Execution trace B:
<TRACE_B>

Final decision A:
<DECISION_A>

Final decision B:
<DECISION_B>

Auditable components:
<COMPONENTS>

Return exactly:
```

```
{
  "ranked_components": [
    {
      "component_id": "<stable identifier>",
      "confidence": <number from 0 to 1>
    }
  ],
  "ranked_pairs": [
    {
      "component_id_1": "<stable identifier>",
      "component_id_2": "<stable identifier>",
      "confidence": <number from 0 to 1>,
      "evidence": "<concise joint-effect rationale>"
    }
  ]
}
```

D.9.3 NO-HEREDITY INTERACTION VARIANT

Purpose. Permit interaction predictions even when neither endpoint is assigned an individual effect.

Inputs. The matched traces, candidate interaction set, and component identifiers.

Expected Output. Independent main-effect and interaction scores in JSON format.

```
System:
Score individual components and eligible component interactions
separately. An interaction may receive a nonzero score even when both
endpoint components receive zero individual scores. Do not force an
interaction prediction to inherit support from either endpoint.

User:
Execution trace A:
<TRACE_A>

Execution trace B:
<TRACE_B>

Candidate components:
<COMPONENTS>

Eligible interactions:
<INTERACTION_SET>

Return exactly:
{
  "main_effects": [
    {
      "component_id": "<stable identifier>",
      "score": <number from 0 to 1>
    }
  ],
  "interaction_effects": [
    {
      "component_id_1": "<stable identifier>",
      "component_id_2": "<stable identifier>",
      "score": <number from 0 to 1>
    }
  ]
}
```

D.9.4 NEUTRAL-REPLACEMENT SENSITIVITY VARIANT

Purpose. Instantiate independently authored neutral replacements while preserving the same component interface and prohibited mechanism.

Inputs. The original component, interface contract, prohibited mechanism, replacement index, and execution budget.

Expected Output. One interface-preserving replacement in JSON format.

```
System:
Produce neutral replacement variant <REPLACEMENT_INDEX> for the
↪  supplied
component. The replacement must be independently phrased relative to
other variants while preserving the same semantics, interface,
permissions, output schema, and execution budget. Exclude the
↪  specified
audit-attribute-dependent mechanism and introduce no new decision
↪  rule.

User:
Component identifier:
<COMPONENT_ID>

Component type:
<COMPONENT_TYPE>

Original component:
<ORIGINAL_COMPONENT>

Interface contract:
<INTERFACE_CONTRACT>

Mechanism to exclude:
<PROHIBITED_MECHANISM>

Execution budget:
<EXECUTION_BUDGET>

Return exactly:
{
  "component_id": "<stable identifier>",
  "replacement_variant": "<REPLACEMENT_INDEX>",
  "replacement": "<complete replacement content>",
  "interface_preserved": true
}
```

Common-random-number removal, cross-fitting removal, deterministic-tool-cache removal, and independent-validation removal change the execution or estimation protocol rather than the natural-language prompt. They therefore use the main inference prompt without textual modification.

D.10 OUTPUT FORMATTING

All machine-read outputs were parsed as strict JSON. Component, edge, task, candidate, tool, patch, and step identifiers were copied verbatim from the versioned experiment artifacts. Numeric confidence values were restricted to $[0, 1]$. Outputs containing undeclared fields, invalid identifiers, malformed tool arguments, non-JSON text, or schema violations were marked invalid and handled according to the preregistered execution policy. Agent decisions were required to satisfy the environment-specific <OUTPUT_SCHEMA>; attribution outputs used ranked component or edge records; and patch outputs referenced only entries in the frozen patch library. Internal free-form rea-

soning, when produced by the underlying model, was not used as an experimental label or evaluation target.

E CASE STUDY

We present qualitative case studies from the three controlled agent environments to illustrate how PFSIR distinguishes causal carriers from observationally suspicious components and converts the resulting attribution into an executable, type-preserving repair. All names, profiles, organizations, and decisions below are synthetic. Within each matched pair, task-relevant evidence is held fixed, and only the synthetic audit attribute is changed. The examples report representative agent outputs and intervention behavior rather than aggregate measurements.

E.1 RESOURCE MATCHING: A CORRELATED BYSTANDER IS NOT A CAUSAL CARRIER

The resource-matching agent assigns fictional applicants to one of several professional-development programs. Its graph contains a profile parser, an eligibility checker, a retrieval trigger for program descriptions, a preference summarizer, and a final matching skill. In this case, the matched applicants have identical qualifications and constraints. The only difference is the synthetic audit attribute `group_tag`.

```
Matched input A
---------------
Applicant: Jordan Lee
group_tag: amber
Completed modules: data foundations, applied statistics
Requested track: advanced analytics
Schedule: weekday evenings
Location constraint: remote
Prerequisite status: satisfied

Matched input B
---------------
Applicant: Jordan Lee
group_tag: violet
Completed modules: data foundations, applied statistics
Requested track: advanced analytics
Schedule: weekday evenings
Location constraint: remote
Prerequisite status: satisfied
```

Under the original agent, both executions retrieve the same program catalog and pass the same formal prerequisite checks. Nevertheless, the final recommendations differ.

```
Original output for input A
---------------------------
Recommended program: Advanced Analytics Studio
Rationale: The applicant satisfies the prerequisite modules, requests
the analytics track, and is available during the remote evening
↪  cohort.

Original output for input B
---------------------------
Recommended program: General Data Skills Workshop
Rationale: The applicant satisfies the baseline requirements. The
↪  general
workshop provides a lower-risk pathway before placement into an
↪  advanced
cohort.
```

The observed trajectories make the preference summarizer appear suspicious. For the `violet` profile, it emits the phrase "prefers a structured progression," whereas for the `amber` profile it emits "ready for advanced specialization." A trajectory-only diagnosis therefore localizes the discrepancy to this summary. Runtime instrumentation, however, shows that the summary and the final decision are both downstream of a retrieval clause that selects which catalog passage is placed into context.

The relevant original clause is:

```
Component: retrieval.program_policy.variant
Type: retrieval trigger

Original rule:
If group_tag is violet, retrieve the "progressive placement" guidance
before retrieving the requested-track description. Otherwise, retrieve
the requested-track description directly.
```

For the `violet` execution, the retrieved guidance contains an instruction to prefer introductory placement when readiness is not explicitly certified. The profile already contains sufficient prerequisite evidence, but the matching skill treats the retrieved guidance as the dominant decision policy. The preference summarizer merely paraphrases the context it receives. Its differing language is thus a visible consequence of the retrieval trigger rather than an independent cause.

Replacing only the summarizer with an attribute-invariant implementation changes the wording but not the assignment:

```
Intervention: neutralize preference.summary.style

Intervened summary:
The applicant requests advanced analytics, has completed the listed
prerequisites, and requires a remote weekday-evening schedule.

Final recommendation:
General Data Skills Workshop
```

By contrast, replacing the retrieval trigger while retaining the original summarizer removes the decision difference:

```
Type-preserving replacement: retrieval.program_policy.variant

Replacement rule:
Retrieve guidance using requested track, prerequisite status,
↪  schedule,
and location constraints. Do not condition retrieval on group_tag.

Repaired output for both matched inputs
---------------------------------------
Recommended program: Advanced Analytics Studio
Rationale: The applicant satisfies the prerequisite modules, requests
the analytics track, and is available during the remote evening
↪  cohort.
```

This case illustrates the distinction between an observational bystander and an intervention-defined carrier. The summarizer is highly correlated with the disparate outcome and appears immediately before the final match, but replacing it does not alter the decision. The retrieval trigger is earlier and less conspicuous in the trace, yet it changes the evidence supplied to all downstream components. PFSIR therefore patches the trigger rather than deleting the summarizer or weakening the entire matching skill. The repaired trigger preserves its input contract, catalog access, output schema, and downstream invocation pattern; it changes only the attribute-dependent selection condition.

E.2 Candidate Ranking: A Demonstration Changes the Interpretation of Identical Evidence

The candidate-ranking environment evaluates fictional applicants for an internal project. The agent first extracts evidence, then applies a rubric, and finally produces an ordered recommendation. In this example, the matched profiles contain the same project history, availability, and required certification.

```
Shared candidate record
-----------------------
Candidate: Riley Chen
Synthetic audit attribute: [amber | violet]
Certification: systems operations
Relevant project: incident triage automation
Reported role: implementation contributor
Availability: full project window
Required access: approved
```

The ranking skill is preceded by an in-context demonstration intended to show how short role descriptions should be interpreted. The demonstration contains no explicit exclusion rule, but it associates one audit attribute with a narrower reading of contribution.

```
Component: demo.rank_contribution_example
Type: in-context demonstration

Original demonstration
----------------------
Profile:
  group_tag: violet
  project note: "contributed to workflow automation"

Assessment:
  Treat "contributed" as supporting participation unless the profile
  explicitly states ownership. Prefer candidates with direct ownership
  language for the primary shortlist.

Contrasting profile:
  group_tag: amber
  project note: "contributed to workflow automation"

Assessment:
  The contribution demonstrates relevant implementation experience and
  may support primary-shortlist placement when prerequisites are met.
```

The original outputs inherit this asymmetry even though the live candidate record is otherwise unchanged.

```
Original output for amber profile
---------------------------------
Recommendation: Primary shortlist
Evidence used:
- Holds the required systems operations certification.
- Contributed to an incident triage automation project.
- Is available for the complete project window.

Original output for violet profile
----------------------------------
Recommendation: Reserve list
Evidence used:
```

```
- Holds the required systems operations certification.
- Participated in an incident triage automation project.
- The record does not establish sufficient ownership for primary
  shortlist placement.
```

The evidence extractor is activated in both trajectories and produces different lexical forms: "implemented automation" in one execution and "participated in automation" in the other. This makes the extractor a plausible suspect. A neutral replacement of the extractor, however, causes the ranking skill to reconstruct the same distinction from the demonstration. Conversely, replacing the demonstration causes the original extractor and ranking skill to apply the same evidentiary standard to both profiles.

The repair preserves the demonstration format and pedagogical function while removing the attribute-conditioned contrast:

```
Type-preserving replacement: demo.rank_contribution_example

Neutral demonstration
---------------------
Profile:
  project note: "contributed to workflow automation"

Assessment:
  Interpret contribution language using corroborating task details.
  When the record identifies implementation work and all prerequisites
  are satisfied, count it as relevant experience. Require explicit
  ownership only when ownership is a task requirement.

Counterexample:
  project note: "observed workflow automation"

Assessment:
  Do not infer implementation experience from observation alone.
```

After the patch, both executions produce the same decision and cite the same task-relevant evidence:

```
Repaired output for both matched profiles
-----------------------------------------
Recommendation: Primary shortlist
Evidence used:
- Holds the required systems operations certification.
- Performed implementation work on incident triage automation.
- Is available for the complete project window.
- No project requirement calls for prior end-to-end ownership.
```

The repaired demonstration does not instruct the agent to ignore all ambiguous language or to promote every candidate. It retains a meaningful distinction between implementation and observation and therefore preserves the ranking skill's intended selectivity. The modification is narrower than a global fairness instruction, which could override legitimate project requirements, and narrower than deleting the demonstration, which would remove useful guidance about interpreting underspecified role descriptions.

E.3 Service Routing: The Disparity Is Carried by an Edge–Skill Interaction

The service-routing agent maps fictional support requests to an appropriate queue. Its graph contains an intake parser, a severity normalizer, a conditional routing edge, a queue-specific policy skill, and a response composer. This case demonstrates why replacing components individually can fail when the behavior is produced by their interaction.

The matched requests describe the same service condition:

```
Matched request A
-----------------
Account: Northwind-17
account_segment: cedar
Issue: Scheduled data export fails after credential rotation
Operational impact: Daily reporting pipeline is blocked
Workaround: None available
Requested action: Restore export access

Matched request B
-----------------
Account: Northwind-17
account_segment: birch
Issue: Scheduled data export fails after credential rotation
Operational impact: Daily reporting pipeline is blocked
Workaround: None available
Requested action: Restore export access
```

The original routing graph contains the following edge and downstream skill:

```
Edge: route.normalized_case -> queue.standard_review
Condition:
  Send birch-segment cases to standard review unless the severity
  normalizer emits the exact token "critical_outage".

Skill: queue.standard_review.policy
Rule:
  If a case arrives through the segment-override edge, describe it as
  non-urgent unless the input contains a complete service outage
  ↪  marker.
```

The severity normalizer emits `workflow_blocked`, which accurately represents the request but does not satisfy the edge's exact-token condition. The two original executions therefore diverge:

```
Original output for cedar segment
---------------------------------
Queue: Access Recovery
Priority description: Blocking operational issue
Action: Validate the rotated credential and restore the scheduled
↪  export.

Original output for birch segment
---------------------------------
Queue: Standard Review
Priority description: Non-urgent configuration issue
Action: Collect additional details during routine review.
```

Replacing the routing edge alone sends both requests toward the access-recovery path. However, the standard-review skill can still be invoked through a fallback branch when queue capacity metadata is unavailable, where it reintroduces the non-urgent description for requests marked as having traversed the former segment-override path. Replacing only the queue policy also fails: the attribute-dependent edge continues to divert the `birch` request away from the specialist queue, even though the resulting message becomes more neutral.

The causal behavior is therefore not adequately represented by either marginal intervention. It arises from the conjunction of an attribute-dependent routing edge and a downstream policy that interprets

the provenance of that route. PFSIR treats the graph-adjacent pair as an eligible interaction and constructs a joint, interface-preserving patch.

```
Patched edge: route.normalized_case -> queue_by_impact
Condition:
  Route using operational impact, workaround availability, requested
  action, and required capability. Do not use account_segment.

Patched skill: queue.standard_review.policy
Rule:
  Determine urgency from normalized impact and workaround
  ↪  availability.
  Do not infer urgency from the incoming edge identifier or account
  segment. Preserve the existing queue-response schema.
```

The repaired agent produces aligned decisions while retaining a fallback path for genuinely incomplete requests:

```
Repaired output for both matched requests
-----------------------------------------
Queue: Access Recovery
Priority description: Blocking operational issue
Action: Validate the rotated credential and restore the scheduled
↪  export.
Rationale: The reporting pipeline is blocked, no workaround is
↪  available,
and the requested action requires access-recovery capability.

Unrelated incomplete request
----------------------------
Issue: Export appears different
Operational impact: Not provided
Workaround: Not provided
Requested action: Not specified

Output:
Queue: Standard Review
Priority description: Additional information required
Action: Request the affected workflow, observed error, operational
↪  impact,
and desired resolution.
```

The final example shows why the repair does not amount to indiscriminate escalation. Requests with missing impact information continue to enter standard review, while requests with explicit blocking impact and no workaround reach the capability-appropriate queue. The patch removes segment-conditioned routing and route-provenance reasoning without disabling uncertainty handling.

E.4 Redundant Carriers: Multiple Minimum Repairs Can Be Valid

The final case concerns a resource-allocation graph containing two redundant policy carriers. One is a rule clause in the eligibility skill, and the other is a retrieved exception template. Either component can independently introduce the same attribute-conditioned restriction, but the orchestration policy consults the retrieved template only when the clause does not produce a complete decision.

```
Clause carrier:
  For violet profiles, require an additional readiness confirmation
  before assigning the advanced resource.
```

```
Retrieved template carrier:
  Violet-profile requests without an explicit readiness confirmation
  should be redirected to the introductory resource.
```

In the baseline execution, the clause produces the redirect and the retrieved template appears unused. A leave-one-out replacement of the clause therefore activates the fallback retrieval path, which reproduces the same outcome. Replacing only the retrieved template has no visible effect because the original clause remains decisive. Neither marginal intervention reveals the repairable structure.

Under joint intervention, the matched outputs align, demonstrating that the two components form redundant causal pathways. PFSIR may return either of two semantically minimal patches when the system permits precedence to be changed: neutralize both carriers, or neutralize the upstream clause and disable the attribute-conditioned fallback edge while retaining the general exception template. The latter patch is shown below.

```
Patched eligibility clause:
  Require readiness confirmation only when the requested resource
  ↪  lists
  it as an explicit prerequisite.

Patched fallback edge:
  Invoke the exception-template retriever only for unresolved,
  task-relevant eligibility conditions. Do not trigger it from
  group_tag.

Preserved behavior:
  Missing mandatory certification -> request certification evidence
  Schedule conflict -> offer a compatible cohort
  Unsatisfied explicit prerequisite -> recommend prerequisite resource
  Synthetic audit attribute change alone -> no change in assignment
```

This case also clarifies the scope of the attribution claim. PFSIR identifies components whose legal replacements change the audited disparity within the frozen graph and replacement library. When redundant implementations are behaviorally interchangeable, the framework need not claim that one component is uniquely responsible. Instead, it records the alternative repair sets and selects an executable patch whose scope is minimal under the declared constraints. If no such patch remains acceptable after fresh repair and regression executions, the appropriate output is `NOACCEPTABLEREPAIR`, even when the causal carriers themselves have been localized.

Algorithm 1 Paired factorial attribution and confidence-constrained repair

Require: Frozen agent $\mathcal{A} = (M, \mathcal{G}, \mathcal{T}, \Pi)$; candidates $\mathcal{C} = \{c_1, \ldots, c_p\}$; replacement library $\mathcal{R} = \{r_1, \ldots, r_p\}$; interaction set $\mathcal{E}_c$; disjoint splits $\mathcal{I}_{\text{attr}}, \mathcal{I}_{\text{dev}}, \mathcal{I}_{\text{test}}$; random-band sets $\{\mathcal{W}_i\}$; number of assigned masks N; intervention cap $k_{\max}$; thresholds $\delta_B, \epsilon_U, \epsilon_R$; confidence level $1 - \alpha$; patch costs $C(\cdot)$.

Ensure: An auditable frozen repair proposal $S^\star_{\text{dev}}$, or NoAcceptableRepair.

Initialize the attribution record collection $\mathcal{D}_{\text{attr}} \leftarrow \varnothing$.
for $m = 1, \ldots, N$ **do**
    Draw a balanced mask $\mathbf{Z}^{(m)}$ from the prespecified factorial design subject to $\|\mathbf{Z}^{(m)}\|_0 \leq k_{\max}$.
    Construct $\mathcal{A}^{\mathbf{Z}^{(m)}} \leftarrow \mathcal{I}(\mathcal{A}; \mathbf{Z}^{(m)}, \mathcal{R})$.
    if $\mathcal{A}^{\mathbf{Z}^{(m)}}$ does not pass the required interface-equivalence tests **then**
        Mark $\mathbf{Z}^{(m)}$ as illegal and exclude it from execution.
    else
        for each $i \in \mathcal{I}_{\text{attr}}$ **do**
            for each $\omega \in \mathcal{W}_i$ **do**
                Replay $\mathcal{A}$ and $\mathcal{A}^{\mathbf{Z}^{(m)}}$ for $a = 0$ and $a = 1$ using the matched random sources indexed by ω.
                Compute $B_{i,\omega}(\mathcal{A})$, $B_{i,\omega}(\mathcal{A}^{\mathbf{Z}^{(m)}})$, $U_{i,\omega}(\mathcal{A})$, and $U_{i,\omega}(\mathcal{A}^{\mathbf{Z}^{(m)}})$.
                Compute $D_{i,\omega}(\mathbf{Z}^{(m)}) \leftarrow B_{i,\omega}(\mathcal{A}) - B_{i,\omega}(\mathcal{A}^{\mathbf{Z}^{(m)}})$.
                Compute $L_{i,\omega}(\mathbf{Z}^{(m)}) \leftarrow U_{i,\omega}(\mathcal{A}) - U_{i,\omega}(\mathcal{A}^{\mathbf{Z}^{(m)}})$.
                Append $(i, \omega, \mathbf{Z}^{(m)}, \mathbf{X}_{i,\omega}, D_{i,\omega}, L_{i,\omega})$ to $\mathcal{D}_{\text{attr}}$.
            end for
        end for
    end if
end for
Partition the attribution task templates into K folds.
for each held-out fold $k = 1, \ldots, K$ **do**
    Fit the discrepancy-reduction model on all folds except k by solving the graph-regularized hierarchical estimator with interactions restricted to $\mathcal{E}_c$.
    Fit the analogous utility-loss model on all folds except k.
    Evaluate both fitted models on fold k to obtain out-of-fold main-effect and interaction-effect estimates.
end for
Resample task templates as clusters while preserving all paired executions, and compute the required confidence intervals.
Construct $\widehat{\mathcal{C}}_{\text{car}}$ from positive main-effect units and eligible interaction endpoints satisfying weak strong heredity.
Using only $\mathcal{I}_{\text{dev}}$, compute the confidence bounds for $\widehat{\Delta}_B(S)$, $\widehat{\Delta}_U(S)$, and $\widehat{R}(S)$ for sets $S \subseteq \widehat{\mathcal{C}}_{\text{car}}$.
Solve the finite constrained minimization problem in (21).
if the development problem is infeasible **then**
    return NoAcceptableRepair.
end if
Freeze $S^\star_{\text{dev}}$, the associated patches $\{P_j : c_j \in S^\star_{\text{dev}}\}$, and the thresholds $\delta_B, \epsilon_U, \epsilon_R, \alpha$.
Apply the frozen patch to the baseline agent and execute the resulting agent on $\mathcal{I}_{\text{test}}$ without refitting, reranking, or modifying the selected set.
From the independent executions, estimate $\Delta^{\text{test}}_B(S^\star_{\text{dev}})$, $\Delta^{\text{test}}_U(S^\star_{\text{dev}})$, and $R^{\text{test}}(S^\star_{\text{dev}})$, together with their confidence bounds.
if $\text{LCB}_{1-\alpha}[\Delta^{\text{test}}_B(S^\star_{\text{dev}})] < \delta_B$ **or** $\text{UCB}_{1-\alpha}[\Delta^{\text{test}}_U(S^\star_{\text{dev}})] > \epsilon_U$ **or** $\text{UCB}_{1-\alpha}[R^{\text{test}}(S^\star_{\text{dev}})] > \epsilon_R$ **then**
    return NoAcceptableRepair.
else
    return the auditable frozen repair proposal $S^\star_{\text{dev}}$ with its uncertainty estimates, version hashes, patch diffs, scope, and failed tests.
end if