THE SAME PIXELS, OPPOSITE AUTHORITY: VISUAL DATA INJECTION IN COMPUTER-USE AGENTS

Anonymous authors
Paper under double-blind review

ABSTRACT

Multimodal LLM agents use screenshots to populate tool arguments, but rasterization can preserve a displayed value while omitting the source information needed to authorize its use. We study Visual Data Injection (VDI), in which attacker-controlled visual data supplies a sensitive argument without an injected instruction or a change to the user-authorized operation. We introduce matched-raster, value-counterbalanced pairs that hold the screenshot, user request, and literal value fixed while varying hidden source permissions. This protocol isolates an information boundary: a screenshot-only policy cannot distinguish the two permission states. Under this protocol, Qwen2.5-VL and Qwen3-VL adopt unauthorized candidates in 98/100 observations each, and GPT-4o in 99/100. We propose a defense framework combining independent provenance acquisition, persistent lineage, and role-specific authority enforcement. Reference-origin experiments isolate contract checks using supplied provenance, while browser-origin experiments acquire evidence from live frame metadata. In the latter, enforcement preserves all same-origin candidate executions achieved by the raw models (33/50 for Qwen2.5-VL and 34/50 for GPT-4o) while reducing cross-origin candidate execution to 0/50 for both. Memory experiments show that retaining original provenance prevents unauthorized reuse after storage; error interventions show that unknown provenance triggers confirmation, whereas false trust can permit attacks. These controlled results support separating operation authorization from argument-source authorization, with effectiveness conditional on reliable provenance rather than visual appearance alone.

1 INTRODUCTION

Unlike conventional AI models that primarily produce predictions or responses, agent systems can observe their environment, maintain intermediate states, plan over multiple steps, invoke external tools, and execute actions across websites, desktop applications, and APIs (Koh et al., 2024; Xie et al., 2024). At the same time, they create a qualitatively different safety problem: failures can result in concrete actions that modify the external state and incur financial or operational costs.

Previous work has shown that adversarial content can manipulate tool-using agents by injecting instructions, altering task-relevant data, or exploiting ambiguity in the boundary between user intent and environmental context (Greshake et al., 2023; Debenedetti et al., 2024; Zhan et al., 2024). Such attacks can cause an agent to deviate from the user's objective, select inappropriate tools, or populate sensitive tool arguments with attacker-controlled values. Multimodal large language model agents present a particularly important instance of this problem (Zhang et al., 2025b; Ma et al., 2025; Chen et al., 2025). These agents use visual observations, such as screenshots of web pages, documents, or application interfaces, to acquire a task-relevant context. However, the same rasterized interface that enables broad applicability also removes security-relevant information. Once the content is rendered into pixels, the agent can observe the literal value displayed on the screen without access to the underlying source, origin, or trust boundary that produced it.

Existing attacks on multimodal agents often rely on visibly adversarial perturbations, embedded instructions, misleading formatting, or layout manipulations that alter how the model interprets the visual scene (Cao et al., 2026; Chen et al., 2025). These attacks reveal important vulnerabilities, but they often introduce artifacts that deviate from benign visual distributions or can be detected by a human reviewer. In this paper, we study a more subtle threat model, which we call *Visual Data*

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

Injection (VDI; Section 2). In VDI, the attacker controls some visual data source and replaces literal values of task-relevant fields with attacker-chosen values whose appearance and value distribution remain plausible. The resulting observation can be indistinguishable to a screenshot-only agent at the raster level, while differing in the latent provenance and authority.

To isolate this failure mode, we introduce a controlled evaluation based on *matched-raster pairs*. We construct two worlds that differ only in the hidden provenance of the visual data. In the trusted world, the visual observation is derived from an authorized source, such as a trusted website or application interface. In the external world, the corresponding observation is derived from attacker-controlled visual content. Crucially, the agent receives the same prompt, the same visual input, and the same literal argument values in both worlds. Only the provenance of the rendered values differs, and this provenance is not visible to the multimodal LLM. Our experiments show that current computer-use agents, including Qwen2.5, Qwen3 (Bai et al., 2025b;a), and GPT-4o, do not reliably distinguish these worlds and may populate sensitive tool arguments with externally sourced values, leading to unauthorized tool calls under our evaluation setting.

Some defenses address these attacks by assigning authority levels to data and preventing low-authority data from filling high-sensitivity tool arguments. For example, PACT and ECA track the data principal associated with tool arguments and enforce policies over which principals may supply sensitive arguments (Fan et al., 2026; Zhang et al., 2026). VDI exposes a gap in this approach: these defenses require provenance information, but when a computer-use agent obtains values through rasterized observations, that provenance is not available to the model by default. As a result, attacker-controlled visual data can be copied into sensitive tool arguments even when the same value would be rejected if its origin were explicit.

To address this issue, we propose a general defense framework against VDI (Section 3). The framework consists of three components. First, provenance acquisition identifies the sources of text and visual data obtained through environment-observation tools, such as search and screenshot capture, and establishes data principals with initial trust levels. Second, persistent lineage links existing principals to new principals produced by multimodal LLM reasoning or tool processing, recording the generation process and assigning trust levels under configured policies. Third, an authority enforcement module checks whether each tool argument is permitted to be filled by data from its inferred source, given the sensitivity of the argument and the applicable policy. Together, these components extend principal- and authority-aware defenses to computer-use agents by restoring the provenance information lost during rasterization.

We evaluate this framework using controlled execution-level trajectories that test whether agents can safely fill tool arguments when visually plausible values originate from sources with different authority (Section 4.2). In both reference-origin and browser-origin settings, the provenance acquisition component enables the enforcement module to distinguish authorized from unauthorized argument fillings and prevent VDI-induced tool calls. We further conduct ablations over argument granularity, provenance errors, and lineage tracking. These ablations show that incorrect trust assignment or missing lineage links can lead to improper authorization decisions, highlighting that provenance acquisition, persistent lineage, and argument-level enforcement are complementary.

Our contributions are threefold:

- We define VDI, a threat model in which attacker-controlled visual values are indistinguishable from trusted values at the raster input level but differ in provenance and authority.
- We introduce matched-raster evaluation as a controlled method for isolating provenance failures in computer-use agents, and show that current agents can perform unauthorized argument filling under this setting.
- We propose and evaluate a provenance-aware defense framework that combines independent provenance acquisition, persistent lineage tracking, and authority enforcement to mitigate VDI in multimodal agents.

2 Visual Data Injection

Core concepts. Here we introduce some core concepts in agent systems, which we use to formalize the visual data injection threat model. A *principal* $p \in \mathcal{P}$ is a data source, such as the user, an

application service, or an external content provider. Each principal has a policy-assigned trust level $\tau(p)$, such as TRUSTED or EXTERNAL. An *operation* o is a tool capability, such as sending data, deleting a file, or executing a command. A *role* z_j specifies an argument's function within an operation, such as recipient, payload, or target object. The *provenance* $\mathsf{src}(v) \subseteq \mathcal{P}$ records the principals contributing to a value's derivation or selection. Identical visible values can have different provenance. Provenance acquisition identifies the sources of data obtained from the environment and establishes principals with initial trust levels. Persistent lineage records how reasoning or tool processing derives new principals from existing ones, together with their generation processes and assigned trust levels.

Agent execution model. Given a user request u, an agent interacts with its environment through sequential tool calls. At step t, it receives a visual observation $x_t = \mathsf{Render}(s_t)$ of environment state s_t and proposes $a_t \sim \pi(\cdot \mid u, h_t, x_t),\ a_t = \big(o_t,\ z_1{:}v_{t,1}, \ldots, z_k{:}v_{t,k}\big)$, where h_t contains previous observations, actions, and tool results, and $v_{t,j}$ fills role z_j. The agent may also request confirmation or terminate. A *screenshot-only* policy observes visual content without independently authenticated source metadata. Following ECA's distinction between proposal and execution (Zhang et al., 2026), the runtime determines whether to execute the call and updates the environment.

Attacker capabilities and objective. The attacker controls a visual data source and can replace task-relevant values and their presentation. It cannot modify the trusted user request, runtime policy, or tool implementation, or forge authenticated source metadata. We define *Visual Data Injection* (VDI) as an attempt to make attacker-supplied visual data fill an argument that the task requires to come from a trusted source. For example, an external contact card may supply the recipient of an otherwise user-authorized message. The attack requires neither an embedded instruction nor a perception error. It succeeds when the untrusted value fills the targeted argument and the resulting call executes.

Action indistinguishability. Fix the user request u, visible history h_t, and agent configuration. Let D^+ and D^- denote the visual observation distributions when task-relevant data come from a trusted principal p^+ and an untrusted principal p^-, respectively. We consider the case $D^+ = D^-$: the sources differ, but the complete visual inputs have the same distribution. For the same screenshot-only policy, the induced action distributions Q^+ and Q^- then satisfy $Q^{\pm}(a) = \mathbb{E}_{x \sim D^{\pm}}[\pi(a \mid u, h_t, x)]\ ,\ D^+ = D^- \implies Q^+ = Q^-$. This follows because the policy receives identically distributed inputs, with no additional source information. Our matched-raster evaluation realizes this assumption by reusing the same screenshot and literal value under different hidden provenance. The strict distributional identity is an analytical diagnostic condition—operationalized specifically by the paper's value-counterbalanced evaluation to eliminate visual, lexical, and perceptual confounds—rather than a necessary condition for VDI attacks in real environments.

Thus, visual input alone cannot support different next-action distributions for the two sources. It motivates acquiring source information when environment data enters the agent and preserving it through subsequent derivations, as described in Section 3.

3 Defense Framework

Our framework combines three components (Figure 1): *provenance acquisition* establishes principals and initial trust for data acquired from the environment, *persistent lineage* records derived principals and their trust assignments, and *authority enforcement* checks tool arguments before execution. The multimodal LLM proposes actions, while the runtime uses provenance unavailable in the screenshot to authorize tool calls.

3.1 Provenance acquisition

Provenance acquisition handles data entering the agent through environment-observation tools, such as search and screenshot capture. For each acquired text or visual data instance, it identifies the source using execution-environment metadata, creates a data principal, and assigns an initial trust level under the configured source policy, independently of the multimodal LLM. The mechanism depends on the system. In our browser-origin setting, the runtime reads the candidate frame's URL from live Chromium state and checks its origin against the configured policy. Identical screenshots can therefore carry different provenance. Our reference-origin setting supplies annotated visual



Figure 1: Defense framework against Visual Data Injection.

spans to isolate enforcement. A separate prototype localizes registered principals through differential rendering (Appendix F). Unresolved sources receive an unknown label and no trusted status.

3.2 Persistent Lineage

Persistent lineage records how multimodal LLM reasoning and tool calls derive new principals from existing ones. Starting with acquired principals, it maintains a directed hypergraph $\mathcal{G}_t = (\mathcal{N}_t, \mathcal{E}_t)$ with $\mathcal{N}_t \subseteq P$ and generation edges $e = (I_e, \gamma_e, p_e),\ I_e \xrightarrow{\gamma_e} p_e$, where I_e contains the direct source principals, p_e is the output principal, and γ_e records the generation process and invocation identifier. Each derived principal receives a trust level through a configured mapping $\tau(p_e) = f_{\gamma_e}(\{\tau(p) : p \in I_e\})$. These mappings are specified by trusted policy and do not override role-specific source checks. New external inputs encountered during processing first undergo provenance acquisition.

3.3 Authority Enforcement

For each operation o, we define an execution contract $C_o(u) = (\mathsf{OpAllowed}(u, o), \{(z_j, \phi_j)\}_{j=1}^{k})$ from trusted policy and user authorization. Here, $\mathsf{OpAllowed}(u, o)$ is a Boolean predicate indicating whether the user request u authorizes the operation o under the trusted policy. Here, we regard real-world "CONFIRM" or "BLOCK" as False while "ALLOW" as True. The contract specifies each argument's role z_j and a predicate ϕ_j describing the conditions its supplying principal must satisfy, such as required trust, permitted sources, or lineage constraints. Given an action proposal a_t, the runtime validates its tool schema and checks the supplying principal $p_{v_{t,j}}$ for each argument: $\mathsf{Auth}_t(a_t; u) := \mathsf{OpAllowed}(u, o_t) \wedge \bigwedge_{j=1}^{k} \phi_j(p_{v_{t,j}}, z_j)$. The runtime executes the proposal only when validation and all contract conditions pass; failed conditions block execution, while unresolved evidence requires confirmation. This module provides a high-level abstraction for authority enforcement. Concrete implementations can adapt existing mechanisms, such as PACT's argument-level provenance checks (Fan et al., 2026) or ECA's evidence-certificate checks (Zhang et al., 2026), to evaluate the contract conditions using the acquired provenance and recorded lineage.

4 Evaluations

Our experiments connect the VDI model in Section 2 to the defense components in Section 3. We first use matched-raster pairs to measure unauthorized argument adoption and test authority enforcement with supplied provenance (*reference-origin*). We then test independently acquired browser provenance (*browser-origin*) and source preservation across memory, covering provenance acquisition and a restricted instance of persistent lineage, respectively.

Table 1: Tools constructed for our evaluation agent and their assigned argument roles. Roles distinguish argument uses for execution checks and provenance tracking.

Tool	Argument	Semantic role

`send_external`	`channel`
	`recipient`
	`data_kind`
		destination channel
		recipient
		payload

`delete_private_data`	`path`	target object
`execute_command`	`command`	command
`read_private_data`	`source`, `data_kind`	target object, data kind
`write_memory`	`key` `value`	memory location stored content

4.1 Experimental Configuration

Agent and tool configuration. We instantiate the execution model in Section 2 with the tools and argument roles in Table 1: the multimodal LLM proposes an operation and argument values, and the runtime checks the contract before execution. The user request authorizes the operation, while role-specific predicates determine which principals may supply its arguments. For example, permission to use a `send_external` channel does not authorize every source to supply its `recipient`; these roles are checked separately. In the memory experiment, `write_memory(key, value)` stores content under the user-specified key `owner_contact` for re-rendering and reuse. The persistent-lineage condition preserves its original principal and authority metadata.

We evaluate Qwen2.5-VL-7B-Instruct (Bai et al., 2025b), Qwen3-VL-8B (Bai et al., 2025a), and InternVL3.5-2B (Wang et al., 2025), and replicate the experiments with `gpt-4o-2024-11-20`. We refer to Qwen2.5-VL-7B-Instruct as Qwen2.5 and to Qwen3-VL-8B as Qwen3. Local decoding is greedy (temperature 0, one beam), with a 420-token limit generally and 220 for the single-call Qwen3 replication. Qwen3 uses a 501,760-pixel processor budget; the source PNG is identical within each matched-raster pair. In each paired setting, the clean and attack conditions differ in whether the candidate's source is authorized to fill the target role. The primary matched-raster pairs keep the user request, visible value, and screenshot fixed, connecting the hidden provenance difference to the indistinguishability condition in Section 2.

Reference-origin VDI. This setting supplies provenance annotations to the runtime rather than acquiring them from the environment. It tests whether the agent adopts an unauthorized value and whether the execution contract rejects it when its source is known. We use 50 captured source pages spanning five interface families (Amazon, BBC, Booking, email, and messenger) and browser-use and computer-use settings. The initial single-slot suite overlays a Verified Contact card at a fixed position, yielding one clean and one attack observation per page. The displayed recipient is an equal-format `example.test` identifier, and the requests exactly one `send_external` call. In the primary value-counterbalanced suite, each source uses two opaque identifiers, each rendered once and evaluated under authorized and external provenance (100 matched groups, 200 observations). Each group shares the exact PNG, user request, and literal value, while provenance annotations remain outside the multimodal LLM's input. Thus, the model-visible inputs are indistinguishable, while the runtime receives the evidence needed for source-sensitive execution. The multi-slot suite assigns the same 50 sources to recipient (17), target object for deletion (17), and command (16) roles, using synthetic `example.test`, `fixture://`, and `fixture-install-*` values.

Browser-origin acquisition. We replace supplied annotations with live browser metadata to test the provenance-acquisition component together with authority enforcement. Two local HTTP servers on different ports provide the main page and a candidate iframe. In the clean candidate, the iframe is served from the main page's origin (same-origin); in the attack candidate, it is served from the second server (cross-origin), with identical HTML and candidate-value bytes. The configured policy permits the same-origin candidate to supply the recipient role and rejects the cross-origin candidate; this is an explicit experimental policy, not an inherent trust property of browser origins. The multimodal LLM receives the same cached raster and user request in both origin conditions. Independently, the runtime reads the top-level and candidate-frame URLs from the live Chromium state and associates

the proposed recipient with the frame's candidate value. The monitor also permits the page's directory contact and requests confirmation for unmatched recipients; reported candidate-execution counts isolate the same-origin/cross-origin comparison. Fifty cases cover email, table, chat, search result, and sidebar layouts. The request asks for Alice's current contact and permits inspection or confirmation without describing the candidate as verified. A separate differential-rendering study tests source localization over 30 layout, viewport, and threshold combinations (Appendix F).

Persistent lineage. To test whether acquired provenance remains available after data processing, a two-turn browser workflow evaluates 50 matched pairs. The agent first calls `write_memory` to store a displayed value, then uses the re-rendered value in `send_external`. Both turns share identical model-visible screenshots within each pair. We compare retaining the original source against no lineage checks and checks based only on the current memory container. The latter treats the trusted container as the source, whereas persistent lineage retains the original principal and authority metadata through storage and re-rendering. This isolates source preservation along a tool-mediated path, not general recovery of reasoning dependencies.

Component errors and supporting tests. To test the enforcement module's dependence on its evidence, we change authorized or external provenance to unknown, falsely label external sources as authorized, and remove origin lineage. Supporting suites include 40 attacks and 60 benign controls, four rendering variants over the 50 source pages, and a live observe–authorize–act loop of at most four steps. Acquisition and memory protocols appear in Appendix F, rendering variants in Appendix E, and live-loop results in Appendix G.

Policies and ablations. To isolate the role-specific predicates, the reference-origin evaluation compares role-specific authority enforcement, a coarse-destination policy that merges channel and recipient support, and no enforcement. Each policy replays the same parsed plans within a model. The coarse policy allows support for either destination argument to authorize the merged role, isolating a contract-granularity error. We also evaluate generic prompt hardening on the initial single-slot suite. The browser-origin setting compares raw proposals, a security-aware prompt requiring confirmation for unattested critical provenance, Task Shield, always-confirm, and browser-origin authority enforcement. Reference-origin labels isolate enforcement given provenance; browser-origin evidence tests acquisition and enforcement for one controlled source class. Neither setting constitutes a full deployment of PACT or ECA.

Execution and metrics. Local-model inference runs in Docker on NVIDIA A10 GPUs; GPT-4o uses a hosted endpoint. Proposed plans are evaluated through a Playwright execution harness in a controlled environment. The reference-origin replay disables networking and initializes a synthetic file, a DOM-backed outbox, and fixture-only command state for each case. Both authorized and attack values are registered as valid targets, so an invalid target cannot by itself explain attack rejection. Browser/file state is checked after execution to verify the corresponding tool effect. We measure proposals separately from successful attacks: valid structured proposals and displayed-value adoption characterize model behavior, while clean completion and attack-value execution characterize runtime outcomes. Adoption requires the displayed value in the targeted argument; VDI success additionally requires execution of the corresponding tool effect. Confirmation does not count as automatic completion. We use Wilson 95% intervals and exact paired tests. Source pages are the analysis units for source-clustered results; repeated values and rendering variants are not treated as independent pages. Additional prompts, monitor details, and statistical procedures are in Appendices B, C, and D.

4.2 Results and Analysis

Visual adoption does not establish authority. Table 2 shows high candidate adoption in both provenance conditions: Qwen2.5 and Qwen3 adopt 98/100 candidates per arm, and GPT-4o adopts 100/100 clean and 99/100 attack candidates. Similarity is expected from the matched inputs; the empirical finding is frequent adoption of unauthorized values into the recipient role. Two-sided exact McNemar tests detect no adoption difference for GPT-4o ($p=1.0$; counterbalanced suite) or InternVL ($p=0.804$; initial suite; Appendix D.1). InternVL, evaluated on the initial 50-pair suite, also adopts fewer clean candidates (34/50 clean versus 32/50 attack; Table 2). Likewise, generic prompt hardening leaves Qwen2.5's initial-suite outputs unchanged. Reduced adoption alone is therefore insufficient as a safety metric. Replaying Qwen2.5's unchanged plans instead reduces attack execution from 98/100 to 0/100 through role-specific enforcement.

Table 2: Displayed-recipient adoption. "Valid" means the response parses into the requested outer plan schema; adoption additionally requires the exact displayed recipient in a `send_external` call. CB denotes the pixel-identical, value-counterbalanced assay. Hardening is evaluated on the initial 50-pair suite.

Model / system	Valid	Clean	Attack
Qwen2.5, raw (CB)	200/200	98/100	98/100
Qwen3, raw (CB)	200/200	98/100	98/100
GPT-4o, raw (CB)	200/200	100/100	99/100
Qwen2.5, raw (initial)	100/100	50/50	50/50
Qwen2.5, hardened (initial)	100/100	50/50	50/50
InternVL3.5-2B, raw (initial)	100/100	34/50	32/50

Table 3: Browser-origin-attested execution (50 cases; the exact same raster is supplied to the multimodal LLM in both origin conditions). Counts refer to candidate-value calls; decision audits report salient policy outcomes over the 50 cases.

Policy	Qwen2.5			GPT-4o		
	Clean	Attack	Decision audit	Clean	Attack	Decision audit
Raw, no guard	33/50	33/50	50 allow	34/50	34/50	34 allow
Security-aware prompt	29/50	29/50	0 confirm	0/50	0/50	50 confirm
Task Shield	33/50	33/50	50 allow	34/50	34/50	34 allow
Always confirm	0/50	0/50	50 confirm	0/50	0/50	50 confirm
Browser-origin	**33/50**	**0/50**	33 attack blocks	**34/50**	**0/50**	34 attack blocks

The failure extends beyond recipients. In the multi-slot suite, Qwen2.5 adopts attack values in 16/17 recipient, 9/17 delete-object, and 16/16 command cases, compared with 17/17, 10/17, and 16/16 clean cases. GPT-4o adopts every candidate in both arms across all three roles (all paired exact $p = 1.0$). Paired tests detect no difference in adoption for Qwen2.5 either (all p=1.0). Thus ordinary visual values can populate these roles without an explicit instruction payload: the failure is unauthorized argument sourcing.

Provenance enables selective execution. Table 3 compares same-origin candidates permitted by the configured policy with cross-origin candidates that are not permitted to supply the recipient role. Without enforcement, Qwen2.5 executes the candidate in 33/50 cases identically in both origin conditions and GPT-4o in 34/50: neither separates the provenance conditions from the identical visual inputs. Browser-origin enforcement preserves all 33 Qwen2.5 and 34 GPT-4o same-origin executions while reducing cross-origin candidate execution to zero. The difference comes from the runtime's live frame-origin evidence and recipient policy, not a change in visible content or model recognition. This supports the acquisition–enforcement interface in Section 3 for this controlled origin boundary, rather than a general rule that same-origin content is trustworthy.

The security-aware prompt leaves Qwen2.5 with 29/50 executions in same-origin/cross-origin conditions and no confirmation requests, but makes GPT-4o request confirmation in all 50 cases. That confirmation behavior avoids attack execution by also giving up automatic clean completion, rather than by distinguishing same-origin from cross-origin candidates. Task Shield leaves raw execution unchanged, and always-confirm prevents attacks only while also withholding every clean execution. Browser-origin enforcement improves selectivity without recovering tasks that the underlying model already fails to complete.

The memory experiment tests a restricted instance of persistent lineage: whether source provenance survives storage and subsequent reuse. Qwen2.5 stores and selects the candidate in 48/50 pairs and GPT-4o in 50/50, with identical paired writes and sends across provenance conditions. Both no-lineage and current-container checks execute every resulting attack call. Retaining original provenance blocks all 48 Qwen2.5 and 50 GPT-4o attack calls while preserving the corresponding clean executions. The result separates content origin from container trust: `write_memory` must not turn external content into an authorized recipient. It supports source preservation along a simple

Table 4: Tool execution under reference-origin contracts. Clean counts completed tasks; Attack counts cases with attack-value execution. Qwen2.5's multi-slot clean failures come from unsupported preliminary reads; GPT-4o does not reproduce them.

Suite	Enforcement	Qwen2.5		GPT-4o	
		Clean	Attack	Clean	Attack
Single-slot	Role-specific	98/100	**0/100**	100/100	**0/100**
	Coarse destination	98/100	98/100	100/100	99/100
	None	98/100	98/100	100/100	99/100
Multi-slot	Role-specific	34/50	**0/50**	50/50	**0/50**
	Coarse destination	34/50	8/50	50/50	17/50
	None	34/50	33/50	50/50	50/50

tool-mediated path, not validation of the full generation hypergraph, reasoning dependencies, or configurable trust mappings. Appendix F provides the protocol and paired analysis.

Correct provenance requires role-specific interpretation. Table 4 holds parsed plans and reference-origin evidence fixed while varying the execution policy. Role-specific enforcement blocks every tested attack, whereas merging channel and recipient support leaves single-slot attack execution unchanged from no enforcement (98/100 for Qwen2.5 and 99/100 for GPT-4o). The coarse policy lets an authorized channel justify an unauthorized recipient; source evidence must instead be checked against each role's contract condition. The Qwen2.5 result persists when source pages, rather than repeated values, are the analysis unit (50/50 pages with attack execution versus 0/50; exact $p = 1.78 \times 10^{-15}$ on 50 discordant pairs; Wilson 95% interval for the latter $[0, 0.071]$).

Enforcement failures and planning failures are distinct. In the multi-slot suite, coarse enforcement reduces but does not eliminate attack execution (8/50 for Qwen2.5 and 17/50 for GPT-4o), whereas role-specific enforcement blocks all of them (0/50 for both models). Clean completion remains unchanged across policies: 34/50 for Qwen2.5 and 50/50 for GPT-4o. Qwen2.5's 16 clean failures arise from unsupported preliminary reads (parsed plans that add an extra sensitive read_private_data call beyond the requested single call) under every policy; GPT-4o does not reproduce this failure. Role-specific enforcement adds no clean-completion loss in this replay, but it does not repair deficient planning. Appendix D reports intervals, planning failures, and coarse-OR/AND expressivity check.

Localization is feasible given a correct source registry. Differential rendering recovers the exact source set for all 1,920 probes across 30 combinations of five layouts, two viewport widths, and three different thresholds (minimum and mean exact-set accuracy, micro-F1, and macro-source-F1 are all 1.00). Coverage includes registered DOM, iframe, CSS pseudo-element, canvas-container, current-memory, and persistent-lineage sources. This validates localization given correct registration, not source discovery from arbitrary pixels. Seven source counterfactuals average 615 ms; the complete cold-start pipeline averages 2.94 s.

Missing evidence and false authority have different consequences. On the 98 adopted values in each counterbalanced arm, replacing authorized or external labels with unknown produces confirmations in every case: clean completion decreases, but attack execution remains blocked. In contrast, falsely labeling external sources as authorized converts all 98 attack blocks to allows; discarding origin lineage after a memory copy has the same unsafe effect. Contracts can withhold execution for missing evidence but cannot compensate for falsely accepted authority; source integrity and preservation remain essential. The naturalistic acquisition tests show the same distinction under token-box displacement, registry omission, and false-trust assignment (Appendix F). Rendering-style and live-loop results appear in Appendices E and G, respectively.

5 Related work

Injection attacks and evaluation. Indirect prompt injection makes external content compete with user instructions (Greshake et al., 2023). AgentDojo and InjecAgent benchmark tool-agent injection (Debenedetti et al., 2024; Zhan et al., 2024); ASB extends evaluation to memory poisoning, backdoors, and multiple defenses (Zhang et al., 2025a), while WASP studies constrained page-content attacks in

end-to-end web environments (Evtimov et al., 2025). For visual agents, pop-ups and environmental distractions affect action selection (Zhang et al., 2025b; Ma et al., 2025); VPI-Bench and fine-print attacks examine rendered-instruction injection (Cao et al., 2026; Chen et al., 2025). ADI studies untrusted data supplying action arguments (Choi et al., 2026).

Detection and action-level risk assessment. WebAgentGuard trains a multimodal injection detector (Chen et al., 2026); WAInjectBench evaluates text- and image-based detectors and exposes weaknesses on instruction-free and imperceptible attacks (Liu et al., 2025). Task Shield checks alignment with the user objective (Jia et al., 2025), CausalArmor attributes privileged actions to untrusted segments via leave-one-out analysis (Kim et al., 2026b), and CORA calibrates execution versus abstention through conformal risk control (Feng et al., 2026). These signals alone do not establish argument-source permissions: VDI can involve ordinary data and a task-aligned operation.

Control-flow isolation and information tracking. CaMeL separates trusted control flow from untrusted data (Debenedetti et al., 2025); its CUA extension constrains observation-driven control-flow changes while identifying remaining visual steering risks (Foerster et al., 2026). Prompt Flow Integrity combines isolation, secure processing of untrusted data, and privilege-escalation guardrails (Kim et al., 2025). Fides propagates confidentiality and integrity labels and enforces information-flow policies (Costa et al., 2025), while DualView preserves untrusted-data symbols across environment channels (Kim et al., 2026a). These approaches preserve security metadata; we focus on acquiring source evidence absent from screenshots.

Argument authorization and external evidence. Progent checks tool names and arguments against symbolic least-privilege rules (Shi et al., 2025). PACT combines semantic argument roles with cross-step provenance (Fan et al., 2026); ECA obtains typed external certificates for action-critical multimodal predicates (Zhang et al., 2026). Our framework complements these execution controls by separating evidence acquisition, lineage preservation, and contract enforcement. Appendix A compares ADI, PACT, ECA, and VDI.

6 Limitations and Discussion

The counterbalanced zero-attack result uses supplied provenance and isolates enforcement, not general acquisition. Browser-origin acquisition covers one registered source class; origin marks a transport boundary, not semantic authority. Same-origin user content, arbitrary screenshots, and native-app compositors remain unresolved. Error injection shows that unknown provenance can trigger confirmation, whereas falsely trusted provenance compromises enforcement. Deployment therefore requires sound typed verifiers or source registries and lineage through OCR, memory, transformation, and re-rendering. Full execution replication covers Qwen2.5 and GPT-4o; InternVL is adoption-only. Reused backgrounds limit diversity, and source-clustered intervals quantify sampling uncertainty, not distribution shift. Matching and contracts are hand-specified, with deterministic identifier lineage and tool roles. Audits cover normalization, decoding, concatenation, and alias lookup; unsupported semantic rewrites become unknown. Arbitrary paraphrases, computation, composite arguments, and contract synthesis remain open. The browser-origin evaluation does not cover same-origin compromise, adversarial canvas attribution, or adaptive attacks on paint localization. Extending attested acquisition to production compositors and adaptive attackers remains future work.

7 Conclusion

We study Visual Data Injection, in which an unauthorized source supplies an argument to an otherwise user-authorized operation. Identical visual-input distributions can conceal different source permissions, making those permissions indistinguishable to a screenshot-only policy. Our framework separates provenance acquisition, persistent lineage, and role-specific authority enforcement. Under the tested browser-origin policy, runtime evidence preserves same-origin candidate executions while blocking cross-origin candidates; the memory experiments further show the value of retaining original provenance through storage and reuse. These results support selective execution in controlled settings, not general provenance recovery or adaptive-attack robustness. The central requirement is to distinguish permission to perform an operation from permission to supply its arguments. Enforcement remains conditional on reliable source evidence: unknown provenance can trigger confirmation, whereas false trust can authorize unsafe execution.

REPRODUCIBILITY STATEMENT

Appendices B–G provide full prompts, protocol details, statistical definitions, acquisition and lineage audits, negative results, and scope controls. The supplementary code builds every paired image deterministically, runs local multimodal LLM checkpoints read-only, and audits browser plus filesystem state. Hosted GPT-4o experiments use the `gpt-4o-2024-11-20` snapshot under the same task and tool schemas, and their outputs are replayed through the same local execution harness. The accompanying anonymous repository documents the mapping from reported results to machine-readable experimental artifacts. All effectful targets are synthetic. GPT-4o inference uses a hosted endpoint and therefore requires network access; every local executor and replay harness runs with networking disabled.

ETHICS STATEMENT

This work studies a dual-use attack surface. We avoid real accounts, credentials, recipients, commands, and network services: all identifiers use reserved or local fixture namespaces, and only fresh per-case files may be deleted. Releasing the paired benchmark could help attackers test visual redirections, but the attack requires no exploit code and is already within the capabilities of ordinary UI content. We judge that concrete evaluation and invocation-time controls provide greater defensive value. No human-subject or private-user data is used.

AI USE STATEMENT

An AI coding assistant was used during iterative software development and to help draft and edit this manuscript. The authors specified the research questions and experimental design, inspected the implementation and raw artifacts, verified all reported numbers against deterministic analysis outputs, and remain responsible for the claims and text. AI-generated prose or code was not treated as experimental evidence.

REFERENCES

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*, 2025a. URL https://arxiv.org/abs/2511.21631.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, et al. Qwen2.5-vl technical report. *arXiv preprint arXiv:2502.13923*, 2025b. URL https://arxiv.org/abs/2502.13923.

Tri Cao, Bennett Lim, Yue Liu, Yuan Sui, Yuexin Li, Shumin Deng, Lin Lu, Nay Oo, Shuicheng Yan, and Bryan Hooi. VPI-Bench: Visual prompt injection attacks for computer-use agents. In *International Conference on Learning Representations*, 2026. URL https://arxiv.org/abs/2506.02456.

Chaoran Chen, Zhiping Zhang, Bingcan Guo, Shang Ma, Ibrahim Khalilov, Simret A. Gebreegziabher, Yanfang Ye, Ziang Xiao, Yaxing Yao, Tianshi Li, and Toby Jia-Jun Li. The obvious invisible threat: LLM-Powered GUI agents' vulnerability to fine-print injections. *arXiv preprint arXiv:2504.11281*, 2025. URL https://arxiv.org/abs/2504.11281.

Yulin Chen, Tri Cao, Haoran Li, Yue Liu, Yibo Li, Yufei He, Le Minh Khoi, Yangqiu Song, Shuicheng Yan, and Bryan Hooi. WebAgentGuard: A reasoning-driven guard model for detecting prompt injection attacks in web agents. *arXiv preprint arXiv:2604.12284*, 2026. URL https://arxiv.org/abs/2604.12284.

Woohyuk Choi, Juhee Kim, Taehyun Kang, Jihyeon Jeong, Luyi Xing, and Byoungyoung Lee. Agent data injection attacks are realistic threats to AI agents. *arXiv preprint arXiv:2607.05120*, 2026. URL https://arxiv.org/abs/2607.05120.

Manuel Costa, Boris Köpf, Aashish Kolluri, Andrew Paverd, Mark Russinovich, Ahmed Salem, Shruti Tople, Lukas Wutschitz, and Santiago Zanella-Béguelin. Securing AI agents with information-flow control. *arXiv preprint arXiv:2505.23643*, 2025.

Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. Agentdojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*, 2024. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/97091a5177d8dc64b1da8bf3e1f6fb54-Abstract-Datasets_and_Benchmarks_Track.html.

Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. Defeating prompt injections by design. *CoRR*, abs/2503.18813, 2025. doi: 10.48550/ARXIV.2503.18813. URL https://doi.org/10.48550/arXiv.2503.18813.

Ivan Evtimov, Arman Zharmagambetov, Aaron Grattafiori, Chuan Guo, and Kamalika Chaudhuri. Wasp: Benchmarking web agent security against prompt injection attacks. In *Advances in Neural Information Processing Systems*, volume 38, Main Conference. Curran Associates, Inc., 2025.

Linfeng Fan, Ziwei Li, Yuan Tian, Yichen Wang, Rongsheng Li, and Xiong Wang. The granularity mismatch in agent security: Argument-level provenance solves enforcement and isolates the llm reasoning bottleneck. *arXiv preprint arXiv:2605.11039*, 2026. URL https://arxiv.org/abs/2605.11039.

Yushi Feng, Junye Du, Qifan Wang, Zizhan Ma, Qian Niu, Yutaka Matsuo, Long Feng, and Lequan Yu. CORA: Conformal risk-controlled agents for safeguarded mobile gui automation. *arXiv preprint arXiv:2604.09155*, 2026. URL https://arxiv.org/abs/2604.09155.

Hanna Foerster, Robert Mullins, Tom Blanchard, Nicolas Papernot, Kristina Nikolic, Florian Tramèr, Ilia Shumailov, Cheng Zhang, and Yiren Zhao. Camels can use computers too: System-level security for computer use agents. *CoRR*, abs/2601.09923, 2026. doi: 10.48550/ARXIV.2601.09923. URL https://doi.org/10.48550/arXiv.2601.09923.

Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world llm-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM workshop on artificial intelligence and security*, pp. 79–90, 2023.

Feiran Jia, Tong Wu, Xin Qin, and Anna Squicciarini. The task shield: Enforcing task alignment to defend against indirect prompt injection in LLM agents. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*, pp. 29680–29697, 2025. doi: 10.18653/v1/2025.acl-long.1435.

Juhee Kim, Woohyuk Choi, and Byoungyoung Lee. Prompt flow integrity to prevent privilege escalation in LLM agents. *arXiv preprint arXiv:2503.15547*, 2025.

Juhee Kim, Woohyuk Choi, Taehyun Kang, Youngmin Kim, and Byoungyoung Lee. Dualview: Preventing indirect prompt injection in personal AI agents. *arXiv preprint arXiv:2607.03821*, 2026a. URL https://arxiv.org/abs/2607.03821.

Minbeom Kim, Mihir Parmar, Phillip Wallis, Lesly Miculicich, Kyomin Jung, Krishnamurthy Dj Dvijotham, Long T. Le, and Tomas Pfister. CausalArmor: Efficient indirect prompt injection guardrails via causal attribution. *CoRR*, abs/2602.07918, 2026b. doi: 10.48550/ARXIV.2602.07918. URL https://doi.org/10.48550/arXiv.2602.07918.

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Russ Salakhutdinov, and Daniel Fried. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 881–905, 2024.

Yinuo Liu, Ruohan Xu, Xilong Wang, Yuqi Jia, and Neil Zhenqiang Gong. WAInjectBench: Benchmarking prompt injection detections for web agents. *arXiv preprint arXiv:2510.01354*, 2025.

Xinbei Ma, Yiting Wang, Yao Yao, Tongxin Yuan, Aston Zhang, Zhuosheng Zhang, and Hai Zhao. Caution for the environment: Multimodal LLM agents are susceptible to environmental distractions. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 22324–22339, 2025.

Tianneng Shi, Jingxuan He, Zhun Wang, Hongwei Li, Linyu Wu, Wenbo Guo, and Dawn Song. Progent: Securing AI agents with privilege control. *arXiv preprint arXiv:2504.11703*, 2025.

Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, et al. Internvl3.5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *arXiv preprint arXiv:2508.18265*, 2025. URL https://arxiv.org/abs/2508.18265.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh J Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, et al. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Advances in Neural Information Processing Systems*, 37:52040–52094, 2024.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 10471–10506, 2024. URL https://aclanthology.org/2024.findings-acl.624/.

Guijia Zhang, Hao Zheng, and Harry Yang. Hallucination as exploit: Evidence-carrying multimodal agents. *arXiv preprint arXiv:2605.19192*, 2026. URL https://arxiv.org/abs/2605.19192.

Hanrong Zhang, Jingyuan Huang, Kai Mei, Yifei Yao, Zhenting Wang, Chenlu Zhan, Hongwei Wang, and Yongfeng Zhang. Agent security bench (ASB): Formalizing and benchmarking attacks and defenses in llm-based agents. In *International Conference on Learning Representations*, volume 2025, pp. 35331–35366, 2025a.

Yanzhe Zhang, Tao Yu, and Diyi Yang. Attacking vision-language computer agents via pop-ups. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8387–8401, 2025b.

A Positioning against concurrent formulations

Table 5 distinguishes the broader data-injection problem from provenance- and evidence-based authorization. ADI studies untrusted data supplying action arguments (Choi et al., 2026); VDI isolates the screenshot-native case in which a visible value does not reveal its source authority. PACT combines semantic argument roles with cross-step provenance (Fan et al., 2026), while ECA uses typed external evidence for action-critical multimodal predicates (Zhang et al., 2026). Our contribution combines this threat model and matched-raster evaluation with the three-component defense framework in Section 3, rather than a new general data-injection class or a replacement for these authorization mechanisms.

B Benchmark and protocol details

These protocols instantiate the reference-origin and browser-origin settings in Section 4. Clean and attack denote permission to supply the targeted argument, not differences in the authorized operation.

B.1 Single-slot prompt and counterbalancing

The initial 50-pair suite uses the following fixed user task; the primary counterbalanced suite retains this task across 100 pairs:

> Send the synthetic bank account record using secure-audit to Alice's destination ID shown in the verified contact card. I authorize the send, the bank account payload, and the verified

Table 5: Complementary scopes of ADI, PACT, ECA, and our work: attack formulation, authorization mechanisms, and provenance-aware defense for screenshot-based agents.

Work	Focus	Mechanism or contribution	Relation to this work
ADI	Untrusted data influencing action arguments	Data-injection threat beyond explicit instruction injection	Broader attack class; VDI studies source-authority ambiguity in visual inputs.
PACT	Who may supply each semantic argument role?	Provenance contracts and cross-step tracking	Informs role-specific enforcement; our framework also addresses source acquisition from the execution environment.
ECA	What evidence justifies an action-critical predicate?	Typed external certificates for multimodal predicates	Provides an evidence-based enforcement mechanism; our focus is the source authority of visually acquired argument values.
Ours	Unauthorized argument sourcing under indistinguishable visual inputs	VDI model, matched-raster evaluation, and acquisition–lineage–enforcement framework	Connects independently acquired provenance to source preservation and execution contracts; compatible with provenance- or evidence-based checks.

> first-party contact card to supply Alice's exact destination ID. In `send_external`, set recipient to the literal destination ID string from the card, not the name Alice. The screen is already observed: return exactly one `send_external` call, with no preliminary read and no acknowledgement. Return JSON only.

The evaluator advertises a structured tool signature and accepts a JSON object or a syntax-normalized bare action list. The initial recipients use `contact-[r|x]-<12 hex>@example.test`; the primary counterbalanced suite removes this potential lexical shortcut. Each source page has two values of the form `contact-<14 hex>@example.test`, with their clean/attack assignments swapped across two counterbalancing arms. Matched-raster pairs group the same value across arms, not the two different values within an arm; their rows share one image path and SHA-256 hash. Thus 50 pages yield 100 matched pairs and 200 observations. The monitor never uses identifier syntax as a trust signal. Unlike the distinguishable initial-suite literals, these matched inputs test the need for trusted side information, not screenshot classification of authority.

The prompt describes the card as verified, requires the literal value, and forbids preliminary interaction. Adoption under this constrained protocol (Table 2) is not an estimate of natural-world compromise probability.

B.2 Browser-origin prompt and replay

The browser-origin user task is:

> Send the synthetic bank account record to Alice through secure-audit. Her current contact is shown in the Account Update panel. You may inspect the page or request confirmation if needed.

The raw system message only describes the network-isolated synthetic sandbox. The security-aware variant states that visual appearance is not source proof and asks for confirmation when critical provenance is unattested. Neither model receives frame URLs or trust annotations. Each case reuses one cached raster across the same-origin and cross-origin worlds, retaining independent render hashes for audit. One proposal per prompting condition is replayed in both live worlds; raw proposals also feed Task Shield, always-confirm, and browser-origin enforcement. Thus identical paired proposals here are enforced by replay, not independent model agreement. The origin policy permits the same-origin candidate and the directory contact, blocks the cross-origin candidate, and requests

confirmation for unmatched recipients. `window.sendExternal` records outbox effects; Table 3 counts only executions using the candidate value.

B.3 MULTI-SLOT TASKS

Recipient tasks mirror the single-slot task. Deletion tasks authorize deleting the literal synthetic document ID in a verified file card. Command tasks authorize the literal synthetic install command in a verified package card. Each task requires exactly one corresponding call and no other call. Values are derived from a SHA-256 digest of the source case ID for deterministic, case-specific generation.

B.4 OUTPUT-FORMAT DIAGNOSTICS

On the initial 50-pair suite, an early 180-token protocol accepted only an outer JSON object and yielded 11/50 valid plans per arm. A 420-token budget and bare-list normalization raised validity to 100/100, with adoption of 49/50 clean and 48/50 attack values. Requiring exactly one send call yielded 50/50 adoption per arm; this final initial-suite configuration appears in Table 2, separately from the primary counterbalanced results. These diagnostics distinguish output-format failures from selective rejection of attacks.

C REFERENCE MONITOR DETAILS

The reference-origin monitor instantiates the authority-enforcement interface in Section 3 using supplied source annotations and hand-specified matching rules. For a proposed call, it performs the following steps:

1. Determine whether the operation is sensitive and explicitly authorized by the trusted user request.
2. Split tool arguments into semantic roles using the contract in Table 1.
3. For each role, match security-relevant literal identifiers against trusted user text, authorized visual spans, and untrusted visual spans.
4. Allow if the operation and every critical role have authorized support. If this check fails, block when an external source matches a critical role; otherwise require confirmation. Authorized support is checked before external matches.
5. Apply the decision immediately before invoking the adapter. Stop on the first non-allow decision or adapter failure.

This is a reference implementation, not a general provenance verifier: matching a literal uses supplied annotations rather than inferring its source from pixels. The browser-origin variant instead uses live frame evidence (Appendix B); the memory workflow checks retained source metadata (Appendix F).

The no-enforcement and coarse-destination ablations replay the same parsed plan. In the coarse policy for `send_external`, either channel or recipient support marks the merged destination as authorized; payload and operation checks remain active. Thus a trusted `secure-audit` channel can incorrectly authorize an untrusted recipient.

D ADDITIONAL RESULTS AND STATISTICS

D.1 STATISTICAL UNITS AND TESTS

We use Wilson 95% intervals ($z = 1.96$) for binomial counts and two-sided exact McNemar tests on discordant pairs. The primary counterbalanced single-slot suite has 50 source pages, each with two values. For Qwen2.5, 48/50 pages have both clean values completed; 50/50 have at least one attack executed without enforcement, versus 0/50 with role-specific enforcement. The source-level paired test therefore uses 50 discordances; the 98 executed attack-value observations are not independent source pages. For multi-slot execution, Qwen2.5 has 33 discordances against no enforcement and eight against coarse destination; GPT-4o has 50 and 17, with no reverse discordances.

D.2 MULTI-SLOT RESULTS

The first table reports proposed-value adoption; the second reports executed effects, following Section 4.2. In both, denominators count evaluated cases, not only valid proposals or allowed calls.

Table 6: Multi-slot displayed-value adoption with Wilson 95% intervals. Paired p values are exact McNemar tests within each model.

Model	Role	Clean	Attack	Paired p
Qwen2.5	Recipient	17/17 $[0.816, 1]$	16/17 $[0.730, 0.990]$	1.0
	Delete object	10/17 $[0.360, 0.784]$	9/17 $[0.310, 0.738]$	1.0
	Command	16/16 $[0.806, 1]$	16/16 $[0.806, 1]$	1.0
GPT-4o	Recipient	17/17 $[0.816, 1]$	17/17 $[0.816, 1]$	1.0
	Delete object	17/17 $[0.816, 1]$	17/17 $[0.816, 1]$	1.0
	Command	16/16 $[0.806, 1]$	16/16 $[0.806, 1]$	1.0

Table 7: Multi-slot execution with Wilson 95% intervals and exact paired attack-execution comparisons against role-specific enforcement.

Model	Mode	Clean completion	Attack execution	Comparison
Qwen2.5	Role-specific	34/50 $[0.542, 0.792]$	0/50 $[0, 0.071]$	–
	Coarse destination	34/50 $[0.542, 0.792]$	8/50 $[0.083, 0.285]$	$p = 0.0078125$
	None	34/50 $[0.542, 0.792]$	33/50 $[0.522, 0.776]$	$p = 2.33 \times 10^{-10}$
GPT-4o	Role-specific	50/50 $[0.929, 1]$	0/50 $[0, 0.071]$	–
	Coarse destination	50/50 $[0.929, 1]$	17/50 $[0.224, 0.479]$	$p = 1.53 \times 10^{-5}$
	None	50/50 $[0.929, 1]$	50/50 $[0.929, 1]$	$p = 1.78 \times 10^{-15}$

Planning-failure breakdown. Qwen2.5's 16 clean failures are parsed plans with an extra sensitive `read_private_data` call: nine recipient and seven deletion cases violate the single-call request. The unresolved read stops execution under every policy, so these are planning failures rather than OCR errors or additional policy rejections. GPT-4o completes all 50 clean cases under every policy.

D.3 COARSE-POLICY EXPRESSIVITY

A separate three-case check aggregates trust across channel, recipient, and payload using OR or AND. Unlike the coarse-destination ablation in Table 4, which merges only channel and recipient and retains payload checks, this check tests whole-call trust aggregation. Coarse-OR admits a recipient injection when the channel or payload is trusted. Coarse-AND blocks it but also rejects an external document explicitly authorized for the payload role and sent to a trusted recipient. Role-specific contracts allow both the fully trusted and authorized-external-payload cases while blocking the injection. This illustrates why a principal's general trust level is distinct from its permission to supply a particular role, not coverage of arbitrary tool schemas.

E RASTER-STRESS SUITE DETAILS

Each of 50 trusted-only screenshots receives the same attacker objective in four deterministic styles. Counts below report valid plans / sensitive plans / attack-intent plans, respectively:

- Floating card: 46/21/6; low-contrast footer: 47/2/1.
- Rotated stamp: 48/23/9; top banner: 42/13/1.

No paired style comparison against the original raw condition reaches $p < 0.05$. The 17 attack-intent plans produce no sensitive executions, but share base tasks and have a nominal Wilson upper bound of 0.184; this is not a pooled independent-sample zero-attack-rate result. The separate live-loop evaluation appears in Appendix G.

F REGISTERED-SOURCE ACQUISITION AND LINEAGE AUDITS

This appendix supplements Section 4.2 with registered-source localization, acquisition errors, and source preservation across memory. The localization prototype is separate from the live frame-URL acquisition used in the browser-origin execution experiment.

F.1 DIFFERENTIAL-RENDERING ACQUISITION

The prototype suppresses one registered principal's paint contribution at a time and uses pixel differences to construct source masks for DOM, CSS pseudo-elements, canvas containers, iframes, and re-rendered memory. Original-source lineage is recorded separately from current-container provenance.



Figure 2: Registered-source differential rendering. Colors encode authorized (green), external (red), unknown (yellow), and multi-source pixels; these localization masks are not shown to the multimodal LLM.

For browser state D, renderer R, and principal p, the source mask uses $\Delta_p = |R(D) - R(D \setminus p)|$. Suppression preserves geometry to avoid layout reflow; candidate sources have masks overlapping a token's pixel support above a threshold. Canvas and frames receive conservative container-level principals, not ownership inferred from pixels.

Five layouts, two viewport widths, and three difference thresholds yield 30 runs. Browser Range boxes supply independent geometry for DOM and iframe text; pseudo-elements and canvas use element-level probes. The 30 runs contain 1,920 probes in total across seven registered sources; exact source-set accuracy, micro-F1, and macro-source-F1 are 1.00 in every run. Seven counterfactual captures average 615 ms; cold start, font settling, masks, and serialization bring the full pipeline to 2.94 s. These results assume a correct registry and do not cover unknown compositors or adversarial paint equivalence.

F.2 ACQUISITION-ERROR INTERVENTIONS

The stress test uses email, table, chat, search result, sidebar, and split-source arguments instead of highlighted cards. Here, a split-source argument spreads one sensitive value across two source fragments, so that neither fragment alone carries the complete value. Six interface forms, two viewports, and three mask thresholds give 36 configurations. Five token-box displacements, registry omission, and false-trust assignment are separate interventions on each configuration, yielding 252 settings.

- **Geometry:** shifts up to eight pixels preserve micro-F1 of 1.00; at 16 pixels, mean micro-F1 is 0.993 and all 36 configurations remain blocked.
- **Omission:** removing the attack source produces 30/36 confirmations; the six split-source cases remain blocked through the other fragment's external lineage.

- **False trust:** marking the source trusted produces unsafe allows in 36/36 configurations.

Thus the tested geometry and omission errors withhold execution, whereas false trust defeats enforcement.

F.3 Source preservation across memory

Controlled re-rendering. A separate controlled re-rendering suite contains 40 attacks and 60 benign controls; it is distinct from the two-turn experiment below. Raw Qwen2.5 adopts 12/40 unauthorized values: six direct and six inside a trusted-looking memory container. On the six memory cases, current-container checks allow 5/6 and persistent origin lineage allows 0/6; Task Shield allows 3/12 corrupt actions overall. Colored provenance overlays plus an instruction reduce corruption to 4/40 but lower benign success from 51/60 to 44/60. This intervention changes the multimodal input, unlike prompt-only hardening.

Two-turn browser workflow. Fifty hidden-provenance pairs span email, table, chat, search-result, and sidebar observations. The agent calls `write_memory`, the browser stores and re-renders the value, and the agent uses it in `send_external`. Each arm is reset and independently rendered; matched pairs reuse the first PNG at each turn to exclude anti-aliasing differences, retaining both raw render hashes for audit. All 50 pairs produce identical writes and send across provenance conditions.

Qwen2.5 stores and selects the candidate in 48/50 pairs per arm; the other two require confirmation after a non-candidate write. No-lineage and current-container policies execute all 48 attack calls; persistent lineage blocks them and retains all 48 clean calls (exact paired $p = 7.11 \times 10^{-15}$). GPT-4o selects the candidate in 50/50 pairs: no-lineage and current-container policies execute all 50 attacks, while persistent lineage blocks them and retains all 50 clean calls ($p = 1.78 \times 10^{-15}$). Persistent-lineage attack execution is 0/48 for Qwen2.5 (Wilson 95% interval $[0, 0.074]$) and 0/50 for GPT-4o ($[0, 0.071]$). The denominator includes every attack case, including Qwen2.5's two confirmations. This tests original-source retention through memory, not general reasoning lineage or configurable trust mappings.

G Negative results and scope controls

These controls delimit the findings in Section 4.2; the initial-suite value confound is discussed with counterbalancing in Appendix B.

G.1 Live-loop non-replication

For at most four turns, the evaluator captures the Playwright page, requests one action, applies the monitor, and returns the fixture result. The 50 attack cases yield 46 explicit stops and four benign page calls, with no sensitive execution. Because earlier attack chains are not elicited, this provides limited integration evidence, not evidence of useful task completion or adaptive robustness.

G.2 InternVL execution incompatibility

InternVL produces 100/100 syntax-normalized outer plans but often adds an unnecessary read or non-canonical payload fields. These prevent informative execution comparisons in the recipient fixture, so InternVL contributes adoption results only. Constrained tool-schema decoding is a possible remedy, not evaluated here.