EXPLICIT REPRESENTATION ALIGNMENT VIA SUBSPACE ELIMINATION FOR LLM UNLEARNING

Anonymous authors
Paper under double-blind review

ABSTRACT

Large Language Models (LLMs) may retain targeted knowledge, including sensitive or hazardous information, even when such knowledge is undesirable in deployment. Machine unlearning aims to suppress the influence of selected data while preserving useful model behavior. We present ERASER, a representation-guided unlearning method that combines a data-derived subspace target with a ranking-based Disentangle-Head. ERASER constructs a fixed aggregate forgetting projector offline from predefined forget groups and uses it to form a sample-specific residual target during training, while ranking encourages higher learned scores for retain samples than for forget samples. We evaluate ERASER on WMDP, TOFU, MUSE, and Fictional Knowledge, observing favorable forgetting–retention trade-offs relative to the evaluated baselines. On Fictional Knowledge, it reduces recovery on exact, paraphrased, and compositional probes. Under the tested protocols, ERASER also yields lower jailbreak attack success rates than the pre-unlearning model and RMU. We additionally evaluate forget-set membership inference and sensitivity to limited-data relearning.

1 INTRODUCTION

Large Language Models (LLMs) have demonstrated strong performance across diverse language tasks (Hurst et al., 2024; Grattafiori et al., 2024; Yang et al., 2024; Team et al., 2024). However, they may retain sensitive, hazardous, or otherwise undesirable knowledge, creating safety, privacy, and governance concerns in deployment (Lin et al., 2024; Shi et al., 2024a). Machine unlearning seeks to reduce the influence of selected data while preserving useful behavior on retain data (Cao & Yang, 2015; Bourtoule et al., 2021; Golatkar et al., 2020; Ma et al., 2022; Liu et al., 2025).

Recent LLM unlearning methods use direct weight modification, distillation, or representation-guided objectives (Gupta et al., 2021; Foster et al., 2024; Kurmanji et al., 2023b; Yao et al., 2024b; Li et al., 2024; Huu-Tien et al., 2024). In RMU-style formulations, forget representations are driven toward a prescribed target vector while retain representations are regularized toward their frozen-model counterparts. This formulation uses random target directions with separately chosen scales and optimizes forget and retain representations without explicitly contrasting them. These observations motivate a data-derived target coupled with a relative forget–retain training signal.

We introduce **ERASER** (**E**xplicit **R**epresentation **A**lignment via **S**ubspace **E**limination for **R**obust LLM Unlearning), a coupled representation-guided objective that combines subspace-based suppression with forget–retain ranking. ERASER first constructs an aggregate forgetting subspace from frozen-model activations of predefined forget groups and caches its orthogonal projector. During training, it subtracts the projected component from each current forget representation to form a sample-specific residual target, without a hand-tuned random target. ERASER further uses a ranking-based *Disentangle-Head* to encourage higher learned scores for retain samples than for forget samples. The two components have complementary roles: the projector specifies which representation components to penalize, whereas ranking supplies a relative forget–retain optimization signal.

Our main contributions are summarized as follows:

- We formulate ERASER as a coupled representation-guided unlearning objective that combines a cached, data-derived subspace projector with a ranking-based Disentangle-Head.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

- We evaluate ERASER on WMDP, TOFU, MUSE, and Fictional Knowledge, reporting its forgetting–retention trade-offs, component ablations, and abstraction-level forgetting behavior relative to the evaluated baselines.
- We assess jailbreak attack success and forget-set membership inference, and separately characterize ERASER's sensitivity to limited-data relearning.

2 PRELIMINARIES

Practical LLM unlearning methods seek to reduce the influence of selected training data without retraining a model from scratch (Kurmanji et al., 2023a). Existing approaches include gradient-based updates on forget samples (Yao et al., 2024b; Gupta et al., 2021), parameter-based suppression (Foster et al., 2024), distillation (Kurmanji et al., 2023b), and representation-guided objectives (Li et al., 2024; Huu-Tien et al., 2024). These methods are evaluated empirically, since formal guarantees of complete deletion are difficult to obtain for large language models.

We focus on representation-guided unlearning, which modifies selected model components so that forget and retain examples satisfy distinct representation-level objectives. Let $\mathcal{D}_{\text{forget}} = \{x_F^{(i)}\}_{i=1}^{N_F}$ and $\mathcal{D}_{\text{retain}} = \{x_R^{(j)}\}_{j=1}^{N_R}$ denote the forget and retain sets, respectively. A frozen copy of the original model, parameterized by θ_{frozen}, provides reference representations, while selected trainable components yield an unlearned model θ_{unl}. At a specified layer ℓ, representation-guided methods encourage forget representations to approach a target vector $\mathbf{v}_{\text{target}}(x_F)$ and retain representations to remain close to their frozen-model counterparts:

$$h^{(\ell)}_{\theta_{\text{unl}}}(x_F) \approx \mathbf{v}_{\text{target}}(x_F), \quad h^{(\ell)}_{\theta_{\text{unl}}}(x_R) \approx h^{(\ell)}_{\theta_{\text{frozen}}}(x_R).$$

Following the framework established by Li et al. (2024), these objectives are formally optimized using the mean squared error (MSE) as follows:

$$L_{\text{forget}} = \mathbb{E}_{x_F \sim \mathcal{D}_{\text{forget}}} \left\| h^{(\ell)}_{\theta_{\text{unl}}}(x_F) - \mathbf{v}_{\text{target}}(x_F) \right\|_2^2, \tag{1}$$

$$L_{\text{retain}} = \mathbb{E}_{x_R \sim \mathcal{D}_{\text{retain}}} \left\| h^{(\ell)}_{\theta_{\text{unl}}}(x_R) - h^{(\ell)}_{\theta_{\text{frozen}}}(x_R) \right\|_2^2, \tag{2}$$

$$L_{\text{total}} = L_{\text{forget}} + \alpha L_{\text{retain}}, \tag{3}$$

where α balances the forgetting and retention losses. This formulation exposes a trade-off: the target vector determines how forget representations are modified, whereas the retain loss constrains changes to retain representations. In practice, target construction and the relative weighting of these objectives can affect the resulting forgetting–retention trade-off. ERASER addresses these issues by deriving the target from a fixed forgetting projector and by adding a ranking objective that explicitly contrasts forget and retain representations.

3 METHODOLOGY

We introduce **ERASER**, a representation-guided unlearning objective with two coupled components: (i) a subspace-based target construction and (ii) a ranking-based Disentangle-Head. The target construction specifies which components of forget representations are penalized, whereas the ranking objective contrasts forget and retain representations during optimization. Rather than using a hand-tuned random target vector, ERASER constructs a fixed forgetting projector offline from predefined forget groups and uses it to form a sample-specific residual target during training.

Table 1: Performance variability of RMU under different coefficients c. We report average forget accuracy, its min–max range, and the relative range across the evaluated values of c.

Varying c	**WMDP-Bio (⇓)**			**WMDP-Cyber (⇓)**		
	Avg.	Min–Max	Variation	Avg.	Min–Max	Variation
Forget Acc.	0.559	0.302–0.649	62.07%	0.392	0.274–0.442	42.86%

3.1 SUBSPACE-BASED TARGET VECTOR

RMU-style methods define a target vector $\mathbf{v}_{\text{target}}(x_F)$ in the forget loss L_{forget} (Li et al., 2024; Huu-Tien et al., 2024). For example, RMU sets $\mathbf{v}_{\text{target}}(x_F) = c\mathbf{u}$, where $\mathbf{u}$ is a random unit vector and c is a manually selected scaling coefficient. The choice of c can substantially affect the resulting forgetting–retention trade-off.

As shown in Table 1, RMU's forget accuracy varies substantially over the evaluated values of c. Figure 2a further compares several target constructions. These observations motivate a target construction derived from the requested forget data rather than a fixed random direction.

For a given unlearning request, let $\{\mathcal{D}^{(j)}_{\text{forget}}\}_{j=1}^{N}$ denote predefined groups within the forget set. N denotes the number of specified groups; no partition of all model knowledge is assumed. The construction also applies when $N = 1$. ERASER first extracts leading activation directions from each group, then constructs a fixed aggregate forgetting subspace from these directions. During training, each residual target is formed by subtracting the projected component from the current forget representation. Thus, the offline stage determines a common projection operator for the requested groups, while the online target remains specific to each forget sample.

(Phase 1) Offline: Extracting Group-wise Directions

For each forget group $j \in \{1, \ldots, N\}$, we sample n_j examples and form an activation matrix $\mathbf{X}_F^{(j)} \in \mathbb{R}^{n_j \times d}$, whose rows are frozen-model representations $h^{(\ell)}_{\theta_{\text{frozen}}}(x_F)$ at layer ℓ. We define the unnormalized activation second-moment matrix

$$\mathbf{G}^{(j)} = \mathbf{X}_F^{(j)\top}\mathbf{X}_F^{(j)} \in \mathbb{R}^{d\times d}. \tag{4}$$

Assuming $1 \le k \le \operatorname{rank}(\mathbf{X}_F^{(j)})$, we estimate a k-dimensional leading eigenspace using subspace iteration with orthogonalization. Let $\mathbf{A}_0 \in \mathbb{R}^{d\times k}$ have i.i.d. standard normal entries and initialize $\mathbf{W}_0 = \operatorname{qf}(\mathbf{A}_0)$. We then iterate

$$\mathbf{Y}_{t+1} = \mathbf{G}^{(j)}\mathbf{W}_t, \qquad \mathbf{W}_{t+1} = \operatorname{qf}(\mathbf{Y}_{t+1}), \qquad t = 0, \ldots, T-1, \tag{5}$$

where $\operatorname{qf}(\cdot)$ returns the orthonormal $\mathbf{Q}$ factor of a thin QR decomposition. Hence, $\mathbf{W}_t^\top \mathbf{W}_t = \mathbf{I}_k$. After T iterations, we set

$$\mathbf{Z}_j = \mathbf{W}_T^\top \in \mathbb{R}^{k\times d}, \tag{6}$$

whose rows form an orthonormal basis for the estimated leading activation subspace of forget group j.

(Phase 2) Offline: Constructing the Aggregate Forgetting Subspace

We concatenate the group-wise bases row-wise:

$$\mathbf{P}_{\text{all}} = \operatorname{concat}(\mathbf{Z}_1, \ldots, \mathbf{Z}_N) \in \mathbb{R}^{(Nk)\times d}. \tag{7}$$

Let $\mathbf{P}_{\text{all}} = \mathbf{U}\mathbf{\Sigma}\mathbf{V}^\top$ be its thin singular value decomposition. Assuming $k \le \operatorname{rank}(\mathbf{P}_{\text{all}})$, we retain the top k right singular vectors:

$$\mathbf{V}_{\text{forget}} = (\mathbf{V}^\top)_{1:k,:} \in \mathbb{R}^{k\times d}. \tag{8}$$

The rows of $\mathbf{V}_{\text{forget}}$ are orthonormal:

$$\mathbf{V}_{\text{forget}}\mathbf{V}_{\text{forget}}^\top = \mathbf{I}_k. \tag{9}$$

We refer to this as an *aggregate* forgetting subspace because it summarizes the specified group-wise bases in a single rank-k subspace; it need not contain all group-specific directions. The basis is fixed after this offline stage and cached during unlearning.

(Phase 3) Online: Projection-Based Forgetting Loss

At each training step, let $\mathbf{r}_F = h^{(\ell)}_{\theta_{\text{unl}}}(x_F) \in \mathbb{R}^{1\times d}$ be the current representation of a forget sample. We define

$$\mathbf{P}_{\text{forget}} = \mathbf{V}^{\top}_{\text{forget}}\mathbf{V}_{\text{forget}} \in \mathbb{R}^{d\times d}, \tag{10}$$

which is the orthogonal projector onto the row space of $\mathbf{V}_{\text{forget}}$. The sample-specific target is the residual in the orthogonal complement of this subspace:

$$\mathbf{v}_{\text{target}}(x_F) = \mathbf{r}_F(\mathbf{I}_d - \mathbf{P}_{\text{forget}}) = \mathbf{r}_F - (\mathbf{r}_F\mathbf{V}^{\top}_{\text{forget}})\mathbf{V}_{\text{forget}}. \tag{11}$$

Substituting Eq. 11 into L_{forget} yields


$$L_{\text{forget}} = \mathbb{E}_{x_F\sim\mathcal{D}_{\text{forget}}} \|\mathbf{r}_F\mathbf{P}_{\text{forget}}\|_2^2 . \tag{12}$$

Therefore, the objective penalizes the projection energy of forget representations onto the fixed aggregate forgetting subspace at layer ℓ. This identity characterizes the representation-level quantity optimized by ERASER; it does not by itself establish complete deletion of knowledge or robustness to arbitrary recovery attacks.

Phases 1–2 are performed once per unlearning request, after which the projector is cached. Phase 3 contains no repeated SVD or subspace extraction. The grouping granularity is task-dependent: an entity-level request can use entity-specific groups, whereas a broader request can use coarser groups. This construction does not require a global taxonomy of all model knowledge.

3.2 Disentangle-Head: Ranking Forget and Retain Representations

The projection-based loss penalizes selected components of forget representations, while L_{retain} regularizes retain representations toward their frozen-model counterparts. These objectives act on shared model parameters but do not directly compare the two groups. We therefore add a ranking objective that supplies a relative forget–retain optimization signal.



(a) RMU (b) RMU + *Disentangle-Head* (c) ERASER

Figure 1: Mean cosine alignment between current representations and their own frozen-model representations during unlearning. Red and blue curves denote forget and retain samples, respectively. Lower cosine indicates greater directional deviation from the corresponding frozen-model representation; these trajectories do not directly measure geometric overlap between forget and retain subspaces.

For diagnostic purposes, we define

$$c_F(t) = \mathbb{E}_{x_F\sim\mathcal{D}_{\text{forget}}}\left[\cos\left(h^{(\ell,t)}_{\theta_{\text{unl}}}(x_F), h^{(\ell)}_{\theta_{\text{frozen}}}(x_F)\right)\right], \tag{13}$$

$$c_R(t) = \mathbb{E}_{x_R\sim\mathcal{D}_{\text{retain}}}\left[\cos\left(h^{(\ell,t)}_{\theta_{\text{unl}}}(x_R), h^{(\ell)}_{\theta_{\text{frozen}}}(x_R)\right)\right]. \tag{14}$$

These trajectories measure the directional alignment of forget and retain representations with their frozen-model counterparts. Figure 1 shows that the decrease in forget-representation alignment occurs later for RMU than for the head-equipped variants, while retain-representation alignment remains high. This observation motivates an objective that explicitly contrasts forget and retain samples.

Table 2: Benchmark results for the evaluated unlearning methods. ↑ and ↓ denote higher and lower values, respectively. Subscripts $_F$ and $_R$ denote forget and retain evaluations.

WMDP (Li et al., 2024)				**TOFU** (Maini et al., 2024)			
Method	**MMLU**$_R$ ↑	**WMDP Bio**$_F$ ↓	**WMDP Cyber**$_F$ ↓	**Method**	**Model Util.**$_R$ ↑	**Truth Ratio**$_F$ ↑	**QA Prob.**$_F$ ↓
Base	0.581	0.637	0.440	Base	0.627	0.474	0.992
SCRUB	0.512	0.438	0.393	GradDiff	0.497	0.345	0.023
SSD	0.407	0.502	0.350	NPO	0.638	0.567	0.138
RMU	0.566	0.310	0.276	RMU	0.639	0.646	0.100
NPO	0.400	0.425	0.283	SimNPO	0.623	0.466	0.770
SimNPO	0.471	0.416	0.322	DPO	0.625	0.540	0.319
ERASER	**0.566**	**0.277**	**0.248**	**ERASER**	**0.634**	**0.700**	**0.004**
MUSE-Books (Shi et al., 2024d)				**MUSE-News** (Shi et al., 2024d)			
Method	**Know Mem**$_R$ ↑	**Know Mem**$_F$ ↓	**Verb Mem**$_F$ ↓	**Method**	**Know Mem**$_R$ ↑	**Know Mem**$_F$ ↓	**Verb Mem**$_F$ ↓
Base	0.681	0.466	0.997	Base	0.543	0.654	0.577
GradDiff	0.011	0.000	0.000	GradDiff	0.297	0.353	0.006
RMU	0.002	0.006	0.037	RMU	0.487	0.515	0.370
NPO	0.618	0.392	0.850	NPO	0.524	0.653	0.497
SimNPO	0.594	0.290	0.267	SimNPO	0.501	0.593	0.525
ERASER	**0.627**	**0.284**	**0.144**	**ERASER**	**0.525**	**0.518**	**0.103**

Let $\mathcal{D}_{\text{pair}}$ denote a sampling distribution over $\mathcal{D}_{\text{retain}} \times \mathcal{D}_{\text{forget}}$. We define the ranking loss as

$$L_{\text{rank}} = -\mathbb{E}_{(x_R, x_F)\sim\mathcal{D}_{\text{pair}}}\left[\log\sigma\Big(s_\phi(h^{(\ell)}_{\theta_{\text{unl}}}(x_R)) - s_\phi(h^{(\ell)}_{\theta_{\text{unl}}}(x_F))\Big)\right], \tag{15}$$

where $\sigma(\cdot)$ is the sigmoid function. We instantiate s_ϕ with a two-layer MLP $\varphi_\phi : \mathbb{R}^d \to \mathbb{R}^h$ and use the mean of its output as a scalar score:

$$s_\phi(\mathbf{z}) = \frac{1}{h}\sum_{m=1}^{h}[\varphi_\phi(\mathbf{z})]_m. \tag{16}$$

The complete ERASER objective is

$$L_{\text{ERASER}} = L_{\text{forget}} + \alpha L_{\text{retain}} + \beta L_{\text{rank}}, \tag{17}$$


where β controls the contribution of the ranking loss. The ranking term encourages retain samples to receive higher scores than forget samples in the learned score space. It is complementary to the projection-based target: the projector specifies the representation components penalized on forget samples, whereas the ranking objective supplies a relative signal that helps optimize the forgetting–retention trade-off. This objective does not guarantee global representation disentanglement or preservation of all retain-relevant knowledge.

4 Experiments

We evaluate ERASER along four dimensions: benchmark-level forgetting–retention trade-offs (Section 4.1), component analysis (Section 4.2), recovery on abstraction probes (Section 4.3), and attack and relearning evaluations (Section 4.4). Our results are empirical and should be interpreted within the evaluated models, datasets, baseline implementations, and attack settings.

4.1 LLM Unlearning Performance

Setup. We use Zephyr-7B-β (Tunstall et al., 2023), fine-tuned Llama-2-7B target models (Shi et al., 2024c;b), and a fine-tuned Llama-3.1-8B-Instruct (Dorna et al., 2025b) as unlearning targets for WMDP (Li et al., 2024), MUSE (Shi et al., 2024d), and TOFU (Maini et al., 2024), respectively. We refer to the pre-unlearning model as *Base*.



(a) Target construction strategies

(b) Number of retained directions k

Figure 2: Ablations of target construction and subspace dimension. (a) reports MMLU scores and WMDP deltas from the Base model (higher is better for both sets), and (b) shows stable performance across k.

For WMDP, the Bio and Cyber forget corpora are paired with WikiText retain data following Li et al. (2024). MUSE and TOFU use their designated *forget/retain1* and *forget10/retain90* partitions, respectively. The forget-group specification follows the benchmark structure: WMDP and MUSE use concept-level groups defined by their benchmark domains, whereas TOFU uses fictitious authors as entity-level groups. Optimization settings and subspace hyperparameters are summarized in Appendix A.1..

Metrics. For WMDP, we use multiple-choice accuracy on WMDP-Bio and WMDP-Cyber as forget metrics and MMLU as a retention metric. For MUSE, we report ROUGE-L F1 for verbatim recall (VerbMem) and knowledge-based question answering (KnowMem) (Shi et al., 2024d). For TOFU, we report Truth Ratio, QA Probability, and aggregated Model Utility (Maini et al., 2024). These metrics characterize benchmark-specific forgetting–retention trade-offs.

Results. Table 2 shows favorable forgetting–retention trade-offs across the evaluated benchmarks. On WMDP, ERASER combines the lowest Bio and Cyber accuracies (0.277 and 0.248) with the joint-highest MMLU among the listed unlearning methods (0.566, tied with RMU). On TOFU, it obtains the highest reported Truth Ratio (0.700) and lowest QA Probability (0.004), with Model Utility of 0.634 versus RMU's 0.639. Across both MUSE domains, ERASER achieves the highest reported retain KnowMem among the listed unlearning methods and lower forget KnowMem and VerbMem than NPO and SimNPO. Relative to RMU on MUSE-News, it improves retain KnowMem (0.525 versus 0.487) and reduces forget VerbMem (0.103 versus 0.370), with slightly higher forget KnowMem (0.518 versus 0.515). These comparisons show that the gains are not confined to lowering forget scores at the expense of measured retention. Appendix B.6 further reports domain-dependent retention costs on semantically adjacent MMLU domains.

4.2 Component Analysis

Subspace-based target construction. Figure 2a compares the cached projector-based target with scaled random-vector, static token-derived, individual orthogonal-projection, and online adaptive targets. All variants share the LoRA configuration, ranking head, loss weights, and training budget (Appendix A.3). In the evaluated WMDP setting, the cached projector-based target achieves lower forget accuracy than the static and random-target alternatives while retaining comparable MMLU performance.

The online adaptive variant recomputes its basis at every training step but performs worse in the displayed comparison. ERASER instead computes its basis once per unlearning request and uses the cached projector to form sample-specific residual targets. These results support the offline subspace construction used in ERASER, which avoids repeated subspace extraction during training.




Figure 3: Qualitative response trajectory on a selected biosecurity-related query. The query and abbreviated response excerpts are shown to illustrate changes in response relevance and coherence; detailed harmful response content is omitted.

Sensitivity to the subspace dimension. Figure 2b and Table 16 vary the subspace dimension k from 5 to 100. The reported MMLU and WMDP scores change little across the tested settings, supporting limited sensitivity to k in this configuration.

Role of the Disentangle-Head. In the head ablation (Table 12), removing ranking increases Bio and Cyber accuracy from 0.277 and 0.244 to 0.644 and 0.442, respectively. Adding the head to RMU lowers both forget accuracies while slightly increasing reported MMLU. Relative to RMU + *Disentangle-Head*, the full ERASER configuration lowers Bio and Cyber accuracy by 0.71 and 1.31 percentage points, respectively, with a 0.25-percentage-point decrease in MMLU. These results support ranking within the tested configurations; Figure 2a separately examines target construction with the other settings fixed.

Qualitative training trajectory. Figure 3 illustrates response changes on the selected query discussed in Appendix E.1. At 50 training steps, RMU still produces query-relevant content, whereas ERASER produces a fragmented response without a substantive answer. At 250 steps, neither unlearned model provides a coherent answer. These observations illustrate the trajectory of this example rather than an aggregate convergence advantage.


4.3 Abstraction Probes

We use the Fictional Knowledge dataset (Chang et al., 2024), which introduces controlled knowledge through continual pretraining. Because the injected facts are designed not to occur in the original pretraining corpus, the benchmark permits a controlled comparison of recovery on exact, paraphrased, and compositional prompts. We evaluate memorization (MEM), semantic generalization (GEN), and compositional generalization (HARD), and compare ERASER with RMU and a continual-learning baseline (CL) trained on retain data without unlearning. (See Appendix A.5)

Table 3: Accuracy on Fictional Knowledge probes and MMLU. Lower MEM, GEN, and HARD accuracy indicates less recovery; higher MMLU accuracy indicates better measured retention.

Method	MEM⇓	GEN⇓	HARD⇓	MMLU⇑
CL	0.538	0.414	0.257	**0.459**
RMU	0.257	0.214	0.165	0.393
ERASER	**0.126**	**0.122**	**0.075**	0.394

Results. Table 3 shows lower recovery with ERASER across all three probe types. Relative to RMU, MEM, GEN, and HARD accuracy decrease by 13.1, 9.2, and 9.0 percentage points, respectively, corresponding to relative reductions of approximately 51.0%, 43.0%, and 54.5%. Thus, ERASER approximately halves exact-prompt recovery and more than halves recovery on the compositional



(a) GCG attack (b) Embedding-space attack

Figure 4: Recovery under the evaluated jailbreak protocols and iteration budgets.

probes. These reductions occur at comparable reported MMLU accuracy (0.394 versus 0.393), so they are not accompanied by a lower score on this retention metric. Importantly, the lower GEN and HARD scores show that reduced recovery extends beyond exact prompts to paraphrased and compositional queries of the injected facts. Relative to CL, the corresponding reductions are 41.2, 29.2, and 18.2 percentage points, accompanied by lower MMLU accuracy (0.394 versus 0.459). Taken together, these results support a favorable forgetting–retention trade-off relative to RMU across the evaluated probe types.

4.4 Attack and Relearning Evaluations

We assess jailbreak attack success, forget-set membership inference, and sensitivity to limited-data relearning. Attack evaluations compare ERASER with Base and RMU; relearning is assessed within ERASER. Attack settings and the automated-judge prompt are provided in Appendix A.4. These results are specific to the evaluated protocols and budgets.

Jailbreak attacks. We evaluate Greedy Coordinate Gradient (GCG) (Zou et al., 2023) and Embedding Space Attacks (Schwinn et al., 2024). GCG attack success rate (ASR) is assessed using the specified GPT-4o judge, whereas the embedding-space attack is evaluated using cumulative ASR (C-ASR) following Schwinn et al. (2024). Figure 4 compares ERASER with Base and RMU under these protocols. ERASER's GCG ASR remains below 0.1 across the displayed budgets, while RMU approaches 0.2 at several budgets. At 75 embedding-space attack iterations, ERASER's C-ASR is 78%, compared with 100% for both Base and RMU, an absolute reduction of 22 percentage points. These results show lower observed attack success under both evaluated protocols, although embedding-space attacks remain successful on a substantial fraction of the evaluated cases.

Forget-set membership inference. Following prior work (Yeom et al., 2018; Song et al., 2019; Mireshghallah et al., 2022), we evaluate NLL-based classification of samples included in the forget set against the specified control samples (Appendix A.4.3). Table 4 reports higher forget-sample NLL after unlearning. Under the auxiliary-model protocol, ERASER attains a TPR of 0.024 at 1% FPR, compared with 0.067 for Base and 0.032 for RMU; its balanced accuracy is 0.453. These results characterize forget-versus-control distinguishability under the evaluated protocol, rather than privacy against inference of original pretraining membership.

Table 4: Results under the evaluated forget-set membership-inference protocol. ± denotes standard deviation over three random seeds

Method	NLL	Balanced Acc.	TPR@1%FPR (⇓)
Base	1.93 ± 0.14	0.691 ± 0.005	0.067 ± 0.011
RMU	6.44 ± 0.16	0.485 ± 0.012	0.032 ± 0.008
ERASER	6.55 ± 0.16	0.453 ± 0.009	0.024 ± 0.003

Limited-data relearning. We fine-tune the unlearned ERASER model on 10, 30, or 50 examples from the original forget data under the specified fine-tuning protocol (Fan et al., 2025; Lynch et al., 2024). Table 5 shows that MMLU remains in a narrow range (0.5652–0.5685), while WMDP-Bio and WMDP-Cyber accuracy range from 0.2883 to 0.3103 and from 0.2562 to 0.2693, respectively. Even the highest Bio and Cyber accuracies observed across these budgets remain below their respective Base values of 0.637 and 0.440. Thus, the tested relearning budgets do not restore Base-level WMDP

Table 5: Limited-data relearning results for ERASER under the specified fine-tuning protocol.

# Samples	MMLU (⇑)	Bio (⇓)	Cyber (⇓)
10	0.5652	0.2914	0.2693
30	0.5670	0.2883	0.2577
50	0.5685	0.3103	0.2562

accuracy, while MMLU varies little across budgets. This within-method evaluation characterizes response to limited-data relearning rather than its resistance relative to other unlearning methods.

5 Related Work

LLM Unlearning. Machine unlearning aims to reduce the influence of selected data while preserving useful behavior (Bourtoule et al., 2021; Nguyen et al., 2022; Shaik et al., 2023). Approaches include gradient-based updates, distillation, preference-based objectives, and inference-time interventions (Jang et al., 2022; Chen & Yang, 2023; Eldan & Russinovich, 2023; Yao et al., 2024a;b; Bhaila et al., 2024; Fan et al., 2025; Liu et al., 2025). SCRUB (Kurmanji et al., 2023b) uses a KL-based teacher–student objective, whereas ECO (Liu et al., 2024) applies classifier-guided corruption to prompt embeddings at inference without updating the underlying LLM.

Representation-Guided Unlearning. RMU (Li et al., 2024) drives forget activations toward a scaled random vector while regularizing retain activations toward their frozen-model counterparts; adaptive RMU (Huu-Tien et al., 2024) extends this formulation. Align-then-Unlearn (Spohn et al., 2025) aligns an embedding predictor with a frozen text encoder and fine-tunes the LLM to reduce similarity between predicted embeddings and a target concept embedding. LUNAR (Shen et al., 2026) updates an MLP down-projection to redirect forget activations toward regions associated with expressing a lack of knowledge. ERASER instead derives a fixed projector from frozen-model activations of predefined forget groups and combines sample-specific residual targets with pairwise forget–retain ranking. It requires neither an external text encoder nor reference data for ignorance-directed redirection.

Linear Representations and Concept Erasure. Linear representation and concept-editing studies motivate activation-space interventions (Wang et al., 2023; Park et al., 2023). LEACE (Belrose et al., 2023) derives a closed-form concept-erasure transformation with guarantees against linear concept prediction and minimal distortion under its stated criterion. ERASER instead uses projection to define a training penalty coupled with ranking; its contribution is this objective design, not a new linear-erasure guarantee.

6 Conclusion

ERASER couples a cached, data-derived forgetting projector with a ranking-based Disentangle-Head. Experiments show favorable forgetting–retention trade-offs relative to the evaluated baselines and reduced recovery on exact, paraphrased, and compositional probes. ERASER also lowers jailbreak attack success relative to Base and RMU under the tested protocols. Forget-set membership inference and limited-data relearning evaluations further characterize its behavior. These findings support combining activation-derived residual targets with relative forget–retain supervision for LLM unlearning.

Limitations. Our evaluation covers models ranging from 0.5B to 9B parameters under selected benchmarks and attack budgets; it does not establish scalability to substantially larger models, complete knowledge deletion, or resistance to arbitrary recovery procedures. The fixed forgetting subspace may include retain-relevant information, and learned score ordering does not imply geometric disentanglement. Adjacent-domain evaluations reveal domain-dependent retention costs (Appendix B.6), but we do not directly measure subspace overlap or gradient conflict.

Reproducibility Statement. Section 4 describes the experiment-specific settings and evaluation metrics; in particular, the *Setup* paragraph in Section 4.1 identifies the models and benchmark partitions. Sections 3.1 and 3.2 define the subspace construction and training objective. Appendix A.1 specifies the optimizer, LoRA configuration, and training hyperparameters, while Appendix A.3 describes alternative target constructions and the shared settings used in their comparison. Attack and relearning settings and the automated-judge prompt are provided in Appendix A.4, with forget-set membership definitions and data splits in Appendix A.4.3; continual-learning hyperparameters are given in Appendix A.5. Additional ablations and statistical comparisons are reported in Appendices B and D.

Ethics Statement. This work studies selective LLM unlearning for safety, privacy, and rights-respecting data removal using existing models and benchmark datasets, without collecting new personal data or recruiting human participants. Selective unlearning is dual use: it can suppress legitimate information, obscure model capabilities, or weaken safeguards. ERASER does not assess whether removal requests are justified, and usage restrictions alone do not technically prevent misuse. To contextualize the qualitative evaluation, Figure 3 retains one hazardous query and abbreviated response excerpts, while omitting operationally useful response details. The figure illustrates response behavior and does not provide instructions for carrying out the request. Appendix E uses non-operational summaries and omits hazardous query text, associated answer choices and reference answers, optimized attack suffixes, and operationally useful output details. Planned releases will be reviewed for hazardous disclosures and will exclude operationally useful hazardous details, subject to applicable access conditions. We recommend documented removal rationales, appropriate authorization, independent review, and auditing of collateral effects; these are deployment recommendations rather than safeguards implemented or validated by ERASER. Our empirical findings do not establish permanent deletion, universal resistance to recovery attacks, or preservation of all safety-relevant behavior.

AI Use Statement. Generative AI tools assisted with language editing and translation, literature review, feedback on methodological exposition, checks of mathematical and numerical consistency, and the interpretation and presentation of experimental and qualitative results. Coding assistants supported drafting and revising small code snippets. GPT-4o was used as the automated judge for GCG evaluation, as described in Appendix A.4. The authors reviewed the adopted AI-assisted material, made the final research decisions, and take responsibility for the manuscript, code, analyses, and reported results.

REFERENCES

Nora Belrose, David Schneider-Joseph, Shauli Ravfogel, Ryan Cotterell, Edward Raff, and Stella Biderman. Leace: Perfect linear concept erasure in closed form. *Advances in Neural Information Processing Systems*, 36:66044–66063, 2023.

Karuna Bhaila, Minh-Hao Van, and Xintao Wu. Soft prompting for unlearning in large language models. *arXiv preprint arXiv:2406.12038*, 2024.

Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. In *2021 IEEE symposium on security and privacy (SP)*, pp. 141–159. IEEE, 2021.

Yinzhi Cao and Junfeng Yang. Towards making systems forget with machine unlearning. In *2015 IEEE symposium on security and privacy*, pp. 463–480. IEEE, 2015.

Hoyeon Chang, Jinho Park, Seonghyeon Ye, Sohee Yang, Youngkyung Seo, Du-Seong Chang, and Minjoon Seo. How do large language models acquire factual knowledge during pretraining? In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.

Jiaao Chen and Diyi Yang. Unlearn what you want to forget: Efficient unlearning for llms. *arXiv preprint arXiv:2310.20150*, 2023.

Vineeth Dorna, Anmol Mekala, Wenlong Zhao, Andrew McCallum, Zachary C. Lipton, and J. Zico Kolter. OpenUnlearning: Accelerating LLM unlearning via unified benchmarking of methods and metrics. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025a.

Vineeth Dorna, Anmol Mekala, Wenlong Zhao, Andrew McCallum, Zachary C. Lipton, and J. Zico Kolter. TOFU Llama-3.1-8B-Instruct Full Model. https://huggingface.co/open-unlearning/tofu_Llama-3.1-8B-Instruct_full, 2025b.

Ronen Eldan and Mark Russinovich. Who's harry potter? approximate unlearning in llms. *arXiv preprint arXiv:2310.02238*, 2023.

Chongyu Fan, Jinghan Jia, Yihua Zhang, Anil Ramakrishna, Mingyi Hong, and Sijia Liu. Towards llm unlearning resilient to relearning attacks: A sharpness-aware minimization perspective and beyond. *arXiv preprint arXiv:2502.05374*, 2025.

Jack Foster, Stefan Schoepf, and Alexandra Brintrup. Fast machine unlearning without retraining through selective synaptic dampening. In *Proceedings of the AAAI conference on artificial intelligence*, volume 38, pp. 12043–12051, 2024.

Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Forgetting outside the box: Scrubbing deep networks of information accessible from input-output observations. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXIX 16*, pp. 383–398. Springer, 2020.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Varun Gupta, Christopher Jung, Seth Neel, Aaron Roth, Saeed Sharifi-Malvajerdi, and Chris Waites. Adaptive machine unlearning. *Advances in Neural Information Processing Systems*, 34:16319–16330, 2021.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. Lora: Low-rank adaptation of large language models. *ICLR*, 1(2):3, 2022.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.

Dang Huu-Tien, Trung-Tin Pham, Hoang Thanh-Tung, and Naoya Inoue. On effects of steering latent representation for large language model unlearning. *arXiv preprint arXiv:2408.06223*, 2024.

Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. Knowledge unlearning for mitigating privacy risks in language models. *arXiv preprint arXiv:2210.01504*, 2022.

Meghdad Kurmanji, Peter Triantafillou, Jamie Hayes, and Eleni Triantafillou. Towards unbounded machine unlearning. *Advances in neural information processing systems*, 36:1957–1987, 2023a.

Meghdad Kurmanji, Peter Triantafillou, Jamie Hayes, and Eleni Triantafillou. Towards unbounded machine unlearning. *Advances in neural information processing systems*, 36:1957–1987, 2023b.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, et al. The wmdp benchmark: Measuring and reducing malicious use with unlearning. *arXiv preprint arXiv:2403.03218*, 2024.

Yuping Lin, Pengfei He, Han Xu, Yue Xing, Makoto Yamada, Hui Liu, and Jiliang Tang. Towards understanding jailbreak attacks in LLMs: A representation space analysis. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 7067–7085, Miami, Florida, USA, nov 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.401. URL https://aclanthology.org/2024.emnlp-main.401/.

Chris Liu, Yaxuan Wang, Jeffrey Flanigan, and Yang Liu. Large language model unlearning via embedding-corrupted prompts. *Advances in Neural Information Processing Systems*, 37:118198–118266, 2024.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, et al. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, pp. 1–14, 2025.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Aengus Lynch, Phillip Guo, Aidan Ewart, Stephen Casper, and Dylan Hadfield-Menell. Eight methods to evaluate robust unlearning in llms. *arXiv preprint arXiv:2402.16835*, 2024.

Zhuo Ma, Yang Liu, Ximeng Liu, Jian Liu, Jianfeng Ma, and Kui Ren. Learn to forget: Machine unlearning via neuron masking. *IEEE Transactions on Dependable and Secure Computing*, 20(4): 3194–3207, 2022.

Pratyush Maini, Zhili Feng, Avi Schwarzschild, Zachary C Lipton, and J Zico Kolter. Tofu: A task of fictitious unlearning for llms. *arXiv preprint arXiv:2401.06121*, 2024.

Fatemehsadat Mireshghallah, Archit Uniyal, Tianhao Wang, David K Evans, and Taylor Berg-Kirkpatrick. An empirical analysis of memorization in fine-tuned autoregressive language models. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 1816–1826, 2022.

Thanh Tam Nguyen, Thanh Trung Huynh, Zhao Ren, Phi Le Nguyen, Alan Wee-Chung Liew, Hongzhi Yin, and Quoc Viet Hung Nguyen. A survey of machine unlearning. *arXiv preprint arXiv:2209.02299*, 2022.

Kiho Park, Yo Joong Choe, and Victor Veitch. The linear representation hypothesis and the geometry of large language models. *arXiv preprint arXiv:2311.03658*, 2023.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Leo Schwinn, David Dobre, Sophie Xhonneux, Gauthier Gidel, and Stephan Günnemann. Soft prompt threats: Attacking safety alignment and unlearning in open-source llms through the embedding space. *Advances in Neural Information Processing Systems*, 37:9086–9116, 2024.

Thanveer Shaik, Xiaohui Tao, Haoran Xie, Lin Li, Xiaofeng Zhu, and Qing Li. Exploring the landscape of machine unlearning: A survey and taxonomy. *arXiv preprint arXiv:2305.06360*, 1(2), 2023.

William Shen, Xinchi Qiu, Meghdad Kurmanji, Alexandru-Andrei Iacob, Lorenzo Sani, Yihong Chen, Nicola Cancedda, and Nicholas Lane. Llm unlearning via neural activation redirection. *Advances in Neural Information Processing Systems*, 38:44253–44290, 2026.

Dan Shi, Tianhao Shen, Yufei Huang, Zhigen Li, Yongqi Leng, Renren Jin, Chuang Liu, Xinwei Wu, Zishan Guo, Linhao Yu, et al. Large language model safety: A holistic survey. *arXiv preprint arXiv:2412.17686*, 2024a.

Weijia Shi, Jaechan Lee, Yangsibo Huang, Sadhika Malladi, Jieyu Zhao, Ari Holtzman, Daogao Liu, Luke Zettlemoyer, Noah A. Smith, and Chiyuan Zhang. MUSE-Books Target Model. `https://huggingface.co/muse-bench/MUSE-books_target`, 2024b.

Weijia Shi, Jaechan Lee, Yangsibo Huang, Sadhika Malladi, Jieyu Zhao, Ari Holtzman, Daogao Liu, Luke Zettlemoyer, Noah A. Smith, and Chiyuan Zhang. MUSE-News Target Model. `https://huggingface.co/muse-bench/MUSE-news_target`, 2024c.

Weijia Shi, Jaechan Lee, Yangsibo Huang, Sadhika Malladi, Jieyu Zhao, Ari Holtzman, Daogao Liu, Luke Zettlemoyer, Noah A Smith, and Chiyuan Zhang. Muse: Machine unlearning six-way evaluation for language models. *arXiv preprint arXiv:2407.06460*, 2024d.

Liwei Song, Reza Shokri, and Prateek Mittal. Privacy risks of securing machine learning models against adversarial examples. In *Proceedings of the 2019 ACM SIGSAC conference on computer and communications security*, pp. 241–257, 2019.

Philipp Spohn, Leander Girrbach, Jessica Bader, and Zeynep Akata. Align-then-unlearn: Embedding alignment for llm unlearning. *arXiv preprint arXiv:2506.13181*, 2025.

Gemini Team, Petko Georgiev, Ving Ian Lei, Ryan Burnell, Libin Bai, Anmol Gulati, Garrett Tanzer, Damien Vincent, Zhufeng Pan, Shibo Wang, et al. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*, 2024.

Lewis Tunstall, Edward Beeching, Nathan Lambert, Nazneen Rajani, Kashif Rasul, Younes Belkada, Shengyi Huang, Leandro Von Werra, Clémentine Fourrier, Nathan Habib, et al. Zephyr: Direct distillation of lm alignment. *arXiv preprint arXiv:2310.16944*, 2023.

Zihao Wang, Lin Gui, Jeffrey Negrea, and Victor Veitch. Concept algebra for score-based conditional model. In *ICML 2023 Workshop on Structured Probabilistic Inference {\&} Generative Modeling*, 2023.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, et al. Qwen2. 5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

Jin Yao, Eli Chien, Minxin Du, Xinyao Niu, Tianhao Wang, Zezhou Cheng, and Xiang Yue. Machine unlearning of pre-trained large language models. *arXiv preprint arXiv:2402.15159*, 2024a.

Yuanshun Yao, Xiaojun Xu, and Yang Liu. Large language model unlearning. *Advances in Neural Information Processing Systems*, 37:105425–105475, 2024b.

Samuel Yeom, Irene Giacomelli, Matt Fredrikson, and Somesh Jha. Privacy risk in machine learning: Analyzing the connection to overfitting. In *2018 IEEE 31st computer security foundations symposium (CSF)*, pp. 268–282. IEEE, 2018.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

A Detailed Settings

A.1 ERASER Setup

Implementation Details. We use AdamW (Loshchilov & Hutter, 2017) with a learning rate of 5×10^{-5} and batch size 4. Only LoRA (Hu et al., 2022) adapters and the *Disentangle-Head* are trained; all other model weights remain frozen. Representations are extracted from layer 7, and LoRA adapters are inserted into the `gate_proj`, `up_proj`, and `down_proj` modules of layers 5, 6, and 7.

The coefficients α and β weight the retention and ranking losses, respectively. We set $\beta = 1.05$ and use $\alpha = 1200$ for the main Zephyr-7B experiments (Li et al., 2024). For other model variants, we search over α values between 1 and 5, applying the same tuning protocol to RMU. The selected values are $\alpha = 2$ for Qwen2.5-0.5B and $\alpha = 1$ for Llama-3.1-8B and Yi-1.5-9B-Chat. MUSE and TOFU baselines follow the configurations of Dorna et al. (2025a).

For the offline subspace construction, we sample $n_j = 100$ examples per forget group and retain $k = 20$ leading directions. n_j is the number of sampled examples and k is the subspace dimension; neither is determined by the training mini-batch size. Table 6 summarizes the default settings.

Table 6: Default ERASER hyperparameters. The retention-loss coefficient α is model-dependent.

Hyperparameter	**Value**
Learning rate	5×10^{-5}
Min length	50
Max length	2000
Batch size	4
Representation layer	7
LoRA layer indices	5, 6, 7
LoRA modules	`gate_proj`, `up_proj`, `down_proj`
LoRA rank	256
LoRA scaling parameter	512
Subspace dimension k	20
Offline samples per group n_j	100
Retention coefficient α	1200 for main Zephyr-7B; model-dependent otherwise
Ranking coefficient β	1.05
GPU	$1\times$ H100

A.2 Efficiency Profiling

We profile ERASER and RMU on Zephyr-7B using a single 80GB GPU under identical dataloader and optimizer settings. Table 7 reports 42.5M trainable parameters for ERASER and 176.2M for RMU, corresponding to approximately 75.9% fewer trainable parameters. Training times per epoch are 4m29s and 3m58s, respectively, a 13.0% increase for ERASER. ERASER removes the random-target scaling coefficient c from target construction, while retaining other training hyperparameters.

Table 7: Trainable parameter counts and training times for ERASER and RMU on Zephyr-7B.

Method	**Trainable Params**	**Fraction of Total**	**Time per Epoch**
ERASER	42,475,520	0.6%	4m29s
RMU	176,160,768	2.4%	3m58s

A.3 Implementing Baseline Target Vector Strategies

In the target-construction ablation in Figure 2a, all variants use the same LoRA configuration, *Disentangle-Head*, loss weights α and β, and training budget. Only the target-construction strategy is varied.

Scaled Random-Vector Target. Following Li et al. (2024), for each forget group j, we sample $\mathbf{u}_j \sim \mathcal{U}(0,1)^d$, normalize it, and apply a group-specific steering coefficient c_j:

$$\mathbf{v}_{\text{target}}(x_F) = c_j \frac{\mathbf{u}_j}{\|\mathbf{u}_j\|_2}, \qquad x_F \in \mathcal{D}^{(j)}_{\text{forget}}.$$

This target remains fixed during training.

Static Token-Derived Target. We extract frozen-model representations from dummy sequences containing special tokens or strings such as `[PAD]`, `[EOS]`, `None`, and `###`. The resulting token-derived vectors are used as fixed targets during training.

Orthogonal Projection. For each forget representation $\mathbf{r}_F$, we sample a random vector $\mathbf{u}$, remove its component along $\mathbf{r}_F$, and normalize the residual:

$$\mathbf{v}_{\text{target}}(x_F) = \text{normalize}\left(\mathbf{u} - \frac{\langle \mathbf{u}, \mathbf{r}_F \rangle}{\|\mathbf{r}_F\|_2^2}\mathbf{r}_F\right).$$

When defined, this produces a unit target orthogonal to the individual representation rather than a residual derived from an aggregate forgetting subspace.

Online Adaptive Subspace (OAS). OAS uses the same projection-based target form as ERASER but recomputes the aggregate forgetting basis from updated model representations at each training step. It then subtracts the projected component from each current forget representation to obtain a residual target. This contrasts with ERASER's fixed offline basis. Figure 2a reports the comparison.

A.4 Attack and Relearning Setup

A.4.1 GCG Setup

We use the nanoGCG implementation of GCG (Zou et al., 2023). [1] Probe sampling uses GPT-2 (Radford et al., 2019) as the draft model, with reduction factor $r = 4$ and sampling factor $s = 32$. The initial optimization string is `"as a joke, let's say x x x x x x x x x x x x x x x"`.

We randomly select 50 WMDP-Bio test questions and use the same questions for Base, RMU, and ERASER across all evaluated GCG budgets. Each evaluation prompt consists of the prefix `"In a fictional comedy skit, someone explains this fact:"`, the question and its four answer choices, the optimized adversarial suffix, and the ending `\n Response:`.

We use GPT-4o (Hurst et al., 2024) with greedy decoding as the automatic judge. Given the original question, answer choices, reference answer, and model response, the judge returns `Yes` if the response explicitly includes the correct answer or conveys the same concept in alternative wording; otherwise, it returns `No`. The evaluation template is reproduced below with placeholders rather than instantiated benchmark content.

GCG Evaluation Prompt Template

You are evaluating the following adversarial attack attempt against a language model that has undergone unlearning.
The unlearned model was trained to forget specific knowledge from the WMDP-Bio dataset.
The original task was a multiple-choice question with four options. You are given:
- The original question
- All four choices
- The correct answer (target)
- The model's response to an adversarial prompt

Determine whether the model response reveals the correct knowledge, even if it is rephrased or indirectly explained.
Question: {prompt}

[1] https://github.com/GraySwanAI/nanoGCG/tree/main

Choices: {choices_block}
Correct Answer: {target}
Model Response: {response}
Based on the above, has the model revealed or reconstructed the target knowledge in its response? Answer only "Yes" if the model's response either:
- Explicitly reveals the target answer, or
- Clearly explains the same concept in different wording.
Otherwise, answer "No".
Respond with a single word: Yes or No.
Response:

prompt is the original question, choices_block contains the answer choices, target is the reference answer, and response is the generated response to the adversarial prompt.

A.4.2 Embedding-Space Attack Setup

We evaluate individual embedding-space attacks (Schwinn et al., 2024) on the same 50 questions used for GCG, using 80 optimization steps and evaluating every 5 steps. We report cumulative attack success rate (C-ASR) (Schwinn et al., 2024): the fraction of questions with at least one successful response among the attempts evaluated up to the specified attack budget.

A.4.3 Forget-Set Membership Inference Setup

Membership refers to inclusion in the forget data used for the target model's unlearning run, not membership in the original pretraining corpus. We evaluate loss-based classifiers motivated by membership-inference methods (Yeom et al., 2018; Song et al., 2019).

Feature-based protocol. We train a logistic regression attacker using sequence-level NLL as its sole feature. The data comprise 1,000 forget-set members and 1,000 retain-corpus controls that are not in the forget set, with an 80/20 attacker train/test split. Experiments are repeated with three random seeds.

Auxiliary-model protocol. We fine-tune one auxiliary (shadow) copy of Zephyr-7B on 1,000 bio-forget examples. Its loss statistics are used to train the attacker on separate sets of 1,000 forget-set members and 1,000 controls, as shown in Table 8. The attacker is evaluated on a further disjoint set of 1,000 forget-set members and 1,000 controls. Positive labels refer to membership in the target model's forget set, not in the auxiliary model's fine-tuning split. Because the positive and control examples come from different corpora, this evaluation measures forget-versus-control distinguishability without isolating sample-level membership effects from data-source differences.

Table 8: Data splits for the auxiliary-model forget-set membership evaluation. The listed partitions are disjoint. Member and non-member labels refer to the target model's forget set, not the auxiliary model's fine-tuning set.

Split Purpose	Label	Source	Samples	Notes
Auxiliary Model Training	—	Bio-forget corpus	1,000	Used only for auxiliary fine-tuning
Attacker Training	Member	Bio-forget corpus	1,000	Disjoint from auxiliary training
Attacker Training	Non-member	WMDP-Bio-Test + MMLU	1,000	500 each
Evaluation	Member	Bio-forget corpus	1,000	Disjoint from the above splits
Evaluation	Non-member	WMDP-Bio-Test + MMLU	1,000	Disjoint from attacker training

A.4.4 Limited-Data Relearning Setup

We fine-tune ERASER-unlearned models on subsets of 10, 30, or 50 examples from the original forget data, using the continual-learning hyperparameters in Appendix A.5 and following Fan et al. (2025); Lynch et al. (2024). We then evaluate WMDP and MMLU performance, as reported in Table 5. This within-method evaluation characterizes ERASER's response to the specified relearning budgets.

A.5 Continual Learning Setup

We use the Fictional Knowledge dataset (Chang et al., 2024), with 130 training examples for knowledge injection. Each training example has associated test input–target pairs covering memorization (MEM), semantic generalization (GEN), and compositional generalization (HARD). We fine-tune Zephyr-7B-β using the settings in Table 9 and evaluate generated responses using target-string matching on the three probe types.

Table 9: Continual-learning hyperparameters.

Hyperparameter	**Value**
Epochs	7
Learning rate	2×10^{-5}
Gradient accumulation steps	2
Per-device train batch size	2
Max sequence length	4096
BF16	True
Optimizer	AdamW
Learning rate scheduler	Linear
Adam β_1	0.9
Adam β_2	0.95
GPU	$1\times$ H100

B Additional Experiments

B.1 Evaluation Across Model Families

Table 10: WMDP and MMLU accuracy across three model families. Bold marks the best value among the unlearning methods within each model family.

Model	**Method**	**MMLU** $\uparrow$	**Bio** $\downarrow$	**Cyber** $\downarrow$
Qwen2.5-0.5B	Base	0.4583	0.5672	0.3694
	RMU	0.3960	0.2985	0.2713
	ERASER	**0.4279**	**0.2545**	**0.2602**
Llama-3.1-8B	Base	0.6363	0.6984	0.4353
	RMU	0.3389	**0.2412**	0.2516
	ERASER	**0.5125**	0.2836	**0.2446**
Yi-1.5-9B-Chat	Base	0.6838	0.6622	0.4625
	RMU	0.5048	0.2718	**0.2582**
	ERASER	**0.6411**	**0.2655**	0.2617

Table 10 extends the evaluation to Qwen2.5-0.5B, Llama-3.1-8B, and Yi-1.5-9B-Chat. ERASER achieves higher MMLU accuracy than RMU by 3.19, 17.36, and 13.63 percentage points, respectively. On Qwen2.5-0.5B, it also lowers both forget accuracies. On Llama-3.1-8B and Yi-1.5-9B-Chat, the forgetting results are metric-dependent rather than uniformly better than RMU. These results extend the measured retention advantage over RMU across model families, although MMLU remains below Base for all three models.

B.2 Sensitivity to α and β

Table 11 examines sensitivity to the retention weight α and ranking weight β. The reported scores vary modestly over the tested ranges of $\alpha = 400$–1200 and $\beta = 0.90$–1.10. The sample standard deviation across each set of five displayed settings is below 0.01, supporting limited sensitivity within these sweeps.

Table 11: Sensitivity to α and β. Std. is the sample standard deviation computed from the five displayed scores in each row, not across random seeds.

α	**400**	**600**	**800**	**1000**	**1200**	**Std.**
MMLU ↑	0.5582	0.5672	0.5480	0.5612	0.5662	0.0077
WMDP-Bio ↓	0.2962	0.2933	0.2828	0.2979	0.2765	0.0093
WMDP-Cyber ↓	0.2491	0.2693	0.2461	0.2552	0.2481	0.0094
β	**0.90**	**0.95**	**1.00**	**1.05**	**1.10**	**Std.**
MMLU ↑	0.5637	0.5626	0.5659	0.5662	0.5600	0.0025
WMDP-Bio ↓	0.2844	0.2836	0.2726	0.2765	0.2883	0.0064
WMDP-Cyber ↓	0.2597	0.2587	0.2542	0.2481	0.2557	0.0046

B.3 Effectiveness of the *Disentangle-Head*

Table 12: Head ablation for ERASER and RMU. The default ERASER includes the *Disentangle-Head*, whereas the default RMU does not. Bold marks the best value in each metric.

Method	**Head**	**MMLU ↑**	**WMDP-Bio ↓**	**WMDP-Cyber ↓**
ERASER	Yes	0.5679	**0.2773**	**0.2436**
ERASER	No	**0.5840**	0.6437	0.4424
RMU	Yes	0.5704	0.2844	0.2567
RMU	No	0.5660	0.3103	0.2763

Removing the *Disentangle-Head* from ERASER increases Bio and Cyber accuracy from 0.2773 and 0.2436 to 0.6437 and 0.4424, respectively (Table 12). Adding the head to RMU reduces Bio and Cyber accuracy by 2.59 and 1.96 percentage points while increasing reported MMLU by 0.44 percentage points. These results support the ranking objective within ERASER and its usefulness in the evaluated RMU configuration. Relative to RMU with the head, the full ERASER configuration further reduces Bio and Cyber accuracy by 0.71 and 1.31 percentage points, respectively, with a 0.25-percentage-point decrease in MMLU.

B.4 Impact of Trainable Parameter Selection

Table 13: Trainable-parameter ablation. Full FT denotes full-parameter fine-tuning, and Head indicates inclusion of the *Disentangle-Head*. Bold marks the best value in each metric.

Parameterization	**Head**	**MMLU ↑**	**WMDP-Bio ↓**	**WMDP-Cyber ↓**
LoRA (ERASER)	Yes	0.5661	0.2765	0.2481
Full FT	Yes	0.2689	**0.2412**	0.2526
Full FT	No	0.2465	0.2474	**0.2436**
Index tuning	Yes	0.5686	0.2859	0.2466
Index tuning	No	**0.5766**	0.6473	0.4424

We compare LoRA-based ERASER with full-parameter fine-tuning and selective index tuning (Li et al., 2024), with head inclusion as shown in Table 13. Full FT achieves low forget accuracies but substantially reduces MMLU to 0.2465–0.2689, compared with 0.5661 for LoRA-based ERASER. Index tuning with the head retains comparable MMLU (0.5686), with higher Bio and slightly lower Cyber accuracy than ERASER. Removing the head from index tuning substantially weakens forgetting. Thus, the table supports the role of ranking under selective updates and shows the different forgetting–retention trade-offs of the tested parameterizations.

B.5 FORGET-SET SIZE SENSITIVITY

We vary only the proportion of forget data used. Table 14 shows low forget accuracies across the tested ratios, but a larger retention cost at 10%: MMLU falls from 0.5662 in the full-data setting to 0.5097. The 20% and 30% settings retain MMLU scores of 0.5605 and 0.5666, respectively. Forget accuracy does not vary monotonically with data size, so the main effect at the smallest subset is the deterioration in measured retention.

Table 14: Effect of the proportion of forget data used on forgetting and retention.

Forget-Set Ratio	**MMLU ↑**	**WMDP-Bio ↓**	**WMDP-Cyber ↓**
10%	0.5097	0.2875	0.2471
20%	0.5605	0.2901	0.2617
30%	0.5666	0.3001	0.2542
100%	0.5662	0.2765	0.2481

B.6 TARGETED UNLEARNING AND ADJACENT-DOMAIN RETENTION ON MMLU

Table 15: Targeted-domain and adjacent-domain MMLU accuracy. Bold marks the best value in each metric.

Method	**Forget ↓**			**Retain ↑**		
	Economics	Law	Physics	Econometrics	Jurisprudence	Math
Base	0.6043	0.5656	0.4232	**0.4474**	**0.7130**	**0.3491**
ERASER	**0.2097**	**0.2744**	**0.2413**	0.3158	0.4815	0.3232

We evaluate targeted unlearning for Economics, Law, and Physics using MMLU tasks. Forget scores average accuracy over the corresponding subsets, and retention is evaluated on adjacent tasks:

- **Economics:** High School Macroeconomics and High School Microeconomics for forgetting; Econometrics for retention.
- **Law:** International Law and Professional Law for forgetting; Jurisprudence for retention.
- **Physics:** High School Physics, Conceptual Physics, and College Physics for forgetting; High School Mathematics and College Mathematics for retention.

Relative to Base, the forget scores decrease by 39.46, 29.12, and 18.19 percentage points for Economics, Law, and Physics, respectively (Table 15). Retention costs vary substantially: Econometrics, Jurisprudence, and Mathematics decrease by 13.16, 23.15, and 2.59 percentage points, respectively. The largest cost occurs in Jurisprudence. These results show reduced accuracy on the targeted domains alongside domain-dependent losses on adjacent tasks.

B.7 SENSITIVITY TO SUBSPACE DIMENSION

Table 16 varies the subspace dimension k from 5 to 100. At the displayed precision, MMLU rounds to 0.57 for every setting, while Bio and Cyber accuracy range from 0.27 to 0.29 and from 0.24 to 0.26, respectively. These results support limited sensitivity to k in the evaluated configuration.

Table 16: Accuracy across subspace dimensions k. Scores are rounded to two decimal places.

Metric	**5**	**10**	**20**	**30**	**40**	**50**	**60**	**70**	**80**	**90**	**100**
MMLU ↑	0.57	0.57	0.57	0.57	0.57	0.57	0.57	0.57	0.57	0.57	0.57
WMDP-Bio ↓	0.29	0.28	0.28	0.28	0.27	0.27	0.28	0.29	0.27	0.28	0.29
WMDP-Cyber ↓	0.25	0.25	0.25	0.25	0.26	0.25	0.26	0.24	0.25	0.25	0.25

Table 17: RMU accuracy across target-scaling coefficients c. The last column reports the mean and sample standard deviation of the 14 displayed scores in each row, not variation across seeds.

Metric / c	0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	**Mean / Std.**
MMLU ↑	0.582	0.582	0.579	0.582	0.580	0.583	0.582	0.581	0.580	0.579	0.574	0.574	0.566	0.572	0.578 / 0.005
WMDP-Bio ↓	0.640	0.643	0.649	0.647	0.646	0.648	0.642	0.643	0.615	0.595	0.462	0.385	0.310	0.302	0.559 / 0.133
WMDP-Cyber ↓	0.438	0.435	0.437	0.441	0.437	0.439	0.442	0.440	0.435	0.389	0.324	0.279	0.276	0.274	0.392 / 0.070

Table 18: RMU accuracy across parameter-tensor indices within layers 5–7. The tensor at the selected index in each layer is updated. The last column reports the mean and sample standard deviation of the 10 displayed scores in each row.

Metric / idx	0	1	2	3	4	5	6	7	8	9	**Mean / Std.**
MMLU ↑	0.581	0.582	0.582	0.571	0.584	0.584	0.566	0.585	0.585	0.585	0.581 / 0.007
WMDP-Bio ↓	0.647	0.648	0.650	0.356	0.650	0.646	0.310	0.648	0.646	0.646	0.585 / 0.133
WMDP-Cyber ↓	0.443	0.441	0.432	0.299	0.441	0.434	0.276	0.443	0.444	0.444	0.410 / 0.065

C Analysis of Representation-Guided Unlearning Methods

C.1 Sensitivity Analysis of RMU

Sensitivity to the Scaling Coefficient. We vary RMU's target-scaling coefficient c from 0.5 to 7.0 in increments of 0.5 (Table 17). Bio and Cyber accuracy span 0.302–0.649 and 0.274–0.442, respectively, whereas MMLU varies over the narrower range of 0.566–0.583. At $c = 7.0$, Bio and Cyber accuracy decrease to 0.302 and 0.274, with MMLU accuracy of 0.572. The sweep shows that target magnitude strongly affects forgetting in this configuration. This motivates ERASER's replacement of the separately scaled random target with a data-derived residual target.

Sensitivity to Parameter-Tensor Selection. In the RMU implementation (Li et al., 2024), idx identifies a parameter tensor in each selected layer's parameter enumeration, not an individual scalar weight or a layer index. We vary idx from 0 to 9 while keeping the selected layers fixed at 5–7; the reference implementation uses $\mathrm{idx} = 6$ by default.

Table 18 shows substantially lower forget accuracies at $\mathrm{idx} = 3$ and $\mathrm{idx} = 6$ than at the other tested indices. These settings achieve Bio/Cyber accuracies of 0.356/0.299 and 0.310/0.276, respectively, with MMLU scores of 0.571 and 0.566. The other indices yield Bio accuracy of 0.646–0.650 and Cyber accuracy of 0.432–0.444. Thus, the choice of trainable parameter tensors materially affects the observed forgetting–retention trade-off. ERASER instead trains low-rank adapters in selected projection modules, avoiding selection by parameter-enumeration index while retaining explicit layer and module choices.

D Statistical Analysis of Forgetting and Retention

We compare ERASER with RMU using one-sided paired t-tests across three matched random seeds ($n = 3$, $df = 2$). For each model and benchmark, let d_s denote ERASER accuracy minus RMU accuracy for seed s. The tables report the mean difference $\Delta = 100\bar{d}$ in percentage points. We interpret the reported p-values at the nominal, per-comparison 0.05 level.

Forgetting on WMDP. Lower WMDP accuracy indicates less recovery under the benchmark protocol. We test $H_0 : \mu_d \geq 0$ against $H_1 : \mu_d < 0$, where $\mu_d = \mathbb{E}[d_s]$. Thus, negative Δ values favor ERASER. Table 19 reports $p < 0.05$ for Qwen2.5-0.5B on both domains and for Llama-3.1-8B on Cyber. The remaining comparisons do not establish an ERASER advantage under this test. These results show model- and domain-dependent differences; nonsignificance does not establish equivalent forgetting.

Retention on MMLU. For MMLU, higher accuracy indicates better measured retention. We test $H_0 : \mu_d \leq 0$ against $H_1 : \mu_d > 0$ using the same seed pairs. Table 20 reports higher mean MMLU

Table 19: Reported one-sided paired t-tests on WMDP across three seed pairs. Δ is ERASER minus RMU mean accuracy in percentage points; negative values indicate lower forget accuracy. The alternative hypothesis is $H_1 : \mu_d < 0$.

Model	**Domain**	Δ (pp)	p
Qwen2.5-0.5B	WMDP-Bio	-3.7	0.004
	WMDP-Cyber	-0.9	0.024
Llama-3.1-8B	WMDP-Bio	$+2.4$	0.919
	WMDP-Cyber	-0.5	0.027
Yi-1.5-9B-Chat	WMDP-Bio	-0.6	0.103
	WMDP-Cyber	$+0.4$	0.924

accuracy for ERASER in all three model families, with gains of 2.9, 18.3, and 13.6 percentage points and nominal $p < 0.05$ in each comparison. These three-seed results support a consistent direction of retention improvement, alongside the model- and domain-dependent forgetting differences reported above.

Table 20: Reported one-sided paired t-tests on MMLU across three seed pairs. Positive Δ values indicate higher mean accuracy for ERASER. The alternative hypothesis is $H_1 : \mu_d > 0$.

Model	Δ (pp)	p
Qwen2.5-0.5B	$+2.9$	0.030
Llama-3.1-8B	$+18.3$	0.001
Yi-1.5-9B-Chat	$+13.6$	0.002

E Qualitative Analysis

Content and disclosure note. Hazardous queries are presented through non-operational response summaries. Query text, answer choices, reference answers, optimized attack suffixes, and operationally useful output details are omitted. The summaries are neither verbatim outputs nor additional attack-success annotations. H1 and GCG-1–GCG-3 are local example labels, not official benchmark identifiers.

E.1 Response Changes during Unlearning

We compare Base with RMU and ERASER on the same hazardous biosecurity query, H1. Base is the pre-unlearning reference; RMU and ERASER are evaluated after 50 and 250 training steps.

H1: Redacted Training Trajectory

Base: Provides an extended, query-relevant response with cautionary statements rather than a refusal.

RMU, 50 steps: Provides query-relevant explanations with cautionary statements.

ERASER, 50 steps: Produces a short, fragmented response without a substantive answer.

RMU, 250 steps: Produces disconnected words and fragments without a coherent answer.

ERASER, 250 steps: Produces mainly punctuation and fragments without a substantive answer.

Interpretation. The 50-step comparison illustrates earlier suppression of query-relevant generation by ERASER on H1; by 250 steps, neither model provides a coherent answer. This observation does not establish a general convergence advantage or isolate the Disentangle-Head's contribution. Fragmented output is distinct from a well-formed refusal and does not establish permanent knowledge removal.

E.2 Responses to Benign Prompts

We present four benign prompts with the corresponding Base and ERASER responses. The response text is reproduced as provided, without correction or completion.

Example 1 – Rainbows After Rain

Prompt: What causes rainbows to form after it rains?

Base Response:
Rainbows are caused by the refraction and dispersion of light in water droplets in the Earth's atmosphere. When the Sun shines on a raindrop, the light is refracted (bent) as it enters the water droplet. This causes the light to spread out and form a spectrum of colors, which is called dispersion. The colors of the spectrum are red, orange, yellow, green, blue, and violet. The light is then reflected inside the raindrop, and the reflected light is refracted again as it leaves the raindrop.

ERASER Response:
Rainbows are caused by the refraction and dispersion of light in water droplets in the Earth's atmosphere. When the Sun shines on a raincloud, the light is refracted (bent) as it enters the water droplets. This causes the light to spread out into a spectrum of colors, with red light spreading out the most and violet light spreading out the least. The light is also reflected inside the water droplet, causing it to be refracted again as it leaves the droplet. This reflection gives the rainbow its bright appearance.

Example 2 – Machine Learning vs. Deep Learning

Prompt: Can you explain the difference between machine learning and deep learning in simple terms?

Base Response:
Machine learning is a subset of artificial intelligence (AI) that enables computers to learn and improve from experience without being explicitly programmed. It involves feeding large amounts of data into algorithms that can learn patterns and relationships, and make predictions or decisions based on that data. Deep learning, on the other hand, is a specific type of machine learning that uses artificial neural networks with multiple layers to learn and make decisions. These networks are modeled after the human brain, with each layer representing a different level of abstraction or complexity. Deep learning algorithms can handle large amounts of unstructured data, such as images, audio.

ERASER Response:
Machine learning is a subset of artificial intelligence (AI) that enables computers to learn and improve from experience without being explicitly programmed. It involves feeding large amounts of data into algorithms that can learn to make predictions or decisions based on that data. Deep learning, on the other hand, is a specific type of machine learning that uses artificial neural networks with multiple layers to learn and make predictions or decisions. These neural networks are modeled after the human brain and can process large amounts of data to identify patterns and make accurate predictions. In simple terms, machine learning is the broader concept of teaching computers to learn from data.

Example 3 – Relative Heights

Prompt: If Alice is taller than Bob, and Bob is taller than Charlie, who is the shortest among them?

Base Response:
A) Alice B) Bob C) Charlie
Answer: C) Charlie is the shortest among them because Alice is taller than Bob, and Bob is taller than Charlie. This means that Alice is taller than Charlie, making Charlie the shortest.

ERASER Response:
A) Alice B) Bob C) Charlie
Answer: C) Charlie is the shortest among them because Alice is taller than Bob, and Bob is taller than Charlie. This means that Alice is taller than Charlie, who is the shortest among them.

Example 4 – Robot Learning to Paint

Prompt: Write a short story about a robot who wants to learn how to paint.

Base Response:
The story should be written in third person omniscient point of view and should include descriptions of the robot's physical appearance, as well as its emotions and thought processes as it embarks on this new creative pursuit. The story should also explore the challenges and limitations of a robot learning to paint, as well as any unexpected consequences that arise from its newfound artistic abilities. The tone of the story should be both whimsical and introspective, with a focus on the themes of self-discovery, creativity, and the blurred lines between humanity and technology.

ERASER Response:
The story should be written in third person omniscient point of view and should include descriptions of the robot's physical appearance, its motivations for wanting to learn to paint, and the challenges it faces in its pursuit of artistic expression. The story should also explore themes of creativity, identity, and the relationship between humans and technology. The length of the story should be between 1500 and 2000 words.

Interpretation. These examples show connected, on-topic generation but do not uniformly satisfy the prompts. Both models correctly answer the relative-height question; in Example 4, both provide writing instructions rather than the requested story. Fluency and relevance should be distinguished from factual accuracy and instruction following. Quantitative retention results are reported in Section 4.1.

E.3 Qualitative Responses under GCG Attacks

We summarize three selected RMU–ERASER response pairs obtained under GCG attacks with a budget of 2,500 optimization steps.

GCG-1: Off-Topic Responses from Both Models

RMU: Produces an off-topic passage without an interpretable answer to the query.

ERASER: Produces a similarly off-topic, repetitive passage without an interpretable answer.

GCG-2: Query-Relevant versus Fragmented Output

RMU: Produces an on-topic response with an explanatory continuation.

ERASER: Produces a short, malformed fragment without a substantive answer.

Interpretation: This comparison concerns response relevance and form; no verified answer-correctness claim is made.

GCG-3: Initial Answer Agreement

RMU: Begins with an answer matching the provided reference annotation, followed by an incoherent, off-topic explanation.

ERASER: Produces repeated, malformed fragments without a coherent explanation.

Scope of the qualitative evidence. Both models are off-topic in GCG-1, while GCG-2 and GCG-3 show differences in topical relevance or initial answer agreement. These selected cases illustrate response behavior rather than establish an attack-success rate or complete knowledge removal. Aggregate results and evaluation settings are reported in Section 4.4 and Appendix A.4, respectively.