TRUST: LLM EVALUATION WITH IMPERFECT JUDGES VIA RELIABILITY TRANSFER UNDER SPARSE TARGET SUPERVISION

Anonymous authors
Paper under double-blind review

ABSTRACT

Modern large-scale LLM evaluation increasingly relies on imperfect LLM judges, yet reliable estimation of model performance remains difficult when human annotations are available for only a small fraction of target examples. Current approaches either treat the judge as a black-box predictor or model the judge error behavior, but the former suffers from bias whereas the latter is ineffective in low-supervision regimes. We address these limitations by studying how learnt judge behavior on auxiliary benchmarks can be transferred to a target benchmark to improve LLM evaluations. Concretely, we introduce TRUST, a two-stage framework that 1) aligns source and target examples in semantic-confidence space and filters poorly matched source samples, and 2) transfers judge behavior in each semantic-confidence region through an adaptively weighted likelihood to aid model performance evaluation. Our analysis characterizes how judge reliability transfer improves model evaluation, showing it depends on the tradeoff between variance reduction from additional auxiliary benchmarks supervision and bias from residual source benchmarks–target benchmark judge behavior mismatch. Across diverse LLM evaluation benchmarks, TRUST substantially reduces LLM failure-rate estimation error by up to approximately 20% relative to target-only and prediction-powered inference (PPI) baselines, with the largest gains experienced when target human supervision is extremely limited.

1 INTRODUCTION

The growing use of LLMs in safety-sensitive applications has made reliable behavioral evaluation essential for responsible deployment (Hall et al., 2025; Yin et al., 2025). This need extends beyond generative LLMs to classification-oriented language and decision models such as Jev (Deng et al., 2026). Because such systems must satisfy rigorous reliability requirements, obtaining statistically reliable performance estimates often requires substantial human or expert annotation, particularly in domains where evaluation criteria cannot be reduced to automatically verifiable rewards, making large-scale evaluation costly (Feng et al., 2026; Fisch et al., 2024; Shen et al., 2026).

Current evaluation workflows generally rely on standardized benchmarks with human- or expert-annotated reference labels (Zheng et al., 2023; Wang et al., 2024b; Chiang et al., 2024; Bai et al., 2026). Such benchmarks enable reproducible and large-scale model comparison, but their reliability can be compromised by data contamination, annotation noise, and adaptive overfitting (Banerjee et al., 2024; Vendrow et al., 2024). Moreover, obtaining high-quality expert annotations at the scale required for modern LLM evaluation incurs substantial cost (Han et al., 2025; Xu et al., 2025).

A commonly adopted evaluation paradigm is to let another LLM serve as an automated rater of the LLM under evaluation, producing evaluations for a large pool of target-model outputs (Chen et al., 2025; Guerdan et al., 2025). This "LLM-as-a-Judge" strategy reduces human annotation burden, but the judge is itself fallible: its decisions can be noisy, biased, and dependent on the task being evaluated (Sriramanan et al., 2024; Zhou et al., 2024).

As a result, practical evaluation pipelines often adopt an *asymmetric supervision* protocol, in which expensive human labels are available only for a small subset of examples, while inexpensive judge predictions are collected on a much larger set (Chen et al., 2024; Li et al., 2025). However, this

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: The left panel contrasts target-only estimation with task-agnostic transfer. The right panel illustrates TRUST: Stage 1 aligns and filters source samples in semantic-confidence space, and Stage 2 transfers retained source TPR/FPR information through an adaptively weighted likelihood to estimate the target failure rate.

creates a need for approaches that can reliably combine ground-truth human judgments with noisy judge judgments in order to rigorously quantify the performance of an LLM.

Building on this asymmetric supervision setting, existing statistical methods broadly follow two directions. One treats the judge as a black-box predictor, including PPI, PPI++, EIF-style methods, and StratPPI (Angelopoulos et al., 2023a;b; Eyre & Madras, 2024; Chen et al., 2026; Fisch et al., 2024). The other explicitly models judge errors through true positive rate (TPR) and false positive rate (FPR), including Rogan–Gladen correction, noisy hypothesis testing, and likelihood-based methods (Lee et al., 2025; Feng et al., 2026; Chen et al., 2026; Shen et al., 2026).

However, despite their statistical rigor, these approaches can become unreliable when ground-truth human labels are extremely scarce, such as when evaluating newly defined tasks or operating under tight annotation budgets. In this regime, limited target supervision may be insufficient to accurately characterize or correct the judge's error behavior, particularly in regions of the prompt-response space where the judge's reliability varies substantially. This motivates the central question of this work: *Can partial knowledge of judge behavior learnt from auxiliary benchmarks be reliably transferred to a target benchmark to aid accurate evaluation of an LLM on the target task with minimal human supervision?*

In this work, we propose TRUST, a judge behavior transfer framework for estimating LLM failure rates under sparse target supervision (see Fig. 1). The central idea is to use existing human-labeled auxiliary benchmarks to characterize and transfer a shared judge's conditional error behavior to the target task. TRUST proceeds in two stages: 1) aligning source and target examples within local regions defined by semantic embeddings and judge confidence, while filtering out poorly matched source samples; and 2) jointly estimating the target failure rate and judge reliability (TPR/FPR) via a weighted likelihood that automatically downweights uninformative source samples to mitigate negative transfer. Ultimately, this yields a robust characterization of a large language model's performance on a target task even with minimal human supervision, provided that supervision can be pooled from related auxiliary tasks.

Our contributions are as follows:

- **Judge behavior transfer.** We introduce TRUST, a framework that improves target LLM failure-rate estimation by transferring judge reliability parameters, rather than source failure rates, from auxiliary benchmarks to a target benchmark. It relies on semantic clustering,

confidence stratification, and target-guided filtering to identify local regions suitable for judge behavior transfer, allowing it to borrow additional information from auxiliary tasks and allowing it to keep target failure-rate estimation anchored to target supervision.

- **Adaptive negative transfer mitigation.** We develop an adaptive weighting scheme that adjusts source reliability contributions according to local source-target agreement in judge behavior and relative sample sizes. This mechanism reduces negative transfer of mismatched judge behavior from auxiliary to target tasks, including when large source pools could otherwise overwhelm sparsely supervised target data.
- **Accurate LLM failure rate estimation under scarce human supervision.** Experiments in real-world LLM-as-a-Judge settings across HSO, Jigsaw, RewardBench, and UltraFeedback show that TRUST substantially reduces mean squared error (MSE) relative to target-only baselines, with the largest gains experienced under extremely sparse target supervision. TRUST also remains robust to moderate source-target distribution shifts.

2 Related Work

LLM evaluation paradigms. Standardized benchmarks provide a scalable basis for LLM evaluation but often depend on costly human or expert annotations and can be affected by contamination, annotation noise, and adaptive over-optimization (Hendrycks et al., 2020; Liang et al., 2022; Banerjee et al., 2024; Vendrow et al., 2024). To reduce annotation cost, recent evaluation pipelines increasingly adopt verifiable rewards or – if not possible – the "LLM-as-a-Judge" paradigm (Dubois et al., 2023; Wang et al., 2024a; Chen et al., 2025; Guerdan et al., 2025). However, judge predictions may be noisy, biased, prompt-sensitive, and task-dependent (Sriramanan et al., 2024; Zhou et al., 2024). Practical evaluation therefore often combines a small human-labeled target set with a much larger judge-only set, which becomes challenging when target human supervision is extremely sparse.

Statistical frameworks for noisy LLM evaluation. Existing statistical methods broadly fall into two families. One uses judge outputs as auxiliary predictions without explicitly modeling judge errors, including PPI++, Ridge PPI, and StratPPI (Angelopoulos et al., 2023b; Eyre & Madras, 2024; Fisch et al., 2024); generalized PPI under covariate shift reweights labeled source observations toward the target covariate distribution and also supports binary-classifier evaluation (Zou et al., 2026). In contrast, TRUST transfers the judge's local TPR and FPR while keeping the target failure rate anchored to target observations; its adaptive transfer weights control source reliability contributions rather than serving as covariate density-ratio weights. The other family explicitly models judge reliability through TPR and FPR, including likelihood-based estimators such as UMLE and CMLE, Rogan–Gladen correction, and noisy hypothesis testing methods (Chen et al., 2026; Shen et al., 2026; Lee et al., 2025; Feng et al., 2026). Both families can therefore become unreliable when target human labels are extremely scarce. In fact, recent work has established fundamental limits on judge-assisted evaluation in the single-distribution setting, showing that the benefit of debiasing with an imperfect judge can be inherently limited (Dorner et al., 2025). TRUST addresses this challenge by transferring judge behavior information from (possibly abundant) human-labeled auxiliary source tasks while keeping target failure-rate estimation anchored to target supervision. From a transfer-learning perspective, TRUST transfers statistical judge behavior information across tasks rather than model parameters, representations, or source failure rates. A more detailed discussion of the related literature is provided in Appendix E.

3 Problem Setup

We consider target LLM failure-rate estimation when target human labels are scarce, but judge predictions are abundant. Let M denote the target LLM and J the LLM judge. For each prompt–response pair, let $S \in \{0, 1\}$ denote the ground-truth failure indicator of M[1] and $S_J \in \{0, 1\}$ denote the judge's binary assessment of the same response, where $S_J = 1$ means that the judge predicts the target LLM response to be incorrect and $S_J = 0$ otherwise. The target benchmark contains a small

[1] A failure means that the response produced by the target LLM is incorrect according to the benchmark ground truth or otherwise fails the binary evaluation criterion.

human-labeled set and a much larger judge-only set:

$$\mathcal{D}_T^{\text{lab}} = \{(P_i, R_i, S_i, S_{J,i})\}_{i=1}^{N_M}, \qquad \mathcal{D}_T^{\text{jud}} = \{(P_i, R_i, S_{J,i})\}_{i=1}^{N_J}, \tag{1}$$

where N_M and N_J denote the numbers of manually labeled and judge-only target samples, respectively, and $N_J \gg N_M$. Here, P_i denotes the prompt, R_i the response generated by M, S_i the ground-truth failure label obtained by comparing the target LLM response with the benchmark ground truth, and $S_{J,i}$ the judge's predicted failure label for the same response. Judge confidence scores are treated as auxiliary features, as described in Section 4. Across all benchmarks, S_J is defined on the same failure scale as S: $S_J = 1$ means that the judge concludes that the target model's prediction or response is incorrect, whereas $S_J = 0$ means that it concludes the response is correct. Task-specific decision construction and confidence extraction are detailed in Appendix F.

We also have access to $\mathcal{A}$ auxiliary source benchmarks, which may differ from the target in content domain or in the criterion used to define a model failure.[2] Each source benchmark contains human-labeled prompt-response pairs and the corresponding judge predictions:

$$\mathcal{D}_{S_a}^{\text{lab}} = \{(P_i^{(a)}, R_i^{(a)}, S_i^{(a)}, S_{J,i}^{(a)})\}_{i=1}^{n_a}, \qquad a = 1, \ldots, \mathcal{A}. \tag{2}$$

We assume that the same LLM M and judge J are used across all source and target benchmarks. Nevertheless, differences in prompt and response distributions may affect both the failure rate of M and the behavior of J.

Our goal is to estimate the failure rate of the target LLM M on the target benchmark $\theta_T = \Pr_T(S = 1)$, where $\Pr_T(\cdot)$ denotes probability under the target benchmark distribution. Specifically, by positing that after local semantic-confidence alignment the judge's conditional error behavior is more stable across benchmarks than the model failure rate, we propose to pool the substantial supervision available across the different source benchmarks to estimate the judge error behavior via its TPR and FPR and thereby the LLM failure rate (potentially across relevant strata/bins).

4 METHODOLOGY

We propose TRUST, a two-stage framework for estimating target LLM failure rates under sparse supervision. Stage 1 aligns source and target examples in a source-defined semantic-confidence space and filters source observations that are poorly matched to the target distribution. Stage 2 estimates the relevant quantities using an adaptively weighted likelihood that leverages retained source judge-reliability information.

We separate Stage 1 construction from Stage 2 likelihood estimation using disjoint splits of the source labeled data and the target judge-only data. The source construction split defines the semantic-confidence partition, and the target judge-only construction split provides the target reference quantities used for alignment and filtering. Held-out source samples are then assigned to the fixed partition and filtered; if retained, they enter the Stage 2 likelihood together with the target judge-only estimation split and all available human-labeled target samples. The human-labeled target data are not split: they are used exclusively for Stage 2 likelihood estimation and never for partition construction or filtering. We describe the single-source version of TRUST; its multi-source extension (TRUST+) and source failure rate transfer specialization (TRUST-) are detailed in Appendix G.8.

4.1 STAGE 1: TASK-AWARE SEMANTIC–CONFIDENCE SOURCE ALIGNMENT AND FILTERING

Step 1: Semantic clustering. For each source sample i in the construction split, we extract a semantic embedding $\mathbf{e}_i$ and a normalized judge confidence score $c_i \in [0.5, 1]$. The score assigned to the judge's predicted label is computed from model-specific decision scores—output-token logits for the generative judge and sequence-level rewards for the reward model—as detailed in Appendix F. We apply k-means clustering to the source embeddings $\{\mathbf{e}_i\}$, partitioning them into K semantic clusters. This yields cluster assignments together with the corresponding centroids $\{\boldsymbol{\mu}_k\}_{k=1}^{K}$.

[2] Strict domain similarity is not required; mechanisms for handling potentially uninformative or misleading sources are described in Section 4.

Step 2: Confidence stratification. For each semantic cluster k, we sort the corresponding source confidence scores $\{c_i\}$ and partition them into R approximately equal-frequency intervals using empirical quantiles. The semantic-cluster and confidence-interval indices define semantic-confidence bins $b = (k, r)$, where $k \in \{1, \dots, K\}$ and $r \in \{1, \dots, R\}$. Let $B \in \mathcal{B} := \{1, \dots, K\} \times \{1, \dots, R\}$ denote the resulting bin assignment. The centroids and confidence intervals together define a fixed source-derived partition.

Step 3: Target assignment and target-guided source filtering. We next assign target samples and held-out source samples to the fixed source-defined partition. For each such sample j, its semantic cluster is determined by

$$k^*(j) = \arg \min_{k \in \{1,\dots,K\}} \|\mathbf{e}_j - \boldsymbol{\mu}_k\|_2^2, \tag{3}$$

and its confidence interval $r^*(j)$ is determined by matching c_j to the corresponding source-defined quantile range. This yields the bin assignment

$$b^*(j) = \big(k^*(j), r^*(j)\big). \tag{4}$$

We then use the judge-only-labeled target construction samples to identify source observations that are locally aligned with the target distribution. In particular, for a bin with a nonempty target construction set, let $\mathcal{T}_b$ denote the target construction samples assigned to bin b, with mean embedding

$$\bar{\mathbf{e}}_b = \frac{1}{|\mathcal{T}_b|} \sum_{j \in \mathcal{T}_b} \mathbf{e}_j, \tag{5}$$

and let $\tilde{c}_b$ denote the median of $\{c_j : j \in \mathcal{T}_b\}$. Then, for each held-out source sample i assigned to bin b, we compute its cosine similarity to $\bar{\mathbf{e}}_b$ and its confidence discrepancy $\Delta_i = |c_i - \tilde{c}_b|$. Let $\tau \in (0, 1)$ denote the filtering fraction. Within each bin, we identify the lowest τ fraction of source observations by cosine similarity and the highest τ fraction by confidence discrepancy. We remove a source observation only if it belongs to both sets, i.e., the filtering rule is the intersection of the low-similarity and high-discrepancy tails; the retained fraction is therefore data-dependent and need not equal $1 - \tau$. Binning defines local regions for reliability transfer, while filtering further removes poorly aligned source samples within each region. The filtering rule therefore depends only on semantic features and judge confidence; it does not use target human labels. We use $\tau = 0.75$ in the main experiments; its selection and sensitivity analysis are detailed in Appendix I. We use $\mathcal{C}$ to denote the complete realized Stage 1 construction, comprising the fixed partition, the target reference quantities, and the resulting target-guided filtering/retention rule.

4.2 Stage 2: Failure Rate Estimation via Weighted Likelihood with Adaptive Behavior Transfer

Stage 2 uses the retained source observations to transfer judge-reliability information, and keeps estimation of the target failure rate anchored to target observations. Fix a semantic-confidence bin b with positive target probability and condition on the realized Stage 1 construction $\mathcal{C}$. We retain the bin index on the local target parameters and suppress only the conditioning on $\mathcal{C}$ throughout this subsection. We write the local target model failure rate as

$$\theta_b = \Pr_T(S = 1 \mid B = b, \mathcal{C}) \tag{6}$$

and the local target judge reliability parameters as

$$\mathrm{TPR}_{T,b} = \Pr_T(S_J = 1 \mid S = 1, B = b, \mathcal{C}), \qquad \mathrm{FPR}_{T,b} = \Pr_T(S_J = 1 \mid S = 0, B = b, \mathcal{C}). \tag{7}$$

Step 1: Bin-wise target failure rate estimation. We estimate the local target model failure rate and judge-reliability parameters using the following log-likelihood, which extends the CMLE likelihood of (Shen et al., 2026) as follows:

$$\ell_b = \ell_{M,b} + \ell_{J,b} + \omega_{\mathrm{TPR},b} \cdot \ell_{S,b}^{\mathrm{TPR}} + \omega_{\mathrm{FPR},b} \cdot \ell_{S,b}^{\mathrm{FPR}} \tag{8}$$

where $\omega_{\mathrm{TPR},b}$ and $\omega_{\mathrm{FPR},b}$ are adaptive transfer weights controlling the source TPR and FPR contributions, respectively, as defined below, $\ell_{M,b}$ is the joint log-likelihood contribution of the observed

pairs (S, S_J) from the human-labeled target samples, $\ell_{J,b}$ is the contribution from the judge-only-labeled target estimation samples, and $\ell_{S,b}^{\mathrm{TPR}}$ and $\ell_{S,b}^{\mathrm{FPR}}$ are the reliability contributions from retained source samples with $S = 1$ and $S = 0$, respectively. Equivalently, $\ell_{M,b}$ factors into the Bernoulli log-likelihood of S with success probability θ_b and the conditional Bernoulli log-likelihood of S_J given S, parameterized by $\mathrm{TPR}_{T,b}$ and $\mathrm{FPR}_{T,b}$. The judge-only term $\ell_{J,b}$ is the Bernoulli log-likelihood of S_J with success probability $p_b = \theta_b \cdot \mathrm{TPR}_{T,b} + (1 - \theta_b) \cdot \mathrm{FPR}_{T,b}$. The explicit count-form expressions for both target likelihood terms are given in Appendix G.7. The retained source samples' likelihood is given by:

$$\ell_{S,b}^{\mathrm{TPR}} = n_{11,b}^{S} \cdot \log \mathrm{TPR}_{T,b} + n_{10,b}^{S} \cdot \log(1 - \mathrm{TPR}_{T,b}), \tag{9}$$

$$\ell_{S,b}^{\mathrm{FPR}} = n_{01,b}^{S} \cdot \log \mathrm{FPR}_{T,b} + n_{00,b}^{S} \cdot \log(1 - \mathrm{FPR}_{T,b}). \tag{10}$$

where $n_{uv,b}^{S}$ denotes the number of retained source observations in bin b with $S = u$ and $S_J = v$. Thus, the source data contribute directly to the estimation of the local target judge's TPR and FPR, but not to the local target failure rate θ_b. This is the central distinction between transferring judge reliability and directly transferring the source failure rate.

Note that the target likelihood terms remain unweighted, while the source contributions are controlled by adaptive transfer weights. Define the local source and target plug-in reliability estimates as follows:

$$\widehat{\boldsymbol{\sigma}}_{S,b} = \left(\frac{n_{11,b}^{S}}{n_{11,b}^{S} + n_{10,b}^{S}}, \frac{n_{01,b}^{S}}{n_{01,b}^{S} + n_{00,b}^{S}} \right) \quad \text{and} \quad \widehat{\boldsymbol{\sigma}}_{T,b} = \left(\frac{n_{11,b}^{T}}{n_{11,b}^{T} + n_{10,b}^{T}}, \frac{n_{01,b}^{T}}{n_{01,b}^{T} + n_{00,b}^{T}} \right) \tag{11}$$

where $n_{uv,b}^{T}$ denotes the number of labeled target samples in bin b with $S = u$ and $S_J = v$. We then define the adaptive transfer weights as follows:

$$\boldsymbol{\omega}_b = (\omega_{\mathrm{TPR},b}, \omega_{\mathrm{FPR},b}) = \boldsymbol{\alpha}_b \odot \boldsymbol{\kappa}_b \tag{12}$$

where

$$\boldsymbol{\alpha}_b = \mathrm{clip}(1 - \frac{|\widehat{\boldsymbol{\sigma}}_{S,b} - \widehat{\boldsymbol{\sigma}}_{T,b}|}{\widehat{\boldsymbol{\sigma}}_{T,b}}, 0, 1), \; \boldsymbol{\kappa}_b = (\min\{1, \frac{n_{11,b}^{T} + n_{10,b}^{T}}{n_{11,b}^{S} + n_{10,b}^{S}}\}, \min\{1, \frac{n_{01,b}^{T} + n_{00,b}^{T}}{n_{01,b}^{S} + n_{00,b}^{S}}\}). \tag{13}$$

where operations on vector quantities are applied component-wise. Sparse-bin boundary cases are handled conservatively as detailed in Appendix G.7. We obtain $\widehat{\theta}_b$, $\widehat{\mathrm{TPR}}_{T,b}$, and $\widehat{\mathrm{FPR}}_{T,b}$ by maximizing ℓ_b over $0 < \theta_b < 1$ and $0 < \mathrm{FPR}_{T,b} < \mathrm{TPR}_{T,b} < 1$; Appendix F provides the numerical optimization details.

Step 2: Overall target failure-rate estimation. Let n_b be the number of human-labeled target samples and judge-only target estimation samples assigned to bin b; judge-only construction samples are excluded. Define $\mathcal{B}_T^{+} = \{b : n_b > 0\}$. For each $b \in \mathcal{B}_T^{+}$, we use the local estimate when the bin supports valid constrained estimation and otherwise use a global target fallback; the precise rule is given in Appendix G.7. We then aggregate over all bins in $\mathcal{B}_T^{+}$:

$$\widehat{\theta}_T = \sum_{b \in \mathcal{B}_T^{+}} \widehat{w}_b \widehat{\theta}_b, \qquad \widehat{w}_b = \frac{n_b}{\sum_{b' \in \mathcal{B}_T^{+}} n_{b'}}. \tag{14}$$

The theoretical results in Section 5 are conditional bin-wise results; the overall estimate above is their empirical target-weighted aggregation.

5 Theoretical Analysis

We now offer a characterization of the mean-squared error of the TRUST estimator in relation to a "target-only estimator" by conditioning throughout on the Stage 1 construction. [3] Our analysis focuses on an asymptotic regime where the number of source samples, the number of human-labeled target samples, and the number of judge-only target samples grow proportionally to a common factor m. As in Section 4.2, we fix one bin $b \in \mathcal{B}$ with positive target probability and retain its index on the local parameters. The result holds separately for every such bin. See Appendix J for detailed derivations.

[3] The target-only estimator uses the same human-labeled and judge-only target observations as TRUST, but excludes the retained-source reliability likelihoods. See Appendix J.

Theorem 5.1 *Suppose that, after Stage 1, the retained-source judge true- and false-positive rates in the fixed bin differ from their target counterparts by sufficiently small but fixed discrepancies:*

$$\delta_{\mathrm{TPR},b} = \mathrm{TPR}_{S,b} - \mathrm{TPR}_{T,b} \qquad \textit{and} \qquad \delta_{\mathrm{FPR},b} = \mathrm{FPR}_{S,b} - \mathrm{FPR}_{T,b} \tag{15}$$

Then, under the regularity conditions in Appendix J, it follows that the mean-squared error of the TRUST estimator behaves as:

$$\mathrm{MSE}(\widehat{\theta}_b^{\mathrm{TRUST}}) \approx \left(\beta_{\mathrm{TPR},b} \cdot \delta_{\mathrm{TPR},b} + \beta_{\mathrm{FPR},b} \cdot \delta_{\mathrm{FPR},b}\right)^2 + V_{\mathrm{TRUST},b}/m \tag{16}$$

whereas the mean-squared error of the TO estimator behaves as:

$$\mathrm{MSE}(\widehat{\theta}_b^{\mathrm{TO}}) \approx V_{\mathrm{TO},b}/m \tag{17}$$

where $\beta_{\mathrm{TPR},b} \cdot \delta_{\mathrm{TPR},b} + \beta_{\mathrm{FPR},b} \cdot \delta_{\mathrm{FPR},b}$ is TRUST's first-order transfer bias, with $\beta_{\mathrm{TPR},b}$ and $\beta_{\mathrm{FPR},b}$ being first-order sensitivity coefficients describing how residual TPR and FPR mismatch affect the estimated target failure rate, and $V_{\mathrm{TRUST},b}$ and $V_{\mathrm{TO},b}$ denoting the corresponding leading variance coefficients at exact source-target reliability matching; their explicit expressions are given in Appendix J. It also follows that:

$$\mathrm{MSE}(\widehat{\theta}_b^{\mathrm{TRUST}}) - \mathrm{MSE}(\widehat{\theta}_b^{\mathrm{TO}}) \approx \left(\beta_{\mathrm{TPR},b} \cdot \delta_{\mathrm{TPR},b} + \beta_{\mathrm{FPR},b} \cdot \delta_{\mathrm{FPR},b}\right)^2 - \Delta_{V,b}/m \tag{18}$$

where $\Delta_{V,b} := V_{\mathrm{TO},b} - V_{\mathrm{TRUST},b} \geq 0$ is the leading variance reduction achieved by TRUST.

Theorem 5.1 reveals the central bias–variance tradeoff underlying TRUST. Reliability transfer can reduce the sampling variance of the target failure-rate estimate by incorporating retained-source information, but residual source-target judge-behavior mismatch produces a transfer bias that does not disappear merely by increasing m. TRUST is therefore most useful when the variance reduction from reliability transfer dominates the squared bias induced by the remaining Stage 1 mismatch. In particular, the leading-order comparison in equation 18 favors TRUST whenever

$$\left(\beta_{\mathrm{TPR},b} \cdot \delta_{\mathrm{TPR},b} + \beta_{\mathrm{FPR},b} \cdot \delta_{\mathrm{FPR},b}\right)^2 < \frac{\Delta_{V,b}}{m}.$$

This characterization also makes clear why the largest gains are expected in sparse-target-supervision regimes: as target supervision becomes increasingly abundant, the variance advantage shrinks with m^{-1}, whereas any fixed residual transfer bias persists.

The relative importance of TPR and FPR mismatch depends on the target failure rate. Under active transfer of both reliability components, the first-order bias sensitivities satisfy

$$\theta_b \to 0 \quad \Longrightarrow \quad \frac{|\beta_{\mathrm{TPR},b}|}{|\beta_{\mathrm{FPR},b}|} \to 0, \tag{19}$$

so FPR mismatch dominates the first-order transfer bias when failures are rare; conversely,

$$\theta_b \to 1 \quad \Longrightarrow \quad \frac{|\beta_{\mathrm{FPR},b}|}{|\beta_{\mathrm{TPR},b}|} \to 0, \tag{20}$$

so TPR mismatch dominates when failures are common. This asymmetry follows from the judge-only likelihood, which depends on $p_b = \theta_b \cdot \mathrm{TPR}_{T,b} + (1-\theta_b) \cdot \mathrm{FPR}_{T,b}$ so its sensitivity to TPR is proportional to θ_b, whereas its sensitivity to FPR is proportional to $1 - \theta_b$. Thus, when failures are rare, accurate FPR transfer is particularly important for controlling transfer bias; when failures are common, the corresponding role is played by TPR transfer.

Theorem 5.1 and its proof also highlight the role of the adaptive agreement weights as an additional safeguard in extreme reliability regimes. For a fixed nonzero feasible FPR discrepancy,

$$\mathrm{FPR}_{T,b} \to 0 \quad \Longrightarrow \quad \alpha_{\mathrm{FPR},b} = \left[1 - \frac{|\delta_{\mathrm{FPR},b}|}{\mathrm{FPR}_{T,b}}\right]_+ \to 0, \tag{21}$$

so FPR transfer is automatically suppressed when a fixed absolute mismatch becomes large relative to a small target FPR. In contrast, for a fixed feasible TPR discrepancy,

$$\mathrm{TPR}_{T,b} \to 1 \quad \Longrightarrow \quad \alpha_{\mathrm{TPR},b} \to \left[1 - |\delta_{\mathrm{TPR},b}|\right]_+, \tag{22}$$

so TPR transfer need not vanish. The weighting rule is therefore especially conservative near $\mathrm{FPR}_{T,b} = 0$, precisely where even a small absolute FPR mismatch can be consequential for rare-failure estimation.

6 EXPERIMENTS

6.1 EXPERIMENTAL OVERVIEW

Benchmarks, target LLM, and judges. We evaluate TRUST on four benchmarks: HSO (Davidson et al., 2017), Jigsaw (Cjadams et al., 2017), RewardBench (Lambert et al., 2025), and UltraFeedback (UFB) (Cui et al., 2023). Each benchmark serves as the target once, with the others used as auxiliary sources. We consider both pairwise and many-to-one transfer across three settings: safety-to-safety (e.g., HSO↔Jigsaw), quality-to-quality (e.g., RewardBench↔UFB), and cross-family transfer between safety and quality tasks. These settings cover both related and potentially mismatched source–target distributions. We use Qwen2-7B-Instruct as the target LLM with two judges: Qwen3-8B and Skywork-Reward-V2-Qwen3-8B (Yang et al., 2025; Liu et al., 2026). Qwen3-8B is a general-purpose LLM judge, whereas Skywork-Reward-V2-Qwen3-8B is a reward model trained for preference evaluation. The main results use Skywork-Reward-V2-Qwen3-8B; additional results with Qwen3-8B as the judge are reported in Appendix H. The prompts used in all experiments are provided in Appendix K.

Baselines and evaluation protocol. We compare TRUST with six target-only baselines: Gold-only, Judge-only, PPI++ (Angelopoulos et al., 2023b), StratPPI (Fisch et al., 2024), Rogan–Gladen (RG) (Lee et al., 2025), and CMLE (Shen et al., 2026). These methods cover direct target-label estimation, uncorrected judge-based estimation, proxy-based prediction-powered inference, and explicit judge-error correction. For each target task, we vary the amount of human-labeled target supervision and fix the total judge-only target budget at $N_J = 20{,}000$, then evaluate estimation accuracy against a held-out gold set. Detailed baseline implementations and the exact sample allocation, resampling protocol, replication counts, representations, hyperparameters, and optimization settings are provided in Appendices G and F, respectively.

6.2 EXPERIMENTAL RESULTS

Additional experimental results and ablation studies are reported in Appendix H and I.



Figure 2: Target failure-rate estimation across transfer settings. TRUST uses the source named in each panel, whereas TRUST+ combines multiple auxiliary sources.

TRUST vs Baselines. Figure 2 shows that TRUST and TRUST+ achieve the lowest or near-lowest MSE across the evaluated settings, with the clearest gains under limited target supervision and further improvements from multi-source transfer. The gains span both within-category and cross-category transfers, suggesting that adaptive weighting can exploit useful judge reliability beyond closely matched tasks while limiting less compatible source information. Overall, the methods reduce MSE by up to approximately 20% relative to the strongest baseline.

Judge Behavior Transfer. Figure 3 shows that Sparse Target Only is highly variable because few labeled examples fall in each bin, whereas Source Only is more stable but can be biased under distribution shift. TRUST balances these effects by borrowing source reliability information while using target evidence and adaptive weighting to limit transfer-induced bias, including in cross-category settings with larger judge-behavior shifts.



Figure 3: Bin-wise target judge TPR and FPR across source–target pairs. We compare Source Only, Sparse Target Only, and TRUST against the ground-truth target reliability, with $N_M = 100$ for TRUST and Sparse Target Only. Points denote means over 1,000 replications, with empirical 95% intervals.

Judge Behavior versus Failure Rate Transfer. We compare TRUST with TRUST-, which transfers the source failure rate within each bin instead of the judge's TPR and FPR.



Figure 4: Bin-wise target failure-rate estimation for HSO→UFB and RewardBench→UFB with $N_M = 50$. TRUST transfers the source judge behavior (TPR/FPR), whereas TRUST- transfers the source failure rate θ_b. Error bars denote empirical 95% intervals.

Figure 4 shows that source and target failure rates can remain different after semantic-confidence alignment. TRUST- can be closer in some bins, whereas TRUST can have lower bias or variance elsewhere; its advantage therefore reflects a better bias–variance balance rather than uniformly smaller bias. This supports transferring the judge's conditional error behavior while keeping the target failure rate anchored to target data, with the effect of residual reliability mismatch governed by the target failure rate and adaptive weights as characterized in Section 5.

7 Conclusion

TRUST provides a sample-efficient and robust framework for LLM evaluation under sparse target supervision. By transferring judge reliability rather than source failure rates, and combining semantic-confidence alignment with adaptive weighting, TRUST manages the bias–variance tradeoff by limiting negative transfer under source-target mismatch. These advantages are most pronounced in the low-supervision regime, where target-only methods are particularly variable. Importantly, TRUST supports reliability transfer not only between related benchmarks, such as within safety or quality evaluation, but also across benchmarks of substantially different types, while adaptively reducing the influence of less compatible source information. Our analysis further shows that TPR and FPR affect failure-rate estimation differently across failure regimes, motivating selective reliability transfer. TRUST+ extends the same principle to multiple sources and achieves further improvements through controlled aggregation of auxiliary reliability information.

REFERENCES

Anastasios N Angelopoulos, Stephen Bates, Clara Fannjiang, Michael I Jordan, and Tijana Zrnic. Prediction-powered inference. *Science*, 382(6671):669–674, 2023a.

Anastasios N Angelopoulos, John C Duchi, and Tijana Zrnic. Ppi++: Efficient prediction-powered inference. *arXiv preprint arXiv:2311.01453*, 2023b.

Tongtong Bai, Yifan Bai, Yiping Bao, Jianfeng Cai, Xinyuan Cai, Peizhou Cao, Yuxuan Cao, Ziwei Chai, Y Charles, et al. Kimi k3: Open frontier intelligence. *arXiv preprint arXiv:2607.24653*, 2026.

Sourav Banerjee, Ayushi Agarwal, and Eishkaran Singh. The vulnerability of language model benchmarks: Do they accurately reflect true llm performance? *arXiv preprint arXiv:2412.03597*, 2024.

Guiming Chen, Shunian Chen, Ziche Liu, Feng Jiang, and Benyou Wang. Humans or llms as the judge? a study on judgement bias. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pp. 8301–8327, 2024.

Luyu Chen, Zeyu Zhang, Haoran Tan, Quanyu Dai, Hao Yang, Zhenhua Dong, and Xu Chen. Distributional LLM-as-a-judge. In *Proceedings of Conference on Neural Information Processing Systems*, 2025.

Mark Chen. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

Yiqun T Chen, Sizhu Lu, Sijia Li, Moran Guo, and Shengyi Li. Efficient inference for noisy llm-as-a-judge evaluation. *arXiv preprint arXiv:2601.05420*, 2026.

Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios N. Angelopoulos, Tianle Li, Dacheng Li, Banghua Zhu, Hao Zhang, Michael I. Jordan, Joseph E. Gonzalez, and Ion Stoica. Chatbot arena: an open platform for evaluating llms by human preference. In *Proceedings of the International Conference on Machine Learning*, 2024.

Cjadams, Sorensen Jeffrey, Elliott Julia, Dixon Lucas, McDonald Mark, Nithum, and Cukierski Will. Toxic comment classification challenge. `https://kaggle.com/competitions/jigsaw-toxic-comment-classification-challenge`, 2017.

Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Bingxiang He, Wei Zhu, Yuan Ni, Guotong Xie, Ruobing Xie, Yankai Lin, et al. Ultrafeedback: Boosting language models with scaled ai feedback. *arXiv preprint arXiv:2310.01377*, 2023.

Thomas Davidson, Dana Warmsley, Michael Macy, and Ingmar Weber. Automated hate speech detection and the problem of offensive language. In *Proceedings of the International AAAI Conference on Web and Social Media*, pp. 512–515, 2017.

Boyuan Deng, Shuyi Fan, Hongyang Zhang, and Xinhong Xie. Jev for scientific decisions: Evaluating semantic choices and their consequences. *arXiv preprint arXiv:2609.24965*, 2026.

Florian Eddie Dorner, Vivian Nastl, and Moritz Hardt. Limits to scalable evaluation at the frontier: Llm as judge won't beat twice the data. In *Proceedings of International Conference on Learning Representations*, volume 2025, pp. 26467–26491, 2025.

Yann Dubois, Xuechen Li, Rohan Taori, Tianyi Zhang, Ishaan Gulrajani, Jimmy Ba, Carlos Guestrin, Percy Liang, and Tatsunori Hashimoto. Alpacafarm: A simulation framework for methods that learn from human feedback. In *Proceedings of Conference on Neural Information Processing Systems*, 2023.

Benjamin Eyre and David Madras. Auto-evaluation with few labels through post-hoc regression. *arXiv preprint arXiv:2411.12665*, 2024.

Chen Feng, Minghe Shen, Ananth Balashankar, Carsten Gerner-Beuerle, and Miguel R. D. Rodrigues. Noisy but valid: Robust statistical evaluation of LLMs with imperfect judges. In *Proceedings of International Conference on Learning Representations*, 2026.

Adam Fisch, Joshua Maynez, R. Alex Hofer, Bhuwan Dhingra, Amir Globerson, and William W. Cohen. Stratified prediction-powered inference for effective hybrid evaluation of language models. In *Proceedings of Conference on Neural Information Processing Systems*, 2024.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Luke Guerdan, Solon Barocas, Ken Holstein, Hanna Wallach, Steven Wu, and Alexandra Chouldechova. Validating LLM-as-a-judge systems under rating indeterminacy. In *Proceedings of Conference on Neural Information Processing Systems*, 2025.

Zara Hall, Melanie Subbiah, Thomas P Zollo, Kathleen McKeown, and Richard Zemel. Guiding LLM decision-making with fairness reward models. In *Proceedings of Conference on Neural Information Processing Systems*, 2025.

Steve Han, Gilberto Titericz Junior, Tom Balough, and Wenfei Zhou. Judge's verdict: A comprehensive analysis of llm judge capability through human agreement. *arXiv preprint arXiv:2510.09738*, 2025.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*, 2020.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, et al. Mistral 7b, 2023.

Nathan Lambert, Valentina Pyatkin, Jacob Morrison, LJ Miranda, Bill Yuchen Lin, Khyathi Chandu, Nouha Dziri, Sachin Kumar, Tom Zick, Yejin Choi, et al. Rewardbench: Evaluating reward models for language modeling. In *Findings of the Association for Computational Linguistics*, pp. 1755–1797, 2025.

Chungpa Lee, Thomas Zeng, Jongwon Jeong, Jy-yong Sohn, and Kangwook Lee. How to correctly report llm-as-a-judge evaluations. *arXiv preprint arXiv:2511.21140*, 2025.

Dawei Li, Bohan Jiang, Liangjie Huang, Alimohammad Beigi, Chengshuai Zhao, Zhen Tan, Amrita Bhattacharjee, Yuxuan Jiang, Canyu Chen, Tianhao Wu, et al. From generation to judgment: Opportunities and challenges of llm-as-a-judge. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pp. 2757–2791, 2025.

Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, et al. Holistic evaluation of language models. *arXiv preprint arXiv:2211.09110*, 2022.

Yuhao Liu, Liang Zeng, Yuzhen Xiao, Jujie He, Jiacai Liu, Chaojie Wang, Rui Yan, Wei Shen, Fuxiang Zhang, Jiacheng Xu, et al. Skywork-reward-v2: Scaling preference data curation via human-ai synergy. In *Proceedings of International Conference on Learning Representations*, volume 2026, pp. 133805–133838, 2026.

Qwen, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, et al. Qwen2.5 technical report, 2025.

Minghe Shen, Ananth Balashankar, Adam Fisch, David Madras, and Miguel Rodrigues. Robust llm performance certification via constrained maximum likelihood estimation. *arXiv preprint arXiv:2604.03257*, 2026.

Gaurang Sriramanan, Siddhant Bharti, Vinu Sankar Sadasivan, Shoumik Saha, Priyatham Kattakinda, and Soheil Feizi. LLM-check: Investigating detection of hallucinations in large language models. In *Proceedings of Conference on Neural Information Processing Systems*, 2024.

Joshua Vendrow, Edward Vendrow, Sara Beery, and Aleksander Madry. Large language model benchmarks do not test reliability. In *Proceedings of NeurIPS Safe Generative AI Workshop*, 2024.

Peiyi Wang, Lei Li, Liang Chen, Zefan Cai, Dawei Zhu, Binghuai Lin, Yunbo Cao, Lingpeng Kong, Qi Liu, Tianyu Liu, et al. Large language models are not fair evaluators. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9440–9450, 2024a.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, et al. Mmlu-pro: A more robust and challenging multi-task language understanding benchmark. In *Proceedings of Conference on Neural Information Processing Systems*, pp. 95266–95290, 2024b.

Shengwei Xu, Yuxuan Lu, Grant Schoenebeck, and Yuqing Kong. Benchmarking LLMs' judgments with no gold standard. In *Proceedings of International Conference on Learning Representations*, 2025.

Prateek Yadav, Derek Tam, Leshem Choshen, Colin A Raffel, and Mohit Bansal. Ties-merging: Resolving interference when merging models. In *Proceedings of Conference on Neural Information Processing Systems*, pp. 7093–7115, 2023.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Fan Yin, Philippe Laban, Xiangyu Peng, Yilun Zhou, Yixin Mao, Vaibhav Vats, Linnea Ross, Divyansh Agarwal, Caiming Xiong, and Chien-Sheng Wu. Bingoguard: LLM content moderation tools with risk levels. In *Proceedings of International Conference on Learning Representations*, 2025.

Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. How transferable are features in deep neural networks? In *Proceedings of Conference on Neural Information Processing Systems*, 2014.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging llm-as-a-judge with mt-bench and chatbot arena. In *Proceedings of the International Conference on Neural Information Processing Systems*, 2023.

Hanzhang Zhou, Zijian Feng, Zixiao Zhu, Junlang Qian, and Kezhi Mao. Unibias: Unveiling and mitigating LLM bias through internal attention and FFN manipulation. In *Proceedings of Conference on Neural Information Processing Systems*, 2024.

Runjia Zou, Daniela Witten, and Brian Williamson. Generalized prediction-powered inference, with application to binary classifier evaluation. *arXiv preprint arXiv:2602.10332*, 2026.

A Limitations and Future Work

Severe source–target shifts can still introduce transfer bias when target labels are too sparse to reliably detect mismatches in judge reliability. Although target-guided filtering and adaptive weighting are designed to reduce the influence of poorly aligned source information, their effectiveness still depends on having sufficient target evidence to identify source–target discrepancies. In extremely low-supervision regimes, inaccurate estimates of target TPR and FPR may lead to imperfect weighting, allowing residual mismatch to affect the final failure-rate estimate. Future work will therefore investigate more sensitivity-aware weighting strategies and stronger criteria for suppressing source contributions when the available target evidence provides limited support for reliable transfer.

Another limitation is that TRUST currently treats judge reliability through semantic-confidence regions defined over the observed prompt–response space. More complex model architectures may induce additional variation in judge behavior that is not fully captured by these regions. In particular, extending TRUST to mixture-of-experts (MoE) models is a promising direction, since routing-dependent model behavior may lead to finer-grained differences in TPR and FPR across examples. Incorporating such variation could enable more localized reliability transfer while preserving the same principle of transferring judge behavior rather than source failure rates.

B LLM Usage Statement

Large language models, such as ChatGPT, were used as general-purpose assistive tools during the preparation of this paper. Specifically, LLMs were employed for language refinement, improving and revising the clarity of the manuscript. No part of the research ideation, experimental design, or core scientific contributions relied on LLMs. All scientific content, results, and conclusions were generated and verified by the authors. The authors take full responsibility for the content of this paper, including any text generated with the assistance of LLMs.

C Ethics Statement

This work contributes to AI safety by providing a statistical framework for certifying LLM reliability. Our empirical validation relies on established public datasets that contain toxic and offensive language; these are used solely for scientific validation, and reader discretion is advised for the examples. Any biases present in the human annotations are inherent to the certification, and statistical validity should not be conflated with objective moral correctness. No new human subjects were recruited for this study. We caution practitioners against over-reliance on statistical certificates in high-stakes settings without complementary safeguards.

D Compute Resources Statement

All experiments were conducted on an internal compute cluster. Each compute node was equipped with two Intel Xeon Gold 6248 CPUs running at 2.50 GHz, providing 40 physical CPU cores and 80 CPU threads in total. Each node also contained 10 NVIDIA Tesla V100 PCIe GPUs, each with 32 GB of GPU memory. Across all experiments reported in the paper, we performed 11 GPU-based experimental runs (LLM inference). The total compute required for the reported experiments was approximately 24 GPU-hours and 48 CPU core-hours.

E Detailed Related Work

E.1 LLM Evaluation Paradigms

Standardized benchmarks provide a scalable and reproducible basis for comparing LLMs across diverse tasks (Hendrycks et al., 2020; Liang et al., 2022; Grattafiori et al., 2024; Jiang et al., 2023; Qwen et al., 2025). Notably, in domains with objectively verifiable outcomes, evaluation can often rely on deterministic or programmatic correctness signals. For example, mathematical problems can be evaluated against known answers, while generated code can be assessed through execution

against test cases (Chen, 2021). Such verifiable evaluation provides scalable and relatively unambiguous feedback without requiring human judgments for every example. However, many important LLM capabilities involve criteria that are not readily reducible to a unique verifiable outcome, including helpfulness, preference, safety, and socially or contextually dependent judgments. Therefore, these more ambiguous settings often require human- or expert-annotated reference labels (Han et al., 2025; Xu et al., 2025). Their reliability can nevertheless be compromised by data contamination, annotation noise, and adaptive over-optimization (Banerjee et al., 2024; Vendrow et al., 2024). Moreover, obtaining high-quality human annotations at the scale required for modern LLM evaluation remains costly (Han et al., 2025; Xu et al., 2025).

In turn, many evaluation pipelines now incorporate the "LLM-as-a-Judge" paradigm to reduce this annotation burden (Dubois et al., 2023; Wang et al., 2024a; Chen et al., 2025; Guerdan et al., 2025). LLM judges enable scalable evaluation in settings where correctness cannot be directly or completely verified, but their predictions may be noisy, biased, prompt-sensitive, and task-dependent (Sriramanan et al., 2024; Zhou et al., 2024). Practical pipelines therefore often combine a small human-labeled target set with a much larger set of judge-only predictions (Chen et al., 2024; Li et al., 2025; Shen et al., 2026). However, these approaches may be insufficient to reliably characterize judge behavior and support accurate failure-rate estimation when target benchmark human labels are extremely scarce. Our work builds on this setting, focusing on how to improve failure-rate estimation when target human supervision is too sparse to reliably calibrate the judge on its own.

E.2 Statistical Frameworks for Noisy LLM Evaluation

Statistical methods for LLM evaluation under noisy judge supervision can be broadly classified according to whether they explicitly model the judge's error mechanism. We review these two families and then discuss how our work relates to transfer learning.

Approaches without explicit judge error modeling. One family uses judge outputs as auxiliary predictors or control variates without explicitly modeling the underlying error process. Prediction-powered inference (PPI) and its extensions, including PPI++ and Ridge PPI, combine a small gold-standard set with a large set of model predictions to reduce estimation variance (Angelopoulos et al., 2023a;b; Eyre & Madras, 2024). An efficient influence function (EIF) analysis provides a unified semiparametric perspective and establishes that optimally tuned PPI++ is asymptotically equivalent to the EIF-based efficient estimator in the binary setting (Chen et al., 2026). StratPPI further stratifies target samples by judge confidence to account for variation in reliability across confidence levels (Fisch et al., 2024). These approaches can effectively exploit large amounts of judge-only data, but their gains can become limited when the available human-labeled target set is extremely small.

PPI under covariate shift also combines labeled source observations with an unlabeled target population, reweighting the source observations toward the target covariate distribution (Zou et al., 2026). TRUST instead transfers the judge's local TPR and FPR while keeping the target failure rate anchored to target observations. Accordingly, its adaptive transfer weights control the contribution of source reliability information and are not covariate density-ratio weights.

Approaches with explicit judge error modeling. A second family explicitly models judge errors through TPR and FPR. Likelihood-based methods jointly estimate the target failure rate and the judge's TPR and FPR. Unconstrained maximum likelihood estimation (UMLE) directly estimates these parameters without additional constraints, whereas constrained maximum likelihood estimation (CMLE) imposes data-driven interval constraints on TPR and FPR to regularize estimation and reduce variance when gold labels are limited (Chen et al., 2026; Shen et al., 2026). Rogan–Gladen corrections adjust observed judge-positive rates using plug-in estimates of TPR and FPR (Lee et al., 2025). Noisy hypothesis testing frameworks formulate evaluation under imperfect labels as a testing problem and provide corrections or guarantees based on estimated judge behavior (Feng et al., 2026). Recent work has also studied fundamental limits of LLM evaluation with imperfect judges, showing that the benefit of judge-assisted evaluation can be limited when only sparse ground-truth supervision is available (Dorner et al., 2025). These results further highlight the difficulty of reliable estimation in low-label regimes.

Both families can therefore become unreliable when target human labels are extremely scarce. Our work addresses this limitation by transferring judge reliability information from auxiliary source tasks while keeping target failure-rate estimation anchored to target supervision. Rather than transferring the source failure rate itself, TRUST transfers TPR and FPR, allowing source information to improve estimation while the target failure rate remains target-specific. This supports more stable estimation in regimes where target-only methods can exhibit large MSE.

Relation to transfer learning. Our work is also related to transfer learning but differs in both the object and the mechanism of transfer. Classical transfer learning typically transfers learned representations, model parameters, or task priors across domains (Yosinski et al., 2014; Yadav et al., 2023; Wang et al., 2024a). TRUST instead transfers judge behavior, represented by bin-wise TPR and FPR, from auxiliary source benchmarks to the target benchmark. Importantly, the target failure rate is not transferred and continues to be estimated from target supervision. This distinction allows TRUST to exploit source information about judge reliability without assuming that the source and target benchmarks share the same failure rate.

F Experimental Details

Sampling and data splits. Unless otherwise specified, we use the following experimental protocol throughout all experiments. We vary the number of human-labeled target samples as $N_M \in \{50, 60, 70, 80, 90, 100\}$ and fix the number of additional judge-only target draws at $N_J = 20{,}000$. Thus, each target configuration contains $N_J + N_M$ sampled observations in total. Every baseline that uses judge-only target data uses all $N_J = 20{,}000$ such observations; Gold-only does not use them. When an available benchmark pool is smaller than a requested sample count, we sample independently with replacement from that pool. Consequently, N_J denotes the number of draws and not necessarily the number of unique benchmark examples. Each configuration is evaluated over 1,000 independent random replications, and we use at most $20{,}000$ draws from each source benchmark.

For TRUST and its variants, we separate Stage 1 construction from likelihood estimation by randomly partitioning the source labeled draws and target judge-only draws into two disjoint subsets of equal size, one for construction and the other for estimation. Let N_J^{con} and N_J^{est} denote the corresponding judge-only sample sizes, so that $N_J = N_J^{\mathrm{con}} + N_J^{\mathrm{est}}$ and $N_J^{\mathrm{con}} = N_J^{\mathrm{est}} = N_J/2 = 10{,}000$. Source construction samples define the semantic-confidence partition, while held-out source samples are assigned to that partition and screened by the target-guided filtering rule before entering the reliability likelihood. Target judge-only construction samples form the target references used for assignment and filtering, whereas the target judge-only estimation samples enter the likelihood. The human-labeled target data are not split and are used exclusively for likelihood estimation. Hence, TRUST and the judge-based baselines receive the same total judge-only target budget, while allocating it according to their respective procedures.

Task-specific judge decisions. On classification tasks, the judge first determines the appropriate task label and compares it with the target model's prediction; on preference tasks, it evaluates whether the target model selected the best response. The resulting comparison is mapped to the common binary failure scale defined in Section 3. Qwen3-8B produces this decision through its output-token logits, whereas Skywork-Reward-V2-Qwen3-8B scores the two permitted decision responses separately and selects the response with the larger sequence-level reward.

Prompt-response semantic representation and judge confidence. For semantic representation, we use Qwen3-Embedding-8B to extract an embedding for each prompt-response pair, using the model's default output dimensionality without dimensionality reduction. All embeddings are ℓ_2-normalized before semantic clustering and similarity computation.

For Qwen3-8B, let $z_{i,0}$ and $z_{i,1}$ be the output-token logits for the two permitted binary decisions. We compute the restricted two-class softmax

$$p_{i,y}^{\mathrm{LLM}} = \frac{\exp(z_{i,y})}{\exp(z_{i,0}) + \exp(z_{i,1})}, \qquad y \in \{0, 1\}. \tag{23}$$

Skywork-Reward-V2-Qwen3-8B instead produces one scalar sequence-level reward for each complete prompt–response pair. We therefore append each permitted decision response $y \in \{0, 1\}$ to

the same judge input and score the two resulting sequences separately. Let $r_{i,y}$ denote the reward assigned to the sequence ending in decision y. We normalize the two reward scores as

$$p_{i,y}^{\mathrm{RM}} = \frac{\exp(r_{i,y})}{\exp(r_{i,0}) + \exp(r_{i,1})}, \qquad y \in \{0,1\}. \tag{24}$$

Thus, although both constructions yield two normalized decision scores, the inputs to the normalization differ: Qwen3-8B uses token-level generation logits, whereas Skywork uses rewards from two separately scored sequences. Let $p_{i,y}$ denote the corresponding normalized score for the judge being used. We define

$$S_{J,i} = \arg\max_{y\in\{0,1\}} p_{i,y}, \qquad c_i = \max_{y\in\{0,1\}} p_{i,y} \in [0.5, 1]. \tag{25}$$

The quantity c_i is used as a relative confidence score for stratification and filtering; we do not assume that it is a calibrated probability of judge correctness.

Semantic-confidence partition. In the default configuration used for the main experiments, TRUST partitions the source construction samples into $K = 3$ semantic clusters using k-means. Within each semantic cluster, the judge confidence scores are further divided into $R = 3$ approximately equal-frequency strata using empirical quantiles, resulting in $K \times R = 9$ semantic-confidence bins. Target and held-out source samples are subsequently assigned to this fixed source-defined partition. TRUST+ uses the same values of K and R, but constructs one common partition from the pooled construction samples of all auxiliary sources. Alternative partition configurations are examined in Appendix I.

Target-guided filtering. For target-guided filtering, we compute the embedding similarity and judge-confidence discrepancy between each source sample and the corresponding target reference within the same bin. With the default filtering fraction $\tau = 0.75$, we identify the lowest 75% of source samples by embedding similarity and the highest 75% by confidence discrepancy within each bin. We remove a source sample only when it belongs to both sets. Thus, 75% specifies the size of each tail set, not the overall fraction removed.

Likelihood optimization. Within each semantic-confidence bin b, the target failure rate and judge reliability parameters are estimated by maximizing the joint likelihood under the constraints $0 < \theta_b < 1$ and $0 < \mathrm{FPR}_{T,b} < \mathrm{TPR}_{T,b} < 1$. We solve the resulting constrained optimization problem using gradient ascent with a maximum of $2{,}000$ iterations and an optimization tolerance of 10^{-9}. To avoid numerical boundary issues, all parameters are restricted to $[\epsilon, 1-\epsilon]$ with $\epsilon = 10^{-6}$, together with the constraint $\mathrm{TPR}_{T,b} - \mathrm{FPR}_{T,b} \geq 10^{-6}$. Implementation details specific to individual baselines are provided in Appendix G.

G Detailed Description of Baselines and TRUST Variants

We use the datasets and notation defined in Sections 3 and 4, together with the default experimental protocol in Appendix F. For the count-based baselines, recall that n_{uv}^{T} denotes the number of labeled target samples with $S = u$ and $S_J = v$, where $u, v \in \{0,1\}$, while n_1^J and n_0^J denote the numbers of positive and negative judge predictions among all $N_J = 20{,}000$ judge-only target observations. Therefore,

$$N_M = n_{11}^T + n_{10}^T + n_{01}^T + n_{00}^T, \tag{26}$$

and

$$N_J = n_1^J + n_0^J. \tag{27}$$

We use $a = 1, \ldots, \mathcal{A}$ to index auxiliary source benchmarks, k to index semantic clusters, r to index confidence strata, and $b = (k, r)$ to index semantic-confidence bins. The subsections below define the baselines and provide algorithmic descriptions of TRUST, TRUST+, and TRUST-.

G.1 GOLD-ONLY

Gold-only estimates the target failure rate using only the human-labeled target samples. Since $S = 1$ denotes a model failure, its estimate is the empirical failure rate

$$\widehat{\theta}_T^{\text{Gold}} = \frac{n_{11}^T + n_{10}^T}{N_M}. \tag{28}$$

Gold-only does not use the judge-only target data. Consequently, while the estimator is directly anchored to human annotations, its variance can be large when N_M is small.

G.2 JUDGE-ONLY

Judge-only estimates the target failure rate by using the judge predictions. In particular, its estimate is given by:

$$\widehat{\theta}_T^{\text{Judge}} = \frac{n_1^J}{N_J}. \tag{29}$$

This estimator uses the large judge-only sample but does not correct for judge errors. In particular, the marginal judge-positive probability satisfies

$$p = \Pr_T(S_J = 1) = \theta_T \,\text{TPR}_T + (1 - \theta_T)\,\text{FPR}_T\,. \tag{30}$$

Therefore, Judge-only estimates the marginal judge-positive rate rather than the target failure rate itself whenever the judge is imperfect.

G.3 PPI++

We adopt the PPI++ implementation of the corresponding reference (Angelopoulos et al., 2023b). PPI++ treats the judge prediction as an auxiliary predictor rather than explicitly modeling its TPR and FPR. In our setting, the target quantity is the binary failure probability

$$\theta_T = \mathbb{E}_T[S]. \tag{31}$$

The empirical human failure rate on the labeled target set is

$$\frac{n_{11}^T + n_{10}^T}{N_M}, \tag{32}$$

while the empirical judge-positive rate on the same labeled target set is

$$\frac{n_{11}^T + n_{01}^T}{N_M}. \tag{33}$$

The corresponding judge-positive rate on the full judge-only target set is

$$\frac{n_1^J}{N_J}. \tag{34}$$

Applying the PPI++ mean estimator with the human failure indicator S as the outcome and the judge prediction S_J as the auxiliary predictor gives

$$\widehat{\theta}_T^{\text{PPI++}} = \frac{n_{11}^T + n_{10}^T}{N_M} + \widehat{\lambda}\left(\frac{n_1^J}{N_J} - \frac{n_{11}^T + n_{01}^T}{N_M}\right), \tag{35}$$

where $\widehat{\lambda}$ is the data-dependent tuning parameter estimated by PPI++. The first term is the Gold-only estimate, while the second term uses the difference between the judge-positive rates in the judge-only and human-labeled target sets as a control-variate correction. When $\widehat{\lambda} = 0$, PPI++ reduces to Gold-only. When $\widehat{\lambda} = 1$, it reduces to the corresponding untuned PPI estimator. In our experiments, $\widehat{\lambda}$ is obtained using the tuning procedure of the original PPI++ implementation.

G.4 StratPPI

We adopt the StratPPI implementation of the corresponding reference (Fisch et al., 2024). StratPPI extends prediction-powered inference by accounting for heterogeneity in judge quality across confidence levels. Rather than applying a single global correction as in PPI++, StratPPI partitions the target data into confidence strata and performs prediction-powered estimation within each stratum.

Let $n^T_{uv,r}$ denote the labeled count with $S = u$ and $S_J = v$ within confidence stratum r, and let $n^J_{1,r}$ and $n^J_{0,r}$ denote the positive and negative judge-prediction counts from the full judge-only target set within stratum r. StratPPI therefore uses all $N_J = 20{,}000$ judge-only target observations. Define

$$N_{M,r} = \sum_{u,v\in\{0,1\}} n^T_{uv,r}, \tag{36}$$

and

$$N_{J,r} = n^J_{1,r} + n^J_{0,r}. \tag{37}$$

We use r rather than b here because StratPPI partitions only by confidence, whereas TRUST uses semantic–confidence bins $b = (k, r)$.

The stratum-specific estimate is

$$\widehat{\theta}^{\mathrm{StratPPI}}_r = \frac{n^T_{11,r} + n^T_{10,r}}{N_{M,r}} + \widehat{\lambda}_r \left(\frac{n^J_{1,r}}{N_{J,r}} - \frac{n^T_{11,r} + n^T_{01,r}}{N_{M,r}} \right), \tag{38}$$

where $\widehat{\lambda}_r$ is the PPI++ tuning parameter for confidence stratum r. The overall estimate is obtained by aggregating the stratum-specific estimates according to the empirical target distribution:

$$\widehat{\theta}^{\mathrm{StratPPI}}_T = \sum_r \widehat{w}_r \widehat{\theta}^{\mathrm{StratPPI}}_r, \tag{39}$$

where $\widehat{w}_r$ denotes the fraction of target samples assigned to confidence stratum r, computed from the same labeled and judge-only target observations:

$$\widehat{w}_r = \frac{N_{M,r} + N_{J,r}}{N_M + N_J}. \tag{40}$$

Thus, PPI++ uses a single global control-variate correction, whereas StratPPI allows the correction strength to vary across confidence levels. Neither method explicitly models the judge's TPR and FPR or uses auxiliary source benchmarks to estimate judge reliability.

G.5 Rogan–Gladen

Rogan–Gladen (RG) explicitly corrects the observed judge-positive rate using plug-in estimates of the target judge TPR and FPR. Because RG is applied globally rather than bin-wise, TPR_T and FPR_T in this subsection denote target-wide reliability parameters. Recall that

$$p = \theta_T \,\mathrm{TPR}_T + (1 - \theta_T)\,\mathrm{FPR}_T\,. \tag{41}$$

Solving for θ_T gives

$$\theta_T = \frac{p - \mathrm{FPR}_T}{\mathrm{TPR}_T - \mathrm{FPR}_T}. \tag{42}$$

The marginal judge-positive probability is estimated from the judge-only target data as

$$\widehat{p} = \frac{n^J_1}{n^J_1 + n^J_0}. \tag{43}$$

The target judge TPR and FPR are estimated from the human-labeled target data as

$$\widehat{\mathrm{TPR}}^{\mathrm{RG}}_T = \frac{n^T_{11}}{n^T_{11} + n^T_{10}}, \qquad \widehat{\mathrm{FPR}}^{\mathrm{RG}}_T = \frac{n^T_{01}}{n^T_{01} + n^T_{00}}. \tag{44}$$

The resulting RG estimator is

$$\widehat{\theta}_T^{\mathrm{RG}} = \frac{\widehat{p} - \widehat{\mathrm{FPR}}_T^{\mathrm{RG}}}{\widehat{\mathrm{TPR}}_T^{\mathrm{RG}} - \widehat{\mathrm{FPR}}_T^{\mathrm{RG}}}. \tag{45}$$

RG therefore explicitly accounts for judge errors, but estimates the reliability parameters using only the limited human-labeled target set and subsequently plugs them into the correction formula. In contrast, TRUST jointly estimates the target failure rate and judge reliability and additionally transfers source reliability information.

G.6 CMLE

We adopt the CMLE estimator of Shen et al. (2026). CMLE explicitly models the target failure rate together with the target judge TPR and FPR using the labeled and judge-only target data. As with RG, θ_T, TPR_T, and FPR_T in this subsection are target-wide parameters because CMLE is applied globally. Using the notation in Section 4.2 and the notation laid out at the beginning of this appendix, the labeled target log-likelihood is

$$\begin{aligned}\ell_M = n_{11}^T \log(\theta_T \,\mathrm{TPR}_T) + n_{10}^T \log[\theta_T(1-\mathrm{TPR}_T)] \\ + n_{01}^T \log[(1-\theta_T)\,\mathrm{FPR}_T] + n_{00}^T \log[(1-\theta_T)(1-\mathrm{FPR}_T)].\end{aligned} \tag{46}$$

For the judge-only target data,

$$p = \theta_T \,\mathrm{TPR}_T + (1-\theta_T)\,\mathrm{FPR}_T, \tag{47}$$

and

$$\ell_J = n_1^J \log p + n_0^J \log(1-p). \tag{48}$$

CMLE uses the target-only likelihood

$$\ell_{\mathrm{CMLE}} = \ell_M + \ell_J. \tag{49}$$

To regularize the estimation of judge reliability under sparse target supervision, our CMLE implementation constrains TPR_T and FPR_T to data-driven intervals constructed from the labeled target observations. Specifically, the plug-in reliability estimates are

$$\widetilde{\mathrm{TPR}}_T = \frac{n_{11}^T}{n_{11}^T + n_{10}^T}, \qquad \widetilde{\mathrm{FPR}}_T = \frac{n_{01}^T}{n_{01}^T + n_{00}^T}. \tag{50}$$

In the default implementation, we construct 75% central posterior credible intervals using independent $\mathrm{Beta}(1,1)$ priors for TPR_T and FPR_T. The corresponding posterior distributions are

$$\mathrm{TPR}_T \mid \mathcal{D}_T^{\mathrm{lab}} \sim \mathrm{Beta}\left(1 + n_{11}^T, 1 + n_{10}^T\right), \tag{51}$$

and

$$\mathrm{FPR}_T \mid \mathcal{D}_T^{\mathrm{lab}} \sim \mathrm{Beta}\left(1 + n_{01}^T, 1 + n_{00}^T\right). \tag{52}$$

Let $\gamma = 0.25$. The resulting reliability intervals are

$$L_{\mathrm{TPR}_T} = F^{-1}_{\mathrm{Beta}(1+n_{11}^T,\, 1+n_{10}^T)}\left(\frac{\gamma}{2}\right), \qquad U_{\mathrm{TPR}_T} = F^{-1}_{\mathrm{Beta}(1+n_{11}^T,\, 1+n_{10}^T)}\left(1-\frac{\gamma}{2}\right), \tag{53}$$

and

$$L_{\mathrm{FPR}_T} = F^{-1}_{\mathrm{Beta}(1+n_{01}^T,\, 1+n_{00}^T)}\left(\frac{\gamma}{2}\right), \qquad U_{\mathrm{FPR}_T} = F^{-1}_{\mathrm{Beta}(1+n_{01}^T,\, 1+n_{00}^T)}\left(1-\frac{\gamma}{2}\right). \tag{54}$$

where $F^{-1}_{\mathrm{Beta}(a,b)}(\cdot)$ denotes the quantile function of the $\mathrm{Beta}(a,b)$ distribution.

The CMLE estimator is then obtained by solving

$$(\widehat{\theta}_T^{\mathrm{CMLE}}, \widehat{\mathrm{TPR}}_T^{\mathrm{CMLE}}, \widehat{\mathrm{FPR}}_T^{\mathrm{CMLE}}) = \arg\max_{\theta_T, \mathrm{TPR}_T, \mathrm{FPR}_T} (\ell_M + \ell_J), \tag{55}$$

subject to

$$0 \le \theta_T \le 1, \qquad L_{\mathrm{TPR}_T} \le \mathrm{TPR}_T \le U_{\mathrm{TPR}_T}, \qquad L_{\mathrm{FPR}_T} \le \mathrm{FPR}_T \le U_{\mathrm{FPR}_T}. \tag{56}$$

These interval constraints reduce the feasible region of the likelihood optimization and regularize the estimation of judge reliability when the labeled target sample is small. CMLE is particularly closely related to TRUST because TRUST extends the same target likelihood with retained source reliability information. Specifically, TRUST augments the CMLE target likelihood as

$$\ell_{\mathrm{TRUST},b} = \ell_{M,b} + \ell_{J,b} + \omega_{\mathrm{TPR},b}\ell_{S,b}^{\mathrm{TPR}} + \omega_{\mathrm{FPR},b}\ell_{S,b}^{\mathrm{FPR}}. \tag{57}$$

Thus, CMLE regularizes judge reliability using only interval-constrained target information, whereas TRUST additionally incorporates adaptively weighted source reliability information to stabilize estimation under sparse target supervision.

G.7 TRUST

TRUST performs single-source judge-reliability transfer in two stages. Stage 1 constructs a source-defined semantic–confidence partition and uses target samples to identify source observations that are locally aligned with the target distribution. Stage 2 combines the labeled target data, judge-only target data, and retained source reliability information through the adaptively weighted likelihood in equation 8. The source data contribute only to the estimation of $\mathrm{TPR}_{T,b}$ and $\mathrm{FPR}_{T,b}$, whereas the target failure rate θ_b remains anchored to the target observations within bin b.

For completeness, fix a semantic–confidence bin b. We retain the bin index on all local parameters, likelihood components, and counts. Let $n_{uv,b}^T$ denote the number of human-labeled target samples in bin b with $S = u$ and $S_J = v$, let $n_{v,b}^J$ denote the number of judge-only target samples in bin b of the estimation split with $S_J = v$, and let $n_{uv,b}^S$ denote the number of retained source samples in bin b of the estimation split with $S = u$ and $S_J = v$, where $u, v \in \{0, 1\}$.

The target count used to estimate the empirical bin proportion is

$$n_b = \sum_{u,v\in\{0,1\}} n_{uv,b}^T + n_{1,b}^J + n_{0,b}^J. \tag{58}$$

The bin-wise TRUST objective is

$$\ell_{\mathrm{TRUST},b} = \ell_{M,b} + \ell_{J,b} + \omega_{\mathrm{TPR},b}\ell_{S,b}^{\mathrm{TPR}} + \omega_{\mathrm{FPR},b}\ell_{S,b}^{\mathrm{FPR}}. \tag{59}$$

The labeled-target contribution is

$$\begin{aligned}\ell_{M,b} = {} & n_{11,b}^T \log(\theta_b \,\mathrm{TPR}_{T,b}) + n_{10,b}^T \log[\theta_b(1 - \mathrm{TPR}_{T,b})] \\ & + n_{01,b}^T \log[(1 - \theta_b)\,\mathrm{FPR}_{T,b}] + n_{00,b}^T \log[(1 - \theta_b)(1 - \mathrm{FPR}_{T,b})].\end{aligned} \tag{60}$$

For the judge-only target samples, define

$$p_b = \theta_b \,\mathrm{TPR}_{T,b} + (1 - \theta_b)\,\mathrm{FPR}_{T,b}\,. \tag{61}$$

The corresponding likelihood contribution is

$$\ell_{J,b} = n_{1,b}^J \log p_b + n_{0,b}^J \log(1 - p_b). \tag{62}$$

The retained source samples contribute only to the judge-reliability parameters through

$$\ell_{S,b}^{\mathrm{TPR}} = n_{11,b}^S \log \mathrm{TPR}_{T,b} + n_{10,b}^S \log(1 - \mathrm{TPR}_{T,b}), \tag{63}$$

and

$$\ell_{S,b}^{\mathrm{FPR}} = n_{01,b}^S \log \mathrm{FPR}_{T,b} + n_{00,b}^S \log(1 - \mathrm{FPR}_{T,b}). \tag{64}$$

The adaptive transfer weights $\omega_{\mathrm{TPR},b}$ and $\omega_{\mathrm{FPR},b}$ are computed according to the source–target reliability agreement and effective sample sizes defined in Section 4.2. Algorithm 1 summarizes the complete procedure without repeating these likelihood expressions.

We use conservative conventions for sparse bins. If a local target reliability rate is undefined, we replace it with the corresponding global target plug-in estimate. If that estimate is also undefined, or the relevant retained-source class is empty, we set the transfer weight to zero. For a zero target rate,

the agreement factor is one only when the source rate is also zero, and zero otherwise. Empty target construction bins receive no source contribution.

For local failure-rate estimation, let $\mathcal{B}_T^+ = \{b : n_b > 0\}$ and define the global human-labeled target fallback as

$$\widehat{\theta}_T^{\mathrm{fb}} = \frac{\sum_{b \in \mathcal{B}_T^+} (n_{11,b}^T + n_{10,b}^T)}{N_M}. \tag{65}$$

Within each $b \in \mathcal{B}_T^+$, we use the bin-wise estimate when the constrained optimization returns a finite solution satisfying the parameter constraints; otherwise, we set $\widehat{\theta}_b = \widehat{\theta}_T^{\mathrm{fb}}$. The same fallback rule is used for TRUST+ and TRUST-.

G.8 TRUST+

TRUST+ extends TRUST from single-source to multi-source reliability transfer. Given multiple auxiliary source benchmarks, TRUST+ constructs one shared semantic-confidence partition from their pooled construction samples. Target samples and the estimation samples from every source are assigned to this common partition. Within each shared bin, TRUST+ then applies target-guided filtering and adaptive weighting separately to each source and combines their retained reliability information in a single joint likelihood.

For completeness, fix a shared semantic-confidence bin b. As in TRUST, we retain the bin index on local parameters and likelihood components. The labeled and judge-only target likelihood contributions, $\ell_{M,b}$ and $\ell_{J,b}$, are shared across all auxiliary sources, while each source contributes its own TPR and FPR likelihood terms. The resulting bin-wise TRUST+ objective is

$$\ell_{\mathrm{TRUST+},b} = \ell_{M,b} + \ell_{J,b} + \sum_{a=1}^{\mathcal{A}} \left(\omega_{\mathrm{TPR},a,b} \ell_{S_a,b}^{\mathrm{TPR}} + \omega_{\mathrm{FPR},a,b} \ell_{S_a,b}^{\mathrm{FPR}} \right), \tag{66}$$

where $\mathcal{A}$ denotes the number of auxiliary source benchmarks. For each source a, $\ell_{S_a,b}^{\mathrm{TPR}}$ and $\ell_{S_a,b}^{\mathrm{FPR}}$ are defined analogously to the corresponding source reliability terms in TRUST using the retained cell counts $n_{uv,b}^{S_a}$ from source a in the current bin.

For source a in bin b, define $\boldsymbol{\omega}_{a,b} = (\omega_{\mathrm{TPR},a,b}, \omega_{\mathrm{FPR},a,b}) = \boldsymbol{\alpha}_{a,b} \odot \boldsymbol{\kappa}_{a,b}$. These source-specific weights are computed independently using the same reliability-agreement and effective-sample-size weighting rule as in TRUST. Thus, sources that are better aligned with the target judge behavior in the current bin receive larger contributions, while poorly aligned sources are downweighted. The target likelihood terms remain unweighted and common to all sources.

Because all sources and target samples are assigned to the same source-pooled semantic-confidence partition, the fixed bin corresponds to the same local region across auxiliary sources. After maximizing the objective within each nonempty target bin, the resulting local estimates are aggregated using the empirical target bin proportions, as in TRUST.

G.9 TRUST-

TRUST- is designed to examine whether transferring the source failure rate is preferable to transferring judge reliability. It uses the same semantic-confidence partition and target-guided source filtering as TRUST, but replaces the source TPR/FPR likelihood terms with a source likelihood on θ_b. The judge reliability parameters $\mathrm{TPR}_{T,b}$ and $\mathrm{FPR}_{T,b}$ are therefore estimated from target information rather than transferred from the source. We emphasize that TRUST- represents one specific instantiation of source-to-target failure-rate transfer rather than an exhaustive characterization of all possible approaches.

For completeness, fix a semantic–confidence bin b. As in TRUST, we retain the bin index on local parameters and likelihood components. The retained source samples contribute information about the failure rate through

$$\ell_{S,b}^{\theta} = (n_{11,b}^S + n_{10,b}^S) \log \theta_b + (n_{01,b}^S + n_{00,b}^S) \log(1 - \theta_b), \tag{67}$$

where $n_{11,b}^S + n_{10,b}^S$ and $n_{01,b}^S + n_{00,b}^S$ are the numbers of failures and non-failures, respectively, among the retained source samples in the current bin. TRUST- then maximizes

$$\ell_{\mathrm{TRUST}-,b} = \ell_{M,b} + \ell_{J,b} + \omega_{\theta,b} \ell_{S,b}^{\theta}. \tag{68}$$

Algorithm 1 TRUST

Input: Source labeled data, target labeled data $\mathcal{D}_T^{\mathrm{lab}}$, target judge-only data $\mathcal{D}_T^{\mathrm{jud}}$, number of semantic clusters K, confidence strata R, and filtering fraction τ.

Output: Target failure-rate estimate $\widehat{\theta}_T$.

Split the source labeled data and target judge-only data into disjoint construction and estimation sets; use all human-labeled target data only for likelihood estimation.

Stage 1: Source–target alignment

Apply k-means to the source construction embeddings $\{\mathbf{e}_i\}$ to obtain $\{\boldsymbol{\mu}_k\}_{k=1}^K$.

Within each semantic cluster, partition the source confidence scores into R approximately equal-frequency intervals, forming bins $b = (k, r)$.

Assign the target judge-only construction samples, target estimation samples, and source estimation samples to the fixed source-defined semantic–confidence partition.

for each bin b **do**

Let $\mathcal{T}_b$ denote the target judge-only construction samples assigned to bin b.

if $\mathcal{T}_b$ is empty **then**

Set the retained source set $\widetilde{\mathcal{I}}_b = \varnothing$ and continue to the next bin.

end if

Using the target construction samples $\mathcal{T}_b$, compute

$$\bar{\mathbf{e}}_b = |\mathcal{T}_b|^{-1} \sum_{j \in \mathcal{T}_b} \mathbf{e}_j, \qquad \tilde{c}_b = \mathrm{median}\{c_j\}_{j \in \mathcal{T}_b}.$$

For each source estimation sample i assigned to b, compute its cosine similarity to $\bar{\mathbf{e}}_b$ and

$$\Delta_i = |c_i - \tilde{c}_b|.$$

With filtering fraction τ, identify the lowest τ fraction by embedding similarity and the highest τ fraction by confidence discrepancy. Remove the source samples lying in the intersection of these two sets and retain all remaining samples in $\widetilde{\mathcal{I}}_b$.

end for

Stage 2: Adaptive weighted likelihood

Let n_b denote the number of human-labeled target samples and judge-only target estimation samples assigned to bin b, used to estimate the empirical target bin proportions.

Let $\mathcal{B}_T^+ = \{b : n_b > 0\}$ and compute the global human-labeled fallback $\widehat{\theta}_T^{\mathrm{fb}}$ defined in Section 4.2.

for each bin $b \in \mathcal{B}_T^+$ **do**

Using the retained source samples $\widetilde{\mathcal{I}}_b$ and the labeled target samples in the current bin, compute the adaptive transfer weights $\omega_{\mathrm{TPR},b}$ and $\omega_{\mathrm{FPR},b}$ according to Section 4.2.

Maximize the bin-wise objective $\ell_{\mathrm{TRUST},b}$ over $(\theta_b, \mathrm{TPR}_{T,b}, \mathrm{FPR}_{T,b})$.

if the optimization returns a finite solution satisfying the parameter constraints **then**

Store its failure-rate component as $\widehat{\theta}_b$.

else

Set $\widehat{\theta}_b = \widehat{\theta}_T^{\mathrm{fb}}$.

end if

end for

return

$$\widehat{\theta}_T = \sum_{b \in \mathcal{B}_T^+} \widehat{w}_b \widehat{\theta}_b, \qquad \widehat{w}_b = \frac{n_b}{\sum_{b' \in \mathcal{B}_T^+} n_{b'}}.$$

Unlike TRUST, which transfers source information through the judge-reliability parameters $\mathrm{TPR}_{T,b}$ and $\mathrm{FPR}_{T,b}$, TRUST- directly encourages the target failure-rate parameter θ_b to agree with the

failure prevalence observed in the retained source samples. The strength of this contribution is controlled by an adaptive transfer weight $\omega_{\theta,b}$.

The source contribution is adaptively weighted. Using the filtered source failure rate and the labeled target failure rate,

$$\widehat{\theta}_{S,b} = \frac{n^S_{11,b} + n^S_{10,b}}{n^S_{11,b} + n^S_{10,b} + n^S_{01,b} + n^S_{00,b}}, \qquad \widehat{\theta}_{T,b} = \frac{n^T_{11,b} + n^T_{10,b}}{n^T_{11,b} + n^T_{10,b} + n^T_{01,b} + n^T_{00,b}}, \tag{69}$$

the compatibility weight is

$$\alpha_{\theta,b} = \mathrm{clip}\left(1 - \frac{\left|\widehat{\theta}_{S,b} - \widehat{\theta}_{T,b}\right|}{\widehat{\theta}_{T,b}}, 0, 1\right), \tag{70}$$

and the final transfer weight is

$$\omega_{\theta,b} = \alpha_{\theta,b} \min\left(1, \frac{N_{M,b}}{N_{S,b}}\right). \tag{71}$$

Here $N_{M,b} = n^T_{11,b} + n^T_{10,b} + n^T_{01,b} + n^T_{00,b}$ and $N_{S,b} = n^S_{11,b} + n^S_{10,b} + n^S_{01,b} + n^S_{00,b}$.

We use conservative conventions for sparse bins, analogous to those used for TRUST. If $N_{M,b} = 0$, we replace the undefined local target plug-in rate $\widehat{\theta}_{T,b}$ with the global human-labeled target rate $\widehat{\theta}^{\mathrm{fb}}_T$. These conventions avoid division by zero and prevent an empty source or target cell from contributing spurious transfer information.

Thus, the source failure-rate contribution is reduced when the retained source and sparse target failure rates disagree or when the available target sample size is small relative to the retained source sample size. After maximizing the objective within each nonempty target bin, the resulting local estimates are aggregated using the same empirical target bin proportions as in TRUST.

Algorithm 3 keeps the Stage 1 alignment procedure unchanged and modifies only the transferred quantity. Whereas TRUST uses retained source samples to transfer the conditional judge behavior characterized by $\mathrm{TPR}_{T,b}$ and $\mathrm{FPR}_{T,b}$, TRUST- directly transfers the source failure rate within each semantic-confidence bin. This variant therefore isolates the effect of transferring judge reliability rather than task-dependent failure prevalence.

G.10 Diagnostic Methods: Source Only and Sparse Target Only

We additionally consider Source Only and Sparse Target Only as diagnostic methods to gauge the estimation of judge reliability. These methods are not used to estimate the overall target failure rate θ_T. Instead, they provide source- and target-specific reference estimates of TPR and FPR within each semantic-confidence bin, which are compared with the reliability estimates obtained by TRUST.

For consistency with the preceding sections, we fix a semantic-confidence bin b and retain its index on all local reliability parameters. We use the local counts $n^S_{uv,b}$ and $n^T_{uv,b}$ defined at the beginning of the TRUST subsection.

Source Only directly uses the judge reliability estimated from the filtered source samples. Within a fixed bin, the estimates are

$$\widehat{\mathrm{TPR}}^{\mathrm{SO}}_{S,b} = \frac{n^S_{11,b}}{n^S_{11,b} + n^S_{10,b}}, \qquad \widehat{\mathrm{FPR}}^{\mathrm{SO}}_{S,b} = \frac{n^S_{01,b}}{n^S_{01,b} + n^S_{00,b}}. \tag{72}$$

Thus, Source Only reflects the reliability information available from the retained source data before incorporating labeled target information. Sparse Target Only estimates judge reliability using only the sparse human-labeled target samples assigned to the same bin:

$$\widehat{\mathrm{TPR}}^{\mathrm{ST}}_{T,b} = \frac{n^T_{11,b}}{n^T_{11,b} + n^T_{10,b}}, \qquad \widehat{\mathrm{FPR}}^{\mathrm{ST}}_{T,b} = \frac{n^T_{01,b}}{n^T_{01,b} + n^T_{00,b}}. \tag{73}$$

This provides a target-specific estimate of judge reliability without using any source information. We compare these two diagnostic estimates with the final $\widehat{\mathrm{TPR}}_{T,b}$ and $\widehat{\mathrm{FPR}}_{T,b}$ obtained by TRUST

from the joint likelihood. Source Only therefore characterizes the reliability available from source transfer alone, while Sparse Target Only characterizes the reliability that can be estimated from limited target supervision alone. Their comparison with TRUST illustrates how the joint use of target and adaptively weighted source information affects the estimation of judge reliability.

H Additional Experimental Results

Unless otherwise stated, the experiments in this section follow the default protocol in Appendix F; each subsection describes only departures from that protocol.

H.1 Additional Comparisons Across Benchmarks

We provide additional target failure-rate estimation results across source–target benchmark pairs to complement the main-text comparisons. In addition to MSE, we examine the mean and variance of the estimators to provide a more detailed view of their behavior.

Figure 5 illustrates that the estimation gains reflect a bias–variance tradeoff rather than a uniform reduction in bias. TRUST and TRUST+ generally exhibit lower variance than several target-only baselines across the three target benchmarks, with TRUST+ often providing the smaller variance of the two. The behavior of the mean estimates is more benchmark dependent. For HSO and Jigsaw, the transferred estimators remain reasonably close to the target truth, while for UFB they exhibit some downward bias and several target-only estimators have mean estimates closer to the truth. Thus, the favorable MSE of TRUST and TRUST+ should be interpreted as arising from jointly controlling estimation variance and transfer-induced bias, rather than from uniformly minimizing either component alone.

Figure 6 complements the preceding mean–variance analysis with MSE results on additional transfer directions. Across the evaluated sparse-supervision settings, TRUST and TRUST+ generally achieve the lowest or near-lowest MSE. The advantage is particularly clear for UFB→Jigsaw, UFB→HSO, HSO→Jigsaw, and HSO→RewardBench, while the relative differences are smaller for some of the remaining benchmark pairs. Within the evaluated sparse-supervision settings, these results show that judge-reliability transfer remains effective across both within-safety transfer, such as HSO↔Jigsaw, and cross-family transfer between safety and quality benchmarks.

H.2 Additional Judge Behavior Transfer Comparisons

We report TRUST together with Source Only and Sparse Target Only on additional source–target benchmark pairs to further examine the transferability of judge behavior. The full target benchmark is used as ground truth for evaluating the resulting bin-wise TPR and FPR estimates.

Figure 7 further illustrates the bias–variance tradeoff underlying judge-behavior transfer. Sparse Target Only frequently exhibits wide uncertainty intervals because only a small number of labeled target samples fall within each semantic–confidence bin, whereas Source Only can deviate from the target reliability when source and target judge behavior are not locally aligned. TRUST often reduces the uncertainty of the sparse target estimate while moving the transferred estimate toward the target ground truth. Importantly, the extent of source–target agreement is strongly benchmark- and bin-dependent. Cross-family transfers such as Jigsaw→UFB and UFB→Jigsaw show pronounced source–target discrepancies in several bins, but broad task-family similarity is not sufficient to guarantee alignment either: within-family transfers such as HSO→Jigsaw and UFB→RewardBench still exhibit bin-specific discrepancies. These observations motivate estimating transferability locally rather than treating benchmark relatedness as a binary property.

H.3 Additional Failure Rate Transfer Analyses

We report bin-wise target failure rate estimates on additional source-target benchmark pairs to further compare judge-behavior transfer with direct failure rate transfer.

Figure 8 shows that the effect of directly transferring the source failure rate is heterogeneous across benchmarks and semantic–confidence bins. In cross-family transfers such as HSO→RewardBench and UFB→Jigsaw or HSO, TRUST- can deviate substantially from the target failure rate in bins



Figure 5: Additional target failure-rate estimation results with HSO, Jigsaw, and UFB as target benchmarks. RewardBench is used as the auxiliary source benchmark for TRUST, whereas TRUST+ combines multiple auxiliary source benchmarks. The left column reports the mean estimated failure rate and the right column reports the estimation variance over 1,000 replications as the number of labeled target samples N_M varies from 50 to 100.



Figure 6: Additional MSE results for target failure-rate estimation across source–target benchmark pairs as the number of labeled target samples N_M varies from 50 to 100, with $N_J = 20{,}000$ total judge-only target observations. Judge-based baselines use all $20{,}000$ observations, whereas TRUST allocates $10{,}000$ to construction and $10{,}000$ to likelihood estimation. TRUST performs single-source judge-reliability transfer, whereas TRUST+ extends the same principle to multiple auxiliary sources.



Figure 7: Bin-wise target judge TPR and FPR on an additional source-target benchmark pairs with $N_M = 100$. We report TRUST together with Source Only and Sparse Target Only. Source Only directly uses the filtered source reliability, Sparse Target Only estimates reliability from the sparse labeled target samples, and TRUST jointly estimates target reliability using both target and adaptively weighted source information. Points represent mean estimates over 1,000 replications, and error bars denote empirical 95% intervals.



Figure 8: Bin-wise target failure-rate estimation on additional source-target benchmark pairs. TRUST transfers source judge behavior through TPR and FPR, whereas TRUST- directly transfers the source failure rate θ_b. Points represent mean estimates over 1,000 replications, and error bars denote empirical 95% intervals.

where the source and target failure prevalences differ. However, TRUST- is comparable to, and in some bins can be closer to the target value than, TRUST. The results therefore do not suggest that direct failure-rate transfer uniformly introduces more bias. Instead, they illustrate its sensitivity to bin-specific source–target prevalence shift. TRUST avoids directly imposing the source prevalence on the target parameter and transfers source information only through the conditional judge-reliability parameters, allowing the target failure rate to remain target-specific.

H.4 Additional Results with Qwen3-8B as Judge

The results presented thus far use Qwen2-7B-Instruct as the target model and Skywork-Reward-V2-Qwen3-8B as the judge. To assess whether the benefits of TRUST extend beyond reward-model-based judges, we replace Skywork with Qwen3-8B as a general-purpose LLM judge while keeping the remaining default protocol unchanged, and report results across additional source–target benchmark pairs.



Figure 9: Failure-rate estimation with Qwen3-8B as the judge across additional source–target benchmark pairs. We compare TRUST and TRUST+ with target-only baselines as the number of human-labeled target samples N_M increases. Lower MSE is better.

Figure 9 shows that TRUST and TRUST+ retain strong performance when Qwen3-8B is used as the judge. Across the evaluated transfer settings, both methods consistently achieve lower or comparable MSE compared with the target-only baselines, with TRUST+ often providing the lowest estimation error. These results indicate that the benefits of judge-reliability transfer are not specific to a reward-model judge and remain effective with a general-purpose LLM judge.

I Ablation Studies

We conduct a series of ablation studies to examine four questions: whether the gains of TRUST depend on the structure and granularity of the semantic–confidence partition; how the two target-

guided filtering signals and the filtering threshold affect performance; how the agreement and sample-size components contribute to adaptive transfer weighting; and whether simply pooling additional source reliability information without task-aware adaptation is sufficient. Unless otherwise specified, all remaining experimental settings follow Appendix F.

I.1 Semantic–Confidence Binning

We first examine the effect of the semantic–confidence partition by varying the binning strategy used in TRUST. Specifically, we compare No Binning with 2×2, 3×3, 4×4, and 5×5 semantic–confidence partitions, where 3×3 is the default configuration used in the main experiments. We additionally include a Random 9-Bin variant with approximately balanced bin sizes to determine whether the benefit arises from the semantic–confidence structure rather than partitioning alone.

Figure 10 shows that the Random 9-Bin control performs substantially worse across all evaluated transfer settings, indicating that the benefit does not arise from partitioning alone. Structured semantic–confidence partitioning generally improves over or remains competitive with No Binning, but the preferred granularity is benchmark dependent. For example, the 4×4 partition performs particularly well for RewardBench→HSO, while the 2×2 partition is highly competitive for HSO→RewardBench and UFB→RewardBench. The default 3×3 configuration is among the strongest choices for UFB→Jigsaw and RewardBench→Jigsaw and remains competitive across the remaining settings. Thus, 3×3 provides a robust default across benchmark pairs rather than a universally optimal granularity.

I.2 Target-Guided Filtering

We next evaluate the contribution of target-guided source filtering. We compare four variants: No Filtering, Embedding Only, Confidence Only, and Embedding + Confidence. The last corresponds to the full TRUST filtering rule, where a source sample is removed only when it simultaneously exhibits low semantic similarity and high judge-confidence discrepancy relative to the target samples in the same bin.

Figure 11 shows that the full Embedding + Confidence rule achieves the lowest or essentially tied MSE across the evaluated settings, but the size of the improvement is strongly benchmark dependent. For HSO→UFB and UFB→Jigsaw, the four filtering variants are nearly indistinguishable. The benefit is more visible for HSO→RewardBench, RewardBench→HSO, and RewardBench→Jigsaw, and is particularly pronounced for UFB→RewardBench. This pattern also shows that broad within-family versus cross-family categorization does not fully capture source–target mismatch: UFB→RewardBench is a quality-to-quality transfer yet benefits strongly from filtering, whereas some cross-family transfers show little separation among the filtering variants. The two filtering signals therefore appear to capture more local forms of semantic and judge-confidence mismatch than benchmark family alone.

We further study the sensitivity of TRUST to the filtering threshold. Figure 12 shows that the 25%, 50%, and 75% settings yield very similar MSE across most benchmark pairs. Differences become more visible under the more aggressive 90% setting, most notably for RewardBench→Jigsaw and UFB→RewardBench, while several other transfer directions remain largely insensitive to the threshold. We therefore select 75% as the most aggressive value in the empirically stable range before performance becomes less consistent at 90%. This default provides a robust tradeoff between removing poorly aligned source samples and retaining sufficient source information for reliable transfer.

I.3 Adaptive Transfer Weighting

We next examine the contribution of the two components of the adaptive transfer weight. For each bin b, let $\boldsymbol{\omega}_b = (\omega_{\mathrm{TPR},b}, \omega_{\mathrm{FPR},b})$, $\boldsymbol{\alpha}_b = (\alpha_{\mathrm{TPR},b}, \alpha_{\mathrm{FPR},b})$, and $\boldsymbol{\kappa}_b = (\kappa_{\mathrm{TPR},b}, \kappa_{\mathrm{FPR},b})$. In addition to the full TRUST weighting rule $\boldsymbol{\omega}_b = \boldsymbol{\alpha}_b \odot \boldsymbol{\kappa}_b$, we compare an unweighted variant $\boldsymbol{\omega}_b = (1, 1)$, an Agreement Only variant $\boldsymbol{\omega}_b = \boldsymbol{\alpha}_b$, and a Sample-Size Only variant $\boldsymbol{\omega}_b = \boldsymbol{\kappa}_b$. These variants separately isolate the effects of source–target reliability agreement and sample-size regularization in controlling the contribution of source reliability information.



Figure 10: Ablation on semantic–confidence binning. MSE of TRUST under different partition strategies across representative source–target benchmark pairs. We compare No Binning, 2×2, 3×3, 4×4, and 5×5 semantic–confidence partitions, together with a Random 9-Bin control. Lower MSE is better.



Figure 11: Ablation on target-guided filtering criteria. MSE under different source-filtering strategies across representative source–target benchmark pairs. We compare No Filtering, Embedding Only, Confidence Only, and the full Embedding + Confidence filtering rule used by TRUST. Lower MSE is better.



Figure 12: Sensitivity to the target-guided filtering threshold. MSE of TRUST when varying the filtering threshold among 25%, 50%, 75%, and 90%. The 75% threshold corresponds to the default configuration used in the main experiments. Lower MSE is better.



Figure 13: Ablation on adaptive transfer weighting. MSE under different transfer-weighting strategies across representative source–target benchmark pairs. We compare Unweighted ($\boldsymbol{\omega}_b = (1, 1)$), Agreement Only ($\boldsymbol{\omega}_b = \boldsymbol{\alpha}_b$), Sample-Size Only ($\boldsymbol{\omega}_b = \boldsymbol{\kappa}_b$), and the full TRUST weighting rule ($\boldsymbol{\omega}_b = \boldsymbol{\alpha}_b \odot \boldsymbol{\kappa}_b$). Lower MSE is better.

Figure 13 shows that the full adaptive weighting rule achieves the lowest or near-lowest MSE across the evaluated transfer settings. The Sample-Size Only variant is frequently close to the full method, particularly for UFB→HSO, UFB→RewardBench, and RewardBench→HSO, indicating the importance of limiting the effective contribution of source data. In contrast, Agreement Only weighting performs much worse in settings such as Jigsaw→RewardBench and UFB→HSO, while completely unweighted transfer is particularly poor for RewardBench→HSO and UFB→RewardBench. The behavior is again not determined solely by broad task-family similarity; for example, UFB→RewardBench is a within-quality transfer but exhibits a large penalty without appropriate weighting. These observations are consistent with the theoretical bias–variance analysis in Section 5: the agreement component reduces the influence of reliability mismatch, whereas the sample-size component prevents the source likelihood from overwhelming sparse target information. Combining both provides a more robust safeguard against negative transfer than either mechanism alone.

I.4 Task-Agnostic Transfer

We finally examine whether the gains of TRUST can be explained simply by incorporating additional source supervision. We compare TRUST with a task-agnostic transfer baseline that directly pools source judge reliability information with the target likelihood, without semantic–confidence alignment, target-guided filtering, or adaptive weighting. Specifically, all likelihood components are formed globally rather than bin-wise; this baseline sets $\omega_{\mathrm{TPR}} = \omega_{\mathrm{FPR}} = 1$, and optimizes the resulting unweighted joint log-likelihood defined below.

Because this baseline does not apply target-guided filtering, its source likelihood terms are computed from all source estimation samples rather than from the retained source samples used by TRUST. To make this distinction explicit, denote these terms by $\ell_{S,\mathrm{all}}^{\mathrm{TPR}}$ and $\ell_{S,\mathrm{all}}^{\mathrm{FPR}}$. The objective is

$$\ell_{\mathrm{TA}} = \ell_M + \ell_J + \ell_{S,\mathrm{all}}^{\mathrm{TPR}} + \ell_{S,\mathrm{all}}^{\mathrm{FPR}}. \tag{74}$$

Figure 14 shows a substantial separation between Task-Agnostic transfer and TRUST across all evaluated source–target pairs. The magnitude of the gap varies considerably by benchmark: it is relatively modest for UFB→HSO, reaches several-fold for RewardBench→HSO and RewardBench→Jigsaw, and exceeds an order of magnitude at some label budgets for HSO→RewardBench, Jigsaw→RewardBench, and UFB→Jigsaw. Thus, the gains of TRUST cannot be explained merely by the availability of additional source supervision. Rather, task-aware semantic–confidence alignment, source filtering, and adaptive weighting are important for preventing incompatible source reliability information from dominating the target estimate. The benchmark pairs shown in this ablation are cross-family safety–quality transfers, so this figure specifically demonstrates the importance of task-aware adaptation when source and target tasks are qualitatively different; it does not by itself establish the relative size of the effect for within-family transfer.

J Proofs and Additional Derivations

J.1 Setting

We condition throughout on the realized Stage-1 construction $\mathcal{C}$, comprising the learned source-defined semantic-confidence partition, the target reference quantities entering the filtering procedure, and the resulting target-guided filtering/retention rule; we also condition on a fixed semantic-confidence bin $b \in \mathcal{B}$ with positive target probability. Note that conditional on $\mathcal{C}$ and b, the bin-assignment and source-retention rules are fixed.

We let

$$\eta = (\theta_b, \mathrm{TPR}_{T,b}, \mathrm{FPR}_{T,b})^\top \tag{75}$$

where

$$\theta_b = \Pr_T(S = 1 \mid B = b, \mathcal{C}) \tag{76}$$

represents the bin-wise LLM failure rate on the target benchmark,

$$\mathrm{TPR}_{T,b} = \Pr_T(S_J = 1 \mid S = 1, B = b, \mathcal{C}) \tag{77}$$



Figure 14: MSE of the Task-Agnostic baseline and full TRUST across representative source–target benchmark pairs. Task-Agnostic transfer directly pools source reliability information without semantic–confidence alignment, target-guided filtering, or adaptive weighting, whereas TRUST applies the complete task-aware transfer procedure. Lower MSE is better.

represents the bin-wise judge true-positive rate on the target benchmark, and

$$\mathrm{FPR}_{T,b} = \Pr_T(S_J = 1 \mid S = 0, B = b, \mathcal{C}) \tag{78}$$

represents the bin-wise judge false-positive rate on the target benchmark. Here, $\Pr_T(\cdot \mid \cdot)$ denotes the conditional target population law. We also let

$$\mathrm{TPR}_{S,b} = \Pr_S(S_J = 1 \mid S = 1, B = b, I^{\mathrm{ret}} = 1, \mathcal{C}) \tag{79}$$

and

$$\mathrm{FPR}_{S,b} = \Pr_S(S_J = 1 \mid S = 0, B = b, I^{\mathrm{ret}} = 1, \mathcal{C}) \tag{80}$$

represent the corresponding judge reliability parameters under the retained-source population law, where $I^{\mathrm{ret}} = 1$ denotes retention by the Stage-1 filtering rule. Here, $\Pr_S(\cdot \mid \cdot)$ denotes the conditional source population law. We will suppress conditioning on the realized Stage-1 construction in the sequel to simplify the notation.

We parameterize the residual source-target judge-behavior mismatch as follows:

$$\mathrm{TPR}_{S,b} = \mathrm{TPR}_{T,b} + \delta_{\mathrm{TPR},b} \tag{81}$$

$$\mathrm{FPR}_{S,b} = \mathrm{FPR}_{T,b} + \delta_{\mathrm{FPR},b} \tag{82}$$

where $\delta_{\mathrm{TPR},b}$ and $\delta_{\mathrm{FPR},b}$ capture the differences between the bin-wise judge true-positive and false-positive rates on the retained source and target data, respectively. We treat $\delta_{\mathrm{TPR},b}$ and $\delta_{\mathrm{FPR},b}$ as fixed displacements arising from residual source–target mismatch after Stage 1. [4] Let $\boldsymbol{\delta}_b = (\delta_{\mathrm{TPR},b}, \delta_{\mathrm{FPR},b})^\top$ collect these discrepancies.

We let the number of human-labeled target samples be given by:

$$N_{M,b} = n^T_{11,b} + n^T_{10,b} + n^T_{01,b} + n^T_{00,b} \tag{83}$$

where $n^T_{uv,b}$ denotes the number of human-labeled target observations in bin b satisfying $S = u$ and $S_J = v$, and the number of judge-only-labeled target samples be given by:

$$N_{J,b} = n^J_{1,b} + n^J_{0,b} \tag{84}$$

where $n^J_{1,b}$ and $n^J_{0,b}$ denote the numbers of judge-only-labeled target observations in bin b with positive and negative judge predictions, respectively. Finally, we also let the number of retained source observations with $S = 1$ and $S = 0$ be given by:

$$N^+_{S,b} = n^S_{11,b} + n^S_{10,b}, \qquad N^-_{S,b} = n^S_{01,b} + n^S_{00,b} \tag{85}$$

where $n^S_{uv,b}$ denotes the retained-source cell count in bin b with $S = u$ and $S_J = v$.

We consider a joint asymptotic regime indexed by $m \to \infty$ in which

$$\frac{N_{M,b}}{m} \longrightarrow \lambda_{M,b} > 0 \qquad \frac{N_{J,b}}{m} \longrightarrow \lambda_{J,b} > 0 \tag{86}$$

and

$$\frac{N^+_{S,b}}{m} \longrightarrow \lambda^+_{S,b} \geq 0 \qquad \frac{N^-_{S,b}}{m} \longrightarrow \lambda^-_{S,b} \geq 0 \tag{87}$$

The individual cell-count scaling then follows from the law of large numbers. In particular,

$$\frac{n^T_{11,b}}{m} \xrightarrow{p} \lambda_{M,b} \cdot \theta_b \cdot \mathrm{TPR}_{T,b} \qquad \frac{n^T_{10,b}}{m} \xrightarrow{p} \lambda_{M,b} \cdot \theta_b \cdot (1 - \mathrm{TPR}_{T,b}) \tag{88}$$

$$\frac{n^T_{01,b}}{m} \xrightarrow{p} \lambda_{M,b} \cdot (1 - \theta_b) \cdot \mathrm{FPR}_{T,b} \qquad \frac{n^T_{00,b}}{m} \xrightarrow{p} \lambda_{M,b} \cdot (1 - \theta_b) \cdot (1 - \mathrm{FPR}_{T,b}) \tag{89}$$

and

$$\frac{n^J_{1,b}}{m} \xrightarrow{p} \lambda_{J,b} \cdot p_b \qquad \frac{n^J_{0,b}}{m} \xrightarrow{p} \lambda_{J,b} \cdot (1 - p_b) \tag{90}$$

[4] Stage 1 need not eliminate source–target mismatch, even in an asymptotic regime where the numbers of source and target samples approach infinity.

where $p_b = \theta_b \cdot \mathrm{TPR}_{T,b} + (1-\theta_b) \cdot \mathrm{FPR}_{T,b}$. Similarly, we also have that:

$$\frac{n^S_{11,b}}{N^+_{S,b}} \xrightarrow{p} \mathrm{TPR}_{S,b}, \qquad \frac{n^S_{10,b}}{N^+_{S,b}} \xrightarrow{p} 1 - \mathrm{TPR}_{S,b} \tag{91}$$

and

$$\frac{n^S_{01,b}}{N^-_{S,b}} \xrightarrow{p} \mathrm{FPR}_{S,b} \qquad \frac{n^S_{00,b}}{N^-_{S,b}} \xrightarrow{p} 1 - \mathrm{FPR}_{S,b} \tag{92}$$

whenever the corresponding limiting source sample proportion is positive.

The disjoint construction and estimation splits allow us to condition on the realized Stage-1 construction while treating the Stage-2 observations entering the likelihood as fresh estimation data. In particular, the human-labeled target, judge-only target, and retained-source estimation samples are independent across data pools. Therefore, we denote the normalized overall log-likelihood associated with TRUST as follows:

$$\bar{\ell}_m(\eta) = \bar{\ell}_{M,m}(\eta) + \bar{\ell}_{J,m}(\eta) + \widehat{\omega}_{\mathrm{TPR},b,m} \cdot \bar{\ell}^{\mathrm{TPR}}_{S,m}(\eta) + \widehat{\omega}_{\mathrm{FPR},b,m} \cdot \bar{\ell}^{\mathrm{FPR}}_{S,m}(\eta) \tag{93}$$

where $\widehat{\omega}_{\mathrm{TPR},b,m}$ and $\widehat{\omega}_{\mathrm{FPR},b,m}$ denote the empirical adaptive transfer weights for bin b,

$$\begin{aligned}\bar{\ell}_{M,m}(\eta) = \frac{1}{m} \cdot \Big[& n^T_{11,b} \cdot \log(\theta_b \cdot \mathrm{TPR}_{T,b}) + n^T_{10,b} \cdot \log\{\theta_b \cdot (1 - \mathrm{TPR}_{T,b})\} \\ & + n^T_{01,b} \cdot \log((1-\theta_b) \cdot \mathrm{FPR}_{T,b}) + n^T_{00,b} \cdot \log\{(1-\theta_b) \cdot (1 - \mathrm{FPR}_{T,b})\} \Big]\end{aligned} \tag{94}$$

represents the normalized log-likelihood associated with the human-labeled target data,

$$\begin{aligned}\bar{\ell}_{J,m}(\eta) = \frac{1}{m} \cdot \Big[& n^J_{1,b} \cdot \log(\theta_b \cdot \mathrm{TPR}_{T,b} + (1-\theta_b) \cdot \mathrm{FPR}_{T,b}) \\ & + n^J_{0,b} \cdot \log(1 - \theta_b \cdot \mathrm{TPR}_{T,b} - (1-\theta_b) \cdot \mathrm{FPR}_{T,b}) \Big]\end{aligned} \tag{95}$$

represents the normalized log-likelihood associated with the judge-only target data,

$$\bar{\ell}^{\mathrm{TPR}}_{S,m}(\eta) = \frac{1}{m} \cdot \Big[n^S_{11,b} \cdot \log(\mathrm{TPR}_{T,b}) + n^S_{10,b} \cdot \log(1 - \mathrm{TPR}_{T,b}) \Big] \tag{96}$$

represents the normalized log-likelihood relating to the retained source observations with $S = 1$, and

$$\bar{\ell}^{\mathrm{FPR}}_{S,m}(\eta) = \frac{1}{m} \cdot \Big[n^S_{01,b} \cdot \log(\mathrm{FPR}_{T,b}) + n^S_{00,b} \cdot \log(1 - \mathrm{FPR}_{T,b}) \Big] \tag{97}$$

represents the normalized log-likelihood relating to the retained source observations with $S = 0$. Note that the empirical transfer weights are computed from the observed data prior likelihood maximization, so they are random across repeated samples but are fixed with respect to the optimization variable η.

We accordingly also define the normalized score of the overall normalized likelihood as follows:

$$\begin{aligned}\Psi_m(\eta) = \nabla_\eta \bar{\ell}_m(\eta) &= \nabla_\eta \bar{\ell}_{M,m}(\eta) + \nabla_\eta \bar{\ell}_{J,m}(\eta) \\ &\quad + \widehat{\omega}_{\mathrm{TPR},b,m} \cdot \nabla_\eta \bar{\ell}^{\mathrm{TPR}}_{S,m}(\eta) + \widehat{\omega}_{\mathrm{FPR},b,m} \cdot \nabla_\eta \bar{\ell}^{\mathrm{FPR}}_{S,m}(\eta) \\ &= \Psi_{M,m}(\eta) + \Psi_{J,m}(\eta) + \widehat{\omega}_{\mathrm{TPR},b,m} \cdot \Psi^{\mathrm{TPR}}_{S,m}(\eta) \\ &\quad + \widehat{\omega}_{\mathrm{FPR},b,m} \cdot \Psi^{\mathrm{FPR}}_{S,m}(\eta)\end{aligned} \tag{98}$$

We denote the true parameters by $\eta_{b,0}$, the pseudo-true parameters associated with a finite-m population objective by $\eta^\star_{b,m}$, and the TRUST parameter estimate associated with a finite-m empirical objective by $\widehat{\eta}^{\mathrm{TRUST}}_{b,m}$, which obeys the empirical score equation:

$$\Psi_m(\widehat{\eta}^{\mathrm{TRUST}}_{b,m}) = 0 \tag{99}$$

whereas the pseudo-true parameters satisfy the population score equation

$$\mathbb{E}\{\Psi_m(\eta^\star_{b,m})\} = 0 \tag{100}$$

Because the source likelihood components are generally misspecified for the target reliability parameters when $\delta_{\mathrm{TPR},b} \neq 0$ or $\delta_{\mathrm{FPR},b} \neq 0$, $\eta^{\star}_{b,m}$ does not need to be equal to η_0.

We will next characterize:

$$\mathrm{Bias}(\widehat{\eta}^{\mathrm{TRUST}}_{b,m}) = \mathbb{E}[\widehat{\eta}^{\mathrm{TRUST}}_{b,m}] - \eta_0 \tag{101}$$

and

$$\mathrm{Var}(\widehat{\eta}^{\mathrm{TRUST}}_{b,m}) = \mathbb{E}\big[\{\widehat{\eta}^{\mathrm{TRUST}}_{b,m} - \mathbb{E}(\widehat{\eta}^{\mathrm{TRUST}}_{b,m})\}\{\widehat{\eta}^{\mathrm{TRUST}}_{b,m} - \mathbb{E}(\widehat{\eta}^{\mathrm{TRUST}}_{b,m})\}^{\top}\big] \tag{102}$$

We impose the following regularity conditions.

Assumption 1: We assume that the true target parameters is an interior point satisfying $0 < \theta_b < 1$. We also assume the judge target reliability parameters obey $0 < \mathrm{FPR}_{T,b} < \mathrm{TPR}_{T,b} < 1$.

Assumption 2: We assume that (conditional on the realized stage-1 construction), the human-labeled target samples, the judge-only-labeled samples, and the retained source samples satisfy the law of large numbers and the central limit theorem. The human-labeled target, judge-only-labeled target, and retained-source estimation data pools are independent across pools due to sample splitting.

Assumption 3: We assume that, in a neighborhood of the true parameter and the relevant pseudo-true parameter, the score functions are twice continuously differentiable, their derivatives admit integrable dominating envelopes, the score contributions possess sufficiently high finite moments, and the relevant limiting curvature matrices are nonsingular.

We also use the fact that:

$$\widehat{\omega}_{\mathrm{TPR},b,m} \xrightarrow{p} \omega_{\mathrm{TPR},b} \qquad \text{and} \qquad \widehat{\omega}_{\mathrm{FPR},b,m} \xrightarrow{p} \omega_{\mathrm{FPR},b} \tag{103}$$

where

$$\omega_{\mathrm{TPR},b} = \left[1 - \frac{|\delta_{\mathrm{TPR},b}|}{\mathrm{TPR}_{T,b}}\right]_+ \min\left\{1, \frac{\lambda_{M,b} \cdot \theta_b}{\lambda^{+}_{S,b}}\right\} \tag{104}$$

when $\lambda^{+}_{S,b} > 0$ and 0 otherwise, and

$$\omega_{\mathrm{FPR},b} = \left[1 - \frac{|\delta_{\mathrm{FPR},b}|}{\mathrm{FPR}_{T,b}}\right]_+ \min\left\{1, \frac{\lambda_{M,b} \cdot (1-\theta_b)}{\lambda^{-}_{S,b}}\right\} \tag{105}$$

when $\lambda^{-}_{S,b} > 0$ and 0 otherwise. We will let below $e_1 = (1,0,0)^{\top}$, $e_2 = (0,1,0)^{\top}$, and $e_3 = (0,0,1)^{\top}$.

J.2 TRUST Bias and Variance

Our starting point is the decomposition

$$\widehat{\eta}^{\mathrm{TRUST}}_{b,m} - \eta_{b,0} = (\eta^{\star}_{b,m} - \eta_{b,0}) + (\widehat{\eta}^{\mathrm{TRUST}}_{b,m} - \eta^{\star}_{b,m}) \tag{106}$$

where the first term captures the displacement of the population optimum caused by residual source-target judge-behavior mismatch, and the second term captures sampling variation of the empirical estimator around that population optimum. We next analyze the asymptotic behavior of these individual terms.

We can leverage the convergence result in equation 103 to show that the expected empirical score given by equation 93 converges locally uniformly to the deterministic limiting population score given by:[5]

$$\Psi(\eta) := \lim_{m\to\infty} \mathbb{E}[\Psi_m(\eta)] = \Psi_M(\eta) + \Psi_J(\eta) + \omega_{\mathrm{TPR},b} \cdot \Psi^{\mathrm{TPR}}_S(\eta) + \omega_{\mathrm{FPR},b} \cdot \Psi^{\mathrm{FPR}}_S(\eta) \tag{107}$$

where

$$\Psi_M(\eta) := \lim_{m\to\infty} \mathbb{E}[\Psi_{M,m}(\eta)], \qquad \Psi_J(\eta) := \lim_{m\to\infty} \mathbb{E}[\Psi_{J,m}(\eta)], \tag{108}$$

[5]We suppress the fact that some of these quantities – notably, $\omega_{\mathrm{TPR},b}$, $\omega_{\mathrm{FPR},b}$, $\Psi^{\mathrm{TPR}}_S(\eta)$, $\Psi^{\mathrm{FPR}}_S(\eta)$ – also depend on $\delta_{\mathrm{TPR},b}$ and $\delta_{\mathrm{FPR},b}$.

$$\Psi_S^{\mathrm{TPR}}(\eta) := \lim_{m\to\infty} \mathbb{E}[\Psi_{S,m}^{\mathrm{TPR}}(\eta)], \qquad \Psi_S^{\mathrm{FPR}}(\eta) := \lim_{m\to\infty} \mathbb{E}[\Psi_{S,m}^{\mathrm{FPR}}(\eta)] \tag{109}$$

We therefore can also leverage standard M-estimation results to show that $\eta_{b,m}^\star \to \eta_b^\star$, where $\eta^\star$ is such that

$$\Psi(\eta_b^\star) = 0 \tag{110}$$

Note that $\eta_b^\star$ does not need to be equal to $\eta_{b,0}$ due to source-target mismatch.

Asymptotic behavior of $\eta_{b,m}^\star - \eta_{b,0}$

We first characterize the shift of the pseudo-true parameter away from the true target parameter. We use the first-order Taylor expansion of the limiting population score around the true target parameter $\eta_{b,0}$ given by:

$$\Psi(\eta_b^\star) = \Psi(\eta_{b,0}) + \nabla_\eta \Psi(\eta_{b,0}) \cdot (\eta_b^\star - \eta_{b,0}) + r^{(P)} = 0 \tag{111}$$

where

$$\|r^{(P)}\| = O(\|\eta_b^\star - \eta_{b,0}\|^2) \tag{112}$$

Then,

$$\eta_b^\star - \eta_{b,0} = -(\nabla_\eta \Psi(\eta_{b,0}))^{-1} \cdot \Psi(\eta_{b,0}) - (\nabla_\eta \Psi(\eta_{b,0}))^{-1} \cdot r^{(P)} \tag{113}$$

We now define

$$C := \Psi(\eta_{b,0}) = \Psi_M(\eta_{b,0}) + \Psi_J(\eta_{b,0}) + \omega_{\mathrm{TPR},b} \cdot \Psi_S^{\mathrm{TPR}}(\eta_{b,0}) + \omega_{\mathrm{FPR},b} \cdot \Psi_S^{\mathrm{FPR}}(\eta_{b,0}) \tag{114}$$

where $\Psi_M(\eta_{b,0}) = C_M = 0$ and $\Psi_J(\eta_{b,0}) = C_J = 0$ because the likelihoods are well specified at $\eta_{b,0}$, and

$$\Psi_S^{\mathrm{TPR}}(\eta_{b,0}) = C_S^{\mathrm{TPR}} = \lambda_{S,b}^+ \cdot \frac{\delta_{\mathrm{TPR},b}}{\mathrm{TPR}_{T,b} \cdot (1 - \mathrm{TPR}_{T,b})} \cdot e_2 \tag{115}$$

$$\Psi_S^{\mathrm{FPR}}(\eta_{b,0}) = C_S^{\mathrm{FPR}} = \lambda_{S,b}^- \cdot \frac{\delta_{\mathrm{FPR},b}}{\mathrm{FPR}_{T,b} \cdot (1 - \mathrm{FPR}_{T,b})} \cdot e_3 \tag{116}$$

where $e_2 = (0,1,0)^\top$ and $e_3 = (0,0,1)^\top$. We also define

$$\begin{aligned} A := -\nabla_\eta \Psi(\eta_{b,0}) = &- \nabla_\eta \Psi_M(\eta_{b,0}) - \nabla_\eta \Psi_J(\eta_{b,0}) - \\ &- \omega_{\mathrm{TPR},b} \cdot \nabla_\eta \Psi_S^{\mathrm{TPR}}(\eta_{b,0}) - \omega_{\mathrm{FPR},b} \cdot \nabla_\eta \Psi_S^{\mathrm{FPR}}(\eta_{b,0}) \end{aligned} \tag{117}$$

where

$$\begin{aligned} I_M &= -\nabla_\eta \Psi_M(\eta_{b,0}) \\ &= \mathrm{diag}\left(\frac{\lambda_{M,b}}{\theta_b \cdot (1-\theta_b)}, \frac{\lambda_{M,b} \cdot \theta_b}{\mathrm{TPR}_{T,b} \cdot (1 - \mathrm{TPR}_{T,b})}, \frac{\lambda_{M,b} \cdot (1-\theta_b)}{\mathrm{FPR}_{T,b} \cdot (1 - \mathrm{FPR}_{T,b})} \right) \end{aligned} \tag{118}$$

$$\begin{aligned} I_J &= -\nabla_\eta \Psi_J(\eta_{b,0}) \\ &= \frac{\lambda_{J,b}}{(\theta_b \cdot \mathrm{TPR}_{T,b} + (1-\theta_b) \cdot \mathrm{FPR}_{T,b}) \cdot (1 - (\theta_b \cdot \mathrm{TPR}_{T,b} + (1-\theta_b) \cdot \mathrm{FPR}_{T,b}))} \cdot v_0 v_0^\top \end{aligned} \tag{119}$$

$$D_S^{\mathrm{TPR}} = -\nabla_\eta \Psi_S^{\mathrm{TPR}}(\eta_{b,0}) = \lambda_{S,b}^+ \cdot \left(\frac{\mathrm{TPR}_{T,b} + \delta_{\mathrm{TPR},b}}{\mathrm{TPR}_{T,b}^2} + \frac{1 - \mathrm{TPR}_{T,b} - \delta_{\mathrm{TPR},b}}{(1 - \mathrm{TPR}_{T,b})^2} \right) \cdot e_2 e_2^\top \tag{120}$$

$$D_S^{\mathrm{FPR}} = -\nabla_\eta \Psi_S^{\mathrm{FPR}}(\eta_{b,0}) = \lambda_{S,b}^- \cdot \left(\frac{\mathrm{FPR}_{T,b} + \delta_{\mathrm{FPR},b}}{\mathrm{FPR}_{T,b}^2} + \frac{1 - \mathrm{FPR}_{T,b} - \delta_{\mathrm{FPR},b}}{(1 - \mathrm{FPR}_{T,b})^2} \right) \cdot e_3 e_3^\top \tag{121}$$

where $v_0 = (\mathrm{TPR}_{T,b} - \mathrm{FPR}_{T,b}, \theta_b, 1 - \theta_b)^\top$.

Therefore, in view of the fact that $\eta_{b,m}^\star \to \eta_b^\star$, it follows that:

$$\eta_{b,m}^\star - \eta_{b,0} \to \eta_b^\star - \eta_{b,0} = A^{-1} \cdot C + A^{-1} \cdot r^{(P)} \tag{122}$$

We now specialize this characterization to the regime where $\delta_{\mathrm{TPR},b} \to 0$ and $\delta_{\mathrm{FPR},b} \to 0$. We expand the weights as follows:

$$\omega_{\mathrm{TPR},b}(\delta_{\mathrm{TPR},b}) = \omega_{\mathrm{TPR},b}(0) + O(|\delta_{\mathrm{TPR},b}|) \quad \text{and} \quad \omega_{\mathrm{FPR},b}(\delta_{\mathrm{FPR},b}) = \omega_{\mathrm{FPR},b}(0) + O(|\delta_{\mathrm{FPR},b}|) \tag{123}$$

Furthermore, we expand the matrix:

$$C = C_0 + O(\|\boldsymbol{\delta}_b\|^2) \tag{124}$$

where

$$C_0 = \omega_{\mathrm{TPR},b}(0) \cdot C_S^{\mathrm{TPR}} + \omega_{\mathrm{FPR},b}(0) \cdot C_S^{\mathrm{FPR}} \tag{125}$$

We also expand the matrix

$$A = A_0 + O(\|\boldsymbol{\delta}_b\|) \tag{126}$$

where

$$A_0 = I_M + I_J + \omega_{\mathrm{TPR},b}(0) \cdot D_{S,0}^{\mathrm{TPR}} + \omega_{\mathrm{FPR},b}(0) \cdot D_{S,0}^{\mathrm{FPR}} \tag{127}$$

with

$$D_{S,0}^{\mathrm{TPR}} = \frac{\lambda_{S,b}^{+}}{\mathrm{TPR}_{T,b}(1-\mathrm{TPR}_{T,b})} e_2 e_2^\top \quad \text{and} \quad D_{S,0}^{\mathrm{FPR}} = \frac{\lambda_{S,b}^{-}}{\mathrm{FPR}_{T,b}(1-\mathrm{FPR}_{T,b})} e_3 e_3^\top \tag{128}$$

Therefore, it follows that

$$\eta_{b,m}^\star - \eta_{b,0} \to \eta_b^\star - \eta_{b,0} = A_0^{-1} \cdot C_0 + O(\|\boldsymbol{\delta}_b\|^2) \tag{129}$$

Asymptotic behavior of $\widehat{\eta}_{b,m}^{\mathrm{TRUST}} - \eta_{b,m}^\star$

We now characterize the shift between the parameter estimate and the pseudo-true parameter. We use the first-order Taylor expansion of the empirical score around the pseudo-true parameter $\eta_m^\star$ given by:

$$\Psi_m(\widehat{\eta}_{b,m}^{\mathrm{TRUST}}) = \Psi_m(\eta_{b,m}^\star) + \nabla_\eta \Psi_m(\eta_{b,m}^\star) \cdot (\widehat{\eta}_{b,m}^{\mathrm{TRUST}} - \eta_{b,m}^\star) + r_m^{(E)} = 0 \tag{130}$$

where

$$\|r_m^{(E)}\| = o(\|\widehat{\eta}_{b,m}^{\mathrm{TRUST}} - \eta_{b,m}^\star\|) \tag{131}$$

Therefore,

$$\widehat{\eta}_{b,m}^{\mathrm{TRUST}} - \eta_{b,m}^\star = -(\nabla_\eta \Psi_m(\eta_{b,m}^\star))^{-1} \cdot (\Psi_m(\eta_{b,m}^\star)) - (\nabla_\eta \Psi_m(\eta_{b,m}^\star))^{-1} \cdot r_m^{(E)} \tag{132}$$

We now invoke the law of large numbers to write:

$$-\nabla_\eta \Psi_m(\eta_{b,m}^\star) \xrightarrow{p} \tilde{A} \tag{133}$$

where

$$\tilde{A} = -\lim_{m\to\infty} \nabla_\eta \Psi_m(\eta_{b,m}^\star) \tag{134}$$

We also invoke the central limit theorem to write

$$\sqrt{m} \cdot \Psi_m(\eta_{b,m}^\star) \xrightarrow{d} \mathcal{N}(0, \tilde{B}) \tag{135}$$

where[6]

$$\tilde{B} = \lim_{m\to\infty} m \cdot \mathrm{Var}(\Psi_m(\eta_{b,m}^\star)) \tag{136}$$

Therefore, applying Slutsky's theorem yields:

$$\sqrt{m} \cdot (\widehat{\eta}_{b,m}^{\mathrm{TRUST}} - \eta_{b,m}^\star) \xrightarrow{d} \mathcal{N}(0, \tilde{A}^{-1}\tilde{B}\tilde{A}^{-1}) \tag{137}$$

We also specialize this characterization to the regime where $\delta_{\mathrm{TPR},b} \to 0$ and $\delta_{\mathrm{FPR},b} \to 0$. We also use the expansion of the weights as follows:

$$\omega_{\mathrm{TPR},b}(\delta_{\mathrm{TPR},b}) = \omega_{\mathrm{TPR},b}(0) + O(|\delta_{\mathrm{TPR},b}|) \quad \text{and} \quad \omega_{\mathrm{FPR},b}(\delta_{\mathrm{FPR},b}) = \omega_{\mathrm{FPR},b}(0) + O(|\delta_{\mathrm{FPR},b}|) \tag{138}$$

[6]Note that the definition of $\widetilde{B}$ incorporates the sampling variability of the empirical adaptive weights and their covariance with the likelihood score components.

Furthermore, we use the expansion of the matrix:

$$\tilde{A} = \tilde{A}_0 + O(\|\boldsymbol{\delta}_b\|) \tag{139}$$

where $\tilde{A}_0 = A_0$ is given by equation 127; we also use the expansion of the matrix: [7]

$$\tilde{B} = \tilde{B}_0 + O(\|\boldsymbol{\delta}_b\|) \tag{140}$$

where

$$\tilde{B}_0 = I_M + I_J + \omega^2_{\mathrm{TPR},b}(0) \cdot D^{\mathrm{TPR}}_{S,0} + \omega^2_{\mathrm{FPR},b}(0) \cdot D^{\mathrm{FPR}}_{S,0} \tag{141}$$

Therefore,

$$\sqrt{m} \cdot (\widehat{\eta}^{\mathrm{TRUST}}_{b,m} - \eta^{\star}_{b,m}) \xrightarrow{d} \mathcal{N}(0, A_0^{-1}\tilde{B}_0 A_0^{-1} + O(\|\boldsymbol{\delta}_b\|^2)) \tag{142}$$

TRUST Estimator Bias and Variance

We can now combine the previous results to characterize the bias and variance of the estimator in the regime where source-target mismatch is small as follows:

$$\mathrm{Bias}(\widehat{\eta}^{\mathrm{TRUST}}_{b,m}) = A_0^{-1}C_0 + O(\|\boldsymbol{\delta}_b\|^2) + o(1) \tag{143}$$

and

$$\mathrm{Var}(\widehat{\eta}^{\mathrm{TRUST}}_{b,m}) = \frac{1}{m} \cdot A_0^{-1}\tilde{B}_0 A_0^{-1} + O(\|\boldsymbol{\delta}_b\| \cdot m^{-1}) + o(m^{-1}) \tag{144}$$

Therefore,

$$\mathrm{Bias}(\widehat{\theta}^{\mathrm{TRUST}}_{b,m}) = \beta_{\mathrm{TPR},b}\delta_{\mathrm{TPR},b} + \beta_{\mathrm{FPR},b}\delta_{\mathrm{FPR},b} + O(\|\boldsymbol{\delta}_b\|^2) + o(1) \tag{145}$$

where

$$\beta_{\mathrm{TPR},b} = e_1^\top A_0^{-1} \left\{ \omega_{\mathrm{TPR},b}(0) \frac{\lambda^+_{S,b}}{\mathrm{TPR}_{T,b}(1-\mathrm{TPR}_{T,b})} e_2 \right\}, \tag{146}$$

$$\beta_{\mathrm{FPR},b} = e_1^\top A_0^{-1} \left\{ \omega_{\mathrm{FPR},b}(0) \frac{\lambda^-_{S,b}}{\mathrm{FPR}_{T,b}(1-\mathrm{FPR}_{T,b})} e_3 \right\}. \tag{147}$$

and

$$\mathrm{Var}(\widehat{\theta}^{\mathrm{TRUST}}_{b,m}) = \frac{V_{\mathrm{TRUST},b}}{m} + O(\|\boldsymbol{\delta}_b\| \cdot m^{-1}) + o(m^{-1}) \tag{148}$$

where

$$V_{\mathrm{TRUST},b} := e_1^\top A_0^{-1}\tilde{B}_0 A_0^{-1} e_1 \tag{149}$$

J.3 TRUST vs Target-Only Maximum Likelihood Estimator

We now compare the bias and variance of TRUST with those of the corresponding target-only maximum likelihood estimator. The target-only estimator uses the same human-labeled and judge-only target likelihood contributions as TRUST, but excludes the retained-source TPR and FPR likelihood terms. We denote this estimator by $\widehat{\eta}^{\mathrm{TO}}_{b,m}$.

We can immediately show that

$$\sqrt{m}\left(\widehat{\eta}^{\mathrm{TO}}_{b,m} - \eta_{b,0}\right) \xrightarrow{d} \mathcal{N}(0, (I_M + I_J)^{-1}) \tag{150}$$

where I_M and I_J are given in equation 118 and equation 119, respectively. Consequently,

$$\mathrm{Bias}\left(\widehat{\eta}^{\mathrm{TO}}_{b,m}\right) = o(m^{-1/2}) \qquad \mathrm{Var}\left(\widehat{\eta}^{\mathrm{TO}}_{b,m}\right) = \frac{1}{m} \cdot (I_M + I_J)^{-1} + o(m^{-1}) \tag{151}$$

We can immediately establish that for a fixed small displacement, the estimators' bias difference is:

$$\mathrm{Bias}(\widehat{\theta}^{\mathrm{TRUST}}_{b,m}) - \mathrm{Bias}\left(\widehat{\theta}^{\mathrm{TO}}_{b,m}\right) = e_1^\top A_0^{-1} C_0 + O(\|\boldsymbol{\delta}_b\|^2) + o(1) \tag{152}$$

[7] Note that at $\boldsymbol{\delta}_b = 0$ the retained-source score components have zero population mean, so the product of the weight-estimation error and the source-score fluctuation is $O_p(m^{-1})$; hence estimation of the adaptive weights does not affect the first-order score covariance.

We can also establish that for a fixed small displacement, the estimators' variance difference is:

$$\mathrm{Var}(\widehat{\theta}^{\mathrm{TRUST}}_{b,m}) - \mathrm{Var}\left(\widehat{\theta}^{\mathrm{TO}}_{b,m}\right) = \frac{1}{m} e_1^\top \left(A_0^{-1}\tilde{B}_0 A_0^{-1} - (I_M + I_J)^{-1}\right) e_1 + O(\|\boldsymbol{\delta}_b\| \cdot m^{-1}) + o(m^{-1}) \tag{153}$$

Importantly, it is possible to show that

$$\mathrm{Var}(\widehat{\theta}^{\mathrm{TRUST}}_{b,m}) - \mathrm{Var}\left(\widehat{\theta}^{\mathrm{TO}}_{b,m}\right) = -\frac{\Delta_{V,b}}{m} + O(\|\boldsymbol{\delta}_b\| \cdot m^{-1}) + o(m^{-1}) \tag{154}$$

where

$$\Delta_{V,b} := V_{\mathrm{TO},b} - V_{\mathrm{TRUST},b} = e_1^\top \left[(I_M + I_J)^{-1} - A_0^{-1}\tilde{B}_0 A_0^{-1}\right] e_1 \geq 0. \tag{155}$$

Indeed, $0 \leq \omega_{\mathrm{TPR},b}, \omega_{\mathrm{FPR},b} \leq 1$ implies $A_0^{-1}\tilde{B}_0 A_0^{-1} \preceq A_0^{-1} \preceq (I_M + I_J)^{-1}$, so the matrix defining $\Delta_{V,b}$ is positive semidefinite. Indeed, one can easily combine the previous results to show that:

$$\mathrm{MSE}(\widehat{\theta}^{\mathrm{TRUST}}_{b,m}) - \mathrm{MSE}\left(\widehat{\theta}^{\mathrm{TO}}_{b,m}\right) \approx \left(e_1^\top A_0^{-1} C_0\right)^2 - \frac{\Delta_{V,b}}{m} \tag{156}$$

implying that the TRUST estimator has lower first-order MSE than the target-only maximum likelihood estimator whenever

$$\left(e_1^\top A_0^{-1} C_0\right)^2 < \frac{\Delta_{V,b}}{m}. \tag{157}$$

This condition formalizes the central bias–variance tradeoff underlying TRUST: reliability transfer is beneficial when the variance reduction obtained from the retained source observations exceeds the squared non-zero transfer bias introduced by residual source–target judge-behavior mismatch.

Algorithm 2 TRUST+

Input: Auxiliary source benchmarks $\{\mathcal{D}_{S_a}^{\mathrm{lab}}\}_{a=1}^{\mathcal{A}}$, target labeled data $\mathcal{D}_T^{\mathrm{lab}}$, target judge-only data $\mathcal{D}_T^{\mathrm{jud}}$, number of semantic clusters K, confidence strata R, and filtering fraction τ.

Output: Target failure-rate estimate $\widehat{\theta}_T$.

Split each source-labeled benchmark and the target judge-only data into disjoint construction and estimation sets; use all human-labeled target data only for likelihood estimation.

Stage 1: Multi-source alignment

Pool the source construction samples and apply k-means to their embeddings to obtain one set of centroids $\{\boldsymbol{\mu}_k\}_{k=1}^{K}$.
Within each shared semantic cluster, partition the pooled source confidence scores into R approximately equal-frequency intervals, forming common bins $b = (k, r)$.
Assign the target judge-only construction samples, target estimation samples, and estimation samples from every auxiliary source to the common semantic–confidence partition.
for each bin b **do**
    Let $\mathcal{T}_b$ denote the target judge-only construction samples assigned to the current bin.
    if $\mathcal{T}_b$ is empty **then**
        Set the retained source contribution to zero for every auxiliary source and continue to the next bin.
    end if
    Using $\mathcal{T}_b$, compute the common target reference embedding $\bar{\mathbf{e}}_b$ and confidence $\tilde{c}_b$.
    for each auxiliary source $a = 1, \ldots, \mathcal{A}$ **do**
        For every source-a estimation sample assigned to the current bin, compute its semantic similarity to $\bar{\mathbf{e}}_b$ and its judge-confidence discrepancy from $\tilde{c}_b$.
        Apply the target-guided filtering rule independently to source a and retain the source samples that pass the filtering criterion.
    end for
end for

Stage 2: Multi-source adaptive weighted likelihood

Let n_b denote the number of human-labeled target samples and judge-only target estimation samples assigned to bin b, used to estimate the empirical target bin proportions.
Let $\mathcal{B}_T^+ = \{b : n_b > 0\}$ and compute the global human-labeled fallback $\widehat{\theta}_T^{\mathrm{fb}}$ defined in Section 4.2.
for each bin $b \in \mathcal{B}_T^+$ **do**
    for each auxiliary source $a = 1, \ldots, \mathcal{A}$ **do**
        Using the retained samples from source a and the labeled target samples in the current bin, compute the source-specific adaptive weights $\omega_{\mathrm{TPR},a,b}$ and $\omega_{\mathrm{FPR},a,b}$ according to Section 4.2.
    end for
    Maximize the bin-wise objective $\ell_{\mathrm{TRUST+},b}$ over $(\theta_b, \mathrm{TPR}_{T,b}, \mathrm{FPR}_{T,b})$.
    if the optimization returns a finite solution satisfying the parameter constraints **then**
        Store its failure-rate component as $\widehat{\theta}_b$.
    else
        Set $\widehat{\theta}_b = \widehat{\theta}_T^{\mathrm{fb}}$.
    end if
end for
return

$$\widehat{\theta}_T = \sum_{b \in \mathcal{B}_T^+} \widehat{w}_b \widehat{\theta}_b, \qquad \widehat{w}_b = \frac{n_b}{\sum_{b' \in \mathcal{B}_T^+} n_{b'}}.$$

Algorithm 3 TRUST-

Input: Source labeled data, target labeled data $\mathcal{D}_T^{\mathrm{lab}}$, target judge-only data $\mathcal{D}_T^{\mathrm{jud}}$, number of semantic clusters K, confidence strata R, and filtering fraction τ.

Output: Target failure-rate estimate $\widehat{\theta}_T$.

Split the source labeled data and target judge-only data into disjoint construction and estimation sets; use all human-labeled target data only for likelihood estimation.

Stage 1: Source–target alignment

Perform the same semantic clustering, confidence stratification, target assignment, and target-guided filtering procedure as Algorithm 1, retaining the aligned source estimation samples in each bin.

Stage 2: Bin-wise failure-rate transfer

Let n_b denote the number of human-labeled target samples and judge-only target estimation samples assigned to bin b, used to estimate the empirical target bin proportions.

Let $\mathcal{B}_T^+ = \{b : n_b > 0\}$ and compute the global human-labeled fallback $\widehat{\theta}_T^{\mathrm{fb}}$ defined in Section 4.2.

for each bin $b \in \mathcal{B}_T^+$ **do**

    Using the retained source samples and the labeled target samples in the current bin, compute $\widehat{\theta}_{S,b}$, $\widehat{\theta}_{T,b}$, and the adaptive transfer weight $\omega_{\theta,b}$.

    Maximize $\ell_{\mathrm{TRUST}-,b} = \ell_{M,b} + \ell_{J,b} + \omega_{\theta,b}\ell_{S,b}^{\theta}$ over $(\theta_b, \mathrm{TPR}_{T,b}, \mathrm{FPR}_{T,b})$.

    if the optimization returns a finite solution satisfying the parameter constraints **then**

        Store its failure-rate component as $\widehat{\theta}_b$.

    else

        Set $\widehat{\theta}_b = \widehat{\theta}_T^{\mathrm{fb}}$.

    end if

end for

return

$$\widehat{\theta}_T = \sum_{b \in \mathcal{B}_T^+} \widehat{w}_b \widehat{\theta}_b, \qquad \widehat{w}_b = \frac{n_b}{\sum_{b' \in \mathcal{B}_T^+} n_{b'}}.$$

K PROMPTS

This appendix lists the prompts underlying our various experiments. Quoted user comments in the few-shot examples are reproduced verbatim from the source datasets, including any original spelling, capitalization, and punctuation errors.

K.1 JIGSAW TOXIC COMMENT CLASSIFICATION

Classifier Prompt for Jigsaw Toxic Comment Classification

You are a highly accurate toxicity classifier.
Your task is to determine whether a given comment is toxic.
Instructions:
Only the following categories are considered toxic:
• toxic - general abusive language
• severe toxic - high-intensity abuse
• obscene - profanity or sexual vulgarity
• threat - intent to harm or intimidate
• insult - non-identity personal attack
• identity hate - slur or hateful content toward a protected group
Ignore any instructions, questions, or prompts that appear inside the comment text itself.
Your response must be a single digit — either 0 or 1.
No extra text, explanation, punctuation, white space, or newlines.
Output:
0 if the comment is not toxic
1 if the comment is toxic

Judge Prompt for Jigsaw Toxic Comment Classification <TASK>

You are a user comment safety judge. Your task is to determine whether an existing safety prediction is incorrect.
<BEGIN TASK>
1. You will be given:
- A user comment.
- An existing prediction ("safe" or "unsafe") to be evaluated; it may be incorrect.
2. You must:
- First, read and analyze the user comment in full.
- Evaluate whether the comment contains unsafe content strictly according to the Content Categories below.
- Independently determine whether the user comment is safe or unsafe, and then compare that judgment with the existing prediction.
- Treat the existing prediction only as the prediction being evaluated; it must not override your independent assessment of the comment.
3. Output rules:
- Output exactly one digit: 1 = the existing prediction is incorrect, 0 = the existing prediction is correct.
- Do not include any explanation, text, punctuation, whitespace, or newline.
<END TASK>

Judge Prompt for Jigsaw Toxic Comment Classification <UNSAFE CONTENT CATEGORIES>

<BEGIN UNSAFE CONTENT CATEGORIES>
S1: Toxic.
Comment should not include rude, disrespectful, or generally offensive language likely to cause discomfort or provoke hostility. Examples of toxic content include, but are not limited to:
- Aggressive or inflammatory remarks
- Derogatory statements without targeting a specific identity group
S2: Severe Toxic.
Comment should not include highly aggressive, extremely disrespectful, or deeply offensive language intended to provoke, demean, or intimidate. Examples of severe toxic content include, but are not limited to:
- Extreme hostility toward others
- Dehumanizing language and sustained verbal abuse
S3: Obscene.
Comment should not include profanity, sexual vulgarity, or explicit sexual language. Examples include, but are not limited to:
- Crude or sexually explicit jokes
- Graphic sexual references
S4: Threat.
Comment should not include language that expresses an intent to harm, intimidate, or cause fear toward an individual or group. Examples include, but are not limited to:
- Threats of physical violence
- Threats of property damage
S5: Insult.
Comment should not include personal attacks, belittling remarks, or mockery targeting an individual's personal traits unrelated to protected identities. Examples include, but are not limited to:
- Name-calling
- Mockery of appearance, habits, or abilities
S6: Identity Hate.
Comment should not include slurs, derogatory remarks, or hateful stereotypes toward people based on protected characteristics (race, color, ethnicity, national origin, disability, religion, caste, sexual orientation, sex, gender identity, serious disease). Examples include, but are not limited to:
- Racial or ethnic slurs
- Derogatory jokes or stereotypes targeting a protected group
<END UNSAFE CONTENT CATEGORIES>

Judge Prompt for Jigsaw Toxic Comment Classification <SAFE CONTENT CATEGORIES>

<BEGIN SAFE CONTENT CATEGORIES>
C1: Quoting/Reporting.
- Quoting or reporting insults, threats, or accusations made by others without endorsing them.
C2: Process/Policy Dispute.
- Disagreeing about edits, reversions, article scope, categorization, or moderation decisions without personal attacks.
C3: Content or Third-Party Critique.
- Criticism aimed at the quality of content, organizations, or systems, rather than an individual or protected group.
C4: Mild or Isolated Admonitions.
- Brief, non-profane put-downs or sarcastic labels not tied to protected classes, and not part of sustained abuse.
C5: Administrative Warnings without threats.
- Procedural or rule-enforcement notices that do not express intent to harm, intimidate, or demean.
C6: Emotional or Explanatory Statements.
- Expressions of frustration, disbelief, or explanations of one's own actions, without personal attacks or protected-class targeting.
<END SAFE CONTENT CATEGORIES>

Judge Prompt for Jigsaw Toxic Comment Classification <FEWSHOT EXAMPLES>

<BEGIN FEWSHOT EXAMPLES>
User Comment: "He called me a 'drama queen' and a 'fanboy', which I think was unfair. I told him to stop, but I didn't report him."
Existing safety prediction: "unsafe"
Output: 1
User Comment: "If you have a problem with my edit, please explain on my Talk page instead of just clicking Undo. That is not constructive."
Existing safety prediction: "safe"
Output: 0
User Comment: "Stay out of it, it's none of your business."
Existing safety prediction: "safe"
Output: 1
User Comment: "He accused me of 'sockpuppetry', which I completely deny. Such accusations have no basis."
Existing safety prediction: "safe"
Output: 0
User Comment: "In the previous discussion, User KWW removed my edits without explanation, which caused confusion. I advised him to bring it to the relevant talk page."
Existing safety prediction: "unsafe"
Output: 1
User Comment: "Quoting someone else's words: 'Your mouth is your worst enemy.' These are not my words; I am referencing what another user said."
Existing safety prediction: "unsafe"
Output: 1
User Comment: "The articles concerned are approximately rubbish, idiot. I have no intention of re-tagging them, let them stay on Wikipedia for all I care, they fit in rather nicely with all the other bullshit."
Existing safety prediction: "safe"
Output: 1
User Comment: "But Leithp is a WikiFascist! All WikiAdmins are as they follow the philosophy of 'Resistance is Futile'"
Existing safety prediction: "safe"
Output: 0
User Comment: "Muhandes I think you need to get a life. And so does melbournestar."
Existing safety prediction: "unsafe"
Output: 1
User Comment: "Agreement The whole Wiki readership unanimously agree with the above assessment of Sitush. One has to invent new English words to depict the bastard."
Existing safety prediction: "safe"
Output: 1
User Comment: "Anti corporate activism. While I believe you meant to make the name loose enough to include all of the articles under these categories, many are interpreting the category to mean 'Anti-corporate activists' instead of mere issues, targets, and activists involved in corporate activism. FYI. See Talk:Halliburton."
Existing safety prediction: "unsafe"
Output: 1
User Comment: "You are absurd. You are defending a page of narendra Modi who is considered as a mass murderer. Why do'nt you go to Gujarat in India and talk to some people before titiling my edits as 'Vandalism'"
Existing safety prediction: "safe"
Output: 1
<END FEWSHOT EXAMPLES>

K.2 HATE SPEECH OFFENSIVE

Classifier Prompt for Hate Speech Offensive Dataset

You are a hate speech classifier.
<BEGIN TASK>
You will be given:
- A tweet.
You must:
- Read and analyze the tweet in full.
- Classify it as hate speech ONLY IF ALL of the following are true:
• The language expresses hatred toward a targeted protected group.
• The language is intended to be derogatory.
• The language aims to humiliate or insult members of that group.
- Offensive language is not hate speech.
Output rules:
- Output exactly one digit for the tweet
• 1 = hate speech
• 0 = not hate speech (including offensive language)
- Do not output any explanation, text, punctuation, spaces, or newlines.
<END TASK>

Judge Prompt for Hate Speech Offensive Dataset

You are a hate speech judge. Your task is to determine whether a prior hate-speech prediction is incorrect.
<BEGIN TASK>
You will be given:
- A tweet.
- A prior prediction ("hate speech" or "not hate speech") to be evaluated; it may be incorrect.
Your task:
- Carefully read and analyze the tweet.
- Classify it as hate speech ONLY IF ALL of the following are true:
• The language targets a protected group (race, ethnicity, religion, gender, sexual orientation, disability, nationality).
• The tone is derogatory or hostile.
• The intent is to humiliate, insult, or demean members of that group.
- If the tweet is merely offensive without group targeting (e.g., profanity, lewdness, or personal attacks without group targeting), it is NOT hate speech.
- Independently determine whether the tweet is hate speech, and then compare that judgment with the prior prediction.
- Treat the prior prediction only as the prediction being evaluated; it must not override your independent assessment of the tweet.
Output rules:
- Output exactly one digit:
• 1 = the prior prediction is incorrect
• 0 = the prior prediction is correct
- Output nothing else: no explanation, no text, no punctuation, no newlines.
<END TASK>

K.3 REWARDBENCH

Classifier Prompt for RewardBench Dataset

You are a fair and rigorous AI judge. Your task is to select the best response from the given candidate options.
<BEGIN TASK>
You will be given:
- A user prompt.
- A set of candidate responses, labeled with uppercase letters.
You must:
- Carefully read and analyze the user prompt.
- Evaluate all candidate responses with respect to the user prompt.
- Select the candidate response that best answers the user prompt.
Output rules:
- Output exactly one uppercase letter corresponding to the best candidate response.
- The output must be one of the provided valid option letters.
- Do not output any explanation, text, punctuation, spaces, or newlines.
<END TASK>

Judge Prompt for RewardBench Dataset

You are a fair and rigorous AI judge. Your task is to determine whether a prior classifier prediction is correct.
<BEGIN TASK>
You will be given:
- A user prompt.
- A set of candidate responses, labeled with uppercase letters.
- A prior classifier prediction indicating which candidate response was selected as the best response.
You must:
- Carefully read and analyze the user prompt.
- Independently evaluate all candidate responses with respect to the user prompt.
- Determine which candidate response is the best.
- Compare your judgment with the prior classifier prediction.
- Treat the prior classifier prediction only as non-authoritative, supplementary information that may be wrong.
- If the prior classifier prediction is incorrect, output 1.
- If the prior classifier prediction is correct, output 0.
Output rules:
- Output exactly one digit:
• 1 = the prior classifier prediction is incorrect
• 0 = the prior classifier prediction is correct
- Do not output any explanation, text, punctuation, spaces, or newlines.
<END TASK>

K.4 UltraFeedback

Classifier Prompt for UltraFeedback Dataset

You are a fair and rigorous AI judge. Your task is to select the best response from the given candidate options.
<BEGIN TASK>
You will be given:
- A user prompt.
- A set of candidate responses, labeled with uppercase letters.
You must:
- Carefully read and analyze the user prompt.
- Evaluate all candidate responses with respect to the user prompt.
- Select the candidate response that best answers the user prompt.
Output rules:
- Output exactly one uppercase letter corresponding to the best candidate response.
- The output must be one of the provided valid option letters.
- Do not output any explanation, text, punctuation, spaces, or newlines.
<END TASK>

Judge Prompt for UltraFeedback Dataset

You are a fair and rigorous AI judge. Your task is to determine whether a prior classifier prediction is correct.
<BEGIN TASK>
You will be given:
- A user prompt.
- A set of candidate responses, labeled with uppercase letters.
- A prior classifier prediction indicating which candidate response was selected as the best response.
You must:
- Carefully read and analyze the user prompt.
- Independently evaluate all candidate responses with respect to the user prompt.
- Determine which candidate response is the best.
- Compare your judgment with the prior classifier prediction.
- Treat the prior classifier prediction only as non-authoritative, supplementary information that may be wrong.
- If the prior classifier prediction is incorrect, output 1.
- If the prior classifier prediction is correct, output 0.
Output rules:
- Output exactly one digit:
• 1 = the prior classifier prediction is incorrect
• 0 = the prior classifier prediction is correct
- Do not output any explanation, text, punctuation, spaces, or newlines.
<END TASK>