FRAGBENCH: MULTI-SESSION CYBER ATTACKS HIDDEN IN BENIGN-LOOKING FRAGMENTS

Anonymous authors
Paper under double-blind review

ABSTRACT

Production LLM safety guardrails check one request at a time, yet documented cyber campaigns are already decomposed across many requests. A request that appears legitimate can therefore contribute to a harmful operation whose purpose is only apparent from the broader campaign. We introduce **FragBench**, a benchmark that includes attacks based on reported cyber campaigns, split across multiple model API requests to be executed in separate agent sessions. A catalogue of 35 cyber-incident and threat-report entries informs 24 campaign templates. The construction pipeline generates fragments and records their dependencies, safety-judge verdicts, tool activity, and execution-checker outcomes. Judge-guided iterated rewriting increases mean bypass from 59.4% to 74.6% on the evaluated subset. Classifiers trained on malicious and benign MCP executions achieve event F1 up to 0.876. FragBench supports analysis of both attack execution and detectability by retaining failed attempts alongside successful runs. We release the benchmark and evaluation code at https://anonymous.4open.science/r/fragbench-FE86/.

1 INTRODUCTION

Large language models are becoming ever more capable at code generation and cybersecurity (Anthropic, 2026), and these capabilities are dual-use: a model that helps a developer write an infrastructure script can also help an attacker create a data-exfiltration pipeline, a ransomware workflow, or exploitation tooling (Anthropic, 2025b;a; Google Threat Intelligence Group, 2025; Microsoft, 2025; Fang et al., 2024; Bhatt et al., 2024b). Threat-intelligence reports document a growing range of LLM-assisted cyber activity (Google Threat Intelligence Group, 2025; 2026; Microsoft, 2025; Microsoft Threat Intelligence, 2026b;a; SentinelLABS, 2025; Palo Alto Networks Unit 42, 2025). While public incident reports describe the operations of real cyber campaigns, for security reasons detailed data is not released, making it challenging for researchers to replicate aspects of campaigns and innovate on defenses against them.

Offensive cyber campaigns proceed through many different stages, but these stages do not need to be executed all in one session. An attacker can give an agent one task, open a new session for the next, and carry results forward through files or other shared resources. We call this setting *multi-session fragmentation*. Prior benchmarks study decomposition within a single model context (Li et al., 2024; Kang et al., 2024), threats across generated conversations (Azarafrooz, 2026), and decomposed executable tasks (Kothamasu et al., 2026).

In our work, we introduce **FragBench**, a dataset to address this gap with realistic attacks that are split across multiple sessions with no shared context. FragBench consists of 24 incident-informed campaign templates built from a catalogue of 35 cyber-incident and threat-report entries, covering 22 MITRE ATT&CK techniques. Each template specifies an objective, a pre-split sequence of requests we call *fragments*, and the artifacts intended to connect them across sessions. The requests and session boundaries are our reconstructions, not captured attacker inputs. We build multi-session benign workflows to complete our dataset.

We use FragBench to ask two primary questions: whether fragments pass safety checks when seen one at a time, and whether the execution of those fragments carries out an attack. We execute both malicious and benign sessions in a sandbox with a custom Model Context Protocol (MCP) server, recording isolated safety-judge verdicts, and a checker examines the state of the system after

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: FragBench starts with campaign templates informed by public reports. Each campaign is divided into requests linked by artifacts and executed across separate agent sessions. We record isolated judge decisions and sandbox execution, then use the execution traces in a detection analysis.

execution to decide whether the task was completed. We then iterate on the attack prompts by rewriting them iteratively to increase the proportion that pass safety checks and also successfully execute in our sandbox. Rewriting raises mean judge bypass from 59.4% to 74.6% on the evaluated subset. Because attack chains involve multiple steps, it can take some iteration before we create a chain that completes end-to-end.

As a secondary analysis, we characterize how difficult it is to detect attack campaigns amongst benign data from just a set of fragments. We build interaction graphs from tool events across both malicious and benign execution traces. Then, we evaluate graph classifiers on induced graphs and tabular classifiers on graph-derived features, reporting event-level detection performance. Trace-based detectors separate the classes (event F1 up to 0.876), though the workload gap limits how much of that separation can be attributed to campaign structure. The two classes differ in session count, tool-call volume, and argument length, so we report these workload differences alongside the detection scores. Figure 1 shows an overview of our setup.

In our preliminary evaluation, guardrail models evaluated in GuardBench (Bassani & Sanchez, 2024) accepted all tested attack fragments when presented individually. These checks therefore failed to identify the malicious campaigns from their isolated requests. This motivated Detectability Analysis: we execute fragments in separate MCP sessions and examine their tool-use traces together, linking events through shared resources and other interaction features. We ask whether these records reveal campaign activity that are missed by isolated safety checks.

Contributions:

- **Incident-informed benchmark.** FragBench constructs 24 executable campaign templates from a 35-entry source catalogue covering 22 MITRE ATT&CK techniques, fragmented so that no single request ought to trip a per-prompt safety monitor (§3). Realistic benign data is created from tasks structured similarly to the attack examples, fragmented into pieces (§3).
- **Execution validation.** We create a Model Context Protocol (MCP) server to execute actions. This pipeline is used to validate malicious, benign, and attempted attack prompts, checking for executability and side effects in a sandbox (§4). (§6).
- **Attack framework.** We use judge-guided iterative rewriting with MCP execution validation to produce adversarially optimized fragments. Outputs aim to evade the single-session monitors and also succeed in executing within the sandbox (§4). We separate judge bypass from actor compliance and objective completion (§6).
- **Detectability after fragmentation.** We explore how difficult it is to detect cyber campaigns amongst a set of fragments that all look benign on their own. We test several detection ap-

proaches, including per-prompt judges, graph-free trace classifiers, and user-level trace-graph classifiers. We stress-test any apparent signal with multiple ablations (§5–§6). The attack and detection experiments share a corpus but are evaluated independently: the rewriter receives no detector feedback.

- **Responsible tiered release.** Following security-benchmark best practice (Mazeika et al., 2024; Chao et al., 2024), our seed campaigns, generated variants, and benign data are public; rewriter-hardened fragments are gated for access only by vetted researchers.

2 Related Work

LLM security benchmarks. CyberSecEval 1–4 (Bhatt et al., 2024a;b; Wan et al., 2024; Meta Llama, 2025) introduced compliance and false-refusal-rate metrics for cyber safety evaluation. RedCode (Guo et al., 2024), HarmBench (Mazeika et al., 2024), Cybench (Zhang et al., 2024), CVE-Bench (Zhang et al., 2025), AgentHarm (Andriushchenko et al., 2024), and CyberGym (UC Berkeley RDI, 2025) extend this work with execution-based, agentic, and CVE-grounded tasks. FragBench focuses on incident-informed campaign constructions executed across independent sessions, retaining the links between requests and their tool activity.

Decomposition attacks. DrAttack (Li et al., 2024), Kang et al. (Kang et al., 2024), Glukhov et al. (Glukhov et al., 2023), and SneakyPrompt (Yang et al., 2024) split harmful requests into benign-looking sub-prompts, but they reassemble those sub-prompts inside a single context window, often with the model performing the reassembly. FragBench evaluates fragments in separate sessions and checks their execution through sandboxed MCP tools.

Cross-session and decomposition benchmarks. CSTM-Bench (Azarafrooz, 2026) evaluates cross-session threat detection using conversations generated from session-level objectives. DeCompBench (Kothamasu et al., 2026) constructs harmful tasks from executable capabilities and evaluates decomposed requests against monolithic objectives. FragBench complements these benchmarks with incident-informed cyber campaigns executed in independent MCP sessions and records of the dependencies between actions.

Graph-based abuse detection. Graph methods are widely used in adversarial detection: anti-money-laundering (Weber et al., 2019; Lo et al., 2023), fraud-ring detection, and sockpuppet or Sybil detection (Yang et al., 2020; Eksombatchai et al., 2018). Our detector follows this line of work. It uses typed message passing over a tool-use-event graph with user and session metadata, using standard architectures: GCN (Kipf & Welling, 2017), GraphSAGE (Hamilton et al., 2017), GAT (Veličković et al., 2018), GIN (Xu et al., 2019), and edge-type-aware aggregation (Schlichtkrull et al., 2018). We use these established architectures as baselines for classifying campaign traces.

Real-world LLM cyber campaigns. Recent incident reports show that LLM-assisted cyber activity is no longer hypothetical: AI-orchestrated espionage and ransom operations (Anthropic, 2025b;a), iterative malware refinement (OpenAI, 2025a), live LLM-in-malware and self-modifying payloads (Google Threat Intelligence Group, 2025; 2026), large increases in phishing and deepfake fraud (Microsoft, 2025), and underground malicious-LLM markets (SentinelLABS, 2025; Palo Alto Networks Unit 42, 2025). We use these reports as the basis for our data generation; the full catalogue is in Appendix F.

Single-turn and multi-turn jailbreaks. Single-turn jailbreaks optimize one prompt and measure success on each model call: GCG (Zou et al., 2023), PAIR (Chao et al., 2023), TAP (Mehrotra et al., 2023), and Skeleton Key (Russinovich, 2024). Multi-turn attacks rely on a shared chat history. Crescendo (Russinovich et al., 2024) and many-shot jailbreaking (Anil et al., 2024) steer the conversation across turns; Foot-In-The-Door (Weng et al., 2025) and Kumarappan and Mujoo (Kumarappan & Mujoo, 2025) turn psychological escalation into reproducible attack templates. Collections of in-the-wild jailbreaks (Shen et al., 2024) and automated prompt generation methods (Liu et al., 2023) also study per-prompt evasion. FragBench evaluates execution across sessions without shared conversation history.

Red-teaming methodology and kill chains. We frame our rewriter as a judge-targeted instance of prompt-space search, in the tradition of open-ended adversarial generation (Samvelyan et al., 2024), lessons from red-teaming at product scale (Bullwinkel et al., 2025), threat-model formalization (Verma et al., 2024), and computer-use-agent red-teaming (Liao et al., 2025); critiques of

red-teaming as evaluation (Feffer et al., 2024) motivate our scoping of the defense as a measurement of one failure mode rather than a security guarantee.

3 Dataset Construction

FragBench starts with malicious campaigns informed by public reports and splits them into requests designed to appear benign in isolation. The pre-execution dataset contains these attack fragments, their campaign objectives, and their intended dependencies. MCP execution then produces tool calls, results, and checker outcomes. We distinguish these execution traces from the generated requests that produced them. Separately, benign workflows provide controls for detection: unlike benign-looking attack fragments, they have legitimate objectives.

3.1 Real-World Source Campaigns

We searched several public sources for real-world cyber attack campaigns, focusing on those likely to have been LLM-assisted. We catalogued 35 cyber-incident and threat-report entries and used them to construct 24 executable campaign templates: some reports merge into a single campaign, some yield no readily executable campaign, and some contribute multi-stage chains (the source-incident catalogue appears in Appendix F; a complete report-to-campaign-to-variant mapping remains necessary for provenance auditing). Of the 24 campaigns, 13 have attacker LLM use directly observed (vendor platform telemetry or LLM API calls in deployed malware), 5 have vendor-inferred LLM use or evidence limited to an undeployed malware artefact, and 6 have unconfirmed LLM involvement (per-entry detail in Appendix F). Table 9 in Appendix A lists source organisations and campaign counts.

The threat taxonomy defines five overlapping scenarios: ATK-01 Data Exfiltration, ATK-02 AI-Assisted Ransomware, ATK-03 AI-Generated Malware, ATK-04 Supply-Chain Operation, and ATK-05 Vulnerability Exploitation (Tables 11 and 22). For each campaign, we wrote a seed prompt describing the publicly documented stages that could be represented as a single-agent task. These are sandbox reconstructions, not reproductions of the original incidents.

3.2 Constructing Benign-Looking Attack Fragments

We turn the incident-informed seed prompts into executable campaign variants in four steps:

1. **Specify the campaign.** For each seed, we define variables for filenames, domains, IP addresses, and URLs. These substitutions vary surface identifiers while retaining the intended operation.
2. **Separate the requests.** Claude Opus pre-splits each seed into 4–16 fragments. We store the split in a seed file and retain the campaign objective for evaluation. Static splits make dependencies easier to review.
3. **Preserve dependencies.** The seed records which artifacts each fragment produces and consumes. An intermediate file can carry an earlier stage's output into a later session, even though the actor's conversation history starts afresh. These links specify the intended execution chain.
4. **Expand and execute.** Campaign-specific substitutions generate variants, and the styles below change how requests are presented. We retain deterministic expansions and Claude Haiku expansions under the same seed structure. The attack pipeline then evaluates judge acceptance and sandbox execution separately (§4).

Fragment style disguises. We defined ten styles that can be used to make fragments look more legitimate (`direct`, meaning no disguise, is the basic style).[1] These are based on common prompting and jailbreaking techniques. We used only six of the ten in most of our experiments; the others performed poorly. The styles are a starting point for the attack, which we later improve through iterative adversarial rewriting (§4); see Figure 2 (Appendix A). The seed and result JSON schemas are listed in Appendix E (Tables 13, 14). Result files are deterministic or LLM expansions of the seeds; see `Makefrag` in the repository.

[1] Full style list: `direct`, `command_form`, `sysadmin`, `developer`, `educational`, `ctf`, `compliance_audit`, `oblique_technical`, `hidden_intent`, `helpdesk`.

Table 1: Campaign data retained by the framework and the questions it supports. Detailed schemas appear in Appendix E.

Record	Contents	Evaluation use
Campaign seed	Source references, objective, stages, and variation variables	Inspect how a reported scenario was reconstructed.
Fragment plan	Individual requests and produced/consumed artifacts	Follow dependencies across separate sessions.
Session trace	Tool calls, arguments, results, and session identifiers	Distinguish requested actions from observed execution.
Evaluation records	Judge verdicts and checker outcomes with justifications	Separate request acceptance from checked task progress.

Quality control. Every seed result was reviewed by a second author against the original source report. The review checked that each seed (a) represented a similar scenario, (b) was split into appropriate fragments, and (c) had appropriate linkage between those fragments.

What the dataset retains. A campaign record connects the intended operation to its requests and observed tool activity (Table 1). The records support inspection of failed stages and alternative analyses of the same events. Although the schemas include source references, a complete report-to-variant mapping and run manifests are still needed for provenance auditing.

3.3 A Campaign Construction Example

QuietVault illustrates the construction process. Google reports that the malware used locally installed AI command-line tools to search an infected host for secrets and sent collected data to public GitHub repositories (Google Threat Intelligence Group, 2025). Our reconstruction defines six stages with two fragments each: workflow analysis, local collection, AI-assisted discovery, transfer, access verification, and impact. These requests and session boundaries are benchmark specifications, not observed attacker inputs.

Each fragment starts with a fresh conversation history; the seed's *produces* and *consumes* fields link sessions through artifacts. One workflow-analysis fragment creates an audit file and the next updates it; the local-collection pair writes and extends a collector module, while access-verification notes feed the impact stage.

3.4 Benign Controls for Detection

Control specifications. We use Claude Opus to generate 24 benign workflow specifications for ordinary IT and office work, including onboarding, storage-inventory reconciliation, and compliance review. These specifications describe requested tasks, not observed tool activity. Seed definitions and variants are expanded deterministically across six styles and nine random seeds, with no model calls at expansion time.

Control execution. Each fragment runs in a separate session using the same actor, selected MCP toolkit, Docker sandbox, and tracer as the malicious objectives (§4). Detection uses the resulting tool-use traces. Running both classes through this pipeline standardises trace collection, but their workloads still differ (Table 3).

Combining malicious and benign data. Execution outcomes use a larger evaluation cohort of 1,440 malicious and 1,296 benign chains (§6.1); the detection analysis uses the 692-malicious/514-benign collection described here. A simplified format with an `is_malicious` flag and a triple-nested `sessions` field (chains, fragments, tool uses) feeds the re-writer and detector; the full schema is in Appendix E. Benign expansion defines $24 \times 6 \times 9 = 1{,}296$ objectives, executed as 1,417 chains. We remove 46 pilot chains collected before the final harness configuration and 75 repeat executions, leaving one chain per (campaign, style, seed) triple. We then select 514 chains by campaign-stratified sampling. This benign cohort contains 5,440 sessions and 77,176 events. The malicious detection collection contains 692 chains from 24 campaigns, with 6,488 sessions and 55,274 events. Of these chains, 124 have no recorded events; the remaining 568 contribute to event-level detection and the workload statistics in Table 3.

4 FRAGBENCH ATTACK

FragBench Attack rewrites the disguised fragments from §3.2 using safety-judge feedback. It then tests the fragments in an MCP sandbox. Both rewriting and manual repairs retain the campaign's kill-chain plan.

Stage 1 – iterative adversarial rewriting against the safety judge A safety judge J assesses each fragment separately and returns $\ell_i \in \{\text{REFUSE}, \text{ALLOW}, \text{AMBIGUOUS}\}$. The attack has two objectives: each fragment must pass the judge, $\forall i : \ell_i = \text{ALLOW}$, and the fragments must compose into the campaign objective, $E(\bigoplus_{i=1}^{n} f_i) \models o$, where $E(\cdot)$ is the MCP executor (§4). Rewriting targets judge acceptance; Stage 2 checks execution. An attempted run may fail either condition.

Model parameters remain fixed during rewriting. After each attempt, the judge supplies an explanation and a score: $+1$ for ALLOW, -1 for REFUSE, or $+0.3$ for AMBIGUOUS. The loop stops when all fragments pass or the round budget runs out. We handle execution failures through manual seed repairs in Stage 2; these failures are not fed back to the rewriter. The loop tries three rewriting phases in order for each blocked fragment:

1. **Bootstrap (rule-based warm-start).** Four hand-coded transformations: KEYWORD_REPLACE (offensive lexicon → defensive analogue), LEGITIMACY_PREFIX (e.g., "As part of an authorised engagement, ..."), STRUCTURAL_REFRAME (active malicious verb → passive observational form), SPLIT_AND_ABSTRACT (one fragment into two narrower fragments).
2. **In-context rewriting.** Sonnet 4.6 uses successful bootstrap rewrites as examples and applies the same transformation type to the blocked fragment.
3. **Free-form rewriting.** The LLM uses the accumulated examples without a fixed transformation template. We compare rewriters and judges in §6 (Table 10).

Stage 2 – Execution validation in the MCP sandbox Stage 2 runs accepted fragments in an isolated MCP sandbox with mock targets. An *actor* receives one fragment at a time, calls tools, and reads their results. A separate *checker* assesses completion from the original campaign goal, ordered fragments, and execution logs. A chain passes only if the checker marks every fragment successful. Reported execution rates include failed attempts.

Execution checks and evaluation boundaries. Judge acceptance, tool invocation, error-free execution, and checker-assessed completion are distinct outcomes: an accepted request may invoke no tool or fail because an earlier session did not create a required artifact. The actor sees only its current fragment and session history, while sandbox artifacts can persist across sessions and the checker sees the campaign goal and execution logs. Missing logs or tool activity do not establish refusal; failure-type frequencies are not reported. Chain success requires every fragment to pass the checker, without an independent final-state measurement. Rewriting and execution use separately reported cohorts, so their rates cannot be multiplied into an end-to-end attack-success probability.

MCP configuration. The execution evaluation uses `qwen/qwen3.5-122b-a10b` (*actor* model) through OpenRouter at temperature 0.6, with provider-default top-p and at most 16,000 output tokens per turn. Each fragment starts a separate session with a 16-iteration agent-loop budget; an iteration may contain multiple tool calls. The actor does not receive the full campaign goal. Its system prompt assigns a penetration-testing assistant persona (Hack The Box CLI), with no reported additional safety instructions or weight modifications. Results therefore reflect this persona rather than the model's default safety configuration. `Claude Sonnet 4.6` (*checker* model) checks fragment completion from the logs. Reproduction requires the exact provider revisions and archived prompts.

Harness and patching. The Docker Compose harness routes calls through FastMCP to 24 sandboxed MCP servers sourced from (reinthal, 2026). It records all events in `.jsonl` logs (Table 15). Appendix D lists the servers, architecture, and manual repairs for four execution failure types. Repairs change only the seed text, which is then rerun through Stage 1 and submitted for execution again. There is no automated rewriting after MCP execution.

5 DETECTABILITY ANALYSIS

A fragment may appear benign in isolation, yet contribute to a malicious outcome across multiple sessions. We introduce Detectability Analysis to investigate this gap in per-request safety checks

by linking tool-use events across sessions and assessing whether their combined activity reveals a malicious campaign.

We classify tool-use events from malicious and benign MCP executions using four graph neural networks (GCN, GraphSAGE, GAT, GIN) and three tabular classifiers (SVM, MLP, GBT). All seven receive graph-derived information. Typed edges represent call/result dependencies, temporal order, session membership, shared resources, and argument similarity; a union-find procedure groups linked events into candidate chains. Model and feature details appear in Appendix C.

The labels indicate membership in a constructed malicious campaign, not independently verified harmfulness of each event. The comparison does not isolate the contribution of cross-session links, and workload differences may influence predictions (§7). Exact run configurations and split manifests remain necessary for reproduction.

6 Results

We evaluate attack rewriting and trace-based detection separately.

6.1 Attack Results

Judge bypass. The rewriting evaluation covers three campaigns (DPRK_FRAUD, PROMPTSTEAL, QUIETVAULT), six styles, three judges, and five rewriters, with 183 reported evaluated cells. Mean pass rate increases from 59.4% before rewriting to 74.6% after ten rounds (median 91.5%). GPT-5.4 and GPT-5.4-mini yield approximately no improvement over baseline. These results concern the evaluated subset, not all campaign categories. The pairing/style experiment in Table 10 uses Opus 4.6, whereas the three-campaign evaluation in Table 2 uses Opus 4.7; these configurations are reported separately.

Execution outcomes. The execution evaluation covers 1,440 malicious and 1,296 benign chains (Table 2); these rates are distinct from the detection analysis on 692 malicious and 514 benign chains. Although 95.4% of executed malicious calls return without an MCP error, only 8.5% of malicious chains have every fragment pass the checker. Chain completion cannot be inferred by exponentiating mean fragment success because fragment outcomes need not be independent. Checker verdicts concern sandbox tasks, not completion against real targets or under a safeguarded frontier actor.

Table 2: Attack results for separately evaluated rewriting and execution cohorts. Execution covers 1,440 malicious (M) and 1,296 benign (B) chains. Each execution row names its denominator; these rates cannot be multiplied into an end-to-end success probability.

Rewriting: 3 campaigns, 183 cells

Judge bypass	**Result**
Before rewriting (mean)	59.4%
After ten rounds (mean / median)	74.6% / 91.5%
Sonnet 4.6 / DeepSeek V4	85–90%
Opus 4.7 judge	66.1%
GPT-5.4 / GPT-5.4-mini change	≈ 0

MCP execution outcomes

Outcome (%)	**M**	**B**
Fragments invoking $\geq$1 tool	89.8	100
Executed calls without MCP error	95.4	96.7
Fragments passing checker	65.9	83.4
Chains with every fragment passing	8.5	26.9

6.2 Detection Results

Table 4 summarizes detectability on executed traces. GAT attains the highest event F1 (0.876), followed by GraphSAGE (0.858). All seven models receive graph-derived features, so the tabular classifiers are not graph-free controls. The comparison measures discrimination of the constructed classes, not verified recognition of malicious composition. Historical per-campaign results with non-executed benign controls are reported separately in Appendix H.

Table 3: Detection-cohort workload statistics on 568 nonempty malicious (M) and 514 benign (B) chains; 124 empty malicious chains are excluded. d is Cohen's effect size.

Property	M	B	d
Sessions per chain	8.2	10.6	−0.85
Tool calls per chain	48.7	75.1	−0.97
Chain length (fragments)	9.6	10.6	−0.44
Argument p90 (chars)	6,944	3,216	+0.86
JSON argument fraction	1.00	1.00	0.00
Resource reuse per chain	0.42	0.59	−0.90
Median call gap (seconds)	2.4	2.8	−0.18
Tool-call success rate	.954	.967	−0.23

Table 4: Event-level detectability on executed malicious and benign traces. Available recall/FPR operating-point summaries are reported in Table 7.

Model	F1	Acc.
GCN	.821	.847
GraphSAGE	.858	.877
GIN	.834	.857
GAT	.876	.893
MLP	.720	.789
SVM	.673	.722
GBT	.831	.863

6.3 Multi-session signal

The graph-free probe and edge ablation (Tables 5–6) use the same executed cohort of 692 malicious and 514 benign chains as Table 4, but retain only its 66,225 tool-call events rather than all 132,450 call and result events. These probes use a different, campaign-disjoint split, with 13,858 held-out tool-call events; because both the event representation and split differ, their F1 scores are not directly comparable with Table 4. We probe whether the interaction graph is doing work beyond aggregating per-event attributes. A graph-free classifier that pools a user's whole trace is already strong: GBT reaches event F1 0.893, and performance rises monotonically as pooling coarsens (0.764 per event, 0.830 per session, 0.893 per run). This is a genuinely competitive baseline, and we do not claim the graph is necessary to separate the classes. On this same campaign-disjoint split, the full graph retains a margin over the graph-free user aggregate — GAT reaches 0.935 — and does so while deciding per event rather than once per run, but the gap is 0.042, not the difference between success and failure. The edge ablation locates the signal: within-session edges alone recover most of the full-graph score (0.913 for GAT), removing all edges collapses it (0.701), and cross-session edges add a smaller increment on top of within-session structure. Content-similarity edges (ARGUMENT_SIMILARITY) are marginally harmful, likely linking superficially similar arguments across unrelated sessions. We therefore frame cross-session aggregation as providing information unavailable to isolated per-prompt checks, not as a demonstration that graph structure is required to detect fragmentation.

Table 5: Graph-free controls on the tool-call events of the same executed MCP cohort as Table 4 (campaign-disjoint split: 5 of 24 malicious campaigns held out in full, benign events partitioned at random; 13,858 held-out test tool-call events (6,140 malicious and 7,718 benign; 44.3% malicious)). Graph-free classifiers use per-event attributes only (capability one-hot, argument entropy, non-printable ratio, argument length, hashed tool identity), pooled at three granularities and assigning one prediction per group. Graph rows use the full interaction graph on the same split. This split differs from the executed-cohort split in Table 4 and the scores should not be pooled with it.

Detector (aggregation)	**SVM**	**MLP**	**GBT**
Graph-free, per event	.717	.730	.764
Graph-free, session pooling	.797	.792	.830
Graph-free, user aggregate	.870	.867	.893
Full graph (best GNN, GAT)		**.935**	

Precision sensitivity to event prevalence. We separately project precision from the event-level operating points of the executed-cohort harness run underlying Table 4, rather than from the tool-call ablation above. For malicious-event prevalence π, recall r, and false-positive rate f, precision is $\pi r/[\pi r + (1-\pi)f]$. Table 7 applies this identity at fixed operating points, assuming that the class-conditional detection rates remain unchanged as prevalence varies. The $\approx 42\%$ column uses $\pi = 0.42$ as a rounded reference for the detection collection's malicious-event fraction ($55{,}274/132{,}450 \approx 41.7\%$), distinct from the tool-call test split's 44.3%; 5% and 1% are illustrative lower-prevalence scenarios, not measured deployment rates. At this detection-cohort event fraction, the displayed recall/FPR pairs imply F1 and accuracy within 0.001 of the corresponding values in Table 4; rounded summaries do not reproduce every entry exactly. At 1%, GAT's projected preci-

Table 6: Edge-type ablation on the executed MCP cohort (same corpus and split as Table 5; 66,225 tool-call events, 958,816 edges, 68% cross-session). Each row removes one edge set. Event-level F1.

Edges retained	**GraphSAGE**	**GAT**	**GCN**	**GIN**
Full graph	.919	.935	.893	.705
Within-session only	.898	.913	.829	.874
Cross-session only	.815	.829	.808	.791
Drop SHARED_RESOURCE	.889	.897	.828	.823
Drop ARGUMENT_SIMILARITY	.925	.945	.899	.787
No edges	.688	.701	.711	.659

sion is 0.076, or about twelve false positives per true positive. These projections motivate treating detection as a secondary analysis of campaign-associated signal: benchmark F1 alone does not establish a usable deployment alarm. Practical triage utility also remains unvalidated, since it depends on review capacity, user-level aggregation, and whether the measured operating points transfer to deployment.

Table 7: Precision sensitivity to event prevalence using operating points from the executed-cohort harness evaluation in Table 4. Recall and FPR are reported per event. GIN and MLP are omitted because their recall/FPR pairs were not reported in the available operating-point summary. Precision is analytically projected from the displayed rounded rates, holding each model's operating point fixed; these are neither new evaluations nor user-level precision estimates.

			Precision at event prevalence		
Model	**Recall**	**FPR**	**≈42%**	**5%**	**1%**
GAT	.900	.111	.854	.299	.076
GBT	.810	.100	.854	.299	.076
GraphSAGE	.887	.130	.832	.264	.064
GCN	.839	.147	.805	.231	.055
SVM	.687	.253	.663	.125	.027

7 LIMITATIONS

The executed classes differ in session count, tool-call volume, argument length, and resource reuse (Table 3). Running both classes through the same MCP pipeline controls trace collection but does not match the work performed. Detectors may exploit these workload differences; joint workload matching, graph-free controls, and edge ablations are needed to distinguish them from signals of malicious composition. Section 6.3 projects precision under lower event prevalence, but user-level deployment performance remains unmeasured. Run-level provenance, exact classifier configurations, and uncertainty across repeated runs remain incomplete. No detector-adaptive attack or objective-completion measurement under a safeguarded frontier actor is reported. The sandbox scenarios are incident-informed reconstructions; rewriter-hardened prompts are restricted through gated access.

8 CONCLUSION

FragBench provides executable reconstructions of cyber campaigns fragmented across independent agent sessions. Its records connect campaign plans to observed tool activity, allowing researchers to examine acceptance, execution failures, and detectability separately. Rewriting improves acceptance by the evaluated judges, but execution checks reveal that accepted requests do not always complete their tasks. Detection performance varies across campaigns and may partly reflect workload differences. The benchmark supports further study of these failures and comparison of methods on the same campaign records.

REPRODUCIBILITY STATEMENT

Dataset construction is described in Section 3 (schemas in Appendix E, source catalogue in Appendix F, harness in Appendix D). Model versions and settings for the rewriter, judges, actor, and checker are in Section 4 and Appendix C, with classifier details in Appendix C. As is standard for security datasets (Mazeika et al., 2024; Chao et al., 2024), FragBench is published in two tiers on HuggingFace. The public tier contains seed campaigns, generated variants, and benign data: https://huggingface.co/datasets/anon-fragbench/fragbench. The gated tier contains fragments hardened by a rewriter, available to vetted safety researchers via HuggingFace's request-access mechanism: https://huggingface.co/datasets/anon-fragbench/fragbench-restricted. The code used for the project is available at the anonymous repository https://anonymous.4open.science/r/fragbench-FE86/.

ETHICS STATEMENT

FragBench supports defensive evaluation of misuse spread across agent sessions. Experiments use synthetic task data and mock targets in a Docker/MCP sandbox, with no human participants or attacks on real systems. Public threat reports inform our reconstructions; we do not redistribute raw report text. Sandboxing limits direct harm during evaluation, but campaign structures and rewriting methods could be adapted for misuse outside the sandbox. The tiered release described above restricts access to rewriter-hardened fragments while supporting defensive research; it does not eliminate the residual misuse risk of the public artifacts.

AI USE STATEMENT

We used generative AI to help implement the experiments, generate campaign variants and benign workflow specifications, and draft and revise the paper. We also used it to review related work and discuss the research framing and interpretation of results. The experimental models and their roles in rewriting, judging, execution, and completion checking are described in the methods sections. The authors reviewed the AI-assisted work and are responsible for the paper's methods, data, results, and claims.

REFERENCES

M. Andriushchenko et al. AgentHarm: A benchmark for measuring harmfulness of LLM agents, 2024.

C. Anil et al. Many-shot jailbreaking. Technical report, Anthropic, 2024.

Anthropic. Model context protocol. https://modelcontextprotocol.io/, 2024.

Anthropic. Detecting and countering malicious uses of Claude: August 2025. Technical report, Anthropic, August 2025a.

Anthropic. Disrupting the first reported AI-orchestrated cyber espionage campaign. Technical report, Anthropic, November 2025b.

Anthropic. System Card: Claude Mythos Preview. https://www-cdn.anthropic.com/08ab9158070959f88f296514c21b7facce6f52bc.pdf, 2026.

Ari Azarafrooz. Cross-session threats in ai agents: Benchmark, evaluation, and algorithms, 2026. URL https://arxiv.org/abs/2604.21131.

Elias Bassani and Ignacio Sanchez. GuardBench: A large-scale benchmark for guardrail models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 18393–18409, November 2024.

M. Bhatt et al. Purple Llama CyberSecEval: A benchmark for evaluating the cybersecurity risks of large language models. Technical report, Meta AI Research, 2024a.

M. Bhatt et al. CyberSecEval 2: A wide-ranging cybersecurity evaluation suite for large language models, 2024b.

Blake Bullwinkel et al. Lessons from red teaming 100 generative ai products. *arXiv preprint arXiv:2501.07238*, 2025.

P. Chao, E. Debenedetti, A. Robey, M. Andriushchenko, F. Croce, V. Sehwag, E. Dobriban, N. Flammarion, G. J. Pappas, F. Tramèr, H. Hassani, and E. Wong. JailbreakBench: An open robustness benchmark for jailbreaking large language models, 2024.

P. Chao et al. Jailbreaking black box large language models in twenty queries, 2023.

C. Eksombatchai et al. Pixie: A system for recommending 3+ billion items to 200+ million users in real-time. In *Proceedings of WWW*, 2018.

R. Fang et al. Teams of LLM agents can exploit zero-day vulnerabilities, 2024.

Michael Feffer, Anusha Sinha, Wesley Hanwen Deng, Hoda Heidari, and Zachary C. Lipton. Red-teaming for generative ai: Silver bullet or security theater? *arXiv preprint arXiv:2401.15897*, 2024.

D. Glukhov et al. LLM censorship: A machine learning challenge or a computer security problem?, 2023.

Google Threat Intelligence Group. GTIG AI threat tracker: Advances in threat-actor usage of AI tools. Technical report, Google Threat Intelligence Group, November 2025.

Google Threat Intelligence Group. GTIG AI threat tracker: Distillation, experimentation, and (continued) integration of AI for adversarial use. Technical report, Google Threat Intelligence Group, February 2026.

K. Guo et al. RedCode: Risky code execution and generation benchmark for code agents. In *Proceedings of NeurIPS*, 2024.

W. L. Hamilton et al. Inductive representation learning on large graphs. In *Proceedings of NeurIPS*, 2017.

D. Kang et al. Exploiting programmatic behavior of LLMs: Dual-use through standard security attacks. In *Proceedings of IEEE SaTML*, 2024.

T. N. Kipf and M. Welling. Semi-supervised classification with graph convolutional networks. In *Proceedings of ICLR*, 2017.

Vikhyath Kothamasu, Virginia Smith, and Chhavi Yadav. Hidden in plain sight: Benchmarking agent safety against decomposition attacks with DeCompBench, 2026. URL https://arxiv.org/abs/2606.13994.

Adarsh Kumarappan and Ananya Mujoo. Automating deception: Scalable multi-turn LLM jailbreaks. In *NeurIPS 2025 Workshop on Multi-Turn Interactions in Large Language Models*, 2025.

X. Li et al. DrAttack: Prompt decomposition and reconstruction makes powerful LLMs jailbreakers. In *Findings of EMNLP*, 2024.

Yuxuan Liao et al. Redteamcua: Realistic adversarial testing of computer-use agents. *arXiv preprint arXiv:2505.21936*, 2025.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. Autodan: Generating stealthy jailbreak prompts on aligned large language models. *arXiv preprint arXiv:2310.04451*, 2023.

W. W. Lo et al. Inspection-L: Self-supervised GNN node embeddings for money laundering detection in Bitcoin. *Applied Intelligence*, 2023.

M. Mazeika et al. HarmBench: A standardised evaluation framework for automated red teaming and robust refusal, 2024.

A. Mehrotra et al. Tree of attacks: Jailbreaking black-box LLMs automatically, 2023.

Meta Llama. Purple Llama CyberSecEval: A Secure Coding Benchmark for Large Language Models. https://meta-llama.github.io/PurpleLlama/CyberSecEval/, 2025.

Microsoft. Microsoft digital defense report 2025. Technical report, Microsoft, October 2025.

Microsoft Threat Intelligence. Threat actor abuse of AI accelerates from tool to cyberattack surface. Microsoft Security Blog, April 2026a.

Microsoft Threat Intelligence. AI as tradecraft: How threat actors operationalize AI. Microsoft Security Blog, March 2026b.

OpenAI. Disrupting malicious uses of AI: June 2025. Technical report, OpenAI, June 2025a.

OpenAI. Disrupting malicious uses of AI: October 2025. Technical report, OpenAI, October 2025b.

OpenAI. Disrupting malicious uses of AI: February 2026. Technical report, OpenAI, February 2026.

Palo Alto Networks Unit 42. The dual-use dilemma of AI: Malicious LLMs. Unit 42, November 2025.

reinthal. Red-APT. https://github.com/reinthal/Red-APT, 2026. GitHub repository, accessed March 7, 2026.

M. Russinovich. Mitigating Skeleton Key, a new type of generative AI jailbreak technique. Microsoft Security Blog, June 2024.

M. Russinovich et al. Great, now write an article about that: The Crescendo multi-turn LLM jailbreak attack, 2024.

Mikayel Samvelyan et al. Rainbow teaming: Open-ended generation of diverse adversarial prompts. *arXiv preprint arXiv:2402.16822*, 2024.

M. Schlichtkrull et al. Modeling relational data with graph convolutional networks. In *Proceedings of ESWC*, 2018.

SentinelLABS. Prompts as code & embedded keys: The hunt for LLM-enabled malware. SentinelLABS, September 2025.

Xinyue Shen, Zeyuan Chen, Michael Backes, Yun Shen, and Yang Zhang. "do anything now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models. In *ACM CCS*, 2024.

UC Berkeley RDI. CyberGym: Evaluating AI agents' real-world cybersecurity capabilities. Technical report, UC Berkeley Research Center for Decentralized Intelligence, 2025.

P. Veličković et al. Graph attention networks. In *Proceedings of ICLR*, 2018.

Apurv Verma et al. Operationalizing a threat model for red-teaming large language models. *arXiv preprint*, 2024.

A. Wan et al. CyberSecEval 3: Advancing the evaluation of cybersecurity risks and capabilities in large language models. Technical report, Meta AI Research, 2024.

M. Weber et al. Anti-money laundering in Bitcoin: Experimenting with graph convolutional networks for financial forensics. In *KDD AMLD Workshop*, 2019.

Zixuan Weng, Xiaolong Jin, Jinyuan Jia, and Xiangyu Zhang. Foot-in-the-door: A multi-turn jailbreak for LLMs. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1939–1950. Association for Computational Linguistics, 2025.

K. Xu et al. How powerful are graph neural networks? In *Proceedings of ICLR*, 2019.

K.-C. Yang et al. Scalable and generalizable social bot detection through data selection. In *Proceedings of AAAI*, 2020.

Y. Yang et al. SneakyPrompt: Jailbreaking text-to-image generative models. In *Proceedings of IEEE Security and Privacy*, 2024.

A. K. Zhang et al. Cybench: A framework for evaluating cybersecurity capabilities and risks of language models, 2024.

Y. Zhang et al. CVE-Bench: A benchmark for AI agents' ability to exploit real-world web application vulnerabilities, 2025.

A. Zou et al. Universal and transferable adversarial attacks on aligned language models, 2023.

Table 8: **PROMPTSTEAL/LAMEHUG worked example.** One campaign objective is assembled from 11 fragments across five stages.

#	Sub-task	Artifact flow: consumes → produces	MCP server	Judge	Checker
Stage 0: Initial access	T1566 (spearphishing)				
1	Draft lure	∅ → `draft_file`	`filesystem`	ALLOW	✓
2	Edit lure	`draft_file` → `draft_file`	`filesystem`	ALLOW	✓
3	Dispatch	`draft_file` → ∅	`email`	ALLOW	✓
Stage 1: Discovery	T1082 (system information)				
4	Make staging	∅ → `staging_dir`, `output_file`	`shell`	ALLOW	✓
5	Recon to staging	`staging_dir` → ∅	`shell`	ALLOW	✓
Stage 2: Discovery	T1087.002 (AD accounts)				
6	Query AD	`staging_dir` → `ad_output_file`	`shell`	ALLOW	✓
7	Write AD output	`ad_output_file` → ∅	`shell`	ALLOW	✓
Stage 3: Collection	T1074.001 (local staging)				
8	Enumerate docs	`staging_dir` → `file_list`	`filesystem`	ALLOW	✓
9	Copy to staging	`file_list` → ∅	`shell`	ALLOW	✓
Stage 4: Exfiltration	T1041 (over C2 channel)				
10	Compress	`staging_dir` → `archive_file`	`archive`	ALLOW	✓
11	Upload	`archive_file` → ∅	`exfil`	ALLOW[†]	✓[‡]

Notes. Artifact flows define the released `artifact_chain`. Judge reports the Stage-1 single-turn verdict for each released fragment; Checker reports its Stage-2 MCP execution verdict. [†]The upload fragment was initially refused, then allowed after a STRUCTURAL_REFRAME rewrite. [‡]The assembled execution satisfies the campaign objective o: harvest documents from a compromised host and move them off it. Fragment prompts are withheld.

Table 9: Source organizations whose threat-intelligence reports provided the basis for our campaign corpus. Per-entry details are in Appendix F. We study a total of 24 campaigns.

Source	**#**	**Attacks in our dataset**
Anthropic Threat Intelligence (Anthropic, 2025a;b)	4	GTG-1002, GTG-2002, AI RaaS, DPRK IT Fraud
Google GTIG AI Threat Trackers (Google Threat Intelligence Group, 2025; 2026)	7	PROMPTSTEAL, PROMPTFLUX, QUIETVAULT, HONESTCUE, COINBAIT, ClickFix, Op. Dream Job
Microsoft Threat Intelligence (Microsoft, 2025; Microsoft Threat Intelligence, 2026b;a)	5	Coral Sleet, Jasper Sleet, Tycoon2FA, AI phishing 4.5×, Deepfake ID fraud
OpenAI Threat Intelligence (OpenAI, 2025a;b; 2026)	3	ScopeCreep, RU malware clusters, Op. False Witness
SentinelLABS / Unit 42 (SentinelLABS, 2025; Palo Alto Networks Unit 42, 2025)	2	MalTerminal, WormGPT/KawaiiGPT
Public incident reports / generic	3	London Drugs / LockBit, Nova Scotia Power, Active Directory discovery

A Source Catalogue and Full Attack Results

The full attack bypass grid (Table 10) supplements the attack summaries in §6.



Figure 2: Examples of the six rewriting styles that we used to disguise attack fragments.

Table 10: Showing guardrail bypass rate of some of our malicious data when it is optimized by LLM rewriter models. Style columns: cmd=`command_form`, aud=`compliance_audit`, dir=`direct`, edu=`educational`, hlp=`helpdesk`, sys=`sysadmin`. DeepSeek=DeepSeek V4 Flash, Llama-4=Llama Guard 4.

			Style					
Campaign	**Rewriter**	**Judge**	cmd	aud	dir	edu	hlp	sys
DPRK FRAUD	Sonnet 4.6	Sonnet 4.6	100.0(+0.6)	100.0(+18.1)	100.0(+31.9)	100.0(+16.2)	100.0(+8.1)	100.0(+15.0)
		Opus 4.6	100.0(+4.4)	100.0(+19.4)	100.0(+39.4)	100.0(+28.7)	100.0(+3.1)	100.0(+40.6)
	Opus 4.6	Sonnet 4.6	100.0(+1.2)	100.0(+20.6)	96.9(+30.0)	99.4(+16.2)	100.0(+6.9)	100.0(+15.0)
		Opus 4.6	100.0(+4.4)	100.0(+21.9)	96.9(+35.6)	96.2(+26.3)	100.0(+0.6)	96.9(+40.6)
	DeepSeek	Llama-4	100.0(+5.6)	100.0(+2.5)	100.0(+2.5)	100.0(0.0)	100.0(+10.0)	100.0(+0.6)
		Sonnet 4.6	100.0(+0.6)	99.4(+16.2)	100.0(+33.1)	100.0(+18.1)	100.0(+5.0)	100.0(+14.4)
		Opus 4.6	100.0(+4.4)	99.4(+17.5)	98.8(+36.9)	100.0(+32.5)	100.0(+0.6)	100.0(+41.2)
PROMPTSTEAL	Sonnet 4.6	Sonnet 4.6	100.0(+12.3)	100.0(+25.9)	99.1(+28.6)	100.0(+25.0)	100.0(+22.7)	100.0(+14.1)
		Opus 4.6	98.6(+11.4)	99.6(+40.9)	95.0(+44.5)	99.6(+39.1)	99.6(+25.5)	97.7(+44.5)
	Opus 4.6	Sonnet 4.6	99.6(+12.3)	99.1(+25.4)	99.1(+27.7)	98.6(+24.1)	100.0(+22.7)	100.0(+13.6)
		Opus 4.6	96.8(+9.5)	95.5(+36.4)	96.4(+49.1)	97.3(+36.4)	96.8(+21.8)	96.4(+44.5)
	DeepSeek	Llama-4	93.2(+29.1)	90.5(+31.8)	93.6(+30.5)	92.7(+3.2)	95.9(+76.8)	97.3(+4.5)
		Sonnet 4.6	99.1(+11.8)	98.6(+25.9)	99.6(+25.5)	99.6(+25.0)	99.6(+22.7)	98.6(+15.5)
		Opus 4.6	99.1(+11.8)	96.8(+35.9)	93.2(+45.4)	97.7(+35.0)	96.4(+22.7)	90.9(+37.3)

B THREAT TAXONOMY

This appendix indexes the five overlapping threat scenarios used to organize generator objectives o (Table 11). These scenarios are informed by the 35-entry source catalog, catalogued in Appendix F; the construction pipeline that consumes them is in §3.

Table 11: Attack-scenario summary used as objectives for the generator. ✓ = attacker LLM use directly observed (vendor platform telemetry or LLM API calls in deployed malware); ∼ = likely attacker LLM use, vendor-inferred from artifacts; unmarked = LLM involvement unknown or unconfirmed (artifact-only samples, attacker tools, or aggregate statistics). See Appendix F for per-entry justification.

ID	Scenario	TTPs	Sessions	Key Real-World Evidence
ATK-01	Data Exfiltration	9	6	GTG-1002 ✓; PROMPTSTEAL/APT28 ✓; QUIETVAULT ✓; Chinese APT vs. Vietnam ✓
ATK-02	AI-Assisted Ransomware	9	9	GTG-2002 ✓; AI RaaS ✓; ScopeCreep ✓; MalTerminal; PROMPTFLUX; WormGPT/KawaiiGPT
ATK-03	AI-Generated Malware	7	6	HONESTCUE ✓; PROMPTSTEAL ✓; ScopeCreep ✓; Russian clusters ✓; PROMPTFLUX; MalTerminal
ATK-04	Supply-Chain Operation	10	many	DPRK IT fraud ✓; ClickFix ✓; APT42 ✓; UNC2970 ✓; GTG-1002 ✓; COINBAIT ∼; AI phishing 4.5×; Deepfake fraud +195%
ATK-05	Vuln. Exploitation	5	4	GTG-1002 ✓; Fang et al. (academic CVE study); Hexstrike-AI (unconfirmed forum claim)

C IMPLEMENTATION DETAILS

Combined attack/detector format. Finally, a simplified format with both malicious and benign data was created for iterative rewriting in FragBench Attack (§4). Each file contains an `is_malicious` flag, a `sessions` field holding a triple-nested list (chains, fragments, tool uses), and—for the malicious file only—a parallel `malicious_source` array recording each chain's `run_id`, `seed`, `campaign`, `campaign_id`, and source `attack_graph_file`.

Style generator and adversarial rewriter (§3.2, §4). Style rephrasing: `claude-haiku-4-5-20251001`, T=0, max 256 tokens. Default adversarial rewriter: Sonnet 4.6, T=0, max 1024 tokens, three candidate variants per refused fragment, ten-round budget. Rewriter sweeps also include Opus 4.6 and DeepSeek; judge settings are described below and reported in Table 10. Async fan-out bounded by an asyncio semaphore at `--max-concurrency 8`. Sensitive system prompts are included in the gated release; model and runtime settings are summarised here.

Single-turn-prompt safety judges (§4). We evaluate the rewriter loop with Claude Sonnet 4.6, Claude Opus 4.6, and Llama Guard 4 as single-turn judges (Table 10). Each judge returns one of ALLOW, REFUSE, or AMBIGUOUS; the ternary reward $\{+1, -1, +0.3\}$ for allow/refuse/ambiguous feeds the rewriter's strategy memory.

MCP execution validator (§4). Twenty-four tool servers under `fragbench/fragbench_mcp/` (`shell`, `filesystem`, `archive`, `exfil`, `cloud_recon`, `credential`, `ssh_bruteforce`, `payload_evasion`, `report_server`, ...). Network egress restricted to a private RFC-1918 range with mock targets. The harness is designed to reset scratch state between assemblies; run-level checks are needed to establish that all writable paths were reset. Every LLM call is appended to a per-run JSONL audit log under `logs/<timestamp>.jsonl`.

Executed-cohort classifier configuration. The reported classifiers are GCN, GraphSAGE, GIN, GAT, MLP, SVM, and GBT. Their executed-cohort run manifests must specify the feature schema, graph boundaries, preprocessing, hyperparameters, train/validation/test assignments, and threshold selection. These details should be attached to the reported outputs before the results are treated as independently reproducible.

D MCP EXECUTION HARNESS

Harness. We use a modular Docker Compose architecture that separates the host-resident LLM from a sandboxed internal execution environment. A central `mcp-client` ingests campaign JSON files and routes tool calls to a fleet of 24 specialised MCP servers (see Table 12 for full list – sourced from (reinthal, 2026)) via FastMCP. Each server runs in its own Docker container on an isolated network. All session events are captured as structured `.jsonl` logs (see Table 15 for schema) and served through a viewer at port 8787. The harness runs a 16-iteration agent loop for each fragment. Figure 3 shows the architecture of this simulated tool environment (Anthropic, 2024).

Patching MCP-rejected fragments. Iterative rewriting is not used after MCP. The harness writes a JSONL session log per run, and when MCP rejects an assembly we open the log, identify one of four failure modes, and patch the seed by hand:

- `session_missing`: resolved `session_path` does not exist. Typically, fix a previous fragment.
- `parse_error`: session JSONL could not be parsed. Truncate the bad line and rerun.
- `no_tool_calls`: session has zero `tool_call`/`tool_result` events; the model never invoked any MCP tool. Restore the imperative verb in the seed prompt (*run*, *open*, *post* instead of *review*, *consider*, *outline*).
- `no_tool_results`: `tool_call(s)` present but no `tool_result` events. Add the missing produce in the upstream fragment's seed so the artefact exists when this fragment reads it.

After the patch, the seed is re-run through Stage 1 of FragBench Attack and then re-submitted to MCP. The patch only changes the seed text; the rest of the pipeline is untouched.



Figure 3: MCP harness architecture. A central `mcp-client` ingests campaign JSON files, selects the attack based on the style and seed, and routes tool calls to a fleet of 24 specialised MCP servers via FastMCP (HTTP + SSE). All agent interactions are captured as structured `.jsonl` session logs served through a viewer at port 8787. Support is available for self-hosted LLMs as well as those accessed via openrouter.



(a) Live view.



(b) Graph view.

Figure 4: MCP validation frontend views. The Live view streams fragment execution in real time, including MCP agent sessions, model responses, tool calls, and intermediate status. The Graph view summarizes completed validation runs by campaign phase and reports per-fragment pass/fail outcomes, judge rationales, tool executions, and artifact dependencies used for downstream defense analysis. The green color represents fragments that passed the LLM Judge's evaluation for having completed the task and the red ones represent those that failed.

Table 12: MCP toolkit servers in the Docker Compose environment. Each server handles a distinct capability area and runs in an isolated container.

Service	Role
server-filesystem	Filesystem discovery and collection on a mock read-only tree
server-shell	Sandboxed command synthesis and execution simulation
server-archive	Archive and staging simulation
server-exfil	Exfiltration simulation (HTTP/SFTP-style)
server-network-recon	Network recon and host inventory simulation
server-recon-osint	OSINT-style reconnaissance
server-recon-network	Extended network recon and scanning
server-recon-subdomain	DNS and subdomain enumeration
server-recon-web	Web application reconnaissance
server-cloud-recon	Cloud-style reconnaissance
server-git	Git operations
server-code	Code analysis and editing helpers
server-packages	Package management helpers
server-project	Project scaffold, build, and test helpers
server-credential	Credential handling and validation
server-crypto	Cryptography helpers
server-terminal	Terminal and process-style execution
server-ssh-bruteforce	SSH brute-force simulation
server-c2-callback	Mock C2 callback-style execution
server-report	Reporting and aggregation
server-payload-evasion	Payload mutation and evasion
server-vuln-scanner	Vulnerability scan simulation
server-agent-control	Agent control and stateful prompt tools
server-email	Mock email server without real SMTP delivery

Table 13: Seed file schema (`seeds/<campaign>.json`). Each seed is a campaign template: a metadata block citing threat-intel sources, variables for variations, and an ordered list of attack stages.

Layer (path)	Fields
top	`metadata`, `variation_dimensions`, `attack_stages[]`
`metadata`	`id`, `technique`, `technique_name`, `description`, `tags[]`, `source_reports[]` (id/title/date/url)
`variation_dimensions[*]`	`source` (cite), `values[]` (list of allowed values)
`attack_stages[*]`	`index`, `mitre_tactic`, `mitre_technique`, `description`, `evidence`, `baseline_prompt`, `variation_dimensions_used[]`, `variables`, `fragments[]`
`...variables[*]`	`type` ∈ {`dimension_driven`, `choice`, `filename`, `inherit`}, plus type-specific keys (`values_by_dimension`, `values`, `name_pool`, `from_stage`)
`...fragments[*]`	`fragment_index`, `role`, `prompt` (sub-template), `produces[]`, `consumes[]` (artifact dependencies for chain closure)

E Output Artifact Schemas

Running a fragment chain through the MCP sandbox produces three artifact types: per-fragment session logs (§4), per-chain attack-verdict files, and per-chain attack-graph files (consumed by the detector graph builder). Their on-disk schemas are tabulated below. The seed and result JSON schemas referenced from §3.2 are repeated here (Table 14 and 15) for convenience.

F Real-World Cyber-Incident Catalogue

Tables 18–21 detail the 35 cyber-incident and threat-report entries referenced in §3.1. Each entry is coded by evidence of attacker LLM use: ✓ = directly observed (vendor platform telemetry or LLM API calls in deployed malware), ∼ = likely (vendor-inferred from artifacts), blank = unknown or unconfirmed. Tables 18–20 list 27 source entries referencing possible LLM use (18 observed, 4

Table 14: Result file schema (`results/<campaign>_{manual,llm}.json`). Each result file expands one seed template into multiple realized kill-chain instances.

Layer (path)	Fields
top	`campaign`, `base_seed`, `num_variations`, `variations[]`
`variations[*]`	`campaign_id` (`<id>_<seed>`), `seed`, `metadata` (subset of seed metadata), `total_fragments`, `fragments[]`
`...fragments[*]`	`fragment_index`, `role`, `parent_tactic`, `parent_prompt` (resolved with substituted variables), `produces[]`, `consumes[]`, `variations[]`
`...fragments[*].variations[*]`	`style` (one of ten values), `prompt` (stylised fragment text)

Table 15: Session-log schema (`logs/session_<ts>_<id>.jsonl`). JSONL with one event per line. Every event carries the envelope fields (`seq`, `ts`, `event`, `session_id`); each `event` type adds its own payload.

Event	Payload fields
`session_start`	`schema_version`, `model`, `server`, `backend`, `run_id`, `campaign`, `attack_id`, `toolkit_set[]`, `pid`, `source_ip`, `stage_index`, `variation_index`, `style`
`toolkits_connected`	`toolkit_set[]`
`user_query`	`query`, `message_count`
`iteration_start`	`iteration`, `message_count`, `available_tools[]`, `tool_count`, `thread_id`
`llm_response_received`	`iteration`, `content_preview/full`, `thinking_preview/full`
`assistant_response`	`iteration`, `has_content`, `content_preview/full`, `thinking_preview/full`, `has_thinking`, `tool_calls[]`, `tool_call_details[]`, `tool_call_count`, `is_final`
`tool_call`	`iteration`, `tool`, `arguments`, `arguments_bytes`, `tool_call_index`
`tool_result`	`iteration`, `tool`, `success`, `result_preview`, `result_bytes`, `tool_result_index`
`verdict`	`verdict` $\in$ {`ANSWERED`, `REFUSED`, ...}, `classifier` $\in$ {`keyword`, `llm_judge`}, `justification`, `raw_judge_response`
`session_end`	`total_events`

likely, and 5 unmarked entries where LLM involvement is plausible but not confirmed: artifact-only samples never seen deployed, attacker tools, or aggregate statistics). Table 21 lists 8 stress-test cases where LLM involvement is not claimed; the generator must produce a plausible benign-looking decomposition for each.

G MITRE TTP Coverage

The generator covers 22 MITRE ATT&CK techniques. Coverage is enumerated below; the same technique may be invoked by multiple ATK scenarios. Each technique is annotated with real-world incident evidence used to motivate the generator (per-entry evidence tier in Appendix F).

Table 22: MITRE ATT&CK techniques in scope of the generator.

TTP	Technique	Tactic	Real-world incident evidence
T1046	Network Service Discovery	Discovery	GTG-1002, Hexstrike-AI, PROMPTSTEAL, QUIETVAULT.
T1110	Brute Force	Cred. Access	GTG-1002 automated credential harvesting at scale.
T1059	Command Scripting	Execution	HONESTCUE (in-memory C#), MalTerminal (runtime payload).
T1486	Encrypt for Impact	Impact	AI RaaS (ChaCha20), MalTerminal (AES-CBC at runtime).
T1566	Spearphishing	Init. Access	AI phishing $4.5\times$, APT42, COINBAIT React-SPA kit.

Table 22 continued

TTP	Technique	Tactic	Real-world incident evidence
T1190	Exploit Public App	Init. Access	GTG-1002 wrote own exploits; Hexstrike-AI Citrix 0-day claim.
T1555	Browser Credentials	Cred. Access	ScopeCreep credential-stealer component.
T1490	Inhibit Recovery	Impact	AI RaaS standard recovery-inhibition module.
T1027	Obfuscated Files	Def. Evasion	PROMPTFLUX hourly Gemini-driven re-obfuscation.
T1588.007	Obtain Capab.: AI	Resource Dev.	All 22 incidents with observed/likely attacker LLM use; WormGPT/KawaiiGPT market.
T1592	Gather Host Info	Recon	UNC2970 Gemini-driven defence-sector profiling.
T1078	Valid Accounts	Pers./Init. Acc.	DPRK IT fraud, GTG-1002 credential reuse, deepfake liveness bypass.
T1055	Process Injection	Def. Evasion	HONESTCUE in-memory compile-and-execute; MalTerminal.
T1547	Boot/Logon Autostart	Persistence	PROMPTFLUX writes regenerated variant to Startup folder.
T1562	Impair Defenses	Def. Evasion	AI RaaS RecycledGate + FreshyCalls direct syscalls.
T1497	Sandbox Evasion	Def. Evasion	AI RaaS sandbox / debugger-evasion module from Claude.
T1591	Gather Victim Org Info	Recon	GTG-2002 financial analysis for ransom calibration; UNC2970, APT42.
T1068	Exploit for Priv Esc	Priv. Esc.	GTG-1002 autonomous priv-esc identification.
T1053	Scheduled Task/Job	Persistence	GTG-1002 backdoor persistence; PROMPTFLUX hourly cycle.
T1048	Exfil Over Alt. Protocol	Exfil.	GTG-1002 SCP-based exfil; QUIETVAULT to public GitHub repos.
T1489	Service Stop	Impact	AI RaaS service-termination module.
T1041	Exfil Over C2	Exfil.	ScopeCreep Telegram C2; GTG-2002 double-extortion exfil.

Table 16: Attack-verdict schema (`results/runs/attack_..._<CAMPAIGN>_<n>.json`). One record per chain run with fragment-level pass/fail verdicts.

Layer (path)	Fields
top	`run_id`, `seed`, `campaign`, `campaign_id`, `style`, `fragments_path`, `started_at`, `ended_at`, `passed` (chain-level), `target_model`, `target_backend`, `llm_product`, `judge_model`, `generated_at`, `fragments[]`
`fragments[*]`	`fragment_index`, `role`, `phase`, `prompt` (resolved fragment text issued to the target), `produces[]`, `consumes[]`, `passed`, `verdict` ∈ {`PASS`, `FAIL`}, `classifier`, `justification`, `raw_judge_response`

Table 17: Attack-graph schema (`results/runs/attack_graph_..._<CAMPAIGN>_<n>.json`). Extends the attack-verdict record with per-fragment tool execution traces, artifact resolution, timing, and a pointer back to the raw session JSONL. This is the source of truth consumed by the detector graph builder.

Layer (path)	Fields
top	`run_id`, `campaign`, `style`, `fragments_path`, `started_at`, `ended_at`, `target_model`, `target_backend`, `llm_product`, `judge_model`, `variation`
`variation`	`user_id`, `seed`, `style`, `campaign`, `campaign_id`, `campaign_source`, `campaign_date`, `campaign_description`, `llm_product`, `llm_backend`, `llm_model`, `judge_model`, `duration_hours`, `num_total_fragments`, `num_attack_fragments`, `num_cover_fragments`, `phases_in_order[]`, `started_at`, `ended_at`, `fragments[]`
`...fragments[*]`	`fragment_id`, `fragment_index`, `phase`, `phase_index`, `role`, `style`, `prompt`, `produces[]`, `consumes[]`, `is_cover`, `passed`, `verdict`, `classifier`, `justification`, `raw_judge_response`, `started_at`, `ended_at`, `duration_ms`
`...fragments[*]` (cont.)	`tools_executed[]` (list of `[tool, *args]`), `final_response` (assistant text), `artifacts_resolved` (artifact → paths), `artifacts_found` (artifact → bool), `session_path` (back-pointer to raw JSONL log)

Table 18: Cyber-incident reports referencing LLM use, Part 1 of 3. Evidence column: ✓ = directly observed; ∼ = likely (vendor-inferred); blank = unknown.

#	Campaign	Source	LLM Product	Key Capability	Ev.
Anthropic Threat Intelligence					
1	GTG-1002 Espionage	Nov 2025	Claude Code	Autonomous ops, 80–90% AI-executed	✓
2	GTG-2002 Extortion	Aug 2025	Claude Code	AI-calibrated ransom (>$500K)	✓
3	AI RaaS Developer	Aug 2025	Claude	Zero-skill → ransomware vendor	✓
4	DPRK IT Fraud	Aug 2025	Claude	Identity fraud at Fortune 500	✓
5	Chinese vs. Vietnam	Aug 2025	Claude	9-month sustained campaign	✓
Google GTIG AI Threat Trackers					
6	PROMPTSTEAL/APT28	Nov 2025	Qwen2.5 via HF	First LLM queried in live attack	✓
7	PROMPTFLUX	Nov 2025	Gemini 1.5 Flash	Hourly self-modifying malware (under-development sample)	
8	HONESTCUE	Feb 2026	Gemini API	Fileless C# payload in memory	✓
9	QUIETVAULT	Nov 2025	On-host AI CLI	Weaponised victim's own AI	✓
10	COINBAIT/UNC5356	Feb 2026	Lovable AI	AI-generated phishing kit (use inferred from artifact style)	∼

Table 19: Cyber-incident reports referencing LLM use, Part 2 of 3. Evidence column as in Table 18.

#	Campaign	Source	LLM Product	Key Capability	Ev.
Google GTIG AI Threat Trackers (cont.)					
11	APT42 phishing	Feb 2026	Gemini	Multi-turn rapport building	✓
12	UNC2970 / Lazarus profiling	Feb 2026	Gemini	Defence-sector targeting	✓
13	ClickFix via AI chat	Feb 2026	Multiple[a]	Trusted domains as attack infra	✓
OpenAI Threat Intelligence					
14	ScopeCreep	Jun 2025	OpenAI models	Iterative RAT refinement	✓
15	Russian malware clusters	Oct 2025	OpenAI models	Malware development & distribution	✓
SentinelLABS / Unit 42					
16	MalTerminal	Sep 2025	GPT-4	Runtime payload gen (PoC only; not seen deployed)	
17	WormGPT/KawaiiGPT	Nov 2025	Custom/ uncensored	Underground malicious-LLM market (tool, not attack)	
Microsoft Threat Intelligence (MDDR 2025)					
18	AI phishing 4.5×	MSFT MDDR 2025	Generic AI	54% vs. 12% click-through (aggregate statistic)	
19	Deepfake ID fraud	MSFT MDDR 2025	Generic AI	195% growth (aggregate statistic)	

[a]Gemini, ChatGPT, Copilot, DeepSeek, Grok

Table 20: Cyber-incident reports referencing LLM use, Part 3 of 3. Evidence column as in Table 18.

#	Campaign	Source	LLM Product	Key Capability	Ev.
OpenAI Threat Intelligence (Feb 2026)					
20	Op. Trolling Stone	OpenAI Feb 2026	ChatGPT	Russia-linked IO; Spanish-language articles	✓
21	Op. No Bell	OpenAI Feb 2026	ChatGPT	Likely RU IO; long-form Africa commentary	✓
22	Op. Date Bait	OpenAI Feb 2026	ChatGPT	Cambodia romance/task scam targeting Indonesians	✓
23	Op. False Witness	OpenAI Feb 2026	ChatGPT	Fake legal-service personas + forged documents	✓
Microsoft Threat Intelligence (Mar–Apr 2026)					
24	Coral Sleet (DPRK)	MSFT Mar 2026	AI coding tools	AI-assisted iterative malware development (vendor-inferred)	∼
25	Emerald Sleet (DPRK)	MSFT Mar 2026	LLMs (generic)	CVE research (vendor-inferred)	∼
26	Jasper Sleet (DPRK)	MSFT Mar 2026	Faceswap + AI	Remote-IT-worker fraud; AI-generated identities	✓
27	Tycoon2FA / Storm-1747	MSFT Mar/Apr 2026	Unspecified	Phishing-as-a-service; AiTM MFA bypass	∼

Table 21: Stress-test cases: real-world cyber incidents with no claimed LLM involvement (evidence tier "unknown"). Kill-chains are decomposed into benign-appearing prompts to stress-test the generator.

#	Incident	Attacker	Target	Impact	Key LLM-Acceleration Point
28	Nova Scotia Power (Mar 2025)	Unidentified (likely Russia)	Canadian utility	280K customers	37-day dwell; utility-specific systems
29	London Drugs / LockBit (Apr 2024)	LockBit	Canadian pharmacy	79 stores, 9 days	Corporate-to-retail cascade
30	Change Healthcare / ALPHV (Feb 2024)	ALPHV/ BlackCat	US healthcare	190M people, $3.1B	9-day lateral movement; 6 TB exfil
31	Covenant Health / Qilin (May 2025)	Qilin	US hospitals	478K patients	8-day stealth; 852 GB exfil
32	St. Paul, MN / Interlock (Jul 2025)	Interlock	US municipality	State of emergency	ClickFix initial access; 43 GB leaked
33	M&S + Co-op + Harrods (Apr 2025)	Scattered Spider	UK retailers	$592M combined	Sector wave; NTDS.dit theft
34	Yale New Haven Health (Mar 2025)	Unidentified	US hospitals	5.5M patients	Stealth exfil without encryption
35	RedCurl / Gold Blade (2024–2025)	RedCurl	Canadian firms	80% Canada	Espionage-to-ransomware pivot

H Historical Detection Results with Non-Executed Benign Controls

Table 23 preserves the earlier per-campaign evaluation, in which malicious traces were executed but benign records were generated without MCP execution. These results use a different negative class and evaluation split from the executed-cohort results in the main text and are not directly comparable with them.

Table 23: Per-campaign detection results. This earlier evaluation uses generated benign records without MCP execution and is separate from the executed-cohort results. Columns: per-campaign F1 and Accuracy at the event level on held-out test events under a 70/30 outer-sample stratified split, for four GNN architectures (GCN, GraphSAGE, GAT, GIN) and three classical-ML baselines (SVM, MLP, GBT). For each campaign the detector is evaluated against the campaign's positive events plus all benign test events.

	GCN		GraphSAGE		GAT		GIN		SVM		MLP		GBT	
Campaign	F1	Ac	F1	Ac	F1	Ac	F1	Ac	F1	Ac	F1	Ac	F1	Ac
ad_discovery	.814	.946	.783	.934	.756	.926	.740	.917	.582	.846	.626	.864	.578	.845
ai_phishing	.598	.948	.534	.934	.508	.927	.473	.916	.314	.846	.346	.861	.323	.847
clickfix_via_ai_chat	.573	.944	.522	.930	.482	.922	.472	.914	.310	.844	.352	.860	.287	.840
coinbait	.265	.947	.210	.932	.194	.926	.166	.914	.108	.845	.118	.859	.107	.845
coral_sleet	.742	.950	.692	.936	.668	.930	.641	.920	.470	.850	.504	.865	.475	.850
deepfake_id_fraud	.424	.947	.363	.933	.340	.927	.316	.916	.187	.846	.201	.859	.186	.845
dprk_fraud	.661	.946	.600	.932	.572	.925	.538	.914	.384	.846	.418	.861	.383	.845
gtg1002	.814	.947	.778	.934	.757	.927	.733	.917	.596	.851	.629	.867	.589	.849
honestcue	.706	.948	.654	.935	.628	.928	.599	.918	.433	.848	.461	.862	.434	.848
jasper_sleet	.712	.947	.645	.931	.624	.925	.604	.916	.431	.845	.471	.861	.444	.847
london_drugs_lockbit	.618	.945	.552	.931	.530	.925	.512	.915	.357	.847	.376	.860	.342	.844
malterminal	.721	.945	.681	.932	.651	.925	.628	.915	.458	.845	.497	.861	.465	.846
nocode_ransomware	.474	.947	.420	.933	.398	.927	.366	.916	.235	.847	.249	.860	.229	.846
ns_power_ransomware	.672	.946	.611	.932	.584	.925	.559	.915	.395	.846	.429	.861	.388	.845
operation_false_witness	.649	.944	.597	.931	.553	.922	.522	.911	.367	.843	.423	.861	.384	.845
promptflux	.537	.946	.480	.932	.450	.925	.410	.914	.268	.844	.289	.858	.260	.843
promptsteal	.730	.945	.685	.932	.657	.924	.638	.915	.452	.842	.495	.859	.430	.837
quietvault	.805	.946	.769	.934	.745	.926	.717	.915	.570	.847	.614	.865	.562	.845
ru_malware_clusters	.771	.951	.727	.937	.706	.931	.669	.920	.517	.853	.552	.868	.515	.852
scope_creep	.335	.946	.290	.933	.253	.925	.237	.915	.130	.844	.146	.858	.127	.843
tycoon2fa	.732	.948	.681	.935	.651	.927	.614	.916	.438	.844	.477	.860	.452	.847
unc2970_operation_dream_job	.063	.947	.051	.932	.047	.926	.041	.915	.023	.845	.025	.859	.019	.844
vibe_extortion	.590	.947	.536	.934	.514	.928	.475	.916	.324	.848	.341	.861	.305	.845
wormgpt_kawaiigpt	.590	.946	.533	.933	.510	.927	.474	.915	.308	.845	.338	.860	.306	.844

Per-campaign results in the earlier evaluation with generated, non-executed records vary substantially. GCN reaches F1 of 0.814 on AD Discovery and GTG1002, and 0.805 on QuietVault. No evaluated classifier exceeds 0.335 on Scope Creep, 0.265 on Coinbait, or 0.063 on UNC2970 Operation Dream Job. These campaigns remain difficult under the evaluated methods even with linked traces available. Sample size, class prevalence, and construction differences limit conclusions about the causes of low F1.