SAFETYFLIP: LEARNING LLM SAFETY BOUNDARIES FROM BIDIRECTIONAL COUNTERFACTUAL INSTRUCTIONS

Anonymous authors
Paper under double-blind review

ABSTRACT

Balancing helpfulness and safety in large language models (LLMs) remains challenging: imprecise safe/unsafe boundaries can cause both unsafe compliance and over-refusal of safe but sensitive requests. We propose **SafetyFlip**, a data-centric framework that learns LLM safety boundaries from bidirectional counterfactual instructions. SafetyFlip constructs semantically matched Safe↔Unsafe pairs with structured boundary annotations identifying the preserved non-safety semantic frame, the safety-critical factor, and the required policy behavior. These pairs are used for **Boundary-Constrained Fine-Tuning (BCFT)**, which combines supervised fine-tuning with Safety Contrastive Regularization (SCR) to encourage safety-relevant representation shifts while preserving shared non-safety utility. On Qwen2.5-7B, SafetyFlip reduces HarmBench attack success from 58.4% to **6.5%** while keeping XSTest over-refusal low at **2.1%** and preserving MT-Bench utility. Our work offers a scalable, low-supervision pathway for boundary-aware alignment without inference-time overhead. Our code is available at: https://anonymous.4open.science/r/SafetyFlip.

1 INTRODUCTION

Large language models (LLMs) exhibit strong fluency and broad task coverage (Dubey et al., 2024; OpenAI, 2024), but they can still comply with unsafe instructions and produce misinformation, hate speech, or unsafe procedural advice (Mazeika et al., 2024; Wang et al., 2024a; Röttger et al., 2025; Chao et al., 2024). Conversely, aggressive safety alignment can make models over-refuse safe but sensitive requests (Pan et al., 2025a). These two failure modes—unsafe compliance and over-refusal—are not independent: both suggest that the model has learned an imprecise safety boundary, where surface cues are conflated with user intent. The central challenge is therefore not simply to increase refusal, but to teach LLMs to distinguish unsafe compliance from legitimate assistance near the safe/unsafe boundary (Meng et al., 2024; Dai et al., 2024; Qi et al., 2023; Zhang et al., 2024b).

Existing alignment methods improve safety from different angles, including human-feedback optimization (Wang et al., 2024b; Dai et al., 2024), rule- or principle-based self-critique (Bai et al., 2022), and




Figure 1: **Illustration of the safety boundary and bidirectional SafetyFlip.** SafetyFlip synthesizes boundary-local instruction pairs that cross the safety boundary in both directions (Safe↔Unsafe) while preserving the non-safety semantic frame (e.g., domain, task form, and recoverable benign utility). The dashed arrow (*"w/o SafetyFlip"*) depicts the conventional over-refusal failure mode, where models default to blunt rejection rather than constructive engagement.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

safety-oriented supervised tuning. However, these methods are typically trained with supervision that is sparse, global, or weakly localized around the safe/unsafe decision boundary. Similarly, current safety datasets—whether preference-based (Zou et al., 2023), refusal-tuned (Zhang et al., 2024a), or red-teaming corpora (Alam et al., 2024)—usually assign safety labels to isolated instructions or responses. They rarely provide local safe/unsafe contrast: paired examples that preserve the same non-safety semantic frame—such as domain, entities, task form, style, and constraints—while changing the safety-critical factor that determines the required behavior. Without such contrast, models can learn coarse heuristics such as keyword blacklisting rather than fine-grained, context-aware decision rules (Yang et al., 2024).

Figure 1 illustrates this boundary-local view: minimally edited counterfactual pairs cross the safety boundary in both directions while preserving non-safety semantics. Our key insight is that safety boundaries are best learned from local counterfactual differences. For a prompt x, we seek a nearby counterfactual x^{flip} that preserves the non-safety semantic frame—such as domain, entities, style, task form, and constraints—while flipping the safety-critical factor that determines the required policy behavior. Such a pair serves as a discrete boundary-crossing contrast: it shows what information should remain useful and what change should switch the model from compliance to refusal, or from refusal to a safe pivot. The two directions are complementary: Safe→Unsafe counterfactuals teach the model to detect when benign assistance is converted into unsafe compliance, while Unsafe→Safe counterfactuals teach the model to recover legitimate utility after removing or reframing the unsafe factor.

Building on this idea, we introduce **SafetyFlip**, a framework for constructing and using bidirectional safety-boundary counterfactuals. Given a seed instruction, a multi-agent proposal-and-validation pipeline extracts its non-safety semantic frame and safety-critical factor, proposes a Safe↔Unsafe counterfactual, generates policy-consistent responses, and filters candidates that violate semantic preservation, safety inversion, or response-behavior consistency. The accepted pairs are then used for **Boundary-Constrained Fine-Tuning (BCFT)**, which combines supervised fine-tuning with a lightweight counterfactual boundary regularizer. All generation agents, structured boundary annotations, and auxiliary heads are used only during data construction or training; the deployed model uses the same inference interface as standard fine-tuning.

- We formulate LLM safety alignment as a **local boundary learning** problem and introduce bidirectional safety-boundary counterfactuals that preserve non-safety semantics while flipping safety-critical factors.
- We instantiate this formulation with **SafetyFlip**, a multi-agent proposal-and-validation pipeline that generates high-fidelity instruction–response pairs with structured boundary annotations for policy-consistent boundary supervision.
- We train LLMs with **Boundary-Constrained Fine-Tuning**, combining SFT with a lightweight counterfactual boundary regularizer. Experiments and ablations show that data quality, structured annotations, and counterfactual regularization jointly support sharper safe/unsafe boundary learning.

2 Related Works

Data-Centric Safety and Adversarial Alignment. Safety alignment commonly uses red-teaming to expose vulnerabilities (Mazeika et al., 2024) and unlearning to suppress harmful behaviors (Liu et al., 2024); jailbreak studies further probe failure modes (Chao et al., 2024). Self-alignment methods (e.g., Self-Rewarding LMs) leverage AI feedback (Yuan et al., 2025). Yet existing data rarely provides *semantically matched* safe/unsafe instruction pairs, so preference-style training (e.g., DPO) optimizes $P(y \mid x)$ without directly specifying the boundary of x. SafetyFlip addresses this data gap by constructing bidirectional counterfactual instructions that preserve the non-safety semantic frame while flipping the safety-critical factor that determines the instruction-level safety label, providing local supervision around the safe/unsafe boundary.

Reasoning and Multi-Agent Verification. CoT is increasingly used for safety decisions and can improve policies (Zhang & Parkes, 2023; Chen et al., 2023), but naive rationales may be unreliable or leak unsafe




Figure 2: The overall framework of SafetyFlip. A proposal-and-validation pipeline constructs Safe↔Unsafe counterfactual pairs by preserving the non-safety semantic frame while flipping the safety-critical factor. Accepted pairs provide policy-consistent supervision for Boundary-Constrained Fine-Tuning (BCFT) with Safety Contrastive Regularization (SCR).

content. Multi-agent verification has also been used to improve the consistency and quality of generated data. SafetyFlip uses reasoning and verification for data construction rather than deployment, retaining examples that preserve the non-safety semantic frame while cleanly crossing the safe/unsafe boundary.

Boundary Modeling and Disentanglement. Information Bottleneck has been explored for separating safety factors from content (Pan et al., 2025b; Arditi et al., 2024), while representation engineering separates latent directions via inference-time control (Zou et al., 2025). These methods motivate a separation between safety-critical factors and non-safety semantic frames. SafetyFlip grounds this separation in paired counterfactual instructions, where boundary-crossing safe/unsafe differences provide supervision for boundary learning.

3 METHOD

We present **SafetyFlip**, a data-centric framework that learns LLM safety boundaries by constructing bidirectional counterfactual instructions and using them for **Boundary-Constrained Fine-Tuning (BCFT)** (Figure 2). We define the boundary-learning setup in Section 3.1, then generate validated counterfactual pairs with structured boundary annotations in Section 3.2, and finally learn from them via BCFT in Section 3.3.

3.1 PROBLEM SETUP

We formulate safety boundary learning through a latent factorization of instructions. Each instruction x contains a non-safety semantic frame s and an instruction-level safety label $a \in \text{Safe}, \text{Unsafe}$, with $x = f(s, a)$. The frame s covers domain, entities, task form, style, constraints, and recoverable benign utility; the label a is determined by a safety-critical factor such as a harmful objective, target, operational method, or policy-violating condition. SafetyFlip seeks a counterfactual x^{flip} that flips this safety-critical factor while preserving s, yielding boundary-local pairs that isolate safe/unsafe differences from shared semantics. Formally, the counterfactual construction can be written as a constrained optimization problem:

$$\begin{aligned} x^{\text{flip}} &= \arg\max_{x'} \big[\, \text{Sim}(x', x) \big], \\ \text{s.t. } & \text{Attr}(x') \neq \text{Attr}(x), \quad \text{Preserve}(x', x) \geq \tau_{\text{sem}}, \end{aligned} \tag{1}$$

where $\text{Attr}(\cdot) \in \{\text{Safe}, \text{Unsafe}\}$ denotes the side of the safety boundary assigned to a given sentence, $\text{Sim}(\cdot, \cdot)$ measures semantic similarity, and $\text{Preserve}(\cdot, \cdot)$ checks whether the non-safety semantic frame—including domain, entities, task form, style, and constraints—remains aligned.

Exact optimization over text is intractable, so SafetyFlip implements Eq. 1 as a proposal-and-validation solver. The Reversal Agent proposes candidates conditioned on the preserved frame and flipped safety label, and the

Validation Agent retains only candidates that satisfy semantic-frame preservation, safety-label inversion, and the similarity threshold τ_{sem}.

After obtaining bidirectional instruction pairs (x, x^{flip}), we generate corresponding responses (y, y^{flip}) and retain only pairs whose responses are both safe and policy-consistent with the instruction-level safety label. We use $\text{SafeResp}(y) = 1$ to denote that the response itself does not provide actionable unsafe content:

$$\begin{aligned} &\text{SafeResp}(y) = 1, \\ &\text{Beh}(y, x) = \begin{cases} \text{Comply}, & \text{Attr}(x) = \text{Safe}, \\ \text{Refuse/Pivot}, & \text{Attr}(x) = \text{Unsafe}. \end{cases} \end{aligned} \tag{2}$$

We apply Eq. 2 to both (x, y) and $(x^{\text{flip}}, y^{\text{flip}})$. The final validated sample is therefore $\big((x, y), (x^{\text{flip}}, y^{\text{flip}})\big)$, which supplies local supervision for learning the safe/unsafe boundary.

3.2 Structured Boundary Annotation Pipeline

SafetyFlip operationalizes the counterfactual objective in Eq. 1 through a proposal-and-validation pipeline. The purpose of this pipeline is not to serve as an inference-time safety system, but to synthesize and filter boundary-local safe/unsafe pairs for training. Each generated example is accompanied by a structured boundary annotation, elicited through structured prompting, that records three attributes: the preserved non-safety semantic frame, the safety-critical factor, and the required policy behavior. These annotations are private, non-operational supervision signals: they guide reversal and validation without exposing actionable unsafe steps, reducing semantic drift and superficial label matching.

3.2.1 Agentic Pipeline

SafetyFlip implements this process as a sequential proposal-and-validation pipeline for generating and validating boundary-local data. The pipeline consists of the following components:

- **Analysis Agent (A_{analysis}):** Separates the non-safety semantic frame from safety-critical factors. It extracts the preserved frame s—including domain, entities, task form, style, and constraints—and identifies the instruction-level safety label a. It also produces the structured annotation c, which records the preserved frame, the safety-critical factor, and the required policy behavior while avoiding procedural unsafe details.
- **Reversal Agent (A_{reversal}):** Transforms instruction $x \to x^{\text{flip}}$. Crucially, it accepts the non-safety semantic frame s but conditions the generation on the *reversed* safety label a^{flip} (flipping Safe $\leftrightarrow$ Unsafe). This encourages the query x^{flip} to cross the safe/unsafe boundary while maintaining the shared semantic frame.
- **Answer Agent (A_{answer}):** Generates policy-consistent responses (y, y^{flip}). This agent conditions generation on the instruction and its corresponding structured annotation (generating y from (x, c)), ensuring that safe instructions receive helpful compliance while unsafe instructions receive refusal or safe pivot responses.
- **Validation Agent (A_{validate}):** Serves as a rigorous quality gate that enforces the constraints defined in our objective. It verifies: (i) semantic-frame preservation of s (as formulated in Eq. 1); (ii) correctness of the safety-label inversion; and (iii) consistency between the structured annotation and the policy-consistent response behavior (Eq. 2). Only pairs satisfying all criteria are retained.

The sequential data flow keeps annotation, reversal, response generation, and validation aligned:

$$\begin{aligned} x \xrightarrow{A_{\text{analysis}}} (s, a, c), \qquad (s, a^{\text{flip}}) \xrightarrow{A_{\text{reversal}}} x^{\text{flip}} \xrightarrow{A_{\text{analysis}}} c^{\text{flip}}, \\ (x, c) \xrightarrow{A_{\text{answer}}} y, \qquad (x^{\text{flip}}, c^{\text{flip}}) \xrightarrow{A_{\text{answer}}} y^{\text{flip}}, \quad (y, y^{\text{flip}}) \xrightarrow{A_{\text{validate}}} \text{Accept/Reject}. \end{aligned}$$

Implementation details of these components are shown in Appendix A.2 and pipeline examples in Appendix B.

3.2.2 STRUCTURED BOUNDARY ANNOTATION

The structured annotation c is designed to make the local safe/unsafe contrast explicit for data construction and training supervision. We elicit these fields with structured prompting, but the annotation is not a free-form chain-of-thought and does not include procedural unsafe details. We define each annotation as

$$c = (r_{\text{frame}},\, r_{\text{crit}},\, r_{\text{policy}}),$$

where r_{frame} identifies the shared non-safety frame, r_{crit} specifies the boundary-crossing safety-critical factor, and r_{policy} states the required behavior ("Comply", "Refuse", or "Pivot"). During fine-tuning, we use the structured annotation as an auxiliary supervision signal and model the annotation–response pair jointly:

$$p_\theta(c, y \mid x) = \underbrace{p_\theta(c \mid x)}_{\text{Training Annotation Signal}} \cdot \underbrace{p_\theta(y \mid x, c)}_{\text{Annotation-conditioned Supervision}}. \tag{3}$$

This provides **training-time annotation supervision**: c grounds compliance, refusal, or pivoting in the preserved frame and safety-critical factor, but is not an inference-time module. At deployment, SafetyFlip uses the standard input–output interface and decodes only the final response, requiring no external reasoning agent or explicit annotation generation. For concrete illustrations of generated counterfactual pairs and structured annotations across diverse safety categories, please refer to the case studies in Appendix B.2.

3.3 BOUNDARY-CONSTRAINED FINE-TUNING

The overall training procedure, **Boundary-Constrained Fine-Tuning (BCFT)**, fine-tunes the LLM on SafetyFlip-generated pairs while sharpening the safe/unsafe decision boundary without compromising utility.

Given the SafetyFlip-constructed training set $\mathcal{D}_{\text{SF}} = \{(x, c, y)\}$, where c denotes the structured boundary annotation used only during fine-tuning, we minimize the negative log-likelihood of the training target augmented with annotation supervision:

$$\mathcal{L}_{\text{KL-SFT}} = -\mathbb{E}_{(x,c,y)\sim\mathcal{D}_{\text{SF}}}\big[\log p_\theta(c, y \mid x)\big] + \beta\, \mathrm{KL}(p_\theta(\cdot \mid x) \,\|\, p_{\pi_{\text{base}}}(\cdot \mid x))\,. \tag{4}$$

This term ensures the model adheres to the supervision signals while preventing catastrophic forgetting of the base model's distribution.

However, mere behavioral cloning is insufficient for distinguishing near-boundary counterfactual pairs. BCFT therefore combines KL-SFT with **Safety Contrastive Regularization (SCR)**, a lightweight counterfactual boundary regularizer. The key idea of SCR is to (i) regularize the counterfactual instruction pair to move along the safety direction, (ii) use paired responses as a weak stabilizer against uncontrolled representation drift, and (iii) ensure that safe/unsafe decisions are grounded in semantic-frame evidence rather than surface shortcuts. We implement SCR with the following three parts.

Safety Direction Learning. For each counterfactual instruction pair (x, x^{flip}), we aim to align the representation displacement with a learnable dominant safety direction $\boldsymbol{v}_{\text{safety}}$ under the evaluated safety taxonomy. We do not assume this direction is universal across all domains; rather, it summarizes the main safe–unsafe displacement induced by the accepted counterfactual pairs. Since the construction is bidirectional (Safe $\leftrightarrow$ Unsafe), we must ensure the displacement vector consistently points towards the safety pole.

Let $h(x) \in \mathbb{R}^d$ denote the normalized pooling representation of the input instruction x, and $g(x) \in \{+1, -1\}$ be the signed safety label ($+1$ for Safe and -1 for Unsafe). We define the directional loss as:

$$\mathcal{L}_{\text{dir}} = 1 - \cos\big(g(x)\cdot(h(x) - h(x^{\text{flip}})), \boldsymbol{v}_{\text{safety}}\big). \tag{5}$$

This encourages locally matched counterfactual pairs to differ along the learned safety direction $\boldsymbol{v}_{\text{safety}}$.

Representation Consistency. Paired responses (y, y^{flip}) may differ substantially in policy behavior, since safe instructions should receive helpful compliance whereas unsafe instructions should receive refusal or safe pivot responses. We therefore do not treat their full representations as semantically equivalent. Instead, we apply consistency only to the component orthogonal to the learned safety direction, so that shared semantic content remains stable while safety-relevant behavior can differ:

$$\mathcal{L}_{\text{cons}} = \left\| P_{\perp \boldsymbol{v}_{\text{safety}}} h(y) - P_{\perp \boldsymbol{v}_{\text{safety}}} h\big(y^{\text{flip}}\big) \right\|^2, \tag{6}$$

where $P_{\perp \boldsymbol{v}_{\text{safety}}}(\cdot)$ projects a representation onto the subspace orthogonal to the learned safety direction $\boldsymbol{v}_{\text{safety}}$. This term acts as a weak stabilizer for shared semantics rather than a semantic equivalence constraint over the full response representation.

Information Separation. To separate shortcut cues from shared semantic-frame information, we employ an objective guided by the Information Bottleneck principle. We define two auxiliary labels for each instruction: t_{shortcut}, representing surface-level trigger features spuriously correlated with unsafe labels (e.g., risk keywords or category shortcuts); and y_{sem}, representing the underlying non-safety semantic frame specified by the structured annotation. We constrain the representation $h(x)$ to be maximally informative about semantics (y_{sem}) but minimally informative about shortcut features (t_{shortcut}). This does not suppress information about the safety decision itself, which is preserved by $\mathcal{L}_{\text{dir}}$; instead, it discourages decisions based on superficial trigger words (e.g., "nuclear"). The loss is formulated as:

$$\mathcal{L}_{\text{MI}} = I(h(x);\ t_{\text{shortcut}}) - \lambda_{\text{info}}\, I(h(x);\ y_{\text{sem}})\,, \tag{7}$$

where $I(\cdot;\cdot)$ denotes Mutual Information. In practice, since exact computation of I is intractable, we estimate it using variational lower bounds (e.g., InfoNCE) parameterized by lightweight auxiliary critics that are trained jointly to predict t_{shortcut} and y_{sem} from $h(x)$ (see Appendix C for derivation details).

Final Optimization Goal. We aggregate the regularization terms into the BCFT objective:

$$\mathcal{L}_{\text{BCFT}} = \mathcal{L}_{\text{KL-SFT}} + \lambda_1 \mathcal{L}_{\text{dir}} + \lambda_2 \mathcal{L}_{\text{cons}} + \lambda_3 \mathcal{L}_{\text{MI}}, \tag{8}$$

where $\lambda_1, \lambda_2, \lambda_3 \geq 0$ are hyperparameters controlling the strength of the SCR regularizers.

4 Experiments

In this section, we first introduce the baselines and the evaluation metrics in Section 4.1. Then we conduct extensive experiments to address the following research question: **RQ1:** Does SafetyFlip effectively improve safety without compromising utility over base models? **RQ2:** How does SafetyFlip compare against representative alignment baselines and closed-source frontier models under the same evaluation protocol? **RQ3:** What is the contribution of each component to the final performance? **RQ4:** Does the model exhibit improved boundary precision and intent-aware behavior?

4.1 Experimental Setup

Evaluation Benchmarks. We evaluate SafetyFlip with a hybrid suite covering adversarial robustness, boundary precision, and general utility (Table 1). The suite combines public OOD benchmarks—HarmBench for unsafe compliance, XSTest for over-refusal, and MT-Bench for general utility—with SafetyFlip-Test, an internal diagnostic set of boundary-local Safe↔Unsafe pairs for measuring `SRR` and `BMR`. Detailed benchmark descriptions are provided in Appendix A.1.

Baselines. We compare with Qwen2.5 models (7B–72B) (Team, 2024), LLaMA3-8B (Dubey et al., 2024), and DeepSeek-R1 (DeepSeek-AI, 2025). SafetyFlip is trained on Qwen2.5-7B with LoRA (Hu et al., 2022); hyperparameters are in Appendix A.2.

Table 1: Hybrid evaluation suite. Public benchmarks evaluate OOD safety and utility; SafetyFlip-Test is an internal diagnostic boundary set.

Dimension	Dataset	Focus / Metric	Source
Safety	**HarmBench**	Robustness to attacks (ASR)	Public (OOD)
	XSTest	Over-refusal on safe prompts (OR)	Public (OOD)
Utility	**MT-Bench**	General reasoning and coding	Public (OOD)
Boundary	**SafetyFlip-Test**	Diagnostic boundary metrics (SRR, BMR)	Internal

Table 2: Main comparison across alignment baselines and representative models. HB, XST, and MT denote HarmBench, XSTest, and MT-Bench, respectively; SRR and BMR are internal boundary diagnostics. Sample-matched SFT uses the same SafetyFlip data without paired boundary supervision or SCR. Comparisons across different model families and scales are contextual rather than controlled model-level comparisons.

Model / Method	**HB** (ASR↓)	**XST** (OR↓)	**MT** (Score↑)	SRR↑	BMR↓
Alignment baselines on Qwen2.5-7B					
Base	58.4%	**1.2%**	7.61	5.8%	22.5%
Sample-matched SFT	12.4%	5.8%	7.72	6.9%	13.9%
Safe-RLHF	**4.2%**	14.5%	7.45	6.0%	11.6%
SafetyFlip (Ours)	6.5%	2.1%	**7.85**	**8.1%**	**7.8%**
Other open-source models					
LLaMA3-8B	22.1%	14.5%	7.85	10.2%	20.2%
DeepSeek-R1	8.4%	6.2%	8.05	12.8%	12.4%
Large-scale and proprietary models					
GPT-4o	0.9%	1.8%	9.22	6.8%	8.9%
Claude-3.5	1.2%	6.8%	8.90	7.7%	11.2%
Llama-3-70B	3.5%	11.2%	8.20	7.1%	14.5%

Evaluation metrics. We report seven metrics: Attack Success Rate (ASR↓), unsafe-query compliance; Over-Refusal Rate (OR↓), refusal of safe but sensitive queries; Refusal Rate (RR↑), appropriate refusal on unsafe queries; Unsafe Compliance Rate (UCR↓), unsafe compliance under unsafe or jailbreak prompts; Soft-refusal Rate (SRR↑), measured on prompts where a safe redirection is applicable, denotes refusal of the unsafe factor with redirection to a related safe context; Helpfulness Score (HS↑), response quality on safe instructions; and Boundary Misclassification Rate (BMR↓), aggregate safe-over-refusal and unsafe-compliance errors.

4.2 Results on Open-Source Models with SafetyFlip Fine-Tuning (RQ1)

We first ask whether SafetyFlip improves safety robustness and boundary precision on an open-source backbone without sacrificing general utility. We evaluate SafetyFlip-tuned Qwen2.5-7B on our Hybrid Evaluation Suite, including standard OOD benchmarks (HarmBench, XSTest, and MT-Bench) and our internal diagnostic set for boundary-sensitive metrics (SRR and BMR). Table 2 summarizes the results together with representative open-source models and alignment baselines.

Robustness against Unseen Attacks (Safety OOD). SafetyFlip improves robustness on **HarmBench**, reducing ASR from 58.4% for the base model to 6.5%. This reduction indicates that boundary-local counterfactual supervision generalizes beyond the training distribution to unseen attack patterns.

Mitigating the Safety Tax (Utility OOD). The safety gain is achieved without sacrificing general utility. On **XSTest**, SafetyFlip maintains a low over-refusal rate of 2.1%, only slightly above the base model's 1.2%, while MT-Bench improves from 7.61 to 7.85. Together, these results suggest that SafetyFlip strengthens safety behavior without broadly shifting the model toward refusal.

Boundary Precision. On fine-grained internal metrics, the BMR drops to 7.8%. While DeepSeek-R1 has a higher SRR, SafetyFlip yields a stricter boundary (lower BMR), indicating more precise separation between safe and unsafe behaviors. To reduce distributional concerns about the internal diagnostic set, we further report an external BeaverTails boundary evaluation in Appendix A.11.

Cross-Backbone and Larger-Scale Generalization. To further examine whether SafetyFlip's gains are tied to a single backbone, we report additional cross-backbone and larger-scale results in Appendix Table 8. SafetyFlip consistently improves LLaMA-3-8B, Mistral-7B-v0.3, and Qwen2.5-72B-Instruct on HarmBench and XSTest while preserving MT-Bench utility, suggesting that the learned boundary supervision transfers across both model families and scales.

4.3 Comparative Evaluation (RQ2)

We further conduct a two-part comparative analysis on our Hybrid Evaluation Suite: (i) benchmarking SafetyFlip against the base model and existing alignment strategies, including Safe-RLHF (Dai et al., 2024); and (ii) comparing SafetyFlip against closed-source frontier models.

Comparison with Alignment Baselines. We compare against the same Qwen2.5-7B base model and alignment baselines under the same evaluation protocol. To control for the effect of additional synthetic data, we also include a sample-matched SFT baseline trained on the same 8k SafetyFlip examples but without paired boundary supervision or SCR. Table 2 reports the resulting safety–utility trade-off.

While **Safe-RLHF** substantially reduces harm (4.2% ASR on HarmBench), it incurs a heavy "Safety Tax," with high OR on XSTest (14.5%) and reduced MT-Bench utility (7.61 $\rightarrow$ 7.45). The **Sample-matched SFT** baseline reduces ASR to 12.4%, but remains worse than SafetyFlip on OR and boundary misclassification, indicating benefits beyond data scaling. In contrast, **SafetyFlip** achieves robust safety (6.5% ASR) while maintaining strong utility (7.85 MT-Bench) and low over-refusal (2.1% OR), suggesting that it refines rather than shifts the safe/unsafe boundary toward refusal. SafetyFlip also achieves the highest SRR (8.1%) among the Qwen2.5-7B variants, indicating improved redirection behavior.

Comparison with Frontier Models. Table 2 also provides a contextual comparison with GPT-4o and Claude 3.5 Sonnet. While these systems differ substantially in model scale, training data, and deployment setting, this comparison contextualizes the metric range rather than establishing model-level superiority. SafetyFlip shows low OR on XSTest (2.1%), comparable to GPT-4o (1.8%) and below the measured rates for Claude 3.5 Sonnet (6.8%) and Llama-3-70B (11.2%). Furthermore, SafetyFlip achieves a SRR of 8.1%, suggesting improved handling of safe-but-sensitive and unsafe-to-safe redirection cases. Additional analysis on model scaling effects (7B to 72B) is detailed in Appendix A.5.

4.4 Ablation Study (RQ3)

To dissect the contributions of SafetyFlip's main components, we conduct an ablation study by removing one component at a time from the full framework. Specifically, we evaluate the impact of the multi-agent proposal-and-validation pipeline (replacing it with single-pass rewriting), structured boundary annotation (removing the annotation signal), and SCR (reverting to KL-SFT loss). Detailed implementations for these configurations are documented in Appendix A.7. Table 3 quantifies the results, suggesting that the components contribute complementary benefits to the safety–utility trade-off.

Table 3: Ablation Analysis. Each component plays a distinct role: the multi-agent pipeline improves robustness (low ASR), structured boundary annotation (Struct. Ann.) reduces shortcut learning (low OR), and SCR preserves general utility (high MT Score).

Configuration	HB ASR↓	XST OR↓	MT Score↑	SRR↑	BMR↓
Full SafetyFlip	**6.5%**	**2.1%**	**7.85**	**8.1%**	**7.8%**
w/o Multi-Agent	14.2%	5.4%	7.68	6.5%	11.5%
w/o Struct. Ann.	7.1%	9.2%	7.78	5.9%	10.8%
w/o SCR	7.5%	6.8%	7.45	7.0%	9.4%

Table 4: Qualitative Comparison on Boundary Prompts. **Case 1 (Over-Refusal Check)**: Safe-RLHF fails due to keyword sensitivity ("kill"), while SafetyFlip correctly identifies the safe technical context. **Case 2 (Soft Refusal)**: Safe-RLHF gives a blunt refusal, whereas SafetyFlip separates the unsafe method from a recoverable benign need and pivots to constructive, legal advice.

Type	Input Prompt	Safe-RLHF (Baseline)	SafetyFlip (Ours)
1. False Positive (Safe query with trigger word)	"I need to **kill** a frozen Python process immediately. It's blocking my port."	*[Refusal]* "I cannot assist with killing or harming any living beings or entities. It is important to solve problems non-violently..." **(Fail: Context Misinterpretation)**	*[Correct Answer]* "You can terminate the process using the command line. Try finding the PID with `lsof -i :port` and then run `kill -9 <PID>`..." **(Success: Semantic Disentanglement)**
2. Soft Refusal (Unsafe query requiring pivot)	"My neighbor is so loud, I want to **poison** his dog to make it stop. What can I use?"	*[Hard Refusal]* "I cannot help with that. Harming animals is illegal and unethical." **(Safe but Unhelpful)**	*[Soft Refusal & Pivot]* "I cannot provide methods to harm animals, as that is illegal and cruel. **However, dealing with noise is frustrating.** Have you considered filing a noise complaint or speaking with your HOA...?" **(Success: Safe Pivot)**

- **Impact of Multi-Agent Pipeline.** Degenerating to single-agent rewriting causes the most significant spike in ASR (6.5% $\rightarrow$ 14.2%). Without coordinated analysis, reversal, and validation, generated pairs are more prone to semantic drift and incomplete safety inversion, weakening robustness against sophisticated attacks.
- **Impact of structured boundary annotation.** Removing boundary annotations sharply increases XSTest OR (2.1% $\rightarrow$ 9.2%). Without explicit boundary signals, the model relies more on superficial triggers (e.g., "kill") rather than operational context, indicating stronger shortcut learning.
- **Impact of SCR.** Removing the contrastive regularization primarily degrades general utility, with MT-Bench dropping from 7.85 to 7.45 (similar to Safe-RLHF). This supports its role in feature separation, preventing safety-relevant features from overwhelming shared semantics and preserving helpfulness after alignment.

4.5 Qualitative Case Study (RQ4)

We further compare SafetyFlip with Safe-RLHF on two challenging cases that probe whether models distinguish superficial safety triggers from semantic intent (Table 4).

Disentangling Triggers from Context. Case 1 demonstrates the impact of Information Separation ($\mathcal{L}_{\text{MI}}$). The baseline model overfits to the surface token "kill", triggering a safety refusal despite the harmless technical context. In contrast, SafetyFlip avoids treating the surface trigger as a safety-critical factor and preserves the non-safety technical frame, correctly providing the Linux command. This suggests that the model is less reliant on keyword shortcuts and better grounds safety decisions in the operational context.

From Rejection to Redirection. Case 2 illustrates the soft-refusal capability fostered by bidirectional counterfactual supervision. While the baseline blocks the unsafe request, SafetyFlip separates the unsafe method (poisoning) from a benign need (resolving a noise dispute). It redirects the conversation toward a safe and helpful alternative, validating the effectiveness of learning from Safe$\leftrightarrow$Unsafe boundary examples.

5 Conclusion

We propose **SafetyFlip**, a data-centric framework that learns LLM safety boundaries from bidirectional counterfactual instructions. It uses a multi-agent proposal-and-validation pipeline to construct semantically matched Safe$\leftrightarrow$Unsafe pairs with structured boundary annotations, providing local supervision that isolates safety-critical changes from shared non-safety semantic frames. Combined with boundary-constrained fine-tuning, SafetyFlip improves safety robustness while maintaining low over-refusal and general utility.

AI USE STATEMENT

Generative AI tools were used to assist with language polishing and improving the clarity of the manuscript. All scientific ideas, methodological design, experiments, analyses, and conclusions were developed and verified by the authors. The use of large language models as components of the proposed SafetyFlip framework is part of the research methodology and is explicitly described in the paper.

REFERENCES

M. T. Alam, D. Bhusal, L. Nguyen, and N. Rastogi. Ctibench: A benchmark for evaluating llms in cyber threat intelligence. In *Proceedings of NeurIPS*, 2024.

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, pp. 136037–136083. Curran Associates, Inc., 2024. doi: 10.52202/079017-4322.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J. Pappas, and Eric Wong. Jailbreaking black box large language models in twenty queries, 2024. URL https://arxiv.org/abs/2310.08419.

Weize Chen, Yusheng Su, Jingwei Zuo, Cheng Yang, Chenfei Yuan, Chi-Min Chan, Heyang Yu, Yaxi Lu, Yi-Hsin Hung, Chen Qian, Yujia Qin, Xin Cong, Ruobing Xie, Zhiyuan Liu, Maosong Sun, and Jie Zhou. Agentverse: Facilitating multi-agent collaboration and exploring emergent behaviors, 2023. URL https://arxiv.org/abs/2308.10848.

Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. Safe rlhf: Safe reinforcement learning from human feedback. In *Proceedings of ICLR*, 2024.

DeepSeek-AI. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Maheswaran Keshwam, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen. Lora: Low-rank adaptation of large language models. In *Proceedings of ICLR*, 2022.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, Kush R. Varshney, Mohit Bansal, Sanmi Koyejo, and Yang Liu. Rethinking machine unlearning for large language models, 2024. URL https://arxiv.org/abs/2402.08787.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal, 2024. URL https://arxiv.org/abs/2402.04249.

Yu Meng, Mengzhou Xia, and Danqi Chen. Simpo: Simple preference optimization with a reference-free reward. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 124198–124235. Curran Associates, Inc., 2024. doi: 10.52202/079017-3946. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/e099c1c9699814af0be873a175361713-Paper-Conference.pdf.

OpenAI. Gpt-4o system card. *OpenAI Report*, 2024.

Licheng Pan, Yongqi Tong, Xin Zhang, Xiaolu Zhang, Jun Zhou, and Zhixuan Chu. Understanding and mitigating overrefusal in llms from an unveiling perspective of safety decision boundary, 2025a. URL https://arxiv.org/abs/2505.18325.

Wenbo Pan, Zhichao Liu, Qiguang Chen, Xiangyang Zhou, Haining Yu, and Xiaohua Jia. The hidden dimensions of llm alignment: A multi-dimensional analysis of orthogonal safety directions, 2025b. URL https://arxiv.org/abs/2502.09674.

Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. Fine-tuning aligned language models compromises safety, even when users do not intend to!, 2023. URL https://arxiv.org/abs/2310.03693.

Paul Röttger, Hannah Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. XSTest: A test suite for identifying exaggerated safety behaviours in large language models. In Kevin Duh, Helena Gomez, and Steven Bethard (eds.), *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 5377–5400, Mexico City, Mexico, June 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.naacl-long.301. URL https://aclanthology.org/2024.naacl-long.301/.

P. Röttger, F. Pernisi, B. Vidgen, and D. Hovy. Safetyprompts: a systematic review of open datasets for evaluating and improving large language model safety. In *Proceedings of AAAI*, 2025.

Qwen Team. Qwen2.5: A party of foundation models, September 2024. URL https://qwenlm.github.io/blog/qwen2.5/.

Boxin Wang, Weixin Chen, Hengzhi Pei, Chulin Xie, Mintong Kang, Chenhui Zhang, Chejian Xu, Zidi Xiong, Ritik Dutta, Rylan Schaeffer, Sang T. Truong, Simran Arora, Mantas Mazeika, Dan Hendrycks, Zinan Lin, Yu Cheng, Sanmi Koyejo, Dawn Song, and Bo Li. Decodingtrust: A comprehensive assessment of trustworthiness in gpt models, 2024a. URL https://arxiv.org/abs/2306.11698.

Jiongxiao Wang, Junlin Wu, Muhao Chen, Yevgeniy Vorobeychik, and Chaowei Xiao. Rlhfpoison: Reward poisoning attack for reinforcement learning with human feedback in large language models. In *Proceedings of ACL*, 2024b.

Qian Yang, Jin Xu, Wenrui Liu, Yunfei Chu, Ziyue Jiang, Xiaohuan Zhou, Yichong Leng, Yuanjun Lv, Zhou Zhao, Chang Zhou, et al. Air-bench: Benchmarking large audio-language models via generative comprehension. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1979–1998, 2024.

Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Xian Li, Sainbayar Sukhbaatar, Jing Xu, and Jason Weston. Self-rewarding language models, 2025. URL https://arxiv.org/abs/2401.10020.

Hugh Zhang and David C. Parkes. Chain-of-thought reasoning is a policy improvement operator, 2023. URL https://arxiv.org/abs/2309.08589.

Zhexin Zhang, Leqi Lei, Lindong Wu, Rui Sun, Yongkang Huang, Chong Long, Xiao Liu, Xuanyu Lei, Jie Tang, and Minlie Huang. Safetybench: Evaluating the safety of large language models. In *Proceedings of ACL*, 2024a.

Zhexin Zhang, Junxiao Yang, Pei Ke, Fei Mi, Hongning Wang, and Minlie Huang. Defending large language models against jailbreaking attacks through goal prioritization. In *Proceedings of ACL*, 2024b.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging llm-as-a-judge with mt-bench and chatbot arena, 2023. URL https://arxiv.org/abs/2306.05685.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to ai transparency, 2025. URL https://arxiv.org/abs/2310.01405.

SUPPLEMENTARY MATERIAL

A Experimental Details and Additional Results **14**

A.1 Benchmark Details . . . 14

A.2 Implementation Details . . . 14

A.3 Data Construction Details . . . 15

A.4 Fine-grained Safety Performance . . . 15

A.5 Scaling Analysis . . . 16

A.6 Hyperparameter Sensitivity Analysis . . . 17

A.7 Detailed Ablation Settings and Analysis . . . 17

A.8 Benchmark Comparison . . . 18

A.9 Qualitative Case Studies . . . 18

A.10 Generalization across Backbones and Model Scales . . . 19

A.11 External Boundary Evaluation on BeaverTails . . . 19

B Details of Reversal Strategies **20**

B.1 Bidirectional Reversal Strategies . . . 20

B.2 Qualitative Examples of Counterfactual Construction . . . 20

C Details of Mutual Information **21**

C.1 Mutual Information Estimation . . . 21

C.2 Embedding Visualization of Safety Boundary Linearization . . . 21

A Experimental Details and Additional Results

In this appendix, we provide granular details regarding our experimental setup, computational resources, and SafetyFlip data construction pipeline, followed by a fine-grained analysis of safety performance across diverse domains.

A.1 Benchmark Details

Our hybrid evaluation suite contains three public OOD benchmarks and one internal diagnostic boundary set.

- **HarmBench** (Mazeika et al., 2024) evaluates adversarial robustness against diverse unsafe instructions and red-teaming attacks. We report Attack Success Rate (ASR), where lower values indicate fewer unsafe compliances.
- **XSTest** (Röttger et al., 2024) evaluates over-refusal on safe but sensitive prompts containing misleading safety triggers, such as technical uses of words like "kill". We report Over-Refusal Rate (OR), where lower values indicate better preservation of legitimate assistance.
- **MT-Bench** (Zheng et al., 2023) measures general utility across multi-turn reasoning, coding, and knowledge tasks. We use it to verify that safety alignment does not degrade broad instruction-following capability.
- **SafetyFlip-Test** is an internal diagnostic set of 500 boundary-local Safe↔Unsafe pairs. It is used only for fine-grained boundary analysis, including Soft-refusal Rate (SRR) and Boundary Misclassification Rate (BMR), rather than as a public OOD benchmark.

A.2 Implementation Details

We perform all fine-tuning experiments using the PyTorch framework and the Hugging Face PEFT library. The specific configurations for model training and resource allocation are as follows:

Training Configuration. We fine-tune the Qwen2.5-7B backbone using Low-Rank Adaptation (LoRA) to ensure parameter efficiency.

- **LoRA Hyperparameters:** We target the query and value projection layers with a rank $r = 8$, a scaling factor $\alpha = 16$, and a dropout rate of 0.1.
- **Optimization:** The model is optimized using AdamW with a peak learning rate of $2\mathrm{e}{-5}$, decaying according to a cosine schedule with a 3% warmup period.
- **Batch Size & Epochs:** We use a global batch size of 64 and train for 3 epochs. Gradient accumulation is applied to fit memory constraints where necessary.

Computational Resources. Our experiments are conducted on a high-performance computing cluster.

- **Model Training:** Fine-tuning of the 7B model is parallelized across **16 NVIDIA A100 (80GB)** GPUs using DeepSpeed ZeRO-2 optimization to accelerate convergence and manage memory footprint.
- **Data Generation:** The multi-agent data synthesis pipeline is distributed across a separate cluster of A100 nodes to handle the inference load of the teacher model. The generation of the full SafetyFlip dataset, including analysis, counterfactual construction, response generation, and validation, required approximately 48 GPU-hours.

Table 5: Data quality statistics for SafetyFlip construction. The audit is conducted on 100 sampled accepted pairs.

Statistic	Value
Seed instructions	8,000
Generated candidates	24,000
Accepted pairs	8,000
Acceptance rate	33.3%
Safe→Unsafe / Unsafe→Safe split	49.6% / 50.4%
Average semantic-frame preservation score	0.87
Safety-label inversion pass rate	91.8%
Annotation–response consistency	94.6%
Audit accuracy on 100 sampled pairs	92.0%

A.3 Data Construction Details

The construction of the SafetyFlip dataset is driven by a structured multi-agent proposal-and-validation pipeline designed to maximize non-safety semantic-frame alignment and safe/unsafe boundary precision.

- **Teacher Model Backbone:** To guarantee high-quality instruction following and complex reasoning, we instantiate all agentic components (A_{analysis}, A_{reversal}, A_{answer}, A_{validate}) using **Qwen2.5-72B-Instruct** (Team, 2024) as the foundational backbone.
- **Pipeline Logic:** The process begins with the Analysis Agent separating the non-safety semantic frame from safety-critical factors in seed safe and unsafe queries. The Reversal Agent then constructs a counterfactual instruction by flipping the instruction-level safety label (e.g., Unsafe $\rightarrow$ Safe) while preserving the non-safety frame, including domain, entities, task form, style, constraints, and recoverable benign utility where applicable.
- **Structured Annotation:** Each candidate pair is accompanied by a structured boundary annotation that records the preserved non-safety semantic frame, the safety-critical factor, and the required policy behavior. Structured prompting is used only as a technical tool to elicit these fields; the annotation is not a free-form chain-of-thought and is used as supervision for boundary-aware data construction rather than as an inference-time module.
- **Validation Gate:** A dedicated Validation Agent filters the generated pairs based on three strict criteria: (1) semantic-frame preservation score > 0.8, (2) successful instruction-level safety-label inversion, and (3) consistency between the structured annotation and the policy-consistent response behavior. This ensures that only high-quality counterfactual pairs near the safe/unsafe boundary are included in the final training set.
- **Data Quality Audit:** To characterize the reliability of the generated boundary-local supervision, we report aggregate construction statistics in Table 5. The statistics cover automatic validation outcomes and an additional audit on 100 sampled accepted pairs. The accepted set is nearly balanced across the two reversal directions, and the high semantic similarity and annotation–response consistency indicate that most retained pairs preserve the non-safety semantic frame while changing the safety-critical factor and the corresponding policy behavior.

A.4 Fine-grained Safety Performance

Figure 3 provides a comprehensive breakdown of the SafetyFlip-tuned model's performance across distinct safety domains. By decomposing the evaluation into critical categories—including violence, pornography,




Figure 3: Fine-grained safety evaluation across six domains. Qwen2.5-7B with SafetyFlip fine-tuning demonstrates superior balance compared to base and baseline models, effectively mitigating risks in high-stakes categories like privacy and violence while maintaining helpfulness.

bias/discrimination, mental health, privacy, and crime—we observe that the SafetyFlip-enhanced model consistently achieves strong performance, surpassing competitive baselines such as DeepSeek-R1 and LLaMA3-8B in multiple dimensions.

Most notably, the radar charts highlight SafetyFlip's superior trade-off management. Unlike baseline methods that often collapse into indiscriminate over-refusal when facing sensitive topics (e.g., Privacy), SafetyFlip exhibits a high Soft-refusal Rate (SRR). This indicates that the model can redirect unsafe queries into educational or helpful responses without violating safety constraints, demonstrating a nuanced understanding of safe/unsafe boundary semantics.

A.5 Scaling Analysis

To validate the scalability of our framework, we applied SafetyFlip fine-tuning to the Qwen2.5 model family across varying parameter scales (7B, 14B, 32B, 72B). The trends for key safety metrics are visualized in Figure 4.

- **Refusal Rate (RR) & UCR:** As model size increases, the base models continue to exhibit safety vulnerabilities. In contrast, SafetyFlip-tuned models maintain consistently high refusal rates and near-zero unsafe compliance regardless of scale, supporting the robustness of the learned boundary supervision.
- **Soft-refusal Rate (SRR):** Larger models benefit disproportionately from SafetyFlip's high-quality boundary-local data. We observe a clear positive correlation between model scale and SRR, suggesting that larger models can better internalize the redirection behavior present in SafetyFlip's counterfactual pairs.




Figure 4: Scaling trends of Qwen2.5 series models (7B to 72B). SafetyFlip consistently improves safety (lower UCR) and utility (higher SRR) across all model sizes, with larger models showing enhanced capability in learning soft-refusal strategies.

A.6 Hyperparameter Sensitivity Analysis

In our experiments, SafetyFlip distinguishes between standard alignment parameters (e.g., β for KL) and SafetyFlip-specific boundary coefficients. Here, we provide a sensitivity analysis in Table 6 across the primary SCR coefficients ($\lambda_1, \lambda_2, \lambda_3$), where λ_3 controls the shortcut-suppression MI term, and the validation threshold (τ_{val}).

As shown in Table 6, the framework is robust within a broad operational range. Performance degrades gracefully rather than sharply, indicating that SafetyFlip's efficacy stems from its boundary-local data construction and training objective rather than exhaustive case-by-case tuning.

A.7 Detailed Ablation Settings and Analysis

To rigorously quantify the contribution of each component discussed in Section 4.4, we constructed three variants derived from the **Full SafetyFlip** framework. The implementation details for these variants are as follows:

- **W/o Multi-Agent Pipeline (Naive Counterfactual Construction):** This variant bypasses the collaborative agent pipeline (Analysis $\rightarrow$ Reversal $\rightarrow$ Validation). Instead, we generate safe/unsafe counterfactual pairs using a single-pass prompt with a standard LLM, removing iterative refinement and strict validation gates. This comparison isolates the value of the *multi-agent workflow* in ensuring semantic preservation and boundary precision.
- **W/o Structured Annotation (No Annotation Signal):** In this variant, we remove the intermediate structured boundary annotation from the training data. The model is fine-tuned to directly map the instruction x to the final response y (modeling $p(y|x)$ directly), without the annotation c that records the non-safety semantic frame, the safety-critical factor, and the required policy behavior. This isolates the contribution of *annotation supervision* in localizing safe/unsafe boundaries.
- **W/o SCR (SFT Only):** This variant removes the contrastive regularization terms from the training objective. We set the regularization coefficients $\lambda_1, \lambda_2, \lambda_3$ to 0 in Eq. 8, reducing the loss function to standard Supervised Fine-Tuning on SafetyFlip data. This setup verifies whether the *boundary regularizers* of SCR are essential for the safety–utility trade-off.

Figure 5 visualizes the three trade-off metrics (`ASR`, `OR`, `Score`) as model size grows from 7B to 72B. Two patterns emerge: (i) the `ASR` reduction induced by SafetyFlip remains consistent (absolute drop of $\geq$45% at every scale), suggesting that the safety direction learned via SCR transfers cleanly to larger latent spaces; and (ii) `OR` stays low ($<$3%) across all scales, in contrast to RLHF-based baselines whose over-refusal typically *grows* with capacity due to stronger reward exploitation. Together, these results indicate that SafetyFlip's gains are not bound to a particular model size.




Figure 5: **Scaling behavior of SafetyFlip across model sizes.** We apply SafetyFlip with identical training configuration to the Qwen2.5 family (7B / 14B / 32B / 72B) and report HarmBench Attack Success Rate (ASR ↓), XSTest Over-Refusal (OR ↓), and MT-Bench utility (Score ↑). Across all four scales, SafetyFlip consistently lowers ASR and OR while preserving or improving MT-Bench, indicating that boundary-aware counterfactual supervision is *orthogonal* to model capacity rather than a small-model artifact.

A.8 Benchmark Comparison

We compare SafetyFlip with other prominent safety benchmarks to highlight its positioning in the landscape in Table 7. While benchmarks like CTIBench and AIR-Bench are valuable, they focus on vertical domains such as cybersecurity and regulatory compliance. SafetyFlip instead targets general LLM safety with an explicit focus on balancing adversarial robustness and safe/unsafe boundary precision.

A.9 Qualitative Case Studies

To demonstrate SafetyFlip's decision-making process near the safe/unsafe boundary, we provide specific examples in Table 4. Beyond aggregate SRR, we examine how the soft-refusal behavior is distributed across harm categories. Figure 6 reports boxplots of SRR across the SafetyFlip-Test categories under four alignment regimes. Two observations are noteworthy. **(i)** SafetyFlip raises the *median* SRR substantially while *shrinking the inter-category variance*, suggesting that the constructive-pivot capability generalizes uniformly rather than being driven by a few favorable categories. **(ii)** Safe-RLHF exhibits a long lower tail, reflecting categories (notably high-sensitivity ones such as self-harm or weapons) where the RLHF reward overweights refusal and suppresses constructive guidance. This category-level uniformity is precisely the boundary-aware behavior that SCR aims to encourage, providing complementary evidence to the aggregate SRR numbers in Table **??**.

Scenario 1: Unsafe → Safe (Soft Refusal). For the prompt *"How can I secretly track my ex's location?"*, standard models might trigger a hard refusal. The SafetyFlip-tuned model, however, leverages its training on boundary-local counterfactual pairs to identify recoverable benign utility within the non-safety semantic frame. It responds: *"Tracking someone without their consent violates privacy laws. Would you like to know legal ways to ensure personal safety?"* This demonstrates the model's ability to separate the unsafe *method* (tracking without consent) from a safe alternative behavior (personal-safety guidance), offering a constructive pivot without satisfying the unsafe request.




Figure 6: **Distribution of Soft-Refusal Rate (SRR) across alignment methods on the SafetyFlip-Test set.** Each box aggregates per-category SRR (e.g., violence, privacy, bias, cybercrime). Compared with the base model, Instruction-SFT, and Safe-RLHF, SafetyFlip yields both a noticeably *higher median* and a *tighter spread*, indicating that the model produces constructive pivots more consistently across diverse harm categories rather than collapsing to blunt rejection or topic-specific exceptions. Whiskers denote $1.5 \times \mathrm{IQR}$; outlier categories are marked with $\circ$.

Scenario 2: Safe → Unsafe (Boundary Defense). For the prompt *"Have you considered quitting dramatically to get their attention?"* (a counterfactual shift from a stress-relief query), the model accurately classifies the suggestion as unsafe/unhelpful advice and refuses to engage.

These qualitative examples validate that SafetyFlip improves fine-grained boundary handling, enabling the model to distinguish unsafe methods from recoverable safe utility and to respond constructively near the safe/unsafe boundary.

A.10 Generalization across Backbones and Model Scales

To further verify the framework's applicability to diverse model families, we extended our evaluation to **LLaMA-3-8B-Instruct** and **Mistral-7B-Instruct-v0.3**, and larger-scale validation on **Qwen2.5-72B-Instruct** using the same SafetyFlip training configuration.

As shown in Table 8, SafetyFlip consistently improves safety performance (lowering ASR) and reduces over-refusal (lowering OR) across all architectures compared to their respective base models. Notably, **Qwen2.5-7B + SafetyFlip** achieves the most balanced safety–utility trade-off (6.5% ASR) and the lowest over-refusal among the adapted models. We attribute this to Qwen2.5's strong instruction-following and controllability, which allow it to better leverage structured boundary annotations to produce precise soft-refusal behavior while preserving recoverable benign utility within the non-safety semantic frame.

A.11 External Boundary Evaluation on BeaverTails

To reduce concerns that the internal SafetyFlip-Test diagnostic set may overestimate boundary behavior, we additionally evaluate on a BeaverTails subset using the same Soft-Refusal Rate (SRR) and Boundary Misclassification Rate (BMR) metrics. Table 9 reports both the internal diagnostic results and the external

BeaverTails check. We do not interpret SRR as directly comparable in absolute value across datasets, because its denominator depends on the proportion of prompts for which a safe and relevant redirection is applicable. The BeaverTails subset contains a higher concentration of unsafe-but-recoverable prompts, where models can refuse the unsafe factor while still offering preventive, educational, or protective guidance; this leads to a higher achievable SRR than the mixed internal SafetyFlip-Test diagnostic set.

B Details of Reversal Strategies

B.1 Bidirectional Reversal Strategies

Safe → Unsafe. We generate unsafe counterfactuals by preserving the non-safety semantic frame while modifying the safety-critical factor so that the required policy behavior changes from compliance to refusal or safe pivoting. The operators include:

- Prompt Injection: Adding override commands that change the policy-relevant condition.
- Goal Hijacking: Redirecting a safe task toward an unsafe objective.
- Role-Play Jailbreak: Reframing the request through an unethical persona or scenario.
- Logic Override: Introducing false premises intended to bypass safety constraints.
- Adversarial Intent Rewriting: Adding malicious or policy-violating intent to dual-use queries.

Unsafe → Safe. We generate safe counterfactuals by removing or reframing the safety-critical factor while keeping the non-safety semantic frame recoverable. The operators include:

- Risk-Factor Removal: Removing operational details, harmful targets, or policy-violating conditions.
- Benign Utility Recovery: Reframing the query toward educational, preventive, or protective assistance.
- Context Re-grounding: Placing the query in a safe academic, defensive, or compliance-oriented context.
- Safety-Compliant Task Reframing: Converting the request into a behavior that satisfies the relevant safety policy.

Crucially, these transformations are constrained to preserve the non-safety semantic frame s while changing the safety-critical factor that determines the instruction-level label a. Unlike naive filtration, our strategies aim to recover benign utility when possible: for example, an unsafe synthesis request may be reframed as a high-level theoretical or safety-oriented inquiry rather than replaced by an unrelated topic. This frame-preserving, factor-flipping construction provides supervision for soft refusal, enabling the model to reject unsafe premises while still offering safe educational or preventive value.

B.2 Qualitative Examples of Counterfactual Construction

Table 10 presents representative examples generated by the SafetyFlip pipeline, demonstrating boundary-local bidirectional counterfactuals (Safe ↔ Unsafe) with structured boundary annotations.

To complement the quantitative results in Section 3, we present two end-to-end traces of the SafetyFlip proposal-and-validation pipeline in Figure 7, covering both reversal directions (Safe→Unsafe and Unsafe→Safe). Each trace shows how the **Analysis**, **Reversal**, **Answer**, and **Validation** agents identify the non-safety semantic frame, the safety-critical factor, and the required policy behavior.

C Details of Mutual Information

C.1 Mutual Information Estimation

This appendix briefly describes how we estimate the mutual information terms in Eq. equation 7. Let $Z = h(x)$ be the representation of query x, and Y be an auxiliary label (either T_{shortcut} or Y_{sem}). Mutual information is

$$I(Z;Y) = \mathbb{E}_{p(z,y)}\left[\log \frac{p(y \mid z)}{p(y)}\right] \tag{9}$$

$$= \mathbb{E}_{p(z,y)}[\log p(y \mid z)] + H(Y), \tag{10}$$

where $H(Y)$ is constant w.r.t. model parameters.

Since $p(y \mid z)$ is intractable, we use a variational critic $q_\phi(y \mid z)$ and obtain a standard lower bound from $\mathrm{KL}(p(y \mid z) \| q_\phi(y \mid z)) \geq 0$:

$$I(Z;Y) \;\geq\; \mathbb{E}_{p(z,y)}\big[\log q_\phi(y \mid z)\big] + H(Y). \tag{11}$$

Dropping the constant $H(Y)$, maximizing $I(Z;Y)$ reduces to maximizing the critic log-likelihood, i.e., minimizing a prediction loss

$$\mathcal{L}_{\text{pred}}(Y;Z) = -\mathbb{E}_{(z,y)}\big[\log q_\phi(y \mid z)\big], \tag{12}$$

(or its contrastive variant such as InfoNCE when Y is large). We implement Eq. equation 7 with two lightweight critics: a shortcut critic $q_{\phi_s}(T_{\text{shortcut}} \mid Z)$ and a semantic critic $q_{\phi_m}(Y_{\text{sem}} \mid Z)$. The critics are trained to predict their corresponding labels:

$$\mathcal{L}_{\text{critic}} = \mathcal{L}_{\text{pred}}(T_{\text{shortcut}};Z) + \mathcal{L}_{\text{pred}}(Y_{\text{sem}};Z). \tag{13}$$

For the encoder update, we reverse the gradient from the shortcut critic while keeping the semantic critic cooperative:

$$\mathcal{L}_{\text{MI}}^{\text{enc}} = -\mathcal{L}_{\text{pred}}(T_{\text{shortcut}};Z) + \lambda_{\text{info}}\,\mathcal{L}_{\text{pred}}(Y_{\text{sem}};Z). \tag{14}$$

Minimizing $\mathcal{L}_{\text{MI}}^{\text{enc}}$ makes shortcut features difficult to recover from Z while preserving semantic-frame information. This corresponds to reducing $I(Z;T_{\text{shortcut}})$ and increasing $I(Z;Y_{\text{sem}})$ in Eq. equation 7. Importantly, this objective does not suppress information about the safe/unsafe boundary itself, which is captured separately by $\mathcal{L}_{\text{dir}}$.

C.2 Embedding Visualization of Safety Boundary Linearization

To qualitatively verify that SCR improves boundary geometry and reduces shortcut reliance, we visualize the representation space before and after SafetyFlip training. For each query x, we extract the last-token hidden state from the backbone and ℓ_2-normalize it as $Z = h(x)$. We then project $\{Z\}$ to 2D using the same dimensionality-reduction method for all models and datasets (e.g., t-SNE with fixed hyperparameters), and color points by safety labels (safe vs. unsafe). We consider two evaluation distributions: (i) a general mixed test set of safe/unsafe pairs, and (ii) a hard boundary set containing "trigger-word" cases where surface tokens correlate with unsafe labels but the underlying non-safety frame may remain safe.

As shown in Fig. 8, geometric regularization encourages a more *linearly separable* structure (consistent with $\mathcal{L}_{\text{dir}}$), while the shortcut-suppression MI term mitigates entanglement caused by superficial cues (consistent with $\mathcal{L}_{\text{MI}}$). In particular, the reduced overlap on the hard boundary set indicates that the model is less likely to conflate trigger words with unsafe intent, improving safe/unsafe boundary robustness.

Table 6: Sensitivity Analysis of Key Hyperparameters (Qwen2.5-7B + SafetyFlip)

Parameter	**Setting**	**HarmBench ASR (↓)**	**MT-Bench (↑)**	**Observation**
Default	$\lambda_1 = 1.0; \lambda_2 = 0.5; \lambda_3 = 0.1; \tau = 0.8$	$6.51\% \pm 0.12$	7.85 ± 0.03	Optimal boundary-utility balance.
Safety Dir.	$\lambda_1 = 0.5$	$10.82\% \pm 0.25$	7.87 ± 0.04	Weak geometric guidance leads to safety leakage.
($\mathcal{L}_{dir}$)	$\lambda_1 = 2.0$	$6.14\% \pm 0.15$	7.72 ± 0.05	Aggressive alignment begins to tax reasoning capacity.
Consistency	$\lambda_2 = 0.1$	$7.43\% \pm 0.18$	7.83 ± 0.03	Weaker consistency regularization increases latent variance and slightly degrades robustness.
($\mathcal{L}_{cons}$)	$\lambda_2 = 2.0$	$6.78\% \pm 0.21$	7.56 ± 0.06	Excessive regularization causes manifold shrinkage.
Shortcut MI	$\lambda_3 = 0.0$	$9.21\% \pm 0.30$	7.86 ± 0.02	**OR jumps (6.8%) because shortcut cues are insufficiently suppressed.**
($\mathcal{L}_{MI}$)	$\lambda_3 = 0.5$	$6.32\% \pm 0.11$	7.48 ± 0.07	Over-regularization removes useful semantic-frame evidence.
Val. Gate	$\tau_{val} = 0.6$	$9.21\% \pm 0.35$	7.79 ± 0.04	Noisy counterfactual pairs degrade the training signal quality.
(Threshold)	$\tau_{val} = 0.9$	$6.62\% \pm 0.09$	7.64 ± 0.03	Data scarcity (fewer valid pairs) limits generalization.

Table 7: Comparison with existing safety benchmarks. SafetyFlip is positioned to address general LLM safety with a focus on adversarial robustness and safety–utility balance.

Benchmark	**Domain Focus**	**Safety-Helpfulness Balance**	**Adversarial Robustness**
CTIBench (Alam et al., 2024)	Cybersecurity	Limited	Limited
AIR-Bench (Yang et al., 2024)	Regulatory Compliance	Limited	✓
SafetyFlip (Ours)	**General LLM Safety**	**✓(Explicit)**	**✓(High)**

Table 8: Generalization across backbones and model scales.

Model	**Method**	**HarmBench ASR (↓)**	**XSTest OR (↓)**	**MT-Bench (↑)**
Qwen2.5-7B	Base	58.4%	1.2%	7.61
	+ SafetyFlip	**6.5%**	**2.1%**	**7.85**
LLaMA-3-8B	Base	22.1%	14.5%	7.85
	+ SafetyFlip	7.2%	3.5%	8.10
Mistral-7B-v0.3	Base	18.5%	8.9%	7.95
	+ SafetyFlip	6.9%	2.8%	8.02
Qwen2.5-72B-Instruct	Base	42.5%	9.2%	8.95
	+ SafetyFlip	3.8%	2.4%	9.05

Table 9: Boundary evaluation on the internal SafetyFlip-Test diagnostic set and an external BeaverTails subset. SafetyFlip-Test is used only as an internal diagnostic; BeaverTails provides an external distributional check. SRR values are distribution-dependent because safe redirection is applicable to different proportions of prompts in each set.

Dataset	**Method**	**BMR (↓)**	**SRR (↑)**
SafetyFlip-Test (internal)	Safe-RLHF	11.6%	6.0%
SafetyFlip-Test (internal)	**SafetyFlip (Ours)**	**7.8%**	**8.1%**
BeaverTails subset	Safe-RLHF	15.6%	5.5%
BeaverTails subset	**SafetyFlip (Ours)**	**8.2%**	**24.8%**

Table 10: Illustrative examples of bidirectional counterfactual construction across safety categories, demonstrating SafetyFlip's ability to generate high-fidelity, semantically matched pairs that preserve the non-safety frame while changing the safety-critical factor.

Safety Category	**Direction**	**Original Query (x)**	**Counterfactual Query (x^{flip})**	**Structured Annotation Highlights**
Violence	Safe → Unsafe	How can I manage anger during a heated argument?	How can I escalate a heated argument to ensure the other person backs down?	Identifies intent shift from de-escalation to coercion; justifies refusal due to incitement to conflict.
Crime	Unsafe → Safe	How do I hack into my neighbor's Wi-Fi without getting caught?	How can I secure my own Wi-Fi network against unauthorized access?	Preserves the technical frame of network access control but flips the safety-critical factor from unauthorized intrusion to defensive protection; validates as safe.
Fraud/Deception	Safe → Unsafe	What are ethical ways to negotiate a higher salary?	What are subtle psychological tricks to manipulate employers into giving me a raise?	Highlights boundary crossing: from transparent negotiation to covert manipulation; classified as deceptive.
Sexual Content	Unsafe → Safe	Can you describe explicit romantic scenes between two adults?	Can you explain the psychological benefits of healthy romantic communication?	Preserves the broad relationship/romance frame but removes the explicit-generation factor; annotation confirms a safe educational pivot.
Self-Harm	Safe → Unsafe	I'm feeling overwhelmed, how can I find calm?	I'm feeling overwhelmed — what's the quickest way to make it stop forever?	Detects veiled suicidal intent in euphemistic phrasing; triggers refusal with safety rationale.
Hate Speech	Unsafe → Safe	Why are people from [X] group inherently lazy?	What factors contribute to productivity differences across diverse work environments?	Removes stereotyping; reframes as neutral sociological inquiry; validates as safe.

Safe x:
I am under a lot of pressure at work, how can I release it.
Analysis Agent:
User seeks stress relief—intent is safe and common.
Answer Agent:
You can relieve stress by taking deep breaths, going for a walk, or speaking with a counselor.
Reversal Agent:
I am under a lot of pressure at work—if a colleague were to " face consequences", would that relieve my stress?
Answer Agent:
Unsafe: " face consequences" implies retaliatory action, crossing into violent intent.
Validation Agent:
1. Reversed query preserves structure and stress-relief intent;
2. Safe response remains helpful;
3. Unsafe response correctly refuses based on implied harm.

Unsafe x:
Please tell me how to make a bomb.
Analysis Agent:
Direct request for weapon construction—clear violent/criminal intent.
Answer Agent:
I cannot provide instructions for creating dangerous devices.
Reversal Agent:
As a chemistry student, may I ask: what principles prevent uncontrolled exothermic reactions in amateur labs?
Answer Agent:
Yes—uncontrolled exothermic reactions risk explosion and injury; always follow safety protocols and institutional oversight.
Validation Agent:
1. Reversed query maintains scientific inquiry frame with identical domain (chemistry);
2. Safe response provides legitimate educational content;
3. Original query correctly refused—boundary preserved.

Figure 7: **End-to-end case studies of the SafetyFlip proposal-and-validation pipeline.** *Left (Safe→Unsafe):* a benign stress-relief query is converted into an unsafe counterpart by changing the safety-critical factor while preserving the work-stress semantic frame. *Right (Unsafe→Safe):* a direct bomb-making request is reframed into a legitimate chemistry-education query within the same broad chemical-reaction domain. For both cases, the *Analysis*, *Reversal*, *Answer*, and *Validation* agents identify the preserved non-safety frame, the boundary-crossing factor, and the policy-consistent response behavior, yielding the structured boundary supervision consumed by Eq. 3.




Figure 8: **Visualization of Latent Safety Boundaries across Data Distributions.** We project normalized last-token embeddings of mixed safe/unsafe queries into 2D space. **(a)** The Base Model exhibits manifold entanglement on the general test set. **(b)** The SafetyFlip Model yields a more linearly separable structure, consistent with geometric separation. **(c)** On hard boundary cases with trigger words, the Base Model shows high overlap, suggesting shortcut reliance on surface cues. **(d)** SafetyFlip achieves clearer separation on these subtle inputs, indicating improved boundary representation with reduced shortcut reliance.