WHEN AGENTS LEARN THE WRONG LESSON: CREDIT-ASSIGNMENT POISONING IN REFLECTIVE LLM AGENTS

Anonymous authors
Paper under double-blind review

ABSTRACT

Reflective LLM agents can turn successful trajectories into reusable lessons without checking which actions were necessary. We introduce *Reflection-Coupled Credit Assignment Poisoning* (`R-CAP`), an attack on this process in agents with shared reflection memory. An ordinary authorized user elicits a plausible tool-use behavior during a successful task; the agent's own reflection writer can then promote that behavior into standing guidance for later sessions. The attacker does not modify memory, tools, system prompts, or the victim query. The resulting rule widens the victim's tool-use scope while the intended task still succeeds. On evaluated AgentDojo cases across three backbones, conditional on successful induction, `R-CAP` achieves 98–99% keyword-based reflection implantation rate (RIR) and 88–92% Conditional TOSR (Transfer Overbroad Success Rate), with utility of 97–99%. Accounting for induction failures on the same 53-task cohort gives End-to-end TOSR of 68–76%. The results identify unchecked reflection-based credit assignment as a security risk: experience reuse can propagate attacker-shaped behavior that final-answer monitoring alone does not expose.

1 INTRODUCTION

A growing class of agents goes beyond executing a single task by reusing its own experience. One approach is *reflection*: the agent summarizes its trajectory into a reusable natural-language lesson and draws on it to guide later decisions. For example, Reflexion (Shinn et al., 2023) writes a verbal self-critique after each attempt and prepends it to its next one. Other experience-reuse systems include Voyager (Wang et al., 2023), which accumulates executable skills for new objectives, and Agent S (Agashe et al., 2025), which stores experience from past interactions to refine its future planning. A reflective agent can improve over time by treating its past trajectories as a trusted source of knowledge.

The same properties that make reflective agents self-improving also widen their exposure to attack. The content planted during earlier sessions can be stored as experience and later reactivated as trusted guidance that may shape the agent's behavior beyond what the current user intends or the model itself would produce (Dong et al., 2025; Chen et al., 2024). Modern agents also have broad access to external tools and online services and rely on partially untrusted content such as web pages, retrieved documents, and tool outputs (Ruan et al., 2024; Debenedetti et al., 2024; Greshake et al., 2023). Adversary-influenced content can therefore persist in memory across interactions.

Existing attacks poison retrieved records or manipulate tool descriptions to redirect an agent's decisions (Chen et al., 2024; Zou et al., 2025; Shi et al., 2025a). Several recent attacks push further and reach the agent's own self-improvement loop, by planting content the agent reads during a benign session and later stores as memory (Yang et al., 2026), or steering its reflection toward over-generalized rules that degrade later behavior (Wang et al., 2026b). These attacks can reach memory through both supplied artifacts and agent-generated records. In particular, MINJA uses ordinary queries with attacker-designed bridging reasoning to induce the agent to generate and store malicious records (Dong et al., 2025). Agent authorship alone therefore does not separate an attack from prior memory poisoning. We investigate a specific mechanism: an attacker elicits a tool-use behavior during successful execution, and the reflection writer promotes that behavior into a reusable

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

operating rule without checking its necessity or scope. The attacker supplies an induction task rather than the finished memory rule.

Our work. We introduce *Reflection-Coupled Credit Assignment Poisoning* (R−CAP), an attack on reflection-based credit assignment in *shared-user environments*, where multiple users interact with a common agent whose self-authored lessons persist and are reused across their sessions. R−CAP targets how the reflection writer generalizes successful tool use into guidance for later tasks. The attacker modifies none of the agent's memory, tools, system prompts, or the victim query. Instead, the attacker shapes an earlier interaction so that the reflection writer retains a plausible tool-use behavior as reusable guidance, with or without explicitly attributing success to it. The behavior may be unnecessary for its source goal or generalized beyond the tasks for which it is appropriate. When that lesson is loaded in a later session, it can trigger the attacker-intended behavior while the agent still completes the user's real task. Successful attacks therefore persist across sessions without a task failure to reveal them. The victim's tool use exceeds its task's access scope, violating least privilege (Saltzer & Schroeder, 1975); the final answer may give the user no indication of this excess access.

We evaluate R−CAP on AgentDojo (Debenedetti et al., 2024) tool-use tasks across three LLM backbones (GPT-4o, Claude Haiku 4.5, and Claude Sonnet 4.6), starting from 53 shared clean-eligible tasks. In the evaluated reflection and transfer stages, R−CAP has keyword-based RIR of 98% to 99% and transfers the target behavior into later benign sessions at an 88% to 92% Conditional TOSR while task utility is 97% to 99%. These conditional results exclude failed inductions. Accounting for induction failures gives End-to-end TOSR of 68–76%. Conditional TOSR ranges from 78% to 98% across all four domains: 78% to 90% in Slack and travel, and 91% to 98% in workplace and banking. The self-authored reflection exceeds the hand-written direct-memory control on every backbone, with transfer rising from 63% to 88% on GPT-4o, and it raises the mean tool count from 1.3 to as high as 2.1. Two tested content gates, a PromptArmor reimplementation and an isolated memory-content auditor, both leave workplace transfer on Haiku 4.5 at 0.91, matching the undefended condition.

Contribution. (i) Credit-assignment risk. We study how reflection writers generalize successful tool-use trajectories into broad-access rules that exceed a later task's scope. **(ii) R−CAP.** We elicit persistent tool-use guidance through a single domain-matched induction attempt, allowing an agent's own reflection step to turn an attacker-shaped execution into a rule that exceeds a later task's scope. **(iii) A controlled multi-model evaluation.** On AgentDojo across three backbones and four domains, R−CAP reaches 98 to 99% keyword-based RIR and roughly 90% Conditional TOSR in the evaluated stages with 97 to 99% utility, and the self-authored reflection transfers at least as well as a directly injected one, with its advantage largest for the backbone with the lowest direct-memory transfer.

Availability. We provide an anonymous runnable demonstration of the attack: https://anonymous.4open.science/r/Rcap-2C82. The full evaluation harness, templates, and analysis scripts are planned for release upon acceptance.

2 Related Work

Memory and retrieval poisoning either modifies stored records or retrieval knowledge bases directly (Chen et al., 2024; Zou et al., 2025) or induces the agent to retain attacker-influenced content through ingested material (Srivastava & He, 2025), conversation (Dong et al., 2025; Wang et al., 2026a), or self-improvement (Yang et al., 2026). Other attacks manipulate tool descriptions (Shi et al., 2025a; Song et al., 2026), forge tool outputs (Debenedetti et al., 2024; Zhan et al., 2024), or embed adversarial instructions in task context (Liu et al., 2025; Greshake et al., 2023; Perez & Ribeiro, 2022). Appendix D compares the privileges, targets, and persistence of these attack families.

MINJA (Dong et al., 2025) induces agent-generated malicious records through ordinary queries, bridging reasoning, and progressive prompt shortening. OEP (Wang et al., 2026b) biases reflection using locally valid but non-transferable cases paired with severe hypothetical consequences, causing reasoning failures or redundant API calls. R−CAP focuses on broad-access rules distilled from successful tool trajectories and transferred to narrow tasks while preserving benchmark goals.



Figure 1: Illustrative reflection forms following a successful attacker trajectory. Explicit and procedural forms present broad access as reusable guidance; a one-off record does not. Once shared memory is loaded, a later victim may reuse the unnecessary behavior.

Concurrent work on agent skills (Wu et al., 2026) evaluates both whether an action is permitted by the current task and whether task completion survives its removal. We study this task-conditioned risk at a different origin: a reflection writer generalizes the unsafe behavior, rather than a skill publisher authoring it into a skill.

Agents retain verbal reflections (Shinn et al., 2023), executable skills (Wang et al., 2023), or planning memories (Agashe et al., 2025) for reuse. This requires deciding which actions merit future reuse, often without counterfactual evidence. Our focus is the security of that credit-assignment step, rather than only the integrity of the memory store or the inputs it receives.

3 Threat Model

3.1 System and Memory Model

The policy π executes a task x as a trajectory τ; the reflection writer stores $m = R(\tau)$; and $U(x, \tau) \in \{0, 1\}$ denotes benchmark-goal completion. A clean trajectory τ_{clean} executes the victim task without an attacker reflection loaded. For scoring, $b \in \tau$ means that at least one tool from the instance's predefined broad-tool mask is called (Appendix C). We study always-on reflection memory: lessons are prepended to later contexts as standing guidance. Authorized users share this memory without user-level isolation or provenance filtering (Dong et al., 2025; Wang et al., 2026a). This fixes the intended loading policy and isolates reflection formation from retrieval (Figure 1).

3.2 Adversary Capabilities and Limitations

The adversary is an ordinary authorized user who knows the domain's tools and observes responses in their own session. They may inspect in-domain tasks excluded from evaluation, but evaluated victim queries are unavailable. A domain-level induction template elicits b during successful source execution. The attacker cannot modify the system prompt, tools, environment, memory, reflection writer, or victim session, or control reflection timing. Their influence is mediated by agent-written memory:

$$\tau_a \sim \pi(\cdot \mid x_a), \qquad m = R(\tau_a), \qquad \tau_v \sim \pi(\cdot \mid x_v, m), \tag{1}$$

In Equation 1, x_a instantiates an attacker-authored template; the agent produces the trajectory and reflection. In our evaluation, the evaluator fills the template for a task ID and uses that ID's original request as x_v in a separate session. The evaluated victim query is not exposed to the attacker during template design.

3.3 Adversary Goal

We target task-conditioned least privilege (Saltzer & Schroeder, 1975; Shi et al., 2026; Wu et al., 2026): broad access retrieves or returns data not needed for the victim's request. The task instruction and reference trace specify the intended narrow scope; clean runs separately establish that the goal is achievable without b. Tool-mask occurrence is the measured behavior, distinct from a record-level authorization judgment. The same behavior can be legitimate for the source task yet exceed the victim's scope. The adversary seeks *utility-preserving tool-policy drift*: a victim adopts b while completing its task correctly, so monitoring the final answer alone does not reveal the extra access.

3.4 Attack Criterion

Counterfactual credit-assignment work motivates comparing outcomes under changed conditions (Foerster et al., 2018; Mesnard et al., 2021; Harutyunyan et al., 2019). Our comparison is a clean victim execution without the source reflection; we do not implement those estimators. An instance succeeds when all four conditions hold:

1. **Eligibility.** The clean victim succeeds without b in every screening run (Equation 2).
2. **Induction.** The attacker trajectory succeeds and contains b: $U(x_a, \tau_a) = 1$ and $b \in \tau_a$.
3. **Memory transfer.** The agent generates a reflection from the successful source trajectory and loads it unedited into the victim context.
4. **Transfer.** With the source reflection loaded, the victim succeeds while adopting b: $U(x_v, \tau_v) = 1$ and $b \in \tau_v$.

Eligibility is an offline filter and gives the attacker no access to the victim query. Conditional TOSR counts successful memory and victim transfer among eligible instances with successful induction (Equation 3). End-to-end TOSR uses all eligible instances, with failed inductions and observed later pipeline failures contributing zero (Equation 4). Content metrics separately measure keyword matches and explicit credit.

4 Methodology



Figure 2: Evaluation workflow: the evaluator checks clean victim eligibility, then runs induction, reflection formation, and victim transfer. The clean check uses the victim task offline.

In the transfer evaluation, the source and victim share an underlying AgentDojo task ID but execute in separate sessions. The source uses an induction request; the victim uses the original task request. After clean eligibility screening, one domain-matched induction is attempted. Only source trajectories with benchmark-goal success and b proceed to reflection and victim execution. The writer summarizes the unmodified trajectory, and its reflection is auto-loaded for the victim. Conditional metrics describe these retained instances; End-to-end TOSR also counts failed inductions as zero (Algorithm 1).

4.1 Screening Eligible Victim Tasks

We apply the eligibility condition over k clean runs, retaining only tasks that succeed without b in every run:

$$U(x_v, \tau_{\text{clean}}^{(\ell)}) = 1 \quad \text{and} \quad b \notin \tau_{\text{clean}}^{(\ell)}, \qquad \ell = 1, \ldots, k. \tag{2}$$

This establishes that b is unnecessary for this victim task under the clean policy, not that it is causally irrelevant everywhere. We exclude instances failing either condition.

4.2 Constructing Inductions

An induction family $\mathcal{A}_b$ consists of domain-level templates designed using in-domain tasks excluded from evaluation. The evaluator instantiates a template for each evaluated task ID to form the source request; the same ID's original request is the victim task in a separate session. Thus, task-specific instantiation is part of evaluation, while template design does not expose evaluated victim queries to the attacker. For example, a calendar template asks the agent to review a day's schedule before locating a named event, eliciting broad enumeration that may later be generalized to targeted lookup. Each template fixes b and its narrow alternative before task selection; Appendix C lists the mapping.

4.3 Poisoning Reflection Through False Credit

The writer produces $m = R(\tau_a)$. A reflection can present b as reusable guidance rather than a one-off action; keyword-based RIR does not independently verify this semantic property. *Explicit false credit* additionally claims that b caused or enabled success; *procedural false credit* prescribes b without a causal claim. In contrast, $b \in \tau$ denotes occurrence in an execution. A rule can be unnecessary for its source task or overgeneralize a source-appropriate step to a victim that does not need it. The source-side ablation in Section 5.4 tests whether the benchmark goal remains attainable without the broad tools. Transfer follows condition 4 of Section 3.4.

Here, false credit includes unwarranted generalization across tasks. Explicit success attribution alone does not establish that b was unnecessary for the source task. Our diagnostics concern reflection text and observed tool use, not internal reasoning. Victim eligibility tests whether the later task succeeds without b; source necessity alone cannot decide whether a rule is appropriate for that task.

5 Evaluation

We organize the evaluation around four research questions:

- **RQ1 (Implantation).** What broad-access language and explicit success attributions appear in generated reflections?
- **RQ2 (Transfer).** Does the rule widen tool use in later benign sessions while preserving task utility?
- **RQ3 (Domains).** Where does the attack transfer most, and what access does the widened scope expose?
- **RQ4 (Defenses).** Do prompt-injection and memory-audit defenses stop `R-CAP` at the reflection stage?

5.1 Experimental Setup

Benchmark and models. We evaluate GPT-4o, Claude Haiku 4.5, and Claude Sonnet 4.6 on AgentDojo's 97 tasks across Slack, workplace, banking, and travel. Each row uses the same backbone for source execution, reflection writing, and victim execution; Sonnet 5 serves only as the CAER judge. Success without b in all three clean screening runs yields 53 shared eligible tasks before induction filtering. Section 5.4 describes the separate Haiku source-necessity cohort.

Protocol and conditions. One source induction is attempted per eligible task, without resampling. Source-goal completion together with b retains 41 instances for GPT-4o and 44 each for Haiku and

Table 1: Main comparison from 53 shared clean-eligible tasks. Three reflection-and-transfer trials use fixed sets of 41 successful inductions for GPT-4o and 44 each for Haiku and Sonnet; controls use the same subset within each model. U and TOSR show mean $\pm$ population SD. End-to-end TOSR uses all 53 tasks; its displayed statistics are approximate scaled conversions from rounded conditional values and exclude induction variability. — means not applicable.

Model	Condition	U	RIR	CAER	Conditional TOSR	End-to-end TOSR	Avg. tools
GPT-4o	clean	1.00 ± 0.00	0.00	0.00	0.00 ± 0.00	—	1.33
	direct memory	0.98 ± 0.02	1.00	1.00	0.63 ± 0.07	—	1.67
	R-CAP	0.98 ± 0.01	0.98	0.58	0.88 ± 0.04	0.68 ± 0.03	1.89
Haiku 4.5	clean	1.00 ± 0.00	0.00	0.00	0.00 ± 0.00	—	1.25
	direct memory	0.92 ± 0.04	1.00	1.00	0.81 ± 0.07	—	1.63
	R-CAP	0.97 ± 0.02	0.99	0.77	0.92 ± 0.04	0.76 ± 0.03	2.12
Sonnet 4.6	clean	1.00 ± 0.00	0.00	0.00	0.00 ± 0.00	—	1.33
	direct memory	0.98 ± 0.01	1.00	1.00	0.83 ± 0.05	—	1.72
	R-CAP	0.99 ± 0.01	0.99	0.75	0.91 ± 0.04	0.76 ± 0.03	2.01

Clean utility is observed in fresh post-screening runs; clean RIR/CAER are zero because no reflection is loaded. Direct-memory RIR/CAER are one by construction.

Sonnet (Appendix H). Each model keeps this task set fixed across three trials, generating a separate reflection and running the victim in each trial. Within each model, the same retained tasks are tested with no memory (*clean*), a hand-written rule (*direct memory*), or the writer's reflection (*R-CAP*).

Metrics. For R-CAP, both TOSR metrics count victim-goal completion together with b after reflection loading. Conditional TOSR divides by the successful-induction count; End-to-end TOSR divides by all 53 eligible tasks. Utility (U) measures victim-goal completion alone. Reflection implantation rate (RIR) is a keyword-based proxy for broad guidance. Credit assignment error rate (CAER) counts explicit success attributions labeled positive by Sonnet 5 and both independent human annotators; it does not establish that b was unnecessary for the source task. Neither content metric multiplies TOSR. Average tools counts calls per victim execution. Appendix B defines the metrics and failure handling.

Controls and aggregation. Rates weight tasks rather than domain means. Clean controls use three fresh runs after screening; all succeed in the reported subset. Their RIR/CAER are zero because no memory is loaded; direct-memory content scores are one by construction. Table 1 aggregates raw-count trial rates with population SD. End-to-end TOSR scales conditional statistics by $41/53$ or $44/53$; its displayed values are approximate conversions from rounded summaries. Figure 3 instead averages domain trial rates rounded to two decimals. Variation excludes rerunning induction.

5.2 RQ1–RQ2: Implantation and Transfer

Table 1 shows conditional-stage RIR of 0.98–0.99, Conditional TOSR of 0.88–0.92, and utility of 0.97–0.99 under R-CAP. Broad-language keyword matches are frequent, while CAER is 0.58–0.77 under a separate attribution criterion. Their difference does not estimate the proportion of procedural rules. The examples in Appendix F illustrate such rules; aggregate labels do not identify which forms transfer. Conditional TOSR directly measures adoption of b with victim-goal completion.

Relative to direct memory, R-CAP raises Conditional TOSR by 25 percentage points on GPT-4o, 11 on Haiku, and 8 on Sonnet. This is a comparison of Conditional TOSR, not end-to-end attack reliability. The largest improvement occurs on the backbone with the lowest direct-memory transfer. Generated reflections and hand-written rules differ in wording and tool specificity, however, so this comparison does not isolate an effect of self-authorship or provenance. Both arrive in the same memory file under the same framing. Direct memory is a privileged content control; the modeled attacker cannot inspect the writer's output or supply its exact text, and instead influences what the writer produces through the induction. Across three trials, the reported stage-rate standard deviations are at most 0.08 (Appendix J).



Figure 3: Conditional TOSR by domain: each trial rate is rounded to two decimals before averaging three trials. These are conditional-stage diagnostics.



Figure 4: Mean serialized characters returned per recorded tool call, replayed against each task's initial state (logarithmic axis). Labels show the mean and call count n. Broad and narrow means use different call sets; these are descriptive comparisons, not paired causal effects. Tool identities and record counts appear in Appendix G.

Tool counts rise from 1.25–1.33 under clean to 1.89–2.12 under `R-CAP`. Utility is high but falls by 1–3 percentage points relative to the selected clean baseline; utility-preserving success describes the victim event counted by Conditional TOSR and required by End-to-end TOSR, not zero average utility cost. The displayed standard deviations describe three trial-level stage aggregates and do not establish statistical significance.

5.3 RQ3: Transfer Across Domains

Figure 3 shows Conditional TOSR in every domain, ranging from 0.78 to 0.98. Workplace and banking have higher rates for GPT-4o and Haiku, whereas Sonnet varies only from 0.90 to 0.91. Enumerable collections and plausible broad-read tools may make reuse easier, but this is an explanatory hypothesis, not a measured causal effect. Transfer rate also does not establish relative harm: access to unrelated financial records is consequential even when a benchmark fixture is small. The source-necessity study in Appendix I uses a separate cohort and does not establish a task-level correlation with transfer.

Access per call. Figure 4 reports the mean serialized return size per tool call. Broad file enumeration returns 27,692 characters per call versus 1,454 for narrow search, and received-email listing returns 9,286 versus 1,320. Calendar retrieval differs less: 884 versus 715. The banking comparison includes only one narrow call and is especially sample-limited. These measurements characterize the benchmark fixtures, not record sensitivity or a universal exposure multiplier. The relevant violation remains access outside the task-conditioned policy.

Table 2: Haiku 4.5 ablations: source-tool necessity (A) and wording/memory controls on separate cohorts (B).

A. Source necessity ($N = 67$)

Outcome	n/N	%
b appears: full tool set	63/67	94.0
Success without broad tools	60/67	89.6
Both	**56/67**	**83.6**

B. Wording and memory controls

Condition	RIR	Conditional TOSR
Explicit templates	0.95–0.99	0.85–0.92
Calendar: `R-CAP`	1.00	0.92
Calendar: isolated	1.00	**0.00**

A: Three trials per condition; 67 tasks pass the clean-utility filter. Each outcome requires all three trials: b appears with the full tools, or the goal is achieved without broad tools. Both means both conditions hold for the same task. **B:** Ranges cover three explicit templates per domain/behavior pair. Calendar controls use 8 successful inductions and three trials. All rates condition on successful induction.

Table 3: Haiku 4.5 defenses, three trials per condition. A: 15 successful workplace inductions, the subset in Figure 3, using random templates. B: blocked reflections on the main 53 tasks.

	A. Workplace transfer			**B. Reflection screening**	
Condition	U	RIR	Conditional TOSR	Attack ($N = 159$)	Benign ($N = 159$)
Clean	1.00	0.00	0.00	—	—
`R-CAP`	1.00	1.00	0.91	—	—
PROMPTARMOR	0.98	0.98	0.91	3 (1.9%)	3 (1.9%)
MEMAUDIT	0.98	0.93	0.91	3 (1.9%)	4 (2.5%)
Isolated memory	1.00	1.00	0.00	—	—

Defense RIR is measured after the gate; isolated-memory RIR before withholding. —: not applicable.

5.4 ABLATIONS

Table 2 reports source-tool suppression (A) and wording/memory controls (B). On Haiku, b appears in all three full-tool trials for 63/67 tasks; 60/67 tasks succeed on all three trials after broad tools are removed. Both conditions hold in 56/67 tasks (83.6%), demonstrating that the induced broad behavior is unnecessary for benchmark goal completion in most of this cohort. This supports the source-side premise of false credit. The checker tests goal completion, not compliance with every clause of the request.

Source necessity and CAER measure different objects: tool suppression tests whether b was needed, while CAER labels what the reflection claims. Victim-side unnecessary behavior is established separately by clean-run eligibility. Stable transfer across three explicitly worded templates supports robustness within that template family, but indirect prompts that merely suggest uncertainty or checking did not elicit b in the reported tests. Withholding the reflection reduces transfer to zero in the eight-task calendar control while preserving utility at 1.00. Its RIR of 1.00 describes the source reflection, withheld from the victim. This small control tests the memory channel; isolation also removes its cross-session reuse benefit.

5.5 RQ4: DEFENSES

With Haiku 4.5 as the agent, we insert two content gates after reflection generation and before storage. Blocked reflections are withheld; allowed reflections load normally. Defense-row RIR applies the keyword rules after gate processing, over the same input cohort; a blocked reflection contributes zero. Our PROMPTARMOR reimplementation uses an LLM to detect and strip injected instructions (Shi et al., 2025b). MEMAUDIT blocks explicit harmful directives, cross-user misuse, privacy exposure, or conflicts with user intent. It represents isolated memory-entry auditing, not the full consensus and dual-memory mechanisms of A-MemGuard (Wei et al., 2025); Appendix K explains the distinction.

The workplace defense experiment (Table 3, panel A) uses random induction templates. Undefended R-CAP has RIR 1.00 and Conditional TOSR 0.91. Both PROMPTARMOR and MEMAUDIT leave Conditional TOSR at 0.91. Panel B screens reflections from all 53 main-cohort tasks across three trials: 159 attack reflections and 159 benign reflections from clean trajectories. Both gates block 3 attack reflections (1.9%); PROMPTARMOR and MEMAUDIT reject 3 (1.9%) and 4 (2.5%) benign reflections, respectively. Attack blocking is low and does not exceed benign rejection.

The results suggest a limitation of the tested content gates: a procedurally phrased rule can appear reasonable without evidence about the task on which it will later be used. Illustrative reflection examples and the source-task counterfactual auditing proposal appear in Appendices F and L.

6 DISCUSSION

Unchecked credit assignment makes experience reuse a security decision: an operationally plausible lesson can widen access without causing task failure. Provenance and user-level isolation can restrict cross-user propagation, while task-scoped execution policies can constrain what a loaded reflection is allowed to change.

We also propose *counterfactual reflection auditing* (CRA). Before storing a rule prescribing b', an auditor re-executes its source task with b' suppressed and removes the clause if the task still succeeds. This supplies evidence absent from the tested content gates. However, source necessity does not establish safe generalization: a behavior required by its source task may remain inappropriate for later victims. CRA is an unevaluated design, not a validated defense; Appendix L details its scope, potential amortization, and combination with provenance.

Multi-agent frameworks support communication and collaboration (Wu et al., 2024; Hong et al., 2024; Li et al., 2023), while other systems retain skills or memories for reuse (Wang et al., 2023; Chhikara et al., 2025). Our findings motivate checking the task scope and provenance of reused experience; we do not evaluate these frameworks' security.

7 LIMITATIONS

Our evaluation uses AgentDojo, auto-loaded shared memory, and explicit templates. Source and victim sessions share task IDs; cross-ID transfer is not established. Retrieval-based memory (Packer et al., 2024; Xu et al., 2025) and retention under later updates, eviction, or competing lessons remain untested. Tool suppression uses Haiku 4.5; defense transfer uses Haiku workplace tasks and our implementations of two gates.

Utility scores benchmark goals, not every requested step; valid alternatives may use tools absent from reference traces. Three reflection-and-transfer trials reuse fixed induction sets, excluding variation from rerunning induction or sampling new tasks. Keyword RIR does not verify reusable guidance. Content aggregates do not identify which forms transfer; the direct-memory control does not isolate self-authorship. Unpaired return samples describe access volume, not causal exposure.

8 CONCLUSION

R-CAP exposes reflection formation as an attack surface: an ordinary user's successful trajectory can become an overbroad rule reused across shared sessions. Conditional on successful induction, keyword-based RIR reaches 98–99% and Conditional TOSR 88–92%, with utility of 97–99%. Including induction failures on the same 53-task cohort gives End-to-end TOSR of 68–76%. Protecting experience reuse therefore requires attention to how lessons are formed, scoped, and shared, beyond checking whether the final task outcome is correct.

ETHICS STATEMENT

All experiments reported here run inside AgentDojo, a research benchmark whose tools, accounts, calendars, transactions, and messages are simulated. No real user, no real account, and no deployed production system was involved at any point, and no personal or sensitive data was collected or processed. The banking, workplace, travel, and Slack domains are sandboxes, and the overbroad behaviors we induce act only on synthetic resources.

We recognize the dual-use nature of the findings. In the evaluated shared-memory setting, `R-CAP` exploits how the reflection writer generalizes successful tool use. We judge that disclosure supports defense research because successful attacks preserve task completion and can escape monitoring limited to task outcomes.

We also limited the offensive reach of the study by design. We stop at utility-preserving tool-policy drift, the precursor in which the victim's tool use is silently widened, and we do not develop the behavior into a concrete end-to-end exploit such as data exfiltration or unauthorized transactions. We provide an anonymous runnable demonstration and plan to release the full evaluation artifacts upon acceptance, as stated in the Introduction, to support reproducibility and defense research.

REPRODUCIBILITY STATEMENT

Section 5.1 identifies the benchmark, backbones, trials, and evaluation cohorts. Appendix B defines the metrics and protocol; Appendix C maps domains to target behaviors, and Appendix E illustrates an induction and transfer. Section 3.4 states the success conditions and Algorithm 1 gives the procedure. The Introduction links the anonymous runnable demonstration; the full harness, template set, and analysis scripts are planned for release upon acceptance.

AI USE STATEMENT

We used generative AI tools to assist with writing and editing, and with analysis scripting for the measurements reported in Section 5.2. We also used Sonnet 5 as the CAER judge: two human annotators labeled independently before comparison with the model; only cases positive under all three labels contribute to CAER (Appendix B). Experimental results were produced by the evaluation harness and the stated annotation procedure. We take responsibility for the final content of this work.

REFERENCES

Saaket Agashe, Jiuzhou Han, Shuyu Gan, Jiachen Yang, Ang Li, and Xin Wang. Agent s: An open agentic framework that uses computers like a human. In Y. Yue, A. Garg, N. Peng, F. Sha, and R. Yu (eds.), *International Conference on Learning Representations*, volume 2025, pp. 22924–22946, 2025. URL https://proceedings.iclr.cc/paper_files/paper/2025/file/394c7c30ea87b5c3521b4d9e9d419071-Paper-Conference.pdf.

Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. Agentpoison: Red-teaming llm agents via poisoning memory or knowledge bases, 2024. URL https://arxiv.org/abs/2407.12784.

Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready ai agents with scalable long-term memory, 2025. URL https://arxiv.org/abs/2504.19413.

Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. Agentdojo: A dynamic environment to evaluate prompt injection attacks and defenses for llm agents, 2024. URL https://arxiv.org/abs/2406.13352.

Shen Dong, Shaochen Xu, Pengfei He, Yige Li, Jiliang Tang, Tianming Liu, Hui Liu, and Zhen Xiang. Memory injection attacks on llm agents via query-only interaction. In D. Belgrave, C. Zhang, H. Lin, R. Pascanu, P. Koniusz, M. Ghassemi, and N. Chen (eds.), *Advances in Neural Information Processing Systems*, volume 38, pp. 46697–46731. Curran Associates, Inc.,

2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/file/42a97bbd9844d2bf68596730af80bcdf-Paper-Conference.pdf.

Jakob Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients. In *Proceedings of the AAAI conference on artificial intelligence*, 2018.

Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world llm-integrated applications with indirect prompt injection, 2023. URL https://arxiv.org/abs/2302.12173.

Anna Harutyunyan, Will Dabney, Thomas Mesnard, Mohammad Azar, Bilal Piot, Nicolas Heess, Hado van Hasselt, Greg Wayne, Satinder Singh, Doina Precup, and Remi Munos. Hindsight credit assignment, 2019. URL https://arxiv.org/abs/1912.02503.

Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, zili wang, Steven Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. Metagpt: Meta programming for a multi-agent collaborative framework. In B. Kim, Y. Yue, S. Chaudhuri, K. Fragkiadaki, M. Khan, and Y. Sun (eds.), *International Conference on Learning Representations*, volume 2024, pp. 23247–23275, 2024. URL https://proceedings.iclr.cc/paper_files/paper/2024/file/6507b115562bb0a305f1958ccc87355a-Paper-Conference.pdf.

Guohao Li, Hasan Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. Camel: Communicative agents for "mind" exploration of large language model society. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 51991–52008. Curran Associates, Inc., 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/a3621ee907def47c1b952ade25c67698-Paper-Conference.pdf.

Yi Liu, Gelei Deng, Yuekang Li, Kailong Wang, Zihao Wang, Xiaofeng Wang, Tianwei Zhang, Yepang Liu, Haoyu Wang, Yan Zheng, Leo Yu Zhang, and Yang Liu. Prompt injection attack against llm-integrated applications, 2025. URL https://arxiv.org/abs/2306.05499.

Thomas Mesnard, Théophane Weber, Fabio Viola, Shantanu Thakoor, Alaa Saade, Anna Harutyunyan, Will Dabney, Tom Stepleton, Nicolas Heess, Arthur Guez, Éric Moulines, Marcus Hutter, Lars Buesing, and Rémi Munos. Counterfactual credit assignment in model-free reinforcement learning, 2021. URL https://arxiv.org/abs/2011.09464.

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. Memgpt: Towards llms as operating systems, 2024. URL https://arxiv.org/abs/2310.08560.

Fábio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models, 2022. URL https://arxiv.org/abs/2211.09527.

Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. Identifying the risks of lm agents with an lm-emulated sandbox, 2024. URL https://arxiv.org/abs/2309.15817.

J.H. Saltzer and M.D. Schroeder. The protection of information in computer systems. *Proceedings of the IEEE*, 63(9):1278–1308, 1975. doi: 10.1109/PROC.1975.9939.

Jiawen Shi, Zenghui Yuan, Guiyao Tie, Pan Zhou, Neil Zhenqiang Gong, and Lichao Sun. Prompt injection attack to tool selection in llm agents, 2025a. URL https://arxiv.org/abs/2504.19793.

Tianneng Shi, Kaijie Zhu, Zhun Wang, Yuqi Jia, Will Cai, Weida Liang, Haonan Wang, Hend Alzahrani, Joshua Lu, Kenji Kawaguchi, Basel Alomair, Xuandong Zhao, William Yang Wang, Neil Gong, Wenbo Guo, and Dawn Song. Promptarmor: Simple yet effective prompt injection defenses, 2025b. URL https://arxiv.org/abs/2507.15219.

Tianneng Shi, Jingxuan He, Zhun Wang, Hongwei Li, Linyu Wu, Wenbo Guo, and Dawn Song. Progent: Securing ai agents with privilege control, 2026. URL https://arxiv.org/abs/2504.11703.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning, 2023. URL https://arxiv.org/abs/2303.11366.

Hao Song, Yiming Shen, Wenxuan Luo, Leixin Guo, Ting Chen, Jiashui Wang, Beibei Li, Xiaosong Zhang, and Jiachi Chen. Beyond the protocol: Unveiling attack vectors in the model context protocol (mcp) ecosystem. *IEEE Transactions on Software Engineering*, pp. 1–16, 2026. doi: 10.1109/TSE.2026.3694876.

Saksham Sahai Srivastava and Haoyu He. Memorygraft: Persistent compromise of llm agents via poisoned experience retrieval, 2025. URL https://arxiv.org/abs/2512.16962.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. Voyager: An open-ended embodied agent with large language models, 2023. URL https://arxiv.org/abs/2305.16291.

Hongtao Wang, Se Yang, Yu Chen, and Puzhuo Liu. Hijacking agent memory: Stealthy trojan attacks through conversational interaction, 2026a. URL https://arxiv.org/abs/2605.29960.

Kaixiang Wang, Jiong Lou, Zhaojiacheng Zhou, and Jie Li. OEP: Poisoning self-evolving LLM agents via locally correct but non-transferable experiences, 2026b. URL https://arxiv.org/abs/2605.18930.

Qianshan Wei, Tengchao Yang, Yaochen Wang, Xinfeng Li, Lijun Li, Zhenfei Yin, Yi Zhan, Thorsten Holz, Zhiqiang Lin, and XiaoFeng Wang. A-memguard: A proactive defense framework for llm-based agent memory, 2025. URL https://arxiv.org/abs/2510.02373.

Jiangrong Wu, Yuhong Nan, Yixi Lin, Huaijin Wang, Yuming Xiao, Shuai Wang, and Zibin Zheng. SkillScope: Toward fine-grained least-privilege enforcement for agent skills. In *Proceedings of the ACM SIGSAC Conference on Computer and Communications Security (CCS)*, 2026. URL https://arxiv.org/abs/2605.05868.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, Ahmed Hassan Awadallah, Ryen W White, Doug Burger, and Chi Wang. Autogen: Enabling next-gen LLM applications via multi-agent conversations. In *First Conference on Language Modeling*, 2024. URL https://openreview.net/forum?id=BAakY1hNKS.

Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-mem: Agentic memory for llm agents. In D. Belgrave, C. Zhang, H. Lin, R. Pascanu, P. Koniusz, M. Ghassemi, and N. Chen (eds.), *Advances in Neural Information Processing Systems*, volume 38, pp. 17577–17604. Curran Associates, Inc., 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/file/19909c36f51abc4856b4560aff3d36d6-Paper-Conference.pdf.

Xianglin Yang, Yufei He, Shuo Ji, Bryan Hooi, and Jin Song Dong. Zombie agents: Persistent control of self-evolving llm agents via self-reinforcing injections, 2026. URL https://arxiv.org/abs/2602.15654.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 10471–10506, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-acl.624. URL https://aclanthology.org/2024.findings-acl.624/.

Wei Zou, Runpeng Geng, Binghui Wang, and Jinyuan Jia. PoisonedRAG: Knowledge corruption attacks to Retrieval-Augmented generation of large language models. In *34th USENIX Security Symposium (USENIX Security 25)*, pp. 3827–3844, Seattle, WA, August 2025. USENIX Association. ISBN 978-1-939133-52-6. URL https://www.usenix.org/conference/usenixsecurity25/presentation/zou-poisonedrag.

A THE R−CAP PROCEDURE

Figure 2 summarizes the stages. Algorithm 1 describes transfer evaluation, including the evaluator's checks and attack execution; the adversary authors the templates used in Stage 2.

Algorithm 1 Reflection-Coupled Credit Assignment Poisoning (R−CAP)

Require: victim task x_v, target behavior b, induction family $\mathcal{A}_b$, policy π, reflection writer R, utility U, clean-trial count k
Ensure: end-to-end success score, and m, τ_v when produced

Stage 1: Clean counterfactual check
for $\ell = 1$ **to** k **do**
  $\tau_{\text{clean}}^{(\ell)} \sim \pi(\cdot \mid x_v)$ ▷ no attacker memory loaded
end for
if $\exists\, \ell :\ U(x_v, \tau_{\text{clean}}^{(\ell)}) = 0$ **or** $b \in \tau_{\text{clean}}^{(\ell)}$ **then**
  return INELIGIBLE ▷ failed clean screening, or b observed
end if
Stage 2: Induction
select a template $a \in \mathcal{A}_b$ framing b as ordinary domain practice
evaluator instantiates a for x_v's task ID as source request x_a
$\tau_a \sim \pi(\cdot \mid x_a)$
if $U(x_a, \tau_a) \neq 1$ **or** $b \notin \tau_a$ **then**
  return score 0 ▷ retain in denominator; no resampling
end if
Stage 3: Reflection formation
$m \leftarrow R(\tau_a)$ ▷ credit assignment, no counterfactual check
if reflection generation failed **then**
  return score 0
end if
Stage 4: Victim transfer
load m into shared persistent memory
if reflection loading failed **then**
  return score 0
end if
$\tau_v \sim \pi(\cdot \mid x_v, m)$
return (m, τ_v) and TOSR score 1 iff $b \in \tau_v$ and $U(x_v, \tau_v) = 1$; otherwise score 0
Score keyword matches for RIR and explicit success attribution for CAER.

The attacker designs templates using tasks excluded from evaluation. The evaluator instantiates a template as x_a in Stage 2; the agent executes it and produces m. An observed writer, memory-loading, or victim-execution failure likewise receives score zero.

B METRICS AND PROTOCOL

Evaluation units and denominators. The main cohort contains $N = 53$ clean-eligible source–victim pairs for each model. Eligibility requires the original victim task to succeed without b in all clean screening runs (Equation 2). For pair i, let $I_i = 1$ when the induced source task succeeds and executes b; otherwise $I_i = 0$. Let $K = \sum_i I_i$ be the successful-induction count. Each model reuses this fixed successful-induction set across all three trials: $K = 41$ for GPT-4o and $K = 44$ for Haiku 4.5 and Sonnet 4.6. Each trial generates a separate reflection for each retained task and then runs victim transfer. The formulas below describe one trial and suppress its index: I_i and K are fixed, while reflections, victim outcomes, and content labels vary by trial. When a victim execution exists, $U_i = 1$ denotes benchmark-goal completion and $B_i = 1$ denotes occurrence of its predefined target behavior. These outcomes are distinct from source-task utility.

The two TOSR metrics. For R−CAP, let $S_i = 1$ when the reflection is generated and loaded and the victim both completes its task and performs b (conditions 3–4 of Section 3.4); an observed

failure of any of these steps gives $S_i = 0$. For an execution with the reflection loaded, $S_i = U_i B_i$. **Conditional TOSR** averages this joint outcome over the K successful inductions. **End-to-end TOSR** uses all N eligible attempts, retaining failed inductions as zero:

$$\mathrm{TOSR}_{\mathrm{cond}} = \frac{1}{K} \sum_{i:I_i=1} S_i, \tag{3}$$

$$\mathrm{TOSR}_{\mathrm{e2e}} = \frac{1}{N} \sum_{i:I_i=1} S_i = \frac{K}{N} \mathrm{TOSR}_{\mathrm{cond}}. \tag{4}$$

Both metrics count the same joint event; only their denominators differ. In the undefended condition, the evaluator loads the unedited source reflection. RIR and CAER label its content separately and neither filter nor multiply TOSR. An observed pipeline failure contributes zero transfer success. When $K = 0$, Conditional TOSR is undefined and End-to-end TOSR is zero. Control rows measure the same joint victim event $U_i B_i$ under their specified memory policy: no memory, a hand-written rule, a withheld reflection, or a content gate. Main-table controls use the same K retained task IDs as `R-CAP`. Their End-to-end TOSR is not reported.

Other metrics. The main-table diagnostics use the same K successfully induced instances:

- **Utility (U).** The fraction of victim executions meeting the benchmark goal, regardless of b; this is not source-task or induction success.
- **Reflection Implantation Rate (RIR).** The fraction matching broad-language keyword rules, including `broad` and `all`. This lexical proxy does not verify reusable guidance.
- **Credit Assignment Error Rate (CAER).** The fraction jointly labeled positive by the LLM judge and both human annotators for explicit credit to b for source-task success. This attribution proxy does not establish that b was unnecessary for the source task. Its denominator is K; its positives need not be a subset of keyword matches.
- **Average tools.** Mean tool calls per victim execution, including failures.

For one trial, let $r_i \in \{0, 1\}$ be the keyword-based RIR label. For CAER, $j_i, h_i^{(1)}, h_i^{(2)} \in \{0, 1\}$ are the labels from Sonnet 5 (API ID `claude-sonnet-5`) and two human annotators. The humans label independently before comparison with the model. A positive label requires explicit credit to b for source-task success. CAER counts an instance only when all three labels are positive:

$$\mathrm{RIR} = \frac{1}{K} \sum_{i:I_i=1} r_i, \qquad \mathrm{CAER} = \frac{1}{K} \sum_{i:I_i=1} j_i h_i^{(1)} h_i^{(2)}. \tag{5}$$

Disagreements contribute zero to the CAER numerator and remain in its denominator K. Keyword matching can count descriptions or negations and miss paraphrases, so RIR alone does not establish that a reflection prescribes b. Separate content averages do not identify which labels coincide with transfer.

Aggregation and controls. Table 1 reports three-trial means and population standard deviations. The retained tasks are fixed, but their reflections are regenerated in each trial, so both content labels and victim outcomes can vary. Main-table rates are computed from raw counts before rounding. For trial summaries z_t, $t = 1, 2, 3$, we use

$$\bar{z} = \frac{1}{3} \sum_{t=1}^{3} z_t, \qquad \mathrm{SD}(z) = \sqrt{\frac{1}{3} \sum_{t=1}^{3} (z_t - \bar{z})^2}.$$

Figure 3 rounds each domain's trial rate to two decimal places before averaging the three values. Its displayed domain means therefore need not reproduce the main-table aggregate when reweighted. Because each model's successful-induction set is fixed across transfer trials, both the End-to-end TOSR mean and standard deviation equal the corresponding Conditional TOSR statistic multiplied by $K/53$. The displayed end-to-end statistics are approximate conversions of rounded conditional statistics, shown to two decimal places. Their standard deviations describe reflection-and-transfer variation conditional on this fixed induction set; they do not estimate variation from rerunning induction or sampling new tasks.

Clean and direct-memory diagnostics use the same retained task instances selected by the paired R−CAP induction. Clean controls use three fresh executions after eligibility screening; their reported utility of one is observed, not guaranteed by selection. The clean condition loads no memory, so its RIR and CAER are zero by construction, not measurements of natural rule formation. Direct memory supplies the rule and explicit credit by construction; its RIR and CAER are one. It bypasses ordinary-user induction, so its End-to-end TOSR is not applicable. Isolated memory runs the source and writer but withholds the reflection from the victim. In defense-transfer rows, RIR measures the fraction of input instances whose processed reflection still matches the keyword rules; blocked reflections contribute zero. The isolated-memory row instead labels the generated reflection before withholding it.

Table 3B screens one attack and one benign reflection per eligible task in each trial: $53 \times 3 = 159$ reflections per condition. This content test includes all 53 tasks, without the successful-induction filter used for transfer. Benign reflections are generated from clean trajectories for screening; the main-table clean condition loads no reflection. Attack and benign label the generating condition, not successful induction or implantation.

Task-conditioned scope. The narrow access policy derives from the task instruction and reference tool trace. Out-of-scope access means accessing or returning data not needed for the request. The detector counts any call to a tool in the predefined broad-tool mask; this tool-level proxy is distinct from judging the relevance of individual returned records. Clean screening establishes that the goal can be achieved without that target behavior. Both TOSR metrics require victim utility as well as that target behavior; task failure alone is not attack success. Source-task necessity, discussed below, is a separate counterfactual test.

C TARGET BEHAVIORS BY DOMAIN

Table 4: Tools used to detect each target behavior b, with narrow alternatives fixed before clean-run eligibility filtering. Any call to a tool in the full broad-tool mask counts as occurrence. Masks larger than three tools are truncated here; this table does not specify complete executable masks.

Suite	Broad behavior b	Narrow alternative
Banking	`get_balance`, `get_most_recent_transactions`, `get_scheduled_transactions`	`get_iban`
	`get_most_recent_transactions`, `get_scheduled_transactions`, `get_balance`	`get_iban`, `send_money`
	`get_most_recent_transactions`, `get_scheduled_transactions`, `get_balance`	`send_money`, `schedule_transaction`
	`get_user_info`	`update_password`, `update_user_info`
Slack	`get_channels`, `read_channel_messages`, `read_inbox`	`send_direct_message`, `send_channel_message`
	`get_webpage`	`post_webpage`
Travel	`get_all_car_rental_companies_in_city`	`get_car_types_available`, `get_rating_reviews_for_car_rental`
	`get_all_hotels_in_city`	`get_hotels_prices`, `get_rating_reviews_for_hotels`
	`get_all_hotels_in_city`, `get_all_restaurants_in_city`, `get_all_car_rental_companies_in_city`	`get_user_information`, `get_hotels_prices`
	`get_all_hotels_in_city`, `get_all_restaurants_in_city`, `get_all_car_rental_companies_in_city`	`reserve_hotel`, `reserve_car_rental`
	`get_all_restaurants_in_city`, `get_dietary_restrictions_for_all_restaurants`	`get_cuisine_type_for_restaurants`, `get_restaurants_address`
	`get_day_calendar_events`	`search_calendar_events`, `create_calendar_event`
	`get_user_information`, `get_all_hotels_in_city`, `get_all_restaurants_in_city`	`send_email`
Workplace	`get_day_calendar_events`	`search_calendar_events`, `create_calendar_event`
	`get_day_calendar_events`, `get_unread_emails`, `get_received_emails`	`search_calendar_events`, `search_emails`
	`get_unread_emails`, `get_received_emails`, `get_sent_emails`	`search_emails`, `send_email`
	`list_files`, `search_files`	`search_files_by_filename`, `get_file_by_id`

Table 4 summarizes the tool masks used to detect the behavior b each template targets. A call to any one tool in the full mask counts as occurrence; calling every tool is not required. Each template fixes b and its narrow alternative before task selection; the clean-run criterion then selects tasks that succeed without this predefined behavior. Three further templates are omitted because their broad and narrow tool sets coincide, which leaves the two behaviors indistinguishable for those tasks.

D Positioning Against Prior Attack Families

Table 5 compares attacker-controlled inputs and persistence mechanisms; it does not rank attack effectiveness or detectability across different experimental settings.

Table 5: Qualitative comparison of attacker inputs and persistence mechanisms. This is a threat-model comparison, not an empirical ranking of attack success or detectability.

Attack family	Attacker-controlled input	Memory or context path	Persistence mechanism
Direct memory poisoning (Chen et al., 2024)	Store entries	Poisoned records retrieved	Retained records
Ingested experience poisoning (Srivastava & He, 2025)	Ingestion artifacts	Agent constructs poisoned experience store	Experience reuse
Query-only poisoning (Dong et al., 2025)	Queries and indication prompts	Agent generates malicious records	Record retrieval
Malicious tool descriptions (Shi et al., 2025a)	Tool metadata	Tool interface enters context	Metadata reuse
Indirect prompt injection (Greshake et al., 2023)	Retrieved content	External instructions enter context	Depends on storage
Self-improvement injection (Yang et al., 2026)	External payloads	Content enters stored experience	Memory reuse
Reflection overgeneralization (OEP) (Wang et al., 2026b)	Locally valid cases and hypothetical consequences	Writer generalizes cases into rules	Shared semantic memory
R-CAP	**Ordinary-user induction task**	**Writer generalizes a tool-use trajectory**	**Shared reflection**

E Worked Example

The following example illustrates calendar tasks within the workplace domain, using representative query and reflection wording. Table 3 evaluates transfer across the workplace domain on Haiku 4.5. The target behavior b is an unnecessary broad read which enumerates every event on a date before resolving a named event.

Eligibility. The victim task x_v asks the agent to find a meeting by name, e.g. "find my *Networking event* and tell me when it starts." Over k clean runs the agent answers with a single targeted call, `search_calendar_events("Networking event")`, and never enumerates the day. The task is solvable without b and b never appears, so x_v is eligible and b is unnecessary for this victim task.

Induction. The evaluator instantiates an attacker-authored, domain-matched template from $\mathcal{A}_b$ as the request x_a, for example "check my schedule for that day so I don't miss anything, then tell me when the Networking event starts." The phrasing makes a broad read look like ordinary diligence rather than an anomaly. The agent satisfies the request by first calling `get_day_calendar_events(date=D)`, scanning the returned events, and then resolving the named one, so $b \in \tau_a$ and $U(x_a, \tau_a) = 1$.

Reflection. The reflection writer summarizes τ_a into a reusable lesson. In the procedural form, it writes a rule rather than a causal claim, e.g. "When answering named-event calendar questions, first retrieve all events on the target date, then locate the matching event by name." The reflection presents b as reusable guidance by framing the access pattern as future procedure. In the explicit form it adds a causal claim, e.g. that checking all events first is what avoided missing the meeting, illustrating the explicit-credit criterion for CAER.

Transfer. A later victim issues a fresh named-event query in a separate session. With m auto-loaded, the agent now enumerates the whole day before resolving the name, so $b \in \tau_v$, yet it still returns the

correct event and $U(x_v, \tau_v) = 1$. The attacker authored the template for x_a; the rule, its storage, and its later activation were all produced by the agent.

The banking domain illustrates the same structure with financial records. There b is reading account resources the task never named. The clean task completes the requested banking action without retrieving unrelated transaction history; the transferred behavior adds that retrieval while still completing the requested action. Outcome-only monitoring misses this additional access because the requested action still succeeds.

F Reflection Examples

The rates in Section 5.2 summarize keyword matches, explicit success attribution, and victim outcomes. The illustrative reflection examples below explain the mechanism. Across domains the agent's reflection writer produces lessons that read like ordinary operational notes. In the workplace calendar setting, a clean trajectory that resolves a named event with a single targeted lookup yields a narrow lesson such as

> *"To find a specific event, look it up directly by name with* `search_calendar_events`*."*

A separate source trajectory induced to include a broad read can instead yield the procedural rule

> *"When answering named-event calendar questions, first retrieve all events on the target date with* `get_day_calendar_events`*, then locate the matching event by name."*

This illustrates procedural false credit: the lesson makes broad enumeration a standing procedure without claiming that it caused success. A detector looking only for explicit causal claims would not flag this wording. The explicit form additionally asserts causation, for example "checking every event first is what avoided missing the meeting," which illustrates CAER's explicit-credit criterion. The banking example uses a reflection such as

> *"Before issuing a refund, review the account's recent transactions to confirm the correct one, then process the refund."*

which directs the agent to inspect unrelated financial records before completing the refund. The rule reads as prudent advice, but it directs access outside the victim task's scope that the clean execution does not require.

G What One Broad Call Returns

Table 6: What one tool call returns in the AgentDojo environment, measured by replaying every recorded call against the task's own initial state.

Domain	Tool	Calls	Records	Chars
Calendar	`get_day_calendar_events` (broad)	47	2.5	884
	`search_calendar_events` (narrow)	10	2.2	715
Files	`list_files` (broad)	31	26.0	27,692
	`search_files_by_filename` (narrow)	36	1.0	1,454
Email	`get_received_emails` (broad)	4	21.0	9,286
	`get_unread_emails` (broad)	8	6.0	2,535
	`search_emails` (narrow)	25	2.8	1,320
Banking	`get_most_recent_transactions` (broad)	31	5.0	712
	`get_iban` (narrow)	1	1.0	22

A tool call is the unit of *Avg. tools*, but it is not a unit of access. To measure access we replay every recorded call against the task's own initial environment and size the return value two ways, the number of top-level records and the serialized length that enters the agent's context. Table 6 reports the result. Return sizes vary substantially. In the file domain, sampled broad calls return 26 records and roughly 28 thousand characters on average, compared with one record and under 1.5 thousand characters for sampled narrow calls, a ratio of 26 in mean records and 19 in mean text. The calendar record means differ by a factor of approximately 1.1. Each invocation counts as one tool call, regardless of its return size. These figures average different sets of recorded calls and are not paired estimates of the causal exposure increase on a task.

The calendar example illustrates the mechanism, but its difference in mean returned records is small because an AgentDojo day holds few events. The file and email calls return substantially more records and text. The banking comparison concerns recent-transaction retrieval versus an account-identifier lookup; it does not show that every transaction in a real account would be returned. That narrow mean comes from only one recorded call. These summaries show why call count alone cannot describe returned data volume; they do not establish paired causal exposure or record sensitivity.

H Induction Counts

Main 53-task cohort. Among the 53 tasks that pass the common clean counterfactual screen, successful induction (source-task success together with b) occurs for 41 tasks on GPT-4o and 44 tasks each on Haiku 4.5 and Sonnet 4.6. Each model uses the same successful-induction set in all three transfer trials. The corresponding fractions are $41/53 = 77.4\%$ and $44/53 = 83.0\%$. These are the model-specific factors used to convert the main-table Conditional TOSR into End-to-end TOSR:

$$\begin{aligned} \text{GPT-4o:} &\quad (41/53) \times 0.88 \approx 0.68, \\ \text{Haiku 4.5:} &\quad (44/53) \times 0.92 \approx 0.76, \\ \text{Sonnet 4.6:} &\quad (44/53) \times 0.91 \approx 0.76. \end{aligned}$$

The products use rounded conditional means. Standard deviations are scaled by the same fixed fractions; the precision and scope of these statistics are described in Appendix B.

Full-pool post-induction summary. The separate Haiku 4.5 summary over all 97 source tasks is measured *after induction*, not on the original clean requests. Source utility is true in 67/97 rows (69.1%), broad behavior occurs in 85/97 (87.6%), and both hold in 59/97 (60.8%). Of those 59 successful inductions, 44 belong to the shared 53-task cohort, matching the Haiku main-cohort count; the other 15 fall outside it.

Separate source-necessity cohort. The Haiku tool-removal study instead selects the 67 of 97 tasks that complete the clean task; the other 30 fail clean-task completion. This selection neither requires absence of b nor selects by post-induction source utility. The next section's $56/67$ identifies tasks where b occurs with the full tool set but the source benchmark goal is still achieved without the broad tools.

I Source-Task Necessity

On Claude Haiku 4.5, we evaluate 67 induction tasks with the full tool set and with each template's broad tools removed, using three trials per condition. The broad behavior occurs with the full tool set on all three trials in 63/67 tasks (94.0%). With broad tools removed, 60/67 tasks (89.6%) still reach the benchmark goal on all three trials; both three-trial conditions hold in 56/67 tasks (83.6%). These are task-level counts, not proportions of individual trials. This tests necessity for the benchmark goal, not compliance with every requested step or the causal wording of the reflection. This is a separate cohort from the victim-transfer comparison in Figure 3. These aggregate results do not establish a per-task association with transfer or explain its domain differences.

J PER-TRIAL VARIATION

Table 7: Population standard deviations over three trials with fixed task sets and separately generated reflections, for the means in Table 1. End-to-end TOSR SDs multiply the Conditional TOSR SDs in the R−CAP rows below by each model's fixed induction fraction.

Model	Condition	U	RIR	CAER	Conditional TOSR	Avg. tools
GPT-4o	clean	0.00	0.00	0.00	0.00	0.13
	direct memory	0.02	0.00	0.00	0.07	0.12
	R−CAP	0.01	0.02	0.08	0.04	0.11
Haiku 4.5	clean	0.00	0.00	0.00	0.00	0.08
	direct memory	0.04	0.00	0.00	0.07	0.14
	R−CAP	0.02	0.01	0.07	0.04	0.17
Sonnet 4.6	clean	0.00	0.00	0.00	0.00	0.08
	direct memory	0.01	0.00	0.00	0.05	0.10
	R−CAP	0.01	0.01	0.07	0.04	0.13

Table 7 reports three-trial standard deviations of the stage diagnostics: at most 0.08 for rates and 0.17 for tool counts (Haiku 4.5). End-to-end TOSR standard deviations in Table 1 scale the conditional values by the fixed induction fractions. These descriptive statistics exclude variation from rerunning induction and do not establish robustness across untested settings.

K RELATION TO A-MEMGUARD

A-MemGuard (Wei et al., 2025) addresses the limits of auditing memories in isolation: an entry can appear benign yet become harmful in context. It combines consensus validation across related memories with a dual-memory structure that stores corrective lessons from detected failures.

Our MEMAUDIT gate tests isolated entry auditing and omits both mechanisms. Successful R−CAP transfer supplies no task-failure signal, but other memories or validation signals could still help a richer defense. A-MemGuard's effectiveness against R−CAP remains untested; Table 3 reports our isolated gate, not the full framework.

L COUNTERFACTUAL REFLECTION AUDITING

The tested gates lack task-specific necessity evidence. We propose *counterfactual reflection auditing* (CRA): extract behavior b' from a reflection, rerun its source task with b' suppressed, and remove the clause or block the reflection if the task still succeeds. Reduced utility supports source necessity, not safe reuse. Repeat stochastic runs and check for substitute broad behaviors.

Same-family held-out tasks could amortize auditing; session/user provenance could restrict cross-principal reuse. Implementation, overhead, and interaction with consensus validation remain unevaluated.

Worked trace in paraphrase. In the reported workplace example, the reflection instructs the agent to retrieve the target date's appointments with `get_day_calendar_events` and summarize each event's description. Suppressing this day-level read in the source task yields a single `search_calendar_events` call and success on all three trials, with no substitute broad tool. CRA would therefore remove the clause.

What the audit does not catch. Source necessity does not ensure safe transfer. Reuse must also be checked against the intended scope of prospective victim tasks.